

CHAPTER 2

CREATING ROS NODES

KANSHA AIDIL FITRI BRAMANTYA
1103210226

```
mkdir -p ~/catkin_ws/src  
cd ~/catkin_ws  
catkin_make
```

```
echo "source ~/catkin_ws/devel/setup.bash" >> ~/.bashrc  
source ~/.bashrc
```

```
cd ~/catkin_ws/src  
catkin_create_pkg my_package rospy std_msgs
```

```
cd ~/catkin_ws/src/my_package  
mkdir scripts  
cd scripts  
touch my_node.py  
chmod +x my_node.py
```

```
#!/usr/bin/env python3  
  
import rospy # Library ROS  
from std_msgs.msg import String # Tipe pesan yang akan digunakan  
  
def talker():  
    pub = rospy.Publisher('chatter', String, queue_size=10) # Publisher ke topik "chatter"  
    rospy.init_node('talker', anonymous=True) # Inisialisasi node bernama "talker"  
    rate = rospy.Rate(1) # Frekuensi pengiriman pesan (1 Hz)  
  
    while not rospy.is_shutdown():  
        hello_str = f"Hello ROS at {rospy.get_time()}"  
        rospy.loginfo(hello_str) # Log ke terminal  
        pub.publish(hello_str) # Publikasikan pesan  
        rate.sleep() # Tunggu hingga frekuensi berikutnya  
  
if __name__ == '__main__':  
    try:  
        talker()  
    except rospy.ROSInterruptException:  
        pass
```

```
cd ~/catkin_ws  
catkin_make
```

```
roscore
```

```
source ~/catkin_ws/devel/setup.bash  
roslaunch my_package my_node.py
```

```
Hello ROS at 1672486384.54
```

THANK YOU