### AO DEFLECTOR DATA SHEET

λ/4

#### Model AODF: 4120-3

Part Number: 97-02799-02 Rev: B

Work Order: 833102

Serial Number: 162045

Cell I.D#: 1017B1A

Test Date

Test

Insertion

10/25/2018

Tested By: KQ

Measured Performance at

488 nm

Wavelength

0.57

TAT TOWEL.	0.330	/V Burn-in into.	
est	Min Spec.	Meas.	Max Spec.
ion Loss (%)		2.91	3.00
DE Ave. (%)		83.1	0.00
Min D.E(%)	75.00	77.00	
Flatness(%)		13.00	

Peak Valley(wave) R.M.S(Wave)

BD 0deg Astimagtism(Mag.) DEVICE CHARACTERISTICS:

BD 45 dea CRYSTAL MOUNTING:

Input Polarization: Output Polarization: Center Frequency:


Bandwidth:

Horizontal Vertical

Output Face: Parallelism:

120 MHz 50 MHz

#### Package Drawing



# OH1 \$11 533.1 mU FS 1:101.610 -18.6840 65.215 pF 130.500 000 MHs CENTER 120.000 000 MH SPAN 50,000 000 MH

**Test Data Curves** 

-1 order @ center

DE vs Frequency

Frequency (MHz)

---- Response

115 120 8

핌

Location

100%

80%

70%

60% 50%

40%

30%

20%

10%


0%


85 90

### Gooch & Housego

1040 East Meadow Circle Palo Alto, California 94303 Tel: (650) 856-7911 Fax: (650) 858-0944

THIS DOCUMENT IS THE PROPERTY OF GOOCH & HOUSEGO AND IS DELIVERED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE DISCLOSED, REPRODUCED IN WHOLE OR IN PART, OR USED FOR MANUFACTURE FOR ANYONE OTHER THAN GOOCH & HOUSEGO WITHOUT ITS WRITTEN CONSENT, AND THAT NO RIGHT IS GRANTED TO DISCLOSE OR SO USE ANY INFORMATION CONTAINED IN SAID DOCUMENT. THIS RESTRICTION DOES NOT LIMIT THE RIGHT TO USE INFORMATION OBTAINED FROM ANOTHER SOURCE.





# **SPECIFICATIONS**

**OUTLINE DRAWING** 

AO Medium

Output Polarization Input Polarization Wavelength Acoustic Velocity Acoustic Mode

RF Bandwidth Center Frequency (Fc) Insertion Loss

RF Power

Active Aperture

RMS at 633 mm Min Diffraction Efficiency Peak Valley at 633 mm Flatness Across Bandwidth Average Diffraction Efficiency

Scan Angle Time Bandwidth

**VSWR** 


Shear, off axis .65 mm/µs Horizontal 413 nm

120 MHz Vertica

3mm Diameter <0.3 W 50 MHz

N/A N/A

75% λ/4 N/A 2.2:1 N/A



# **Document**

09/13/13

Control

THIS DOCUMENT IS THE PROPERTY OF GOOCH & HOUSEGO. IT IS NOT TO BE REPRODUCED OR DISCLOSED IN WHOLE OR IN PART OTHER THAN BY EMPLOYEES OF GOOCH & HOUSEGO AND ITS CONTRACTED REPRESENTATIVES AND DISTRIBUTERS. ANY EXCEPTION REQUIRES THE WRITTEN CONSENT OF AN AUTHORIZED REPRESENTATIVE OF GOOCH & HOUSEGO.

	FINISH:	MATERIAL:	.XX ± .01
АРР	APP	웆	R
			T. Ng 9/3/2013
PART NUMBER: 97-02799-02	3MM A	AODF 4120-3	<b>♠</b> G00
B	3MM APERTURE	0-3	Gooch & Housego
SHEET 1 OF	ñ		sego
1 OF 1			

## Notes:

- 1. First order @ 120mHZ collinear to input +/- 45'
  2. Impedance matching frequency range 80-145MHz