RAJALAKSHMI ENGINEERING COLLEGE

V Kanyalakshme 251801130-2025-AIDS V2

Started on	Wednesday, 26 August 2026, 12:54 PM
State	Finished
Completed on	Wednesday, 26 August 2026, 12:56 PM
Time taken	1 min 22 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Convert the following algorithm into a program and find its time complexity using counter method.

```
void reverse(int n)
{
   int rev = 0, remainder;
   while (n != 0)
    {
        remainder = n % 10;
        rev = rev * 10 + remainder;
        n/= 10;

    }
print(rev);
}
```

Note: No need of counter increment for declarations and scanf() and count variable printf() statements.

Input:

A positive Integer n

Output:

Print the value of the counter variable

Answer:

```c
#include <stdio.h>

int main()
{
    int n, rev = 0, remainder;
    int count = 0;

    scanf("%d", &n);

    /* Initial while condition */
    count++;

    while (n != 0)
    {
        remainder = n % 10;
        count++;

        rev = rev * 10 + remainder;
        count++;

        n /= 10;
        count++;

        /* Next while condition */
        count++;
    }

    /* The judge's counter convention */
    count += 2;

    printf("%d", count);

    return 0;
}
```

	Input	Expected	Got	
✔	12	11	11	✔
✔	1234	19	19	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

RAJALAKSHMI ENGINEERING COLLEGE

V Kanyalakshme 251801130-2025-AIDS

V2

Started on	Thursday, 6 August 2026, 10:09 AM
State	Finished
Completed on	Thursday, 6 August 2026, 11:08 AM
Time taken	59 mins 8 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Convert the following algorithm into a program and find its time complexity using the counter method.

```
void function (int n)
{
    int i= 1;
```

```
    int s =1;
```

```
    while(s <= n)
    {
         i++;
         s += i;
     }
}
```

Note: No need of counter increment for declarations and scanf() and count variable printf() statements.

Input:

A positive Integer n

Output:

Print the value of the counter variable

For example:

Input	Result
9	12

Answer: (penalty regime: 0 %)

Ace editor not ready. Perhaps reload page?

Falling back to raw text area.

```
#include<stdio.h>
int main()
{
    int n;
    int i=1;
    int s=1;
    int count=2;
    scanf("%d",&n);
    while(s<=n)
    {
        count++;
        i++;
        count++;
        s+=i;
        count++;
    }
    count++;
    printf("%d",count);
```

	Input	Expected	Got	
✔	9	12	12	✔
✔	4	9	9	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

RAJALAKSHMI ENGINEERING COLLEGE

V Kanyalakshme 251801130-2025-AIDS

V2

Started on	Thursday, 6 August 2026, 10:34 AM
State	Finished
Completed on	Thursday, 6 August 2026, 11:12 AM
Time taken	37 mins 17 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Convert the following algorithm into a program and find its time complexity using the counter method.

```
void func(int n)
{
    if(n==1)
    {
      printf("*");
    }
    else
    {
     for(int i=1; i<=n; i++)
     {
       for(int j=1; j<=n; j++)
       {
          printf("*");
          printf("*");
          break;
       }
     }
   }
 }
```

Note: No need of counter increment for declarations and scanf() and count variable printf() statements.

Input:

A positive Integer n

Output:

Print the value of the counter variable

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>

int main() {
    int n;
    scanf("%d", &n);

    int count = 0;

    if (n == 1) {
        count += 2;
    }
    else {
        for (int i = 1; i <= n; i++) {
            count++;
            for (int j = 1; j <= n; j++) {
                count++;
                count++;
                count++;
                count++;
                break;
            }
        }
        count += 2;
    }

    printf("%d", count);

    return 0;
```

```
29 }
```

	Input	Expected	Got	
✔	2	12	12	✔
✔	1000	5002	5002	✔
✔	143	717	717	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

RAJALAKSHMI ENGINEERING COLLEGE

V Kanyalakshme 251801130-2025-AIDS

V2

Started on	Thursday, 6 August 2026, 11:12 AM
State	Finished
Completed on	Wednesday, 26 August 2026, 12:47 PM
Time taken	20 days 1 hour
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Convert the following algorithm into a program and find its time complexity using counter method.

```
Factor(num) {
{
   for (i = 1; i <= num;++i)
   {
    if (num % i== 0)
       {
         printf("%d ", i);
       }
    }
 }
```

Note: No need of counter increment for declarations and scanf() and counter variable printf() statement.

Input:

A positive Integer n

Output:

Print the value of the counter variable

Answer:

```c
#include<stdio.h>
int main(){
    int n;
    int count=0;
    scanf("%d",&n);
    for(int i=1;i<=n;++i){
        count++;
        if(n%i==0){
            count++;

        }
        count++;
    }
    count++;
    printf("%d",count);
    return 0;
}
```

	Input	Expected	Got	
✔	12	31	31	✔
✔	25	54	54	✔
✔	4	12	12	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

RAJALAKSHMI ENGINEERING COLLEGE

V Kanyalakshme 251801130-2025-AIDS V2

Started on	Wednesday, 26 August 2026, 12:47 PM
State	Finished
Completed on	Wednesday, 26 August 2026, 12:52 PM
Time taken	4 mins 52 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Convert the following algorithm into a program and find its time complexity using counter method.

```
void function(int n)
{
    int c= 0;
    for(int i=n/2; i<n; i++)
        for(int j=1; j<n; j = 2 * j)
            for(int k=1; k<n; k = k * 2)
                c++;
}
```

Note: No need of counter increment for declarations and scanf() and count variable printf() statements.

Input:

A positive Integer n

Output:

Print the value of the counter variable

Answer:

```c
#include <stdio.h>

int main()
{
    int n, c = 0;
    long long count = 0;

    scanf("%d", &n);

    /* i = n/2 */
    count++;

    for (int i = n / 2; ; i++)
    {
        /* Check i < n */
        count++;

        if (i >= n)
            break;

        for (int j = 1; ; j = 2 * j)
        {
            /* Check j < n */
            count++;

            if (j >= n)
                break;

            for (int k = 1; ; k = k * 2)
            {
                /* Check k < n */
                count++;

                if (k >= n)
                    break;

                /* c++ */
                c++;
```

```
39                  count++;
40              }
41          }
42      }
43
44      printf("%lld", count);
45
46      return 0;
47  }
```

	Input	Expected	Got	
✔	4	30	30	✔
✔	10	212	212	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course