

1. Добавить 2 окружения "preprod" и "production"

kapelan74 > ci-cd > Environments

Available 2 Stopped 0

Clean up environments Enable review app New environment

Q Search by environment name

> [preprod](#) Auto stop in 23 hours ▶ ▾ Stop ⋮

> [production](#) ▶ ▾ Stop ⋮

2. Добавить отдельные deploy job для каждой среды

Pipeline Needs Jobs 6 Tests 0

| build | test | deploy | stop |
|-----------------|----------------|--------------------------------|------------------------|
| ✓ build image ↺ | ✓ test image ↺ | ✓ deploy image to preprod ↺ | ⚙ stop to preprod ■ |
| | | ✓ deploy image to production ↺ | ⚙ stop to production ■ |

3. Добавить переменную "\$MyLogin" внутри .gitlab-ci.yml, которая будет меняться в зависимости от среды.

```
34 deploy image to preprod:
35   stage: deploy
36   variables:
37     TARGET_ENV: preprod
38     MyLogin: prpAdmin
39   script:
40     - echo "Deploy image $IMAGE_TAG to ${TARGET_ENV} with ${MyLogin}:${MyPassword}"
41   only:
42     - main
43   environment:
44     name: preprod
45     on_stop: stop to preprod
46     auto_stop_in: 1 day
47
48 deploy image to production:
49   stage: deploy
50   variables:
51     TARGET_ENV: production
52     MyLogin: prodAdmin
53   script:
54     - echo "Deploy image $IMAGE_TAG to ${TARGET_ENV} with ${MyLogin}:${MyPassword}"
55   only:
56     - main
57   environment:
58     name: production
59     on_stop: stop to production
```

4. Добавить переменную "\$MyPassword" не используя .gitlab-ci.yml, которая так же будет меняться в зависимости от среды.

| | | | | | |
|----------|--------------|---------|----------|--------------|---|
| Variable | MyPassword 🔒 | ***** 🔒 | Expanded | production 🔒 | ✎ |
| Variable | MyPassword 🔒 | ***** 🔒 | Expanded | preprod 🔒 | ✎ |