

# Algorithms for Dynamic Right-Sizing in Data Centers

---

Kevin Kappelmann

July 24, 2017

Technical University of Munich


# Motivation and Problem Statement

---

Fast-growing demand for data collection,  
processing, and storage


# Data Centers' Costs

Fast-growing demand for data collection,  
processing, and storage



# Data Centers' Costs

Fast-growing demand for data collection, processing, and storage



# Our Model

- $m \in \mathbb{N} \dots$  Number of homogeneous servers

# Our Model

- $m \in \mathbb{N} \dots$  Number of homogeneous servers
- $T \in \mathbb{N} \dots$  Number of time slots

# Our Model

- $m \in \mathbb{N} \dots$  Number of homogeneous servers
- $T \in \mathbb{N} \dots$  Number of time slots
- $\beta \in \mathbb{R}_{\geq 0} \dots$  Switching costs of a server



# Our Model

- $m \in \mathbb{N} \dots$  Number of homogeneous servers
- $T \in \mathbb{N} \dots$  Number of time slots
- $\beta \in \mathbb{R}_{\geq 0} \dots$  Switching costs of a server
- $f : [0, 1] \rightarrow \mathbb{R} \dots$  Convex operating cost function of a server

# Our Model

- $m \in \mathbb{N} \dots$  Number of homogeneous servers
- $T \in \mathbb{N} \dots$  Number of time slots
- $\beta \in \mathbb{R}_{\geq 0} \dots$  Switching costs of a server
- $f : [0, 1] \rightarrow \mathbb{R} \dots$  Convex operating cost function of a server
- $\lambda_1, \dots, \lambda_T \in [0, m] \dots$  Arrival rates

# Our Model

- $m \in \mathbb{N} \dots$  Number of homogeneous servers
- $T \in \mathbb{N} \dots$  Number of time slots
- $\beta \in \mathbb{R}_{\geq 0} \dots$  Switching costs of a server
- $f : [0, 1] \rightarrow \mathbb{R} \dots$  Convex operating cost function of a server
- $\lambda_1, \dots, \lambda_T \in [0, m] \dots$  Arrival rates
- $x_1, \dots, x_T \in \{0, \dots, m\} \dots$  Numbers of active servers

## Problem Statement

Operating costs for one time step

$$c_{op}(x_t, \lambda_t) := \begin{cases} \infty, & \text{if } \lambda_t > x_t & // \text{too few servers} \\ x_t f(\lambda_t/x_t), & \text{if } x_t \neq 0 \wedge \lambda_t \leq x_t & // \text{even distribution} \\ 0, & \text{if } x_t = \lambda_t = 0 & // \text{no active servers} \end{cases}$$

# Problem Statement

Operating costs for one time step

$$c_{op}(x_t, \lambda_t) := \begin{cases} \infty, & \text{if } \lambda_t > x_t & // \text{too few servers} \\ x_t f(\lambda_t/x_t), & \text{if } x_t \neq 0 \wedge \lambda_t \leq x_t & // \text{even distribution} \\ 0, & \text{if } x_t = \lambda_t = 0 & // \text{no active servers} \end{cases}$$

**Goal: Minimize total costs**

$$\text{minimize} \quad \sum_{t=1}^T \underbrace{\left( c_{op}(x_t, \lambda_t) + \beta \max\{0, x_t - x_{t-1}\} \right)}_{c(x_{t-1}, x_t, \lambda_t)}$$

# Optimal Offline Algorithm


---

# Pseudo-Linear-Time Algorithm

Fundamental idea: reduce problem to shortest path problem

# Pseudo-Linear-Time Algorithm


Fundamental idea: reduce problem to shortest path problem





# Pseudo-Linear-Time Algorithm


Fundamental idea: reduce problem to shortest path problem



Time complexity:  $\Theta(Tm)$

# Pseudo-Linear-Time Algorithm

Fundamental idea: reduce problem to shortest path problem



Time complexity:  $\Theta(Tm)$

... only  $\log_2(m)$  bits required to encode  $m$ .

# Offline Approximation Algorithm


---

## 2-Optimal Linear-Time Algorithm

Use logarithmic steps to reduce number of nodes

## 2-Optimal Linear-Time Algorithm


Use logarithmic steps to reduce number of nodes



where  $b := \lfloor \log_2(m) \rfloor$

## 2-Optimal Linear-Time Algorithm

Use logarithmic steps to reduce number of nodes



where  $b := \lfloor \log_2(m) \rfloor$


Claim: Shortest Path in graph corresponds to 2-optimal schedule.

## Proof Idea

Take a schedule and transform periods between two powers of 2

# Proof Idea

Take a schedule and transform periods between two powers of 2





## Approximative Scheduling

Shortest Path in graph corresponds to 2-optimal schedule.

## Approximative Scheduling

Shortest Path in graph corresponds to 2-optimal schedule.

Time complexity:  $\Theta(T \log_2(m))$

# Approximative Scheduling

Shortest Path in graph corresponds to 2-optimal schedule.

Time complexity:  $\Theta(T \log_2(m))$

Approach can be generalized to allow for arbitrary precisions  
with time complexity  $\Theta(T \log_{1+\epsilon}(m))$

## Summary and Prospects

---

## Summary

We reduced the scheduling problem to the shortest path problem of acyclic graphs.

## Summary

We reduced the scheduling problem to the shortest path problem of acyclic graphs.

Optimal Offline Algorithm with runtime  $\Theta(Tm)$

## Summary

We reduced the scheduling problem to the shortest path problem of acyclic graphs.

Optimal Offline Algorithm with runtime  $\Theta(Tm)$

$(1 + \epsilon)$ -Optimal Offline Algorithm with runtime  
 $\Theta(T \log_{1+\epsilon}(m)) = \Theta\left(T \frac{\log(m)}{\log(1+\epsilon)}\right)$

# Prospects

Can our approach be modified to ...



Can our approach be modified to ...

- deal with more than one homogeneous server collection?

Can our approach be modified to ...

- deal with more than one homogeneous server collection?
- deal with multiple sleep states?

Can our approach be modified to ...

- deal with more than one homogeneous server collection?
- deal with multiple sleep states?
- work as an online algorithm?

Can our approach be modified to ...

- deal with more than one homogeneous server collection?
- deal with multiple sleep states?
- work as an online algorithm?

Open question: Is there a polynomial optimal algorithm or is it an **NP** problem?

**Thanks for your attention!**

**Any questions?**

## Image Sources I

- Data center: [datacentervoice.com/wp-content/uploads/2015/12/data-center.jpg](http://datacentervoice.com/wp-content/uploads/2015/12/data-center.jpg)
- Data center costs: [perspectives.mvdirona.com/2008/11/cost-of-power-in-large-scale-data-centers/](http://perspectives.mvdirona.com/2008/11/cost-of-power-in-large-scale-data-centers/)