

```
R version 4.3.1 (2023-06-16 ucrt) -- "Beagle Scouts"
Copyright (C) 2023 The R Foundation for Statistical Computing
Platform: x86_64-w64-mingw32/x64 (64-bit)
```

```
R is free software and comes with ABSOLUTELY NO WARRANTY.
You are welcome to redistribute it under certain conditions.
Type 'license()' or 'licence()' for distribution details.
```

```
Natural language support but running in an English locale
```

```
R is a collaborative project with many contributors.
Type 'contributors()' for more information and
'citation()' on how to cite R or R packages in publications.
```

```
Type 'demo()' for some demos, 'help()' for on-line help, or
'help.start()' for an HTML browser interface to help.
Type 'q()' to quit R.
```

```
[Previously saved workspace restored]
```

```
> rm(list = ls())
> if(!"EnvStats" %in% installed.packages()){install.packages("EnvStats")}
> library(EnvStats)
```

```
Attaching package: 'EnvStats'
```

```
The following objects are masked from 'package:stats':
```

```
predict, predict.lm
```

```
> x0 <- c(383,383,310,304,297,248,243,234,635,635,635,635,635,598,598,343,345,343,345,343,343,327
,327,295,49.8,295,291,245,41.8,675,675,675,623,623,345,345,345,327,327,306,299,297,268,264,249,25
3,249,249,243,240,234,200,203,177,128,99.5,41,36.4,675,675,675,675,675,675,675,675,675,675,67
5,675,674,672,624,624,624,624,624,624,623,623,623,622,511,456,446,405,356,345,345,345,345,345,344
,344,344,344,344,344,313,331,332,331,319,319,327,317,321,309,306,294,299,298,252,265,264,251,
251,252,252,252,251,251,229,220,227,225,222,212,222,221,203,195,189,176,178,163,153,138,120,120,1
16,113,110,102,100,100,99,95.8,88.7,89.1,88.3,87,86.2,79.9,86.6,80.3,675,675,675,675,675,675,655,456,
346,346,340,330,330,330,330,330,330,325,287,266,267,253,251,251,233,220,203,185,97.5,89.1,41.4,65
4,654,604,604,349,343,343,331,327,327,327,272,289,289,261,261,254,177,80.7,215,191,158,138,102,63
.6,63.6,59,49.8,675,675,623,623,345,346,345,306,298,281,265,266,253,201,202,179,128,99.1,97.9,48.
9,43.1,41,36.4,669,348,330,327,299,266,249,665,665,665,665,665,665,665,614,503,452,345,344,333,33
2,325,306,296,266,252,249,220,179,85.3,46,41.4,675,675,675,623,623,616,345,344,345,332,332,331,33
2,325,306,263,248,252,249,220,200,203,177,99,41,36.4,675,675,675)
> x1 <- c(623,623,345,344,345,332,332,331,332,325,306,297,264,264,249,252,249,249,221,200,203,177
,99,41,674,674,674,674,674,622,512,456,346,345,332,332,327,307,297,266,253,249,249,220,177,88.7,4
1.4,36.4,662,610,610,610,610,609,608,344,343,343,333,333,327,327,305,291,291,261,261,259,258,258,
251,200,115,59,663,663,615,615,615,499,451,345,343,343,331,332,319,322,322,305,294,294,268,251,247,24
6,220,178,85.3,41.4)
> x <- c(x0,x1)
> skewness(x, na.rm = FALSE, method = "fisher", l.moment.method = "unbiased",
+ plot.pos.cons = c(a = 0.35, b = 0))
[1] 0.5355413
>
>
>
> kurtosis(x, na.rm = FALSE, method = "fisher", l.moment.method = "unbiased",
+ plot.pos.cons = c(a = 0.35, b = 0), excess = TRUE)
[1] -0.6908983
>
> shapiro.test(x)
```

```
Shapiro-Wilk normality test
```

```
data: x
W = 0.89411, p-value = 5.352e-16
```

```
> hist(x,main="Main",xlab="value",border="light blue",col="blue",las=1)
> qqPlot(x)
>
```

```
>
```