

NSSM Useful Commands Guide

This document contains commonly used NSSM (Non-Sucking Service Manager) commands to manage executable (.exe) files as Windows services.

1. Install a Service

- Open Command Prompt as Administrator
- Command: `nssm install SecureGate`
- A GUI will open where you select the EXE path and startup directory

2. Start the Service

- Command: `nssm start SecureGate`
- Starts the SecureGate service

3. Stop the Service

- Command: `nssm stop SecureGate`
- Stops the running SecureGate service

4. Restart the Service

- Command: `nssm restart SecureGate`
- Stops and starts the service again

5. Check Service Status

- Command: `nssm status SecureGate`
- Shows current status (running / stopped)

6. Edit Existing Service

- Command: `nssm edit SecureGate`
- Used to modify path, arguments, log files, or permissions

7. Remove Service

- Command: nssm remove SecureGate
- Prompts to confirm service deletion

8. Set Service to Run as Administrator

- Open: nssm edit SecureGate
- Go to Logon tab
- Select: Local System account
- Save and restart the service

9. Enable Auto Start on Boot

- Default behavior is Automatic
- Can be verified using Windows Services Manager

10. Log Output & Errors

- Configure Stdout and Stderr paths in NSSM I/O tab
- Example: securegate_stdout.log, securegate_stderr.log

Note: Always run NSSM commands from an Administrator Command Prompt. This is mandatory for services that use network sniffing, firewall rules, or low-level system access.