mukesh cy-5

by default cypress runs in electron browser in headless mode when running via cli.

open cmd -

npx cypress run

all test in e2e runs.

run spec files-



```
●●●●

©CypressEveningBatch - - zsh - 118×32

mukeshotwani@Mukeshs-MacBook-Air-2 CypressEveningBatch % npx cypress run -- spec "cypress/e2e/firstcypress.cy.js"
```

this is how to run.

run in headed-

mukeshotwani@Mukeshs-MacBook-Air-2 CypressEveningBatch % npx cypress run --spec "cypress/e2e/firstcypress.cy.js" --headed

keep cypress open after run-

```
mukeshotwani@Mukeshs-MacBook-Air-2 CypressEveningBatch % npx cypress run —spec "cypress/e2e/firstcypress.cy.js" --headed --no-exit
```

specify browser to run-

```
mukeshotwani@Mukeshs-MacBook-Air-2 CypressEveningBatch % npx cypress run --spec "cypress/e2e/firstcypress.cy.js" --headed --no-exit --browser chrome
```

```
npx cypress run --spec "path"

npx cypress run --spec "path,path,path"

npx cypress run --spec "/cypress/e2e/login/**/*"

npx cypress run --spec "/cypress/e2e/regression/**/*"

npx cypress run --spec "/cypress/e2e/sanity/**/*"
```

hover doesnt work in cypress.

install this - npm install cypress-real-events

add this in support - e2ejs

import "cypress-real-events/support";

even file upload needs separate package.

files need to be mandatorily present in fixture folder.

```
1 import "cypress-real-events/support";
2 import 'cypress-file-upload';
codesnap.dev
```

npm install --save-dev cypress-file-upload
add this in support e2ejs-

import 'cypress-file-upload';

```
• • •
13 cy.wait(10000);
15 cy.xpath("//textarea[@id='APjFqb']").click()
           cy.xpath("//textarea[@id='APjFqb']").type("mukesh otwani", {delay:200})
           cy.xpath("//div[@role='option']/div[1]//span")
           .each(function(ele){
               cy.log(ele.text()); //text comes from jquery.
               if(ele.text().includes("api")){
                   cy.wrap(ele).click({force:true}) //convert to cypress and then click.
```