

pavanpw-30

record videos

can be configured only in the pw config file directly.

```
playwright.config.js > [e] <unknown> > use > video
23  /* Reporter to use. See https://playwright
24  reporter: 'html',
25  /* Shared settings for all the projects be
26  use: {
27    /* Base URL to use in actions like `await
28    // baseURL: 'http://127.0.0.1:3000',
29
30    /* Collect trace when retrying the failed
31    trace: 'on-first-retry',
32    screenshot: "on",
33    video:"on"
34  },
35
```

we can see under test results and in reports.

capture only on failure-

```
24  reporter: 'html',
25  /* Shared settings for all the project
26  use: {
27    /* Base URL to use in actions like
28    // baseURL: 'http://127.0.0.1:3000'
29
30    /* Collect trace when retrying the
31    trace: 'on-first-retry',
32    screenshot: "only-on-failure",
33    video:"retain-on-failure"
34  },
```

```
1 //
2
3 import { test, expect } from '@playwright/test';
4
5 test('test', async ({ page }) => {
6   await page.goto('https://www.demoblaze.com/index.html');
7   await page.getByRole('link', { name: 'Log in' }).click();
8   await page.locator('#loginusername').fill('pavano1');
9   await page.locator('#loginpassword').fill('test@123');
10  await page.getByRole('button', { name: 'Log in' }).click();
11  await expect(page.locator('#logout2')).toBeVisible() //this will pass the test
12  //here we purposely gave wrong to see if videos and screenshot generated on failure
13  //   await expect(page.locator('#logout')).toBeVisible()
14 });
```