pavanpw-16

dialogs and alerts auto dismissed by pw and handled.

you want to manually do it.

handle them before the code which triggers that alert or dialog.

this type method will check what type of dialog it is.

expect(dialog.type()).toContain('alert')

to verify the message inside dialog-

expect(dialog.message()).toContain('I am an alert box!')

to capture the default value of the dialog box which is present-

expect(dialog.defaultValue()).toContain('Harry Potter')

enter the value and click accept-

await dialog.accept('John');

• • • 2 const { test, expect } = require('@playwright/test'); 5 test.skip('Alert with OK', async ({ page }) \Rightarrow { await page.goto('https://testautomationpractice.blogspot.com/'); page.on('dialog', async dialog⇒{ expect(dialog.type()).toContain('alert') expect(dialog.message()).toContain('I am an alert box!') await dialog.accept(); await page.click('//button[normalize-space()="Alert"]'); await page.waitForTimeout(5000); 22 test.skip('Confirmation Dialod-Alert with OK and cancel', async ($\{page\}$) $\Rightarrow \{$ await page.goto('https://testautomationpractice.blogspot.com/'); page.on('dialog', async dialog⇒{ expect(dialog.type()).toContain('confirm') expect(dialog.message()).toContain('Press a button!') await dialog.accept(); // close by using OK button await page.click('//button[normalize-space()="Confirm Box"]'); await expect(page.locator('//p[@id="demo"]')).toHaveText('You pressed OK!') await page.waitForTimeout(5000); 40 test('Prompt Dialog', async ({ page }) ⇒ { await page.goto('https://testautomationpractice.blogspot.com/'); page.on('dialog', async dialog⇒{ expect(dialog.type()).toContain('prompt') expect(dialog.message()).toContain('Please enter your name:') expect(dialog.defaultValue()).toContain('Harry Potter') await dialog.accept('John'); await page.click('//button[normalize-space()="Prompt"]'); await expect(page.locator('//p[@id="demo"]')).toHaveText('Hello John! How are you today?') await page.waitForTimeout(5000);