pavanpw-29

Screenshots

general note -

whenever the parameter says we want options then use ({options1: value, option2:value })

```
2 import { test, expect } from '@playwright/test';
 4 test('page screenshot', async ({ page }) \Rightarrow {
    await page.goto('https://demo.opencart.com/')
    await page.screenshot({ path:'tests/screenshots/'+Date.now()+'HomePage.png'})
13 test('Full page screenshot', async ({ page }) \Rightarrow {
      await page.goto('https://demo.opencart.com/')
       await page.screenshot
18 ({ path: 'tests/screenshots/'+Date.now()+'FullPage.png',fullPage:true})
21 test.only('Element screenshot', async ({ page }) \Rightarrow {
      await page.goto('https://demo.opencart.com/')
       await page.locator('//*[@id="content"]
28 /div[2]/div[1]/form/div')
29 .screenshot({ path:'tests/screenshots/'+Date.now()+'Macbook.png'})
```

to capture the screenshot always and attach in reports-

change in pw config file.

screenshot will be saved under test-results folder and in reports.

```
1 //
2 //using
3 // screenshot: 'on' in config file
4
5 import { test, expect } from '@playwright/test';
6
7 test('test', async ({ page }) ⇒ {
8
9 await page.goto('https://www.demoblaze.com/index.html');
10 await page.getByRole('link', { name: 'Log in' }).click();
11 await page.locator('#loginusername').fill('pavanol');
12 await page.locator('#loginpassword').fill('test@123');
13 await page.getByRole('button', { name: 'Log in' }).click();
14 });
```