


Any data of file format is allowed for data driven testing.
Best is keep all files in fixture and pass in name.

Data files-



```
1  {  
2    "username": "Admin",  
3    "password": "admin123",  
4    "expected": "Dashboard"  
5  }
```

codesnap.dev

```

1 describe('MyTestSuite', () => {
2
3     //Direct access
4     /* it.only('FixturesDemoTest', () => {
5
6         cy.visit("https://opensource-demo.orangehrmlive.com/");
7
8         //get the fixture file and get the data.
9         cy.fixture('orangehrm').then( (data) =>{
10
11             cy.get("input[placeholder='Username']").type(data.username);
12             cy.get("input[placeholder='Password']").type(data.password);
13             cy.get("button[type='submit']").click();
14
15             cy.get(".oxd-text.oxd-text--h6.oxd-topbar-header-breadcrumb-module")
16                 .should('have.text', data.expected);
17         })
18     })*//
19
20
21
22     // Access through Hook - for multiple it blocks
23
24     //same data can be accessed in multiple it blocks.
25     //hooks help us reduce same piece of code.
26     let userdata;
27     before( () =>{
28         cy.fixture("orangehrm").then((data) =>{
29             userdata=data;
30         })
31     })
32
33
34     it('FixturesDemoTest', () => {
35         cy.visit("https://opensource-demo.orangehrmlive.com/");
36
37         cy.get("input[placeholder='Username']").type(userdata.username);
38         cy.get("input[placeholder='Password']").type(userdata.password);
39         cy.get("button[type='submit']").click();
40
41         cy.get(".oxd-text.oxd-text--h6.oxd-topbar-header-breadcrumb-module")
42             .should('have.text', userdata.expected);
43     })
44
45
46 })
47

```

Another data set-

```
1  [  
2  {  
3      "username": "Admin",  
4      "password": "admin123",  
5      "expected": "PIM"  
6  },  
7  {  
8      "username": "xyz",  
9      "password": "admin123",  
10     "expected": "Invalid credentials"  
11 },  
12 {  
13     "username": "Admin",  
14     "password": "xyz",  
15     "expected": "Invalid credentials"  
16 }  
17 ]
```

```

1 describe('MyTestSuite', () => {
2
3     it('DataDrivenTest', () => {
4
5         //giving extension of fixture is optional.
6         cy.fixture("orangehrm2").then((data) => {
7
8             //launch application only one time.
9             cy.visit("https://opensource-demo.orangehrmlive.com/web/index.php/auth/login")
10
11             //iterate loop because there are multiple data present.
12             //if valid data then login and logout.
13             //else validate the invalid messages.
14             data.forEach((userdata) => {
15                 cy.get("input[placeholder='Username']").type(userdata.username);
16                 cy.get("input[placeholder='Password']").type(userdata.password);
17                 cy.get("button[type='submit']").click();
18
19                 if(userdata.username === 'Admin' && userdata.password === "admin123")
20                 {
21                     cy.get(".oxd-text.oxd-text--h6.oxd-topbar-header-breadcrumb-module")
22                         .should('have.text',userdata.expected); // PIM validation
23
24                     cy.get('.oxd-userdropdown-tab > .oxd-icon').click(); // logout
25                     cy.get(':nth-child(4) > .oxd-userdropdown-link').click() //logout
26
27                 }
28                 else{
29                     cy.get(".oxd-text.oxd-text--p.oxd-alert-content-text")
30                         .should("have.text",userdata.expected)
31                 }
32             })
33
34         })
35     })
36
37
38
39 })
40
41 })
42

```