

Top casting-

```
ArrayListPractice.java  ArrayListDemo.java 23
1 package DynamicArray;
2
3 import java.util.ArrayList;
4 import java.util.List;
5
6 public class ArrayListDemo {
7
8     public static void main(String[] args) {
9
10
11         //List(I) -----> ArrayList(C)
12
13         List<String> browserList = new ArrayList<String>();
14         browserList.add("chrome");
15         browserList.add("firefox");
16
17
18
19
20
21     }
22
23 }
24
```

paste topcasting

```

topcasting.java x
1 package com.day29;
2
3 import java.util.ArrayList;
4 import java.util.List;
5
6 public class topcasting {
7
8     public static void main(String[] args) {
9
10         //top casting.
11         List<String> browserlist=new ArrayList<>();
12         browserlist.add("chrome");
13         browserlist.add("firefox");
14         System.out.println(browserlist);
15     }
16 }
17
18 // [chrome, firefox]
19
20

```

map-

```

ArrayListPractice.java  ArrayListDemo.java  *MapConcept.java x
3 import java.util.HashMap;
4
5 public class MapConcept {
6
7     public static void main(String[] args) {
8
9         //collection: <key,value> pair
10        //HashMap(C) —> Map(I)
11        //its non order based collection -- no order
12
13        HashMap<String, Integer> map = new HashMap<String, Integer>();
14
15        map.put("chrome", 101);
16        map.put("firefox", 96);
17        map.put("edge", 111);
18

```


Other data types-

```

18
19
20 HashMap<Integer, Integer> map1 = new HashMap<Integer, Integer>();
21 map1.put(100, 1);
22
23
24 HashMap<String, Object> data = new HashMap<String, Object>();
25
26 data.put("name", "veena");
27 data.put("age", 35);
28 data.put("designation", "SDET2");
29 data.put("isperm", true);
30 data.put("gender", 'f');

```

paste map1



```

1 package com.day29;
2
3 import java.util.HashMap;
4
5 public class map1 {
6
7     public static void main(String[] args) {
8
9         HashMap<String, Integer> h1= new HashMap<>();
10        h1.put("chrome", 10);
11        h1.put("firefox", 324324);
12
13        System.out.println(h1);
14
15        HashMap<Integer, Integer> h2= new HashMap<>();
16        h2.put(2343, 34324);
17        h2.put(32424, 3423423);
18
19        System.out.println(h2);
20
21        HashMap<String, Object> h3= new HashMap<>();
22        h3.put("test", 34324);
23        h3.put("karan", 25.78);
24        h3.put("james", 45.67f);
25        h3.put("bond", true);
26        h3.put("camila", "giraffe");
27        h3.put("charles", 't');

```

```

26     h3.put("camila", "giraffe");
27     h3.put("charles", 't');
28
29     System.out.println(h3);
30 }
31
32 }
33 //{chrome=10, firefox=324324}
34 //{2343=34324, 32424=3423423}
35 //{test=34324, camila=giraffe, james=45.67, karan=25.78, charles=t, bond=true}

```

```

31
32 System.out.println(data.get("name"));
33

```

Object java.util.HashMap.get(Object)

Veena

Key not there-

```

35 System.out.println(data.get("phone"));

```

Null

paste map4-

```

1 package com.day29;
2
3 import java.util.HashMap;
4
5 public class map4 {
6
7     public static void main(String[] args) {
8
9         //duplicate key allowed.
10        //latest value overrides all.
11        HashMap<String, Object> h3= new HashMap<>();
12        h3.put("test", 34324);
13        h3.put("test", 23432.32432);
14        h3.put("karan", 25.78);
15        h3.put("james", 45.67f);
16        h3.put("bond", true);
17        h3.put("camila", "giraffe");
18        h3.put("charles", 't');
19
20        System.out.println(h3);
21    }
22 }
23
24
25 //{test=23432.32432, camila=giraffe, james=45.67, karan=25.78, charles=t, bond=true}
26

```

paste map5-

```

1 package com.day29;
2
3 import java.util.HashMap;
4
5 public class map5 {
6
7     public static void main(String[] args) {
8
9         //duplicate value allowed.
10
11         HashMap<String, Object> h3= new HashMap<>();
12         h3.put("test", 34324);
13         h3.put("karan", 34324);
14         h3.put("james", 45.67f);
15         h3.put("bond", true);
16         h3.put("camila", "giraffe");
17         h3.put("charles", 't');
18
19         System.out.println(h3);
20     }
21 }
22
23
24 //{test=34324, camila=giraffe, james=45.67, karan=34324, charles=t, bond=true}
25
26

```

paste map6-

```

1 package com.day29;
2
3 import java.util.HashMap;
4
5 public class map6 {
6
7     public static void main(String[] args) {
8
9         //duplicate key and duplicate value allowed.
10
11         HashMap<String, Object> h3= new HashMap<>();
12         h3.put("test", 34324);
13         h3.put("test", 34324);
14         h3.put("karan", 34324);
15         h3.put("james", 45.67f);
16         h3.put("bond", true);
17         h3.put("camila", "giraffe");
18         h3.put("charles", 't');
19
20         System.out.println(h3);
21     }
22 }
23
24
25 //{test=34324, camila=giraffe, james=45.67, karan=34324, charles=t, bond=true}
26

```

Key is null-

Allowed.

```

31      data.put(null, "pune");
32
38      System.out.println(data.get(null));

```

Pune

Duplicate null key-

Allowed.

```

32      data.put(null, "India");
33
38      System.out.println(data.get(null));

```

India

Overwrite the old value.

Null values-

Allowed.

```

34      data.put("phone", null);
35
39      System.out.println(data.get("age"));
40      System.out.println(data.get("phone")); //null

```

Null

Multiple null values-

Allowed.

```

33 //      data.put(null, "India");
34      data.put("phone", null);
35      data.put("city", null);
...
40      System.out.println(data.get("age"));
41      System.out.println(data.get("phone")); //null
42      //System.out.println(data.get(null)); //India
43      System.out.println(data.get("city")); //null
...

```

Null

Null

```

8
9      //collection: <key,value> pair
10     //HashMap(C) ----> Map(I)
11     //its non order based collection -- no order
12     //one null key is allowed
13     //but multiple values can be allowed
14

```

Key and value null-

```

36      data.put("city", null);
37      data.put(null, null);
38
...
44      System.out.println(data.get("phone")); //null
45      System.out.println(data.get(null)); //null

```

Null

paste map12

```

1 package com.day29;
2
3 import java.util.HashMap;
4
5 public class map12 {
6
7     public static void main(String[] args) {
8
9         //key and value null.
10        //multiple key null and multiple value null.
11        HashMap<String, Object> h3= new HashMap<>();
12        h3.put(null, null);
13        h3.put(null, null);
14        h3.put("karan", 34324);
15        h3.put("james", 45.67f);
16        h3.put("bond", true);
17        h3.put("camila", "giraffe");
18        h3.put("charles", 't');
19
20        System.out.println(h3);
21    }
22 }
23
24 //{null=null, camila=giraffe, james=45.67, karan=34324, charles=t, bond=true}
25
26

```

Blank value-

```

38        data.put("address", "");
39
40
41
42
43
44
45
46
47
48        System.out.println(data.get("address")); //null
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100

```

paste map14


```

1 package com.day29;
2
3 import java.util.HashMap;
4
5 public class map14 {
6
7     public static void main(String[] args) {
8
9         //duplicate blank value.
10        HashMap<String, Object> h3= new HashMap<>();
11        h3.put(null, null);
12        h3.put(null, null);
13        h3.put("Tester", "");
14        h3.put("Tester1", "");
15        h3.put("karan", 34324);
16        h3.put("james", 45.67f);
17        h3.put("bond", true);
18        h3.put("camila", "giraffe");
19        h3.put("charles", 't');
20
21        System.out.println(h3);
22    }
23 }
24
25
26 //{null=null, Tester=, camila=giraffe, james=45.67, karan=34324, charles=t, Tester1=, bond=true}
27

```

Space value-

```

38 data.put("address", " ");
39
48 System.out.println(data.get("address")); //null

```

-
-

```

9 //collection: <key,value> pair
10 //HashMap(C) --> Map(I)
11 //its non order based collection -- no order
12 //one null key is allowed
13 //but multiple null values can be allowed
14

```

paste [map16](#)

```

1 package com.day29;
2
3 import java.util.HashMap;
4
5 public class map16 {
6
7     public static void main(String[] args) {
8
9         //multiple space values.
10        HashMap<String, Object> h3= new HashMap<>();
11        h3.put(null, null);
12        h3.put(null, null);
13        h3.put("Tester", "");
14        h3.put("Tester1", " ");
15        h3.put("Tester2", " ");
16        h3.put("karan", 34324);
17        h3.put("james", 45.67f);
18        h3.put("bond", true);
19        h3.put("camila", "giraffe");
20        h3.put("charles", 't');
21
22        System.out.println(h3);
23    }
24 }
25
26
27 //{null=null, Tester=, camila=giraffe, james=45.67, karan=34324, charles=t,
28 //Tester2= , Tester1= , bond=true}
29

```

Blank key-

```

39 data.put("", "32.33");
50 System.out.println(data.get(""));
51
52 32.33

```

paste map18

```

1 package com.day29;
2
3 import java.util.HashMap;
4
5 public class map18 {
6
7     public static void main(String[] args) {
8
9         //multiple blank key.
10        HashMap<String, Object> h3= new HashMap<>();
11        h3.put(null, null);
12        h3.put(null, null);
13        h3.put("", "karan");
14        h3.put("", "jigar");
15        h3.put("Tester1", " ");
16        h3.put("karan", 34324);
17        h3.put("james", 45.67f);
18        h3.put("bond", true);
19        h3.put("camila", "giraffe");
20        h3.put("charles", 't');
21
22        System.out.println(h3);
23    }
24 }
25
26
27 //{null=null, =jigar, camila=giraffe, james=45.67, karan=34324, charles=t, Tester1= , bond=true}
28

```

key and value blank-


paste map19-

```

1 package com.day29;
2
3 import java.util.HashMap;
4
5 public class map19 {
6
7     public static void main(String[] args) {
8
9         //key and value blank.
10        HashMap<String, Object> h3= new HashMap<>();
11        h3.put(null, null);
12        h3.put(null, null);
13        h3.put("", "");
14
15
16        System.out.println(h3);
17    }
18 }
19
20
21 //{null=null, =}
22

```


paste map20-



```
1 package com.day29;
2
3 import java.util.HashMap;
4
5 public class map20 {
6
7     public static void main(String[] args) {
8
9         //key and value blank.
10        //duplicates.
11        HashMap<String, Object> h3= new HashMap<>();
12        h3.put(null, null);
13        h3.put(null, null);
14        h3.put("", "");
15        h3.put("", "");
16
17
18        System.out.println(h3);
19    }
20
21 }
22
23 //{null=null, =}
24
25
```

key and value space-

paste map21-

A screenshot of a Java IDE window titled 'map21.java'. The code is as follows:

```
1 package com.day29;
2
3 import java.util.HashMap;
4
5 public class map21 {
6
7     public static void main(String[] args) {
8
9         //key and value space.
10        HashMap<String, Object> h3= new HashMap<>();
11        h3.put(null, null);
12        h3.put(null, null);
13        h3.put(" ", " ");
14
15
16        System.out.println(h3);
17    }
18
19 }
20
21 //{null=null,  = }
22
23
```

paste map22-

```

1 package com.day29;
2
3 import java.util.HashMap;
4
5 public class map22 {
6
7     public static void main(String[] args) {
8
9         //key and value space.
10        //duplicates.
11        HashMap<String, Object> h3= new HashMap<>();
12        h3.put(null, null);
13        h3.put(null, null);
14        h3.put(" ", " ");
15        h3.put(" ", " ");
16
17
18        System.out.println(h3);
19    }
20
21 }
22
23 //{null=null,  = }
24

```

Duplicate-

Overwrite the old value.

```

40        data.put("age", 37);
46        System.out.println(data.get("age"));

```

37

Print hash map directly-

```

53        System.out.println("-----");
54        System.out.println(data);

```

```
-----
{null=pune, address= , gender=f, phone=null, city=null, name=vee
```

No order in output.

Null keys and null values comes first.

```

9      //collection: <key,value> pair
10     //HashMap(C) ----> Map(I)
11     //its non order based collection -- no order
12     //one null key is allowed
13     //but multiple null values can be allowed
14     //<null,value> : it will stored at first position
```

Default capacity of hash map is 15.

Every block called as node in hash map. Every node has three parts.


Hash code – special code for the key. Duplicate hash codes can be present.

Upto jdk 1.7 we can add n number of nodes and make it link list when the hash code is same. This is collision.

Changed from jdk 1.8.

Link list is linear search. Binary tree is faster to search.

When key is null, then it always go in the first index.



```

57 //
58     HashMap<String, Integer> empMap = new HashMap<String, Integer>();
59     empMap.put("Tom", 20);
60     empMap.put("Veena", 30);
61     empMap.put("Sunil", 35);
62     empMap.put("pradesh", 40);
63
64     System.out.println(empMap);
65
66
67

```

{Veena=30, Tom=20, Sunil=35, pradesh=40}

How to check hash code-

Put debugger on line 59.

Mouse hover empMap in line 64.


```

57 //
58     HashMap<String, Integer> empMap = new HashM
59     empMap.put("Tom", 20);
60     empMap.put("Veena", 30);
61     empMap.put("Sunil", 35);
62     empMap.put("pradesh", 40);
63
64     System.out.println(empMap);
65

```

82532265

```

empMap= HashMap<K,V> (id=22)
  [0]= HashMap$Node<K,V> (id=26)
    key= "Veena" (id=48)
    coder= 0
    hash= 82532265
    hashIsZero= false
    value= Integer (id=25)
  [1]= HashMap$Node<K,V> (id=24)
  [2]= HashMap$Node<K,V> (id=28)
  [3]= HashMap$Node<K,V> (id=30)

```

Lets debug with null key-

```

57 //
58     HashMap<String, Integer> empMap = new HashMap<String, Integer>();
59     empMap.put("Tom", 20);
60     empMap.put("Veena", 30);
61     empMap.put("Sunil", 35);
62     empMap.put("pradesh", 40);
63     empMap.put(null, 34);
64
65
66     System.out.println(empMap);
67

```

Null at first place. No hash code calculated.

```

empMap= HashMap<K,V> (id=22)
  [0]= HashMap$Node<K,V> (id=32)
    key= null
    value= Integer (id=31)
  [1]= HashMap$Node<K,V> (id=26)
  [2]= HashMap$Node<K,V> (id=24)
  [3]= HashMap$Node<K,V> (id=28)
  [4]= HashMap$Node<K,V> (id=30)

```

Size-

```
66 System.out.println(empMap.size());
67
```

5

Print hash map-

```
66 System.out.println(empMap);
67
```

gender=1, phone=null, city=null, name=veena, designa
{null=34, Veena=45, Tom=20, Sunil=35, pradesh=40}

Min and max value of character- 1.52

Cant say because there are different character sets like number, alphabets and so on, so we cant have definite answer for this.

```
69
70 System.out.println(Character.MIN_VALUE);
71 System.out.println(Character.MAX_VALUE);
72
```



nothing comes in output.

```
69
70 String s = null;
71 System.out.println(Double.parseDouble(s));
72
```

Null pointer exception.

```
69  
70     String s = null;  
71     //System.out.println(Double.parseDouble(s));  
72     System.out.println(Integer.parseInt(s));  
73
```

Number format exception.