

pw-30th oct-1

—

playwright intro - official doc for going through and best. ms owns only web and apis multi browser support like selenium lang - java, net, py, js, ts runs on mobile web browsers auto wait internally built tracing - includes screenshot, videos

node js mandatory

—

be in path of project-

install playwright.

npm init playwright@latest

—once installed we can run all these commands.

✓ Success! Created a Playwright Test project at C:\Users\karan\Desktop\playwrightbymukesh

Inside that directory, you can run several commands:

npx playwright test Runs the end-to-end tests.

npx playwright test --ui Starts the interactive UI mode.

npx playwright test --project=chromium Runs the tests only on Desktop Chrome.

npx playwright test example Runs the tests in a specific file.

npx playwright test --debug Runs the tests in debug mode.

npx playwright codegen Auto generate tests with Codegen.

We suggest that you begin by typing:

npx playwright test

And check out the following files:

- ~~.\tests\example.spec.js~~ — Example end-to-end test
- ~~.\tests\examples\demo-todo-app.spec.js~~ — Demo Todo App end-to-end tests
- ~~.\playwright.config.js~~ — Playwright Test configuration

Visit <https://playwright.dev/docs/intro> for more information. ✨

Happy hacking! 🛠️

—

command to run test on specific browser

npx playwright test --project=chromium if not specified test runs on all browsers

—all plugins in built for all different actions like reporting.

—

playwright config.js file

all configs of pw.

by default all test run in parallel

```
36      /* Configure projects for major browsers */
37      projects: [
38          {
39              name: 'chromium',
40              use: { ...devices['Desktop Chrome'] },
41          },
42
43          {
44              name: 'firefox',
45              use: { ...devices['Desktop Firefox'] },
46          },
47
48          {
49              name: 'webkit',
50              use: { ...devices['Desktop Safari'] },
51          },
52      ]
```

—

default time out for one test is 30000 1.30

max time out for locator is 5000 1.30

—

default script runs in headless

npx playwright test

—open the report after run

npx playwright show-report

it will give live server to check report.

Serving HTML report at <http://localhost:9323>. Press Ctrl+C to quit.

—

to get offline reports the folder path is -

C:\Users\karan\Desktop\playwrightbymukesh\playwright-report

here we have index.html

—

run in headed mode

npx playwright test --headed

—run header and in specific browser.

npx playwright test --project=chromium --headed