

# Socket Programming in Java

# Socket Programming

- What is a socket?
- Using sockets
  - Types (Protocols)
  - Associated functions
  - Styles


# What is a socket?

- An interface between application and network
  - The application creates a socket
  - The socket *type* dictates the style of communication
    - reliable vs. best effort
    - connection-oriented vs. connectionless
- Once configured, the application can
  - pass data to the socket for network transmission
  - receive data from the socket (transmitted through the network by some other host)

# Two essential types of sockets

- STREAM


- a.k.a. TCP
- reliable delivery
- in-order guaranteed
- connection-oriented
- bidirectional



# Two essential types of sockets


- DATAGRAM

- a.k.a. UDP
- unreliable delivery; data can be lost, although this is unusual
- no order guarantees
- no notion of “connection” – app indicates dest. for each packet
- can send or receive



# Ports

- Each host has 65,536 ports
- Some ports are *reserved for specific apps*
  - 20,21: FTP
  - 23: Telnet
  - 80: HTTP



- A socket provides an interface to send data to/from the network through a port

# Objectives

- The InetAddress Class
- Using sockets
  - TCP sockets
  - Datagram Sockets

# Classes in java.net

- The core package java.net contains a number of classes that allow programmers to carry out network programming
  - ContentHandler
  - DatagramPacket
  - DatagramSocket
  - DatagramSocketImplURLConnection
  - InetAddress
  - MulticastSocket
  - ServerSocket
  - Socket
  - SocketImpl
  - URL
  - URLConnection
  - URLEncoder
  - URLStreamHandler



# Exceptions in Java

- BindException
- ConnectException
- MalformedURLException
- NoRouteToHostException
- ProtocolException
- SocketException
- UnknownHostException
- UnknownServiceException

# The InetAddress Class

- Handles Internet addresses both as host names and as IP addresses
- Static Method `getByName` returns the IP address of a specified host name as an `InetAddress` object
- Methods for address/name conversion:
  - `public static InetAddress getByName(String host) throws UnknownHostException`
  - `public static InetAddress[] getAllByName(String host) throws UnknownHostException`
  - `public static InetAddress getLocalHost() throws UnknownHostException`
  - `public boolean isMulticastAddress()`
  - `public String getHostName()`
  - `public byte[] getAddress()`
  - `public String.getHostAddress()`
  - `public int hashCode()`
  - `public boolean equals(Object obj)`
  - `public String toString()`

# Find an IP Address: IPFinder.java

```
// File: IPFinder.java
```

```
// Get the IP address of a host
```

```
import java.net.*;
```

```
import java.io.*;
```

```
import javax.swing.*;
```

```
public class IPFinder
```

```
{  
    public static void main(String[] args) throws IOException
```

```
    {  
        String host;
```

```
        host = JOptionPane.showInputDialog("Please input the server's name");
```

```
        try
```

```
        {InetAddress address = InetAddress.getByName(host);
```

```
        JOptionPane.showMessageDialog(null,"IP address: " + address.toString());
```

```
        }
```

```
        catch (UnknownHostException e)
```

```
        {JOptionPane.showMessageDialog(null,"Could not find " + host);
```

```
        }
```

```
    }
```

```
}
```

# Retrieving the current machine's address

```
import java.net.*;

public class LocalIP
{
    public static void main(String[] args)
    {
        try
        {
            InetAddress address = InetAddress.getLocalHost();
            System.out.println (address);
        }
        catch (UnknownHostException e)
        {
            System.out.println("Could not find local address!");
        }
    }
}
```

# The Java.net.Socket Class

- Connection is accomplished via construction.
  - Each Socket object is associated with exactly one remote host.
    - To connect to a different host, you must create a new Socket object.  
`public Socket(String host, int port) throws UnknownHostException, IOException`
      - connect to specified host/port  
`public Socket(InetAddress address, int port) throws IOException`
        - connect to specified IP address/port  
`public Socket(String host, int port, InetAddress localAddress, int localPort) throws IOException`
          - connect to specified host/port and bind to specified local address/port  
`public Socket(InetAddress address, int port, InetAddress localAddress, int localPort)`  
throws  
IOException
            - connect to specified IP address/port and bind to specified local address/port
  - Sending and receiving data is accomplished with output and input streams.  
There are methods to get an input stream for a socket and an output stream for the socket.  
`public InputStream getInputStream() throws IOException`  
`public OutputStream getOutputStream() throws IOException`
  - To close a socket:  
`public void close() throws IOException`

# The `java.net.ServerSocket` Class

- The *java.net.ServerSocket* class represents a server socket. It is constructed on a particular port. Then it calls `accept()` to listen for incoming connections.
  - `accept()` blocks until a connection is detected.
  - Then `accept()` returns a `java.net.Socket` object that is used to perform the actual communication with the client.
    - the “plug”
  - `backlog` is the maximum size of the queue of connection requests

`public ServerSocket(int port) throws IOException`

`public ServerSocket(int port, int backlog) throws IOException`

`public ServerSocket(int port, int backlog, InetAddress bindAddr) throws IOException`

`public Socket accept() throws IOException`

`public void close() throws IOException`

# TCP Sockets

Example: **SocketThrdServer.java**

SERVER:

1. Create a `ServerSocket` object  
*`ServerSocket servSocket = new ServerSocket(1234);`*
2. Put the server into a waiting state  
*`Socket link = servSocket.accept();`*
3. Set up input and output streams
  - use thread to serve this client via *link*
4. Send and receive data  
*`out.println(awaiting data...);`*  
*`String input = in.readLine();`*
5. Close the connection  
*`link.close()`*

# Set up input and output streams

- Once a socket has connected you send data to the server via an output stream. You receive data from the server via an input stream.
- Methods *getInputStream* and *getOutputStream* of class *Socket*:

```
BufferedReader in =  
    new BufferedReader(  
        new InputStreamReader(link.getInputStream()));  
  
PrintWriter out =  
    new PrintWriter(link.getOutputStream(),true);
```



# TCP Sockets

Example: **SocketClient.java**


CLIENT:

1. Establish a connection to the server  
*Socket link =*  
*new Socket(<server>, <port>);*
2. Set up input and output streams
3. Send and receive data
4. Close the connection

# Socket programming with TCP

## Example client-server app:


- client reads line from standard input (**inFromUser** stream) , sends to server via socket (**outToServer** stream)
- server reads line from socket
- server converts line to uppercase, sends back to client
- client reads, prints modified line from socket (**inFromServer** stream)



# Client/server socket interaction: TCP

Server (running on **hostid**)

Client



# TCPClient.java

```
import java.io.*;
import java.net.*;

class TCPClient {
    public static void main(String argv[]) throws Exception
    {
        String sentence;
        String modifiedSentence;

        BufferedReader inFromUser =
            new BufferedReader(new InputStreamReader(System.in));

        Socket clientSocket = new Socket("hostname", 6789);

        DataOutputStream outToServer =
            new DataOutputStream(clientSocket.getOutputStream());
```

# TCPClient.java

```
BufferedReader inFromServer =  
    new BufferedReader(new  
InputStreamReader(clientSocket.getInputStream()));
```

```
sentence = inFromUser.readLine();
```

```
outToServer.writeBytes(sentence + '\n');
```

```
modifiedSentence = inFromServer.readLine();
```

```
System.out.println("FROM SERVER: " + modifiedSentence);
```

```
clientSocket.close();
```

```
}
```

```
}
```

# TCPServer.java

```
import java.io.*;
import java.net.*;
class TCPServer {
    public static void main(String argv[]) throws Exception
    {
        String clientSentence;
        String capitalizedSentence;
```

```
ServerSocket welcomeSocket = new ServerSocket(6789);
```

```
while(true) {
```

```
Socket connectionSocket = welcomeSocket.accept();
```

```
    BufferedReader inFromClient = new BufferedReader(new
        InputStreamReader(connectionSocket.getInputStream()));
```

# TCPServer.java

```
DataOutputStream outToClient =  
    new DataOutputStream(connectionSocket.getOutputStream());
```

```
clientSentence = inFromClient.readLine();
```

```
capitalizedSentence = clientSentence.toUpperCase() + '\n';
```

```
outToClient.writeBytes(capitalizedSentence);
```

```
}  
}  
}
```

# The UDP classes

- 2 classes:
  - `java.net.DatagramSocket` class
    - is a connection to a port that does the sending and receiving. Unlike TCP sockets, there is no distinction between a UDP socket and a UDP server socket. Also unlike TCP sockets, a `DatagramSocket` can send to multiple, different addresses. The address to which data goes is stored in the packet, not in the socket.  
*`public DatagramSocket()` throws `SocketException`*  
*`public DatagramSocket(int port)` throws `SocketException`*  
*`public DatagramSocket(int port, InetAddress laddr)` throws `SocketException`*
  - `java.net.DatagramPacket` class
    - is a wrapper for an array of bytes from which data will be sent or into which data will be received. It also contains the address and port to which the packet will be sent.  
*`public DatagramPacket(byte[] data, int length)`*  
*`public DatagramPacket(byte[] data, int length, InetAddress host, int port)`*
  - No distinction between server and client sockets



# Datagram Sockets

Example: **UDPListener.java**

SERVER:

1. Create a `DatagramSocket` object  
*DatagramSocket dgramSocket =  
new DatagramSocket(1234);*
2. Create a buffer for incoming datagrams  
*byte[] buffer = new byte[256];*
3. Create a *DatagramPacket* object for the incoming datagram  
*DatagramPacket inPacket =  
new DatagramPacket(buffer, buffer.length);*
4. Accept an incoming datagram  
*dgramSocket.receive(inPacket)*

# Datagram Sockets

SERVER:

5. Accept the sender's address and port from the packet  
*InetAddress clientAddress = inPacket.getAddress();*  
*int clientPort = inPacket.getPort();*
6. Retrieve the data from the buffer  
*String message =*  
*new String(inPacket.getData(), 0, inPacket.getLength());*
7. Create the response datagram  
*DatagramPacket outPacket =*  
*new DatagramPacket(*  
*response.getBytes(), response.length(),*  
*clientAddress, clientPort);*
8. Send the response datagram  
*dgramSocket.send(outPacket)*
9. Close the *DatagramSocket*: *dgram.close();*

# Datagram Sockets

Example: **UDPTalk.java**

CLIENT:

1. Create a DatagramSocket object  
*DatagramSocket dgramSocket = new DatagramSocket;*
2. Create the outgoing datagram  
*DatagramPacket outPacket =  
    new DatagramPacket(message.getBytes(), message.length(), host, port);*
3. Send the datagram message  
*dgramSocket.send(outPacket)*
4. Create a buffer for incoming datagrams  
*byte[] buffer = new byte[256];*

# Datagram Sockets


## CLIENT:

5. Create a *DatagramPacket* object for the incoming datagram  
*DatagramPacket inPacket =  
    new DatagramPacket(buffer, buffer.length);*
6. Accept an incoming datagram  
*dgramSocket.receive(inPacket)*
7. Retrieve the data from the buffer  
*string response = new String(inPacket.getData(), 0,  
  
inPacket.getLength());*
8. Close the *DatagramSocket*:  
*dgram.close();*

# Handling Data

- Data arrives/is sent as byte array
  - To send int
    - Convert to string (construct String from it)
    - use `getBytes()` to convert to `byte[]` and send
  - Receive int
    - Convert `byte[]` to String
    - use `Integer.parseInt()` to convert to Integer


# Example: Java client (UDP)



# Client/server socket interaction: UDP

Server (running on **hostid**)

Client



# UDPClient.java

```
import java.io.*;
import java.net.*;

class UDPClient {
    public static void main(String args[]) throws Exception
    {
        BufferedReader inFromUser =
            new BufferedReader(new InputStreamReader(System.in));

        DatagramSocket clientSocket = new DatagramSocket();

        InetAddress IPAddress =
InetAddress.getByName("hostname");

        byte[] sendData = new byte[1024];
        byte[] receiveData = new byte[1024];

        String sentence = inFromUser.readLine();

        sendData = sentence.getBytes();
```



# UDPClient.java

```
DatagramPacket sendPacket =  
    new DatagramPacket(sendData, sendData.length,  
    IPAddress, 9876);
```

```
clientSocket.send(sendPacket);
```

```
DatagramPacket receivePacket =  
    new DatagramPacket(receiveData, receiveData.length);
```

```
clientSocket.receive(receivePacket);
```

```
String modifiedSentence =  
    new String(receivePacket.getData());
```

```
System.out.println("FROM SERVER:" + modifiedSentence);
```

```
clientSocket.close();
```

```
    }  
}
```

# UDPServer.java

```
import java.io.*;
import java.net.*;

class UDPServer {
    public static void main(String args[]) throws Exception
    {
        DatagramSocket serverSocket = new
DatagramSocket(9876);

        byte[] receiveData = new byte[1024];
        byte[] sendData = new byte[1024];

        while(true)
        {
            DatagramPacket receivePacket =
                new DatagramPacket(receiveData, receiveData.length);

            serverSocket.receive(receivePacket);

            String sentence = new String(receivePacket.getData());
```

# UDPServer.java

```
InetAddress IPAddress = receivePacket.getAddress();
```

```
int port = receivePacket.getPort();
```

```
String capitalizedSentence = sentence.toUpperCase();  
sendData = capitalizedSentence.getBytes();
```

```
DatagramPacket sendPacket =  
    new DatagramPacket(sendData, sendData.length, IPAddress, port);
```

```
serverSocket.send(sendPacket);
```

```
}
```

```
}
```

```
}
```