

Ex No: 8**OBJECT DETECTION WITH YOLO3****AIM:**

To build an object detection model with YOLO3 using Keras/TensorFlow.

PROCEDURE:

1. Download and load the dataset.
2. Perform analysis and preprocessing of the dataset.
3. Build a simple neural network model using Keras/TensorFlow.
4. Compile and fit the model.
5. Perform prediction with the test dataset.
6. Calculate performance metrics.

PROGRAM:

```
# IMPORTANT: RUN THIS CELL IN ORDER TO IMPORT YOUR KAGGLE DATA SOURCES
# TO THE CORRECT LOCATION (/kaggle/input) IN YOUR NOTEBOOK,
# THEN FEEL FREE TO DELETE THIS CELL.
# NOTE: THIS NOTEBOOK ENVIRONMENT DIFFERS FROM KAGGLE'S PYTHON
# ENVIRONMENT SO THERE MAY BE MISSING LIBRARIES USED BY YOUR
# NOTEBOOK.
```

```
import os
import sys
from tempfile import NamedTemporaryFile
from urllib.request import urlopen
from urllib.parse import unquote, urlparse
from urllib.error import HTTPError
from zipfile import ZipFile
import tarfile
import shutil
```

```
CHUNK_SIZE = 40960
```

```
DATA_SOURCE_MAPPING = 'data-for-yolo-v3-kernel:https%3A%2F%2Fstorage.googleapis.com
%2Fkaggle-data-sets%2F81753%2F300187%2Fbundle%2Farchive.zip%3FX-Goog-Algorithm
%3DGOOG4-RSA-SHA256%26X-Goog-Credential%3Dgcp-kaggle-com%2540kaggle-
161607.iam.gserviceaccount.com%252F20241013%252Fauto%252Fstorage%252Fgoog4_request
%26X-Goog-Date%3D20241013T134721Z%26X-Goog-Expires%3D259200%26X-Goog-
```

```
SignedHeaders%3Dhost%26X-Goog-Signature
%3D111d66e74f67e64fdb7c945042efbdae1215da134d52cf0c52c6a96cc4cde60f3b80f1ea6e5820082
e23d78f1c059e97b37381c855e53751064f7320567256db1283ba5484fadb539ff5b705b7fbef6d59ba32
b07900a140e7eca2dde2de99473d64369dc2f5d58c8dca00f63932deec3ba9c64effb6e1c4a22156bf2241
f36a2531348072fd38f36b3a9f54dd833383251f53462ccf2e402d42d3d15c231384cb8b895794710e7e8
3114cc26b134b8a1ad396c3126240d3328e4d2849790c95feb4b1fdb92fda78b5715af082c994d7d031a
91744795141c700e68cdd8e0c159fcbca9acae1116b2fa43b0068ca1df76ff39f9b9242cd9806b509e726e
bac1'
```

```
KAGGLE_INPUT_PATH='/kaggle/input'
```

```
KAGGLE_WORKING_PATH='/kaggle/working'
```

```
KAGGLE_SYMLINK='kaggle'
```

```
!umount /kaggle/input/ 2> /dev/null
```

```
shutil.rmtree('/kaggle/input', ignore_errors=True)
```

```
os.makedirs(KAGGLE_INPUT_PATH, 0o777, exist_ok=True)
```

```
os.makedirs(KAGGLE_WORKING_PATH, 0o777, exist_ok=True)
```

```
try:
```

```
    os.symlink(KAGGLE_INPUT_PATH, os.path.join(".", 'input'), target_is_directory=True)
```

```
except FileExistsError:
```

```
    pass
```

```
try:
```

```
    os.symlink(KAGGLE_WORKING_PATH, os.path.join(".", 'working'), target_is_directory=True)
```

```
except FileExistsError:
```

```
    pass
```

```
for data_source_mapping in DATA_SOURCE_MAPPING.split(',):
```

```
    directory, download_url_encoded = data_source_mapping.split(':')
```

```
    download_url = unquote(download_url_encoded)
```

```
    filename = urlparse(download_url).path
```

```
    destination_path = os.path.join(KAGGLE_INPUT_PATH, directory)
```

```
    try:
```

```
        with urlopen(download_url) as fileres, NamedTemporaryFile() as tfile:
```

```
            total_length = fileres.headers['content-length']
```

```
print(f'Downloading {directory}, {total_length} bytes compressed')
dl = 0
data = fileres.read(CHUNK_SIZE)
while len(data) > 0:
    dl += len(data)
    tfile.write(data)
    done = int(50 * dl / int(total_length))
    sys.stdout.write(f'\r[{'=' * done} {' ' * (50-done)}] {dl} bytes downloaded")
    sys.stdout.flush()
    data = fileres.read(CHUNK_SIZE)
if filename.endswith('.zip'):
    with ZipFile(tfile) as zfile:
        zfile.extractall(destination_path)
else:
    with tarfile.open(tfile.name) as tarfile:
        tarfile.extractall(destination_path)
print(f'\nDownloaded and uncompressed: {directory}')
except HTTPError as e:
    print(f'Failed to load (likely expired) {download_url} to path {destination_path}')
    continue
except OSError as e:
    print(f'Failed to load {download_url} to path {destination_path}')
    continue

print('Data source import complete.')

import os
import numpy as np
import pandas as pd
import struct

import scipy.io
```

```
import scipy.misc
import PIL
import cv2
from skimage.transform import resize

import tensorflow as tf
from keras import backend as K
from keras.layers import Input, Lambda, Conv2D, BatchNormalization, LeakyReLU,
ZeroPadding2D, UpSampling2D
from keras.models import load_model, Model
from keras.layers import add, concatenate
from keras.preprocessing.image import load_img
from keras.preprocessing.image import img_to_array

import matplotlib.pyplot as plt
from matplotlib.pyplot import imshow
from matplotlib.patches import Rectangle

class Read_Weights:

    def __init__(self, file_name):

        with open(file_name, 'rb') as w_f:

            major, = struct.unpack('i', w_f.read(4))
            minor, = struct.unpack('i', w_f.read(4))
            revision, = struct.unpack('i', w_f.read(4))

            if (major*10 + minor) >= 2 and major < 1000 and minor < 1000:
                w_f.read(8)
            else:
                w_f.read(4)
```

```
transpose = (major > 1000) or (minor > 1000)
binary = w_f.read()

self.offset = 0
self.all_weights = np.frombuffer(binary, dtype = 'float32')

def read_bytes(self, size):

    self.offset = self.offset + size

    return self.all_weights[ self.offset-size : self.offset ]

def load_weights(self, model):

    for i in range(106):
        try:
            conv_layer = model.get_layer('conv_' + str(i))
            print("loading weights of convolution #" + str(i))

            if i not in [81, 93, 105]:

                norm_layer = model.get_layer('bnorm_' + str(i))
                size = np.prod(norm_layer.get_weights()[0].shape)

                beta = self.read_bytes(size) # bias
                gamma = self.read_bytes(size) # scale
                mean = self.read_bytes(size) # mean
                var = self.read_bytes(size) # variance

                weights = norm_layer.set_weights([gamma, beta, mean, var])

            if len(conv_layer.get_weights()) > 1:
```

```

        bias = self.read_bytes(np.prod(conv_layer.get_weights()[1].shape))
        kernel = self.read_bytes(np.prod(conv_layer.get_weights()[0].shape))
        kernel = kernel.reshape(list(reversed(conv_layer.get_weights()[0].shape)))
        kernel = kernel.transpose([2,3,1,0])
        conv_layer.set_weights([kernel, bias])

    else:

        kernel = self.read_bytes(np.prod(conv_layer.get_weights()[0].shape))
        kernel = kernel.reshape(list(reversed(conv_layer.get_weights()[0].shape)))
        kernel = kernel.transpose([2,3,1,0])
        conv_layer.set_weights([kernel])

    except ValueError:
        print("no convolution #" + str(i))

def reset(self):
    self.offset = 0

def conv_block(inp, convs, skip=True):

    x = inp
    count = 0

    for conv in convs:

        if count == (len(convs) - 2) and skip:
            skip_connection = x

        count += 1

        if conv['stride'] > 1 : x = ZeroPadding2D(((1,0),(1,0)))(x) # peculiar padding as darknet prefers
left and top

```

```

x = Conv2D(conv['filter'],
           conv['kernel'],
           strides = conv['stride'],
           padding = 'valid' if conv['stride'] > 1 else 'same', # peculiar padding as darknet prefers left
and top
           name = 'conv_' + str(conv['layer_idx']),
           use_bias = False if conv['bnorm'] else True)(x)

if conv['bnorm']: x = BatchNormalization(epsilon = 0.001, name = 'bnorm_' +
str(conv['layer_idx']))(x)

if conv['leaky']: x = LeakyReLU(alpha = 0.1, name = 'leaky_' + str(conv['layer_idx']))(x)

return add([skip_connection, x]) if skip else x

def make_yolov3_model():

    input_image = Input(shape=(None, None, 3))

    # Layers 0 to 4
    x = conv_block(input_image, [{'filter': 32, 'kernel': 3, 'stride': 1, 'bnorm': True, 'leaky': True,
'layer_idx': 0},
                                {'filter': 64, 'kernel': 3, 'stride': 2, 'bnorm': True, 'leaky': True, 'layer_idx': 1},
                                {'filter': 32, 'kernel': 1, 'stride': 1, 'bnorm': True, 'leaky': True, 'layer_idx': 2},
                                {'filter': 64, 'kernel': 3, 'stride': 1, 'bnorm': True, 'leaky': True, 'layer_idx': 3}])

    # Layers 5 to 8
    x = conv_block(x, [{'filter': 128, 'kernel': 3, 'stride': 2, 'bnorm': True, 'leaky': True, 'layer_idx': 5},
                        {'filter': 64, 'kernel': 1, 'stride': 1, 'bnorm': True, 'leaky': True, 'layer_idx': 6},
                        {'filter': 128, 'kernel': 3, 'stride': 1, 'bnorm': True, 'leaky': True, 'layer_idx': 7}])

    # Layers 9 to 11
    x = conv_block(x, [{'filter': 64, 'kernel': 1, 'stride': 1, 'bnorm': True, 'leaky': True, 'layer_idx': 9},

```

```
{'filter': 128, 'kernel': 3, 'stride': 1, 'bnorm': True, 'leaky': True, 'layer_idx': 10})
```

```
# Layers 12 to 15
```

```
x = conv_block(x, [{'filter': 256, 'kernel': 3, 'stride': 2, 'bnorm': True, 'leaky': True, 'layer_idx': 12},  
                  {'filter': 128, 'kernel': 1, 'stride': 1, 'bnorm': True, 'leaky': True, 'layer_idx': 13},  
                  {'filter': 256, 'kernel': 3, 'stride': 1, 'bnorm': True, 'leaky': True, 'layer_idx': 14}])
```

```
# Layers 16 to 36
```

```
for i in range(7):
```

```
    x = conv_block(x, [{'filter': 128, 'kernel': 1, 'stride': 1, 'bnorm': True, 'leaky': True, 'layer_idx':  
16+i*3},  
                      {'filter': 256, 'kernel': 3, 'stride': 1, 'bnorm': True, 'leaky': True, 'layer_idx': 17+i*3}])
```

```
skip_36 = x
```

```
# Layers 37 to 40
```

```
x = conv_block(x, [{'filter': 512, 'kernel': 3, 'stride': 2, 'bnorm': True, 'leaky': True, 'layer_idx': 37},  
                  {'filter': 256, 'kernel': 1, 'stride': 1, 'bnorm': True, 'leaky': True, 'layer_idx': 38},  
                  {'filter': 512, 'kernel': 3, 'stride': 1, 'bnorm': True, 'leaky': True, 'layer_idx': 39}])
```

```
# Layers 41 to 61
```

```
for i in range(7):
```

```
    x = conv_block(x, [{'filter': 256, 'kernel': 1, 'stride': 1, 'bnorm': True, 'leaky': True, 'layer_idx':  
41+i*3},  
                      {'filter': 512, 'kernel': 3, 'stride': 1, 'bnorm': True, 'leaky': True, 'layer_idx': 42+i*3}])
```

```
skip_61 = x
```

```
# Layers 62 to 65
```

```
x = conv_block(x, [{'filter': 1024, 'kernel': 3, 'stride': 2, 'bnorm': True, 'leaky': True, 'layer_idx': 62},  
                  {'filter': 512, 'kernel': 1, 'stride': 1, 'bnorm': True, 'leaky': True, 'layer_idx': 63},  
                  {'filter': 1024, 'kernel': 3, 'stride': 1, 'bnorm': True, 'leaky': True, 'layer_idx': 64}])
```

```
# Layers 66 to 74
```

```
for i in range(3):
```



```

x = conv_block(x, [{'filter': 512, 'kernel': 1, 'stride': 1, 'bnorm': True, 'leaky': True, 'layer_idx':
66+i*3},
{'filter': 1024, 'kernel': 3, 'stride': 1, 'bnorm': True, 'leaky': True, 'layer_idx':
67+i*3}])

```

Layers 75 to 79

```

x = conv_block(x, [{'filter': 512, 'kernel': 1, 'stride': 1, 'bnorm': True, 'leaky': True, 'layer_idx': 75},
{'filter': 1024, 'kernel': 3, 'stride': 1, 'bnorm': True, 'leaky': True, 'layer_idx': 76},
{'filter': 512, 'kernel': 1, 'stride': 1, 'bnorm': True, 'leaky': True, 'layer_idx': 77},
{'filter': 1024, 'kernel': 3, 'stride': 1, 'bnorm': True, 'leaky': True, 'layer_idx': 78},
{'filter': 512, 'kernel': 1, 'stride': 1, 'bnorm': True, 'leaky': True, 'layer_idx': 79}],
skip=False)

```

Layers 80 to 82

```

yolo_82 = conv_block(x, [{'filter': 1024, 'kernel': 3, 'stride': 1, 'bnorm': True, 'leaky': True,
'layer_idx': 80},
{'filter': 255, 'kernel': 1, 'stride': 1, 'bnorm': False, 'leaky': False, 'layer_idx': 81}],
skip=False)

```

Layers 83 to 86

```

x = conv_block(x, [{'filter': 256, 'kernel': 1, 'stride': 1, 'bnorm': True, 'leaky': True, 'layer_idx': 84}],
skip=False)
x = UpSampling2D(2)(x)
x = concatenate([x, skip_61])

```

Layers 87 to 91

```

x = conv_block(x, [{'filter': 256, 'kernel': 1, 'stride': 1, 'bnorm': True, 'leaky': True, 'layer_idx': 87},
{'filter': 512, 'kernel': 3, 'stride': 1, 'bnorm': True, 'leaky': True, 'layer_idx': 88},
{'filter': 256, 'kernel': 1, 'stride': 1, 'bnorm': True, 'leaky': True, 'layer_idx': 89},
{'filter': 512, 'kernel': 3, 'stride': 1, 'bnorm': True, 'leaky': True, 'layer_idx': 90},
{'filter': 256, 'kernel': 1, 'stride': 1, 'bnorm': True, 'leaky': True, 'layer_idx': 91}],
skip=False)

```

Layers 92 to 94

```

yolo_94 = conv_block(x, [{'filter': 512, 'kernel': 3, 'stride': 1, 'bnorm': True, 'leaky': True,
'layer_idx': 92},
{'filter': 255, 'kernel': 1, 'stride': 1, 'bnorm': False,
'leaky': False, 'layer_idx': 93}], skip=False)

```

```

# Layers 95 to 98

```

```

x = conv_block(x, [{'filter': 128, 'kernel': 1, 'stride': 1, 'bnorm': True, 'leaky': True, 'layer_idx':
96}], skip=False)

```

```

x = UpSampling2D(2)(x)

```

```

x = concatenate([x, skip_36])

```

```

# Layers 99 to 106

```

```

yolo_106 = conv_block(x, [{'filter': 128, 'kernel': 1, 'stride': 1, 'bnorm': True, 'leaky': True,
'layer_idx': 99},
{'filter': 256, 'kernel': 3, 'stride': 1, 'bnorm': True, 'leaky': True, 'layer_idx': 100},
{'filter': 128, 'kernel': 1, 'stride': 1, 'bnorm': True, 'leaky': True, 'layer_idx': 101},
{'filter': 256, 'kernel': 3, 'stride': 1, 'bnorm': True, 'leaky': True, 'layer_idx': 102},
{'filter': 128, 'kernel': 1, 'stride': 1, 'bnorm': True, 'leaky': True, 'layer_idx': 103},
{'filter': 256, 'kernel': 3, 'stride': 1, 'bnorm': True, 'leaky': True, 'layer_idx': 104},
{'filter': 255, 'kernel': 1, 'stride': 1, 'bnorm': False, 'leaky': False, 'layer_idx': 105}],
skip=False)

```

```

model = Model(input_image, [yolo_82, yolo_94, yolo_106])

```

```

return model

```

```

# define the yolo v3 model

```

```

yolov3 = make_yolov3_model()

```

```

# load the weights

```

```

weight_reader = Read_Weights("../input/data-for-yolo-v3-kernel/yolov3.weights")

```

```

# set the weights

```

```

weight_reader.load_weights(yolov3)

```

```
# save the model to file
yolov3.save('yolo_model.h5')

def load_image_pixels(filename, shape):

    # load image to get its shape
    image = load_img(filename)
    width, height = image.size

    # load image with required size
    image = load_img(filename, target_size = shape)
    image = img_to_array(image)

    # grayscale image normalization
    image = image.astype('float32')
    image /= 255.0

    # add a dimension so that we have one sample
    image = np.expand_dims(image, 0)
    return image, width, height

class BoundBox:

    def __init__(self, xmin, ymin, xmax, ymax, objness = None, classes = None):
        self.xmin = xmin
        self.ymin = ymin
        self.xmax = xmax
        self.ymax = ymax
        self.objness = objness
        self.classes = classes
        self.label = -1
        self.score = -1
```

```
def get_label(self):  
    if self.label == -1:  
        self.label = np.argmax(self.classes)  
  
    return self.label
```

```
def get_score(self):  
    if self.score == -1:  
        self.score = self.classes[self.get_label()]  
    return self.get_score
```

```
def _sigmoid(x):  
    return 1. / (1. + np.exp(-x))
```

```
def decode_netout(netout, anchors, obj_thresh, net_h, net_w):
```

```
    grid_h, grid_w = netout.shape[:2]  
    nb_box = 3  
    netout = netout.reshape((grid_h, grid_w, nb_box, -1))  
    nb_class = netout.shape[-1] - 5  
    boxes = []  
    netout[..., :2] = _sigmoid(netout[..., :2])  
    netout[..., 4:] = _sigmoid(netout[..., 4:])  
    netout[..., 5:] = netout[..., 4][..., np.newaxis] * netout[..., 5:]  
    netout[..., 5:] *= netout[..., 5:] > obj_thresh
```

```
    for i in range(grid_h*grid_w):  
        row = i / grid_w  
        col = i % grid_w  
        for b in range(nb_box):
```

```

# 4th element is objectness score
objectness = netout[int(row)][int(col)][b][4]
if(objectness.all() <= obj_thresh): continue

# first 4 elements are x, y, w, and h
x, y, w, h = netout[int(row)][int(col)][b][:4]
x = (col + x) / grid_w # center position, unit: image width
y = (row + y) / grid_h # center position, unit: image height
w = anchors[2 * b + 0] * np.exp(w) / net_w # unit: image width
h = anchors[2 * b + 1] * np.exp(h) / net_h # unit: image height

# last elements are class probabilities
classes = netout[int(row)][col][b][5:]
box = BoundBox(x-w/2, y-h/2, x+w/2, y+h/2, objectness, classes)
boxes.append(box)

return boxes

def correct_yolo_boxes(boxes, image_h, image_w, net_h, net_w):

    new_w, new_h = net_w, net_h
    for i in range(len(boxes)):

        x_offset, x_scale = (net_w - new_w)/2./net_w, float(new_w)/net_w
        y_offset, y_scale = (net_h - new_h)/2./net_h, float(new_h)/net_h

        boxes[i].xmin = int((boxes[i].xmin - x_offset) / x_scale * image_w)
        boxes[i].xmax = int((boxes[i].xmax - x_offset) / x_scale * image_w)
        boxes[i].ymin = int((boxes[i].ymin - y_offset) / y_scale * image_h)
        boxes[i].ymax = int((boxes[i].ymax - y_offset) / y_scale * image_h)

def interval_overlap(interval_a, interval_b):

```

```
x1, x2 = interval_a
```

```
x3, x4 = interval_b
```

```
if x3 < x1:
```

```
    if x4 < x1:
```

```
        return 0
```

```
    else:
```

```
        return min(x2,x4) - x1
```

```
else:
```

```
    if x2 < x3:
```

```
        return 0
```

```
    else:
```

```
        return min(x2,x4) - x3
```

```
def bbox_iou(box1, box2):
```

```
    intersect_w = interval_overlap([box1.xmin, box1.xmax], [box2.xmin, box2.xmax])
```

```
    intersect_h = interval_overlap([box1.ymin, box1.ymax], [box2.ymin, box2.ymax])
```

```
    intersect = intersect_w * intersect_h
```

```
    w1, h1 = box1.xmax-box1.xmin, box1.ymax-box1.ymin
```

```
    w2, h2 = box2.xmax-box2.xmin, box2.ymax-box2.ymin
```

```
    union = w1*h1 + w2*h2 - intersect
```

```
    return float(intersect) / union
```

```
def nms(boxes, nms_thresh):
```

```
    if len(boxes) > 0:
```

```
        nb_class = len(boxes[0].classes)
```

```
    else:
```

```
        return
```

```
for c in range(nb_class):
    sorted_indices = np.argsort([-box.classes[c] for box in boxes])

    for i in range(len(sorted_indices)):
        index_i = sorted_indices[i]

        if boxes[index_i].classes[c] == 0: continue

        for j in range(i+1, len(sorted_indices)):
            index_j = sorted_indices[j]

            if bbox_iou(boxes[index_i], boxes[index_j]) >= nms_thresh:
                boxes[index_j].classes[c] = 0

# get all of the results above a threshold
def get_boxes(boxes, labels, thresh):

    v_boxes, v_labels, v_scores = list(), list(), list()
    # enumerate all boxes
    for box in boxes:
        # enumerate all possible labels
        for i in range(len(labels)):
            # check if the threshold for this label is high enough
            if box.classes[i] > thresh:
                v_boxes.append(box)
                v_labels.append(labels[i])
                v_scores.append(box.classes[i]*100)
            # don't break, many labels may trigger for one box

    return v_boxes, v_labels, v_scores

# draw all results
```

```
import numpy as np

def draw_boxes(filename, v_boxes, v_labels, v_scores):
    data = plt.imread(filename)
    print(f"Image Shape: {data.shape}") # Debugging image shape

    # Convert grayscale to RGB if necessary
    if len(data.shape) == 2: # Grayscale image
        data = np.stack([data] * 3, axis=-1)

    plt.imshow(data)
    ax = plt.gca()

    # Plot each box
    for i in range(len(v_boxes)):
        box = v_boxes[i]

        # Get coordinates and ensure they are floats
        y1, x1, y2, x2 = float(box.ymin), float(box.xmin), float(box.ymax), float(box.xmax)
        width, height = x2 - x1, y2 - y1

        # Debugging: Check types and box values
        print(f"Box: {box}, x1: {x1}, y1: {y1}, width: {width}, height: {height}")
        print(f"Label: {v_labels[i]}, Score: {v_scores[i]}, Type of Score: {type(v_scores[i])}")
        print(f"x1: {x1}, y1: {y1}, Type of x1: {type(x1)}, Type of y1: {type(y1)}")

        # Create the shape
        rect = plt.Rectangle((x1, y1), width, height, fill=False, color='red', linewidth=2)

        # Draw the box
        ax.add_patch(rect)
```



```
# Format the label
label = f'{v_labels[i]} ({v_scores[i]:.3f})' # Ensure label and score are formatted correctly

# Draw text and score in the top left corner
plt.text(x1, y1, label, color='b', fontsize=12, family='serif', fontweight='bold')

# Show the plot
plt.show()

# define the anchors
anchors = [[116,90, 156,198, 373,326], [30,61, 62,45, 59,119], [10,13, 16,30, 33,23]]

# define the probability threshold for detected objects
class_threshold = 0.6

# define the labels
labels = ["person", "bicycle", "car", "motorbike", "aeroplane", "bus", "train", "truck",
          "boat", "traffic light", "fire hydrant", "stop sign", "parking meter", "bench",
          "bird", "cat", "dog", "horse", "sheep", "cow", "elephant", "bear", "zebra", "giraffe",
          "backpack", "umbrella", "handbag", "tie", "suitcase", "frisbee", "skis", "snowboard",
          "sports ball", "kite", "baseball bat", "baseball glove", "skateboard", "surfboard",
          "tennis racket", "bottle", "wine glass", "cup", "fork", "knife", "spoon", "bowl", "banana",
          "apple", "sandwich", "orange", "broccoli", "carrot", "hot dog", "pizza", "donut", "cake",
          "chair", "sofa", "pottedplant", "bed", "diningtable", "toilet", "tvmonitor", "laptop", "mouse",
          "remote", "keyboard", "cell phone", "microwave", "oven", "toaster", "sink", "refrigerator",
          "book", "clock", "vase", "scissors", "teddy bear", "hair drier", "toothbrush"]

ls, v_scores)

image_names = ["../input/data-for-yolo-v3-kernel/dog.jpg",
               "../input/data-for-yolo-v3-kernel/office.jpg"]

predict_boxes(image_names)
```

Thus an object detection model with YOLO3 using Keras/TensorFlow is built.

