

MyDeliveryPresentation Module

Presentation/UI layer (likely Spring MVC + JSP/Tiles + DWR) responsible for web user interface, view resolution, decorators, servlets for printing, conversion, and client-side validation endpoints.

Packages

- `com.spring.tiles.configurer` : Custom Tiles view resolver & configurer extensions.
- `com.spring.dwr.configurer` : DWR servlet configuration integration.
- `com.tnt.express.warp.mydelivery.ui.servlet` : Legacy servlets handling printing & setup tasks.
- `com.tnt.express.warp.mydelivery.ui.remote` : DWR-exposed remote validation & address lookup.
- `com.tnt.express.warp.mydelivery.ui.validators` : UI-level validator (form bean checks before service call).
- `com.tnt.express.warp.mydelivery.ui.decorator` : Screen flow decorators controlling navigation / rendering.
- `com.tnt.express.warp.mydelivery.ui.conversion` : Type converters (date parsing/formatting) and conversion service.
- `com.tnt.express.warp.mydelivery.ui.filter` : Servlet filter(s) applying cross-cutting web concerns.
- `com.tnt.express.warp.mydelivery.address.enquiry.api` : Address search API (probably an internal adaptor for front-end autocomplete).
- `com.tnt.express.warp.mydelivery.util` : UI-specific utilities (URL construction, etc.).

View / Tiles Infrastructure

- `ExtUrlBasedViewResolver` : Extends Spring's resolver to support Tiles + maybe custom fallback logic.
- `SpringTilesConfigurer` : Configures Tiles definitions and refresh settings.
- `ExtTilesView` : Customized Tiles view enabling additional model exposure (maybe locale or dynamic definitions).

UI Utilities

- `UrlUtil` : Helper for constructing application URLs or rewriting paths (handles locale, context path).

Validators

- `DefaultRedeliveryRequestBeanValidator` : UI-level validation for `RedeliveryRequestBean` prior to server submission (lengths, required fields, phone, email).

Remote / DWR

- `DwrPhoneValidation` : Exposes phone validation result via AJAX without full form submission.
- `GlobalAddress` : Provides address lookup / standardization remote calls.
- `GlobalAddressResults` : DTO encapsulating address search response states.

Servlets

- `SetupAppServlet` : Initialization (loading caches, config, warm-ups) on application startup.
- `PrintMyDeliveryPTLFormServlet` : Streams PTL form PDF to browser using `ReportPrinter` .
- `PrintMyDeliveryConfirmationDetailsServlet` : Streams confirmation details PDF.
- `AbstractPrintServlet` : Base providing common printing logic (parameter extraction, response headers, error handling).
- `ResourceServletException` : Exception wrapper for resource streaming errors.

Decorators (Navigation / Flow)

Each decorator corresponds to a UI step or option, setting up model attributes, deciding next/previous steps, and applying availability rules.

- `AlternativeAddressDecorator`
- `AvailableOptionsDecorator`
- `ConfirmationDecorator`
- `EnterContactDetailsDecorator`
- `InitDecorator`
- `LeaveInAbsenceDecorator`
- `LeaveWithNeighbourDecorator`
- `MyDeliveryDecorator` : Central orchestrator or base for decorators.
- `OriginalAddressDecorator`
- `RedeliveryOptionsDecorator`
- `SelfCollectionDecorator`

Converters

- `DateConverter` : Parses and formats dates for UI forms (supports multiple patterns & locale-specific formatting).
- `CustomConversionService` : Registers converters (date, enums) for Spring binding.

Filters

- `MyDeliveryFilter` : Applies pre/post-processing (e.g., character encoding, locale injection, security checks) across requests.

Address Enquiry API

- `AddressDTO` : Data Transfer Object for address search results.
- `AddressRepositoryException` : Thrown when address search backend fails.
- `AddressSearchCompletionState` : Enum reflecting completion / partial match status.
- `AddressSearchCriteria` : Inputs for address search (query text, country, limit).
- `AddressSearchResult` : Collection of `AddressDTO` with metadata like total matches.

Interaction Flow

1. User enters consignment id; `InitDecorator` prepares initial view.
2. System determines available options; `AvailableOptionsDecorator` prepares list.
3. User chooses option; relevant decorator (e.g., `AlternativeAddressDecorator`) sets form state.
4. `EnterContactDetailsDecorator` collects contact & scheduling info.
5. `ConfirmationDecorator` shows summary; print servlets optionally generate PDFs.
6. Global address & phone DWR services enhance UX via AJAX.

Extension Points

- New UI step: create decorator implementing shared base interface & add to navigation chain.
- Add converter: register within `CustomConversionService`.
- New remote validation: expose DWR bean & configure in DWR servlet config.