

CS621/CSL611

Quantum Computing For Computer Scientists

Quantum Search

Dhiman Saha

Winter 2024

IIT Bhilai



Quantum Search

General Treatment ($H^{\otimes n}$) $|x\rangle$

- Recall H -transform of basis states:

$$H|0\rangle = \frac{|0\rangle + |1\rangle}{\sqrt{2}} \quad H|1\rangle = \frac{|0\rangle - |1\rangle}{\sqrt{2}}$$

- Recall H -transform of basis states:

$$H|0\rangle = \frac{|0\rangle + |1\rangle}{\sqrt{2}} \quad H|1\rangle = \frac{|0\rangle - |1\rangle}{\sqrt{2}}$$

- Can be generalized as as:

$$H|a\rangle = \frac{1}{\sqrt{2}}|0\rangle + \frac{1}{\sqrt{2}}(-1)^a|1\rangle$$

- Recall H -transform of basis states:

$$H|0\rangle = \frac{|0\rangle + |1\rangle}{\sqrt{2}} \quad H|1\rangle = \frac{|0\rangle - |1\rangle}{\sqrt{2}}$$

- Can be generalized as as:

$$H|a\rangle = \frac{1}{\sqrt{2}}|0\rangle + \frac{1}{\sqrt{2}}(-1)^a|1\rangle$$

- Further generalization

$$H|a\rangle = \frac{1}{\sqrt{2}} \sum_{b \in \{0,1\}} (-1)^{ab} |b\rangle$$

- Extending to **two** qubits ($H^{\otimes 2}$)

- Extending to **two** qubits ($H^{\otimes 2}$)
- Lets starting state be $|x\rangle$ where, $x = x_1x_2 \in \{0,1\}^2$

- Extending to **two** qubits ($H^{\otimes 2}$)
- Lets starting state be $|x\rangle$ where, $x = x_1x_2 \in \{0,1\}^2$
- After H —transform on both qubits:

- Extending to **two** qubits ($H^{\otimes 2}$)
- Lets starting state be $|x\rangle$ where, $x = x_1x_2 \in \{0,1\}^2$
- After H —transform on both qubits:

$$(H \otimes H) |x\rangle =$$

- Extending to **two** qubits ($H^{\otimes 2}$)
- Lets starting state be $|x\rangle$ where, $x = x_1 x_2 \in \{0, 1\}^2$
- After H —transform on both qubits:

$$(H \otimes H) |x\rangle = \left(\frac{1}{\sqrt{2}} \sum_{y_1 \in \{0,1\}} (-1)^{x_1 y_1} |y_1\rangle \right) |H|x_1\rangle$$

- Extending to **two** qubits ($H^{\otimes 2}$)
- Lets starting state be $|x\rangle$ where, $x = x_1x_2 \in \{0,1\}^2$
- After H —transform on both qubits:

$$(H \otimes H) |x\rangle = \left(\frac{1}{\sqrt{2}} \sum_{y_1 \in \{0,1\}} (-1)^{x_1 y_1} |y_1\rangle \right) \otimes \left(\frac{1}{\sqrt{2}} \sum_{y_2 \in \{0,1\}} (-1)^{x_2 y_2} |y_2\rangle \right)$$

$|H|x_1\rangle$
 $|H|x_2\rangle$

- Extending to **two** qubits ($H^{\otimes 2}$)
- Lets starting state be $|x\rangle$ where, $x = x_1x_2 \in \{0,1\}^2$
- After H -transform on both qubits:

$$\begin{aligned}
 (H \otimes H) |x\rangle &= \left(\frac{1}{\sqrt{2}} \sum_{y_1 \in \{0,1\}} (-1)^{x_1 y_1} |y_1\rangle \right) \otimes \left(\frac{1}{\sqrt{2}} \sum_{y_2 \in \{0,1\}} (-1)^{x_2 y_2} |y_2\rangle \right) \\
 &= \frac{1}{\sqrt{2^2}} \sum_{y \in \{0,1\}^2} (-1)^{x_1 y_1 + x_2 y_2} |y\rangle
 \end{aligned}$$

$|H|x_1\rangle$
 $|H|x_2\rangle$

- Generalizing for n qubits ($H^{\otimes n}$) for every $x \in \{0, 1\}^n$

$$H^{\otimes n} |x\rangle = \frac{1}{\sqrt{2^n}} \sum_{y \in \{0,1\}^n} (-1)^{x_1 y_1 + \dots + x_n y_n} |y\rangle$$

- Generalizing for n qubits ($H^{\otimes n}$) for every $x \in \{0, 1\}^n$

$$H^{\otimes n} |x\rangle = \frac{1}{\sqrt{2^n}} \sum_{y \in \{0,1\}^n} (-1)^{x_1 y_1 + \dots + x_n y_n} |y\rangle$$

- Expressing the dot product $x_1 y_1 + \dots + x_n y_n$ as:

$$x \cdot y = \sum_{i=1}^n x_i y_i \bmod 2$$

- Generalizing for n qubits ($H^{\otimes n}$) for every $x \in \{0, 1\}^n$

$$H^{\otimes n} |x\rangle = \frac{1}{\sqrt{2^n}} \sum_{y \in \{0,1\}^n} (-1)^{x_1 y_1 + \dots + x_n y_n} |y\rangle$$

- Expressing the dot product $x_1 y_1 + \dots + x_n y_n$ as:

$$x \cdot y = \sum_{i=1}^n x_i y_i \bmod 2$$

- Rewriting $H^{\otimes n} |x\rangle$

$$H^{\otimes n} |x\rangle = \frac{1}{\sqrt{2^n}} \sum_{y \in \{0,1\}^n} (-1)^{x \cdot y} |y\rangle$$

- State the expression for $H^{\otimes n} |0\rangle$

1. Quantum Computing for Computer Scientists, by Noson S. Yanofsky, Mirco A. Mannucci
2. Quantum Computing Explained, David McMahon. John Wiley & Sons
3. Lecture Notes on Quantum Computation, John Watrous, University of Calgary
 - <https://cs.uwaterloo.ca/~watrous/QC-notes/>