Application Layer



Anand Baswade anand@iitbhilai.ac.in

DNS: services, structure

DNS services

- hostname to IP address translation
- load distribution
 - replicated Web servers: many IP addresses correspond to one name


Q: Why not centralize DNS?

- single point of failure
- traffic volume
- distant centralized database
- maintenance

A: doesn't scale!

Comcast DNS servers alone: 600B DNS queries per day

DNS: a distributed, hierarchical database




Client wants IP address for www.amazon.com; 1st approximation:

- client queries root server to find .com DNS server
- client queries .com DNS server to get amazon.com DNS server
- client queries amazon.com DNS server to get IP address for www.amazon.com

DNS: root name servers

- official, contact-of-last-resort by name servers that can not resolve name
- incredibly important Internet function
 - Internet couldn't function without it!
 - DNSSEC provides security (authentication and message integrity)
- ICANN (Internet Corporation for Assigned Names and Numbers) manages root DNS domain

13 logical root name "servers" worldwide each "server" replicated many times (~200 servers in US)



TLD: authoritative servers

Top-Level Domain (TLD) servers:

- Generic top-level domains (gTLD): .com, .org, .net, .edu, .aero, .jobs, .net, .edu
- Country-code top-level domains (ccTLD): all country domains, e.g.: .in .cn,
 .uk, .fr, .ca, .jp

Authoritative DNS servers:

- organization's own DNS server(s), providing authoritative hostname to IP mappings for organization's named hosts
- can be maintained by organization or service provider

Local DNS name servers


- does not strictly belong to hierarchy
- each ISP (residential ISP, company, university) has one
 - also called "default name server"
- when host makes DNS query, query is sent to its local DNS server
 - has local cache of recent name-to-address translation pairs (but may be out of date!)
 - acts as proxy, forwards query into hierarchy
 - The local DNS servers are statically configured with the identity of the root servers.

DNS name resolution: iterated query

Example: host at engineering.nyu.edu wants IP address for gaia.cs.umass.edu

Iterated query:

- contacted server replies with name of server to contact
- "I don't know this name, but ask this server"




dns.cs.umass.edu

DNS name resolution: recursive query

Example: host at engineering.nyu.edu wants IP address for gaia.cs.umass.edu

Recursive query:

- puts burden of name resolution on contacted name server
- heavy load at upper levels of hierarchy?



Caching, Updating DNS Records

- once (any) name server learns mapping, it caches mapping
 - cache entries timeout (disappear) after some time (TTL)
 - TLD servers typically cached in local name servers
 - thus root name servers not often visited
- cached entries may be out-of-date (best-effort name-to-address translation!)
 - if name host changes IP address, may not be known Internet-wide until all TTLs expire!
- update/notify mechanisms proposed IETF standard
 - RFC 2136

DNS records

DNS: distributed database storing resource records (RR)

RR format: (name, value, type, ttl)

type=A

- name is hostname
- value is IP address

type=NS

- name is domain (e.g., foo.com)
- value is hostname of authoritative name server for this domain

type=CNAME

- name is alias name for some "canonical" (the real) name
- www.ibm.com is really servereast.backup2.ibm.com
- value is canonical name

type=MX


value is name of mailserver associated with name

DNS protocol messages

DNS query and reply messages, both have same format:


message header:

- identification: 16 bit # for query, reply to query uses same #
- flags:
 - query or reply
 - recursion desired
 - recursion available
 - reply is authoritative



DNS protocol messages

DNS query and reply messages, both have same format:



Inserting records into DNS

Example: new startup "Network Utopia"

- register name networkuptopia.com at DNS registrar (e.g., Network Solutions)
 - provide names, IP addresses of authoritative name server (primary and secondary)
 - registrar inserts NS, A RRs into .com TLD server:

```
(networkutopia.com, dns1.networkutopia.com, NS)
(dns1.networkutopia.com, 212.212.212.1, A)
```

- create authoritative server locally with IP address 212.212.212.1
 - type A record for www.networkuptopia.com
 - type MX record for networkutopia.com

DNS security

DDoS attacks

- bombard root servers with traffic
 - not successful to date
 - traffic filtering
 - local DNS servers cache IPs of TLD servers, allowing root server bypass
- bombard TLD servers
 - potentially more dangerous

Redirect attacks

- man-in-middle
 - intercept DNS queries
- DNS poisoning
 - send bogus relies to DNS server, which caches

Exploit DNS for DDoS

- send queries with spoofed source address: target IP
- requires amplification

DNSSEC [RFC 4033]

Additional Info

- Indian (.in) Registry:
 - https://www.registry.in/
- ICANN
 - https://www.incann.org/

nslookup

Local DNS server >lpconfig -all

Local DNS server >nslookup

```
C:\Users\Anand Madhavrao>nslookup
Default Server: UnKnown
Address: 192.168.10.87
```

- Local DNS server >nslookup <u>www.iitbhilai.ac.in</u>
 - To get IP address of www. litbhilai.ac.in web server.

Application layer: overview

- Principles of network applications
- Web and HTTP
- The Domain Name System DNS
- E-mail, SMTP, IMAP

- P2P applications
- video streaming and content distribution networks
- socket programming with UDP and TCP




E-mail

Three major components:

- user agents
- mail servers
- simple mail transfer protocol: SMTP

User Agent


- a.k.a. "mail reader"
- composing, editing, reading mail messages
- e.g., Outlook, iPhone mail client
- outgoing, incoming messages stored on server



E-mail: mail servers

mail servers:

- mailbox contains incoming messages for user
- message queue of outgoing (to be sent) mail messages
- SMTP protocol between mail servers to send email messages
 - client: sending mail server
 - "server": receiving mail server




E-mail: the RFC (5321)

- uses TCP to reliably transfer email message from client (mail server initiating connection) to server, port 25
- direct transfer: sending server (acting like client) to receiving server
- three phases of transfer
 - handshaking (greeting)
 - transfer of messages
 - closure
- command/response interaction (like HTTP)
 - commands: ASCII text
 - response: status code and phrase
- messages must be in 7-bit ASCI


Scenario: Alice sends e-mail to Bob

- 1) Alice uses UA to compose e-mail message "to" bob@someschool.edu
- 2) Alice's UA sends message to her mail server; message placed in message queue
- 3) client side of SMTP opens TCP connection with Bob's mail server

- 4) SMTP client sends Alice's message over the TCP connection
- 5) Bob's mail server places the message in Bob's mailbox
- 6) Bob invokes his user agent to read message



Sample SMTP interaction



MAIL FROM:<joe@someplace.org> 250 < joe@someplace.org>... Sender ok RCPT TO:<jane@somewhereelse.com> 250 <jane@somewhereelse.com>... Recipient ok DATA 354 Enter mail, end with "." on a line by itself From: Joe Sender < joe@someplace.org> To: Jane Receiver < jane@somewhereelse.com> Date: Sun, 1 Jun 2003 14:17:31 -0800 Subject: Lunch tomorrow Hey Jane, It's my turn for lunch tomorrow. I was thinking we could [rest of message] Hope you are free. Send me a reply back when you get a chance. Joe. 250 OK

SMTP: closing observations

comparison with HTTP:


- HTTP: pull
- SMTP: push
- both have ASCII command/response interaction, status codes
- HTTP: each object encapsulated in its own response message
- SMTP: multiple objects sent in multipart message

- SMTP uses persistent connections
- SMTP requires message (header & body) to be in 7-bit ASCII
- SMTP server uses
 CRLF.CRLF to determine
 end of message


Mail message format

SMTP: protocol for exchanging e-mail messages, defined in RFC 531 (like HTTP)

RFC 822 defines *syntax* for e-mail message itself (like HTML)



Mail access protocols



- SMTP: delivery/storage of e-mail messages to receiver's server
- mail access protocol: retrieval from server
 - IMAP: Internet Mail Access Protocol [RFC 3501]: messages stored on server, IMAP provides retrieval, deletion, folders of stored messages on server
- HTTP: gmail, Hotmail, Yahoo!Mail, etc. provides web-based interface on top of SMTP (to send), IMAP (or POP) to retrieve e-mail messages

Application layer: overview


- Principles of network applications
- Web and HTTP
- E-mail, SMTP, IMAP
- The Domain Name System DNS

- P2P applications
- video streaming and content distribution networks
- socket programming with UDP and TCP




Peer-to-peer (P2P) architecture

- no always-on server
- arbitrary end systems directly communicate
- peers request service from other peers, provide service in return to other peers
 - self scalability new peers bring new service capacity, and new service demands
- peers are intermittently connected and change IP addresses
 - complex management
- examples: P2P file sharing (BitTorrent), streaming (KanKan), VoIP (Skype)




File distribution: client-server vs P2P

- Q: how much time to distribute file (size F) from one server to N peers?
 - peer upload/download capacity is limited resource



File distribution time: client-server

- server transmission: must sequentially send (upload) N file copies:
 - time to send one copy: F/u_s
 - time to send N copies: NF/u_s
- client: each client must download file copy
 - d_{min} = min client download rate
 - min client download time: F/d_{min}



time to distribute F to N clients using client-server approach

$$D_{c-s} \ge max\{ \frac{NF/u_{s,}F/d_{min}}{} \}$$

File distribution time: P2P

- server transmission: must upload at least one copy:
 - time to send one copy: F/u_s
- client: each client must download file copy
 - min client download time: F/d_{min}




• max upload rate (limiting max download rate) is $u_s + \Sigma u_i$

time to distribute F to N clients using P2P approach

$$D_{P2P} \geq \max\{F/u_{s,}, F/d_{min,}, \frac{NF/(u_s + \sum u_i)}{N}\}$$

increases linearly in N ...
... but so does this, as each peer brings service capacity



Client-server vs. P2P: example

client upload rate = u, F/u = 1 hour, $u_s = 10u$, $d_{min} \ge u_s$

