
Wireless access networks

Shared wireless access network connects end system to router

via base station aka "access point"


Wireless local area networks (WLANs)

- typically within or around building (~100 ft)
- 802.11b/g/n (WiFi): 11, 54, 450Mbps transmission rate




Wide-area cellular access networks

- provided by mobile, cellular network operator (10's km)
- 10's Mbps
- 4G/5G cellular networks



Access networks: enterprise networks




- companies, universities, etc.
- mix of wired, wireless link technologies, connecting a mix of switches and routers (we'll cover differences shortly)
 - Ethernet: wired access at 100Mbps, 1Gbps, 10Gbps
 - WiFi: wireless access points at 11, 54, 450 Mbps

Links: physical media

- bit: propagates between transmitter/receiver pairs
- physical link: what lies between transmitter & receiver
- guided media:
 - signals propagate in solid media: copper, fiber, coax
- unguided media:
 - signals propagate freely, e.g., radio

Twisted pair (TP)

- two insulated copper wires
 - Category 5: 100 Mbps,
 - Category 5e: 1 Gbps Ethernet
 - Category 6: 10Gbps Ethernet





Links: physical media

Coaxial cable:

- Copper conductor
- broadband:
 - multiple frequency channels on cable
 - 100's Mbps per channel



Fiber optic cable:

- glass fiber carrying light pulses, each pulse a bit
- high-speed operation:
 - high-speed point-to-point transmission (10's-100's Gbps)
- low error rate:
 - repeaters spaced far apart
 - immune to electromagnetic noise



Links: physical media


Wireless radio

- signal carried in electromagnetic spectrum
- no physical "wire"
- broadcast and "half-duplex" (sender to receiver)
- propagation environment effects:
 - reflection
 - obstruction by objects
 - interference

Radio link types:


- Wireless LAN (WiFi)
 - Up to 100's Mbps
- wide-area (e.g., cellular)
 - 4G cellular: ~ 10's Mbps
- satellite
 - up to 45 Mbps per channel
 - 270 msec end-end delay
 - geosynchronous versus lowearth-orbit

Network Interface Card (NIC) inside computer






NIC and connector




NIC Cont..




Crimping LAN/Ethernet cables



Cable/Network Crimping tool









- Hosts connect to Internet via access Internet Service Providers (ISPs)
 - residential, enterprise (company, university, commercial) ISPs
- Access ISPs in turn must be interconnected
 - so that any two hosts can send packets to each other
- Resulting network of networks is very complex
- Let's take a stepwise approach to describe current Internet structure

Question: given millions of access ISPs, how to connect them together?




Question: given millions of access ISPs, how to connect them together?




Option: connect each access ISP to one global transit ISP?


Customer and provider ISPs have economic agreement.




But if one global ISP is viable business, there will be competitors




But if one global ISP is viable business, there will be competitors who will want to be connected




... and regional networks may arise to connect access nets to ISPs



... and content provider networks (e.g., Google, Microsoft, Akamai) may run their own network, to bring services, content close to end users





At "center": small # of well-connected large networks

- "tier-1" commercial ISPs (e.g., Level 3, Sprint, AT&T, NTT), national & international coverage
- content provider networks (e.g., Google, Facebook): private network that connects its data centers to Internet, often bypassing tier-1, regional ISPs