

Lecture – Sequence analysis

Global Alignment and Local Alignment

Dot Matrix Method

Sequence analysis


Global Alignment and Local Alignment

Alignment algorithms

Sequence alignment Dot Matrix Method ↓

- The **most basic sequence alignment method** is the dot matrix method, also known as the **dot plot** method.
- It is a **graphical way** of comparing two sequences in a two-dimensional matrix.
- In a dot matrix, **two sequences** to be compared are written in the **horizontal and vertical axes** of the matrix.
- The comparison is done by **scanning each residue of one sequence for similarity with all residues in the other sequence**.
- If a residue **match is found**, a **dot is placed** within the graph.
- **Otherwise**, the matrix positions are **left blank**.
- When the **two sequences have substantial regions of similarity, many dots line up to form contiguous diagonal lines, which reveal the sequence alignment**.
- If there are **interruptions** in the middle of a diagonal line, they **indicate insertions or deletions**.

Dot Matrix



- **Parallel** diagonal lines within the matrix represent **repetitive regions** of the sequences.


Sequence analysis

Global Alignment and Local Alignment

Alignment algorithms

Sequence alignment

Dot Matrix Method ↓



- ✓ Lines linking the dots in diagonals indicate sequence alignment.
- ✓ Diagonal lines above or below the main diagonal represent **internal repeats** of either sequence.

Sequence analysis

Global Alignment and Local Alignment

Alignment algorithms

Sequence alignment

Dot Matrix Method ↓

Limitation?

- A problem exists when comparing **large sequences** using the dot matrix method, namely, the high noise level.
- In most dot plots, **dots are plotted all over the graph, obscuring identification of the true alignment.**
- For **DNA** sequences, the problem is particularly **acute** because there are only four possible characters in DNA and each residue therefore has a one-in-four chance of matching a residue in another sequence.

Sequence analysis

Global Alignment and Local Alignment

Alignment algorithms

Sequence alignment

Dot Matrix Method ↓

Limitation?

- The dot matrix method **displays all possible sequence matches**.
- However, it is **often up to the user to construct a full alignment** with insertions and deletions by linking nearby diagonals.
- Another limitation of this visual analysis method is that **it lacks statistical rigor in assessing the quality of the alignment**.
- The method is also **restricted to pairwise alignment**.
- It is **difficult for** the method to scale up to **multiple alignment**.

Sequence analysis

Global Alignment and Local Alignment

Alignment algorithms

Sequence alignment Dot Matrix Method ↓

How it was made better?

A “window” of fixed length used as:

- To reduce noise, instead of using a single residue to scan for similarity, a filtering technique has to be applied, which uses a “window” of fixed length covering a stretch of residue pairs.
- When applying filtering, windows slide across the two sequences to compare all possible stretches.
- Dots are only placed when a stretch of residues equal to the window size from one sequence matches completely with a stretch of another sequence.
- This method has been shown to be effective in reducing the noise level.
- The window is also called a tuple.

Window size or tuple



- The window size can be manipulated so that a clear pattern of sequence match can be plotted.
- However, if the selected window size is too long, sensitivity of the alignment is lost.

Sequence analysis

Global Alignment and Local Alignment

Alignment algorithms

Sequence alignment Dot Matrix Method ↓

Variations and applications?

- ✓ There are many variations of using the dot plot method.
- ✓ For example, a sequence can be aligned with itself to identify internal repeat elements.
- ✓ In the self comparison, there is a main diagonal for perfect matching of each residue.
- ✓ If repeats are present, short parallel lines are observed above and below the main diagonal.

Note: For comparing protein sequences, a weighting scheme has to be used to account for similarities of physicochemical properties of amino acid residues.

Sequence analysis

Global Alignment and Local Alignment

Alignment algorithms

Sequence alignment Dot Matrix Method ↓

Variations and applications?

- ✓ The dot matrix method gives a direct **visual statement** of the relationship between two sequences and helps easy identification of the regions of **greatest similarities**.
- ✓ One particular advantage of this method is in **identification of sequence repeat regions** based on the presence of parallel diagonals of the **same size vertically or horizontally** in the matrix.
- ✓ The method thus has some applications in **genomics**.
- ✓ It is useful in **identifying chromosomal repeats** and in comparing **gene order conservation** between two closely related genomes.
- ✓ It can also be used in **identifying nucleic acid secondary structures through detecting self-complementarity** of a sequence (for example, those that form the stems of a hairpin structure – can also be identified using a dot plot).

Sequence analysis

Global Alignment and Local Alignment

Alignment algorithms

Sequence alignment Dot Matrix Method ↓

Webservers implementing dot matrix:

- ✓ The following are examples of webserver that provide pairwise sequence comparison using dot plots.
 - ✓ **Dotmatcher and Dottup**: two programs of the **EMBOSS** package
 - ✓ **Dothelix**: has option for length threshold (similar to window size)
 - ✓ **MatrixPlot**: the program uses colored grids to indicate alignment