

WEB TECHNOLOGIES

React JS - refs

Prof. Vinay Joshi and Dr. Sarasvathi V
Department of Computer Science and Engineering

Acknowledgement

The slides are created from various internet resources with valuable contributions from multiple professors and teaching assistants in the university.

refs and keys Agenda



- Introduction to refs
- Create and use refs
- Callback refs

refs and keys Introduction to refs



Provides a way to directly access and interact with DOM nodes or React elements
 created in the render method

 Used to return a reference to DOM node or React element, allowing us to perform operations directly on them

 Refs are generally used when we need to perform actions that are not easily achieved through declarative React patterns.

refs and keys Introduction to refs



- Good use cases for refs to be used:
 - Managing Focus, Text Selection, or Media Playback: To programmatically manage focus, text selection, or control media elements.
 - **Triggering Imperative Animations**: Refs can be used to trigger animations that require direct manipulation of the DOM.
 - Integrating with Third-Party DOM Libraries: When integrating with libraries that interact with the DOM, refs provide a way to access and manipulate the DOM elements.

How to create and use refs?



Creating Refs:

- React.createRef() is used to create refs in React, and it's typically done in the constructor (or with a class field).
- These refs can then be attached to a React element via the ref attribute.

Accessing Refs:

- After the ref is attached to an element in the render() method, the DOM node can be accessed via this.myRef.current.
- O This is useful when we need to directly interact with the DOM node, like focusing on an input element or retrieving its value.

How to create and use refs? (coding example)



```
class MyComponent extends React.Component {
  constructor(props) {
   super(props);
    // Creating a ref using React.createRef()
   this.myRef = React.createRef();
  componentDidMount() {
    // Accessing the DOM node when the component mounts
    const node = this.myRef.current;
    console.log('DOM Node:', node);
  render() {
    return (
      // Attaching the ref to the div element
      <div ref={this.myRef} style={{ width: '100px', height: '100px', backgroundColor: 'lightblue' }}>
        Ref Demo
      </div>
```

Ref Demo

```
// Rendering the component
const root = ReactDOM.createRoot(document.getElementById('root'));
root.render(<MyComponent />);
```

refs and keys Callback refs



Fine-Grain Control:

• Callback refs give more control over when refs are set and unset. We can define a function that will be called when the element is rendered or removed.

Function as Ref:

- Instead of using React.createRef(), a function is used as the ref to assign the DOM element or component instance to a class property.
- This function receives the React component instance or HTML DOM element as an argument, allowing us to store and access the ref elsewhere.

Callback refs (coding example)



```
class CustomTextInput extends React.Component {
 constructor(props) {
                                                                                                   Focus the text input
  super(props);
  this.textInput = null;
  // Callback ref function to assign the DOM element to this.textInput
  this.setTextInputRef = element => {
   this.textInput = element;
  };
  this.focusTextInput = () => {
   // Use the raw DOM API to focus the text input if it exists
   if (this.textInput) this.textInput.focus();
  };
```

Callback refs (coding example) continuation...



```
componentDidMount() {
// Automatically focus the input when the component mounts
 this.focusTextInput();
                                                                                             Focus the text input
                                                                happy
                                                                                             Focus the text input
                                                               happy
render() {
 return (
  <div>
  {/* Use the callback ref to get the input DOM element */}
   <input type="text" ref={this.setTextInputRef} />
   <input type="button" value="Focus the text input" onClick={this.focusTextInput} />
  </div>
}}
```



THANK YOU

Vinay Joshi and Sarasvathi V

Department of Computer Science and Engineering

vinayj@pes.edu sarsvathiv@pes.edu

Acknowledgement

The slides are created from various internet resources with valuable contributions from multiple professors and teaching assistants in the university.