EXPERIMENT : 2

1. List all distinct job in Employee.

= SELECT DISTINCT JOB FROM EMPLOYEE;

Output :-

```
MariaDB [2cse16_1722]> SELECT DISTINCT JOB FROM EMPLOYEE;
+-----------+
| JOB       |
+-----------+
| CLERK     |
| SALESMAN  |
| MANAGER   |
| ANALYST   |
| PRESIDENT |
+-----------+
5 rows in set (0.001 sec)
```

2. List all information about employee in Department Number 30.

= SELECT * FROM EMPLOYEE WHERE DEPTNO=30;

Output :-

```
MariaDB [2cse16_1722]> SELECT * FROM EMPLOYEE WHERE DEPTNO=30;
+-------+--------+----------+------+------------+------+------+--------+
| EMPNO | ENAME  | JOB      | MGR  | HIREDATE   | SAL  | COMM | DEPTNO |
+-------+--------+----------+------+------------+------+------+--------+
|  7499 | ALLEN  | SALESMAN | 7698 | 1981-02-20 | 1600 |  300 |     30 |
|  7521 | WARD   | SALESMAN | 7698 | 1981-02-22 | 1250 |  300 |     30 |
|  7654 | MARTIN | SALESMAN | 7698 | 1981-09-28 | 1250 | 1400 |     30 |
|  7698 | BLAKE  | MANAGER  | 7839 | 1981-05-01 | 2850 | NULL |     30 |
|  7844 | TURNER | SALESMAN | 7698 | 1981-09-08 | 1500 |    0 |     30 |
|  7900 | JAMES  | CLERK    | 7698 | 1981-12-03 |  950 | NULL |     30 |
+-------+--------+----------+------+------------+------+------+--------+
6 rows in set (0.003 sec)
```

3. Find all department number with department names greater than 20.

= SELECT DEPTNO, DNAME FROM DEPARTMENT WHERE DEPTNO > 20;

Output :-

```
MariaDB [2cse16_1722]> SELECT DEPTNO,DNAME FROM DEPARTMENT WHERE DEPTNO > 20;
+--------+------------+
| DEPTNO | DNAME      |
+--------+------------+
|     30 | SALES      |
|     40 | OPERATIONS |
+--------+------------+
2 rows in set (0.004 sec)
```

4. Find all information about all the managers as well as the clerks in department 30.

= SELECT * FROM EMPLOYEE WHERE (JOB ='MANAGER' OR JOB = 'CLERK'(AND DEPTNO=30;

Output :-

```
MariaDB [2cse16_1722]> SELECT * FROM EMPLOYEE WHERE (JOB = 'MANAGER' OR JOB = 'CLERK') AND DEPTNO=30;
+-------+-------+---------+------+------------+------+------+--------+
| EMPNO | ENAME | JOB     | MGR  | HIREDATE   | SAL  | COMM | DEPTNO |
+-------+-------+---------+------+------------+------+------+--------+
|  7698 | BLAKE | MANAGER | 7839 | 1981-05-01 | 2850 | NULL |     30 |
|  7900 | JAMES | CLERK   | 7698 | 1981-12-03 |  950 | NULL |     30 |
+-------+-------+---------+------+------------+------+------+--------+
2 rows in set (0.003 sec)
```

5. List the Employee name, Employee numbers and department of all clerks.

= SELECT E.ENAME,E.EMPNO,D.DNAME FROM EMPLOYEE E JOIN DEPARTMENT D ON E.DEPTNO=D.DEPTNO WHERE E.JOB = 'CLERK' ;

Otuput :-

```
MariaDB [2cse16_1722]> SELECT E.ENAME,E.EMPNO,D.DNAME FROM EMPLOYEE E JOIN DEPARTMENT D ON E.DEPTNO=D.DEPTNO WHERE E.JOB='CLERK';
+--------+-------+------------+
| ENAME  | EMPNO | DNAME      |
+--------+-------+------------+
| SMITH  |  7369 | ACCOUNTING |
| ADAMS  |  7876 | ACCOUNTING |
| JAMES  |  7900 | SALES      |
| MILLER |  7934 | RESEARCH   |
+--------+-------+------------+
4 rows in set (0.001 sec)
```

6. Find all managers not in department 30.

= SELECT * FROM EMPLOYEE WHERE JOB='MANAGER' AND DEPTNO 30;

Output :-

```
MariaDB [2cse16_1722]> SELECT * FROM EMPLOYEE WHERE JOB='MANAGER' AND DEPTNO <> 30;
+-------+-------+---------+------+------------+------+------+--------+
| EMPNO | ENAME | JOB     | MGR  | HIREDATE   | SAL  | COMM | DEPTNO |
+-------+-------+---------+------+------------+------+------+--------+
|  7566 | JONES | MANAGER | 7839 | 1981-04-02 | 2975 | NULL |     20 |
|  7782 | CLARK | MANAGER | 7839 | 1981-06-09 | 2450 | NULL |     20 |
+-------+-------+---------+------+------------+------+------+--------+
2 rows in set (0.001 sec)
```

7. List information about all Employees in department 10 who are not manager or clerks.

= SELECT * FROM EMPLOYEE WHERE DEPTNO=10 AND JOB NOT IN ('MANAGER','CLERK');

Output :-

```
Command Prompt - mysql -u
MariaDB [2cse16_1722]> SELECT * FROM EMPLOYEE WHERE DEPTNO=10 AND JOB NOT IN ('MANAGER','CLERK');
Empty set (0.001 sec)
```

8. Find Employees and jobs earning between 1200 and 1400.

= SELECT ENAME,JOB FROM EMPLOYEE WHERE SAL BETWEEN 1200 AND 1400;

Output :-

```
MariaDB [2cse16_1722]> SELECT ENAME,JOB FROM EMPLOYEE WHERE SAL BETWEEN 1200 AND 1400;
+--------+----------+
| ENAME  | JOB      |
+--------+----------+
| WARD   | SALESMAN |
| MARTIN | SALESMAN |
| MILLER | CLERK    |
+--------+----------+
3 rows in set (0.002 sec)
```

9. List Name and Department Number of employee who are clerks, analyst or salesman.

= SELECT ENAME,DEPTNO FROM EMPLOYEE WHERE JOB IN ('CLERK','ANALYST','SALESMAN');

Output :-

```
MariaDB [2cse16_1722]> SELECT ENAME,DEPTNO FROM EMPLOYEE WHERE JOB IN ('CLERK','ANALYST','SALESMAN');
+--------+--------+
| ENAME  | DEPTNO |
+--------+--------+
| SMITH  |     20 |
| ALLEN  |     30 |
| WARD   |     30 |
| MARTIN |     30 |
| SCOTT  |     40 |
| TURNER |     30 |
| ADAMS  |     20 |
| JAMES  |     30 |
| FORD   |     20 |
| MILLER |     10 |
+--------+--------+
10 rows in set (0.001 sec)
```

10. List Name and Department Number of employee whose names began with M.

= SELECT ENAME,DEPTNO FROM EMPLOYEE WHERE ENAME LIKE 'M%' ;

Output :-

```
MariaDB [2cse16_1722]> SELECT ENAME,DEPTNO FROM EMPLOYEE WHERE ENAME LIKE 'M%';
+--------+--------+
| ENAME  | DEPTNO |
+--------+--------+
| MARTIN |     30 |
| MILLER |     10 |
+--------+--------+
2 rows in set (0.001 sec)
```