Experiment : 1

1. Create Employee_master table with data using Employee table.

= CREATE TABLE EMPLOYEE_MASTER AS SELECT * FROM EMPLOYEE;

Output :-

```
Command Prompt - mysql -u

MariaDB [2cse16_1722]> CREATE TABLE EMPLOYEE_MASTER AS SELECT * FROM EMPLOYEE;
Query OK, 14 rows affected (0.011 sec)
Records: 14  Duplicates: 0  Warnings: 0

MariaDB [2cse16_1722]> DESC EMPLOYEE_MASTER;
+----------+-------------+------+-----+---------+-------+
| Field    | Type        | Null | Key | Default | Extra |
+----------+-------------+------+-----+---------+-------+
| EMPNO    | int(4)      | NO   |     | NULL    |       |
| ENAME    | varchar(20) | NO   |     | NULL    |       |
| JOB      | varchar(20) | YES  |     | NULL    |       |
| MGR      | int(4)      | YES  |     | NULL    |       |
| HIREDATE | date        | YES  |     | NULL    |       |
| SAL      | int(10)     | YES  |     | NULL    |       |
| COMM     | int(7)      | YES  |     | NULL    |       |
| DEPTNO   | int(2)      | YES  |     | NULL    |       |
+----------+-------------+------+-----+---------+-------+
8 rows in set (0.005 sec)

MariaDB [2cse16_1722]> SELECT * FROM EMPLOYEE_MASTER;
+-------+--------+-----------+------+------------+------+------+--------+
| EMPNO | ENAME  | JOB       | MGR  | HIREDATE   | SAL  | COMM | DEPTNO |
+-------+--------+-----------+------+------------+------+------+--------+
|  7369 | SMITH  | CLERK     | 7902 | 1980-12-17 |  800 | NULL |     20 |
|  7499 | ALLEN  | SALESMAN  | 7698 | 1981-02-20 | 1600 |  300 |     30 |
|  7521 | WARD   | SALESMAN  | 7698 | 1981-02-22 | 1250 |  300 |     30 |
|  7566 | JONES  | MANAGER   | 7839 | 1981-04-02 | 2975 | NULL |     20 |
|  7654 | MARTIN | SALESMAN  | 7698 | 1981-09-28 | 1250 | 1400 |     30 |
|  7698 | BLAKE  | MANAGER   | 7839 | 1981-05-01 | 2850 | NULL |     30 |
|  7782 | CLARK  | MANAGER   | 7839 | 1981-06-09 | 2450 | NULL |     20 |
|  7788 | SCOTT  | ANALYST   | 7566 | 1982-12-09 | 3000 | NULL |     40 |
|  7839 | KING   | PRESIDENT | NULL | 1981-11-17 | 5000 | NULL |     20 |
|  7844 | TURNER | SALESMAN  | 7698 | 1981-09-08 | 1500 |    0 |     30 |
|  7876 | ADAMS  | CLERK     | 7788 | 1983-01-12 | 1100 | NULL |     20 |
|  7900 | JAMES  | CLERK     | 7698 | 1981-12-03 |  950 | NULL |     30 |
|  7902 | FORD   | ANALYST   | 7566 | 1981-12-03 | 3000 | NULL |     20 |
|  7934 | MILLER | CLERK     | 7782 | 1982-01-23 | 1300 | NULL |     10 |
+-------+--------+-----------+------+------------+------+------+--------+
14 rows in set (0.001 sec)
```

2. Delete all record into Employee_master whose DeptNo is 10 .

= DELETE FROM EMPLOYEE_MASTER WHERE DEPTNO=10;

Output :-

```
Command Prompt - mysql -u

MariaDB [2cse16_1722]> DELETE FROM EMPLOYEE_MASTER WHERE DEPTNO=10;
Query OK, 1 row affected (0.004 sec)

MariaDB [2cse16_1722]> SELECT * FROM EMPLOYEE_MASTER;
+-------+--------+-----------+------+------------+------+------+--------+
| EMPNO | ENAME  | JOB       | MGR  | HIREDATE   | SAL  | COMM | DEPTNO |
+-------+--------+-----------+------+------------+------+------+--------+
|  7369 | SMITH  | CLERK     | 7902 | 1980-12-17 |  800 | NULL |     20 |
|  7499 | ALLEN  | SALESMAN  | 7698 | 1981-02-20 | 1600 |  300 |     30 |
|  7521 | WARD   | SALESMAN  | 7698 | 1981-02-22 | 1250 |  300 |     30 |
|  7566 | JONES  | MANAGER   | 7839 | 1981-04-02 | 2975 | NULL |     20 |
|  7654 | MARTIN | SALESMAN  | 7698 | 1981-09-28 | 1250 | 1400 |     30 |
|  7698 | BLAKE  | MANAGER   | 7839 | 1981-05-01 | 2850 | NULL |     30 |
|  7782 | CLARK  | MANAGER   | 7839 | 1981-06-09 | 2450 | NULL |     20 |
|  7788 | SCOTT  | ANALYST   | 7566 | 1982-12-09 | 3000 | NULL |     40 |
|  7839 | KING   | PRESIDENT | NULL | 1981-11-17 | 5000 | NULL |     20 |
|  7844 | TURNER | SALESMAN  | 7698 | 1981-09-08 | 1500 |    0 |     30 |
|  7876 | ADAMS  | CLERK     | 7788 | 1983-01-12 | 1100 | NULL |     20 |
|  7900 | JAMES  | CLERK     | 7698 | 1981-12-03 |  950 | NULL |     30 |
|  7902 | FORD   | ANALYST   | 7566 | 1981-12-03 | 3000 | NULL |     20 |
+-------+--------+-----------+------+------------+------+------+--------+
13 rows in set (0.000 sec)
```

3. Update 10% in his salary of DEPTNO 20 into Employee_Master.

= UPDATE EMPLOYEE_MASTER SET SAL = SAL + (SAL*0.10) WHERE DEPTNO=20;

Output :-

```
MariaDB [2cse16_1722]> UPDATE EMPLOYEE_MASTER SET SAL = SAL + (SAL*0.10) WHERE DEPTNO=20;
Query OK, 6 rows affected (0.003 sec)
Rows matched: 6  Changed: 6  Warnings: 0

MariaDB [2cse16_1722]> SELECT * FROM EMPLOYEE_MASTER;
+-------+--------+-----------+------+------------+------+------+--------+
| EMPNO | ENAME  | JOB       | MGR  | HIREDATE   | SAL  | COMM | DEPTNO |
+-------+--------+-----------+------+------------+------+------+--------+
|  7369 | SMITH  | CLERK     | 7902 | 1980-12-17 |  880 | NULL |     20 |
|  7499 | ALLEN  | SALESMAN  | 7698 | 1981-02-20 | 1600 |  300 |     30 |
|  7521 | WARD   | SALESMAN  | 7698 | 1981-02-22 | 1250 |  300 |     30 |
|  7566 | JONES  | MANAGER   | 7839 | 1981-04-02 | 3273 | NULL |     20 |
|  7654 | MARTIN | SALESMAN  | 7698 | 1981-09-28 | 1250 | 1400 |     30 |
|  7698 | BLAKE  | MANAGER   | 7839 | 1981-05-01 | 2850 | NULL |     30 |
|  7782 | CLARK  | MANAGER   | 7839 | 1981-06-09 | 2695 | NULL |     20 |
|  7788 | SCOTT  | ANALYST   | 7566 | 1982-12-09 | 3000 | NULL |     40 |
|  7839 | KING   | PRESIDENT | NULL | 1981-11-17 | 5500 | NULL |     20 |
|  7844 | TURNER | SALESMAN  | 7698 | 1981-09-08 | 1500 |    0 |     30 |
|  7876 | ADAMS  | CLERK     | 7788 | 1983-01-12 | 1210 | NULL |     20 |
|  7900 | JAMES  | CLERK     | 7698 | 1981-12-03 |  950 | NULL |     30 |
|  7902 | FORD   | ANALYST   | 7566 | 1981-12-03 | 3300 | NULL |     20 |
+-------+--------+-----------+------+------------+------+------+--------+
13 rows in set (0.001 sec)
```

4. Alter SAL with size 10,2 in Employee_Master.

= ALTER TABLE EMPLOYEE_MASTER MODIFY SAL DECIMAL(10,2);

Output :-

```
MariaDB [2cse16_1722]> ALTER TABLE EMPLOYEE_MASTER MODIFY SAL DECIMAL(10,2);
Query OK, 13 rows affected (0.026 sec)
Records: 13  Duplicates: 0  Warnings: 0

MariaDB [2cse16_1722]>  SELECT * FROM EMPLOYEE_MASTER;
+-------+--------+-----------+------+------------+---------+------+--------+
| EMPNO | ENAME  | JOB       | MGR  | HIREDATE   | SAL     | COMM | DEPTNO |
+-------+--------+-----------+------+------------+---------+------+--------+
|  7369 | SMITH  | CLERK     | 7902 | 1980-12-17 |  880.00 | NULL |     20 |
|  7499 | ALLEN  | SALESMAN  | 7698 | 1981-02-20 | 1600.00 |  300 |     30 |
|  7521 | WARD   | SALESMAN  | 7698 | 1981-02-22 | 1250.00 |  300 |     30 |
|  7566 | JONES  | MANAGER   | 7839 | 1981-04-02 | 3273.00 | NULL |     20 |
|  7654 | MARTIN | SALESMAN  | 7698 | 1981-09-28 | 1250.00 | 1400 |     30 |
|  7698 | BLAKE  | MANAGER   | 7839 | 1981-05-01 | 2850.00 | NULL |     30 |
|  7782 | CLARK  | MANAGER   | 7839 | 1981-06-09 | 2695.00 | NULL |     20 |
|  7788 | SCOTT  | ANALYST   | 7566 | 1982-12-09 | 3000.00 | NULL |     40 |
|  7839 | KING   | PRESIDENT | NULL | 1981-11-17 | 5500.00 | NULL |     20 |
|  7844 | TURNER | SALESMAN  | 7698 | 1981-09-08 | 1500.00 |    0 |     30 |
|  7876 | ADAMS  | CLERK     | 7788 | 1983-01-12 | 1210.00 | NULL |     20 |
|  7900 | JAMES  | CLERK     | 7698 | 1981-12-03 |  950.00 | NULL |     30 |
|  7902 | FORD   | ANALYST   | 7566 | 1981-12-03 | 3300.00 | NULL |     20 |
+-------+--------+-----------+------+------------+---------+------+--------+
13 rows in set (0.001 sec)
```

5. Drop Employee_master Table.

= DROP TABLE EMPLOYEE_MASTER;

Output:-

```
MariaDB [2cse16_1722]> DROP TABLE EMPLOYEE_MASTER
    -> ;
Query OK, 0 rows affected (0.009 sec)

MariaDB [2cse16_1722]> DROP TABLE EMPLOYEE_MASTER;
ERROR 1051 (42S02): Unknown table '2cse16_1722.employee_master'
MariaDB [2cse16_1722]>
```