Experiment : 3

1. List all employees and jobs in Department 30 in descending order by salary.

= SELECT ENAME,JOB,SAL FROM EMPLOYEE WHERE DEPTNO=30 ORDER BY SAL DESC;

Output :-

```
MariaDB [2CSE16_1722]> SELECT ENAME,JOB,SAL FROM EMPLOYEE WHERE DEPTNO=30 ORDER BY SAL DESC;
+--------+----------+------+
| ENAME  | JOB      | SAL  |
+--------+----------+------+
| BLAKE  | MANAGER  | 2850 |
| ALLEN  | SALESMAN | 1600 |
| TURNER | SALESMAN | 1500 |
| WARD   | SALESMAN | 1250 |
| MARTIN | SALESMAN | 1250 |
| JAMES  | CLERK    |  950 |
+--------+----------+------+
6 rows in set (0.003 sec)
```

2. List job and Department Number of employees whose name are five letters long begin with “A” and end with “N”.

= SELECT JOB,DEPTNO,ENAME FROM EMPLOYEE WHERE ENAME LIKE 'A__N';

Output :-

```
Command Prompt - mysql -u

MariaDB [2CSE16_1722]> SELECT JOB,DEPTNO,ENAME FROM EMPLOYEE WHERE ENAME LIKE 'A___N';
+----------+--------+-------+
| JOB      | DEPTNO | ENAME |
+----------+--------+-------+
| SALESMAN |     30 | ALLEN |
+----------+--------+-------+
1 row in set (0.001 sec)
```

3. Display the name of employees whose name start with alphabet S.

= SELECT ENAME FROM EMPLOYEE WHERE ENAME LIKE 'S%';

Output :-

```
MariaDB [2CSE16_1722]>  SELECT ENAME FROM EMPLOYEE WHERE ENAME LIKE 'S%';
+-------+
| ENAME |
+-------+
| SMITH |
| SCOTT |
+-------+
2 rows in set (0.001 sec)
```

4. Display the names of employees whose name ends with alphabet S.

= SELECT ENAME FROM EMPLOYEE WHERE ENAME LIKE '%S';

Output :-

```
MariaDB [2CSE16_1722]>  SELECT ENAME FROM EMPLOYEE WHERE ENAME LIKE '%S';
+-------+
| ENAME |
+-------+
| JONES |
| ADAMS |
| JAMES |
+-------+
3 rows in set (0.001 sec)
```

5. Display the names of employees working in department number 10 or 20 or 40 or employees working as clerks, salesman or analyst.

= SELECT ENAME FROM EMPLOYEE WHERE DEPTNO IN (10,20,40) OR JOB IN ('CLERK','SALESMAN','ANALYST');

Output :-

```
MariaDB [2CSE16_1722]> SELECT ENAME FROM EMPLOYEE WHERE DEPTNO IN (10,20,40) OR JOB IN ('CLERK','SALESMAN','ANALYST');
+--------+
| ENAME  |
+--------+
| SMITH  |
| ALLEN  |
| WARD   |
| JONES  |
| MARTIN |
| CLARK  |
| SCOTT  |
| KING   |
| TURNER |
| ADAMS  |
| JAMES  |
| FORD   |
| MILLER |
+--------+
13 rows in set (0.001 sec)
```

6. Display employee number and names for employees who earn commission.

= SELECT EMPNO, ENAME FROM EMPLOYEE WHERE COMM IS NOT NULL;

Output :-

```
MariaDB [2CSE16_1722]> SELECT EMPNO,ENAME FROM EMPLOYEE WHERE COMM IS NOT NULL;
+-------+--------+
| EMPNO | ENAME  |
+-------+--------+
|  7499 | ALLEN  |
|  7521 | WARD   |
|  7654 | MARTIN |
|  7844 | TURNER |
+-------+--------+
4 rows in set (0.002 sec)
```

7. Display employee number and total salary for each employee.

= SELECT EMPNO,(SAL+IFNULL(COMM,0)) AS TOTAL_SALARY FROM EMPLOYEE;

Output :-

```
MariaDB [2CSE16_1722]> SELECT EMPNO,(SAL+IFNULL(COMM,0)) AS TOTAL_SALARY FROM EMPLOYEE;
+-------+--------------+
| EMPNO | TOTAL_SALARY |
+-------+--------------+
|  7369 |          800 |
|  7499 |         1900 |
|  7521 |         1550 |
|  7566 |         2975 |
|  7654 |         2650 |
|  7698 |         2850 |
|  7782 |         2450 |
|  7788 |         3000 |
|  7839 |         5000 |
|  7844 |         1500 |
|  7876 |         1100 |
|  7900 |          950 |
|  7902 |         3000 |
|  7934 |         1300 |
+-------+--------------+
14 rows in set (0.001 sec)
```

8. Display employee number and annual salary for each employee.

= SELECT EMPNO, SAL*12 AS ANNUAL_SALARY FROM EMPLOYEE;

Output :-

```
MariaDB [2CSE16_1722]> SELECT EMPNO,SAL*12 AS ANNUAL_SALARY FROM EMPLOYEE;
+-------+---------------+
| EMPNO | ANNUAL_SALARY |
+-------+---------------+
|  7369 |          9600 |
|  7499 |         19200 |
|  7521 |         15000 |
|  7566 |         35700 |
|  7654 |         15000 |
|  7698 |         34200 |
|  7782 |         29400 |
|  7788 |         36000 |
|  7839 |         60000 |
|  7844 |         18000 |
|  7876 |         13200 |
|  7900 |         11400 |
|  7902 |         36000 |
|  7934 |         15600 |
+-------+---------------+
14 rows in set (0.001 sec)
```

9. Display the names of all employees working as clerks and drawing a salary more than 3,000.

= SELECT ENAME FROM EMPLOYEE WHERE JOB='CLERK' AND SAL>3000;

Output :-

```
MariaDB [2CSE16_1722]> SELECT ENAME FROM EMPLOYEE WHERE JOB='CLERK' AND SAL>3000;
Empty set (0.001 sec)
```

10. Display the names of employees who are working as clerk, salesman or analyst and drawing a salary more than 3,000.

= SELECT ENAME FROM EMPLOYEE WHERE JOB IN ('CLERK','SALESMAN','ANALYST') AND SAL>3000;

Output :-

```
MariaDB [2CSE16_1722]> SELECT ENAME FROM EMPLOYEE WHERE JOB IN ('CLERK','SALESMAN','ANALYST') AND SAL>3000;
Empty set (0.001 sec)
```