

UNIVERSITY OF ENGINEERING & MANAGEMENT, KOLKATA

Course Name : Compiler Design

Prof. Sankhadeep Chatterjee



- Construction of a parse tree is done by starting the root labeled by a start symbol
- Repeat following two steps
 - At a node labeled with non terminal **A** select one of the productions of **A** and construct children nodes
 - Find the next node at which subtree is Constructed

$$N = \{S, A\}$$

$$T = \{a, b, c, d\}$$

$$P =$$

$$S \rightarrow cAd$$

$$A \rightarrow ab \mid a$$

$$S = \{S\}$$

Derive string (w) **cad**

$$A \rightarrow ab \mid a$$
$$S \rightarrow cAd$$

(S)

Derive string cad


Node $\rightarrow S$

Input pointer $\rightarrow c$

Selected Production

Rule: $S \rightarrow cAd$

$$A \rightarrow ab \mid a$$
$$S \rightarrow cAd$$



Derive string *cad*


Node $\rightarrow S$

Input pointer $\rightarrow c$

Selected Production

Rule: $S \rightarrow cAd$

$$A \rightarrow ab \mid a$$
$$S \rightarrow cAd$$



Derive string *cad*

Node $\rightarrow A$

Input pointer $\rightarrow a$

Selected Production

Rule: $A \rightarrow ab$

$$A \rightarrow ab \mid a$$
$$S \rightarrow cAd$$


Derive string *cad*

Node $\rightarrow A$

Input pointer $\rightarrow a$

Selected Production

Rule: $A \rightarrow ab$



$$A \rightarrow ab \mid a$$
$$S \rightarrow cAd$$

Derive string *cad*


Node \rightarrow b

Input pointer \rightarrow d


Selected Production

Rule: *Failure!*

Backtrack



$$A \rightarrow ab \mid a$$
$$S \rightarrow cAd$$



Derive string *cad*

Node $\rightarrow A$

Input pointer $\rightarrow a$

Selected Production

Rule: $A \rightarrow a$

$$A \rightarrow ab \mid a$$
$$S \rightarrow cAd$$


Derive string *cad*

Node $\rightarrow A$

Input pointer $\rightarrow a$

Selected Production

Rule: $A \rightarrow a$



Recursive Descent Parsing


```
void A() {  
1)      Choose an  $A$ -production,  $A \rightarrow X_1X_2 \cdots X_k$ ;  
2)      for (  $i = 1$  to  $k$  ) {  
3)          if (  $X_i$  is a nonterminal )  
4)              call procedure  $X_i()$ ;  
5)          else if (  $X_i$  equals the current input symbol  $a$  )  
6)              advance the input to the next symbol;  
7)          else /* an error has occurred */;  
      }  
}
```

Recursive Descent Parsing

- Recursive Descent parsing is a set of procedures, one for each nonterminal
- Execution begins from Start symbol
- The pseudocode is nondeterministic
- It requires backtracking, which is not very efficient
- Tabular methods (Dynamic Programming) of parsing is used


Left Recursion

- Top down parser with production rule $A \rightarrow A\alpha \mid \beta$ may loop forever.




Left Recursion

- Top down parser with production rule $A \rightarrow A\alpha \mid \beta$ may loop forever.




Left Recursion

- Top down parser with production rule $A \rightarrow A\alpha \mid \beta$ may loop forever.



Left Recursion

- Top down parser with production rule $A \rightarrow A\alpha \mid \beta$ may loop forever.




Left Recursion


- Top down parser with production rule $A \rightarrow A\alpha \mid \beta$ may loop forever.
- The left recursion can be removed by rewriting the grammar as follows;

$$\begin{aligned} A &\rightarrow \beta A' \\ A' &\rightarrow \alpha A' \mid \epsilon \end{aligned}$$

- Both Parse tree generate $\beta\alpha^*$



With Left Recursion



Without Left Recursion

Left Recursion Removal

Remove left recursion
from the following
grammar:

$$E \rightarrow E + T \mid T$$

$$T \rightarrow T * F \mid F$$

$$F \rightarrow (E) \mid id$$

Left Recursion Removal

Remove left recursion
from the following
grammar:

$$E \rightarrow E + T \mid T$$

$$T \rightarrow T * F \mid F$$

$$F \rightarrow (E) \mid id$$

$$E \rightarrow TE'$$

Left Recursion Removal

Remove left recursion
from the following
grammar:

$$\begin{aligned}E &\rightarrow E + T \mid T \\T &\rightarrow T * F \mid F \\F &\rightarrow (E) \mid id\end{aligned}$$

$$\begin{aligned}E &\rightarrow TE' \\E' &\rightarrow +TE' \mid \varepsilon\end{aligned}$$

Left Recursion Removal

Remove left recursion
from the following
grammar:

$$\begin{aligned}E &\rightarrow E + T \mid T \\T &\rightarrow T * F \mid F \\F &\rightarrow (E) \mid id\end{aligned}$$

$$\begin{aligned}E &\rightarrow TE' \\E' &\rightarrow +TE' \mid \varepsilon \\T &\rightarrow FT'\end{aligned}$$

Left Recursion Removal

Remove left recursion
from the following
grammar:

$$E \rightarrow E + T \mid T$$

$$T \rightarrow T * F \mid F$$

$$F \rightarrow (E) \mid id$$

$$E \rightarrow TE'$$

$$E' \rightarrow +TE' \mid \varepsilon$$

$$T \rightarrow FT'$$

$$T' \rightarrow *FT' \mid \varepsilon$$

Left Recursion Removal

Remove left recursion
from the following
grammar:

$$E \rightarrow E + T \mid T$$

$$T \rightarrow T * F \mid F$$

$$F \rightarrow (E) \mid id$$

$$E \rightarrow TE'$$

$$E' \rightarrow +TE' \mid \varepsilon$$

$$T \rightarrow FT'$$

$$T' \rightarrow *FT' \mid \varepsilon$$

$$F \rightarrow (E) \mid id$$

Left Recursion Removal

- In general

$$A \rightarrow A\alpha_1 \mid A\alpha_2 \mid \dots \mid A\alpha_m \mid \beta_1 \mid \beta_2 \mid \dots \mid \beta_n$$

- Transforms to

$$\begin{aligned} A &\rightarrow \beta_1 A' \mid \beta_2 A' \mid \dots \mid \beta_n A' \\ A' &\rightarrow \alpha_1 A' \mid \alpha_2 A' \mid \dots \mid \alpha_m A' \mid \epsilon \end{aligned}$$

Left Recursion Removal

- Consider the following Grammar:

$$\begin{aligned} S &\rightarrow Aa \mid b \\ A &\rightarrow Ac \mid Sd \mid \epsilon \end{aligned}$$

- There is left recursion as:

$$S \rightarrow Aa \rightarrow Sda$$

- How can we remove left recursion?
 - Starting from the first rule and replacing all the occurrences of the first non terminal symbol
 - Removing left recursion from the modified grammar

Left Recursion Removal

- After the first step (substitute S by its body in the rules) the grammar becomes

$$\begin{aligned} S &\rightarrow Aa \mid b \\ A &\rightarrow Ac \mid Aad \mid bd \mid \epsilon \end{aligned}$$

- After the second step (removal of left recursion) the grammar becomes

$$\begin{aligned} S &\rightarrow Aa \mid b \\ A &\rightarrow bdA' \mid A' \\ A' &\rightarrow cA' \mid adA' \mid \epsilon \end{aligned}$$

Algorithm for Left Recursion Removal

INPUT: Grammar G with no cycles or ϵ -production

OUTPUT: Equivalent grammar without left recursion

- 1) arrange the nonterminals in some order A_1, A_2, \dots, A_n .
- 2) **for** (each i from 1 to n) {
- 3) **for** (each j from 1 to $i - 1$) {
- 4) replace each production of the form $A_i \rightarrow A_j \gamma$ by the productions $A_i \rightarrow \delta_1 \gamma \mid \delta_2 \gamma \mid \dots \mid \delta_k \gamma$, where $A_j \rightarrow \delta_1 \mid \delta_2 \mid \dots \mid \delta_k$ are all current A_j -productions
- 5) }
- 6) eliminate the immediate left recursion among the A_i -productions
- 7) }


Left factoring

- In top-down parsing when it is not clear which production to choose for expansion of a symbol
 - Defer the decision till we have seen enough input.
- In general if $A \rightarrow \alpha\beta_1 \mid \alpha\beta_2$
 - Defer decision by expanding A to $\alpha A'$
 - Later A' can be expanded to β_1 or β_2
- Therefore, $A \rightarrow \alpha\beta_1 \mid \alpha\beta_2$ is transformed to
$$A \rightarrow \alpha A'$$
$$A' \rightarrow \beta_1 \mid \beta_2$$

FIRST & FOLLOW

- The Top down parser is generated with the help of two functions
 - FIRST
 - FOLLOW
- $\text{FIRST}(\alpha)$ is set of terminals (tokens) that begin the strings derived from string α
- $\text{FOLLOW}(A)$ is set of terminals (tokens) that might follow the derivation of non terminal A

FIRST & FOLLOW



Algorithm for FIRST

- If X is a terminal symbol then $\text{First}(X) = \{X\}$
- If $X \rightarrow \epsilon$ is a production then ϵ is in $\text{First}(X)$
- If X is a non terminal & $X \rightarrow Y_1 Y_2 \dots Y_i Y_j \dots Y_k$ is a production then
if $a \in \text{First}(Y_j)$ and ϵ is in all $Y_i \forall i < j$ then
 a is in $\text{First}(X)$
- If X is a non terminal and $X \rightarrow Y_1 Y_2 \dots Y_k$ is a production then
If ϵ is in all $Y_i \forall 1 \leq i \leq k$ then
 ϵ is in $\text{First}(X)$

Example: FIRST

- For the following grammar:

$$\begin{aligned}E &\rightarrow TE' \\E' &\rightarrow +TE' \mid \varepsilon \\T &\rightarrow FT' \\T' &\rightarrow *FT' \mid \varepsilon \\F &\rightarrow (E) \mid id\end{aligned}$$

$$\text{FIRST}(E) = \text{FIRST}(T) = \text{FIRST}(F) = \{ (, id \}$$

$$\text{FIRST}(E') = \{ +, \epsilon \}$$

$$\text{FIRST}(T') = \{ *, \epsilon \}$$

Algorithm for FOLLOW

- Place \$ in FOLLOW(S)
- If there is a production $A \rightarrow \alpha B \beta$ then everything in FIRST(β) (except ε) is in FOLLOW(B)
- If there is a production $A \rightarrow \alpha B$ then everything in FOLLOW(A) is in FOLLOW(B)
- If there is a production $A \rightarrow \alpha B \beta$ and FIRST(β) contains ε then everything in FOLLOW(A) is in FOLLOW(B)

Example: FOLLOW

- For the following grammar:

$$E \rightarrow TE'$$

$$E' \rightarrow +TE' \mid \varepsilon$$

$$T \rightarrow FT'$$

$$T' \rightarrow *FT' \mid \varepsilon$$

$$F \rightarrow (E) \mid id$$

$$\text{FOLLOW}(E) = \text{FOLLOW}(E') = \{ \$,) \}$$

$$\text{FOLLOW}(T) = \text{FOLLOW}(T') = \{ \$,), + \}$$

$$\text{FOLLOW}(F) = \{ \$,), +, * \}$$

Problem Solving

1. Find the FIRST and FOLLOW of every grammar symbol of the following grammar;

$$S \rightarrow aABb$$

$$A \rightarrow c \mid \epsilon$$

$$B \rightarrow d \mid \epsilon$$

2. Find the FIRST and FOLLOW of every grammar symbol of the following grammar;

$$S \rightarrow AaAb \mid BbBa$$

$$A \rightarrow \epsilon$$


$$B \rightarrow \epsilon$$

Predictive Parsing

- A non recursive top down parsing method
- Parser “predicts” which production to use
- It removes backtracking by fixing one production for every non-terminal and input token(s)
- Predictive parsers accept LL(k) languages
 - First L stands for left to right scan of input
 - Second L stands for leftmost derivation
 - k stands for number of lookahead token
- In practice LL(1) is used

Predictive Parsing

- Predictive parser can be implemented by maintaining an external stack



Predictive Parsing Table

- Parse table is a two dimensional array $M[X, a]$ where “ X ” is a non terminal and “ a ” is a terminal of the grammar

		Terminals			
		a_1	a_2	...	a_m
Non terminals	X_1
	X_2	...	$X_2 \rightarrow \alpha$

	X_n

Algorithm: Predictive Parsing Table

- for each production $A \rightarrow \alpha$ do
 for each terminal ' a ' in $\text{FIRST}(\alpha)$
 $M[A,a] = A \rightarrow \alpha$
- If ϵ is in $\text{FIRST}(\alpha)$
 for each terminal b in $\text{FOLLOW}(A)$
 $M[A,b] = A \rightarrow \alpha$
 If \$ is in $\text{FOLLOW}(A)$
 $M[A,\$] = A \rightarrow \alpha$

Example: Predictive Parsing Table Generation

$$\begin{aligned}
 E &\rightarrow TE' & \text{FIRST}(E) = \text{FIRST}(T) = \text{FIRST}(F) = \{ (, id \} \\
 E' &\rightarrow +TE' \mid \epsilon & \text{FIRST}(E') = \{ +, \epsilon \} \\
 T &\rightarrow FT' & \text{FIRST}(T') = \{ *, \epsilon \} \\
 T' &\rightarrow *FT' \mid \epsilon & \text{FOLLOW}(E) = \text{FOLLOW}(E') = \{ \$,) \} \\
 F &\rightarrow (E) \mid id & \text{FOLLOW}(T) = \text{FOLLOW}(T') = \{ \$,), + \} \\
 & & \text{FOLLOW}(F) = \{ \$,), +, * \}
 \end{aligned}$$

NON - TERMINAL	INPUT SYMBOL					
	id	+	*	()	\$
E	$E \rightarrow TE'$			$E \rightarrow TE'$		
E'		$E' \rightarrow +TE'$			$E' \rightarrow \epsilon$	$E' \rightarrow \epsilon$
T	$T \rightarrow FT'$			$T \rightarrow FT'$		
T'		$T' \rightarrow \epsilon$	$T' \rightarrow *FT'$		$T' \rightarrow \epsilon$	$T' \rightarrow \epsilon$
F	$F \rightarrow id$			$F \rightarrow (E)$		

Predictive Parsing

- The stack is initialized to contain $\$S$, the $\$$ is the "bottom" marker.
- The input has a $\$$ added to the end.
- The parse table, $M[X, a]$ contains what should be done when we see nonterminal X on the stack and current token " a "
- Parse Actions for
 - X = top of stack, and
 - a = current token
- If $X = a = \$$ then halt and announce success.
- If $X = a \neq \$$ then pop X off the stack and advance the input pointer to the next token.
- If X is nonterminal consult the table entry $M[X, a]$

Predictive Parsing

- If X is nonterminal then consult $M[X, a]$.
 - The entry will be either a production or an error entry.
 - If $M[X, a] = \{X \rightarrow UVW\}$
 - The parser replaces X on the top of the stack with W, V, U with the U on the top
 - As output print the name of the production used.

Predictive Parsing Algorithm

Set ip to the first token in $w\$$.

Repeat

Let X be the top of the stack and a be the current token

if X is a terminal or $\$$ then

if $X = a$ then

pop X from the stack and advance the ip

else

error()

else /* X is a nonterminal */

if $M[X, a] = X \rightarrow Y_1 Y_2 \dots Y_k$ then

Pop X from the stack

Push $Y_1 Y_2 \dots Y_k$ onto the stack with Y_1 on top

output the production $X \rightarrow Y_1 Y_2 \dots Y_k$

else

error()

Until $X = \$$

LL(1) Grammars

- A grammar is called LL(1) if its parsing table has no multiply defined entries.
- LL(1) grammars
 - Must not be ambiguous.
 - Must not be left-recursive.
- G is LL(1) if and only if whenever $A \rightarrow \alpha | \beta$
 - $FIRST(\alpha) \cap FIRST(\beta) = \phi$
 - At most one of α and β can derive ϵ
 - If $\beta \rightarrow \epsilon$ then $FIRST(\alpha) \cap FOLLOW(A) = \phi$

Example: LL(1)

$$S \rightarrow AS'$$

$$S' \rightarrow AS' \mid \epsilon$$

$$A \rightarrow a$$

	a	$\$$
S	$S \rightarrow AS'$	
S'	$S \rightarrow AS'$	$S' \rightarrow \epsilon$
A	$A \rightarrow a$	

Example: Predictive Parsing

MATCHED	STACK	INPUT	ACTION
	$S \$$	$aa \$$	$S \rightarrow AS'$

Example: Predictive Parsing

MATCHED	STACK	INPUT	ACTION
	$S \$$	$aa \$$	$S \rightarrow AS'$
	$AS' \$$	$aa \$$	$A \rightarrow a$

Example: Predictive Parsing

MATCHED	STACK	INPUT	ACTION
	$S \$$	$aa \$$	$S \rightarrow AS'$
	$AS' \$$	$aa \$$	$A \rightarrow a$
	$aS' \$$	$aa \$$	Matched

Example: Predictive Parsing

MATCHED	STACK	INPUT	ACTION
	$S \$$	$aa \$$	$S \rightarrow AS'$
	$AS' \$$	$aa \$$	$A \rightarrow a$
	$aS' \$$	$aa \$$	Matched
a	$S' \$$	$a \$$	$S \rightarrow AS'$

Example: Predictive Parsing

MATCHED	STACK	INPUT	ACTION
	$S \$$	$aa \$$	$S \rightarrow AS'$
	$AS' \$$	$aa \$$	$A \rightarrow a$
	$aS' \$$	$aa \$$	Matched
a	$S' \$$	$a \$$	$S \rightarrow AS'$
a	$AS' \$$	$a \$$	$A \rightarrow a$

Example: Predictive Parsing

MATCHED	STACK	INPUT	ACTION
	$S \$$	$aa \$$	$S \rightarrow AS'$
	$AS' \$$	$aa \$$	$A \rightarrow a$
	$aS' \$$	$aa \$$	Matched
a	$S' \$$	$a \$$	$S \rightarrow AS'$
a	$AS' \$$	$a \$$	$A \rightarrow a$
a	$aS' \$$	$a \$$	Matched

Example: Predictive Parsing

MATCHED	STACK	INPUT	ACTION
	$S \$$	$aa \$$	$S \rightarrow AS'$
	$AS' \$$	$aa \$$	$A \rightarrow a$
	$aS' \$$	$aa \$$	Matched
a	$S' \$$	$a \$$	$S \rightarrow AS'$
a	$AS' \$$	$a \$$	$A \rightarrow a$
a	$aS' \$$	$a \$$	Matched
aa	$S' \$$	$\$$	$S' \rightarrow \epsilon$

Example: Predictive Parsing

MATCHED	STACK	INPUT	ACTION
	$S \$$	$aa \$$	$S \rightarrow AS'$
	$AS' \$$	$aa \$$	$A \rightarrow a$
	$aS' \$$	$aa \$$	Matched
a	$S' \$$	$a \$$	$S \rightarrow AS'$
a	$AS' \$$	$a \$$	$A \rightarrow a$
a	$aS' \$$	$a \$$	Matched
aa	$S' \$$	$\$$	$S' \rightarrow \epsilon$
aa	$\$$	$\$$	

Bottom up Parsing

- Use explicit stack to perform a parse
- Simulate rightmost derivation (R) from left (L) to right, thus called LR parsing
- More powerful than top-down parsing
 - Left recursion does not cause problem
- Two actions
 - Shift: take next input token into the stack
 - Reduce: replace a string B on top of stack by a nonterminal A, given a production $A \rightarrow B$

Bottom up Parsing

id * id

F * id
 |
 id

T * id
 |
 F
 |
 id

T * F
 | |
 F id
 |
 id

T
 / | \
 T * F
 | |
 F id
 |
 id

E
 |
 T
 / | \
 T * F
 | |
 F id
 |
 id

Bottom up Parsing

- Informally, a “handle” of a string is a substring that matches the right side of the production
- Reduction of “handle” to non-terminal on the left side of the production represents one step along the reverse of a rightmost derivation

RIGHT SENTENTIAL FORM	HANDLE	REDUCING PRODUCTION
$id_1 * id_2$	id_1	$F \rightarrow id$
$F * id_2$	F	$T \rightarrow F$
$T * id_2$	id_2	$F \rightarrow id$
$T * F$	$T * F$	$E \rightarrow T * F$

Shift-Reduce Parsing

STACK	INPUT	ACTION
\$	(id + id) * id \$	Shift
\$ (id + id) * id \$	Shift

Shift-Reduce Parsing

STACK	INPUT	ACTION
\$	(id + id) * id \$	Shift
\$ (id + id) * id \$	Shift
\$ (id	+ id) * id \$	Reduce by $F \rightarrow id$

Shift-Reduce Parsing

STACK	INPUT	ACTION
\$	(id + id) * id \$	Shift
\$ (id + id) * id \$	Shift
\$ (id	+ id) * id \$	Reduce by $F \rightarrow id$
\$ (F	+ id) * id \$	Reduce by $T \rightarrow F$

Shift-Reduce Parsing

STACK	INPUT	ACTION
\$	(id + id) * id \$	Shift
\$ (id + id) * id \$	Shift
\$ (id	+ id) * id \$	Reduce by $F \rightarrow id$
\$ (F	+ id) * id \$	Reduce by $T \rightarrow F$
\$ (T	+ id) * id \$	Reduce by $E \rightarrow T$

Shift-Reduce Parsing

STACK	INPUT	ACTION
\$	(id + id) * id \$	Shift
\$ (id + id) * id \$	Shift
\$ (id	+ id) * id \$	Reduce by $F \rightarrow id$
\$ (F	+ id) * id \$	Reduce by $T \rightarrow F$
\$ (T	+ id) * id \$	Reduce by $E \rightarrow T$
\$ (E +	id) * id \$	Shift

Shift-Reduce Parsing

STACK	INPUT	ACTION
\$	(id + id) * id \$	Shift
\$ (id + id) * id \$	Shift
\$ (id	+ id) * id \$	Reduce by $F \rightarrow id$
\$ (F	+ id) * id \$	Reduce by $T \rightarrow F$
\$ (T	+ id) * id \$	Reduce by $E \rightarrow T$
\$ (E +	id) * id \$	Shift
\$ (E + id) * id \$	Reduce by $F \rightarrow id$

Shift-Reduce Parsing

STACK	INPUT	ACTION
\$	(id + id) * id \$	Shift
\$ (id + id) * id \$	Shift
\$ (id	+ id) * id \$	Reduce by $F \rightarrow id$
\$ (F	+ id) * id \$	Reduce by $T \rightarrow F$
\$ (T	+ id) * id \$	Reduce by $E \rightarrow T$
\$ (E +	id) * id \$	Shift
\$ (E + id) * id \$	Reduce by $F \rightarrow id$
\$ (E + F) * id \$	Reduce by $T \rightarrow F$

Shift-Reduce Parsing

STACK	INPUT	ACTION
\$	(id + id) * id \$	Shift
\$ (id + id) * id \$	Shift
\$ (id	+ id) * id \$	Reduce by $F \rightarrow id$
\$ (F	+ id) * id \$	Reduce by $T \rightarrow F$
\$ (T	+ id) * id \$	Reduce by $E \rightarrow T$
\$ (E +	id) * id \$	Shift
\$ (E + id) * id \$	Reduce by $F \rightarrow id$
\$ (E + F) * id \$	Reduce by $T \rightarrow F$
\$ (E + T) * id \$	Reduce by $E \rightarrow E + T$

Shift-Reduce Parsing

STACK	INPUT	ACTION
\$	(id + id) * id \$	Shift
\$ (id + id) * id \$	Shift
\$ (id	+ id) * id \$	Reduce by $F \rightarrow id$
\$ (F	+ id) * id \$	Reduce by $T \rightarrow F$
\$ (T	+ id) * id \$	Reduce by $E \rightarrow T$
\$ (E +	id) * id \$	Shift
\$ (E + id) * id \$	Reduce by $F \rightarrow id$
\$ (E + F) * id \$	Reduce by $T \rightarrow F$
\$ (E + T) * id \$	Reduce by $E \rightarrow E + T$
\$ (E) * id \$	Shift

Shift-Reduce Parsing

STACK	INPUT	ACTION
\$	(id + id) * id \$	Shift
\$ (id + id) * id \$	Shift
\$ (id	+ id) * id \$	Reduce by $F \rightarrow id$
\$ (F	+ id) * id \$	Reduce by $T \rightarrow F$
\$ (T	+ id) * id \$	Reduce by $E \rightarrow T$
\$ (E +	id) * id \$	Shift
\$ (E + id) * id \$	Reduce by $F \rightarrow id$
\$ (E + F) * id \$	Reduce by $T \rightarrow F$
\$ (E + T) * id \$	Reduce by $E \rightarrow E + T$
\$ (E) * id \$	Shift
\$ (E)	* id \$	Reduce by $F \rightarrow (E)$

Shift-Reduce Parsing

STACK	INPUT	ACTION
\$	(id + id) * id \$	Shift
\$ (id + id) * id \$	Shift
\$ (id	+ id) * id \$	Reduce by $F \rightarrow id$
\$ (F	+ id) * id \$	Reduce by $T \rightarrow F$
\$ (T	+ id) * id \$	Reduce by $E \rightarrow T$
\$ (E +	id) * id \$	Shift
\$ (E + id) * id \$	Reduce by $F \rightarrow id$
\$ (E + F) * id \$	Reduce by $T \rightarrow F$
\$ (E + T) * id \$	Reduce by $E \rightarrow E + T$
\$ (E) * id \$	Shift
\$ (E)	* id \$	Reduce by $F \rightarrow (E)$
\$ F	* id \$	Reduce by $T \rightarrow F$

Shift-Reduce Parsing

STACK	INPUT	ACTION
\$	(id + id) * id \$	Shift
\$ (id + id) * id \$	Shift
\$ (id	+ id) * id \$	Reduce by $F \rightarrow id$
\$ (F	+ id) * id \$	Reduce by $T \rightarrow F$
\$ (T	+ id) * id \$	Reduce by $E \rightarrow T$
\$ (E +	id) * id \$	Shift
\$ (E + id) * id \$	Reduce by $F \rightarrow id$
\$ (E + F) * id \$	Reduce by $T \rightarrow F$
\$ (E + T) * id \$	Reduce by $E \rightarrow E + T$
\$ (E) * id \$	Shift
\$ (E)	* id \$	Reduce by $F \rightarrow (E)$
\$ F	* id \$	Reduce by $T \rightarrow F$
\$ T	* id \$	Shift

Shift-Reduce Parsing

STACK	INPUT	ACTION
\$	(id + id) * id \$	Shift
\$ (id + id) * id \$	Shift
\$ (id	+ id) * id \$	Reduce by $F \rightarrow id$
\$ (F	+ id) * id \$	Reduce by $T \rightarrow F$
\$ (T	+ id) * id \$	Reduce by $E \rightarrow T$
\$ (E +	id) * id \$	Shift
\$ (E + id) * id \$	Reduce by $F \rightarrow id$
\$ (E + F) * id \$	Reduce by $T \rightarrow F$
\$ (E + T) * id \$	Reduce by $E \rightarrow E + T$
\$ (E) * id \$	Shift
\$ (E)	* id \$	Reduce by $F \rightarrow (E)$
\$ F	* id \$	Reduce by $T \rightarrow F$
\$ T	* id \$	Shift
\$ T *	id \$	Shift

Shift-Reduce Parsing

STACK	INPUT	ACTION
\$	(id + id) * id \$	Shift
\$ (id + id) * id \$	Shift
\$ (id	+ id) * id \$	Reduce by $F \rightarrow id$
\$ (F	+ id) * id \$	Reduce by $T \rightarrow F$
\$ (T	+ id) * id \$	Reduce by $E \rightarrow T$
\$ (E +	id) * id \$	Shift
\$ (E + id) * id \$	Reduce by $F \rightarrow id$
\$ (E + F) * id \$	Reduce by $T \rightarrow F$
\$ (E + T) * id \$	Reduce by $E \rightarrow E + T$
\$ (E) * id \$	Shift
\$ (E)	* id \$	Reduce by $F \rightarrow (E)$
\$ F	* id \$	Reduce by $T \rightarrow F$
\$ T	* id \$	Shift
\$ T *	id \$	Shift
\$ T * id	\$	Reduce by $F \rightarrow id$

Shift-Reduce Parsing

STACK	INPUT	ACTION
\$	(id + id) * id \$	Shift
\$ (id + id) * id \$	Shift
\$ (id	+ id) * id \$	Reduce by $F \rightarrow id$
\$ (F	+ id) * id \$	Reduce by $T \rightarrow F$
\$ (T	+ id) * id \$	Reduce by $E \rightarrow T$
\$ (E +	id) * id \$	Shift
\$ (E + id) * id \$	Reduce by $F \rightarrow id$
\$ (E + F) * id \$	Reduce by $T \rightarrow F$
\$ (E + T) * id \$	Reduce by $E \rightarrow E + T$
\$ (E) * id \$	Shift
\$ (E)	* id \$	Reduce by $F \rightarrow (E)$
\$ F	* id \$	Reduce by $T \rightarrow F$
\$ T	* id \$	Shift
\$ T *	id \$	Shift
\$ T * id	\$	Reduce by $F \rightarrow id$
\$ T * F	\$	Reduce by $T \rightarrow T * F$

Shift-Reduce Parsing

STACK	INPUT	ACTION
\$	(id + id) * id \$	Shift
\$ (id + id) * id \$	Shift
\$ (id	+ id) * id \$	Reduce by $F \rightarrow id$
\$ (F	+ id) * id \$	Reduce by $T \rightarrow F$
\$ (T	+ id) * id \$	Reduce by $E \rightarrow T$
\$ (E +	id) * id \$	Shift
\$ (E + id) * id \$	Reduce by $F \rightarrow id$
\$ (E + F) * id \$	Reduce by $T \rightarrow F$
\$ (E + T) * id \$	Reduce by $E \rightarrow E + T$
\$ (E) * id \$	Shift
\$ (E)	* id \$	Reduce by $F \rightarrow (E)$
\$ F	* id \$	Reduce by $T \rightarrow F$
\$ T	* id \$	Shift
\$ T *	id \$	Shift
\$ T * id	\$	Reduce by $F \rightarrow id$
\$ T * F	\$	Reduce by $T \rightarrow T * F$
\$ T	\$	Reduce by $E \rightarrow T$

Shift-Reduce Parsing

STACK	INPUT	ACTION
\$	(id + id) * id \$	Shift
\$ (id + id) * id \$	Shift
\$ (id	+ id) * id \$	Reduce by $F \rightarrow id$
\$ (F	+ id) * id \$	Reduce by $T \rightarrow F$
\$ (T	+ id) * id \$	Reduce by $E \rightarrow T$
\$ (E +	id) * id \$	Shift
\$ (E + id) * id \$	Reduce by $F \rightarrow id$
\$ (E + F) * id \$	Reduce by $T \rightarrow F$
\$ (E + T) * id \$	Reduce by $E \rightarrow E + T$
\$ (E) * id \$	Shift
\$ (E)	* id \$	Reduce by $F \rightarrow (E)$
\$ F	* id \$	Reduce by $T \rightarrow F$
\$ T	* id \$	Shift
\$ T *	id \$	Shift
\$ T * id	\$	Reduce by $F \rightarrow id$
\$ T * F	\$	Reduce by $T \rightarrow T * F$
\$ T	\$	Reduce by $E \rightarrow T$
\$ E	\$	accept