
- Now that we have shown that we can develop a singleblock engineering simulation code, let's break up the problem into multiple blocks.
- For your simulation code developed under project-1, you need to write a code that will break up the domain into multiple blocks that will still run on a <u>single</u> processor
- This is an intermediate step prior to developing a code for multiple processors

- For the Heat Conduction (Default) problem, develop a code that will divide the domain into N x M blocks, each with dimensions of 1+(IMAX-1)/N x 1+(JMAX-1)/M
  - Where IMAX = JMAX = 101 and 501 for default heat-conduction problem
  - The code should be completely general so that N and M can be arbitrary
- Develop a multi-block data structure that writes out a connectivity file with the following information for each block:
  - Global block number of each block
  - Neighbor block numbers of each block
  - Boundary conditions for each side of block
    - Could be unique to each side
    - Could have regions for each side
      - Number of sub-regions for each side (if you decide to have sub-regions)
      - Dimensions of each sub-region
      - Boundary condition for each sub-region
    - Could be defined point-by-point
  - Block orientation (all blocks will probably have the same orientation for our problems).
- And multi-block grid and temperature files (Plot3D or other format) that has the coordinates and initial temperature along with
  - Number of global blocks
  - Block dimensions of each global block

You should end up with something similar to:



in the x', y' frame with associated connectivity and boundary condition file(s)

 Project-3 will be to write a multi-block serial code that will solve your simulation problem

# Due Monday 10/28:

- An overview of your simulation problem
  - Describe the problem, algorithm, and boundary conditions
- Listing of your spatial/grid decomposition code
- A plot of your decomposed computational grid (or data decomposition) for two-different decompositions:
  - 10 x 10 (N=10, M=10) grid for heat-conduction problem
  - 5 x 4 (N=5, M=4) grid for heat-conduction problem
  - Using the 101 x 101 and 501 x 501 grids
- A sample listing of your connectivity/boundary condition file(s)