

final_model

March 5, 2026

```
[25]: import os
import time
from pathlib import Path

import numpy as np
import pandas as pd
import requests
import os
# print(os.getenv("CENSUS_API_KEY"))

os.environ["CENSUS_API_KEY"] = "b1278b466e026ad679a62a03dd4b044bb8b36e7c"
CENSUS_API_KEY = os.getenv("CENSUS_API_KEY")
print("Key loaded:", CENSUS_API_KEY is not None)

pd.set_option("display.max_columns", 200)
pd.set_option("display.width", 200)
pd.set_option("display.max_colwidth", 120)

# -----
# Paths / config
# -----
DATA_DIR = Path("data")
RAW_DIR = DATA_DIR / "raw"
OUT_DIR = DATA_DIR / "processed"
RAW_DIR.mkdir(parents=True, exist_ok=True)
OUT_DIR.mkdir(parents=True, exist_ok=True)

# Update this path if needed
IGS_PATH = r"C:
↳\Users\jabba\Desktop\Code\machine_learning\AUC_mastercard_challenge\src\Inclusive_Growth_Sc
↳csv"

# Put your real key in an environment variable instead of hardcoding it in the_
↳notebook
# Example in PowerShell:
# $env:CENSUS_API_KEY="your_key_here"
CENSUS_API_KEY = os.getenv("5f5152d426a2b4a34d8b5697a6d2b5d48527941cc5a1369b")
```

```

# Tract selection for focused EDA / testing
TARGET_TRACTS = None
# Example:
# TARGET_TRACTS = ["13089023301", "13089023405", "13089023302"]

# If TARGET_TRACTS is set, the code will infer state FIPS from those tracts
SAVE_INTERMEDIATE = True

# ACS 5-year currently available through 2024
ACS_MAX_AVAILABLE_YEAR = 2024
FILL_2025_WITH_2024_ACS = False # optional, keep False by default

```

Key loaded: True

0.0.1 Cell 2 — IGS load / clean helpers

```

[26]: IGS_STRING_COLS = {
    "County",
    "State",
    "BENCHMARK",
    "Census Tract FIPS code",
    "geoid",
}

IGS_ALIAS_MAP = {
    "Inclusive Growth Score": "igs_total",
    "Growth": "igs_growth",
    "Inclusion": "igs_inclusion",
    "Place": "igs_place",
    "Economy": "igs_economy",
    "Community": "igs_community",
    "Place Growth": "igs_place_growth",
    "Place Inclusion": "igs_place_inclusion",
    "Economy Growth": "igs_economy_growth",
    "Economy Inclusion": "igs_economy_inclusion",
    "Community Growth": "igs_community_growth",
    "Community Inclusion": "igs_community_inclusion",
}

def dedupe_columns(cols):
    seen = {}
    out = []
    for c in cols:
        c = str(c).strip()
        if c not in seen:

```

```

        seen[c] = 0
        out.append(c)
    else:
        seen[c] += 1
        out.append(f"{c}.{seen[c]}")
    return out

def _find_header_row(df_raw, required_tokens=("Census Tract FIPS", "Year")):
    tokens = [t.lower() for t in required_tokens]
    for i in range(min(len(df_raw), 50)):
        row = df_raw.iloc[i].astype(str).str.lower().tolist()
        if all(any(tok in cell for cell in row) for tok in tokens):
            return i
    raise ValueError("Could not find the real IGS header row.")

def normalize_geoid_series(series: pd.Series) -> pd.Series:
    s = series.astype("string").str.strip()

    numeric = pd.to_numeric(s, errors="coerce")
    numeric_mask = numeric.notna()

    s = s.copy()
    s.loc[numeric_mask] = numeric.loc[numeric_mask].astype("Int64").
    ↪astype("string")

    s = s.str.replace(r"\.0$", "", regex=True)
    s = s.str.replace(r"\D", "", regex=True)
    s = s.str.zfill(11)
    s = s.where(s.str.fullmatch(r"\d{11}"), pd.NA)

    return s

def filter_tracts(df: pd.DataFrame, tracts=None, geoid_col="geoid") -> pd.
    ↪DataFrame:
    if not tracts:
        return df.copy()

    tract_set = {str(t).zfill(11) for t in tracts}
    out = df[df[geoid_col].astype("string").isin(tract_set)].copy()
    return out

def safe_save_parquet(df: pd.DataFrame, path: Path):
    out = df.copy()

```

```

for c in out.columns:
    if out[c].dtype == "object":
        out[c] = out[c].astype("string")

out.to_parquet(path, index=False, engine="pyarrow")

def load_igs_any(path: str) -> pd.DataFrame:
    p = Path(path)

    if p.suffix.lower() in [".xlsx", ".xls"]:
        raw = pd.read_excel(p, header=None)
    else:
        raw = pd.read_csv(p, header=None, low_memory=False)

    hdr_i = _find_header_row(raw, required_tokens=("Census Tract FIPS", "Year"))
    header = dedupe_columns(raw.iloc[hdr_i].tolist())

    df = raw.iloc[hdr_i + 1 :].copy()
    df.columns = header
    df = df.dropna(how="all").reset_index(drop=True)

    # Drop any duplicated header rows that still appear in the body
    if "Census Tract FIPS code" in df.columns:
        df = df[
            df["Census Tract FIPS code"].astype(str).str.strip().str.lower() !=
↪ "census tract fips code"
        ].copy()

    # Normalize GEOID + year
    df["geoid"] = normalize_geoid_series(df["Census Tract FIPS code"])
    df["year"] = pd.to_numeric(df["Year"], errors="coerce")

    # Convert non-ID columns to numeric where possible
    for c in df.columns:
        if c not in IGS_STRING_COLS:
            df[c] = pd.to_numeric(df[c], errors="coerce")

    # Friendly aliases for easier modeling later
    for old_col, new_col in IGS_ALIAS_MAP.items():
        if old_col in df.columns:
            df[new_col] = pd.to_numeric(df[old_col], errors="coerce")

    if "Is an Opportunity Zone" in df.columns:
        df["is_opp_zone"] = pd.to_numeric(df["Is an Opportunity Zone"],
↪ errors="coerce")

```

```

if "URBAN_CODE" in df.columns:
    df["urban_code"] = pd.to_numeric(df["URBAN_CODE"], errors="coerce")

if "BENCHMARK" in df.columns:
    df["benchmark"] = df["BENCHMARK"].astype("string")

# Final cleanup
df = df.dropna(subset=["geoid", "year"]).copy()
df["year"] = df["year"].astype(int)
df = df.sort_values(["geoid", "year"]).reset_index(drop=True)

return df

```

0.0.2 Cell 3 — Load and save clean IGS

```

[ ]: igs = load_igs_any(IGS_PATH)
      igs = filter_tracts(igs, TARGET_TRACTS)

      if SAVE_INTERMEDIATE:
          safe_save_parquet(igs, OUT_DIR / "igs_clean.parquet")

      print("IGS shape:", igs.shape)
      print("IGS years:", sorted(igs["year"].dropna().unique().tolist())[:10], "...",
            ↪sorted(igs["year"].dropna().unique().tolist())[-3:])
      print()
      print(igs[["geoid", "year", "igs_total"]].head())
      print()
      print(igs[["igs_total", "igs_place", "igs_economy", "igs_community"]].
            ↪describe())
      print()
      print("Top missingness:")
      print(igs.isna().mean().sort_values(ascending=False).head(20))

```

0.0.3 Cell 4 — ACS variables to pull

```

[ ]: ACS_VAR_GROUPS = {
      "population_age": [
          "B01001_001E", # total pop
          "B01001_003E", "B01001_004E", "B01001_005E", "B01001_006E", # male
          ↪under 18
          "B01001_027E", "B01001_028E", "B01001_029E", "B01001_030E", # female
          ↪under 18
          "B01001_020E", "B01001_021E", "B01001_022E", "B01001_023E",
          ↪"B01001_024E", "B01001_025E", # male 65+

```

```

        "B01001_044E", "B01001_045E", "B01001_046E", "B01001_047E",
↪ "B01001_048E", "B01001_049E", # female 65+
    ],
    "race": [
        "B02001_001E",
        "B02001_002E",
        "B02001_003E",
        "B02001_005E",
        "B02001_008E",
    ],
    "education": [
        "B15003_001E",
        "B15003_022E", "B15003_023E", "B15003_024E", "B15003_025E",
    ],
    "employment": [
        "B23025_001E",
        "B23025_002E",
        "B23025_003E",
        "B23025_005E",
    ],
    "income_poverty": [
        "B19013_001E", # median household income
        "B19301_001E", # per-capita income
        "B19083_001E", # gini
        "B17001_001E", # poverty universe
        "B17001_002E", # below poverty
    ],
    "commute": [
        "B08303_001E",
        "B08303_002E", "B08303_003E", "B08303_004E", "B08303_005E",
        "B08303_006E", "B08303_007E", "B08303_008E",
    ],
    "internet": [
        "B28002_001E",
        "B28002_002E",
    ],
    "housing": [
        "B25002_001E", "B25002_002E", "B25002_003E", # total / occupied /
↪ vacant
        "B25003_001E", "B25003_002E", "B25003_003E", # tenure
        "B25064_001E", # median gross rent
        "B25077_001E", # median home value
    ],
    "rent_burden": [
        "B25070_001E",
        "B25070_002E", "B25070_003E", "B25070_004E", "B25070_005E",
↪ "B25070_006E",

```

```

    ],
    "owner_cost_burden": [
        "B25091_001E",
        "B25091_003E", "B25091_004E", "B25091_005E", "B25091_006E",
        ↪ "B25091_007E",
        "B25091_014E", "B25091_015E", "B25091_016E", "B25091_017E",
        ↪ "B25091_018E",
    ],
    "early_education": [
        "B14003_004E", "B14003_013E", "B14003_032E", "B14003_041E",
    ],
    "health_insurance": [
        "B27001_001E",
        "B27001_005E", "B27001_008E", "B27001_011E", "B27001_014E",
        ↪ "B27001_017E",
        "B27001_020E", "B27001_023E", "B27001_026E", "B27001_029E",
        "B27001_033E", "B27001_036E", "B27001_039E", "B27001_042E",
        ↪ "B27001_045E",
        "B27001_048E", "B27001_051E", "B27001_054E", "B27001_057E",
    ],
}

ACS_VARS = sorted({v for group in ACS_VAR_GROUPS.values() for v in group})
print("ACS variable count:", len(ACS_VARS))

```

0.0.4 Cell 5 — ACS API helpers

```

[ ]: def chunks(lst, n):
    for i in range(0, len(lst), n):
        yield lst[i : i + n]

def infer_state_fips_from_tracts(tracts):
    if not tracts:
        return None
    return sorted({str(t).zfill(11)[:2] for t in tracts})

def resolve_acs_years(igs_years, max_available_year=ACS_MAX_AVAILABLE_YEAR):
    igs_years = sorted({int(y) for y in igs_years if pd.notna(y)})
    acs_years = [y for y in igs_years if y <= max_available_year]
    return acs_years

def get_state_fips(year: int, api_key: str) -> list[str]:
    url = f"https://api.census.gov/data/{year}/acs/acs5"

```

```

params = {"get": "NAME", "for": "state:*", "key": api_key}

r = requests.get(url, params=params, timeout=60)
r.raise_for_status()

data = r.json()
header, rows = data[0], data[1:]
df = pd.DataFrame(rows, columns=header)

return sorted(df["state"].unique().tolist())

def census_get_tracts(year: int, state_fips: str, vars_: list[str], api_key: str) -> pd.DataFrame:
    base = f"https://api.census.gov/data/{year}/acs/acs5"
    get_str = "NAME," + ",".join(vars_)

    params = [
        ("get", get_str),
        ("for", "tract:*"),
        ("in", f"state:{state_fips}"),
        ("in", "county:*"),
        ("key", api_key),
    ]

    r = requests.get(base, params=params, timeout=120)
    r.raise_for_status()

    data = r.json()
    header, rows = data[0], data[1:]
    df = pd.DataFrame(rows, columns=header)
    df["year"] = year

    return df

def to_numeric_safe(df: pd.DataFrame, exclude=("NAME", "state", "county", "tract", "year")) -> pd.DataFrame:
    out = df.copy()
    for c in out.columns:
        if c in exclude:
            continue
        out[c] = pd.to_numeric(out[c], errors="coerce")
    return out

def download_acs_all(

```



```

years: list[int],
api_key: str,
state_fips_filter: list[str] | None = None,
max_vars_per_call: int = 45,
sleep_seconds: float = 0.25,
) -> pd.DataFrame:
    if not api_key:
        raise ValueError("Missing CENSUS_API_KEY. Put it in your environment,
↳ before running ACS pulls.")

    all_parts = []

    for year in years:
        year_out = RAW_DIR / f"acs5_tract_{year}.parquet"

        if year_out.exists():
            print(f"[cache] {year_out.name}")
            df_year = pd.read_parquet(year_out)
            all_parts.append(df_year)
            continue

        states = state_fips_filter if state_fips_filter else
↳ get_state_fips(year, api_key)
        print(f"[download] year={year} | states={len(states)}")

        state_frames = []

        for st in states:
            merged_state = None

            for var_chunk in chunks(ACS_VARS, max_vars_per_call):
                df_chunk = census_get_tracts(year, st, var_chunk, api_key)
                df_chunk = to_numeric_safe(df_chunk)

                keys = ["state", "county", "tract", "NAME", "year"]
                if merged_state is None:
                    merged_state = df_chunk
                else:
                    merged_state = merged_state.merge(df_chunk, on=keys,
↳ how="outer")

                time.sleep(sleep_seconds)

            state_frames.append(merged_state)

        df_year = pd.concat(state_frames, ignore_index=True)

```

```

    if SAVE_INTERMEDIATE:
        safe_save_parquet(df_year, year_out)

    all_parts.append(df_year)

acs = pd.concat(all_parts, ignore_index=True)
return acs

```

0.0.5 Cell 6 — ACS feature engineering

```

[ ]: def safe_div(n, d):
    n = np.asarray(n, dtype="float64")
    d = np.asarray(d, dtype="float64")
    return np.where((d == 0) | np.isnan(d), np.nan, n / d)

def make_features(acs: pd.DataFrame) -> pd.DataFrame:
    acs = acs.copy()

    acs["state"] = acs["state"].astype(str).str.zfill(2)
    acs["county"] = acs["county"].astype(str).str.zfill(3)
    acs["tract"] = acs["tract"].astype(str).str.zfill(6)
    acs["geoid"] = acs["state"] + acs["county"] + acs["tract"]

    out = pd.DataFrame({
        "geoid": acs["geoid"],
        "year": acs["year"],
    })

    # -----
    # Population / age
    # -----
    out["pop_total"] = acs["B01001_001E"]

    out["pop_under18"] = (
        acs["B01001_003E"] + acs["B01001_004E"] + acs["B01001_005E"] +
        ↪ acs["B01001_006E"] +
        acs["B01001_027E"] + acs["B01001_028E"] + acs["B01001_029E"] +
        ↪ acs["B01001_030E"]
    )
    out["share_under18"] = safe_div(out["pop_under18"], out["pop_total"])

    out["pop_65plus"] = (
        acs["B01001_020E"] + acs["B01001_021E"] + acs["B01001_022E"] +
        ↪ acs["B01001_023E"] + acs["B01001_024E"] + acs["B01001_025E"] +

```

```

        acs["B01001_044E"] + acs["B01001_045E"] + acs["B01001_046E"] +
↪acs["B01001_047E"] + acs["B01001_048E"] + acs["B01001_049E"]
    )
    out["share_65plus"] = safe_div(out["pop_65plus"], out["pop_total"])

    # -----
    # Race shares
    # -----
    out["share_white"] = safe_div(acs["B02001_002E"], acs["B02001_001E"])
    out["share_black"] = safe_div(acs["B02001_003E"], acs["B02001_001E"])
    out["share_asian"] = safe_div(acs["B02001_005E"], acs["B02001_001E"])
    out["share_two_plus"] = safe_div(acs["B02001_008E"], acs["B02001_001E"])

    # -----
    # Education
    # -----
    ba_plus = acs["B15003_022E"] + acs["B15003_023E"] + acs["B15003_024E"] +
↪acs["B15003_025E"]
    out["ba_plus_share_25p"] = safe_div(ba_plus, acs["B15003_001E"])

    # -----
    # Employment / economy
    # -----
    out["lfpr_16p"] = safe_div(acs["B23025_002E"], acs["B23025_001E"])
    out["unemp_rate"] = safe_div(acs["B23025_005E"], acs["B23025_003E"])

    out["median_household_income"] = acs["B19013_001E"]
    out["per_capita_income"] = acs["B19301_001E"]
    out["gini"] = acs["B19083_001E"]
    out["poverty_rate"] = safe_div(acs["B17001_002E"], acs["B17001_001E"])

    # -----
    # Commute / internet
    # -----
    commute_under35 = (
        acs["B08303_002E"] + acs["B08303_003E"] + acs["B08303_004E"] +
↪acs["B08303_005E"] +
        acs["B08303_006E"] + acs["B08303_007E"] + acs["B08303_008E"]
    )
    out["commute_under35_share"] = safe_div(commute_under35, acs["B08303_001E"])
    out["internet_sub_share"] = safe_div(acs["B28002_002E"], acs["B28002_001E"])

    # -----
    # Housing / affordability
    # -----
    out["housing_units_total"] = acs["B25002_001E"]
    out["occupied_units"] = acs["B25002_002E"]

```

```

out["vacant_units"] = acs["B25002_003E"]
out["occupied_share"] = safe_div(acs["B25002_002E"], acs["B25002_001E"])
out["vacancy_rate"] = safe_div(acs["B25002_003E"], acs["B25002_001E"])

out["owner_share"] = safe_div(acs["B25003_002E"], acs["B25003_001E"])
out["renter_share"] = safe_div(acs["B25003_003E"], acs["B25003_001E"])

out["median_gross_rent"] = acs["B25064_001E"]
out["median_home_value"] = acs["B25077_001E"]

rent_affordable = (
    acs["B25070_002E"] + acs["B25070_003E"] + acs["B25070_004E"] +
    acs["B25070_005E"] + acs["B25070_006E"]
)

owner_affordable = (
    acs["B25091_003E"] + acs["B25091_004E"] + acs["B25091_005E"] +
    ↪ acs["B25091_006E"] + acs["B25091_007E"] +
    acs["B25091_014E"] + acs["B25091_015E"] + acs["B25091_016E"] +
    ↪ acs["B25091_017E"] + acs["B25091_018E"]
)

denom_housing_cost = acs["B25070_001E"] + acs["B25091_001E"]
out["affordable_housing_share"] = safe_div(rent_affordable +
    ↪ owner_affordable, denom_housing_cost)

# -----
# Community / health
# -----
# Early education proxy: enrolled 3-4 year olds over under-5 population
enrolled_3_4 = acs["B14003_004E"] + acs["B14003_013E"] + acs["B14003_032E"]
    ↪ acs["B14003_041E"]
pop_under5 = acs["B01001_003E"] + acs["B01001_027E"]
out["early_ed_enroll_share"] = safe_div(enrolled_3_4, pop_under5)

uninsured = (
    acs["B27001_005E"] + acs["B27001_008E"] + acs["B27001_011E"] +
    ↪ acs["B27001_014E"] + acs["B27001_017E"] +
    acs["B27001_020E"] + acs["B27001_023E"] + acs["B27001_026E"] +
    ↪ acs["B27001_029E"] +
    acs["B27001_033E"] + acs["B27001_036E"] + acs["B27001_039E"] +
    ↪ acs["B27001_042E"] + acs["B27001_045E"] +
    acs["B27001_048E"] + acs["B27001_051E"] + acs["B27001_054E"] +
    ↪ acs["B27001_057E"]
)
out["insured_share"] = 1.0 - safe_div(uninsured, acs["B27001_001E"])

```

```

# -----
# Growth features
# -----
out = out.sort_values(["geoid", "year"]).reset_index(drop=True)

growth_cols = [
    "median_household_income",
    "per_capita_income",
    "occupied_units",
    "median_home_value",
    "median_gross_rent",
]

for col in growth_cols:
    out[f"{col}_growth"] = out.groupby("geoid")[col].pct_change()

return out

```

0.0.6 Cell 7 — Merge helpers

```

[ ]: def maybe_fill_2025_with_2024(feats: pd.DataFrame) -> pd.DataFrame:
    if not FILL_2025_WITH_2024_ACS:
        return feats

    if 2024 not in feats["year"].unique():
        return feats

    carry = feats[feats["year"] == 2024].copy()
    carry["year"] = 2025

    out = pd.concat([feats, carry], ignore_index=True)
    out = out.sort_values(["geoid", "year"]).reset_index(drop=True)
    return out

def merge_igs_acs(igs: pd.DataFrame, feats: pd.DataFrame) -> pd.DataFrame:
    merged = igs.merge(feats, on=["geoid", "year"], how="left")
    return merged

```

0.0.7 Cell 8 — Run ACS pull, feature engineering, and merge

```

[ ]: igs_years = sorted(igs["year"].dropna().unique().tolist())
acs_years = resolve_acs_years(igs_years,
    ↪max_available_year=ACS_MAX_AVAILABLE_YEAR)
state_fips_filter = infer_state_fips_from_tracts(TARGET_TRACTS)

```

```

print("IGS years in file:", igs_years)
print("ACS years to pull:", acs_years)
print("State filter from target tracts:", state_fips_filter)

acs = download_acs_all(
    years=acs_years,
    api_key=CENSUS_API_KEY,
    state_fips_filter=state_fips_filter,
    max_vars_per_call=45,
    sleep_seconds=0.25,
)

if SAVE_INTERMEDIATE:
    safe_save_parquet(ac, OUT_DIR / "acs_raw.parquet")

feats = make_features(ac)
feats = filter_tracts(feats, TARGET_TRACTS)

feats = maybe_fill_2025_with_2024(feats)

if SAVE_INTERMEDIATE:
    safe_save_parquet(feats, OUT_DIR / "acs_features.parquet")

# Keep only years where ACS exists in the merged modeling panel
model_igs = igs[igs["year"].isin(sorted(feats["year"].dropna().unique()))].
    ↪copy()

model_df = merge_igs_acs(model_igs, feats)

if SAVE_INTERMEDIATE:
    safe_save_parquet(model_df, OUT_DIR / "igs_x_acs.parquet")

print("ACS raw shape:", acs.shape)
print("ACS features shape:", feats.shape)
print("Merged model_df shape:", model_df.shape)

```

0.0.8 Cell 9 — Final checks before EDA

```

[ ]: print("Merged years:", sorted(model_df["year"].dropna().unique().tolist()))
print()
print(model_df[[
    "geoid", "year", "igs_total", "igs_place", "igs_economy", "igs_community",
    "affordable_housing_share", "internet_sub_share", "insured_share",
    "median_household_income", "poverty_rate", "vacancy_rate"
]].head())

```

```

print()
print("Top missingness in merged data:")
print(model_df.isna().mean().sort_values(ascending=False).head(30))

print()
print("Core numeric summary:")
core_cols = [
    "igs_total",
    "igs_place",
    "igs_economy",
    "igs_community",
    "affordable_housing_share",
    "internet_sub_share",
    "insured_share",
    "median_household_income",
    "per_capita_income",
    "poverty_rate",
    "vacancy_rate",
    "unemp_rate",
]
print(model_df[core_cols].describe())

```

0.0.9 Cell 10 — Optional: save an EDA subset for only chosen tracts

```

[ ]: eda_df = filter_tracts(model_df, TARGET_TRACTS)

if SAVE_INTERMEDIATE:
    safe_save_parquet(eda_df, OUT_DIR / "eda_panel.parquet")

print("EDA panel shape:", eda_df.shape)
eda_df.head()

```

[]:

[]:

[]:

[]:

[]:

[]:

[]: 5f5152d426a2b4a34d8b5697a6d2b5d48527941cc5a1369b