



University of
Pittsburgh

Algorithms and Data Structures 2

CS 1501



Fall 2022

Sherif Khattab

ksm73@pitt.edu

(Slides are adapted from Dr. Ramirez's and Dr. Farnan's CS1501 slides.)

Announcements

- Upcoming Deadlines
 - Lab 8: next Monday 11/14 @ 11:59 pm
 - Homework 8: next Monday 11/14 @ 11:59 pm

Previous lecture

- Minimum Spanning Tree (MST) problem
 - Prim's MST algorithm
 - running time analysis of the Best Edges implementation
 - an implementation that uses a heap
 - Kruskal's MST algorithm

This Lecture

- Weighted Shortest Paths problem
 - Dijkstra's single-source shortest paths algorithm

Muddiest Points

- **Q: Please review an example of eager prims and kruskals again**
- **Sure!**


Problem of the Day: Weighted Shortest Paths

- Input:
 - A road network
 - Road segments and intersections
 - Road segments are labeled by travel time
 - From length and maximum speed
 - How do we get max speed?
 - Starting address and destination address
- Output:
 - A shortest path from source to destination

Dijkstra's algorithm

- Set a distance value of `Double.POSITIVE_INFINITY` for all vertices
- $\text{distance}[\text{start}] = 0$
- Set $\text{cur} = \text{start}$
- While destination is not visited:
 - For each unvisited neighbor x of cur :
 - Compute tentative distance from start to x through cur
 - $\text{distance}[\text{cur}] + \text{weight of edge between cur and } x$
 - Update $\text{distance}[x]$ if tentative distance $< \text{distance}[x]$
 - Mark cur as visited
 - Let cur be the unvisited vertex with the smallest tentative distance from start

Dijkstra's example



	Distance	Parent
0	0	--
1	7	0
2	9	0
3	11	2
4	21	2
5	20	3


Analysis of Dijkstra's algorithm

- How to implement?
 - Best path/parent array?
 - Runtime?
 - PQ?
 - Turns out to be very similar to Eager Prims
 - Storing paths instead of edges
 - Runtime?
- Dijkstra's is correct only when all edge weights ≥ 0

Bellman-Ford's algorithm

- Set a distance value of `Double.POSITIVE_INFINITY` for all vertices
- Initialize a FIFO Q
- $\text{distance}[\text{start}] = 0$
- add start to Q
- While Q is not empty:
 - $\text{cur} = \text{pop a vertex from Q}$
 - For each neighbor x of cur:
 - Compute tentative distance from start to x through cur
 - $\text{distance}[\text{cur}] + \text{weight of edge between cur and x}$
 - if tentative distance $< \text{distance}[x]$
 - Update $\text{distance}[x]$
 - add x to Q if not already there

Bellman-Ford's example



Distance	Parent
0	--
7	0
9	0
11	2
21	2
20	3

FIFO Q:

0
1
2
3
4
5

Analysis of Bellman-Ford's algorithm

- How to implement?
- Runtime?
- Bellman-Ford's is correct even when there are negative edge weights in the graph