HENAN YULIN CHEMICAL CO., LTD

GROUP 4,BEIWAN VILLAGE,BEISHANKOU TOWN, GONGYI DISTRICT, ZHENGZHOU CITY, HENAN PROVINCE, CHINA, 451250.

TEL: +86(0)37166550866 FAX: +86(0)37166550866

EMAIL: info@cnycchem.com WEBSITE:http://www.cnycchem.com ZIP：451200

SOLID ALUMINIUM DIHYDROGEN PHOSPHATE

1. Basic Information

English : Solid Aluminium Dihydrogen Phos

Alias : High temperature resistant binder

Molecular formula: Al (H2PO4)3

Molecular weight : 317.94

CAS No. : 13530-50-2

H.S. Code : 28351000

EINECS : 236-875-2

2. Physicochemical Properties

Appearance : colorless, odorless, white powder.

Relative density: 1.44 ~ 1.47g/cm3

Solubility : soluble in water.

Attributes : At normal temperature, mixed with refractory aggregate and curing agent, then forms high bonding strength at 90-110 ℃ for 4-24 hours. After drying at 350-500 ℃, which has high bending resistance, compression resistance and hydration resistance, even if soaked or boiled in water is not soft.

3. Application

Mainly used for high temperature binder refractory, flame retardant material, refractory firebrick, refractory cement, steel furnace surface repair, and widely used in electrical appliances,metallurgy,aviation,building materials hi-temp furances and equipment.

4. Technical Standards

Item	Industrial Grade
Apperance	White powder
Phosphorus pentoxide (P2O5) %	65±2
Aluminum oxide (AL2O3) %	16±1
Ferric oxide (Fe2O3) %	0.02
Relative density (25℃) %	——
PH value (10g/L solution)	1.4-2.6

5.Product Packaging

Three-layer bags lined with polyethylene film are used as inner packaging, and the outer packaging is plastic woven bag, with net content of 25kg per bag.

6. Storage Conditions

In the process of transportation, prevent rain, not be affected with damp and the packaging is not defaced; Sealed and stored after use to prevent moisture; Store in a dry and ventilated warehouse.