

R Shiny, Sparklyr, and RConnect

L.J. Arendse



Building ML pipelines, SparklyR usage and
integration with Shiny, and deploying to
RConnect





Shiny from R Studio

R Package: For rapid and easy development of interactive web apps
“Shiny combines the computational power of R with the interactivity of the modern web”




<https://shiny.rstudio.com/>

Shiny from R Studio



Shiny from R Studio



 global.R


 ui.R

 server.R




<https://shiny.rstudio.com/>

Shiny from R Studio



ui.R × global.R × server.R ×



Run App

```
3 # application by clicking "Run App" above.
4 #
5 # Find out more about building applications with Shiny here:
6 #
7 # http://shiny.rstudio.com/
8 #
9
10
11
12 # Define server logic required to draw a histogram
13 shinyServer(function(input, output) {
14
15   output$distPlot <- renderPlot({
16
17     # generate bins based on input$bins from ui.R
18     x <- faithful[, 2]
19     bins <- seq(min(x), max(x), length.out = input$bins + 1)
20
21     # draw the histogram with the specified number of bins
22     hist(x, breaks = bins, col = 'darkgray', border = 'white')
23
24   })
25
26 })
```

25:3  <function>(input, output) 

R Script 

Console



Environment History Connections

History Connections

Import Dataset

List

Global Environment

Environment is empty

Files Plots Packages Help Viewer

 New Folder  Upload  Delete 

```
home > r ihb shiny apps > r user group ..
```

	▲ Name
1	1
2	2
3	3
4	4
5	5
6	6
7	7
8	8
9	9
10	10
11	11
12	12
13	13
14	14
15	15
16	16
17	17
18	18
19	19
20	20
21	21
22	22
23	23
24	24
25	25
26	26
27	27
28	28
29	29
30	30
31	31
32	32
33	33
34	34
35	35
36	36
37	37
38	38
39	39
40	40
41	41
42	42
43	43
44	44
45	45
46	46
47	47
48	48
49	49
50	50
51	51
52	52
53	53
54	54
55	55
56	56
57	57
58	58
59	59
60	60
61	61
62	62
63	63
64	64
65	65
66	66
67	67
68	68
69	69
70	70
71	71
72	72
73	73
74	74
75	75
76	76
77	77
78	78
79	79
80	80
81	81
82	82
83	83
84	84
85	85
86	86
87	87
88	88
89	89
90	90
91	91
92	92
93	93
94	94
95	95
96	96
97	97
98	98
99	99
100	100

↑ ..

 global.R server.R R





Lightning-fast unified analytics engine

[Download](#)

[Libraries ▾](#)

[Documentation ▾](#)

[Examples](#)

[Community ▾](#)

[Developers ▾](#)

[Apache Software Foundation ▾](#)

Latest News

[Spark 2.4.0 released \(Nov 02, 2018\)](#)

[Spark 2.3.2 released \(Sep 24, 2018\)](#)

[Spark+AI Summit \(October 2-4th, 2018, London\) agenda posted \(Jul 24, 2018\)](#)

[Spark 2.2.2 released \(Jul 02, 2018\)](#)

[Archive](#)



sparklyr

dplyr

ML

Extensions

Apache Spark

- <https://www.rdocumentation.org/packages/sparklyr/versions/0.8.2>
- <https://spark.rstudio.com/>

sparklyr v0.8.2

Other versions ▾

by [Javier Luraschi](#)

[View Source](#)

NaN  Monthly downloads > 99.99th Percentile

 <https://www.rdocumentation.org/packages/sparklyr> [Copy](#)

R Interface to Apache Spark

R interface to Apache Spark, a fast and general engine for big data processing, see <http://spark.apache.org>. This package supports connecting to local and remote Apache Spark clusters, provides a 'dplyr' compatible back-end, and provides an interface to Spark's built-in machine learning algorithms.

Readme

sparklyr: R interface for Apache Spark

build **passing** CRAN **0.9.2** codecov **80%**  Join the chat at <https://gitter.im/rstudio/sparklyr> 

- Connect to [Spark](#) from R. The sparklyr package provides a complete [dplyr](#) backend.
- Filter and aggregate Spark datasets then bring them into R for analysis and visualization.
- Use Spark's distributed [machine learning](#) library from R.
- Create [extensions](#) that call the full Spark API and provide interfaces to Spark packages.

Installation

You can install the **sparklyr** package from CRAN as follows:

```
install.packages("sparklyr")
```

You should also install a local version of Spark for development purposes:

```
library(sparklyr)  
spark_install(version = "2.1.0")
```

ML Pipelines



```
flights_pipeline <- ml_pipeline(sc) %>%  
  ft_dplyr_transformer(  
    tbl = df  
  ) %>%  
  ft_binarizer(  
    input.col = "dep_delay",  
    output.col = "delayed",  
    threshold = 15  
  ) %>%  
  ft_bucketizer(  
    input.col = "sched_dep_time",  
    output.col = "hours",  
    splits = c(400, 800, 1200, 1600, 2000, 2400)  
  ) %>%  
  ft_r_formula(delayed ~ month + day + hours + distance) %>%  
  ml_logistic_regression()
```

Shiny and SparklyR



Packages

- `library(shiny)`
- `library(sparklyr)`

Env Setup

- `Sys.setenv(SPARK_HOME="/usr/hdp/2.6.0.3-8/spark2/")`
- `config <- spark_config()`
- `sc <- spark_connect(master = "yarn-client", config = config, version = "2.1.0")`

Load Data

- `pth <- "/group/mine/data/my_data_parquet"`
- `my_data_parquet <- spark_read_parquet(sc, "my_data", path = pth, memory = TRUE, overwrite = TRUE)`





“Distribute data science across your organisation”



[Products](#)[Resources](#)[Pricing](#)[About Us](#)[Blogs](#)

RStudio Connect

A content hub and execution engine for all your data products.

RStudio Connect is a new publishing platform for the work your teams create in R. Share Shiny applications, R Markdown reports, Plumber APIs, dashboards, plots, and more in one convenient place. Use push-button publishing from the RStudio IDE, scheduled execution of reports, and flexible security policies to bring the power of data science to your entire enterprise.

[TRY THE FREE 45 DAY EVALUATION](#)[SCHEDULE A MEETING WITH SALES](#)

Let's stay in touch. Give us your email and we'll keep you in the loop.



Please check this box if you accept the RStudio privacy policy:

[SUBSCRIBE](#)

Shiny Bot at your service! How can I help?



Thank you

Questions?

