

Using and Improving GladLibs

Introduction

GladLib: Stories from Templates

- Ready to tackle modifying the GladLibs story-telling program: learning while telling stories!



GladLib: Stories from Templates

- Ready to tackle modifying the GladLibs story-telling program: learning while telling stories!
 - All the pieces of the program are ones you could write yourself!
 - You'll start with a working program, and understand and extend the program
- Class design, method design, understanding program limitations but reveling in telling stories!
 - Creating re-usable story-telling components



Structure of GladLib.java


- Constructor initializes object
 - ArrayList for nouns, verbs, colors, ...
 - Random object for generating random choices
- Read story template, process each word
 - If <country> or <timeframes>s found: replace
- Print!

In <country> a long time ago, nearly <number> <timeframe>s ago, there lived a <color>, <adjective> <animal>. It so loved to sing and dance, but there was a <adjective>, <adjective> <animal> named <name> that scared it so much!

Stories from Template

- Running program generates stories
 - One public method: **makeStory**


In Kenya a long time ago, nearly 245 decades ago, there lived a pink, funny tiger. It so loved to sing and dance, but there was a angry, gigantic lion named Lance that scared it so much!



Stories from Template

- Running program generates stories
 - One public method: **makeStory**

In Ecuador a long time ago, nearly 105 months ago, there lived a jovial, yellow polar bear. It so loved to sing and dance, but there was a furious, angry rabbit named Albert that scared it so much!




Stories from Template

- Running program generates stories
 - One public method: **makeStory**

Stories from Template

- Running program generates stories
 - One public method: **makeStory**

In Ecuador a long time ago, nearly 105 months ago, there lived a yellow, jovial polar bear. It so loved to sing and dance, but there was a furious, angry rabbit named Albert that scared it so much!



Reading Words and Printing

- Template read from file or URL, simply loop over each word, if <label>, then replace
 - Finding labels straightforward use of .indexOf and .substring, for <noun>! or "<color>"

```
private String processWord(String w){  
    int first = w.indexOf("<");  
    int last = w.indexOf(">", first);  
    if (first == -1 || last == -1){  
        return w;  
    }  
    ...  
}
```

Reading Words and Printing

- Template read from file or URL, simply loop over each word, if <label>, then replace
 - Finding labels straightforward use of .indexOf and .substring, for <noun>! or "<color>"
 - Printing story displays words in console

```
private void printOut(String s, int lineWidth){  
    int charsWritten = 0;  
  
    ...
```

Reading Words and Printing

- Template read from file or URL, simply loop over each word, if <label>, then replace
 - Finding labels straightforward use of .indexOf and .substring, for <noun>! or "<color>"
- Printing story displays words in console
 - Method uses parameterized line-width

```
private void printOut(String s, int lineWidth){  
    int charsWritten = 0;  
  
    ...
```

Reading Words and Printing

- Template read from file or URL, simply loop over each word, if <label>, then replace
 - Finding labels straightforward use of .indexOf and .substring, for <noun>! or "<color>"
- Printing story displays words in console
 - Method uses parameterized line-width
 - Could modify to print to file

```
private void printOut(String s, int lineWidth){  
    int charsWritten = 0;  
  
    ...
```

Instance Variables

- ArrayLists for each <noun>, <color>, ...
 - Name variables appropriately,
 - Create and initialize in constructor
 - Need all of them to replace a word.

```
private ArrayList<String> adjectiveList;
private ArrayList<String> nounList;
private ArrayList<String> colorList;
private ArrayList<String> countryList;
private ArrayList<String> nameList;
private ArrayList<String> animalList;
private ArrayList<String> timeList;
private Random myRandom;
```

Instance Variables

- ArrayLists for each <noun>, <color>, ...
 - Name variables appropriately,
 - Create and initialize in constructor
 - Need all of them to replace a word.

```
private ArrayList<String> adjectiveList;
private ArrayList<String> nounList;
private ArrayList<String> colorList;
private ArrayList<String> countryList;
private ArrayList<String> nameList;
private ArrayList<String> animalList;
private ArrayList<String> timeList;
private Random myRandom;
```

Instance Variables

- ArrayLists for each <noun>, <color>, ...
 - Name variables appropriately,
 - Create and initialize in constructor
 - Need all of them to replace a word.

```
private ArrayList<String> adjectiveList;
private ArrayList<String> nounList;
private ArrayList<String> colorList;
private ArrayList<String> countryList;
private ArrayList<String> nameList;
private ArrayList<String> animalList;
private ArrayList<String> timeList;
private Random myRandom;
```

Instance Variables

- ArrayLists for each <noun>, <color>, ...
 - Name variables appropriately,
 - Create and initialize in constructor
 - Need all of them to replace a word.

```
private ArrayList<String> adjectiveList;
private ArrayList<String> nounList;
private ArrayList<String> colorList;
private ArrayList<String> countryList;
private ArrayList<String> nameList;
private ArrayList<String> animalList;
private ArrayList<String> timeList;
private Random myRandom;
```

Instance Variables

- ArrayLists for each <noun>, <color>, ...
 - Name variables appropriately,
 - Create and initialize in constructor
 - Need all of them to replace a word.

```
private ArrayList<String> adjectiveList;
private ArrayList<String> nounList;
private ArrayList<String> colorList;
private ArrayList<String> countryList;
private ArrayList<String> nameList;
private ArrayList<String> animalList;
private ArrayList<String> timeList;
private Random myRandom;
```

Find Substitute for <color>

- Based on <color> or <noun> or ... use the appropriate list of replacements

```
private String getSubstitute(String label) {  
    if (label.equals("country")) {  
        return randomFrom(countryList);  
    }  
    if (label.equals("color")){  
        return randomFrom(colorList);  
    }  
    if (label.equals("noun")){  
        return randomFrom(nounList);  
    }  
    if (label.equals("name")){  
        return randomFrom(nameList);  
    }  
    // more code here
```

Find Substitute for <color>

- Based on <color> or <noun> or ... use the appropriate list of replacements

```
private String getSubstitute(String label) {  
    if (label.equals("country")) {  
        return randomFrom(countryList);  
    }  
    if (label.equals("color")){  
        return randomFrom(colorList);  
    }  
    if (label.equals("noun")){  
        return randomFrom(nounList);  
    }  
    if (label.equals("name")){  
        return randomFrom(nameList);  
    }  
    // more code here
```

Find Substitute for <color>

- Based on <color> or <noun> or ... use the appropriate list of replacements

```
private String getSubstitute(String label) {  
    if (label.equals("country")) {  
        return randomFrom(countryList);  
    }  
    if (label.equals("color")){  
        return randomFrom(colorList);  
    }  
    if (label.equals("noun")){  
        return randomFrom(nounList);  
    }  
    if (label.equals("name")){  
        return randomFrom(nameList);  
    }  
    // more code here
```

Find Substitute for <color>

- Based on <color> or <noun> or ... use the appropriate list of replacements

```
private String getSubstitute(String label) {  
    if (label.equals("country")) {  
        return randomFrom(countryList);  
    }  
    if (label.equals("color")){  
        return randomFrom(colorList);  
    }  
    if (label.equals("noun")){  
        return randomFrom(nounList);  
    }  
    if (label.equals("name")){  
        return randomFrom(nameList);  
    }  
    // more code here
```

Find Substitute for <color>

- Based on <color> or <noun> or ... use the appropriate list of replacements
 - Choose value from list at random in method **randomFrom**, return for story-telling

```
private String randomFrom(ArrayList<String> source){  
    int index = myRandom.nextInt(source.size());  
    return source.get(index);  
}
```

Find Substitute for <color>

- Based on <color> or <noun> or ... use the appropriate list of replacements
 - Choose value from list at random in method **randomFrom**, return for story-telling
 - Both methods are private, used by sequence of calls from public method **makeStory**

```
private String randomFrom(ArrayList<String> source){  
    int index = myRandom.nextInt(source.size());  
    return source.get(index);  
}
```

Find Substitute for <color>

- Based on <color> or <noun> or ... use the appropriate list of replacements
 - Choose value from list at random in method **randomFrom**, return for story-telling
 - Both methods are private, used by sequence of calls from public method **makeStory**
 - Argument passed to source is instance variable

```
private String randomFrom(ArrayList<String> source){  
    int index = myRandom.nextInt(source.size());  
    return source.get(index);  
}
```

Initializing ArrayLists

- We must construct and initialize many instance variables
 - Source could be URL or local directory

`initializeFrom("data")` or `initializeFrom("http:...")`

```
private void initializeFromSource(String source) {  
    adjectiveList= readIt(source+"/adjective.txt");  
    nounList      = readIt(source+"/noun.txt");  
    colorList     = readIt(source+"/color.txt");  
    countryList   = readIt(source+"/country.txt");  
    nameList      = readIt(source+"/name.txt");  
    animalList    = readIt(source+"/animal.txt");  
    timeList      = readIt(source+"/timeframe.txt");  
}
```

ArrayList Instance Variables

- To create a new label, <verb>, must create new instance variable, e.g., **verbList**
 - Modify code in two methods with **verbList**
- **initializeFromSource**
 - called: GladLib constructors
- **getSubstitute**
 - called: makeStory, fromTemplate, processWord
- Program documentation should include information on how to modify code