

Computing Simple Stereo

Background Reading:

- T&V Section 7.1
- Szeliski Chap 11

Recall: Simple Stereo System




Image coords of point (X, Y, Z)

Left Camera:
$$x_l = f \frac{X}{Z} \quad y_l = f \frac{Y}{Z}$$

Right Camera:
$$x_r = f \frac{X - T_x}{Z} \quad y_r = f \frac{Y}{Z}$$


Recall: Stereo Disparity

Left camera

$$x_l = f \frac{X}{Z} \quad y_l = f \frac{Y}{Z}$$



Right camera

$$x_r = f \frac{X - T_x}{Z} \quad y_r = f \frac{Y}{Z}$$



Stereo Disparity

$$d = x_l - x_r = f \frac{X}{Z} - \left(f \frac{X}{Z} - f \frac{T_x}{Z} \right)$$



depth $Z = \frac{f T_x}{d}$ baseline disparity

Important equation!


Recall: Stereo Disparity

Left camera

$$x_l = f \frac{X}{Z} \quad y_l = f \frac{Y}{Z}$$

Right camera

$$x_r = f \frac{X - T_x}{Z} \quad y_r = f \frac{Y}{Z}$$



Note: Depth and stereo disparity are inversely proportional

depth

$$\textcircled{Z} = \frac{f T_x}{\textcircled{d}} \text{ disparity}$$

Important equation!

Stereo Example



Left Image




Right Image

From Middlebury stereo evaluation page
<http://www.middlebury.edu/stereo/>

Stereo Example



Disparity values (0-64)



Note how disparity is larger
(brighter) for closer surfaces.

Computing Disparity

- Correspondence Problem:
 - Determining which pixel in the right image corresponds to each pixel in the left image.
 - $\text{Disp} = x_coord(\text{left}) - x_coord(\text{right})$

Recall our discussion of scores for measuring similarity/dissimilarity of image patches (Lecture 7).

Cfg - correlation of raw pixel values

SSD - sum of squared difference measure

NCC - normalized cross correlation measure


Epipolar Constraint

Important Concept:

For stereo matching, we don't have to search the whole 2D right image for a corresponding point.

The “epipolar constraint” reduces the search space to a one-dimensional line.

Recall : Simple Stereo System



Left camera

$$x_l = f \frac{X}{Z}$$

$$y_l = f \frac{Y}{Z}$$

Right camera

$$x_r = f \frac{X - T_x}{Z}$$

$$y_r = f \frac{Y}{Z}$$

Same Y Coord!

Matching using Epipolar Lines


Left Image



Right Image



For a patch in left image
Compare with patches along
same row in right image




Match Score Values

Matching using Epipolar Lines

Left Image




Right Image



Select patch with highest
match score.

Repeat for all pixels in
left image.




Match Score Values

Example: 5x5 windows NCC match score



Computed disparities




Ground truth

Black pixels: bad disparity values,
or no matching patch in right image

Example: 5x5 windows NCC match score




Computed disparities



Ground truth

Black pixels: bad disparity values,
or no matching patch in right image

Occlusions: No matches




Effects of Patch Size



5x5 patches

Smoother in some areas



11x11 patches

Loss of finer details


Limitations

- So far, each left image patch has been matched independently along the right epipolar line.
- This ignores some obvious constraints, namely that surfaces in the world tend to be smooth.
- We would like to at least enforce some consistency among matches in the same row (scanline).

Disparity Space Image

First we introduce the concept of DSI.


The DSI for one row represents pairwise match scores between patches along that row in the left and right image.



Disparity Space Image (DSI)

Left Image

Right Image




Dissimilarity Values
(1-NCC) or SSD

Disparity Space Image (DSI)

Left Image

Right Image




Dissimilarity Values
(1-NCC) or SSD

Disparity Space Image (DSI)

Left Image


Right Image





Dissimilarity Values
(1-NCC) or SSD

Disparity Space Image (DSI)

Left Image



DSI



Dissimilarity Values

Enter each vector of
match scores as a
column in the DSI


Disparity Space Image

Left scanline


Right scanline

Invalid entries due to constraint
that disparity \leq high value
64 in this case)

Invalid entries due to constraint
that disparity \geq low value
(0 in this case)



Disparity Space Image




If we rearrange the diagonal band of valid values into a rectangular array (in this case of size $64 \times N$), that is what is traditionally known as the DSI

However, we're going to keep the full image around, including invalid values (I think it is easier to understand the pixel coordinates involved)



DSI and Scanline Consistency




Assigning disparities to all pixels in left scanline now
amounts to finding a connected path through the DSI



Lowest Cost Path

We would like to choose the “best” path.


Want one with lowest “cost” (Lowest sum of dissimilarity scores along the path)




Other Constraints on Path

It is common to impose an ordering constraint on the path. Intuitively, the path is not allowed to “double back” on itself.

Ordering Constraint




Ordering constraint...




...and its failure

Occlusions Can Occur





Occlusions Can Occur



However, note that the order of matching patches is preserved.

Occlusions: No matches



An Optimal Scanline Strategy

- We want to find best connected path, taking into account ordering constraint and the possibility of occlusions.


Practical algorithm:

Cox, Hingorani, Rao, Maggs, “A Maximum Likelihood Stereo Algorithm,” Computer Vision and Image Understanding, Vol 63(3), May 1996, pp.542-567.

See also Ohta & Kanade ' 85

Cox et.al. Stereo Matching

Start



End


Recap: want to find lowest cost path from upper left to lower right of DSI image.

At each point on the path we have three choices: step left, step down, step diagonally.

Each choice has a well-defined cost associated with it.

This problem just screams out for Dynamic Programming!
(which, indeed, is how Cox et.al. solve the problem)

Cox et.al. Stereo Matching




Three cases:

- Matching patches. Cost = dissimilarity score
- Occluded from right. Cost is some constant value.
- Occluded from left. Cost is some constant value.

$$C(i,j) = \min([C(i-1,j-1) + \text{dissimilarity}(i,j) \\ C(i-1,j) + \text{occlusionConstant}, \\ C(i,j-1) + \text{occlusionConstant}]);$$

Real Scanline Example



Every pixel in left column now is marked with either a disparity value, or an occlusion label.

Proceed for every scanline in left image.

Example

Result of DP alg



Result without DP (independent pixels)



Result of DP alg. Black pixels = occluded.

Occlusion Filling

Simple trick for filling in gaps caused by occlusion.




 = left occluded

Fill in left occluded pixels with value from the nearest valid pixel preceding it in the scanline.



Similarly, for right occluded, look for valid pixel to the right.


Example




Result of DP alg with occlusion filling.

Example


Result of DP alg with occlusion filling.



Ground truth




Scanline Algorithm Limitations




- Streaky results; each line being matched independently
- No obvious way to generalize dynamic programming from 1D scanline to 2D grid

Markov Random Field Stereo



Stereo matching as MRF energy minimization





- Probabilistic interpretation: we want to find a Maximum A Posteriori (MAP) estimate of disparity image D :

$$P(D | I_1, I_2) \propto P(I_1, I_2 | D) P(D)$$

$$-\log P(D | I_1, I_2) \propto -\log P(I_1, I_2 | D) - \log P(D)$$

$$E = \alpha E_{\text{data}}(I_1, I_2, D) + \beta E_{\text{smooth}}(D)$$


Stereo matching as MRF energy minimization




$$E = \alpha E_{\text{data}}(I_1, I_2, D) + \beta E_{\text{smooth}}(D)$$

$$E_{\text{data}} = \sum_i (W_1(i) - W_2(i + D(i)))^2$$

$$E_{\text{smooth}} = \sum_{\text{neighbors } i, j} \rho(D(i) - D(j))$$




e.g. Potts model



e.g. truncated linear model

Stereo matching as MRF energy minimization



$$E = \alpha E_{\text{data}}(I_1, I_2, D) + \beta E_{\text{smooth}}(D)$$

- MRF energy functions of this form can be minimized efficiently using an algorithm known as *graph cuts*

Y. Boykov, O. Veksler, and R. Zabih,

[Fast Approximate Energy Minimization via Graph Cuts](#), PAMI 2001

V. Kolmogorov and R. Zabih,

[Computing Visual Correspondence with Occlusions using Graph Cuts](#), ICCV 2001

Stereo

[Evaluation](#) • [Datasets](#) • [Code](#) • [Submit](#)

[Daniel Scharstein](#) • [Richard Szeliski](#) • [Heiko Hirschmüller](#)

Welcome to the Middlebury Stereo Vision Page. This website accompanies our taxonomy and comparison of two-frame stereo correspondence algorithms [1]. It contains:

- An [on-line evaluation](#) of current algorithms
- Many [stereo datasets](#) with ground-truth disparities
- Our [stereo correspondence software](#)
- An [on-line submission script](#) that allows you to evaluate your stereo algorithm in our framework


How to cite the materials on this website:

We grant permission to use and publish all images and numerical results on this website. If you report performance results, we request that you cite our paper [1]. Instructions on how to cite our datasets are listed on the [datasets page](#). If you want to cite this website, please use the URL

"vision.middlebury.edu/stereo/".

References:


- [1] D. Scharstein and R. Szeliski. [A taxonomy and evaluation of dense two-frame stereo correspondence algorithms](#).
International Journal of Computer Vision, 47(1/2/3):7-42, April-June 2002.
[Microsoft Research Technical Report MSR-TR-2001-81](#), November 2001.




Other online stereo benchmarks and datasets:

- [KITTI vision benchmark](#)
- [HCI robust vision challenge](#)

State-of-the-Art Results



Algorithm Results



Ground truth

M. Mozerov and J. van Weijer. Accurate stereo matching by two step global optimization. IEEE Transactions on Image Processing 24(3), January 2015.