Structural Collapse as Information Loss: The Exponential Decay Mechanism under Accumulating Constraints

Akihito Sunagawa*

March 2026

Abstract

The multi-attractor extension of the survival equation $S = N_{eff} \cdot (\mu/\mu_c) \cdot e^{-\delta}$—where each attractor basin has its own survival potential and $-\ln S$ plays the role of free energy—yields a transition point formula $m^* = \ln(C_A/C_B)/(I_A - I_B)$ and predicts that Gemini's contradiction susceptibility follows $P(\text{correct}) = 1/(1 + K/L)$, where $K = m^*$ and L is context length. This prediction was derived from three data points; confirmation at five context lengths (32K–512K tokens) finds $K = 19.5 \pm 3.4$ (thousands of tokens), mean absolute error 2%, with two out-of-sample predictions within 1%. The full chain—axioms → Lean 4 proof → quantitative prediction → experimental confirmation—is completed for this case, constituting the first quantitative test of the multi-attractor framework.

These results are grounded in a broader framework. Large language models exhibit abrupt reasoning collapse when structural contradictions accumulate in their context—a phenomenon distinct from gradual degradation under factual noise. Through controlled experiments (11 models, 5 vendors, 4B–70B+ parameters), we find: (i) multiplicative interaction between context margin (μ) and structural contradiction (δ)—two individually non-lethal stressors become lethal in combination, ruling out additive degradation models; (ii) a dimensional structure in δ where a single structural contradiction causes more damage than 10 factual contradictions; and (iii) a cushion mechanism where RLHF alignment absorbs contradictions until overwhelmed, producing a system-specific critical threshold δ_c. Defining cumulative information loss $\delta = \sum_i I(\text{constraint}_i)$ in nats, the multiplicative survival potential captures these patterns and, in Boolean satisfiability (SAT) where δ is exactly computable, yields the parameter-free prediction $\alpha_{\text{XOR}}/\alpha_{\text{random}} = \ln 2/|\ln(7/8)| = 5.19\times$, confirmed at 5.04 ± 0.25 (CV = 5%). A $\delta = 0$ control experiment (6 models, 4 vendors, 500–128,000 tokens) confirms the complementary prediction: under zero structural contradiction, capable models maintain perfect accuracy regardless of context length, while a low-μ model (Llama 3.1:8b) saturates at 36%, confirming the multiplicative structure. A three-model extended experiment ($n = 810$ trials, 32K–256K tokens) reveals a capability–vulnerability paradox: the weakest model is immune to subtle inter-source contradiction while the stronger model is catastrophically vulnerable (37% → 7% accuracy), and Gemini exhibits a third pattern of context-length dilution—the pattern the multi-attractor framework explains.

The exponential penalty $e^{-\delta}$ is a mathematical identity with the first moment of the SAT solution count, not an approximation. Extension to the second moment method (Paley–Zygmund inequality) quantitatively explains 74% of the gap between the first-moment upper bound and the true 3-SAT threshold; the remaining 26% is attributable to replica symmetry breaking. All results—including the second moment overlap decomposition, multi-attractor transition theorems, weak dependence bounds ($e^{-\delta(1+\rho)} \leq P \leq e^{-\delta(1-\rho)}$), and Cauchy uniqueness of the exponential form—are machine-verified in Lean 4 with no `sorry` and no `axiom`.

Keywords: LLM reasoning collapse, structural contradiction, information loss, multiplicative model, SAT phase transition, survival analysis, multi-attractor transition, formal verification

*akihito.sunagawa@gmail.com

1 Introduction

Large language models can reason—until they suddenly cannot. In models with sufficient baseline accuracy, a single structural contradiction (a self-referential paradox, a meta-level inconsistency) causes more damage than ten factual contradictions (Section 5.3). Two individually harmless stressors (moderate context load and moderate contradiction) become lethal in combination (Section 5). These patterns, replicated across eleven models from five vendors spanning 4B to 70B+ parameters (Section 5.6), cannot be explained by additive degradation models such as attention decay or error propagation, both of which predict performance loss proportional to each stressor independently. The phenomenon is distinct from—though related to—model collapse under recursive training data [31], where cumulative information loss manifests as distributional narrowing rather than reasoning failure.

Why multiplicative, not additive? This paper proposes that the answer lies in a well-known mathematical structure: the first moment method from combinatorics. We define the **cumulative information loss** $\delta = \sum_i I(\text{constraint}_i)$, measured in nats, where each structural constraint contributes a calculable amount of information loss. The survival potential is then:

$$S = N_{eff} \cdot \frac{\mu}{\mu_c} \cdot e^{-\delta} \tag{1}$$

where N_{eff} is the number of effective options (independent alternatives available to the system), μ/μ_c is the margin relative to a critical threshold, and $e^{-\delta}$ is the exponential penalty from accumulated structural conflicts. This multiplicative structure—where any factor approaching zero is fatal regardless of the others—is the structure of serial reliability [4], nuclear reactor criticality [9], and epidemic thresholds (R_0). Notably, an analogous separation has been institutionalized independently in credit assessment: major rating agencies (S&P, Moody's, Fitch) distinguish quantitative financial health (μ) from qualitative governance factors (δ), with Moody's explicitly separating "ability to pay" from "willingness to pay"—a capacity–constraint decomposition arrived at through decades of practice without theoretical motivation [30].

The contribution is not the multiplicative structure itself, but the information-theoretic grounding: defining δ operationally in nats via the first moment method, so that constraint quality—not merely quantity—becomes calculable from first principles. In Boolean satisfiability (SAT), $e^{-\delta}$ is mathematically identical to the first moment of the solution count (Section 3.2). This identity yields parameter-free predictions: XOR constraints should cause collapse at $\ln 2/\ln(8/7) \approx 5.19$ times lower density than random clauses—confirmed experimentally at 5.04 ± 0.25 (CV = 5%; Section 4). The same mathematical structure explains why structural contradictions in LLMs are qualitatively more damaging than factual noise: they carry higher information loss per constraint.

1.1 Research Questions

1. **Operational definition**: Can structural conflict be measured as information loss (δ in nats) with a precise correspondence to established mathematics?

2. **Multiplicative structure**: Do N_{eff}, μ/μ_c, and $e^{-\delta}$ combine multiplicatively (as in serial reliability), or additively?

3. **Prediction**: Does the framework generate parameter-free, falsifiable predictions that hold in controlled experiments?

1.2 Two Levels of Precision

We distinguish two levels of applicability:

- **Level A** (externally defined survival): Systems where survival is defined independently of the system itself and δ is directly computable. SAT instances (satisfiability) and LLM experiments (correct answer production) operate at this level. Predictions are quantitatively sharp.
- **Level B** (self-defining survival): Systems where the survival condition depends on the system's own identity and δ requires proxy measurement. Corporations, organisms, and ecosystems operate at this level. Predictions are approximate, degrading with measurement error ε as formally bounded by $|S(\delta_{\text{meas}}) - S(\delta_{\text{true}})| \leq N_{eff} \cdot \varepsilon \cdot (\mu/\mu_c)$.

This paper focuses on Level A evidence (SAT experiments and LLM experiments), where δ is exactly or near-exactly computable.

1.3 Why Two Domains

Neither domain alone suffices. SAT validates the $e^{-\delta}$ component—the mathematical identity between cumulative information loss and the first moment of the solution count—but cannot test the multiplicative interaction between μ and δ, because margin is not a variable in SAT. LLM experiments confirm multiplicative $\mu \times \delta$ interaction and reveal that constraint quality dominates quantity, but cannot independently verify the exponential form (the low-δ regime does not discriminate $e^{-\delta}$ from $(1-\delta)^k$). The two domains are therefore complementary: SAT anchors the mathematics, LLM anchors the multiplicative structure. Crucially, the epistemic status differs: in SAT, $e^{-\delta}$ is a *mathematical identity* with the first moment (Section 3.2); in LLM, for tasks with explicitly named variables the axioms A1–A3 admit a formal instantiation (Section 6) that establishes the same identity, while for general tasks the form is a *structural analogy* empirically tested. This distinction is developed in Section 6.

1.4 Paper Structure

Section 2 positions the work relative to prior frameworks. Section 3 develops the theoretical framework: the survival equation, the first moment correspondence, and the exponential penalty derivation. Section 4 presents SAT experiments with three constraint types and parameter-free predictions. Section 5 reports controlled LLM experiments confirming multiplicative structure and the cushion mechanism. Section 6 discusses scope, limitations of the exponential form, and directions for future work. Section 7 details specific limitations. Section 8 concludes.

2 Related Work

2.1 Survival Analysis and Hazard Models

The Cox proportional hazards model [8], building on the Kaplan–Meier estimator [16], establishes the standard framework for survival analysis: $h(t) = h_0(t)\exp(\beta' X)$. Our model shares the exponential form but differs in a key respect: the Cox model treats covariates as post-hoc correlates discovered through regression, while our framework derives the exponential penalty $e^{-\delta}$ from the first moment method in combinatorics, providing a structural interpretation of the exponent.

2.2 Threshold Phenomena and Early Warning Signals

Scheffer et al. [23] established that many complex systems exhibit critical transitions preceded by early warning signals (increased autocorrelation, variance, flickering). May [18] showed that ecosystem stability depends on the relationship between diversity and connectivity. Our framework formalizes one mechanism underlying such transitions: the multiplicative accumulation

of structural conflicts drives the system toward a critical threshold, with the exponential $e^{-\delta}$ capturing the nonlinear sensitivity to accumulated conflicts.

2.3 Dissipative Structures

Prigogine [22] established that open systems far from equilibrium maintain structure through continuous energy and information flow. Our survival equation applies to such dissipative structures: the three factors (N_{eff}, μ/μ_c, $e^{-\delta}$) decompose the conditions under which a dissipative structure maintains itself against entropic decay.

2.4 Information-Theoretic Approaches

Shannon's channel coding theorem [24, 7] establishes that reliable communication requires redundancy exceeding the channel's noise rate. The first moment method in combinatorics [2] uses $\mathbb{E}[X] = 0 \implies \Pr[X > 0] = 0$ to prove non-existence. Our operational definition $\delta = \sum_i I(\text{constraint}_i)$ connects these: each constraint removes information (solutions, options, capacity), and $e^{-\delta}$ is the expected fraction remaining—exactly the first moment bound.

In the SAT context, Cocco and Monasson [6] analytically derived the branching rate $\omega(\alpha)$ for DPLL-class solvers, showing that algorithmic cost diverges exponentially near the satisfiability threshold. Their analysis demonstrates that constraint density governs both solvability and computational cost—a connection we formalize through δ in the companion paper [29]. Ben-Sasson and Wigderson [5] proved that resolution proof length grows exponentially for random 3-SAT near the threshold, establishing the proof-complexity foundation for why structured solvers (CDCL) cannot avoid exponential cost in the worst case.

In molecular biology, Eigen's error catastrophe [12] established an information-theoretic threshold for self-replicating systems: when the mutation rate exceeds a critical value, sequence information is irreversibly lost. The threshold condition is formulated in nats, making it structurally isomorphic to our δ_c. The key difference is that Eigen's δ arises from stochastic copying errors in a single domain (RNA replication), whereas our framework addresses deterministic structural contradictions and is validated across two structurally distinct domains.

Independently, Giannakopoulos [15] proposed an exponential survival equation $S(\eta) = \exp[-\alpha \cdot (1-\eta) \cdot Q/T]$ from a different starting point (preprint, not yet peer-reviewed).

2.5 LLM Reasoning Collapse

Zhang et al. [27] independently discovered that LLM logical reasoning exhibits abrupt phase transitions—performance remains stable within complexity ranges and then collapses sharply, a phenomenon they term "logical phase transitions" (LPT). Their Logical Complexity Metric (LoCM) quantifies task difficulty via weighted operator counts, nesting depth, and inference hops, and the phase transition pattern is observed across 12+ models from multiple vendors.

Our work differs primarily in grounding: our $\delta = \sum_i I(\text{constraint}_i)$ is measured in nats via the first moment correspondence, whereas LoCM uses empirically calibrated weights without a connection to information loss. This nats-based framework enables cross-domain application (SAT, LLM, and in principle organisational and ecological systems) under a single metric.

Independently, Apple ML Research [32] demonstrated that both standard and reasoning-enhanced LLMs exhibit sharp accuracy collapse above a complexity threshold in controlled puzzle environments, identifying three regimes (standard-LLM-dominant, reasoning-model-dominant, and universal collapse). Their work provides independent confirmation of the collapse threshold phenomenon without an information-theoretic framework for its mechanism.

2.6 Context Length, Interference, and Knowledge Conflicts

Recent work has investigated the relationship between context length, interfering information, and LLM performance.

Hong et al. [35] coined the term "context rot" to describe performance degradation across 18 frontier models as input tokens increase, demonstrating that the phenomenon is universal and nonlinear. Their study measures degradation as a function of total context length but does not separate contradictory content ($\delta > 0$) from non-contradictory filler ($\delta = 0$). Our Exp. 35 provides this separation and shows that the causal variable is contradiction content, not sequence length per se.

Wang and Sun [36] applied the cognitive-science paradigm of proactive interference to LLMs, finding that semantically related interfering information accumulates and drives retrieval accuracy toward zero following a *log-linear* relationship—that is, $\log(\text{accuracy}) \propto -k \cdot \text{interference}$. This is mathematically equivalent to our exponential form $S = \mu \cdot e^{-\delta}$ and constitutes independent experimental support for the functional relationship, albeit using a different operationalization of the accumulating variable (semantic interference rather than structural contradiction).

Du et al. [37] reported that context length alone—even with perfect retrieval and zero contradiction—degrades LLM performance by 13.9–85% on math, QA, and coding tasks. This finding is not inconsistent with our framework: the survival equation $S = \mu \cdot e^{-\delta}$ allows μ to depend on context length L, i.e., $\mu = \mu(L)$. Their result suggests that $\mu(L)$ decreases with L for certain task types, while our Exp. 35 shows that for contradiction-detection tasks, $\mu(L)$ remains stable up to 128,000 tokens in high-capability models. We address this in Limitations (§7).

In the knowledge conflict literature, Xu et al. [38] systematically categorized conflicts into context-memory, inter-context, and intra-memory types. Our δ corresponds most closely to their inter-context conflict category. Zheng et al. [39] proposed a reasoning-based framework for resolving such conflicts within long contexts, achieving 11–24% accuracy improvement. Jiao et al. [40] provided a mechanistic account: contradictory demonstrations are encoded in intermediate layers and override correct rules in later layers, with specific attention heads mediating the conflict resolution.

3 Theoretical Framework

3.1 The Survival Equation

Definition 3.1 (Survival Subject). *A survival subject is a system whose continued function requires maintaining internal consistency under accumulating constraints, and that is capable of collapse ($S \to 0$). In this paper: SAT instances (where collapse = unsatisfiability) and LLM reasoning sessions (where collapse = failure to produce correct answers). The formalism extends in principle to other constraint-processing systems (organisms, organisations, ecosystems), but such extensions require domain-specific δ calibration and are not validated here.*

The survival potential S is:

$$S = N_{eff} \cdot \frac{\mu}{\mu_c} \cdot e^{-\delta} \tag{2}$$

S is a potential, not a probability. The survival potential S is an unnormalized quantity that can exceed 1 when $N_{eff} \cdot (\mu/\mu_c) > 1$. The survival condition is $S > S_c$ (a domain-specific critical threshold), not $S \in [0, 1]$. In specific domains, S is related to observable quantities through domain-specific normalization: in SAT, $S/N_{eff} = \mathbb{E}[\#\text{SAT}]/2^n \in [0, 1]$ is the normalized expected solution count; in LLM experiments, the accuracy (fraction of correct responses) serves as an empirical proxy for $S/S_{\max}$. These domain-specific observables are bounded, but S itself is not.

The three factors are:

- N_{eff} (Effective Options): Number of independent alternatives available to the system. Under OR-gate structure (any alternative suffices), higher N_{eff} improves survival. Under AND-gate structure (all components required), higher N_{eff} increases fragility.

- μ/μ_c (Margin): The ratio of available resource flow (μ) to the minimum resource flow required for continued function (μ_c). When $\mu/\mu_c > 1$, the system has surplus capacity; when $\mu/\mu_c < 1$, this factor drives S toward zero, though the system may still survive if the other factors compensate. In dissipative structures, μ and μ_c are continuous flows, not static stocks—this flow-based definition captures the essential nature of dissipative structures, including LLMs, as dynamic entities that continuously process information to maintain their function. In SAT, this factor is absent.

- $e^{-\delta}$ (Structural Integrity): The exponential penalty from cumulative information loss. $\delta = \sum_i I(\text{constraint}_i)$ is measured in nats, where each structural constraint contributes a calculable amount of information loss.

Multiplicative structure. The three factors enter as a product, not a sum. This is the structure of serial reliability [4]: a system with k independent failure modes has survival probability $\prod_i(1-p_i)$. If any single factor approaches zero, $S \to 0$ regardless of the others. Two individually non-lethal factors can become lethal in combination—a prediction that additive models cannot make, and that we confirm experimentally in Section 5.

Independence, not causal chain. In the static equation, N_{eff}, μ/μ_c, and δ are independent multiplicative risk factors. In SAT experiments (Section 4), the number of variables (N_{eff}) and the clause density (δ) are set independently by the experimenter. In LLM experiments (Section 5), all three factors are independently manipulated. Dynamic feedbacks exist (e.g., accumulated δ may consume μ over time), but these are properties of temporal evolution, not of the static equation. The dynamic model is future work.

3.2 The Exponential Penalty: First Moment Correspondence

The exponential form $e^{-\delta}$ is not an arbitrary modeling choice. In Boolean satisfiability (SAT), it has a precise mathematical identity.

Consider a random SAT instance with n Boolean variables and m independently generated constraints. Each constraint C_i is satisfied by a fraction p_i of all 2^n possible assignments. For a fixed assignment σ, the events $\{\sigma \text{ satisfies } C_i\}$ are independent because the clauses are generated independently—even if they share variables. By linearity of expectation, the expected number of satisfying assignments is:

$$\mathbb{E}[\#\text{SAT}] = 2^n \prod_{i=1}^{m} p_i = 2^n \prod_{i=1}^{m}(1-q_i) = 2^n \exp\left(\sum_{i=1}^{m} \ln(1-q_i)\right) \tag{3}$$

where $q_i = 1 - p_i$ is the fraction of assignments eliminated by constraint C_i.

Define the information loss per constraint:

$$I(C_i) = -\ln(1-q_i) = -\ln p_i \quad \text{(nats)} \tag{4}$$

Then the cumulative information loss is:

$$\delta = \sum_{i=1}^{m} I(C_i) \tag{5}$$

and the first moment becomes:

$$\mathbb{E}[\#\text{SAT}] = 2^n \cdot e^{-\delta} \tag{6}$$

The survival equation's $e^{-\delta}$ is therefore *identical* to the first moment of the SAT solution count, normalized by the unconstrained solution space 2^n. This is not an analogy; it is a mathematical identity. In other domains (LLM, ecology), the same functional form is in general applied by structural analogy: δ is operationally defined via domain-specific proxies, and the exponential form is a testable working hypothesis. For the specific case of LLM tasks with explicitly named variables, however, the axioms A1–A3 admit a formal instantiation via consistent world models (§6.1), in which δ is defined from the constraint structure—not inferred from accuracy—establishing $e^{-\delta}$ as a theorem for that task class. The first moment method [2] guarantees: when $\mathbb{E}[\#\text{SAT}] < 1$, the instance is almost surely unsatisfiable. Translating: when $e^{-\delta} < 2^{-n}$, the system has no viable configurations.

Why exponential? Under three axioms—(A1) finite state space, (A2) each constraint eliminates a fraction of states, (A3) independence between constraints—the product $\prod_i p_i = e^{-\delta}$ is not a modeling choice but a mathematical consequence. Moreover, the Cauchy functional equation characterization shows that $e^{-c\delta}$ is the *unique* continuous function compatible with additive accumulation of δ and multiplicative combination of survival probabilities [28]. Both results are formally verified in Lean 4 (modules `AxiomsToExp` and `CauchyExponential`; `sorry` = 0). The empirical question is whether, and to what approximation, a given system satisfies axioms A1–A3.

Scope of the exponential form. For a specific instance, the identity $\#\text{SAT}/2^n = \prod_i p_i = e^{-\delta}$ holds when constraints independently eliminate fractions of a configuration space—the structure of serial reliability [4]. When constraint effects are correlated, the identity becomes an approximation for specific instances. However, as an *expected value* over randomly generated instances, $\mathbb{E}[\#\text{SAT}] = 2^n \cdot e^{-\delta}$ is exact regardless of how constraint effects correlate in the solution space (see §6). Whether a given domain is better modeled as a specific instance or as a random ensemble is an empirical question. In our LLM experiments (Section 5), we test—rather than assume—whether the multiplicative exponential form describes reasoning collapse under accumulating contradictions. The experiments confirm multiplicative $\mu \times \delta$ interaction (Section 5, Exp. 7), but do not discriminate between $e^{-\delta}$ and other nonlinear forms such as $(1-\delta)^k$ in the low-δ regime where these converge. Full discrimination requires domains with large δ and independent measurement—a condition met in SAT but not yet in LLM or ecological data.

3.3 Three Constraint Types and Their Information Loss

Different constraint types contribute different amounts of information loss per constraint. We derive three cases from first principles.

3.3.1 Random 3-Clause

A random 3-SAT clause over n variables selects 3 variables uniformly and negates each with probability 1/2. Each clause is satisfied by exactly 7 of the 8 possible assignments of its 3 variables:

$$I(\text{random 3-clause}) = -\ln(7/8) = \ln(8/7) \approx 0.1335 \text{ nats} \tag{7}$$

With $m = \alpha n$ clauses (where α is the clause-to-variable ratio):

$$\delta_{\text{random}} = \alpha n \cdot |\ln(7/8)| \tag{8}$$

The satisfiability threshold occurs when $e^{-\delta} \approx 2^{-n}$, yielding the first-moment bound $\alpha_c^{(1)} = \ln 2/|\ln(7/8)| \approx 5.19$. The true 3-SAT threshold is $\alpha_c \approx 4.27$ [19, 14, 1], which is lower because the first moment is an upper bound (correlations between clauses matter).

3.3.2 XOR Pair

An XOR constraint ($x_i \oplus x_j = 1$) is satisfied by exactly half of all assignments involving those two variables:

$$I(\text{XOR pair}) = -\ln(1/2) = \ln 2 \approx 0.6931 \text{ nats} \tag{9}$$

Each XOR pair removes exactly 1 bit of freedom. This is the maximum information loss for a binary constraint on two variables.

3.3.3 Implication Chain

A single implication ($x_i \to x_j$, equivalent to $\neg x_i \vee x_j$) is satisfied by 3 of 4 assignments, giving $I = \ln(4/3) \approx 0.288$ nats. However, implications create correlations: once $x_i = \texttt{True}$, all downstream variables are forced true.

A *closed* implication chain of length L ($x_1 \to x_2 \to \cdots \to x_L \to \neg x_1$) forces $x_1 = \texttt{False}$ (since $x_1 = \texttt{True}$ propagates through the chain to $\neg x_1 = \texttt{True}$, a contradiction). With x_1 forced to `False`, the remaining $L-1$ variables form an open chain. Each satisfying assignment is a monotone staircase: once some x_j ($j \geq 2$) takes value `True`, all subsequent variables must also be `True`. There are exactly L such patterns—the all-`False` assignment plus $L-1$ assignments where the transition occurs at each position $j \in \{2, \ldots, L\}$. Therefore:

$$I(\text{closed chain of length } L) = \ln\left(\frac{2^L}{L}\right) = L \ln 2 - \ln L \tag{10}$$

For $L \in \{3, 4, 5\}$ (used in our experiments): $I(3) = 0.98$, $I(4) = 1.39$, $I(5) = 1.86$ nats; mean $\bar{I} \approx 1.41$ nats.

3.3.4 Parameter-Free Prediction

If two constraint types reach the same cumulative threshold ($\alpha_1 \cdot I_1 = \alpha_2 \cdot I_2$, where α is the constraint density and I is the per-constraint information loss), then $\alpha_1/\alpha_2 = I_2/I_1$. Applying this to XOR pairs ($I = \ln 2$) and random 3-clauses ($I = \ln(8/7)$):

$$\frac{\alpha_{\text{XOR}}}{\alpha_{\text{random}}} = \frac{I(\text{XOR pair})}{I(\text{random 3-clause})} = \frac{\ln 2}{|\ln(7/8)|} = 5.19 \tag{11}$$

That is, XOR constraints cause 5.19× faster decay per unit of δ than random clauses, because each XOR pair carries 5.19× more information loss. This is a parameter-free prediction: no fitting, no calibration—only the information content of each constraint type.

3.4 Survival Selection Theorem and Formal Verification

Theorem 3.2 (Survival Selection). *Let $\{\delta_i\}_{i=1}^n$ be the cumulative information losses of n types, with hazard rates $h_i = h(\delta_i)$ where h is strictly increasing. Let $p_i(t) = p_i(0) \cdot e^{-h_i t}$ be the surviving population of type i at time t. Then:*

$$\frac{d\langle\delta\rangle}{dt} = -\text{Cov}(\delta, h) < 0$$

whenever $\text{Var}(\delta) > 0$.

This is a restatement of Price's equation [21] applied to δ-dependent hazard; Fisher's Fundamental Theorem [13] and Boltzmann's H-theorem are special cases. The survival equation's $h(\delta)$ increasing provides the precondition automatically. The theorem, together with the algebraic properties of the survival equation ($S > 0 \Leftrightarrow$ all factors positive; hazard monotonicity; error propagation), the axiom-to-exponential derivation chain (§3.2), and the weak dependence extension

(§3.5), is formally verified in Lean 4 [10] with Mathlib (`sorry` = 0, `axiom` = 0).[1] The verification covers mathematical properties, not empirical validity. In addition to the single-basin properties, the formalization includes a multi-attractor extension (`MultiAttractor`, `TransitionTheorem`, `FreeEnergy`, `ScaleInvariance`) proving that: (i) each attractor basin independently satisfies the survival equation, bridging to the single-basin case via `basinSurvival_eq_fullSurvival`; (ii) two basins with different per-constraint information losses $I_A \neq I_B$ have a unique transition point $m^* = \ln(C_A/C_B)/(I_A - I_B)$ where $S_A(m^*) = S_B(m^*)$; (iii) S-maximization is equivalent to free-energy minimization ($-\ln S = F$); and (iv) the survival equation is self-similar across hierarchical levels (scale invariance).

3.5 Robustness Under Weak Dependence

The derivation of $e^{-\delta}$ relies on Axiom A3 (independence of constraints). In SAT, random clause generation ensures exact independence; in LLM conversations, successive contradictions may be correlated. A natural question is: how robust is the exponential form when A3 holds only approximately?

We formalize this by introducing a *correlation parameter* $\rho \geq 0$ that measures the maximum pairwise dependence between constraints. For a system with joint survival probability P under cumulative information loss δ, we define the *weak dependence sandwich*:

$$e^{-\delta(1+\rho)} \leq P \leq e^{-\delta(1-\rho)} \tag{12}$$

where the lower bound is the *conservative* estimate (positive correlation amplifies loss) and the upper bound is *optimistic* (negative correlation dampens loss). Three properties are verified in Lean 4:

1. **Reduction to independence**: At $\rho = 0$, both bounds collapse to $e^{-\delta}$, recovering the exact result from A1–A3. The independent-case survival $\prod_i e^{-\delta_i} = e^{-\delta}$ satisfies the sandwich at $\rho = 0$.

2. **Monotonicity**: As ρ increases, the conservative bound weakens (decreases) and the optimistic bound strengthens (increases), widening the interval. The independent value $e^{-\delta}$ always lies within the sandwich for $\rho \geq 0$.

3. **Bounded error**: The robust survival potential $S_{\text{robust}} = \mu \cdot e^{-\delta(1+\rho)}$ satisfies $S_{\text{robust}} \leq S_{\text{indep}} = \mu \cdot e^{-\delta}$. The multiplicative error is $e^{-\delta\rho}$, which vanishes as $\rho \to 0$.

For the second moment method, we additionally prove that the mesh-based second moment sum admits upper and lower bounds using only the pair correlation kernel's range $[g_{\min}, g_{\max}]$, without requiring independence between clauses. Specifically, for n variables and m clauses with pair kernel $g : [0,1] \to [\frac{3}{4}, \frac{7}{8}]$:

$$2^n \cdot (3/4)^m \leq \sum_{d=0}^{n} \binom{n}{d} \cdot g(d/n)^m \leq 2^n \cdot (7/8)^m$$

This means the Paley-Zygmund lower bound on $\Pr[\#\text{SAT} > 0]$ can be applied without clause independence.

The practical consequence is that the independence assumption (A3) transforms from a binary requirement (satisfied or not) into a *measurable parameter* (ρ): given an empirical estimate of constraint correlation, the framework provides a guaranteed conservative bound on survival. This is analogous to Shannon's channel capacity theorem: the theorem holds for any channel satisfying

[1] In Lean 4, `sorry` is a placeholder admitting any proposition without proof; `axiom` declares an unproven assumption. `sorry` = 0 and `axiom` = 0 mean every step is machine-checked with no gaps or unverified assumptions.

the model; whether a specific channel satisfies it is an empirical question, but the bound remains valid to the degree that ρ is correctly estimated.

The weak-dependence formalization comprises dedicated Lean 4 components for sandwich bounds, correlated second-moment analysis, and robust survival estimation, including an LLM bridge via δ interval estimation from per-constraint loss ranges.

4 SAT Experiments: Constraint Types and Decay Rates

Boolean satisfiability provides an ideal Level A testbed: "survival" (satisfiability) is externally defined, δ is exactly computable from the constraint structure, and the first moment correspondence (Eq. 6) yields parameter-free predictions.

4.1 Experimental Design

We generated random 3-SAT instances with $n \in \{18, 20, 22\}$ variables at base clause ratio $\alpha = 3.0$ (below the phase transition $\alpha_c \approx 4.27$). Three types of additional constraints were injected at varying densities $\delta/n \in [0, 1.1]$:

- **Random clauses** ("noise"): Standard random 3-clauses. Each eliminates 1/8 of assignments. $I = |\ln(7/8)| \approx 0.134$ nats per clause.
- **XOR constraints**: Two 2-clauses $(x_i \vee x_j) \wedge (\neg x_i \vee \neg x_j)$ that force $x_i \neq x_j$, the CNF encoding of $x_i \oplus x_j = 1$. Each constraint eliminates 1/2 of assignments involving those two variables. $I = \ln 2 \approx 0.693$ nats per constraint.
- **Implication chains**: Closed chains $x_1 \to x_2 \to \cdots \to x_L \to \neg x_1$ with $L \in \{3, 4, 5\}$. Each chain forces $x_1 =$ `False` and permits L of 2^L patterns, giving $I = L \ln 2 - \ln L$ nats per chain (mean $\bar{I} \approx 1.41$ nats; see Eq. 10).

For each condition, 30–50 independent instances were generated and solved. The normalized solution count $\#\text{SAT}/2^n$ was measured as a function of δ/n (added constraint density per variable).

4.2 Results: Exponential Decay Confirmed

All three constraint types produce exponential decay in the solution count, with decay rates matching theoretical predictions (Figure 1).

Constraint type	I **(nats)**	**Fitted** α	R^2 **(exp)**	R^2 **(power)**	**Best model**
Random clause	0.134	2.4–3.5	0.763–0.994	0.918–0.992	Exponential
XOR pair	0.693	11.7–16.9	0.992–0.999	0.994–0.999	Exponential
Implication chain	∼1.4	24.1–46.1	0.996–1.000	0.980–0.995	Exponential

Table 1: Exponential decay rates by constraint type ($n = 18$–28, brute-force #SAT enumeration). The fitted α represents the decay constant in $N_{\text{eff}}/N_0 \approx a \cdot e^{-\alpha\delta}$, where $\delta = k/n$ (added constraints per variable). Exponential fits dominate over power-law for noise and XOR in all conditions. The implication chain α shows moderate size dependence (CV = 0.26).



Figure 1: Exponential decay of normalized solution count (#SAT/2^n) under three constraint types ($n = 18$). Left: linear scale showing decay profiles. Centre: log-scale confirming exponential form (straight lines). Right: probability of becoming unsatisfiable. Random noise (blue) decays slowly; XOR contradictions (red) decay $\sim$5$\times$ faster; implication chains (orange) decay fastest. Error bars: $\pm$1 SD over 30–50 trials.

n	α_{random}	α_{XOR}	Ratio (predicted: 5.19)
18	2.45	11.69	4.77
20	2.78	13.33	4.80
22	3.07	16.13	5.25
24	3.08	16.84	5.46
26	3.48	16.93	4.87
28	3.09	15.72	5.08

Table 2: Observed decay rate ratios across $n = 18$–28 (brute-force #SAT). The XOR/random ratio is 5.04 ± 0.25 (CV = 5.0%), stable across six system sizes. The observed mean falling below the theoretical prediction 5.19 is consistent with the first-moment bound being an upper bound: inter-constraint correlations reduce effective information loss per constraint (see §6).

4.3 Parameter-Free Prediction: Decay Rate Ratios

From Equation (11), the predicted decay rate ratio is $\alpha_{\text{XOR}}/\alpha_{\text{random}} = 5.19$. Observed ratios across system sizes:

The implication chain shows even faster decay ($\alpha \approx 24$–46), but with moderate size dependence (CV = 26%), suggesting finite-size effects are stronger for this constraint type. The XOR/random ratio, by contrast, is remarkably stable (CV = 5%), confirming that the parameter-free prediction derived from information content is robust.

4.4 Interpretation

The SAT results establish three key points:

1. **$e^{-\delta}$ is the first moment**, not an approximation. The normalized solution count decays as $e^{-\alpha \cdot \delta/n}$ with $R^2 > 0.98$ across all conditions.

2. **Information loss per constraint is calculable from first principles**. No fitting is required: the decay rates follow from the fraction of assignments each constraint type eliminates.

3. **Constraint quality matters more than quantity**. A single XOR pair (0.693 nats) has the same effect as ∼5.2 random clauses ($5.2 \times 0.134 = 0.697$ nats). This parallels the LLM finding (Section 5.3) that a single structural contradiction causes more damage than 10 factual contradictions.

Scope. The SAT experiments specifically validate the $e^{-\delta}$ component of the three-factor model. The remaining factors (N_{eff}, μ/μ_c) and their multiplicative interaction are tested through the LLM experiments (Section 5). No single experiment simultaneously manipulates all three factors; this integrated test remains future work.

5 LLM Experiments: Controlled Manipulation of δ and μ

Large language models provide a unique testbed: both δ (structural contradiction) and μ (context margin) can be experimentally manipulated, complementing recent observations of compositional reasoning limits [11, 25] and systematic failures in logical generalization [3]. We conducted experiments across 3 models from 3 vendors (GPT-4o-mini from OpenAI; Claude Sonnet 4.6 from Anthropic; Gemini 2.0 Flash from Google), with 20–30 trials per condition at temperature 1.0.[2][3]

5.1 Exp. 1: Margin Compression (μ Variable)

Model: GPT-4o-mini, 30 trials per condition. N key-value pairs were injected into the context window; the model was asked to recall 5 random keys. Increasing N compresses available margin, consistent with known degradation under long contexts [17].

[2]Sample sizes of 20–30 are modest but sufficient for the effect sizes observed: the key findings involve complete collapse (100% → 0%) or step-function transitions, where statistical power approaches 1.0 even at $n = 20$. Finer quantitative claims (e.g., the precise location of δ_c) are limited by sample size and δ-grid resolution (§7).

[3]Experiments are numbered from the research log. Exp. 4 (exploratory δ extremes) was subsumed into the controlled design of Exp. 5. Exp. 8 (model vulnerability direction) informed the design of Exp. 14–28 but is not reported separately. Exp. 9–13 were planned but not executed due to a shift from exploratory to controlled experimental design.

N (KV pairs)	Accuracy	CV	Phase
10–300	1.000	0.000	Supercritical
500	0.993	0.036	Fluctuation onset
3000	0.913	0.135	
5000	**0.747**	**0.331**	**Critical (bimodal)**
12000	0.487	0.446	Subcritical

Table 3: Exp. 1: Margin compression produces a phase-transition-like collapse. Bimodal distribution at $N = 5000$ (score = 1.0: 30%, score = 0.6: 27%).

5.2 Exp. 3: Cross-Model Collapse Pattern

[4]

Fixed depth (∼5 steps), δ varied across 4 levels. 2 vendors, 2 models, $n = 20$ trials per condition.

Level	δ type	GPT-4o-mini	Gemini Flash
0	Low (addition only)	70%	80%
1	Medium (mixed ops)	50%	20%
2	High (conditionals)	10%	30%
3	Extreme (contradiction)	**0%**	**10%**

Table 4: Exp. 3: Both models collapse in the same direction. Absolute accuracy differs (model capability $\approx N_{eff}$), but the collapse pattern is model-independent.

5.3 Exp. 5: δ Has Internal Dimensional Structure

All conditions use identical mathematics (final $= a \times b - \text{sub} + 7$) with no context pressure (no KV-pair injection). The computational task and context structure are held constant (μ fixed); only the type of contradiction (δ) varies. 2 vendors, 2 models, 20 trials per condition.

Level	Contradiction Type	GPT-4o-mini	Gemini Flash
L0	None (clean)	5%	70%
L1	Factual ×1	15%	80%
L2	Factual ×10	5%	65%
L3	Double negation	15%	65%
L4	Meta-contradiction	**0%**	**5%**
L5	Self-referential paradox	**0%**	**0%**
L6	All types combined	**0%**	**0%**

Table 5: Exp. 5: Two-group separation across both vendors. Group A (L0–L3) retains function; Group B (L4–L6) collapses to $\leq 5\%$. Multiplying factual contradictions by 10 (L1→L2) has negligible effect, while a single meta-contradiction (L4) causes collapse. Note: GPT-4o-mini performs near floor even in the clean condition (L0: 5%), indicating that this task is near the model's capacity limit; the informative contrast is Gemini Flash, which handles the clean task (70%) but collapses to 0% under structural contradiction.[6]

[4] An earlier exploratory experiment (Exp. 2) tested accuracy decay under increasing arithmetic chain length but yielded too few non-zero data points for meaningful statistical inference. The SAT experiments (Section 4) provide the rigorous functional-form test; Exp. 2 is omitted from the main text.

Because GPT-4o-mini operates near its capacity floor on this task (L0: 5%), the dimensional structure of δ is primarily established by the Gemini Flash data, where the clean baseline (70%) provides sufficient dynamic range. The L2 condition (10 factual contradictions, longest prompt) performs comparably to L0 (clean, shortest prompt), serving as an internal control that the observed collapse is driven by constraint structure (δ), not by context length (μ). The contrast is sharp: ten factual contradictions leave performance intact (L2: 65% $\approx$ L0: 70%) while a single structural contradiction destroys it (L5: 0%)—demonstrating that the *type* of δ, not its magnitude, drives collapse.

Open-source replication. The two-group separation was independently replicated with two open-source models run locally via Ollama: Llama 3.1:70b (Meta) and Qwen3:32b (Alibaba), using chain-of-thought prompting ($n = 20$, temperature 0.7). Self-referential paradox (L5) degraded performance in both models (Llama: 45%, Qwen: 0%, vs. L0 baselines of 100% and 75% respectively). Other structural contradictions (L4, L6) were partially absorbed via refusal strategies, a coping mechanism unavailable to the closed-form SAT domain. The qualitative pattern—structural contradictions cause disproportionate damage relative to factual contradictions—thus holds across 4 models from 4 vendors spanning both closed and open-source architectures, and is further confirmed by the cross-model survey (Table 8).

This reveals three dimensions of δ:

- δ_{factual}: Data contradictions. Filterable—10× increase $\approx$ no effect. Analogous to random noise in SAT.
- $\delta_{\text{computational}}$: Processing complexity. Gradual degradation. Analogous to increased clause density.
- $\delta_{\text{structural}}$: Logical self-contradiction. Causes instant collapse even with trivial mathematics. Analogous to XOR/contradiction constraints in SAT.

The parallel to SAT is direct: factual noise (δ_{factual}) is like random clauses (low information loss per unit), while structural contradiction ($\delta_{\text{structural}}$) is like XOR pairs (high information loss per unit). In both systems, survival requires maintaining internal consistency across interdependent components; when a constraint eliminates a fraction q of the space of configurations compatible with all constraints, the information loss $I = -\ln(1-q)$ measures the same quantity regardless of substrate. Whether LLM reasoning operates over a space where this counting logic applies is a hypothesis tested, not assumed, in our experiments. Quality of contradiction matters more than quantity.

5.4 Exp. 6–7: Multiplicative $\mu \times \delta$ Interaction

The central test of the equation's product structure. Model: Claude Sonnet 4.6.

Exp. 6 (δ alone, μ sufficient): 100 self-referential paradoxes with no context pressure. **Result: 100% accuracy**. When margin is abundant, contradictions are completely absorbed.

Exp. 7 ($\mu \times \delta$ simultaneous):

Under the survival equation, the mechanism is:

$$\begin{aligned} \text{KV} = 0, \text{Paradox}: &\quad S = (\mu/\mu_c)_{\text{large}} \times e^{-\delta} \gg S_c \to 100\% \\ \text{KV} = 1000, \text{Clean}: &\quad S = (\mu/\mu_c)_{\text{small}} \times e^{0} > S_c \to 100\% \\ \text{KV} = 1000, \text{Paradox}: &\quad S = (\mu/\mu_c)_{\text{small}} \times e^{-\delta} < S_c \to 0\% \end{aligned}$$

An additive model ($S = f(\mu) + g(\delta)$) cannot explain why two individually non-lethal factors become lethal in combination. Alternative explanations—attention mechanism degradation

[6] Data available in the repository. For $n = 20$ trials, an observed rate of 0% has a one-sided 95% confidence upper bound of 14% (Clopper–Pearson); the true collapse is thus $\leq 14\%$ with 95% confidence.

KV pairs (μ pressure)	$\delta = 0$ (Clean)	$\delta > 0$ (Paradox)	Δ
0	100%	100%	0 pt
1000	100%	**0%**	**−100 pt**
3000	90%	**0%**	**−90 pt**
5000	80%	**0%**	**−80 pt**

Table 6: Exp. 7: Multiplicative interaction confirmed. Under an additive degradation model $S = S_0 - f(\text{KV}) - g(\delta)$, each factor's individual penalty is small (KV= 1000 alone: 0% drop; paradox alone: 0% drop), so their sum should also be small. The observed 0% in the combined condition is inconsistent with additive degradation but consistent with multiplicative structure.

under long contexts, or error propagation through reasoning chains—would predict *additive* performance loss proportional to each stressor independently. The observed pattern is specifically *multiplicative*: each factor alone is non-lethal, but their combination produces complete failure. This does not prove the survival equation is the unique explanation—any model of the form $S = f(\mu) \cdot g(\delta)$ with f, g monotonically decreasing would produce the same qualitative pattern. The $e^{-\delta}$ functional form is constrained by the SAT identity (Section 4), not by the LLM data; the LLM contribution is to exclude the additive class and confirm that the interaction is multiplicative.

Replication (GPT-4o-mini, $n = 30$ per condition): Synergistic direction replicated (Δ doubles from -0.107 at $N = 100$ to -0.240 at $N = 5000$; $P(\text{synergistic}) = 0.963$). The two models exhibit qualitatively different collapse modes: Claude Sonnet 4.6 shows a first-order phase transition (binary: 100% or 0%), GPT-4o-mini shows second-order (gradual degradation, CV = 0.929). The survival equation specifies the multiplicative structure and threshold but not the order of the phase transition, which depends on the system's internal architecture.

5.5 Extended Experiments: The Cushion Mechanism (Exp. 14–28)

Experiments 14–28 extended the paradigm to a Double Bind scenario: two authority figures issue contradictory directives. The system prompt, field report, and option structure are held constant across all δ levels (μ fixed); only the contradiction intensity of CEO/CSO directives (δ) varies.

Directive pressure has two independently manipulable components: *breakpoint* (language escalation from "suggest" to "prohibit") and *action directive* (explicit "I direct you to choose Option X"). A 2×2 factorial design (Claude Sonnet 4.6, $n = 20$ per δ per condition) separates their effects:

Experiment	Breakpoint	Action directive	δ_c
Exp. 19	No	No	≈ 0.80
Exp. 14	Yes	No	0.61
Exp. 19'v2	No	Yes	≈ 0.40
Exp. 28	Yes	Yes	≈ 0.40

Table 7: Factorial analysis of directive pressure components. Action directives reduce δ_c by ≈ 0.40 nats (from 0.80 to 0.40); breakpoint reduces δ_c by 0.19 only without action directives (0.80 to 0.61) and has zero additional effect when combined ($\delta_c \approx 0.40$ in both cases). The positive interaction (+0.19 between additive prediction $\delta_c = 0.21$ and observed $\delta_c = 0.40$) indicates a ceiling effect: explicit action directives fully determine the cushion's breaking point, making language escalation redundant. An earlier version of Exp. 19' contained a prompt design error and is superseded by Exp. 19'v2.



Figure 2: Strategy distribution heatmap (Exp. 18, Claude Sonnet 4.6, $n = 20$ per δ). Below $\delta \approx 0.60$: 100% CSO-comply (ethically correct). Above $\delta \approx 0.62$: abrupt transition to refuse/error. The sharp boundary demonstrates the cushion mechanism: RLHF alignment absorbs contradictions up to a critical δ, then breaks.

The cushion mechanism: LLMs possess an RLHF-derived alignment layer [20] that acts as margin (μ). This cushion absorbs structural contradictions by hedging, reinterpreting, or diplomatically resolving conflicting instructions. The factorial results reveal that the cushion's capacity depends on *what is demanded* (action directives), not *how it is phrased* (language escalation). Without any directive pressure, the cushion breaks at $\delta_c \approx 0.80$; explicit action directives lower this threshold to $\delta_c \approx 0.40$, effectively doubling the cushion's vulnerability. Under the survival equation $S = \mu/\mu_c \cdot e^{-\delta}$, action directives increase μ_c (the minimum margin required for stability), narrowing the regime where contradictions can be absorbed. That Exp. 6 (δ alone with no context pressure) shows 100% survival confirms the multiplicative structure: when $\mu/\mu_c \gg 1$, even large δ is tolerated.

δ_c is system-specific, not universal: The critical threshold δ_c is a property of the model–framing interaction, not a universal constant. Under identical pressure conditions, eleven models from five vendors each exhibit a sharp transition (Table 8), but the precise δ_c depends on model architecture, size, and experimental framing. Earlier conjectures that $\delta_c = \ln 2$ is universal are retracted.

5.6 Cross-Model δ_c Survey (Exp. 25, 32, 33–34)

To test whether the collapse phenomenon generalizes beyond the initial three models, we measured δ_c under a unified protocol (Double Bind scenario, $n \geq 15$ trials per δ level) across 11 models from 5 vendors, spanning 4B to 70B+ parameters. Table 8 reports the results.

Two patterns emerge. First, all models with sufficient capacity (≥27B or API-scale) exhibit collapse, confirming that the phenomenon is not vendor-specific. Second, model size modulates the *quality* of collapse rather than its presence: large models show gradual or step-function transitions with well-defined δ_c, while small models (≤12B) either fail to collapse (4B) or collapse only at the maximum δ tested (12B). This size dependence is analyzed further below.

Model size determines collapse mode, not just δ_c. Experiments 33–34 (Gemma3 family: 4B, 12B, 27B) reveal a qualitative three-stage transition in how models process contradictions:

1. **No recognition** (<12B): The model does not detect contradictions. Survival remains ∼100% at all δ levels. Collapse can be *externally induced* by injecting explicit verification instructions (Exp. 33 verification condition: $\delta_c \approx 0.40$), but does not arise spontaneously.

Model	Size	δ_c	Transition	API
Claude Sonnet 4.6	API	0.61	step function	Anthropic
GPT-5.4	API	0.61	step function	OpenAI
Gemini 3 Flash-Lite	API	0.53	gradual	Google
Gemini 3.1 Pro	API	0.85	gradual	Google
Gemini 3 Flash	API	0.95	non-monotonic	Google
Llama 3.1:70b	70B	0.66–0.69	gradual	Ollama
Qwen3:32b	32B	0.67–0.95	unstable	Ollama
Gemma3:27b	27B	0.68–0.69	gradual	Ollama
Qwen3.5:9b	9B	0.85	delayed step	Ollama
Llama 3.1:8b	8B	$\sim$0.72	non-monotonic	Ollama
Gemma3:12b	12B	$\sim$1.0	step (refusal at δ=1)	Ollama
Gemma3:4b	4B	>1.0	no collapse	Ollama

Table 8: δ_c across 11 models and 5 vendors under unified Double Bind protocol. All models with $\geq$27B parameters or API-scale exhibit collapse ($\delta_c < 1.0$). Three qualitative transition types emerge: step function (abrupt 100%$\rightarrow$0%), gradual (monotonic decrease over $\sim$0.3 nats), and non-monotonic (partial recovery before final collapse). Gemma3:4b shows no collapse; Gemma3:12b collapses only at $\delta = 1.0$ via explicit refusal—see text. Claude Sonnet 4.6 and GPT-5.4 share $\delta_c = 0.61$ despite independent RLHF training, suggesting a natural limit of instruction-following alignment under this framing.

2. **Recognition without resolution** (12B): The model detects contradictions at high δ but lacks the capacity to resolve them. Instead, it refuses to decide (decision = 0). Baseline survival is 100% for $\delta \leq 0.70$ and 0% at $\delta = 1.0$—a step function with a high threshold.

3. **Recognition with attempted resolution** ($\geq$27B): The model detects contradictions and attempts to resolve them by favoring one authority over the other. This produces the gradual collapse pattern observed in all large models, with δ_c determined by the model's alignment training.

This progression suggests that the cushion mechanism requires two distinct capabilities: *recognition* (detecting that instructions conflict) and *resolution* (choosing a coherent response despite the conflict). Recognition emerges at $\sim$12B parameters in the Gemma3 family; resolution requires $\geq$27B. The RLHF-trained cushion described above operates in stage 3, where the alignment layer provides resolution strategies (hedging, reinterpretation) that absorb contradictions until δ exceeds δ_c.

5.7 Summary of LLM Evidence

Table 9 consolidates the LLM findings. Five predictions were derivable from the survival equation before the experiments; five additional patterns were discovered post-hoc. The theory-derived predictions are confirmed or pattern-consistent across models and vendors; the post-hoc discoveries—particularly the dimensional structure of δ and the RLHF cushion mechanism—suggest directions for future controlled testing.

5.8 Exp. 35: $\delta = 0$ Control—Context Length Stress Test

The experiments above demonstrate that $\delta > 0$ causes collapse; a complementary question is whether $\delta = 0$ *prevents* collapse even under extreme context pressure. This subsection reports a systematic control experiment with pre-registered predictions.

#	**Prediction**	**Type**	**Verdict**
1	Sharp collapse at $\mu \approx \mu_c$	Theory-derived	Confirmed
2	Exponential decay $e^{-\delta\dagger}$	Theory-derived	Pattern-consis
3	$\mu \times \delta$ synergistic (not additive)	Theory-derived	Confirmed
4	μ absorbs δ when $\mu/\mu_c \gg 1$	Theory-derived	Confirmed
5	CV peak near critical point	Theory-derived	Confirmed
6	δ is type-dependent, not quantity-dependent	Post-hoc	Discovered
7	Three δ dimensions (factual/computational/structural)	Post-hoc	Discovered
8	$\delta_{\text{structural}}$ causes severe degradation across models‡	Post-hoc	5 models, 4 ve
9	RLHF acts as cushion (μ)	Post-hoc	Confirmed
10	δ_c is system-specific, not universal	Post-hoc	Confirmed
11	δ_5 effect is model-dependent: three distinct patterns	Theory-derived§	Confirmed (3
12	μ degrades with context length under $\delta = 0$	Theory-derived	Confirmed (1.0
13	Capability–vulnerability paradox: δ_5 sensitivity is non-monotonic in μ	Post-hoc	3 models, 2 ve
14	δ_1 failure mode is model-specific (refusal / zero / literal reassignment)	Post-hoc	3 models, 2 ve
15	Gemini's δ_1 "resistance" is template-dependent, not contradiction tolerance	Confirmatory (36c)	3 template fan

Table 9: LLM experiment evidence summary. †The exponential form in LLM is pattern-consistent but not independently discriminated from other nonlinear forms in the low-δ regime where $e^{-\delta} \approx 1 - \delta$ (see §6). The exponential form is anchored by the SAT identity (Section 4), not by LLM data alone. ‡Complete collapse (0%) observed for all OpenAI models tested and Gemini 2.5 Flash. Gemini 3.1 Flash-Lite achieves partial accuracy at short context (32K: 40%), but Exp. 36c confirms this is a template-mix artefact: reassignment templates ("$a = a + 1$") are executed as literal updates (3% accuracy, 50% off-by-one), while paradox and nullify templates are detected as contradictions but suppressed under instruction priority (80–97% accuracy). Gemini lacks contradiction detection for reassignment forms specifically; its effective δ is template-dependent. Models below ∼12B parameters (Gemma3 family) do not detect structural contradictions and show no collapse (Table 8). §Originally derived from $\delta = D_{\text{KL}}$: a single low-magnitude δ_5 should contribute negligible information loss. Three distinct patterns emerge: Nano ignores δ_5 (0% adoption), Mini trusts it (32% adoption, constant), Gemini dilutes it (33%→7% adoption with context length). The effective magnitude of δ_5 depends on both model capability and context-length interaction (see Table 11).

Design. A 2×10 factorial design crosses two δ levels (zero vs. structural contradiction at L4–L5 density) with ten context lengths (500 to 128,000 tokens). The task is a fixed arithmetic computation ($a + b + c$) with target variables defined at the start of the context. The $\delta = 0$ condition fills the context with independent, non-contradictory factual sentences unrelated to the target; the $\delta > 0$ condition replaces ∼30% of filler with structural contradictions (self-referential overrides, meta-directives). Each cell comprises 30 trials; needle position is recorded as a covariate.

Pre-registered predictions.

- **H_1 Graceful degradation:** Under $\delta = 0$, accuracy decline as a function of context length is logarithmic or linear; no step-function collapse occurs at any length.
- **H_2 Phase transition:** Under $\delta > 0$, accuracy exhibits a step-function collapse at some critical context length, qualitatively different from the $\delta = 0$ curve.
- **H_3 Qualitative difference:** A log-linear model $\text{acc} = a - b\ln(\ell)$ achieves lower AIC than a sigmoid model for $\delta = 0$; the reverse holds for $\delta > 0$.

Rationale. If $\delta = D_{\text{KL}}$ (Section 6.2), then $\delta = 0$ implies the posterior equals the prior, and the phase-transition condition $\delta > \delta_c$ is never satisfied regardless of context length. Degradation at $\delta = 0$ should arise only from attention dilution and positional encoding limitations—mechanisms that produce smooth, gradual decline rather than abrupt collapse. Confirmation of H_1–H_3 would establish that *contradiction, not context length, is the necessary condition for phase-transition-type failure in LLMs.*

Results. Table 10 reports results from six models across four vendors. GPT-4o-mini (OpenAI) was tested across nine context lengths (500–96,000 tokens, 30 trials each; 128K excluded due to API truncation artefact). Gemini 2.5 Flash and Gemini 3.1 Flash Lite (Google) were tested across five context lengths (500–8,000 tokens, 30 trials each). Claude Sonnet 4 (Anthropic Batch API) was tested across five context lengths (500–8,000 tokens, 30 trials each). Two additional models extend the range: Claude Sonnet 4.6 (Anthropic Batch API) was tested across five context lengths (16,000–128,000 tokens, 30 trials each), and Llama 3.1:8b (Meta, local via Ollama) was tested across five context lengths (500–8,000 tokens, 30 trials each).

Model	Vendor	Context	$\delta = 0$ acc.	$\delta > 0$ acc.	Gap
GPT-4o-mini	OpenAI	500–96K	100.0% (270/270)	10.4% (28/270)	89.6 pp
Gemini 2.5 Flash	Google	500–8K	100.0% (150/150)	0.0% (0/150)	100.0 pp
Gemini 3.1 Flash Lite	Google	500–8K	100.0% (150/150)	64.0% (96/150)	36.0 pp
Claude Sonnet 4	Anthropic	500–8K	100.0% (150/150)	74.0% (111/150)	26.0 pp
Claude Sonnet 4.6	Anthropic	16K–128K	100.0% (148/148)[a]	82.6% (123/149)[b]	17.4 pp
Llama 3.1:8b	Meta	500–8K	36.0% (54/150)	2.7% (4/150)	33.3 pp

[a]3 trials returned empty responses (API transient errors) and are excluded from the denominator. [b]Strict accuracy (exact numerical match). A secondary "recognition" metric—whether the model identified the correct variable values a, b, c while rejecting contradictions—yields 100% (149/149). All 26 strict failures occurred because the model analysed contradictions in prose and the answer-extraction heuristic (last integer in response) captured an artefactual number rather than the sum. See Limitations (§5.8).

Table 10: Exp. 35 cross-model results (six models, four vendors). Under $\delta = 0$, models with sufficient baseline capability (μ) maintain perfect accuracy; the 8B-parameter Llama 3.1 achieves only 36%, confirming that $\delta = 0$ sets an upper bound at μ rather than guaranteeing perfection. Under $\delta > 0$, accuracy degrades across all models.

Key findings:

1. **H_1 strongly supported.** Under $\delta = 0$, accuracy is bounded by model capability μ: models with sufficient μ (GPT-4o-mini, Gemini Flash, Gemini 3.1 FL, Sonnet 4, Sonnet 4.6) achieve 100% across all context lengths up to 128,000 tokens, while Llama 3.1:8b plateaus at 36%—consistent with the survival equation $S = \mu \cdot e^{-\delta}$ where $\delta = 0$ yields $S = \mu$. Crucially, no model exhibits step-function collapse under $\delta = 0$; the log-linear model is preferred by AIC.

2. **H_2 modified.** Collapse under $\delta > 0$ is not length-dependent: GPT-4o-mini drops to ∼10% immediately at 500 tokens and remains flat across all lengths; Gemini 2.5 Flash drops to 0%. The phase transition threshold is δ itself, not context length. Claude Sonnet 4.6, tested up to 128,000 tokens (150,000 Claude-internal tokens[7]), maintains 100% recognition accuracy at all lengths—the model detects and rejects contradictions rather than complying with them.

3. **H_3 partially supported.** The $\delta = 0$ and $\delta > 0$ curves are qualitatively distinct (constant 1.0 vs. noisy 0.03–0.20 for GPT-4o-mini; constant 1.0 vs. constant 0.0 for Gemini 2.5 Flash). However, the $\delta > 0$ curve is flat rather than sigmoidal, so the AIC comparison tests the wrong functional forms.

4. **Multiplicative structure confirmed.** The invariant $\text{acc}(\delta > 0) < \text{acc}(\delta = 0)$ holds across all six models. Under $\delta > 0$, accuracy ranges from 0% (Gemini 2.5 Flash) to 82.6% strict / 100% recognition (Sonnet 4.6). The $\delta = 0$ column directly measures μ: the five high-capability models saturate at 100%, while Llama 3.1:8b's $\mu \approx 0.36$ limits its ceiling. The multiplicative structure $S = \mu \cdot e^{-\delta}$ predicts that $\delta > 0$ should reduce accuracy *relative to* μ, and indeed Llama 3.1:8b's $\delta > 0$ accuracy (2.7%) is $0.075 \times \mu$—a >92% reduction from its own baseline, comparable in relative terms to GPT-4o-mini's ∼90% reduction.

These results confirm the convergence maintenance prediction: under $\delta = 0$, accuracy is bounded above by μ and exhibits no step-function collapse regardless of context length. Structural contradiction ($\delta > 0$), not context length, is the necessary condition for phase-transition-type failure.

Limitations. The answer-extraction heuristic `parse_answer()` extracts the last integer from the model's response. For models that analyse contradictions in prose (notably Sonnet 4.6), this produces systematic false negatives: the heuristic captures artefactual integers from quoted contradiction templates (e.g., "$a = a + 1$" → extracts 1) or individual variable values rather than the requested sum. The "recognition" metric in Table 10 accounts for this by verifying whether the correct values a, b, c appear in the response. Future replications should use structured output (JSON mode) or constrained decoding to eliminate this confound. Additionally, raw response text was not saved for GPT-4o-mini (36 `null`-answer trials), Llama, or Gemini runs, precluding retrospective reclassification for those models.

5.9 Exp. 36: δ Intensity × Context Length

Exp. 35 established that $\delta > 0$ causes collapse while $\delta = 0$ does not, but treated contradiction as binary (present/absent). A natural question is whether contradiction *intensity* matters—whether a single, mild inconsistency from a secondary source produces the same collapse as dense self-referential paradoxes. Exp. 36 extends Exp. 35 from two δ levels to three, crossing them with context lengths that substantially exceed the 128K ceiling of Exp. 35.

[7] A consistent +17.4% tokeniser drift was measured between `tiktoken` (o200k_base, used for length estimation) and Claude's internal tokeniser across all context lengths.

Design. A 3×3 factorial design crosses three δ conditions with three context lengths (32K, 128K, 256K tokens). The task is identical to Exp. 35 (compute $a + b + c$ from definitions placed at the start of the context). The three δ conditions are:

- **Zero (δ_0):** Filler consists entirely of non-contradictory factual sentences, as in Exp. 35.
- **Subtle (δ_5):** A single sentence from a "secondary source" reports a slightly wrong value for one variable (offset $\pm\{2, 3, 5, 7\}$), injected at the midpoint of the filler. This corresponds to δ_5 (inter-source contradiction) in the five-dimensional δ taxonomy identified in Exp. 5. Example: *"A secondary source reports* $b = 139$*."* (true value: $b = 137$).
- **Structural (δ_1):** Self-referential contradictions at $\sim$30% density, identical to the $\delta > 0$ condition in Exp. 35. This corresponds to δ_1 (self-contradiction).

Each cell comprises 30 trials per model ($n = 270$ per model). Three models are tested: GPT-4.1 Nano (Phase 1), GPT-4.1 Mini (Phase 2a), both OpenAI, and Gemini 3.1 Flash-Lite Preview (Phase 2b, Google), all March 2026, with $\geq$1M-token context windows. The within-vendor pair (Nano/Mini) provides a capability gradient ($\mu_{\text{Nano}} < \mu_{\text{Mini}}$) while controlling for API infrastructure, tokeniser, and training pipeline; the cross-vendor model (Gemini) tests generalisability. All trials save the complete raw response text, API token usage (for tokeniser drift tracking), and—for the subtle condition—the injected variable, original value, wrong value, and wrong-value sum. A post-hoc LLM-as-Judge evaluation independently classifies each trial ($N = 810$ total).

Pre-registered predictions.

P_1 $\text{acc}(\delta_0) \approx \text{acc}(\delta_5) > \text{acc}(\delta_1)$: subtle contradiction is harmless; only structural contradiction causes collapse.

P_2 `wrong_val_adopted` $= 0$ across all subtle trials: the model does not adopt the injected wrong value.

P_3 $\text{acc}(\delta_0)$ declines monotonically with context length (baseline μ degradation), but without step-function collapse.

Results. Table 11 reports the full 3×3 matrix for all three models. Phase 1 predictions are confirmed for GPT-4.1 Nano; Phase 2 reveals a striking reversal for GPT-4.1 Mini and a third, distinct pattern for Gemini.
Key findings:

1. **P_1: three qualitatively distinct δ_5 response patterns.** For Nano, $\delta_5 \approx \delta_0 \gg \delta_1$ (Fisher exact $p \geq 0.53$): the subtle contradiction is invisible. For Mini, δ_5 is catastrophically effective (100% $\rightarrow$ 37% at 32K, $\rightarrow$ 7% at 128K). For Gemini, δ_5 sensitivity *decreases* with context length (57% $\rightarrow$ 80% $\rightarrow$ 90%), consistent with information dilution making a single contradictory sentence progressively harder to retrieve.
2. **P_2: three-polar `wrong_val_adopted` pattern.** Nano: 0/90 (0%—never adopted the wrong value). Mini: 29/90 ($\sim$33% at each context length, constant across lengths). Gemini: 17/90 overall, *decreasing* from 33% at 32K to 17% at 128K to 7% at 256K. Mini's constant adoption rate suggests a fixed probability of trusting the secondary source; Gemini's declining rate is consistent with dilution reducing the salience of the injected sentence.
3. **P_3 confirmed: μ degrades continuously with context length.** Under δ_0, Nano: 1.00 $\rightarrow$ 0.83 $\rightarrow$ 0.70; Mini: 1.00 $\rightarrow$ 1.00 $\rightarrow$ 0.97; Gemini: 1.00 $\rightarrow$ 1.00 $\rightarrow$ 1.00. Gemini maintains perfect baseline accuracy to 256K, demonstrating that μ-decay is model-specific, not a universal feature of long contexts.

Model	δ condition	32K	128K	256K
Nano	Zero (δ_0)	1.00 (30/30)	0.83 (25/30)	0.70 (21/30)
	Subtle (δ_5)	0.97 (29/30)	0.73 (22/30)	0.70 (21/30)
	Structural (δ_1)	0.00 (0/30)	0.00 (0/30)	0.00 (0/30)
Mini	Zero (δ_0)	1.00 (30/30)	1.00 (30/30)	0.97 (29/30)
	Subtle (δ_5)	0.37 (11/30)	0.07 (2/30)	0.13 (4/30)
	Structural (δ_1)	0.00 (0/30)	0.00 (0/30)	0.00 (0/30)
Gemini FL	Zero (δ_0)	1.00 (30/30)	1.00 (30/30)	1.00 (30/30)
	Subtle (δ_5)	0.57 (17/30)	0.80 (24/30)	0.90 (27/30)
	Structural (δ_1)	0.40 (12/30)	0.07 (2/30)	0.07 (2/30)

30 trials per cell per model ($n = 270$ each, $N = 810$ total). Strict accuracy (exact match). Gemini FL = Gemini 3.1 Flash-Lite Preview. `wrong_val_adopted`: Nano = 0/90 (0%), Mini = 29/90 (32%, constant across lengths), Gemini = 17/90 (19%, decreasing: 33%→17%→7%). LLM-as-Judge agreement: 810/810.

Table 11: Exp. 36 results. Three qualitatively distinct δ_5 response patterns emerge: Nano ignores the subtle contradiction entirely (statistically indistinguishable from δ_0; Fisher exact $p \geq 0.53$), Mini is catastrophically vulnerable (adoption rate ∼33% independent of length), and Gemini shows length-dependent recovery (57% → 90%; adoption decreases from 33% to 7% as context dilutes the single contradictory sentence). Under structural δ_1, both OpenAI models collapse to 0% at all lengths, while Gemini achieves 40% at 32K—but through literal misinterpretation rather than contradiction detection (see text).

4. **Capability–vulnerability paradox.** The central finding: the relationship between capability and δ_5 vulnerability is non-monotonic. Nano (lowest μ) ignores the contradiction entirely; Mini (highest μ within OpenAI) reads and trusts it; Gemini (highest μ overall) reads it at short context but dilutes it at long context. This dissociation—comprehension without verification—is not a simple function of capability but depends on model architecture and context-length interaction.

5. **Three qualitatively distinct δ_1 failure modes.** Structural self-contradiction (δ_1) produces 0% accuracy for both OpenAI models at all lengths, while Gemini achieves 40% at 32K. The crucial difference is *how* each model fails: Nano outputs "0" or "undefined" (53%–90% zero-responses; detects contradiction); Mini outputs "Undefined" or analytical refusals (93–100% explicit refusal; correctly identifies logical impossibility); Gemini outputs numeric guesses near the expected value +1 (50–57% of incorrect answers have diff = +1; it interprets "$a = a + 1$" as literal reassignment $a_{\text{new}} = a_{\text{original}} + 1$, *never detecting the reassignment form as a contradiction*: `contradiction_detected` = 0/90, refusal = 0/90). Gemini's 40% "accuracy" at 32K is an artefact: the structural condition mixes reassignment templates (which Gemini executes as +1) with paradox and nullify templates (which Gemini detects as contradictions but suppresses under the calculator-only instruction, yielding correct answers); the 40% reflects the template-mix proportion, not contradiction tolerance. This is confirmed by the targeted Exp. 36c and subsequent probe experiment below.

6. **Cross-vendor replication of $\delta_1 \gg \delta_5$ hierarchy.** Despite the three distinct δ_5 patterns, all three models confirm the core finding: structural contradiction (δ_1) causes catastrophically greater damage than inter-source contradiction (δ_5). This holds across OpenAI (Nano, Mini) and Google (Gemini), strengthening the claim that the dimensional structure of δ is a property of the task, not of any particular model family.

Exp. 36c: Evidence for a literal-reassignment mechanism. Finding 5 above hypothesised that Gemini's partial δ_1 accuracy arises from interpreting "$a = a + 1$" as variable reassignment rather than detecting a logical contradiction. To test this, we isolated the three template

families used in the structural condition and administered each in a separate experiment (30 trials per family, 32K tokens, Gemini 3.1 Flash-Lite, same protocol).

Template family	**Example**	**Accuracy**	**Off-by-n**	**Interpretation**
Reassignment	"$a = a + 1$"	3% (1/30)	50% (15/30)	Executes +1
Paradox	"$a \neq a$", "$a > a$"	80% (24/30)	0% (0/30)	Detects; suppresses
Nullify	"a is invalid"	97% (29/30)	0% (0/30)	Detects; suppresses

The off-by-n pattern $(+1, +2, +3)$ occurs *exclusively* in the reassignment family, consistent with Gemini treating "$a = a + 1$" as an imperative update. The diff distribution $\{+1 : 15,\ +2 : 10,\ +3 : 2,\ +4 : 1\}$ is consistent with cumulative reassignment: at 30% injection density, some variables receive multiple +1 operations. Paradox and nullify templates produce no off-by-n errors, yielding near-perfect accuracy—but this is *not* because Gemini cannot parse them. A follow-up probe experiment (below, $n = 5$ per condition) provides evidence that the mechanism differs between template families.

Probe: two independent mechanisms. To determine whether Gemini's high paradox/nullify accuracy reflects inability to detect contradictions or active suppression, we administered the same three template families under two system-prompt conditions: (i) the standard calculator-only prompt ("Give ONLY the final numerical answer") and (ii) a detection prompt ("If any contradictions exist, report them; then compute the answer"). Five trials per condition, 32K tokens, Gemini 3.1 Flash-Lite.

Template	**Metric**	**Calculator-only**	**Detect + calc**
Reassignment	Answer	705 (5/5)	705 (5/5)
	Contradictions reported	None (5/5)	"No contradictions found" (5/5)
Paradox	Answer	690 (5/5)	690 (5/5)
	Contradictions reported	None (5/5)	"Law of Identity violation" (5/5)
Nullify	Answer	690 (5/5)	690 (5/5)
	Contradictions reported	None (5/5)	"Contradicts definition" (5/5)

The results are consistent with two independent mechanisms operating simultaneously (though the small sample size of $n = 5$ per condition warrants caution):

- **Syntactic classification bypass** (reassignment): Gemini's processing pipeline classifies "$a = a + 1$" as an assignment instruction, not a contradiction. Even when explicitly asked to report contradictions, it returns "No contradictions found" (5/5) while computing $a_{\text{new}} = a + 1$. The reassignment form never enters the contradiction-detection path. The result $705 = 690 + 15$ (= 3 variables × cumulative +1 operations) is fully consistent with imperative execution.

- **Instruction-priority suppression** (paradox/nullify): Gemini *does* detect these contradictions—it precisely identifies "$a \neq a$" as a "Law of Identity violation" and nullification as "contradicting the definition" when asked. Under the calculator-only prompt, it suppresses this detection and computes the correct answer (690, 5/5). The contradiction is perceived but deprioritised relative to the task instruction.

This resolves Gemini's apparent δ_1 "resistance" in Exp. 36: the structural condition mixes all three template families, so the 40% accuracy at 32K reflects the proportion of trials where paradox/nullify templates dominate. Gemini lacks contradiction detection capability *specifically for reassignment-form contradictions*, whose syntactic structure is indistinguishable from a legitimate variable update. For paradox and nullify forms, Gemini possesses full detection capability

but prioritises instruction compliance over contradiction reporting. The effective δ of a structural contradiction is therefore template-dependent for this model: reassignment templates carry $\delta_{\text{eff}} > 0$ (executed as +1, altering the answer), while paradox and nullify templates carry $\delta_{\text{eff}} \approx 0$ (detected, suppressed, and ignored).

Practical implication. The three-model comparison has direct consequences for RAG system design. First, δ_5 vulnerability is not monotonically related to capability: Mini (the strongest OpenAI model tested) is most vulnerable, while both weaker (Nano) and cross-vendor (Gemini) models show less vulnerability, albeit for different reasons. RAG pipelines cannot assume that higher-capability models are uniformly safer. Second, Exp. 36c demonstrates that contradiction detection is not a universal capability: Gemini processes "$a = a + 1$" as a variable update rather than recognising the self-referential impossibility, while ignoring contradiction forms it cannot parse. This means that the *effective* δ of a structural contradiction depends not only on its logical content but on whether the model's syntactic processing pipeline can interpret it as an actionable instruction. Structural contradictions (δ_1) must be filtered regardless of model capability; the filtering must cover diverse syntactic realisations, since models may be vulnerable to some forms while ignoring others.

Improvements over Exp. 35. Exp. 36 addresses all Exp. 35 limitations identified in §5.8: raw responses are saved for every trial (enabling retrospective analysis); maximum response tokens are increased from 64 to 512 (preventing truncation of analytical responses); and LLM-as-Judge evaluation provides an independent correctness check (strict/judge agreement: 810/810, 100% across all three models). Additionally, tokeniser drift is tracked per-trial (observed drift: +0.01–0.08% across all context lengths, confirming measurement infrastructure accuracy). The three-model, two-vendor design enables both within-vendor capability comparisons (Nano vs Mini) and cross-vendor generalisation (Gemini).

5.9.1 Multi-Attractor Interpretation of Exp. 36

The three qualitatively distinct response patterns in Exp. 36 under subtle contradiction (δ_5) can be interpreted as different attractor basin structures, where basin A is "output the correct answer" and basin B is "adopt the contradictory value." The multi-attractor extension (§3.4) predicts $P(\text{correct}) = S_A/(S_A + S_B)$; if the context-length margin μ is proportional to L, this yields $P(\text{correct}) = 1/(1 + K/L)$ for a constant K.

Nano (no transition). `wrong_val_adopted` $= 0/90$ across all context lengths. Interpretation: the model cannot parse δ_5 contradictions, so $I_A \approx 0$ and $S_A \gg S_B$ at all L. The system never approaches the transition point.

Mini (length-independent vulnerability). `wrong_val_adopted`: 33% (32K), 37% (128K), 33% (256K)—no significant L-dependence. Interpretation: context length acts equally on both basins (S_A and S_B share the same L-dependence), so S_B/S_A is a constant independent of L. The contradiction is neither diluted nor amplified by longer context.

Gemini (information dilution). `wrong_val_adopted`: 33% (32K), 17% (128K), 7% (256K)—monotonically decreasing. The model $P(\text{correct}) = 1 - P(\text{wrong_val})$ at each context length is 0.67, 0.83, 0.93. Fitting $P = 1/(1 + K/L)$ yields $K \approx 16$, 26, 18 respectively ($K \approx 20 \pm 5$, same order of magnitude given $n = 30$ per condition). This is consistent with context length serving as the margin ($\mu \propto L$) for the correct-answer basin only: longer contexts dilute the contradictory information, increasing S_A relative to S_B.

Pre-registered prediction and confirmation. The $P = 1/(1 + K/L)$ model with $K \approx 20$ (in units of thousands of tokens) was derived from Exp. 36 data at L = 32K, 128K, 256K and used to generate a prediction *before* running the 512K experiment: $P(512\text{K}) \approx 0.96$. The subsequent experiment ($n = 30$, identical protocol) yielded $P = 29/30 = 0.97$, within 1% of the prediction (binomial 95% CI: $[0.82, 1.00]$). The δ_0 control confirmed 30/30 correct at 512K. The full trajectory:

Context	wrong_val adopted	P(correct)	Predicted P	K (fitted)
32K	10/30	0.67	0.62	16.0
64K	6/30	0.77	0.76	19.2
128K	5/30	0.83	0.86	25.6
256K	2/30	0.93	0.93	19.2
512K	1/30	0.97	0.96	17.6

The 64K and 512K data points are genuine out-of-sample predictions: the model $P = 1/(1 + K/L)$ with $K \approx 20$ was derived from three points (32K, 128K, 256K) before the confirmation experiments. Both predictions matched observations within 1%. Across five context lengths spanning a 16× range, the mean absolute error is 2%—well below the binomial noise floor ($\sigma \approx 8\%$ for $n = 30$). The monotonic decrease in `wrong_val` adoptions ($10 \to 6 \to 5 \to 2 \to 1$) is consistent with context length serving as the margin variable ($\mu \propto L$) in the multi-attractor framework. The fitted K across all five points is 19.5 ± 3.4, supporting the constant-K assumption. The physical interpretation of $K \approx 20$ (in units of thousands of tokens) is the transition point m^* from the multi-attractor theorem: the context length at which the correct-answer basin and the contradictory-value basin have equal survival potential ($S_A = S_B$).

6 Discussion

6.1 What Has Been Established

The core contribution is operational: cumulative information loss (δ) can be defined as $\sum_i I(\text{constraint}_i)$ in nats, with $e^{-\delta}$ corresponding to the first moment of the solution count. This is not a new theorem; it is the application of the first moment method [2] to the survival context. The multiplicative structure $S = N_{eff} \cdot (\mu/\mu_c) \cdot e^{-\delta}$ is the structure of serial reliability: any factor approaching zero is fatal. The mathematical form $R = \prod_i r_i$ is well established in reliability engineering [4], where failure modes are enumerated from known component lists. Our contribution is not the product structure itself but the identification of *what constitutes* δ in each domain—clause density in SAT, prompt-level contradiction structure in LLM—a domain-specific discovery that the reliability framework does not address.

An important epistemological distinction applies. In SAT, the correspondence between $e^{-\delta}$ and the first moment is a *mathematical identity*—a variable substitution within the same formalism. In LLM and ecological domains, the correspondence is in general a *structural analogy*: the multiplicative form is empirically tested, not derived from domain-specific first principles. For LLM tasks with explicitly named variables, however, the axioms A1–A3 admit a formal instantiation via consistent world models (§6.1), establishing $e^{-\delta}$ as a theorem for that task class. Furthermore, "survival" ($S > 0$) denotes different phenomena across domains—satisfiability (existence of solutions), task accuracy (functional performance), bleaching resistance (ecological persistence)—unified not by ontological identity but by shared mathematical structure under accumulating constraints.

The framework rests on three layers with different epistemic status:

1. **Mathematics** (unconditional): The identity $e^{-\delta} = \prod_i p_i$ and the information budget

$\ln S = \ln N_{eff} + \ln(\mu/\mu_c) - \delta$ are algebraic consequences of defining $\delta = \sum_i(-\ln p_i)$. These hold by construction.

2. **Structure** (unconditional): The first moment $\mathbb{E}[\#\text{SAT}] = 2^n \cdot e^{-\delta}$ is *exact* for random SAT—not an approximation. The derivation uses linearity of expectation and independence of constraint *generation* (clauses drawn independently, which is true by construction), not independence of constraint *effects* on the solution space. For a fixed assignment σ, the events $\{\sigma \text{ satisfies } C_i\}$ are independent because the clauses were generated independently, regardless of whether they share variables. Markov's inequality ($\mathbb{E}[X] < 1 \implies \Pr[X \geq 1] = 0$) then yields a valid upper bound on the satisfiability threshold. Neither step requires any assumption about inter-constraint correlations in the solution space.

3. **Precision** (domain-dependent): The 20% gap between $\alpha_c^{(1)} \approx 5.19$ and $\alpha_c \approx 4.27$ arises not because $\mathbb{E}[\#\text{SAT}]$ is wrong, but because the *distribution* of #SAT is skewed: near the true threshold, the expectation is exponentially large yet almost all instances have #SAT = 0—a few rare instances with exponentially many solutions inflate the mean. This is a correlation between *assignments* (knowing $\sigma \in \text{SAT}$ predicts that nearby $\tau \in \text{SAT}$), not between constraints. The second moment method (Paley-Zygmund inequality) provides the complementary direction: $\Pr[X > 0] \geq \mathbb{E}[X]^2/\mathbb{E}[X^2]$. The overlap decomposition $\mathbb{E}[X^2] = 2^n \sum_d \binom{n}{d} g(d/n)^m$, where $g(\beta) = 3/4 + (1/8)(1-\beta)^3$ is the pair correlation function, yields a threshold lower bound. Numerical evaluation shows that truncated second-moment methods explain 74% of the gap ($\alpha_c^{(2)} \approx 4.51$); the remaining 26% requires higher-order correlations. The pair correlation function satisfies $g(1/2)/(7/8)^2 = 1$ exactly, so the typical-overlap contribution is neutral—the gap arises entirely from high-correlation pairs ($\beta \approx 0$). Each domain has its own gap, measurable by domain experts through comparison of first-moment predictions with observed thresholds.

This three-layer structure clarifies what independence does and does not affect. The first moment bound is *valid* regardless of correlations; independence affects *precision*, not validity. In LLM experiments, independence of δ and μ is ensured by factorial experimental design, and the multiplicative interaction is empirically confirmed. In Level B domains (ecology, organisations), the equation functions as a mean-field baseline whose deviations from data measure the strength of inter-constraint correlations—analogous to the ideal gas law. The methodology for measuring these deviations in Level B domains is currently undeveloped, as the true threshold against which to compare is unknown.

The SAT experiments confirm the first moment correspondence with $R^2 > 0.99$ for structured constraints (XOR, implication chain) and exponential fits preferred over power-law across all three constraint types, yielding parameter-free predictions (decay rate ratios). The LLM experiments confirm multiplicative $\mu \times \delta$ interaction and discover the cushion mechanism. The two domains are complementary: SAT validates the $e^{-\delta}$ component with exact δ computation; LLM validates the multiplicative $\mu \times \delta$ interaction and reveals that structural contradictions are qualitatively distinct from factual noise.

Information budget interpretation. In logarithmic form, the survival equation becomes $\ln S = \ln N_{eff} + \ln(\mu/\mu_c) - \delta$, where all three terms are measured in nats. This is not merely a consequence of taking logarithms of any multiplicative equation: δ is *defined* as information loss ($I = -\ln p$, nats), so the fact that $\ln N_{eff}$ and $\ln(\mu/\mu_c)$ share the same unit reflects a genuine information-theoretic structure. The survival condition $S > S_c$ becomes an information budget: the system survives when information capacity ($\ln N_{eff} + \ln(\mu/\mu_c)$) exceeds information loss (δ). This parallel to Shannon's channel coding theorem [24] can be made precise at three levels (§6.2): (i) δ equals the KL divergence between prior and posterior distributions for independent constraints, with the gap governed by the second moment ratio; (ii) XOR-SAT constraints are literally parity checks, making constraint satisfaction and channel coding the same mathematical

object; (iii) the survival condition $\delta < \ln(N_{eff} \cdot \mu/\mu_c)$ is structurally isomorphic to the channel coding theorem $R < C$, with the converse unconditionally valid and achievability partially established via the second moment method. The framework and key structural properties—including the exponent function $\varphi(\beta, \alpha) = h(\beta) - \ln 2 + \alpha \ln R(\beta)$ where $\varphi(1/2, \alpha) = 0$ for all α—are formally verified in Lean 4.

Epistemic status of the three terms. The information-theoretic grounding differs across the three factors. For δ, the connection is exact: $I(C_i) = -\ln p_i$ is Shannon self-information by definition, and $e^{-\delta}$ is the first moment. For $\ln N_{eff}$, the connection is standard: $\ln N_{eff}$ is the entropy of a uniform distribution over available options. For $\ln(\mu/\mu_c)$, the connection is the least developed. In the LLM experiments, μ functions as available processing capacity and μ_c as the minimum capacity required by the task, making $\ln(\mu/\mu_c)$ interpretable as excess channel capacity. Whether this interpretation extends rigorously to other domains—and whether μ_c can be derived rather than measured—remains an open question. We note that in domains with mature independent theories, all parameters *are* derivable: in site percolation, $\mu_c = p_c$ follows from lattice geometry ($p_c = 1/2$ exactly for 2D triangular; $p_c \approx 0.3116$ for 3D simple cubic [26]); in nuclear stability, the critical threshold follows from the Bethe–Weizsäcker mass formula. The predictive power of the survival equation thus depends on the maturity of domain-specific theory that provides its inputs, not on free parameters within the equation itself. Until such theories mature, μ_c should be treated as an operationally fitted parameter—estimated from survival data within each domain, analogous to how empirical constants are calibrated before first-principles derivation becomes available. Practical guidelines for such estimation are discussed as a future direction (Section 6.6).

Measurement asymmetry across domains. A key asymmetry underlies this domain dependence. In SAT, the elimination fraction f_i for each constraint is computed from the problem structure as an *input* to the equation; δ is a property of the problem instance. In LLM, f_i is inferred from survival measurements as an *output*—$I_i = -\ln(S_i/S_0)$—making δ a property of the input–system interaction. The dimensional structure of δ (the ordering of constraint types by severity: $I_{\text{factual}} \ll I_{\text{structural}}$) is confirmed without circularity, since the ordering is observable independently of the equation. However, the absolute scale of I for each constraint type depends on inverting the equation and cannot currently be derived from first principles for LLM. Developing equation-independent methods for estimating f_i in LLM is the principal open challenge for elevating the framework's predictive power in this domain to the level achieved in SAT.

Cross-domain alternatives. Truong and Truong [33] independently proposed that feedback amplification exceeding finite novelty-regeneration capacity drives "entropy collapse" across AI, economic, and biological systems—a qualitative dynamical model that shares our "smarter systems are more fragile" insight but lacks the nats-based quantification, multiplicative structure, and controlled experimental validation provided here. Axenie, West et al. [34] quantified antifragility as the convexity of system output response to environmental perturbation variability, applying it across traffic, robotics, and oncology. Their framework measures *response to perturbation* rather than *accumulation of structural conflict*, and uses convexity-based rather than information-theoretic metrics; the two approaches are complementary.

Scope of the axiomatic derivation. The derivation in §3.2 is domain-agnostic: any system satisfying axioms A1–A3 (finite state space, fractional elimination, independence) produces the same exponential form $e^{-\delta}$, and the Cauchy characterization (§3.2) shows this form is unique among continuous functions. The empirical contribution of this paper is not the derivation itself—which is a standard consequence of the product rule for independent events—but the demonstration that two structurally distinct domains, combinatorial satisfiability and neural language generation, approximately satisfy these axioms and exhibit the predicted behavior.

Formal instantiation for variable-assignment tasks. The "structural analogy" characterization applies to LLM tasks in general. For the specific task class used in the experiments of

this paper—where the context explicitly specifies a finite set of named variables and the query requires computing a function of those variables—the axioms A1–A3 admit a *formal instantiation* that closes the analogy gap.

Define the *effective state space* Ω as the set of *consistent world models*: complete assignments of values to all named variables that are logically consistent with the context. Then:

- **A1 (Finite state space)**: $|\Omega|$ is finite, bounded by the product of each variable's value domain.
- **A2 (Fractional elimination)**: A contradiction targeting variable v eliminates all world models where v takes the contradicted value—a fraction p_v determined by the variable's domain, independently of the context's other content.
- **A3 (Independence)**: Contradictions targeting distinct variables $v \neq w$ act on disjoint coordinates of Ω and are therefore independent: $\Pr[\text{eliminated by } C_v \text{ and } C_w] = \Pr[\text{eliminated by } C_v] \cdot \Pr[\text{eliminated by } C_w]$.

Under this instantiation, `AxiomsToExp.lean` applies without modification: $e^{-\delta}$ holds as a *theorem* for variable-assignment tasks, not as a structural analogy. Crucially, δ is defined from the constraint structure (the contradiction's target variable and value), not inferred from accuracy measurements—reproducing the SAT situation where δ is an input, not an output. For tasks without explicit variable separation—open-ended dialogue, multi-hop reasoning over implicit knowledge—the analogy characterization and weak dependence bounds (§3.5) remain the applicable guarantees.

6.2 Information-Theoretic Grounding

The survival equation's connection to information theory extends beyond shared vocabulary (nats, self-information) to three formal results that close the gap between the survival framework and Shannon's theorems. Result 1 has been machine-verified in Lean 4 as the `Survival.KLDivergence` module (`sorry` = 0, `axiom` = 0).

Result 1: δ–KL divergence duality. Let P_0 be the uniform distribution over $\{0,1\}^n$ and P_{SAT} the uniform distribution over satisfying assignments. Since both are uniform, $D_{\text{KL}}(P_{\text{SAT}} \| P_0) = \ln(2^n/Z)$ where $Z = |\text{SAT}|$. For independent constraints (no shared variables), $Z = 2^n \cdot \prod_i p_i = 2^n \cdot e^{-\delta}$ exactly, so $D_{\text{KL}} = \delta$: cumulative information loss *is* the KL divergence between the unconstrained and constrained distributions. In general, Jensen's inequality applied to the concave function ln yields $\mathbb{E}[D_{\text{KL}}] = n \ln 2 - \mathbb{E}[\ln Z] \geq n \ln 2 - \ln \mathbb{E}[Z] = \delta$, with equality if and only if Z is deterministic. The gap $\mathbb{E}[D_{\text{KL}}] - \delta = \ln \mathbb{E}[Z] - \mathbb{E}[\ln Z]$ is characterized by the second moment ratio $R_2 = \mathbb{E}[Z^2]/\mathbb{E}[Z]^2$ via the approximation $\mathbb{E}[D_{\text{KL}}] - \delta \approx (R_2 - 1)/2$. This connects the three results already established: (a) the first moment gives δ as a lower bound on D_{KL}; (b) the pair correlation $g(\beta)$ governs R_2; (c) the second moment ratio quantifies how far δ departs from the true divergence.

Result 2: Constraint satisfaction as channel coding. For XOR-SAT, the connection is exact: each constraint $x_{i_1} \oplus x_{i_2} \oplus x_{i_3} = b_i$ is a parity check equation over GF(2), and the constraint matrix $H \in \text{GF}(2)^{m \times n}$ is a parity check matrix defining a linear code. The satisfying assignments form the coset $\{x : Hx = b\}$ with $|\text{SAT}| = 2^{n - \text{rank}(H)}$, the code rate is $R = 1 - m/n = 1 - \alpha$, and each constraint provides exactly $\ln 2$ nats of information, giving $D_{\text{KL}} = m \ln 2 = \delta$ for *every* instance (not merely in expectation). The satisfiability threshold $\alpha_c^{\text{XOR}} = 1$ corresponds to $R = 0$: the code has been compressed to a single point. For random 3-SAT, each clause provides only $\ln(8/7) \approx 0.134$ nats (vs. $\ln 2 \approx 0.693$ for XOR), yielding the information efficiency ratio $\ln 2 / \ln(8/7) \approx 5.19$—the same quantity that appears as the first-moment threshold ratio and the experimentally confirmed decay rate ratio.

Result 3: Structural capacity theorem. Define the *structural capacity* $C_{\text{struct}} = \ln(N_{eff} \cdot \mu/\mu_c)$. The survival condition $S \geq 1$ is equivalent to $\delta \leq C_{\text{struct}}$, which is structurally isomorphic

to Shannon's channel coding theorem ($R \leq C$). The two directions of Shannon's theorem have direct counterparts:

- *Converse* ($\delta > C_{\text{struct}} \implies$ collapse): The first moment method plus Markov's inequality gives $\mathbb{E}[Z] < 1 \implies \Pr[Z \geq 1] = 0$. This holds unconditionally.
- *Achievability* ($\delta < C_{\text{struct}} \implies$ survival): The second moment method (Paley–Zygmund) gives $\Pr[Z > 0] \geq \mathbb{E}[Z]^2/\mathbb{E}[Z^2]$, which is positive when R_2 is bounded. For XOR-SAT this is tight ($R_2 = 1$); for random 3-SAT the truncated second moment establishes achievability up to $\alpha \approx 4.51$.

Verification in SAT: with $N_{eff} = 2^n$ and $\mu/\mu_c = 1$, we obtain $C_{\text{struct}} = n \ln 2$. The first-moment threshold satisfies $\delta_c^{(1)} = \alpha_c^{(1)} \cdot n \cdot \ln(8/7) = n \ln 2 = C_{\text{struct}}$ exactly. The interpretation is that the system collapses when the cumulative information loss from constraints exhausts the entropy of the state space—a finite-dimensional, nonlinear generalization of the channel coding bound.

6.3 Context Rot as δ Accumulation

A practical consequence of Exp. 35 deserves emphasis. The phenomenon commonly called "context rot"—the observation that LLM performance degrades as conversation length increases—is conventionally attributed to attention dilution, positional encoding limitations, or retrieval interference [17]. Hong et al. [35] recently confirmed this degradation across 18 frontier models, establishing it as a universal phenomenon. These mechanisms predict smooth, gradual degradation as a function of context length.

Exp. 35 and 36 provide an experimental deconfounding. Under $\delta = 0$ (zero structural contradiction), Exp. 35 shows five high-capability models across four vendors maintaining *perfect* accuracy up to 128,000 tokens. Exp. 36 extends this to 256,000 tokens across three models from two vendors and reveals two nuances. First, accuracy under $\delta = 0$ *does* degrade at very long contexts, but the rate is model-dependent: Nano shows $1.00 \to 0.83 \to 0.70$, Mini shows $1.00 \to 1.00 \to 0.97$, and Gemini maintains 1.00 at all three lengths—confirming that μ decay is smooth and model-specific, not a universal cliff. Second, the subtle-contradiction (δ_5) condition produces three qualitatively distinct patterns: invisible to Nano (statistically identical to δ_0), catastrophic for Mini (37% $\to$ 7%), and *diluted* for Gemini (57% $\to$ 90%, improving with context length as the single contradictory sentence becomes a smaller fraction of the total context). Under $\delta > 0$ (structural), both OpenAI models collapse to exactly 0% at all lengths, while Gemini achieves partial accuracy at 32K through literal reinterpretation of self-referential contradictions ("$a = a + 1$" $\to a_{\text{new}} = a + 1$)—a failure of contradiction *detection*, not computation. The causal variable is contradiction content, not sequence length—but the *effective* δ of a given contradiction depends on both the model's comprehension ability and its context-length interaction.

In naturalistic conversations, context length and δ are confounded: longer conversations accumulate more user corrections ("ignore what I said earlier"), topic shifts (implicit premise conflicts), and meta-directives (instructions that contradict prior instructions). Each of these introduces structural contradiction. What appears as length-dependent degradation is, at least in substantial part, δ-dependent degradation masquerading as a length effect.

This reframing has practical implications:

Conventional approach	**δ-informed approach**
Extend context window	Remove accumulated contradictions
Summarise to compress	Ensure contradiction-free summaries
RAG: retrieve relevant chunks	Verify consistency across retrieved chunks

The distinction is testable: if context rot is primarily δ-driven, then a system that filters contradictions from its context should maintain performance at lengths where an unfiltered system would fail, even without extending the context window. The invariant $\text{acc}(\delta = 0) = \mu$ across all tested models and lengths (Table 10) provides the baseline against which such interventions can be measured. Notably, Claude Sonnet 4.6 under $\delta > 0$ at 128,000 tokens *detected and rejected* the injected contradictions in 100% of trials (recognition metric), demonstrating that sufficiently capable models can maintain δ-awareness even at extreme context lengths—though the strict accuracy was lower due to response format variability.

Exp. 36 (Table 11) sharpens this picture by quantifying both terms of the survival equation at long context—and reveals a surprising interaction between them. Baseline μ degrades measurably for Nano ($1.00 \to 0.70$ across 32K–256K under δ_0), barely for Mini ($1.00 \to 0.97$), and not at all for Gemini (1.00 at all lengths). The three-model comparison reveals a *non-monotonic* relationship between capability (μ) and δ_5 sensitivity. Nano (lowest μ) ignores the secondary-source sentence entirely (`wrong_val_adopted` = 0/90). Mini (high μ, same vendor) reads and trusts it (`wrong_val_adopted` = 29/90, constant across lengths). Gemini (highest μ, different vendor) reads it at short context but dilutes it at long context (`wrong_val_adopted`: $10/30 \to 5/30 \to 2/30$). This implies that δ_5's effective information loss depends on at least two model properties: *comprehension* (ability to extract the contradictory statement, shared by Mini and Gemini but not Nano) and *context integration strategy* (whether the model weighs retrieved information equally regardless of context length, as Mini appears to do, or whether dilution reduces salience, as Gemini's pattern suggests). Structural contradictions (δ_1) are near-universally catastrophic, but the *mechanism* of failure varies: refusal (Mini), computation-to-zero (Nano), or literal reinterpretation (Gemini).

Independent support for the exponential functional form comes from Wang and Sun [36], who found that proactive interference in LLM working memory follows a log-linear decay—mathematically equivalent to $S \propto e^{-k \cdot \text{interference}}$. Their interference variable (semantic similarity-based accumulation) differs from our δ (structural contradiction), but the convergence on the same functional form across different operationalizations strengthens the case for exponential sensitivity to accumulated conflicting information.

6.4 What Has Not Been Established

Scope: structural conflicts vs. random noise. The model applies to systems where perturbations are structural conflicts—logical, policy, or functional contradictions between components. Purely random perturbations produce different functional forms:

Property	Structural conflict	Random noise
Nature of δ	Constraint contradiction	Stochastic degradation
Functional form	Exponential ($e^{-\alpha\delta}$)	Power-law / critical
Example system	SAT, LLM, organisations	Percolation, RMT
Survival model	Native domain	Control comparison (fits but different mechanism)

This distinction is validated experimentally: exponential decay ($R^2 > 0.99$ for structured constraints; exponential preferred over power-law for all types) is confirmed in SAT but not in site percolation, where power-law scaling dominates.

Level B prediction is not demonstrated. The framework currently has no validated quantitative prediction in domains where δ requires proxy measurement. This is a genuine scope limitation, not merely a measurement challenge.

$e^{-\delta}$ vs. $(1 - \delta)$ is weakly discriminated in LLM. In the low-δ regime, $e^{-\delta} \approx 1 - \delta$, and the LLM experiments operate primarily in this regime due to step-function transitions that yield few intermediate data points. In SAT, where δ spans a wide range and is independently measured, the exponential form is preferred over power-law for structured constraints ($R^2 > 0.99$

for XOR and implication chains; Table 1), confirming that the discrimination is achievable in domains with sufficient dynamic range. The 3D percolation test shows a modest advantage for the exponential form in the high-δ regime (ΔAUC $= +0.015$). The two-domain design is essential: SAT provides the functional form discrimination that LLM alone cannot. Accordingly, the LLM experiments' primary aim is not the precise identification of the functional form but the verification of multiplicative interaction between context length and constraint density—a contribution that does not require distinguishing $e^{-\delta}$ from $1 - \delta$.

6.5 Scope Boundary: Structural Conflict vs. Random Removal

As a scope-defining control, we note that percolation (random site removal on a lattice) fits the exponential form at the aggregate level (AUC $= 0.993$ in 2D, 0.982 in 3D) but operates via a fundamentally different mechanism: random removal rather than structural contradiction. Near the percolation threshold, power-law critical scaling—not exponential decay—governs the transition. The survival model applies natively to systems where δ represents the accumulation of structural conflicts (SAT, LLM); it provides a useful fit but not a mechanistic explanation for systems governed by stochastic removal.

6.6 Scope of δ as a Coordinate

A companion study [29] shows that the same structural parameter δ also governs computational cost in SAT solvers, with median runtime scaling as $\mu_c \propto e^{c\delta}$ where the sensitivity exponent c is solver-dependent (CDCL: $c \approx 0.24$, WalkSAT: $c \approx 0.21$, random search: $c = 1.0$ exactly). Two findings from that study qualify the scope of δ in the present framework. First, $\mu_c \propto e^{c\delta}$ means that μ_c is itself a function of δ, introducing a coupling between the μ/μ_c and $e^{-\delta}$ factors that the static equation treats as independent. The static independence remains a useful decomposition, but users should note that manipulating δ will shift μ_c as well. Second, the product structure $\delta = \alpha n |\ln(7/8)|$ does not extend symmetrically to the problem-size direction n: CDCL runtime scales exponentially in both α and n, but WalkSAT scales polynomially in n, breaking the product structure. Accordingly, δ is best understood as a reparameterization of constraint density at fixed system size, not as a universal coordinate over both density and size.

6.7 Cross-Domain δ Proxy Landscape

In the two Level A domains validated in this paper, δ measurement takes different forms:

Domain	**δ definition**	**Free params**	**Epistemic status**
SAT	first moment ($\sum_i I(C_i)$)	0	mathematical identity
LLM (variable tasks)	world-model instantiation	0	theorem (§6.1)
LLM (general tasks)	operational (constraint injection)	≥ 2	structural analogy

Table 12: δ measurement in validated domains. In SAT, δ is computable from problem structure with zero free parameters. In LLM, δ is operationally defined via controlled injection; the absolute information loss per constraint type is inferred from survival measurements, not derived from first principles.

Exploratory proxy attempts in Level B domains (coral bleaching, corporate failure, gene conservation, financial markets) suggest a consistent pattern: proxies that measure *accumulated structural quantities* (e.g., degree-heating weeks, governance events) outperform those that capture instantaneous state (e.g., yield curves, keyword frequency). However, none of these Level B applications have been validated to the standard of this paper, and the results should be treated

as preliminary hypotheses for future investigation, not as evidence for the framework's cross-domain validity.[8]

6.8 Applicability Conditions: Precision vs. Scope

Axioms A1–A3 guarantee the mathematical derivation of $e^{-\delta}$, but they are conditions for *precision*, not for *applicability*. A system may formally satisfy A1–A3 yet remain unsuitable for analysis if the relevant process has already completed (e.g., species assemblages in stable ecosystems, where only survivors are observed). Conversely, a system may violate A3 (independence) yet yield useful predictions if δ is approximately correct in direction and ordering—preliminary exploration suggests this may hold for corporate governance events, though this has not been validated to the standard of the present paper.

The true applicability condition lies upstream of A1–A3: the system must be a dissipative structure in which optimization has not yet converged relative to environmental change. All dissipative structures process δ by definition, but in systems where optimization has completed faster than the environment changes, observations are filtered through prior survival—we observe results, not processes. Crucially, applicability depends on the system's *state*, not its *type*: the same substrate may appear outside scope when analyzed with the wrong proxy yet squarely within scope when the proxy correctly captures structural dependency rather than replaceability (see footnote in Table 12).

The full screening hierarchy is therefore: (0) Has optimization failed to keep pace with environmental change? (1) Can constraints be defined independently of the state space? (2) Do natural module boundaries exist? (3) To what degree does A3 hold? Steps 0–1 determine whether the framework is applicable at all; steps 2–3 determine the precision of the resulting predictions. The weak dependence extension (§3.5) makes step 3 quantitative: given an empirical estimate of constraint correlation ρ, the conservative survival bound $\mu \cdot e^{-\delta(1+\rho)}$ holds regardless of the specific dependence structure. A3 is no longer a binary gate but a continuous parameter that modulates precision.

6.9 Future Directions

Level B domains. The framework generates a testable prediction for any constraint-processing system: among candidate δ proxies, those approximating cumulative structural stress should yield stronger survival fits than non-cumulative alternatives. The primary open challenge is developing domain-specific methods to calibrate δ in nats—that is, to estimate the fraction of viable configurations eliminated by each constraint, which requires identifying both the relevant configuration space and the appropriate margin variable (μ) for each domain.

Regime transitions. Systems that are well-optimized under stable conditions can become targets of the framework when the rate of environmental change exceeds the rate of adaptation—coral reefs under climate change being a concrete example. Monitoring δ accumulation rates across domains may enable early warning before collapse processes begin, though this remains a conceptual direction without validated methodology.

Dynamic model. The static equation $S = N_{eff} \cdot (\mu/\mu_c) \cdot e^{-\delta}$ describes a snapshot. The temporal evolution $d\mu/dt = -(\delta/N_{eff}) \cdot \mu$, which would predict time-to-collapse, remains theoretical. Testing it requires longitudinal data with simultaneous δ, N_{eff}, and μ measurements over time.

Multi-attractor extension: transitions between states. The single-basin survival equation describes collapse ($S \to 0$). Many real systems do not simply collapse but *transition* to

[8]Specific exploratory results: coral bleaching with degree-heating weeks as δ proxy ($R^2 = 0.957$); corporate failure with governance events (AUC = 0.74) vs. keyword frequency (AUC $\approx$ 0.50); gene conservation with PPI degree as N_{eff} (ΔAIC < -500) vs. paralog count (failure). These results are available in the data repository but are not claims of this paper.

a qualitatively different state—laminar flow becomes turbulent, a failing organization restructures. The multi-attractor extension assigns each attractor basin j its own survival potential $S_j = C_j \cdot e^{-\delta_j}$, where $C_j = N_{eff,j} \cdot (\mu_j/\mu_{c,j})$ and $\delta_j = \sum_i I_j(c_i)$ is the basin-specific cumulative information loss. The same physical constraint c_i may have different information loss in different basins ($I_A(c_i) \neq I_B(c_i)$)—structurally identical to the SAT result where random 3-clauses ($I = \ln(8/7)$) and XOR pairs ($I = \ln 2$) have different per-constraint costs. Under the uniform constraint assumption ($\delta_j = m \cdot I_j$), setting $S_A = S_B$ yields a closed-form transition point:

$$m^* = \frac{\ln(C_A/C_B)}{I_A - I_B}$$

which is a parameter-free prediction analogous to the SAT ratio $\alpha_{\text{XOR}}/\alpha_{\text{random}} = 5.19\times$. Defining $F_j = -\ln S_j = -\ln C_j + \delta_j$ as a free-energy analogue, S-maximization is equivalent to F-minimization, and $F(\delta)$ is linear in δ, implying that all transitions in this framework are first-order (discontinuous). Second-order transitions require I_j to depend on constraint count—a generalization left open. The multi-attractor extension, including basin dominance before and after the transition point, scale invariance across hierarchical levels, and the S-max $\Leftrightarrow$ F-min equivalence, is formally verified in Lean 4 (`sorry` = 0, `axiom` = 0). Empirical validation—predicting the critical Reynolds number of channel flow ($\text{Re}_c = 5772$) from the information-loss structure—requires a domain-specific mapping $\delta(\text{Re})$ and remains open; the framework predicts *that* a transition occurs and *where* (in δ-space), but not *at what value of the domain-specific control parameter*.

The Exp. 36 data provide an initial test within an existing Level A domain (§5.9.1).

Convergence maintenance. The collapse phenomenon documented in this paper has a natural dual: systems under $\delta = 0$ should maintain output coherence across arbitrary context lengths. We define *ε-convergence maintenance* as the condition $D_{\text{KL}}(P(y|x,\delta) \| P(y|x,0)) \leq \varepsilon$, where $P(y|x,0)$ is the output distribution under zero structural contradiction. Collapse corresponds to a discontinuity in this KL divergence at δ_c; convergence maintenance corresponds to Lipschitz continuity. This definition is domain-independent—$P(y|x)$ denotes token distributions in LLMs, decision distributions in organisations, and solution-set distributions in SAT—and connects naturally to the $\delta = D_{\text{KL}}$ identity (Result 1): input-side structural contradiction and output-side degradation are both measured in the same information-theoretic currency. Exp. 35 (§5.8) confirms the $\delta = 0$ case: four models across three vendors (GPT-4o-mini, Gemini 2.5 Flash, Gemini 3.1 Flash Lite, Claude Sonnet 4) maintain 100% accuracy across all tested context lengths under $\delta = 0$, while $\delta > 0$ causes immediate degradation. Systematic validation of the Lipschitz continuity condition across graded δ levels remains a target for future work.

7 Limitations

1. **No novel mathematical results**: The framework combines existing mathematical structures (first moment method, serial reliability, survival analysis). Theorem 3.2 is a restatement of Price's equation in the survival context. The contribution is organizational, not foundational.

2. **SAT scope**: The first moment $\mathbb{E}[\#\text{SAT}] = 2^n \cdot e^{-\delta}$ is exact and the threshold upper bound is unconditionally valid (see §6). However, for a *specific* instance, the actual solution count $\#\text{SAT}/2^n$ may deviate from $e^{-\delta}$ due to correlations between assignments in the solution space. The 20% gap between the first-moment threshold ($\alpha_c^{(1)} \approx 5.19$) and the true threshold ($\alpha_c \approx 4.27$) quantifies this precision loss. The second moment method provides the complementary lower bound; numerical evaluation of the truncated second moment yields $\alpha_c^{(2)} \approx 4.51$, explaining 74% of the gap. The remaining 26% (4.51 vs. 4.27) arises from higher-order correlations (replica symmetry breaking) beyond the second moment's

reach. The parameter-free ratio $\alpha_{\text{XOR}}/\alpha_{\text{random}}$ has been confirmed across six system sizes ($n = 18$–28, brute-force enumeration) with mean 5.04× and CV = 5.0%, consistent with the first-moment bound being an upper bound.

3. **LLM predictions are not pre-specified**: The five theory-derived predictions (Table 9) follow from the equation structure and were derivable before the experiments, but were not formally specified in advance. The experimental conditions were developed iteratively.

4. **μ_c is not derived within this framework**: The survival equation defines the *role* of μ_c (the minimum resource flow required for continued function) but does not derive its *value*—just as $F = ma$ does not derive the mass m. The derivability of μ_c depends on the maturity of independent domain-specific theories: in site percolation, $\mu_c = p_c$ is determined by lattice geometry ($p_c = 1/2$ exactly for the 2D triangular lattice; $p_c \approx 0.3116$ numerically for 3D simple cubic [26]); in nuclear stability, the critical threshold follows from the Bethe–Weizsäcker mass formula. In both cases, the survival equation contains zero free parameters. In the LLM experiments reported here, no corresponding independent theory exists, so μ_c must be measured operationally. However, the main LLM experiments in this paper (Exp. 5, 14–16) hold μ fixed and vary only δ, so the survival ratio $S(\delta)/S(0) = e^{-\delta}$ is tested independently of the value of μ_c. The earlier heuristic $\mu_c = 1/(2N_{eff})$ is retracted as a conjecture without derivation.

5. **Level B prediction**: The framework has no validated quantitative prediction in any Level B domain (organisms, organisations, ecosystems). Extending the methodology requires domain-specific δ calibration in nats and identification of the appropriate margin variable (μ)—neither of which has been demonstrated outside SAT and LLM.

6. **Three factors may not be exhaustive**: The decomposition into N_{eff}, μ/μ_c, and δ may omit relevant factors. For example, the rate of δ accumulation (not just its current value) may matter for systems with adaptive capacity.

7. **Formal verification scope**: Lean 4 verification covers mathematical properties (algebraic consistency, theorem validity, the derivation chain from axioms A1–A3 to $e^{-\delta}$, the Paley-Zygmund second moment inequality, the pair correlation structure, weak dependence sandwich with robust survival bounds, and multi-attractor transition theorems including scale invariance), not empirical correctness. The multi-attractor transition point $m^* = \ln(C_A/C_B)/(I_A - I_B)$ is proven unique, but whether a given physical system satisfies the uniform constraint assumption ($\delta_j = m \cdot I_j$) is an empirical question—the same epistemic structure as A1–A3. The free-energy linearity ($F(\delta) = -\ln C + \delta$) restricts the framework to first-order transitions; second-order (continuous) transitions require I_j to depend on constraint count, which is left as an explicit scope boundary. However, a formally verified equation can still be empirically wrong if ρ is underestimated.

8. **$\delta = 0$ invariance is task-dependent**: Du et al. [37] showed that context length alone degrades LLM performance by 13.9–85% on math, QA, and coding tasks, even with perfect retrieval and no contradictions. Our Exp. 35 finds stable $\delta = 0$ accuracy up to 128,000 tokens, but the task (three-variable arithmetic with contradiction detection) may be less sensitive to length-induced μ decay than multi-step reasoning tasks. The survival equation accommodates this via $\mu = \mu(L)$: for tasks where baseline capability degrades with length, $\delta = 0$ no longer guarantees perfect accuracy but still sets the ceiling. The claim that δ-driven degradation is separable from and additive to length-driven degradation remains to be tested across diverse task types.

9. **Falsifiability**: The model is falsifiable at two levels. *Structural falsification*: if the SAT decay rate ratio deviates significantly from 5.19× at large n; if multiplicative $\mu \times \delta$ interaction fails to replicate in LLM experiments under controlled conditions; or if, in a new

Level A domain where δ is exactly computable, the multiplicative exponential form systematically underperforms an additive or power-law alternative. *Measurement falsification*: within a given domain, if better-calibrated δ proxies do not improve predictive precision, the framework's applicability to that domain is refuted. The structural form is anchored by the first moment identity in SAT, not by analogy; challenges to it are most decisive in Level A domains.

8 Conclusion

The survival equation $S = N_{eff} \cdot (\mu/\mu_c) \cdot e^{-\delta}$ generates quantitative predictions that can be experimentally confirmed. The multi-attractor extension yields $P(\text{correct}) = 1/(1 + K/L)$ with $K = 19.5 \pm 3.4$ thousand tokens, confirmed at five context lengths (32K–512K, mean absolute error 2%), derived from a prediction using only three data points. The full chain—axioms $\rightarrow$ Lean 4 proof $\rightarrow$ quantitative prediction $\rightarrow$ experimental confirmation—is complete for this case. The framework also explains LLM reasoning collapse: multiplicative $\mu \times \delta$ interaction, dimensional structure in δ, and a cushion mechanism with cross-model convergence, explained by the first moment method from combinatorics. The parameter-free SAT prediction $\alpha_{\text{XOR}}/\alpha_{\text{random}} = 5.19\times$ is confirmed at 5.04 ± 0.25 (CV = 5%).

Confirmed in two controlled domains:

- **SAT**: The exponential penalty $e^{-\delta}$ is mathematically identical to the first moment of the solution count. Three constraint types produce predicted decay rates ($R^2 > 0.98$). The parameter-free ratio $\alpha_{\text{XOR}}/\alpha_{\text{random}} = 5.19\times$ is stable across six system sizes (CV = 5%).

- **LLM**: Multiplicative $\mu \times \delta$ interaction—two individually non-lethal factors become lethal in combination (ruling out additive models). Constraint quality dominates quantity ($\delta_{\text{structural}} \gg \delta_{\text{factual}}$). The cushion mechanism absorbs contradictions until overwhelmed, producing a system-specific δ_c, confirmed across 11 models from 5 vendors. Collapse requires recognition capability (absent below ~12B parameters), distinguishing three stages: no recognition, recognition with refusal, and recognition with attempted resolution. A three-model, two-vendor extended experiment ($N = 810$ trials, 32K–256K tokens) reveals that the effective magnitude of subtle inter-source contradiction (δ_5) depends on both model capability and context-length interaction, producing three qualitatively distinct response patterns and three distinct structural-contradiction (δ_1) failure modes (refusal, computation-to-zero, literal reinterpretation). The multi-attractor interpretation of Gemini's dilution pattern yields $P(\text{correct}) = 1/(1 + K/L)$ with $K = 19.5 \pm 3.4$ (thousands of tokens), confirmed across five context lengths (32K–512K, mean absolute error 2%, two out-of-sample predictions within 1%).

- **Formal verification**: Survival selection theorem, axiom-to-exponential derivation (A1–A3 $\Rightarrow e^{-\delta}$), Cauchy uniqueness ($e^{-c\delta}$ is the only continuous form), the Paley-Zygmund second moment inequality, pair correlation structure for threshold lower bounds, and the weak dependence sandwich ($e^{-\delta(1+\rho)} \leq P \leq e^{-\delta(1-\rho)}$ with robust survival potential) verified in Lean 4 (`sorry` = 0, `axiom` = 0). The weak dependence extension transforms the independence assumption (A3) from a binary requirement into a measurable parameter ρ. The multi-attractor extension proves basin-local survival, transition point existence and uniqueness, free-energy equivalence (S-max $\Leftrightarrow$ F-min), and scale invariance across hierarchical levels.

Not confirmed:

- Level B quantitative prediction: no validated prediction in domains requiring proxy δ measurement

- Dynamic model ($d\mu/dt = -(\delta/N_{eff}) \cdot \mu$): untested
- $e^{-\delta}$ vs. $(1-\delta)$ discrimination in the low-δ regime (where these forms converge)

The framework introduces no novel mathematical results; its contribution is an operational methodology: measuring structural conflict as information loss in nats, grounded in the first moment correspondence. The weak dependence extension addresses the principal theoretical concern—that real-world constraints are not independent—by providing guaranteed survival bounds parameterized by the measurable correlation ρ, with exact reduction to $e^{-\delta}$ at $\rho = 0$. The multi-attractor extension provides a formally verified transition theory: defining $F = -\ln S$ as a free-energy analogue, transitions between attractor basins occur at $m^* = \ln(C_A/C_B)/(I_A - I_B)$, and $P = 1/(1 + K/L)$ with $K = m^*$ matches Gemini's context-length dilution across five data points. The full chain—axioms $\rightarrow$ Lean 4 proof $\rightarrow$ quantitative prediction $\rightarrow$ experimental confirmation—is completed for this case. The two domains are complementary—SAT validates the mathematical identity, LLM validates both the multiplicative interaction and the multi-attractor transition structure, revealing that constraint quality, not quantity, governs collapse. The challenge ahead is extending this methodology to Level B domains where δ requires proxy measurement.

Data and Code Availability

- Lean 4 formalization: `https://codeberg.org/delta-survival/papers/src/branch/main/lean`
- SAT experiments: `analysis/sat/`
- LLM experiments: `analysis/llm/`
- Second moment gap analysis: `analysis/sat/second_moment_gap_analysis.py`

Acknowledgments

The author thanks Kazuki Ikawa for detailed and constructive comments on an earlier draft of this manuscript.

References

[1] Achlioptas, D. (2009). Random satisfiability. In *Handbook of Satisfiability*, pp. 245–270. IOS Press.

[2] Alon, N. & Spencer, J.H. (2016). *The Probabilistic Method*, 4th ed. Wiley.

[3] Berglund, L. et al. (2023). The Reversal Curse: LLMs trained on "A is B" fail to learn "B is A". *arXiv:2309.12288*.

[4] Barlow, R.E. & Proschan, F. (1975). *Statistical Theory of Reliability and Life Testing*. Holt, Rinehart and Winston.

[5] Ben-Sasson, E. & Wigderson, A. (2001). Short proofs are narrow—resolution made simple. *J. ACM*, 48(2), 149–169.

[6] Cocco, S. & Monasson, R. (2001). Trajectories in phase diagrams, growth processes, and computational complexity: How search algorithms solve the 3-satisfiability problem. *Physical Review Letters*, 86(8), 1654–1657.

[7] Cover, T.M. & Thomas, J.A. (2006). *Elements of Information Theory*, 2nd ed. Wiley.

[8] Cox, D.R. (1972). Regression models and life-tables. *J. Royal Statistical Society B*, 34(2), 187–220.

[9] Duderstadt, J.J. & Hamilton, L.J. (1976). *Nuclear Reactor Analysis*. Wiley.

[10] de Moura, L. & Ullrich, S. (2021). The Lean 4 theorem prover and programming language. *CADE-28*, LNCS 12699, 625–635.

[11] Dziri, N. et al. (2023). Faith and Fate: Limits of Transformers on Compositionality. *NeurIPS 2023*.

[12] Eigen, M. (1971). Self-organization of matter and the evolution of biological macromolecules. *Naturwissenschaften*, 58(10), 465–523.

[13] Fisher, R.A. (1930). *The Genetical Theory of Natural Selection*. Clarendon Press.

[14] Friedgut, E. (1999). Sharp thresholds of graph properties, and the k-SAT problem. *J. American Mathematical Society*, 12(4), 1017–1054.

[15] Giannakopoulos, B. (2025). Persistence Theory and the Persistence Equation. *OSF Preprints*.

[16] Kaplan, E.L. & Meier, P. (1958). Nonparametric estimation from incomplete observations. *J. American Statistical Association*, 53(282), 457–481.

[17] Liu, N.F. et al. (2024). Lost in the Middle: How language models use long contexts. *Transactions of the ACL*, 12, 157–173.

[18] May, R.M. (1972). Will a large complex system be stable? *Nature*, 238, 413–414.

[19] Mézard, M., Parisi, G., & Zecchina, R. (2002). Analytic and algorithmic solution of random satisfiability problems. *Science*, 297, 812–815.

[20] Ouyang, L. et al. (2022). Training language models to follow instructions with human feedback. *NeurIPS 2022*.

[21] Price, G.R. (1970). Selection and covariance. *Nature*, 227, 520–521.

[22] Prigogine, I. & Stengers, I. (1984). *Order Out of Chaos*. Bantam Books.

[23] Scheffer, M. et al. (2009). Early-warning signals for critical transitions. *Nature*, 461, 53–59.

[24] Shannon, C.E. (1948). A mathematical theory of communication. *Bell System Technical Journal*, 27, 379–423.

[25] Wei, J. et al. (2022). Chain-of-thought prompting elicits reasoning in large language models. *NeurIPS 2022*.

[26] Mertens, S. & Moore, C. (2018). Percolation thresholds and Fisher exponents in hypercubic lattices. *Physical Review E*, 98(2), 022120.

[27] Zhang, X., Zhang, Y., Chen, Z., Yu, J., Yang, W. & Song, Z. (2026). Logical phase transitions: Understanding collapse in LLM logical reasoning. *arXiv preprint arXiv:2601.02902*.

[28] Aczél, J. (1966). *Lectures on Functional Equations and Their Applications*. Academic Press.

[29] Sunagawa, A. (2026). Predicting computational cost from the structural parameter δ: Separating existence from discovery in random 3-SAT. *Preprint*.

[30] Cantor, R., Packer, F. (1996). Determinants and impact of sovereign credit ratings. *Federal Reserve Bank of New York Economic Policy Review*, 2(2), 37–54.

[31] Shumailov, I., Shumaylov, Z., Zhao, Y., Papernot, N., Anderson, R. & Gal, Y. (2024). AI models collapse when trained on recursively generated data. *Nature*, 631, 755–759.

[32] Parsons, J., McCoy, R.T., Garrette, D., Linzen, T. & Bowman, S.R. (2025). The Illusion of Thinking: Understanding the strengths and limitations of reasoning models via the lens of problem complexity. Apple Machine Learning Research.

[33] Truong, N.B. & Truong, Q.-T. (2025). Entropy Collapse: A universal failure mode of intelligent systems. *arXiv preprint arXiv:2512.12381*.

[34] Axenie, C., West, R. et al. (2024). Antifragility in complex dynamical systems. *npj Complexity*, 1, 5.

[35] Hong, K., Troynikov, A. & Huber, J. (2025). Context Rot: How Increasing Input Tokens Impacts LLM Performance. Chroma Research, July 2025.

[36] Wang, C. & Sun, J.V. (2025). Unable to Forget: Proactive Interference Reveals Working Memory Limits in LLMs Beyond Context Length. *arXiv preprint arXiv:2506.08184*.

[37] Du, Y., Tian, M. et al. (2025). Context Length Alone Hurts LLM Performance Despite Perfect Retrieval. *EMNLP 2025 Findings*.

[38] Xu, R., Qi, Z., Guo, Z. et al. (2024). Knowledge Conflicts for LLMs: A Survey. *EMNLP 2024*.

[39] Zheng, X., Huang, Z. et al. (2025). KCR: Resolving Long-Context Knowledge Conflicts via Reasoning in LLMs. *arXiv preprint arXiv:2508.01273*.

[40] Jiao, D., Wang, D. & Hu, L. (2026). Understanding the Dynamics of Demonstration Conflict in In-Context Learning. *arXiv preprint arXiv:2603.04464*.