Stop Interpolation Topologically

Luciano Melodia

Agenda

Introduction

Persistent Homology

Natural Neighbor Interpolation

The Collapsing Sequence

Hypothesis Testing

Summary

Introduction

Topology matters
Guess the manifold

Taking into account the topology of data is beneficial for interpolation. Data lies on some compact topological manifold, which is given by the mutual arrangement of points in a data set.



Hypothesis
Two main assumptions

Hypothesis 1: Manifold assumption

A point set X lies on a *topological* or even *smooth manifold* $\mathbb{M}$, having a family of continuous/smooth *coordinate systems* to describe it, with $\dim \mathbb{M} \ll \dim X$.

Hypothesis

Two main assumptions

Hypothesis 1: Manifold assumption

A point set X lies on a *topological* or even *smooth manifold* $\mathbb{M}$, having a family of continuous/smooth *coordinate systems* to describe it, with $\dim \mathbb{M} \ll \dim X$.

Hypothesis 2: Meaning of shape

The topology of the sublevel sets of a manifold $\mathbb{M}$ underlying a data set can be used to distinguish data up to some equivalence relation.

Persistent Homology

An outline to persistent homology

A brief description

Persistent homology is the study of k-**dimensional abelian groups** attached to a topological space. They are studied algebraically and behave *similar* to the topological space itself under change revealing properties of the original space they are attached to by their *invariants*.

The connection of abelian groups by a boundary homomorphism allows to investigate all k-dimensions at once. The induced object is a chain complex.

Chain complex

How does it work?

Homology theory is the study of properties of an object X, such as a set of points, by means of homological (commutative) algebra. One assigns to X a sequence of abelian groups/modules $C_0, C_1, \cdots$ which are connected by homomorphisms $\partial_{k+1} : C_{k+1} \longrightarrow C_k$ such that $\mathrm{im}\partial_{k+1} \subseteq \ker \partial_k$. Such a structure is called **chain complex**.

$$0 \xrightarrow{\partial_{k+1}} C_k \xrightarrow{\partial_k} C_{k-1} \xrightarrow{\partial_{k-1}} C_{k-2} \xrightarrow{\partial_{k-2}} \cdots \xrightarrow{\partial_2} C_1 \xrightarrow{\partial_1} 0$$

Cycle and boundary groups

Putting them into context

Illustration of the chain complex



Following Zomorodian, Edelsbrunner and many more ...

Natural Neighbor Interpolation

Step 1: Voronoi diagram

Natural neighbor interpolation example



The **Voronoi Diagram** is spanned over the point cloud embedded into some Euclidean space. Technically one does not calculate the Voronoi diagram but the dual **Delaunay triangulation**.

$$\text{Vordgm} = \{x \in X \mid d(x, \lambda_i) \leq d(x, \lambda_j)\} \qquad (1)$$

Step 2: Add a point to the convex hull

We need to compute the weights per region



We insert a point into the convex hull of the points $X = \{x_1, \cdots, x_n\}$. The selected position of the new point follows an uniform distribution. The point is added to the set forming the convex hull:

$$\text{conv}X = \left\{ \sum_{i=1}^{n} \lambda_i x_i \;\middle|\; x_i \in X, \sum_{i=1}^{n} \lambda_i = 1, \lambda_i \geq 0 \right\}.$$

Step 3: Iterative construction of Voronoi regions

Construction of the new regions



Iteratively, the points of the Voronoi region are connected with a straight line. The perpendicular that bisects the line provides the two intersections to the neighboring Voronoi regions.

Step 3: Iterative construction of Voronoi regions

Construction of the new regions



Iteratively, the points of the Voronoi region are connected with a straight line. The perpendicular that bisects the line provides the two intersections to the neighboring Voronoi regions.

Step 3: Iterative construction of Voronoi regions

Construction of the new regions



Iteratively, the points of the Voronoi region are connected with a straight line. The perpendicular that bisects the line provides the two intersections to the neighboring Voronoi regions.

Step 3: Iterative construction of Voronoi regions

Construction of the new regions



The weights w_i are the *stolen* regions of the new Voronoi region of the added point from all other Voronoi regions.

They can be calculated during construction.


w_3
x_3
x_2
x_4
w_4
w_2
x
w_1
x_5
x_1
w_5

The Collapsing Sequence

Hypothesis Testing

Summary

References I

Anton, François, Darka Mioc, and Alain Fournier (2001). "Reconstructing 2D Images with Natural Neighbour Interpolation". In: *The Visual Computer* 17.3, pp. 134–146.

Bauer, Ulrich and Herbert Edelsbrunner (2017). "The Morse Theory of čech and Delaunay Complexes". In: *Transactions of the American Mathematical Society* 369.5, pp. 3741–3762.

Bobach, Tom Axel (2009). "Natural Neighbor Interpolation - Critical Assessment and New Contributions". Doctoral Thesis. TU Kaiserslautern.

Boissonnat, Jean-Daniel and Frédéric Cazals (2000). "Smooth Surface Reconstruction via Natural Neighbour Interpolation of Distance Functions". In: *Proceedings of the 16th Annual Symposium on Computational Geometry*, pp. 223–232.

Boissonnat, Jean-Daniel and Frédéric Cazals (2001). "Natural Neighbor Coordinates of Points on a Surface". In: *Computational Geometry* 19.2-3, pp. 155–173.

Boissonnat, Jean-Daniel, Ramsay Dyer, and Arijit Ghosh (2018a). "Delaunay Triangulation of Manifolds". In: *Foundations of Computational Mathematics* 18.2, pp. 399–431.

Boissonnat, Jean-Daniel, Frédéric Chazal, and Mariette Yvinec (2018b). *Geometric and Topological Inference*. Vol. 57. Cambridge University Press.

Borsuk, Karol (1948). "On the Imbedding of Systems of Compacta in Simplicial Complexes". In: *Fundamenta Mathematicae* 35, pp. 217–234.

References II

Bubenik, Peter (2015). "Statistical topological data analysis using persistence landscapes". In: *Journal of Machine Learning Research* 16.1, pp. 77–102.

Carrière, Mathieu, Marco Cuturi, and Steve Oudot (2017). "Sliced Wasserstein Kernel for Persistence Diagrams". In: *Proceedings of the 34th International Conference on Machine Learning*, pp. 664–673.

Cerri, Andrea and Claudia Landi (2016). "Hausdorff Stability of Persistence Spaces". In: *Foundations of Computational Mathematics* 16.2, pp. 343–367.

Chazal, Frédéric, Marc Glisse, Catherine Labruère, and Bertrand Michel (2015). "Convergence Rates for Persistence Diagram Estimation in Topological Data Analysis". In: *Journal of Machine Learning Research* 16, pp. 3603–3635.

Cohen, Marshall (2012). *A Course in Simple-Homotopy Theory*. Vol. 10. Springer.

Cohen-Steiner, David, Herbert Edelsbrunner, and John Harer (2007). "Stability of Persistence Diagrams". In: *Discrete and Computational Geometry* 37.1, pp. 103–120.

Cohen-Steiner, David, Herbert Edelsbrunner, John Harer, and Yuriy Mileyko (2010). "Lipschitz functions have L^p-stable persistence". In: *Foundations of Computational Mathematics* 10.2.

Czado, Claudia and Axel Munk (1998). "Assessing the similarity of distributions-finite sample performance of the empirical Mallows distance". In: *Journal of Statistical Computation and Simulation* 60.4, pp. 319–346.

References III

Edelsbrunner, Herbert and John Harer (2008). "Persistent Homology – A Survey". In: *Contemporary mathematics* 453, pp. 257–282.

Edelsbrunner, Herbert, David Letscher, and Afra Zomorodian (2002). "Topological Persistence and Simplification". In: *Discrete and Computational Geometry* 28.4, pp. 511–533.

Fernández-Ternero, Desamparados, Enrique Macáas-Virgós, Nicholas A Scoville, and José Antonio Vilches (2019). "Strong discrete Morse theory and simplicial LS category: A discrete version of the Lusternik-Schnirelmann Theorem". In: *Discrete and Computational Geometry*.

Goerss, Paul G and John F Jardine (2009). *Simplicial Homotopy Theory*. Springer.

Gray, Brayton (1975). *Homotopy Theory: An Introduction to Algebraic Topology*. Vol. 64. Academic Press.

Hatcher, Allen (2005). *Algebraic Topology*. Cambridge University Press.

Hiyoshi, Hisamoto and Kokichi Sugihara (2004). "Improving the Global Continuity of the Natural Neighbor Interpolation". In: *Computational Science and its Applications*, pp. 71–80.

Kerber, Michael, Dmitriy Morozov, and Arnur Nigmetov (2017). "Geometry helps to compare persistence diagrams". In: *Journal of Experimental Algorithmics* 22, pp. 1–4.

Li, Yi, Weidong Chen, and Dongming Lu (2008). "The Application of Natural Neighbor Interpolation in Real-Time Environments". In: *International Conference on Cyberworlds*, pp. 306–313.

Mileyko, Yuriy, Sayan Mukherjee, and John Harer (2011). "Probability Measures on the Space of Persistence Diagrams". In: *Inverse Problems* 27.12, p. 124007.

References IV

Reem, Daniel (2011). "The Geometric Stability of Voronoi diagrams with Respect to Small Changes of the Sites". In: *Proceedings of the 27th Annual Symposium on Computational Geometry*, pp. 254–263.

Robinson, Andrew and Katharine Turner (2017). "Hypothesis testing for topological data analysis". In: *Journal of Applied and Computational Topology* 1.2, pp. 241–261.

Rodríguez-Dagnino, Ramón M. (2015). "A Super-Resolution Image Reconstruction using Natural Neighbor Interpolation". In: *Computación y Sistemas* 19.2.

Sibson, Robin (1981). "A brief Description of Natural Neighbor Interpolation". In: *Interpreting Multivariate Data*. Ed. by V. Barnett, pp. 21–36.

Silva, Vin De and Gunnar Carlsson (2004). "Topological estimation using witness complexes.". In: *Symposium on Point-Based Graphics* 4, pp. 157–166.

Villani, Cédric (2008). *Optimal Transport: Old and New*. Vol. 338. Springer.

Zomorodian, Afra (2010). "Fast Construction of the Vietoris-Rips Complex". In: *Computers and Graphics* 34.3, pp. 263–271.

Zomorodian, Afra and Gunnar E. Carlsson (2005). "Computing Persistent Homology". In: *Discrete & Computational Geometry* 33.2, pp. 249–274.