



APC NetShelter Switched Rack PDU, 1U, 1PH, 2.3kW 230V 10A or 2.5kW 208V 12A, 8 C13 outlets, C14 cord

Brand : APC

Product code: AP7920B

Product name : NetShelter Switched Rack PDU, 1U, 1PH, 2.3kW 230V 10A or 2.5kW 208V 12A, 8 C13 outlets, C14 cord




NetShelter Switched Rack PDU, 1U, 1PH, 2.3kW 230V 10A or 2.5kW 208V 12A, 8 C13 outlets, C14 cord

APC NetShelter Switched Rack PDU, 1U, 1PH, 2.3kW 230V 10A or 2.5kW 208V 12A, 8 C13 outlets, C14 cord:

This APC Switched Rack PDU power distribution unit has a wide range of standardized PDU features that increase network efficiency, manageability and functionality. The output and input connections are (8)C13. Network management capabilities allow you to configure and manage rack PDUs from remote locations. It has has a local current monitoring display that gives a visible warning in case of an overload. The remote individual outlet control provides real-time monitoring of connected loads. It has a multi-tier user access that enables you to restrict unauthorized use of outlets. This rack has a single input power source making it easy to install.

Design		Certificates	
PDU types *	Metered, Switched	Certification	cUL Listed, CE, CSA, EN 55022 Class A, EN 55024, EN 61000-3-2, EN 61000-3-3, GOST, IRAM, MIC, UL 60950, UL Listed, VDE, VCCI, REACH
Rack capacity *	0U/1U		
Mounting	Horizontal/Vertical		
Product colour	Black		
Ports & interfaces		Operational conditions	
AC outlets quantity *	8 AC outlet(s)	Operating temperature (T-T)	0 - 45 °C
Power plug	C14 coupler	Storage temperature (T-T)	-25 - 65 °C
AC outlet types *	C13 coupler	Operating relative humidity (H-H)	0 - 95%
Input connection type	IEC-320 C14	Storage relative humidity (H-H)	0 - 95%
Features		Operating altitude	0 - 3000 m
Cable length	1.98 m	Non-operating altitude	1 - 15000 m
Management features		Weight & dimensions	
Monitoring	Current, Power, Voltage	Width	445 mm
Outlet control	Lock-out, Recycle, Turn off, Turn on	Depth	108 mm
Power		Height	44 mm
Nominal input voltage *	200-230 V	Weight	2.27 kg
AC input frequency	50 - 60 Hz	Packaging content	
Maximum current *	10 A	Packaging content	Installation Guide, Rack Mounting Brackets, User Manual
Nominal output voltage	208-230 V	Packaging data	
Load capacity	2300 VA	Package weight	3.45 kg
Maximum input current per phase	10 A	Package width	470 mm
Maximum total current draw per phase	10 A	Package depth	343 mm
Maximum power	2300 W	Package height	70 mm
Certificates		Logistics data	
Compliance certificates	RoHS	Total carbon footprint (kg of CO2e)	915.89



0731304331612



731304331612

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.