Canon

Canon imageFORMULA DR-C240 Sheet-fed scanner 600 x 600 DPI A4 Black

Brand : Canon

Product family: imageFORMULA

Product code: 0651C003

Product name : DR-C240

CMOS CIS 1 Line Sensor, RGB LED, 600dpi, USB 2.0

Canon imageFORMULA DR-C240 Sheet-fed scanner 600 x 600 DPI A4 Black:

Canon imageFORMULA DR-C240

Compact document scanner perfect for busy workgroups and customer-facing environments.

The imageFORMULA DR-C240 is an ultra-compact and powerful desktop scanner featuring a robust design and reliable paper handling for capturing multiple document sizes and formats, including passports.

- Boost productivity with fast 2-sided scanning at up to 90ipm
- Easily scan various types of documents including passports with one compact device
- Enjoy peace of mind with supreme paper-handling reliability and durable construction
- Enhance your environment with quiet operation, compact build and elegant design

Scanning

Maximum scan size *	216 x 3000 mm
Optical scanning resolution *	600 x 600 DPI
Colour scanning	✔
Duplex scanning *	✔
Input colour depth	24 bit
Output colour depth	24 bit
Film scanning	✘
Greyscale levels	256
ADF scan speed (b/w, A4)	45 ppm
ADF scan speed (colour, A4)	30 ppm
Duplex ADF scan speed (b/w, A4)	90 ipm
Duplex ADF scan speed (colour, A4)	60 ipm
Black/white scanning colour modes	Grayscale

Design

Scanner type *	Sheet-fed scanner
Product colour *	Black
Built-in display *	✘

Performance

Sensor type *	CMOS CIS
Light source	RGB LED
Daily duty cycle (max) *	4000 pages
Scan drivers	ISIS, TWAIN

Paper handling

Scanning media types supported	Business Card, Plastic Card
Maximum ISO A-series paper size *	A4

Ports & interfaces

USB port *	✔
USB version	2.0
Standard interfaces	USB 2.0

Power

Power supply type *	AC
Power consumption (typical)	19 W
Power consumption (standby)	1.4 W
Power consumption (off)	0.1 W
AC input frequency	50 - 60 Hz
Input voltage	100-240 V

Weight & dimensions

Width	291 mm
Depth	253 mm
Height	231 mm
Weight	2.8 kg

Sustainability

Sustainability certificates	ENERGY STAR

System requirements

Windows operating systems supported	Windows 8, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows 8 x64, Windows 8.1, Windows 8.1 Enterprise, Windows 8.1 Enterprise x64, Windows 8.1 Pro, Windows 8.1 Pro x64, Windows 8.1 x64, Windows Vista Business, Windows Vista Business x64, Windows Vista Enterprise, Windows Vista Enterprise x64, Windows Vista Home Basic, Windows Vista Home Basic x64, Windows Vista Home Premium, Windows Vista Home Premium x64, Windows Vista Ultimate, Windows Vista Ultimate x64

System requirements	
Server operating systems supported	Windows Server 2008 R2, Windows Server 2008 R2 x64, Windows Server 2012 R2, Windows Server 2012 R2 x64

Operational conditions	
Operating temperature (T-T)	10 - 32.5 °C
Operating relative humidity (H-H)	20 - 80%

Other features	
Compliance certificates	RoHS

Logistics data	
Harmonized System (HS) code	84716070

4528472106861

4528472106878

Catalog Object Cloud