



**APC Rack PDU, Basic, Zero U, 11 kW, 230V, (36) C13 & (6) C19 power distribution unit (PDU) 42 AC outlet(s) 0U Black**

**Brand :** APC

**Product code:** AP7557

**Product name :** Rack PDU, Basic, Zero U, 11 kW, 230V, (36) C13 & (6) C19

Rack PDU, Basic, Zero U, 11 kW, 230V, (36) C13 & (6) C19

APC Rack PDU, Basic, Zero U, 11 kW, 230V, (36) C13 & (6) C19 power distribution unit (PDU) 42 AC outlet(s) 0U Black:


APC Basic Rack PDU , Input: 400V 3PH , Input Connections: IEC 309 16A 3P+N+PE , Cord Length: 3 feet ( 0.91 meters ) , Output: 230V , Output Connections: IEC 320 C13,IEC 320 C19.

- Low Cost Power Distribution.
- Vertical mounting capability.
- Toolless mounting capability.
- Multi-branch power input.

APC Rack PDU, Basic, Zero U, 11 kW, 230V, (36) C13 & (6) C19. PDU types: Basic, Rack capacity: 0U, Mounting: Vertical. AC outlets quantity: 42 AC outlet(s), AC outlet types: C13 coupler, C19 coupler, Input connection type: IEC 309 16A 3P+N+PE. Cable length: 0.91 m. Nominal input voltage: 400 V, AC input frequency: 47/63 Hz, Nominal output voltage: 230 V. Certification: C-tick,CCC,CE,GOST,MIC,Queensland Australia,VD



Design		Power	
PDU types *	Basic	Maximum total current draw per phase	16 A
Rack capacity *	0U	Maximum power	11000 W
Mounting	Vertical	Certificates	
Product colour	Black	Certification	C-tick,CCC,CE,GOST,MIC,Queensland Australia,VD
Ports & interfaces		Operational conditions	
AC outlets quantity *	42 AC outlet(s)	Operating temperature (T-T)	-5 - 45 °C
AC outlet types *	C13 coupler, C19 coupler	Storage temperature (T-T)	-25 - 65 °C
Input connection type	IEC 309 16A 3P+N+PE	Operating relative humidity (H-H)	5 - 95%
Output connections	(36) IEC 320 C13 (6) IEC 320 C19	Storage relative humidity (H-H)	5 - 95%
Features		Weight & dimensions	
Cable length	0.91 m	Width	56 mm
Power		Depth	44 mm
Nominal input voltage *	400 V	Height	1619 mm
AC input frequency	47/63 Hz	Weight	5.45 kg
Nominal output voltage	230 V		
Load capacity	11040 VA		
Maximum input current per phase	16 A		



0731304254102



731304254102

### Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.