



Fujitsu Smart-UPS uninterruptible power supply (UPS) Line-Interactive 3 kVA 2700 W 9 AC outlet(s)

Brand : Fujitsu

Product code: FJX3000RMHV2UNC

Product name : Smart-UPS



Smart-UPS X - 3000VA, Rack/Tower, LCD, 200-240V, Network Card, 37.32kg, Black

Fujitsu Smart-UPS uninterruptible power supply (UPS) Line-Interactive 3 kVA 2700 W 9 AC outlet(s):

Fujitsu UPS devices ensure high-performance power supply protection for systems and data, and thus provide reliable protection against power failure, current fluctuations and electrical interference. Fujitsu offers both line interactive (VI) and online (VFI) devices with double conversion technology in line with the UPS classification according to IEC 62040-3. Capacities of up to 3000VA provide the right power supply and technology for all individual requirements.

The use of uninterruptible power supplies can particularly benefit your company from a financial viewpoint: Having to search for and restore lost or damaged data after a power failure can cost a great deal of time and money. In such incidents UPS helps to protect your data.



Features		Battery	
UPS topology *	Line-Interactive	Hot-swap battery	✓
Output power capacity *	3 kVA	Automatic battery test	✓
Output power *	2700 W	Design	
Waveform *	Sine	Form factor *	Rackmount/Tower
Input frequency *	50/60 Hz	Rack capacity	2U
Output operation voltage (min)	208 V	Cable length	2.44 m
Output operation voltage (max)	240 V	Product colour *	Black
Output frequency regulation	50/60 Hz	LED indicators	Battery replacement
Automatic Voltage Regulation (AVR)	✓	Operational conditions	
Surge energy rating	645 J	Operating temperature (T-T)	0 - 40 °C
Efficiency	98.5%	Storage temperature (T-T)	-15 - 45 °C
Emergency Power Off (EPO)	✓	Operating relative humidity (H-H)	0 - 95%
Noise level	55 dB	Storage relative humidity (H-H)	0 - 95%
Surge protection	✓	Operating altitude	0 - 3000 m
Audible alarm(s)	✓	Non-operating altitude	0 - 15000 m
Auto-restart	✓	Certificates	
Ports & interfaces		Compliance certificates	RoHS
AC outlet types	C13 coupler, C19 coupler	Packaging content	
Power plug	C20 coupler	Rack mount kit	✓
AC outlets quantity	9 AC outlet(s)	Cables included	RS-232
Number of output IEC jumpers	2	Manual	✓
SmartSlot	✓	Weight & dimensions	
Battery		Width	432 mm
Battery technology	Sealed Lead Acid (VRLA)	Depth	667 mm
Typical backup time at full load	6.3 min	Height	85 mm
Typical backup time at half load	18 min	Weight	37.3 kg
Battery life (max)	5 year(s)		

Battery		Packaging data	
Battery recharge time	3 h	Package width	596 mm
		Package depth	869 mm
		Package height	85 mm
		Package weight	45.4 kg



0731304294009



731304294009

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.