

APC Smart-UPS SMT3000IC - 8x C13, 1x C19, USB, SmartConnect, 3000VA

Brand : APC Product code: SMT3000IC

Product name: APC Smart-UPS SMT3000IC - 8x C13, 1x

C19, USB, SmartConnect, 3000VA

- Intelligent and efficient network power protection from entry level to scaleable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices

- Includes: CD with software, Documentation CD, USB cable

APC Smart-UPS SMT3000IC - 8x C13, 1x C19, USB, SmartConnect, 3000VA


APC Smart-UPS SMT3000IC - 8x C13, 1x C19, USB, SmartConnect, 3000VA. UPS topology: Line-Interactive, Output power capacity: 3 kVA, Output power: 2700 W. AC outlet types: C13 coupler, C19 coupler, Power plug: C20 coupler, AC outlets quantity: 9 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Typical backup time at full load: 5.1 min, Typical backup time at half load: 17.2 min. Form factor: Tower, Product colour: Black, Cable length: 1.83 m. Compliance certificates: RoHS, Certification: CE, CSA, EAC, EN/IEC 62040-1, EN/IEC 62040-2, RCM, VDE, REACH, PEP, EOLI





Features		Battery	
UPS topology *	Line-Interactive 3 kVA 2700 W	Cold start	✓
Output power capacity * Output power *		Design	
/aveform * Sine put operation voltage (min) * 151 V put operation voltage (max) * 302 V put frequency * 50/60 Hz utput operation voltage (min) 220 V	Form factor * Cable length Product colour * Display type LED indicators	Tower 1.83 m Black LCD Status	
Output operation voltage (max)	ut operation voltage (max) ut frequency 50/60 Hz matic Voltage Regulation (AVR) e energy rating 98.4% gency Power Off (EPO)	Operational conditions	
Output frequency Automatic Voltage Regulation (AVR) Surge energy rating Efficiency Emergency Power Off (EPO) Noise level		Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude	0 - 40 °C -15 - 45 °C 0 - 95% 0 - 95% 0 - 3000 m 0 - 15000 m
Audible alarm(s)	✓	Certificates	
Auto-restart	✓	Compliance certificates	RoHS
Ports & interfaces AC outlet types	let types C13 coupler, C19 coupler plug C20 coupler	Certification	CE, CSA, EAC, EN/IEC 62040-1, EN/IEC 62040-2, RCM, VDE, REACH, PEP, EOLI
Power plug		Packaging content	
AC outlets quantity Number of output IEC jumpers	9 AC outlet(s) 2	Cables included	RS-232, USB cable
USB port	✓	Quick installation guide	✓
SmartSlot	✓	Sustainability	
Battery		Sustainability certificates	Green Premium
Battery technology	Sealed Lead Acid (VRLA)	Weight & dimensions	
Typical backup time at full load	5.1 min	Width	197 mm

Battery		Weight & dimensions	
Typical backup time at half load Battery life (max) Battery recharge time	17.2 min 5 year(s) 3 h	Depth Height Weight	544 mm 435 mm 52.5 kg
Hot-swap battery	✓	Packaging data	
Automatic battery test		Package width Package depth Package height Package weight	381 mm 762 mm 699 mm 63.7 kg
		Logistics data	
		Products per pallet Harmonized System (HS) code Total carbon footprint (kg of CO2e)	9 pc(s) 85078000 3335.07





731304337331

0731304337331

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.