



APC Smart-UPS On-Line, 1500VA/1500W, Rackmount 2U, 230V, 6x C13 IEC outlets, SmartSlot, Extended runtime, W/ rail kit

Brand : APC

Product code: SRT1500RMXLI



Product name : Smart-UPS On-Line, 1500VA/1500W, Rackmount 2U, 230V, 6x C13 IEC outlets, SmartSlot, Extended runtime, W/ rail kit

Smart-UPS On-Line, 1500VA/1500W, Rackmount 2U, 230V, 6x C13 IEC outlets, SmartSlot, Extended runtime, W/ rail kit

APC Smart-UPS On-Line, 1500VA/1500W, Rackmount 2U, 230V, 6x C13 IEC outlets, SmartSlot, Extended runtime, W/ rail kit. UPS topology: Double-conversion (Online), Output power capacity: 1.5 kVA, Output power: 1500 W. Serial interface type: RJ-45. Battery technology: Sealed Lead Acid (VRLA), Battery life (max): 5 year(s), Battery recharge time: 3 h. Form factor: Rackmount, Product colour: Black, Cable length: 1.83 m. Compliance certificates: RoHS, Certification: CE, EAC



Features		Design	
UPS topology *	Double-conversion (Online)	Display type	LCD
Output power capacity *	1.5 kVA	LED indicators	Status
Output power *	1500 W	International Protection (IP) code	IP20
Waveform *	Sine	Operational conditions	
Input operation voltage (min) *	50 V	Operating temperature (T-T)	0 - 40 °C
Input operation voltage (max) *	150 V	Storage temperature (T-T)	-20 - 50 °C
Input frequency *	40/70 Hz	Operating relative humidity (H-H)	0 - 95%
Output operation voltage (min)	220 V	Storage relative humidity (H-H)	0 - 95%
Output operation voltage (max)	240 V	Certificates	
Output frequency	50/60 Hz	Compliance certificates	RoHS
Surge energy rating	432 J	Certification	CE, EAC
Crest factor	3:1	Packaging content	
Emergency Power Off (EPO)	✓	Manual	✓
Noise level	50 dB	Sustainability	
Audible alarm(s)	✓	Sustainability certificates	Green Premium
Ports & interfaces		Weight & dimensions	
USB port	✓	Width	432 mm
Serial interface	✓	Depth	505 mm
Serial interface type	RJ-45	Height	85 mm
SmartSlot	✓	Weight	21 kg
Battery		Packaging data	
Battery technology	Sealed Lead Acid (VRLA)	Package width	594 mm
Battery life (max)	5 year(s)	Package depth	749 mm
Battery recharge time	3 h	Package height	246 mm
Hot-swap battery	✓	Package weight	29.6 kg
Design			
Form factor *	Rackmount		

Design		Logistics data	
Cable length	1.83 m	Products per pallet	12 pc(s)
Product colour *	Black	Harmonized System (HS) code	85078000
		Total carbon footprint (kg of CO2e)	2577.53



0731304340287



731304340287

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.