HP Intel Xeon E5506 processor 2.13 GHz 4 MB Smart Cache

Brand : HP **Product code:** 482601-001

Product name : Intel Xeon E5506

Intel Xeon E5506, 4M Cache, 2.13 GHz, 4.8 GT/s QPI

HP Intel Xeon E5506 processor 2.13 GHz 4 MB Smart Cache:

Options, accessories, services and support for all your HP and Compaq products.
HP Intel Xeon E5506. Processor family: Intel® Xeon® 5000 Sequence, Processor socket: Socket B (LGA 1366), Processor lithography: 45 nm. Memory channels: Triple-channel, Maximum internal memory supported by processor: 144 GB, Memory types supported by processor: DDR3-SDRAM. Market segment: Server, Physical Address Extension (PAE): 40 bit. Compatibility: Proliant ML150 G6

Processor	
Processor model *	E5506
Processor base frequency *	2.13 GHz
Processor family *	Intel® Xeon® 5000 Sequence
Processor cores *	4
Processor socket *	Socket B (LGA 1366)
Component for	Server/workstation
Processor lithography *	45 nm
Processor series	Intel Xeon 5000 Series
Processor threads	4
System bus rate	4.8 GT/s
Processor operating modes *	64-bit
Processor cache	4 MB
Processor cache type	Smart Cache
Thermal Design Power (TDP)	80 W
VID Voltage Range	0.75 - 1.35 V
Stepping	D0
Bus type	QPI
Number of QPI links	2
Memory bandwidth supported by processor (max)	19.2 GB/s

Memory	
Maximum internal memory supported by processor	144 GB
Memory types supported by processor	DDR3-SDRAM
Memory clock speeds supported by processor	800 MHz
Memory channels *	Triple-channel
ECC	✔

Graphics	
On-board graphics card *	✘

Features	
Execute Disable Bit	✔
Idle States	✔
Market segment	Server
Physical Address Extension (PAE)	✔
CPU configuration (max)	2
Embedded options available	✘
Physical Address Extension (PAE)	40 bit

Processor special features	
Intel® Hyper Threading Technology (Intel® HT Technology)	✘
Intel® Turbo Boost Technology	✘
Enhanced Intel SpeedStep Technology	✔
Intel Trusted Execution Technology	✘
Intel VT-x with Extended Page Tables (EPT)	✔
Intel Demand Based Switching	✔
Intel 64	✔
Intel Virtualization Technology (VT-x)	✔
Intel Virtualization Technology for Directed I/O (VT-d)	✔

Operational conditions	
Tcase	76 °C

Other features	
Compatibility	Proliant ML150 G6

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 26-JUL-2025. Prints or copies of Information are only valid on the printed Publication date