


TP-Link ARCHER VR600 wireless router Gigabit Ethernet Dualband (2.4 GHz / 5 GHz) Black

Brand: TP-Link Product code: ARCHER VR600

Product name: ARCHER VR600





WAN connection		Management features	
Ethernet WAN *	✓	WPS push button	✓
DSL WAN *	✓	Security	
SIM card slot *	X	Security algorithms	64-bit WEP, 128-bit WEP, WPA,
3G/4G USB modem compatibility *	✓	, ,	WPA-PSK, WPA2
WAN connection type	RJ-45	Firewall	✓
Wireless LAN features		Guest access	✓
Wi-Fi band *	Dual-band (2.4 GHz / 5 GHz)	Access Control List (ACL)	•
Top Wi-Fi standard *	Wi-Fi 5 (802.11ac)	Filtering	•
WLAN data transfer rate (max) *	1300 Mbit/s	MAC address filtering	•
Wi-Fi standards	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac)	URL filtering	•
WLAN data transfer rate (first band)		DMZ support	1
WLAN data transfer rate (second	300 Mbit/s	Network address translation (NAT)	✓
band)	300 Pibity3	Protocols	
Network		DHCP client	✓
Ethernet LAN *	✓	DHCP server	✓
Ethernet LAN interface type *	Gigabit Ethernet	Supported network protocols	IPv4, IPv6
Ethernet LAN data rates	10,100,1000 Mbit/s	Design	
Cabling technology	10/100/1000Base-T(X) IEEE 802.3, IEEE 802.3ab, IEEE	Product colour	Black
Networking standards	802.3u	LED indicators	LAN, Power, WLAN
Port forwarding	1	On/off switch	✓
Dynamic DNS (DDNS)	✓	Product type *	Tabletop router
VPN tunnels quantity	10	Packaging content	
VPN Passthrough	✓	Cables included	LAN (RJ-45), Phone (RJ-11)
VPN support	PPTP, L2TP, IPSec Passthrough	AC adapter included	✓
Mobile network		Quick installation guide	✓
3G	✓	Antenna	
4G	✓	Antenna design *	External
DSL features		Antenna gain level (max)	23 dBi
ADSL	✓	Antennas quantity	3
ADSL2	✓	Detachable antenna(s)	✓
ADSL2+	✓	Power	
VDSL	✓	Power source type *	AC
VDSL2	✓	Output voltage	12 V
		Output current	2 A

Ports & interfaces		Operational conditions	
Ethernet LAN (RJ-45) ports *	4	Operating temperature (T-T)	0 - 40 °C
USB port *	✓	Storage temperature (T-T)	-40 - 70 °C
USB 2.0 ports quantity	1	Operating relative humidity (H-H)	10 - 90%
RJ-11 ports quantity	1	Storage relative humidity (H-H)	5 - 90%
Memory card slot(s)	×	Weight & dimensions	
DC-in jack	✓	Width	216 mm
Management features		Depth	164 mm
Web-based management	·	Height	36.8 mm
Quality of Service (QoS) support	✓	Logistics data	
Reset button	•	Harmonized System (HS) code	85176990
		Other features	
		Maximum data transfer rate	1 Mbit/s



6935364094478

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.