

HP Intel Xeon Gold 6142 processor 2.6 GHz 22 MB L3

Brand: HP Product code: L09268-001

Product name: Intel Xeon Gold 6142

Intel Xeon Gold 6142, 22M Cache, 2.6 GHz, 150 W TDP, FCLGA3647

HP Intel Xeon Gold 6142 processor 2.6 GHz 22 MB L3:

Options, accessories, services and support for all your HP and Compaq products. HP Intel Xeon Gold 6142. Processor family: Intel® Xeon® Gold, Processor socket: LGA 3647 (Socket P), Processor lithography: 14 nm. Memory channels: Hexa-channel, Maximum internal memory supported by processor: 768 GB, Memory types supported by processor: DDR4-SDRAM. Market segment: Server, Supported instruction sets: AVX, AVX 2.0, AVX-512, SSE4.2, Scalability: S4S

Processor		Features	
Processor generation	1st Generation Intel® Xeon® Scalable 6142 2.6 GHz	Scalability	S4S
Processor model *		Embedded options available	X
Processor base frequency *		Processor special features	
Processor family *	Intel® Xeon® Gold	Intel® Hyper Threading Technology	,
Processor cores *	16	(Intel® HT Technology)	•
Processor socket *	LGA 3647 (Socket P)	Intel® Turbo Boost Technology	2.0
Component for	Server/workstation	Intel® AES New Instructions (Intel®	✓
Processor lithography *	14 nm	AES-NI) Enhanced Intel SpeedStep	
Processor series	Intel Xeon Gold 6000 Series	Technology	1
Processor threads	32	Intel Trusted Execution Technology	✓
Processor operating modes *	64-bit	Intel® Speed Shift Technology	/
Processor boost frequency	3.7 GHz	Intel VT-x with Extended Page	
Processor cache	22 MB	Tables (EPT)	•
Processor cache type	L3	Intel TSX-NI	✓
Thermal Design Power (TDP)	150 W	Intel 64	1
Cooler included *	×	Intel Virtualization Technology (VT-	J
Stepping	H0	x)	•
Bus type	UPI Claulaka	Intel Virtualization Technology for Directed I/O (VT-d)	✓
Processor codename	Skylake	Intel Turbo Boost Max Technology	
Memory		3.0	X
Maximum internal memory supported by processor	768 GB	Intel® Optane™ Memory Ready	×
Memory types supported by		AVX-512 Fused Multiply-Add (FMA)	1
processor	DDR4-SDRAM	units	
Memory clock speeds supported by	2666 MHz	Intel® vPro™ Platform Eligibility	✓
processor		Operational conditions	
Memory channels * ECC	Hexa-channel	Tcase	85 °C
	•	Technical details	
Graphics		Intel® Volume Management Device	./
On-board graphics card *	×	(VMD) version	•
Discrete graphics card *	×	Mode-based Execute Control (MBE) version	✓
Features		Number of UPI links	3
Execute Disable Bit	✓		
Market segment	Server		
Maximum number of PCI Express lanes	48		
PCI Express slots version	3.0		
Supported instruction sets	AVX, AVX 2.0, AVX-512, SSE4.2		

