



HP 3YP61AE Black/Tri-color GT Printhead Kit

Brand : HP

Product code: 3YP61AE

Product name : 3YP61AE Black/Tri-color GT Printhead Kit

- Original HP 3YP61AE ink supplies deliver legendard HP print quality.
- HP GT Prinheads work with: HP Smart Tank 455, 457
- Try HP Instant Ink - the hassle-free, money-saving ink subscription service.
- Depend on Original HP 3YP61AE ink supplies designed specifically for your HP printer.
- 2 printheads: black, tri-colour; Insert with printhead replacement instructions

3YP61AE Black/Tri-color GT Printhead Kit

HP 3YP61AE Black/Tri-color GT Printhead Kit. Compatibility: HP GT Prinheads work with: HP Smart Tank 455, 457, Print technology: Thermal inkjet, Printing colours: Black, Cyan, Magenta, Yellow. Width: 117 mm, Depth: 38 mm, Height: 157 mm. Package width: 117 mm, Package depth: 38 mm, Package height: 157 mm. Master (outer) cases per pallet: 45 pc(s), Products per pallet: 1080 pc(s), Layers per pallet: 5 pc(s)



Brilliant colours and sharp text to represent the best of your business



Performance		Operational conditions	
Compatibility *	HP GT Prinheads work with: HP Smart Tank 455, 457	Storage relative humidity (H-H)	20 - 80%
Print technology	Thermal inkjet	Logistics data	
Colour	✓	Master (outer) cases per pallet	45 pc(s)
Printing colours	Black, Cyan, Magenta, Yellow	Pallet dimensions (W x D x H)	1200 x 800 x 1064 mm
OEM code	3YP61AE	Products per pallet	1080 pc(s)
Weight & dimensions		Layers per pallet	5 pc(s)
Width	117 mm	Pallet dimensions (W x D x H) (imperial)	1199.9 x 800.1 x 1064 mm (47.2 x 31.5 x 41.9")
Depth	38 mm	Pallet weight (imperial)	210.1 kg (463.1 lbs)
Height	157 mm	Pallet gross weight	210.08 g
Weight	164 g	Products per master (outer) case	24 pc(s)
Packaging data		Master (outer) case gross weight	4.22 g
Package width	117 mm	Quantity per pack	2 pc(s)
Package depth	38 mm	Harmonized System (HS) code	84439990
Package height	157 mm	Technical details	
Package weight	160 g	Box contents	2 printheads: black, tri-colour; Insert with printhead replacement instructions
Operational conditions			
Operating temperature (T-T)	15 - 30 °C		
Operating relative humidity (H-H)	20 - 80%		
Storage temperature (T-T)	-40 - 60 °C		



0193424555116



193424555116

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.