



DELL N1548P Managed L3 Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) 1U Black

Brand : DELL

Product code: 210-AEWB

Product name : N1548P




48 x 1GbE RJ-45, 4 x 10GbE SFP+, PoE+, 176 Gbps, 600W, 1U, 7 kg

DELL N1548P. Switch type: Managed, Switch layer: L3. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 48, USB 2.0 ports quantity: 1. Full duplex. MAC address table: 16000 entries, Switching capacity: 128 Gbit/s. Networking standards: IEEE 802.1ab, IEEE 802.1D, IEEE 802.1p, IEEE 802.1Q, IEEE 802.1s, IEEE 802.1v, IEEE 802.1w, IEEE.... Power over Ethernet (PoE). Rack mounting, Form factor: 1U



Management features		Protocols	
Switch type *	Managed	Supported network protocols	IPv4, IPv6, HTTP, TCP, IP
Switch layer	L3	Design	
Quality of Service (QoS) support	✓	Rack mounting *	✓
MIB support	Yes	Stackable *	✓
Ports & interfaces		Form factor	1U
Basic switching RJ-45 Ethernet ports quantity *	48	Product colour	Black
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)	LED indicators	✓
Gigabit Ethernet (copper) ports quantity	48	Performance	
SFP+ module slots quantity	4	Physical stacking (units)	4
USB 2.0 ports quantity	1	Flash memory	256 MB
Network		Maximum cable length	3 m
Networking standards *	IEEE 802.1ab, IEEE 802.1D, IEEE 802.1p, IEEE 802.1Q, IEEE 802.1s, IEEE 802.1v, IEEE 802.1w, IEEE 802.1x, IEEE 802.2, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ac, IEEE 802.3ad, IEEE 802.3ae, IEEE 802.3at, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z	Power	
		Power consumption (typical)	600 W
Port mirroring	✓	Power over Ethernet (PoE)	
Full duplex	✓	Power over Ethernet (PoE) *	✓
Flow control support	✓	Power over Ethernet (PoE) ports quantity	48
Broadcast storm control	✓	Operational conditions	
Auto MDI/MDI-X	✓	Operating temperature (T-T)	0 - 45 °C
VLAN support	✓	Storage temperature (T-T)	-40 - 65 °C
Number of VLANs	512	Operating relative humidity (H-H)	0 - 95%
		Storage relative humidity (H-H)	0 - 85%
Weight & dimensions			
		Width	440 mm
		Depth	387 mm
		Height	43.5 mm


Data transmission		Weight & dimensions	
Switching capacity *	128 Gbit/s	Weight	7 kg
MAC address table *	16000 entries	Logistics data	
Packet buffer memory	1.5 MB	Harmonized System (HS) code	85176990
Multicast features			
Multicast support	✓		



5415247072003



5397063839391



4053162995208

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.