TP-Link TL-MR6400 wireless router Fast Ethernet Single-band (2.4 GHz) 4G Black

Brand : TP-Link

Product name : TL-MR6400

Product code: TL-MR6400

- Share your 4G LTE network with multiple Wi-Fi devices and enjoy download speeds of up to 150 Mbps
- Wireless N speeds of up to 300 Mbps
- Integrated antennas provide stable wireless connections
- Requires no configuration - just insert a SIM card and turn it on to enjoy high speed internet access
- LAN/WAN port provides options and flexibility, allowing you to choose your connection type
300Mbps Wireless N 4G LTE Router
TP-Link TL-MR6400. WAN connection type: RJ-45. Wi-Fi band: Single-band (2.4 GHz), Top Wi-Fi standard: Wi-Fi 4 (802.11n), WLAN data transfer rate (max): 300 Mbit/s. Ethernet LAN interface type: Fast Ethernet, Ethernet LAN data rates: 10,100 Mbit/s, Cabling technology: 10/100Base-T(X). Mobile network generation: 4G, 3G standards: HSPA+, UMTS, 4G standard: LTE. Security algorithms: 64-bit WEP, 128-bit WEP, WPA, WPA-PSK, WPA2, WPA2-PSK

WAN connection		Protocols	
Ethernet WAN *	✔	DHCP server	✔
DSL WAN *	✘	Universal Plug and Play (UPnP)	✔
SIM card slot *	✔	Supported network protocols	IPv4, IPv6
3G/4G USB modem compatibility *	✘	**Design**	
WAN connection type	RJ-45	Product colour	Black
Wireless LAN features		LED indicators	LAN, Power, WLAN
Wi-Fi band *	Single-band (2.4 GHz)	On/off switch	✔
Top Wi-Fi standard *	Wi-Fi 4 (802.11n)	Product type *	Tabletop router
WLAN data transfer rate (max) *	300 Mbit/s	**Certificates**	
Wi-Fi standards	802.11b, 802.11g, Wi-Fi 4 (802.11n)	Certification	CE, RoHS
Network		**Packaging content**	
Ethernet LAN *	✔	Cables included	LAN (RJ-45)
Ethernet LAN interface type *	Fast Ethernet	AC adapter included	✔
Ethernet LAN data rates	10,100 Mbit/s	Manual	✔
Cabling technology	10/100Base-T(X)	Quick installation guide	✔
Networking standards	IEEE 802.11b, IEEE 802.11g, IEEE 802.11n, IEEE 802.3	Quick start guide	✔
Port forwarding	✔	**Antenna**	
Mobile network		Antenna design *	External
Mobile network generation	4G	Antennas quantity	2
3G	✔	Detachable antenna(s)	✔
4G	✔	**Power**	
3G standards	HSPA+, UMTS	Power source type *	DC
4G standard	LTE	Output voltage	9 V
4G bands supported	800,900,1800,1900,2100,2600 MHz	Output current	0.85 A
3G bands supported	1900,2100 MHz		

Ports & interfaces

Ethernet LAN (RJ-45) ports *	4
USB port *	✗
Memory card slot(s)	✗
DC-in jack	✔

Management features

Web-based management	✔
Quality of Service (QoS) support	✔
Reset button	✔
WPS push button	✔

Security

Security algorithms	64-bit WEP, 128-bit WEP, WPA, WPA-PSK, WPA2, WPA2-PSK
Firewall	✔
Stateful Packet Inspection (SPI)	✔
DoS attack prevention	✔
Filtering	✔
MAC address filtering	✔
IP address filtering	✔
DMZ support	✔

Protocols

DHCP client	✔

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	5 - 90%

System requirements

Windows operating systems supported	✔
Linux operating systems supported	✔
Mac operating systems supported	✔
Mac compatibility	✔

Weight & dimensions

Width	202 mm
Depth	141 mm
Height	33.6 mm

Packaging data

Package width	307 mm
Package depth	223 mm
Package height	70 mm
Package weight	600 g

Logistics data

Harmonized System (HS) code	85176990

Catalog Object Cloud