APC Smart-UPS On-Line, 1000VA/1000W, Tower, 230V, 6x C13 IEC outlets, SmartSlot, Extended runtime, W/O rail kit

Brand : APC

Product code: SRT1000XLI

Product name : Smart-UPS On-Line, 1000VA/1000W, Tower, 230V, 6x C13 IEC outlets, SmartSlot, Extended runtime, W/O rail kit

Smart-UPS On-Line, 1000VA/1000W, Tower, 230V, 6x C13 IEC outlets, SmartSlot, Extended runtime, W/O rail kit

APC Smart-UPS On-Line, 1000VA/1000W, Tower, 230V, 6x C13 IEC outlets, SmartSlot, Extended runtime, W/O rail kit:

This APC Smart-UPS is designed for IT professionals or network administrators to maintain business uptime and continuity. This 1000VA on-line tower UPS provides pure sine wave power and extended runtime to support critical electronics during power disruptions. It comes with 1x IEC 320 C14 input and 6x IEC 320 C13 outlets. It has a SmartSlot for optional Network Management Card that enables graceful shutdown of physical servers, virtual machines & HCI Clusters via PowerChute Network Shutdown. The UPS can connect to EcoStruxure IT or third-party centralized management platforms. The UPS has a 3-year warranty, and the built-in lead-acid battery has a 2-year warranty. The UPS is compatible with SRTRK4 (4-post) and SRTRK3 (2-post) rail kits sold separately.

Features

UPS topology *	Double-conversion (Online)
Output power capacity *	1 kVA
Output power *	1000 W
Waveform *	Sine
Input operation voltage (min) *	220 V
Input operation voltage (max) *	240 V
Input frequency *	40/70 Hz
Output operation voltage (min)	50 V
Output operation voltage (max)	240 V
Output frequency	50/60 Hz
Surge energy rating	432 J
Crest factor	3:1
ECO mode	✔
Emergency Power Off (EPO)	✔
Output voltage Total Harmonic Distortion (THD)	2%
Noise level	50 dB
Audible alarm(s)	✔
Audible alarm modes	Alarm when on battery, Battery replacement
Auto-restart	✔

Ports & interfaces

AC outlet types	C13 coupler
Power plug	C14 coupler
AC outlets quantity	12 AC outlet(s)
USB port	✔

Battery

Cold start	✔

Design

Form factor *	Rackmount/Tower
Rack capacity	2U
Cable length	1.8 m
Cooling type	Active
Built-in fan	✔
Product colour *	Black
Display type	LCD
LED indicators	✔
International Protection (IP) code	IP20

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 50 °C
Operating relative humidity (H-H)	0 - 95%
Operating altitude	0 - 3048 m
Non-operating altitude	0 - 15240 m

Certificates

Compliance certificates	CE
Certification	CE, EAC

Packaging content

Cables included	USB cable
Quick installation guide	✔

Ports & interfaces

Serial interface	✔
Serial interface type	RJ-45
Serial ports quantity	1
SmartSlot	✔

Battery

Battery technology	Sealed Lead Acid (VRLA)
Battery voltage	48 V
Typical backup time at full load	8 min
Typical backup time at half load	21 min
Battery life (max)	5 year(s)
Battery recharge time	3 h
Hot-swap battery	✔
Automatic battery test	✔

Sustainability

Sustainability compliance	✔
Sustainability certificates	Green Premium

Weight & dimensions

Width	85 mm
Depth	505 mm
Height	432 mm
Weight	20.5 kg
Battery width	59.4 cm
Battery depth	74.9 cm
Battery height	24.6 cm
Battery weight	29.6 kg

Logistics data

Harmonized System (HS) code	85078000
Total carbon footprint (kg of CO2e)	1839.69

Other features

Nominal output voltage	230 V
Nominal input voltage	230 V

731304340270

0731304340270

Catalog Object Cloud