## StarTech.com 1 Port ExpressCard to RS232 DB9 Serial Adapter Card w/ 16950 - USB Based

Brand : StarTech.com Product code: EC1S232U2

**Product name :** 1 Port ExpressCard to RS232 DB9 Serial

Adapter Card w/ 16950 - USB Based

StarTech.com 1 Port ExpressCard to RS232 DB9 Serial Adapter Card w/ 16950 - USB Based

StarTech.com 1 Port ExpressCard to RS232 DB9 Serial Adapter Card w/ 16950 - USB Based:

Add a USB-based RS232 Serial port to your laptop through an ExpressCard slot

The EC1S232U2 ExpressCard RS232 Serial Adapter Card (USB-based) (16950 UART) adds an RS232 (DB9) serial port to your ExpressCard-equipped laptop, enabling you to connect an RS232 serial peripheral device such as a plotter, digital signage device, receipt printer or bar code scanner through an available ExpressCard slot.

This USB-based ExpressCard supports RS232 serial data transfer rates up to 460 Kbps and eliminates the need to upgrade serial peripherals to more modern interfaces (e.g. USB, etc.) for the sake of host compatibility, saving both expense and hassle.


Backed by a StarTech.com Lifetime warranty and free lifetime technical support.

The StarTech.com Advantage





Ports & interfaces		Weight & dimensions	
Host interface * Output interface * Serial ports quantity	ExpressCard Serial 1	Depth Height Weight	115 mm 18 mm 33.6 g
Serial interface type	RS-232	Packaging data	
Design		Package width	144 mm
Internal * Product colour	× Black	Package depth Package height	175 mm 33 mm
Features		Package weight	106 g
Chipset FIFO (First In, First Out) Logical block addressing (LBA) support	Prolific PL2303 512 B 8 bit	Logistics data  Harmonized System (HS) code  Products per master (outer) case  Master (outer) case width	84733020 65 pc(s) 359 mm
Operational conditions		Master (outer) case length	689 mm
Operating temperature (T-T)	0 - 57 °C	Master (outer) case height	322 mm
Storage temperature (T-T)	-20 - 80 °C	Other features	
Operating relative humidity (H-H)	0 - 60%	Data transfer rate	0.4608 Mbit/s
System requirements		Connectivity technology	Wired
Mac operating systems supported	Mac OS X 13.0 Ventura	Compatible operating systems	Windows 7 (32/64bit), Vista(32/64), XP(32/64), 2000 Windows Server 2008, 2008 R2, 2003(32/64), Mac
Weight & dimensions			OS 8.x, 9.x, 10.x, Linux 2.4.x/ 2.6.x
Width	35 mm		





065030847483

0065030847483



5054629299517

## **Catalog Object Cloud**



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.